SPECIFICATION FOR APPROVAL

CUSTOMER:	Dongguan Kafulle Electronics Co., LTD	
CUST P/N:		
FINE P/N:	iphone Watch transmitter coil8.1UH soft magnetic	0.08*24P*14Ts
DESC:		
DATE:	November 8, 2022	
Version:	A.0	

PREPARED BY	CHECKED BY	APPROVED BY	CUSTOMER APPROVE
Yanming Huang	Yuanan Ning	Jinhua Huang	

Shenzhen Songdao Technology Co., LTD

Add: 8th Floor, Building 2, Sanjia High-tech Industrial Park, No.123 Junfa Third Road, Dongkeng Town, Dongguan City

TEL: 13728755750

FAX: 0755-84526500

E-mail: 506388681@qq.com



Version Change History


Rev.	Before Change	After Change	Change Date	Approved By
A.0	New issue		March 9, 2018	Jinhua Huang



SPECIFICATION

DESC	15*21.5-8.1UH-8MM-25C	Rev:	CUST:	xxx
	2 3.1011 3 200	A.0	CUST P/N:	

一、DIMENSION:(mm)



For watch: 300kHz-350kHz

Antenna gain: OdBi

二、SCHEMATIC DIAGRAM:



A	25±1
В	23.6 ± 0.5
С	21.5 ± 0.5
D	14.5 \pm 0.3
Е	7.7 \pm 0.05
F	3 ± 2
Н	8±2
NT-4	

Notes:

- 1. Crossing out the line.
- 2. Out of the line position wrapped mm (ref) width of high-temperature adhesive paper Ts.
- 3.coil paste round soft magnetic sheet with notch at both ends, magnetic sheet size 25 ± 1 mm, inner hole 7.7mm, thickness 2.8 ± 0.2 mm.
- 4.Installation of 7.5 * 2.2mm, N52 magnet, paste the backing.

三、Winding Specification:

NO.	TERM	INAL	WIRE	Turns	Winding Direction
1	S	F	enameled wire 0.08*24P	14Ts	CCW

四、ELECTRICAL CHARACTERISTICS:

TEMPERATURE:25±10°C, RELATIVE HUMIDITY:65±20%

NO.	ITEM	TERMINAL	SPECIFICATION	TEST FREQUENCY	TEST EQUIPMENTS
1	IND.	S-F	4.0uH ±10% single coil	1KHz/0.3V	LCZ METER 1062B
2	IND.	S-F	8.1uH ±10% single coil	1KHz/0.3V	LCZ METER 1062B
3	DCR	S-F	≤137m Ω	1KHz/0.3V	LCZ METER 502B
4	Q	S-F	≥25	1KHz/0.3V	LCZ METER 502B

Fine Page 4 of 4

PREPARED BY/DATE	CHECKED BY/DATE
Yanming Huang November 8, 2022	Jinhua Huang November 8, 2022