

Prüfbericht-Nr.: <i>Test report no.:</i>	CN22B9BA 002	Auftrags-Nr.: <i>Order no.:</i>	168390091	Seite 1 von 12 <i>Page 1 of 12</i>
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	2022-09-09	
Auftraggeber: <i>Client:</i>	UP Global Sourcing UK Ltd. Manor Mill, Victoria Street, Chadderton, Oldham, United Kingdom			
Prüfgegenstand: <i>Test item:</i>	BLUETOOTH HOME POD SPEAKER			
Bezeichnung / Typ-Nr.: <i>Identification / Type no.:</i>	EE6154XXXXXXXXXX (X = any alphanumeric character or blank) (Trademark: PRIMARK)			
Auftrags-Inhalt: <i>Order content:</i>	Test Report			
Prüfgrundlage: <i>Test specification:</i>	FCC CFR Title 47, Part 15, Subpart B			
Wareneingangsdatum: <i>Date of sample receipt:</i>	2022-09-14	Please refer to Photo Document		
Prüfmuster-Nr.: <i>Test sample no.:</i>	A003334934-001~002			
Prüfzeitraum: <i>Testing period:</i>	2022-10-09 – 2022-10-12			
Ort der Prüfung: <i>Place of testing:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von: <i>tested by:</i>	genehmigt von: <i>authorized by:</i>			
Datum: <i>Date:</i>	2022-10-21		2022-10-21	
Stellung / Position:	Senior Project Manager		Reviewer	
Sonstiges / Other:	FCC ID: 2AAR2EE6154			
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>			
* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	4 = ausreichend N/A = nicht anwendbar
* Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory F(ail) = failed a.m. test specification(s)	4 = sufficient N/A = not applicable
5 = mangelhaft N/T = nicht getestet				
5 = poor N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht - Nr.: CN22B9BA 002
Test Report No.:

Seite 2 von 12
Page 2 of 12

Test Summary

5.1.1 CONDUCTED EMISSION ON AC MAINS

RESULT: Pass

5.1.2 RADIATED EMISSIONS

RESULT: Pass

Table of Contents

1	GENERAL REMARKS	4
1.1	COMPLEMENTARY MATERIALS	4
2	TEST SITES	5
2.1	TEST FACILITIES	5
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	5
2.3	TRACEABILITY	6
2.4	CALIBRATION	6
2.5	MEASUREMENT UNCERTAINTY.....	6
2.6	LOCATION OF ORIGINAL DATA.....	6
2.7	STATUS OF FACILITY USED FOR TESTING.....	6
3	GENERAL PRODUCT INFORMATION	7
3.1	PRODUCT FUNCTION AND INTENDED USE.....	7
3.2	RATINGS AND SYSTEM DETAILS	7
3.3	INDEPENDENT OPERATION MODES	7
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS.....	7
3.5	SUBMITTED DOCUMENTS.....	7
4	TEST SET-UP AND OPERATION MODES	8
4.1	PRINCIPLE OF CONFIGURATION SELECTION	8
4.2	TEST OPERATION AND TEST SOFTWARE.....	8
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	8
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	8
4.5	TEST SETUP DIAGRAM	9
5	TEST RESULTS	10
5.1.1	<i>Conducted Emission on AC Mains.....</i>	<i>10</i>
5.1.2	<i>Radiated Emissions.....</i>	<i>11</i>
6	PHOTOGRAPHS OF THE TEST SET-UP	12
7	LIST OF TABLES.....	12

Prüfbericht - Nr.: CN22B9BA 002
Test Report No.:

Seite 4 von 12
Page 4 of 12

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Test Results of FCC 15B

Appendix B: Photographs of the Test Set-up

2 Test Sites

2.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

362 Huanguan Road Middle Longhua District, Shenzhen 518110 People's Republic of China

FCC Accreditation Designation No.: CN1260

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Conducted Emission				
Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
EMI Test Receiver	R&S	ESR3	102680	2023-02-27
Artificial Mains Network	R&S	ENV216	101445	2023-02-27
EMC32 test software	R&S	EMC32(Ver.10.50.00)	N/A	N/A
Radiated Emission (3m chamber)				
Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
3m SAC	ETS-Lindgren	SAC3	CT001632-Q1362	2024-04-26
EMI Test Receiver	R&S	ESR7	102111	2022-12-01
Horn Antenna	R&S	HF907	102706	2023-08-08
Preamplifier (1-18GHz)	FIT	SCU-18F	180077	2023-08-01
EMC32 test software	R&S	EMC32(Ver.10.50.00)	N/A	N/A
Radiated Emission (10m chamber)				
Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
10m SAC	ETS-Lindgren	SAC10	CT001632-Q1399	2024-03-01
EMI Test Receiver 1	R&S	ESR7	102022	2023-07-31
EMI Test Receiver 2	R&S	ESR7	102023	2023-07-31
Bilog Antenna 1	TESEQ	CBL6112D	51321	2023-08-23
Bilog Antenna 2	TESEQ	CBL6112D	51322	2023-07-07
Preamplifier 1 (30-1000MHz)	SCHWARZBECK	BBV9745	115	2023-08-01
Preamplifier 2 (30-1000MHz)	EMCI	EMC9135-P	980629	2023-08-01
EMC32 test software	R&S	EMC32(Ver.10.50.00)	N/A	N/A

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

Parameter	Uncertainty
Radiated Emission (3m SAC), 30MHz to 1000MHz	± 4.52 dB
Radiated Emission (3m SAC), above 1000MHz	± 4.37 dB
Radiated Emission (10m SAC), 30MHz to 1000MHz	± 4.66 dB
Radiated Emission (10m SAC), above 1000MHz	± 4.35 dB
Conducted Emission, (9kHz to 150kHz)/(150kHz to 30MHz)	± 3.70 dB / ± 3.30 dB

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at 362 Huanguan Road Middle Longhua District, Shenzhen 518110 People's Republic of China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The EUT is a BLUETOOTH HOME POD SPEAKER which supports Classic Bluetooth wireless technology.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 2: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment:	BLUETOOTH HOME POD SPEAKER
Type Designation:	EE6154XXXXXXXXXX (X = any alphanumeric character or blank) Note1: According to the declaration of the applicant, the above model are same as the schematics, PCB layout and electronic components, only the appearance color is different for market strategy. Note2: the EE6154 is selected to test as master device.
Trademark:	PRIMARK
FCC ID:	2AAR2EE6154
Operating Voltage:	USB port operated (5Vdc) Internal Battery operated (3.7Vdc, Li-ion battery)
Operating Temperature Range:	0 °C ~ 55 °C

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, BT mode
- B. On, TWS mode
- C. On, TWS + USB Charging
- D. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- Application Form
- ID Label and Location Info
- Schematics
- Operation Description
- Block Diagram
- PCB Layout

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All tests were performed according to the procedures in ANSI C63.4: 2014.

According to clause 3.1, all tests were performed on model EE6154 in this report.

4.3 Special Accessories and Auxiliary Equipment

Table 3: Auxiliary Equipment Used during Test

Description	Manufacturer	Model	S/N	Rating
Portable Laptop	Lenovo	ThinkPad T480	10Q67059	N/A
Mobile phone	HUAWEI	STK-AL00	7PRNW20721000279	N/A
Adapter	HUAWEI	HW-050100C01	H779KBHAZ30411	Input: 100-240V, 50/60Hz, 0.2A Output: DC 5V, 1A

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)





Diagram of Measurement Configuration for Mains Conduction Measurement



5 Test Results

5.1.1 Conducted Emission on AC Mains

RESULT:

Pass

Test Specification

Test standard	: FCC Part 15.107(a)
Basic standard	: ANSI C63.4:2014
Frequency range	: 0.15 – 30MHz
Classification	: Class B
Limits	: FCC Part 15.107(a)
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2022-10-12
Input voltage	: USB operated (Adapter input voltage 120Vac, 60Hz) USB operated (PC input voltage 120Vac, 60Hz)
Operation mode	: C
Ambient temperature	: 25.0 °C
Relative humidity	: 50.2 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix A.

5.1.2 Radiated Emissions

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.109(a)
Basic standard	: ANSI C63.4:2014
Frequency range	: 30MHz to 5 th harmonic of the highest frequency
Classification	: Class B
Limits	: FCC Part 15.109(a)
Kind of test site	: 3m Semi-anechoic Chamber for below 1GHz 10m Semi-anechoic Chamber for above 1GHz

Test Setup

Date of testing	: 2022-10-09 to 2022-10-12
Input voltage	: Internal battery operated (3.7Vdc) USB operated (Adapter input voltage 120Vac, 60Hz)
Operation mode	: A, B, C
Ambient temperature	: Refer to test result
Relative humidity	: Refer to test result
Atmospheric pressure	: Refer to test result

For the measurement records, refer to the appendix A.

6 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix B.

7 List of Tables

Table 1: List of Test and Measurement Equipment.....	5
Table 2: Technical Specification of EUT	7
Table 3: Auxiliary Equipment Used during Test	8