



中认信通

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: Shenzhen Teslong Technology Co., Ltd.

Address: 2nd Floor, Block 4, Jinhua Industrial Park, East of Donghuan 2 avenue,
Longhua, Shenzhen, China

FCC ID: 2AXAVNTS700C03

Product Name: Digital Borescope Camera

Standard(s): 47 CFR Part 15, Subpart C(15.247)

ANSI C63.10-2013

KDB 558074 D01 15.247 Meas Guidance v05r02

The above device has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR230308451-00

Date Of Issue: 2023/12/28

Reviewed By: Calvin Chen

Title: RF Engineer

Approved By: Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,
Guangdong, China

Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

DOCUMENT REVISION HISTORY	5
1. GENERAL INFORMATION	6
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	6
1.2 DESCRIPTION OF TEST CONFIGURATION.....	8
1.2.1 EUT Operation Condition:.....	8
1.2.2 Support Equipment List and Details	8
1.2.3 Support Cable List and Details	8
1.2.4 Block Diagram of Test Setup.....	9
1.3 MEASUREMENT UNCERTAINTY	10
2. SUMMARY OF TEST RESULTS	11
3. REQUIREMENTS AND TEST PROCEDURES	12
3.1 AC LINE CONDUCTED EMISSIONS.....	12
3.1.1 Applicable Standard.....	12
3.1.2 EUT Setup.....	13
3.1.3 EMI Test Receiver Setup	13
3.1.4 Test Procedure	14
3.1.5 Corrected Amplitude & Margin Calculation.....	14
3.2 RADIATION SPURIOUS EMISSIONS.....	15
3.2.1 Applicable Standard.....	15
3.2.2 EUT Setup.....	15
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup	16
3.2.4 Test Procedure	16
3.2.5 Corrected Amplitude & Margin Calculation.....	17
3.3 MINIMUM 6 dB EMISSION BANDWIDTH	18
3.3.1 Applicable Standard.....	18
3.3.2 EUT Setup.....	18
3.3.3 Test Procedure	18
3.4 99% OCCUPIED BANDWIDTH.....	19
3.4.1 EUT Setup.....	19
3.4.2 Test Procedure	19
3.5 MAXIMUM CONDUCTED OUTPUT POWER.....	20
3.5.1 Applicable Standard.....	20
3.5.2 EUT Setup.....	20
3.5.3 Test Procedure	20
3.6 MAXIMUM POWER SPECTRAL DENSITY	21
3.6.1 Applicable Standard.....	21
3.6.2 EUT Setup.....	21
3.6.3 Test Procedure	21
3.7 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE.....	22
3.7.1 Applicable Standard.....	22
3.7.2 EUT Setup.....	22
3.7.3 Test Procedure	22

3.8 DUTY CYCLE	23
3.8.1 EUT Setup.....	23
3.8.2 Test Procedure	23
3.9 ANTENNA REQUIREMENT.....	23
3.9.1 Applicable Standard.....	23
3.9.2 Judgment.....	23
4. Test DATA AND RESULTS	24
4.1 AC LINE CONDUCTED EMISSIONS.....	24
4.2 RADIATION SPURIOUS EMISSIONS	27
4.3 MINIMUM 6 dB EMISSION BANDWIDTH	44
4.4 99% OCCUPIED BANDWIDTH.....	49
4.5 MAXIMUM CONDUCTED OUTPUT POWER.....	54
4.6 MAXIMUM POWER SPECTRAL DENSITY	55
4.7 100 KHz BANDWIDTH OF FREQUENCY BAND EDGE:	60
4.8 DUTY CYCLE:.....	65
5. RF EXPOSURE EVALUATION	68
5.1 APPLICABLE STANDARD.....	68
6. EUT PHOTOGRAPHS	69
7. TEST SETUP PHOTOGRAPHS	70

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	CR230308451-00	Original Report	2023/12/28

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	Digital Borescope Camera
EUT Model:	NTS700
Operation Frequency:	2412-2462 MHz(802.11b/g/n ht20) 2422-2452 MHz(802.11n ht40)
Maximum Peak Output Power (Conducted):	17.92dBm
Modulation Type:	802.11b:DSSS-DBPSK, DQPSK, CCK 802.11g/n:OFDM-BPSK, QPSK, 16QAM, 64QAM
Rated Input Voltage:	DC 5/9/12V from adapter or DC 3.7V from battery
Serial Number:	RF: 22NH_2 CE&RE: 22NH_3
EUT Received Date:	2023/3/29
EUT Received Status:	Good

Operation Frequency Detail:

For 802.11b/g/n ht20:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	/	/
6	2437	/	/
7	2442	/	/

Per section 15.31(m), the below frequencies were performed the test as below:

Test Channel	Frequency (MHz)
Lowest	2412
Middle	2437
Highest	2462

For 802.11n ht40:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	8	2447
4	2427	9	2452
5	2432	/	/
6	2437	/	/
7	2442	/	/

Per section 15.31(m), the below frequencies were performed the test as below:

Test Channel	Frequency (MHz)
Lowest	2422
Middle	2437
Highest	2452

Antenna Information Detail▲:

Antenna Manufacturer	Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
Shenzhen Tianyiyuan Elec &Technology Co.,Ltd	FPC	50	2.4~2.5GHz	4.54dBi
The Method of §15.203 Compliance: ☒ Antenna was permanently attached to the unit. ☐ Antenna use a unique type of connector to attach to the EUT. ☐ Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.				

Accessory Information:

Accessory Description	Manufacturer	Model	Parameters
/	/	/	/

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

For 802.11b/g/n:

EUT Operation Mode:		The system was configured for testing in Engineering Mode, which was provided by the manufacturer.		
Equipment Modifications:		No		
EUT Exercise Software:		FCC Show.exe		
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:				
Test Modes	Data Rate	Power Level Setting		
		Lowest Channel	Middle Channel	Highest Channel
802.11b	1Mbps	21	21	22
802.11g	6Mbps	36	36	37
802.11n ht20	MCS0	34	36	37
802.11n ht40	MCS0	34	36	35
Note: The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.				

1.2.2 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
UMDIGI	Adapter	HJ-050200W2-US	Unknown

1.2.3 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	NO	NO	1	Adapter	EUT

1.2.4 Block Diagram of Test Setup

AC Line Conducted Emissions:



Spurious emissions:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	9kHz~30MHz: 4.12dB, 30M~200MHz: 4.15 dB, 200M~1GHz: 5.61 dB, 1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.26 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	Minimum 6 dB Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth Of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.203	Antenna Requirement	Compliant
FCC§15.247 (i) & §1.1310	RF Exposure Evaluation	Compliant

3. REQUIREMENTS AND TEST PROCEDURES

3.1 AC Line Conducted Emissions

3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

3.1.2 EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.2 Radiation Spurious Emissions


3.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.2.2 EUT Setup


9 kHz-30MHz:



30MHz-1GHz:



Above 1GHz:



The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	300 Hz	1 kHz	200Hz	QP
150 kHz – 30 MHz	10 kHz	30 kHz	9 kHz	QP
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	AV

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

3.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result


3.3 Minimum 6 dB Emission Bandwidth

3.3.1 Applicable Standard

FCC §15.247 (a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

3.3.2 EUT Setup




3.3.3 Test Procedure

According to ANSI C63.10-2013 Section 11.8

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.4 99% Occupied Bandwidth

3.4.1 EUT Setup



3.4.2 Test Procedure

According to ANSI C63.10-2013 Section 6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.
- Step a) through step c) might require iteration to adjust within the specified range.
- Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).


3.5 Maximum Conducted Output Power

3.5.1 Applicable Standard

FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

3.5.2 EUT Setup



3.5.3 Test Procedure

According to ANSI C63.10-2013 Section 11.9.2.3.2

Method AVGPM-G is a measurement using a gated RF average power meter.

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.


3.6 Maximum Power Spectral Density

3.6.1 Applicable Standard

FCC §15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.6.2 EUT Setup



3.6.3 Test Procedure

According to ANSI C63.10-2013 Section 11.10.3

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set VBW $\geq [3 \times \text{RBW}]$.
- e) Detector = power averaging (rms) or sample detector (when rms not available).
- f) Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / \text{RBW}]$.
- g) Sweep time = auto couple.
- h) Employ trace averaging (rms) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If the measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).


3.7 100 kHz Bandwidth of Frequency Band Edge

3.7.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.7.2 EUT Setup



3.7.3 Test Procedure


According to ANSI C63.10-2013 Section 11.11

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

3.8 Duty Cycle

3.8.1 EUT Setup



3.8.2 Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

3.9 Antenna Requirement

3.9.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.9.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.

4. Test DATA AND RESULTS

4.1 AC Line Conducted Emissions

Serial Number:	22NH_3	Test Date:	2023/12/1
Test Site:	CE	Test Mode:	Transmitting (Maximum output power 802.11g 2437MHz mode)
Tester:	David Huang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.9	Relative Humidity: (%)	48	ATM Pressure: (kPa)	101.3
-------------------	------	------------------------	----	---------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101134	2023/3/31	2024/3/30
R&S	EMI Test Receiver	ESR3	102726	2023/3/31	2024/3/30
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2023/8/6	2024/8/5
Audix	Test Software	E3	190306 (V9)	N/A	N/A

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:


Project No.: CR230308451-RF

Tester: David Huang

Port: Line

Note: Transmitting

Date: 2023-12-01



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.542	27.49	9.61	37.10	56.00	18.90	QP
2	0.542	17.32	9.61	26.93	46.00	19.07	Average
3	0.686	31.37	9.62	40.99	56.00	15.01	QP
4	0.686	17.97	9.62	27.59	46.00	18.41	Average
5	1.275	33.25	9.62	42.87	56.00	13.13	QP
6	1.275	20.57	9.62	30.19	46.00	15.81	Average
7	2.591	28.25	9.64	37.89	56.00	18.11	QP
8	2.591	16.98	9.64	26.62	46.00	19.38	Average
9	7.417	28.40	9.66	38.06	60.00	21.94	QP
10	7.417	16.71	9.66	26.37	50.00	23.63	Average
11	19.005	40.04	9.77	49.81	60.00	10.19	QP
12	19.005	26.60	9.77	36.37	50.00	13.63	Average


Project No.: CR230308451-RF

Tester: David Huang

Port: neutral

Note: Transmitting

Date: 2023-12-01



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.150	38.35	9.61	47.96	66.00	18.04	QP
2	0.150	20.22	9.61	29.83	56.00	26.17	Average
3	0.200	32.07	9.61	41.68	63.63	21.95	QP
4	0.200	15.75	9.61	25.36	53.63	28.27	Average
5	0.718	35.90	9.62	45.52	56.00	10.48	QP
6	0.718	21.54	9.62	31.16	46.00	14.84	Average
7	1.291	32.39	9.62	42.01	56.00	13.99	QP
8	1.291	19.75	9.62	29.37	46.00	16.63	Average
9	3.719	31.27	9.65	40.92	56.00	15.08	QP
10	3.719	20.21	9.65	29.86	46.00	16.14	Average
11	17.297	39.16	9.69	48.85	60.00	11.15	QP
12	17.297	25.97	9.69	35.66	50.00	14.34	Average

4.2 Radiation Spurious Emissions

Serial Number:	22NH_3	Test Date:	2023/11/30~2023/12/1
Test Site:	966-1, 966-2	Test Mode:	Transmitting
Tester:	Carl Xue, Coco Tian	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.5~25.3	Relative Humidity: (%)	52~56	ATM Pressure: (kPa)	101.3~101.4
----------------------	-----------	---------------------------	-------	---------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-6	2023/9/18	2026/9/17
BACL	Loop Antenna	1313-1P	3092721	2023/11/9	2026/11/8
R&S	EMI Test Receiver	ESR3	102724	2023/3/31	2024/3/30
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2023/7/16	2024/7/15
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2023/7/16	2024/7/15
Sonoma	Amplifier	310N	186165	2023/7/16	2024/7/15
AH	Double Ridge Guide Horn Antenna	SAS-571	1394	2023/2/22	2026/2/21
R&S	Spectrum Analyzer	FSV40	101591	2023/3/31	2024/3/30
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2023/8/6	2024/8/5
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2023/8/6	2024/8/5
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2023/11/8	2024/11/7
Audix	Test Software	E3	201021 (V9)	N/A	N/A
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2021/2/5	2024/2/4
Quinstar	Preamplifier	QLW-18405536-JO	15964001005	2023/9/15	2024/9/14
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2023/8/6	2024/8/5
E-Microwave	Band Rejection Filter	2400-2483.5MHz	OE01902424	2023/8/6	2024/8/5
Mini Circuits	High Pass Filter	VHF-6010+	31119	2023/8/6	2024/8/5


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

After pre-scan in the X, Y and Z axes of orientation, the worst case is refer to plots.
For 9kHz-30MHz, The amplitude of spurious emissions attenuated more than 20 dB below the limit was not be recorded.


1) 30MHz-1GHz Low Channel

Project No.: CR230308451-RF
Tester: Carl Xue
Polarization: horizontal
Note: Transmitting(802.11g Low Channel)



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	71.832	50.37	-16.74	33.63	40.00	6.37	QP
2	103.806	40.68	-13.58	27.10	43.50	16.40	Peak
3	119.856	44.06	-11.45	32.61	43.50	10.89	Peak
4	161.474	40.31	-12.11	28.20	43.50	15.30	Peak
5	216.024	48.89	-12.68	36.21	46.00	9.79	Peak
6	306.754	41.25	-10.58	30.67	46.00	15.33	Peak


Project No.: CR230308451-RF
Tester: Carl Xue
Polarization: vertical
Note: Transmitting(802.11g Low Channel)




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	31.399	38.58	-4.86	33.72	40.00	6.28	Peak
2	71.832	49.15	-16.74	32.41	40.00	7.59	Peak
3	119.856	37.33	-11.45	25.88	43.50	17.62	Peak
4	160.909	35.98	-12.05	23.93	43.50	19.57	Peak
5	216.024	41.15	-12.68	28.47	46.00	17.53	Peak
6	520.888	31.52	-5.85	25.67	46.00	20.33	Peak

Middle Channel

Project No.: CR230308451-RF
Tester: Carl Xue
Polarization: horizontal
Note: Transmitting(802.11g Middle Channel)




Project No.: CR230308451-RF
Tester: Carl Xue
Polarization: vertical
Note: Transmitting(802.11g Middle Channel)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.962	38.10	-4.53	33.57	40.00	6.43	Peak
2	71.832	48.52	-16.74	31.78	40.00	8.22	Peak
3	119.856	36.49	-11.45	25.04	43.50	18.46	Peak
4	161.474	35.63	-12.11	23.52	43.50	19.98	Peak
5	218.309	41.13	-12.79	28.34	46.00	17.66	Peak
6	520.888	31.64	-5.85	25.79	46.00	20.21	Peak


High Channel

Project No.: CR230308451-RF
Tester: Carl Xue
Polarization: horizontal
Note: Transmitting(802.11g High Channel)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	72.024	49.89	-16.76	33.13	40.00	6.87	QP
2	97.456	42.90	-14.94	27.96	43.50	15.54	Peak
3	119.856	42.64	-11.45	31.19	43.50	12.31	Peak
4	216.024	49.83	-12.68	37.15	46.00	8.85	Peak
5	286.982	39.96	-11.24	28.72	46.00	17.28	Peak
6	431.032	37.78	-7.46	30.32	46.00	15.68	Peak

Project No.: CR230308451-RF
Tester: Carl Xue
Polarization: vertical
Note: Transmitting(802.11g High Channel)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.531	38.04	-4.20	33.84	40.00	6.16	Peak
2	71.832	49.50	-16.74	32.76	40.00	7.24	Peak
3	119.856	37.50	-11.45	26.05	43.50	17.45	Peak
4	161.474	34.53	-12.11	22.42	43.50	21.08	Peak
5	216.024	43.13	-12.68	30.45	46.00	15.55	Peak
6	431.032	34.11	-7.46	26.65	46.00	19.35	Peak

2) 1-25GHz:**802.11b Mode**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				2412	MHz		
2390.000	26.27	PK	H	31.71	57.98	74.00	16.02
2390.000	14.41	AV	H	31.71	46.12	54.00	7.88
2390.000	27.00	PK	V	31.71	58.71	74.00	15.29
2390.000	14.93	AV	V	31.71	46.64	54.00	7.36
4824.000	47.42	PK	H	11.26	58.68	74.00	15.32
4824.000	41.39	AV	H	11.26	52.65	54.00	1.35
4824.000	42.68	PK	V	11.26	53.94	74.00	20.06
4824.000	36.22	AV	V	11.26	47.48	54.00	6.52
Middle Channel:				2437	MHz		
4874.000	46.42	PK	H	11.45	57.87	74.00	16.13
4874.000	41.79	AV	H	11.45	53.24	54.00	0.76
4874.000	42.58	PK	V	11.45	54.03	74.00	19.97
4874.000	31.97	AV	V	11.45	43.42	54.00	10.58
High Channel:				2462	MHz		
2483.500	26.69	PK	H	32.19	58.88	74.00	15.12
2483.500	14.17	AV	H	32.19	46.36	54.00	7.64
2483.500	26.31	PK	V	32.19	58.50	74.00	15.50
2483.500	14.82	AV	V	32.19	47.01	54.00	6.99
4924.000	46.37	PK	H	11.67	58.04	74.00	15.96
4924.000	41.71	AV	H	11.67	53.38	54.00	0.62
4924.000	42.53	PK	V	11.67	54.20	74.00	19.80
4924.000	33.67	AV	V	11.67	45.34	54.00	8.66

802.11g Mode

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				2412	MHz		
2390.000	26.02	PK	H	31.71	57.73	74.00	16.27
2390.000	14.77	AV	H	31.71	46.48	54.00	7.52
2390.000	26.25	PK	V	31.71	57.96	74.00	16.04
2390.000	14.76	AV	V	31.71	46.47	54.00	7.53
4824.000	42.99	PK	H	11.26	54.25	74.00	19.75
4824.000	29.62	AV	H	11.26	40.88	54.00	13.12
4824.000	42.42	PK	V	11.26	53.68	74.00	20.32
Middle Channel:				2437	MHz		
4874.000	43.30	PK	H	11.45	54.75	74.00	19.25
4874.000	30.13	AV	H	11.45	41.58	54.00	12.42
4874.000	42.35	PK	V	11.45	53.80	74.00	20.20
High Channel:				2462	MHz		
2483.500	41.38	PK	H	32.19	73.57	74.00	0.43
2483.500	19.67	AV	H	32.19	51.86	54.00	2.14
2483.500	37.78	PK	V	32.19	69.97	74.00	4.03
2483.500	16.75	AV	V	32.19	48.94	54.00	5.06
4924.000	44.89	PK	H	11.67	56.56	74.00	17.44
4924.000	31.05	AV	H	11.67	42.72	54.00	11.28
4924.000	42.15	PK	V	11.67	53.82	74.00	20.18


802.11n ht20 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2412 MHz							
2390.000	26.62	PK	H	31.71	58.33	74.00	15.67
2390.000	14.69	AV	H	31.71	46.40	54.00	7.60
2390.000	26.89	PK	V	31.71	58.60	74.00	15.40
2390.000	14.47	AV	V	31.71	46.18	54.00	7.82
4824.000	42.90	PK	H	11.26	54.16	74.00	19.84
4824.000	28.71	AV	H	11.26	39.97	54.00	14.03
4824.000	41.55	PK	V	11.26	52.81	74.00	21.19
Middle Channel: 2437 MHz							
4874.000	42.12	PK	H	11.45	53.57	74.00	20.43
4874.000	41.65	PK	V	11.45	53.10	74.00	20.90
High Channel: 2462 MHz							
2483.500	40.58	PK	H	32.19	72.77	74.00	1.23
2483.500	19.66	AV	H	32.19	51.85	54.00	2.15
2483.500	35.31	PK	V	32.19	67.50	74.00	6.50
2483.500	15.83	AV	V	32.19	48.02	54.00	5.98
4924.000	45.33	PK	H	11.67	57.00	74.00	17.00
4924.000	31.13	AV	H	11.67	42.80	54.00	11.20
4924.000	41.82	PK	V	11.67	53.49	74.00	20.51

802.11n ht40 Mode:


Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				2422	MHz		
2390.000	26.06	PK	H	31.71	57.77	74.00	16.23
2390.000	14.11	AV	H	31.71	45.82	54.00	8.18
2390.000	26.89	PK	V	31.71	58.60	74.00	15.40
2390.000	14.74	AV	V	31.71	46.45	54.00	7.55
4844.000	43.20	PK	H	11.31	54.51	74.00	19.49
4844.000	28.87	AV	H	11.31	40.18	54.00	13.82
4844.000	42.19	PK	V	11.31	53.50	74.00	20.50
Middle Channel:				2437	MHz		
4874.000	42.72	PK	H	11.45	54.17	74.00	19.83
4874.000	28.82	AV	H	11.45	40.27	54.00	13.73
4874.000	41.81	PK	V	11.45	53.26	74.00	20.74
High Channel:				2452	MHz		
2483.500	36.63	PK	H	32.19	68.82	74.00	5.18
2483.500	21.50	AV	H	32.19	53.69	54.00	0.31
2483.500	31.41	PK	V	32.19	63.60	74.00	10.40
2483.500	16.92	AV	V	32.19	49.11	54.00	4.89
4904.000	42.86	PK	H	11.58	54.44	74.00	19.56
4904.000	29.32	AV	H	11.58	40.90	54.00	13.10
4904.000	41.65	PK	V	11.58	53.23	74.00	20.77

Note: If the maximized peak measured value complies with under the average limit, then it is unnecessary to perform an Average measurement.

Listed with the worst harmonic margin test plot (802.11b Mode High Channel)

Horizontal

Project No.: CR230308451-RF
Tester: coco Tian
Polarization: Horizontal
Note: 802.11b Mode High Channel




6-18GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	17733.550	16.28	31.38	47.66	54.00	6.34	Average
2	17733.550	28.15	31.38	59.53	74.00	14.47	Peak

Horizontal

Project No.: CR230308451-RF
Tester: coco Tian
Polarization: Horizontal
Note: 802.11b Mode High Channel




18-25GHz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	24259.250	39.33	5.04	44.37	54.00	9.63	Average
2	24259.250	51.68	5.04	56.72	74.00	17.28	Peak

Vertical

Project No.: CR230308451-RF
Tester: coco Tian
Polarization: vertical
Note: 802.11b Mode High Channel




1-6GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4924.000	33.67	11.67	45.34	54.00	8.66	Average
2	4924.000	42.53	11.67	54.20	74.00	19.80	Peak

Vertical

Project No.: CR230308451-RF
Tester: coco Tian
Polarization: vertical
Note: 802.11b Mode High Channel




6-18GHz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	17567.910	17.16	30.39	47.55	54.00	6.45	Average
2	17567.910	29.31	30.39	59.70	74.00	14.30	Peak

Vertical

Project No.: CR230308451-RF
Tester: coco Tian
Polarization: Vertical
Note: 802.11b Mode High Channel



18-25GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	21758.350	40.20	5.02	45.22	54.00	8.78	Average
2	21758.350	52.69	5.02	57.71	74.00	16.29	Peak

4.3 Minimum 6 dB Emission Bandwidth

Serial Number:	22NH_2	Test Date:	2023/12/28
Test Site:	RF	Test Mode:	Transmitting
Tester:	Aaron Lv	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.3	Relative Humidity: (%)	48	ATM Pressure: (kPa)	101
----------------------	------	------------------------------	----	------------------------	-----


Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200120	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A


** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:




Test Modes	Test Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	2412	9.12	0.5
	2437	9.12	0.5
	2462	9.15	0.5
802.11g	2412	16.65	0.5
	2437	16.65	0.5
	2462	16.65	0.5
802.11n ht20	2412	17.82	0.5
	2437	17.85	0.5
	2462	17.85	0.5
802.11n ht40	2422	36.48	0.5
	2437	36.54	0.5
	2452	36.48	0.5







6dB Emission Bandwidth

802.11n ht40
Lowest ChannelProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:46:43802.11n ht40
Middle ChannelProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:52:15802.11n ht40
Highest ChannelProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:56:47

4.4 99% Occupied Bandwidth

Serial Number:	22NH_2	Test Date:	2023/12/28
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rod Luo	Test Result:	N/A

Environmental Conditions:

Temperature: (°C)	25.3	Relative Humidity: (%)	48	ATM Pressure: (kPa)	101
----------------------	------	---------------------------	----	------------------------	-----




Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200120	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*


Test Data:

Test Modes	Test Channel	Test Frequency (MHz)	99% Occupied Bandwidth (MHz)
802.11b	Lowest	2412	13.48
	Middle	2437	13.48
	Highest	2462	13.48
802.11g	Lowest	2412	16.96
	Middle	2437	16.96
	Highest	2462	17.00
802.11n ht20	Lowest	2412	17.92
	Middle	2437	17.96
	Highest	2462	17.96
802.11n ht40	Lowest	2422	36.32
	Middle	2437	36.40
	Highest	2452	36.40

99% Occupied Bandwidth802.11b
Lowest Channel802.11b
Middle Channel802.11b
Highest Channel


99% Occupied Bandwidth

802.11g
Lowest Channel




ProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:17:49

802.11g
Middle Channel






ProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:22:15

802.11g
Highest Channel






ProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:25:57

99% Occupied Bandwidth

802.11n ht20
Lowest ChannelProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:31:40802.11n ht20
Middle ChannelProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:36:59802.11n ht20
Highest ChannelProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:40:17

99% Occupied Bandwidth

802.11n ht40
Lowest ChannelProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:46:19802.11n ht40
Middle ChannelProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:51:53802.11n ht40
Highest ChannelProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:56:24

4.5 Maximum Conducted Output Power

Serial Number:	22NH_2	Test Date:	2023/12/28
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rod Luo	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.3	Relative Humidity: (%)	48	ATM Pressure: (kPa)	101
----------------------	------	---------------------------	----	------------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Anritsu	Power Meter	ML2495A	1106009	2023/8/4	2024/8/3
Anritsu	Pulse Power Sensor	MA2411A	10780	2023/8/4	2024/8/3
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Modes	Test Frequency (MHz)	Maximum Conducted Peak Output Power (dBm)	Maximum Conducted Average Output Power (dBm)	Limit (dBm)
802.11b	2412	12.76	9.13	30
	2437	12.84	9.22	30
	2462	12.96	9.32	30
802.11g	2412	17.39	9.15	30
	2437	17.92	9.52	30
	2462	17.58	9.33	30
802.11n ht20	2412	16.58	9.04	30
	2437	17.91	9.35	30
	2462	17.81	9.27	30
802.11n ht40	2422	16.61	9.20	30
	2437	17.63	9.20	30
	2452	16.93	9.50	30

4.6 Maximum Power Spectral Density

Serial Number:	22NH_2	Test Date:	2023/12/28
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rod Luo	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.3	Relative Humidity: (%)	48	ATM Pressure: (kPa)	101
----------------------	------	------------------------------	----	------------------------	-----




Test Equipment List and Details:




Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200120	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*




Test Data:

Test Channel	Test Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	2412	-20.49	8.00
	2437	-20.41	8.00
	2462	-20.35	8.00
802.11g	2412	-19.06	8.00
	2437	-18.89	8.00
	2462	-19.38	8.00
802.11n ht20	2412	-18.98	8.00
	2437	-18.13	8.00
	2462	-18.58	8.00
802.11n ht40	2422	-18.95	8.00
	2437	-18.96	8.00
	2452	-19.13	8.00




Maximum power spectral density802.11b
Lowest ChannelProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:04:36802.11b
Middle ChannelProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:08:08802.11b
Highest ChannelProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:11:55

Maximum power spectral density802.11g
Lowest ChannelProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:18:36802.11g
Middle ChannelProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:23:08802.11g
Highest ChannelProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:26:41

Maximum power spectral density

802.11n ht20
Lowest ChannelProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:32:37802.11n ht20
Middle ChannelProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:37:45802.11n ht20
Highest ChannelProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:41:05

Maximum power spectral density

802.11n ht40
Lowest ChannelProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:47:08802.11n ht40
Middle ChannelProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:52:40802.11n ht40
Highest ChannelProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:57:32

4.7 100 kHz Bandwidth of Frequency Band Edge:

Serial Number:	22NH_2	Test Date:	2023/12/28
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rod Luo	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.3	Relative Humidity: (%)	48	ATM Pressure: (kPa)	101
----------------------	------	---------------------------	----	------------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200120	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A


** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

Test Modes	Test Frequency (MHz)	Result (dB)	Limit (dB)
802.11b	2412	43.63	20
	2462	42.72	20
802.11g	2412	33.15	20
	2462	39.36	20
802.11n ht20	2412	33.12	20
	2462	39.39	20
802.11n ht40	2422	31.94	20
	2452	34.63	20


100 kHz Bandwidth of Frequency Band Edge

802.11b
Lowest Band edge



ProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 17:28:45


802.11b
Highest Band edge



ProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 17:59:56


100 kHz Bandwidth of Frequency Band Edge

802.11g
Lowest Band edge



ProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 17:30:38


802.11g
Highest Band edge



ProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 18:06:06


100 kHz Bandwidth of Frequency Band Edge

802.11n ht20
Lowest Band edge



ProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 17:32:32


802.11n ht20
Highest Band edge



ProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 18:13:11


100 kHz Bandwidth of Frequency Band Edge

802.11n ht40
Lowest Band edge



ProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 17:50:55

802.11n ht40
Highest Band edge



ProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 18:16:30

4.8 Duty Cycle:

Serial Number:	22NH_2	Test Date:	2023/12/28
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rod Luo	Test Result:	N/A

Environmental Conditions:

Temperature: (°C)	25.3	Relative Humidity: (%)	48	ATM Pressure: (kPa)	101
----------------------	------	---------------------------	----	------------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200120	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A


** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

Test Modes	Ton (ms)	Ton+off (ms)	Duty cycle (%)	VBW setting (Hz)
802.11b	100	100	100	10
802.11g	100	100	100	10
802.11n ht20	100	100	100	10
802.11n ht40	100	100	100	10


Duty Cycle

802.11b




ProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:06:42

802.11g




ProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:21:15

802.11n ht20



ProjectNo.:CR230308451-RF Tester:Rod Luo
Date: 28.DEC.2023 16:35:54

802.11n ht40



ProjectNo.:CR230308451-RF Tester:Red Luo
Date: 28.DEC.2023 16:50:46

5. RF EXPOSURE EVALUATION

5.1 Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

5.2 Measurement Result

The max average conducted power including tune-up tolerance is 9.6dBm (9.12mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 9.12/5 \cdot (\sqrt{2.462}) = 2.9 < 3.0.$

Result: Compliant. The stand-alone SAR evaluation is not necessary.

6. EUT PHOTOGRAPHS

Please refer to the attachment CR230208451-EXP EUT EXTERNAL PHOTOGRAPHS and CR230208451-INP EUT INTERNAL PHOTOGRAPHS

7. TEST SETUP PHOTOGRAPHS

Please refer to the attachment CR230308451-00-TSP TEST SETUP PHOTOGRAPHS.

===== END OF REPORT =====