

RF Exposure Report

Report No.: SABEIH-WTW-P20120144

FCC ID: P27XHB1

Test Model: XHB1

Series Model: XHB1xxxxxxxxx; SCHB1AExxxxxxxxx

(the 1st x should be "blank" or "-"; the rest x could be 0 to 9, A to Z, a to z,

"blank" or "-", for marketing purpose)

Received Date: Dec. 04, 2020

Test Date: Dec. 30, 2020

Issued Date: Jan. 18, 2021

Applicant: Sercomm Corp.

Address: 8F, No. 3-1, YuanQu St., NanKang, Taipei 115, Taiwan, R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,

Taiwan

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,

laiwan

FCC Registration / Designation Number:

723255 / TW2022

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Report No.: SABEIH-WTW-P20120144 Page No. 1 / 7 Report Format Version: 6.1.1



Table of Contents

Relea	Release Control Record3				
1	Certificate of Conformity				
2	RF Exposure	5			
2.1	Limits For Maximum Permissible Exposure (MPE)	5			
2.2	MPE Calculation Formula	5			
	B Classification				
2.4	4 Antenna Gain	6			
2.5	5 Calculation Result	7			



Release Control Record

Issue No.	Description	Date Issued
SABEIH-WTW-P20120144	Original release.	Jan. 18, 2021



1 Certificate of Conformity

Product: Comcast Xfinity Home Doorbell Camera

Brand: Sercomm, Comcast, Xfinity

Test Model: XHB1

Series Model: XHB1xxxxxxxxx; SCHB1AExxxxxxxxx

(the 1st x should be "blank" or "-"; the rest x could be 0 to 9, A to Z, a to z,

"blank" or "-", for marketing purpose)

Sample Status: Engineering sample

Applicant: Sercomm Corp.

Test Date: Dec. 30, 2020

Standards: FCC Part 2 (Section 2.1091)

IEEE C95.3 -2002

References Test Guidance KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : , **Date:** Jan. 18, 2021

Joyce Kuo / Specialist

Approved by: , Date: Jan. 18, 2021

Clark Lin / Technical Manager



2 RF Exposure

2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	, ,			Average Time (minutes)	
	Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30	
1.34-30	824/f	2.19/f	(180/f ²)*	30	
30-300	27.5	0.073	0.2	30	
300-1500			f/1500	30	
1500-100,000			1.0	30	

f = Frequency in MHz; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



2.4 Antenna Gain

Main source					
Frequency Range (GHz)	Antenna Peak Gain (dBi)	Antenna Type	Antenna Connector		
2.4~2.5	3.03	, ,			
5.15~5.25	5.24	1			
5.25~5.35	6.09	6.09 PIFA			
5.47~5.725	6.56]			
5.725~5.85	6.27]			
	2 nd source				
Frequency Range (GHz)	Antenna Peak Gain (dBi)	Antenna Type	Antenna Connector		
2.4~2.5	3				
5.15~5.25	5.2				
5.25~5.35	6.0	PIFA	NA		
5.47~5.725	6.3				
5.725~5.85	6.0				
Note: The maximum gain w	as chosen for test.				

^{*}The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.



2.5 Calculation Result

Operation Mode	Evaluation Frequency (MHz)	Max Avg. Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
WLAN 2.4GHz	2412-2462	533.335	3.03	20	0.21317	1
WLAN 5GHz (U-NII-1)	5180-5240	58.884	5.24	20	0.03915	1
WLAN 5GHz (U-NII-2A)	5250-5320	48.753	6.09	20	0.03942	1
WLAN 5GHz (U-NII-2C)	5500-5700	191.867	6.56	20	0.17287	1
WLAN 5GHz (U-NII-3)	5745-5825	459.198	6.27	20	0.38702	1
Bluetooth	2402-2480	5.61	3.03	20	0.00224	1

NOTE:

1.	Determining compliance based on the results of the compliance measurement, not taking into account
	measurement instrumentation uncertainty.

--- END ---