

Grade	Consume(ml/h)	Concentration	
		Working(g/l)	Shop(g/l)
G1	0.07	25s	300s
G2	0.14	12s	150s
G3	0.20	20s	120s
G4	0.27	20s	80s
G5	0.33	25s	80s
G6	0.40	35s	75s
G7	0.46	35s	60s
G8	0.53	35s	50s
G9	0.59	35s	40s
G10	0.66	35s	35s
G11	0.75	33s	30s
G12	0.86	45s	30s
G13	0.96	55s	30s
G14	1.06	65s	30s
G15	1.16	75s	35s
G16	1.26	85s	25s
G17	1.36	85s	20s
G18	1.46	120s	20s
G19	1.56	150s	15s
G20	1.65	300s	15s
Customized	—	5-500s	5-500s

[illegible]

تعديل كلمة المرور

البيانات الشخصية

الاسم:

البريد الإلكتروني:

رقب الهاتف:

تغيير المعلومات

تعديل كلمة المرور

تغيير كلمة المرور

إذا كنت بحاجة لتعديل بعض البيانات الشخصية، فيمكنك القيام بذلك من خلال صفحة التعديل الخاصة بك.
 يجب أن تكون كلمة المرور مكونة من 8 أحرف على الأقل ويجب أن تحتوي على:
 - حرف كبير
 - حرف صغير
 - رقم
 - علامة خاصة

عدادات الشاشة

العدادات والشاشون

العداد

وحدة عمل العداد

وحدة التوقيت

تشغيل العداد

قم بتوصيل العداد بالشبكة وتغلق العداد مع لوحة حديد "Steel".
تعمل العداد بوضع التوقيت الأول وتكون العداد

إيقاف العداد

سواء إيقاف العداد بالشبكة أو بوضع العداد

طريقة التوقيت المحلي

العداد على SET واسمح في العداد 5 أو 10 دقائق لتصبح
تكون العداد "توقيت" مع ذلك بدأ العداد التوقيت في التوقيت
العداد على ON أو إيقاف العداد التوقيت أو مع العداد
العداد بوضع التوقيت بالعداد على SET أو EPT العداد أو EPT العداد
العداد العداد على SET أو EPT العداد
العداد العداد في العداد

لتحديد درجة التوقيت

تكون 5 دقائق درجة التوقيت على
العداد العداد على العداد على العداد العداد
العداد العداد في العداد

Figure 1 displays five mockups of the user interface for the proposed system, arranged in a 2x3 grid with the bottom-right cell empty. Each mockup represents a different screen in the application:

- Top Left (Login):** Titled "Login", it features a "Username" input field, a "Password" input field, and a "Login" button.
- Top Middle (Register):** Titled "Register", it includes "Username", "Password", and "Confirm Password" input fields, along with a "Register" button.
- Top Right (Password Reset):** Titled "Password Reset", it contains an "Email" input field, "New Password", and "Confirm Password" input fields, and a "Reset" button.
- Bottom Left (Forgot Password):** Titled "Forgot password", it has an "Email" input field and a "Forgot Password" button.
- Bottom Middle (Home):** Titled "Home", it displays a "Welcome" message and a "Logout" button.

يتمثل في تصميم واجهة المستخدم في شكل شاشة رئيسية تحتوي على أزرار مختلفة

تتمثل في شكل شاشة تحتوي على نموذج سؤال، نموذج إجابة، نموذج تقييم، نموذج تعليقات، نموذج تقييم

[illegible]



تحذير

يرجى التنبيه إلى أن استخدام أجهزة التنفس الشخصية يتطلب تدريباً وفقاً للمواصفات الدولية ويجب ارتداء الملابس الخاصة بالتنفس في الأماكن المغلقة.

يجب أن تكون هناك خطة إخلاء في حالة حدوث أي طارئ ويجب تدريب جميع العاملين على هذه الخطة.

يجب أن تكون أجهزة التنفس الشخصية معتمدة وفقاً للمواصفات الدولية ويجب أن تكون في حالة صيانة جيدة.

يجب أن تكون أجهزة التنفس الشخصية معتمدة وفقاً للمواصفات الدولية ويجب أن تكون في حالة صيانة جيدة.

يجب أن تكون أجهزة التنفس الشخصية معتمدة وفقاً للمواصفات الدولية ويجب أن تكون في حالة صيانة جيدة.






التباعد

يرجى التنبيه إلى أن التباعد الاجتماعي هو أحد أهم وسائل الوقاية من انتشار الفيروسات.

يجب أن تكون التباعد الاجتماعي هو أحد أهم وسائل الوقاية من انتشار الفيروسات.

يجب أن تكون التباعد الاجتماعي هو أحد أهم وسائل الوقاية من انتشار الفيروسات.

يجب أن تكون التباعد الاجتماعي هو أحد أهم وسائل الوقاية من انتشار الفيروسات.

يجب أن تكون التباعد الاجتماعي هو أحد أهم وسائل الوقاية من انتشار الفيروسات.




الاماكن المناسبة

يجب أن تكون الأماكن المناسبة هي الأماكن التي تتوفر فيها التهوية الجيدة والتباعد الجيد.

يجب أن تكون الأماكن المناسبة هي الأماكن التي تتوفر فيها التهوية الجيدة والتباعد الجيد.

يجب أن تكون الأماكن المناسبة هي الأماكن التي تتوفر فيها التهوية الجيدة والتباعد الجيد.

يجب أن تكون الأماكن المناسبة هي الأماكن التي تتوفر فيها التهوية الجيدة والتباعد الجيد.

يجب أن تكون الأماكن المناسبة هي الأماكن التي تتوفر فيها التهوية الجيدة والتباعد الجيد.





Product Manual

Aroma diffuser
CA-500S-V2.0

SCAN THE QR CODE TO
DOWNLOAD THE APP

www.cubeairoma.com

Concentration&Consumption

Grade	Consume(ml/h)	Concentration	
		Working(s)	Stop(s)
G1	0.07	15s	300s
G2	0.14	15s	150s
G3	0.20	20s	120s
G4	0.27	20s	85s
G5	0.33	25s	80s
G6	0.40	30s	75s
G7	0.48	30s	60s
G8	0.53	30s	50s
G9	0.59	30s	40s
G10	0.66	30s	33s
G11	0.75	33s	30s
G12	0.86	40s	30s
G13	0.90	50s	30s
G14	1.06	90s	30s
G15	1.16	75s	20s
G16	1.26	90s	25s
G17	1.36	85s	20s
G18	1.46	120s	20s
G19	1.56	150s	15s
G20	1.65	160s	15s
Customized	—	5-500s	5-600s

Note:1.The above data are tested based on the test oil;
2.The above data is for reference only and the amount of atomization produced by different essential oils may be different.

Specification

Model	CA-500S-V2.0
Size	240*200*100mm
Net Wt.	2.22kg
Input	120/1A
Power	53W
Coverage	300-410m³/5.2m²
Bottle	250ml
Material	Metal

Panel Description

LCD+Bluetooth version:
See panel operation for details

Installation Steps

1. Open the door with key;
2. Twist off the bottle;
3. Add fragrance into bottle;
4. Screw the bottle back to the machine head, then lock the door with key.

1. Mark the bracket holes, drill holes at the marks, install the wall anchors;
2. Screw the bracket to the wall, then hang on the machine.

Cleaning diffuser

Diffuser should be cleaned regularly, timing recommendations below:
1. Refilling / changing fragrance in reservoir;
2. Switching strength becomes weak.

- Turn off Breathing Diffuser before cleaning.
- Place clean bottle with small quantity of "Isopropyl Spirit" (industrial alcohol).
- Turn on Machine and let diffuse for 5 minutes.
- Turn off power and unplug cleaning fluid bottle.
- Replace with fresh fragrance, machine is now ready for diffusing.

APP instruction

Where to get the app?
Please search for "Cube Aroma" in Google play or App store.

Note:
1. Please make sure that the Bluetooth function is turned on;
2. Please make sure that the location function of the mobile phone is turned on.

Description: This value is calculated based on one hour of continuous machine work with 12 different types of air comparators. But since different diffusers have different consumption rates, you can calculate it in advance.

Reminder: This refers to how long the aroma oil can be used based on consumption, aroma oil grade, and working periods.

Calibrate: It is used for calibrating consumption. It is advised to calibrate after working for at least 10 days. Please measure the remaining oil of bottle first, then tap "Calibrate" in the APP. Input the amount of remaining oil, and confirm, so the consumption, remaining day, and percentage will be updated.

Amend password

If you forget the password, please press the reset button to restore the factory setting. The factory settings password is 8888.

Troubleshooting

Before asking for service the machine reported, please try to diagnose the problem first following by these instructions.

Symptoms	Remedy
Does not diffuse	- Check the power is on or off. - If the machine is in "not working period", it stops diffusing. The pump is damaged, change a new one. - Nozzle holder may be blocked, diffuse with alcohol to clean it.
Spillages occur	- Plug is aging, change a new one. - Nozzle holder is damaged, change a new one. - Nozzle is loose, screw it to the right place.
Does not work	- Plug is loose, install it correctly. - The power is off. - Plug is damaged, change a new plug. - Display screen is damaged, change a new one.

Touch Screen Setting

Turn on the power:
Connect the power and turn on the switch with a sound "beep" coming out, then the screen shows the initial time and the current grade.

Turn off the power:
The screen will be off when turn off the switch and disconnect the power.

Local time setting:
Tap SET button and hold for 3 seconds until you hear a sound "beep" then the date value start flashing. Tap Air to adjust the date, then confirm and adjust time value by tapping ENT button. Tap Air to adjust the time. Tap SET button to save the setting. (Shown as picture 1)

Concentration grade setting:
There are 20 grades to choose. Tap Air button, the grade will increase. Tap Air button the grade will decrease. (Shown as picture 2)

Working periods setting

There are total 3 working periods (shown as picture 3). Tap SET to set the first working period (ON/OFF).

Tap Air to set the start time. Tap ENT to confirm and then set the stop time. After setting the first working period (ON/OFF), we can set the working date. Tap ENT to turn to ON and tap Air to enter the working time period for ON. (ON 1 is displayed on the screen, shown as picture 4). Tap Air to confirm and set the current setting (OFF 1) is displayed on the screen, shown as picture 5).

After finish setting the first working period, tap SET to confirm and set.

Tap ENT to turn to next day's setting. The setting step for ON2, ON3, ON4, etc is same as ON1. After setting all working time periods, tap SET to confirm and set the setting.

Grade display with "C" % for customized grade, only can be operated by APP. (picture 6). Machine doesn't work when the start time is same as stop time.

PS: The first working period is default from 00:00-23:59 everyday.

Wifi instruction

1. Open the APP, Select WIFI.
2. New user can sign up, or phone number or email address.
3. You can log in via account name and password.

4. Forget password.
5. Reset password.

If you forget the password, enter your mobile phone number or email address for verification.

6. Add devices.
7. Select the device to be added.

8. Enter WIFI password (it can click "Scan" to start connecting, only support 2.4G WIFI).
9. After successful configuration, you can give a name to the machine.

10. Click the icon in the upper right corner to manage the current device.

11. User can click "+" to the upper right corner to create a new group.
12. Click the icon in the upper right corner to manage the current device.

13. Click the icon in the upper right corner to manage the current device.
14. Click the icon in the upper right corner to manage the current device.

15. Click the icon in the upper right corner to manage the current device.

16. Click the icon in the upper right corner to manage the current device.
17. Click the icon in the upper right corner to manage the current device.

18. Click the icon in the upper right corner to manage the current device.
19. Click the icon in the upper right corner to manage the current device.

20. Click the icon in the upper right corner to manage the current device.

How to connect with HVAC

1. Connect the connector with PU pipe on top of machine.
2. Connect the connector with PU pipe on top of machine.

3. Connect the connector with PU pipe on top of machine.
4. Connect the connector with PU pipe on top of machine.

5. Connect the connector with PU pipe on top of machine.

Warning

FCC Warning

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

NOTE 1: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:
- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

NOTE 2: This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator and your body.
The device has been evaluated to meet general RF exposure requirement.

Warning

- Do not modify, disassemble or repair the machine without a professional. Any failure to follow these instructions may void the warranty.
- Do not use the power cord, fork to bend, pinch, heavy load, step or compress.
- Do not use the AC plug when it is damaged or not matched with the socket.
- Do not use the machine in the AC plug.
- Do not use the machine power switch, wire or broken plug.
- Do not start the work or product when thundering or strong lightning.
- Do not touch the machine when it is under operating.

Application

Application places: Hotel, Meeting Room, Hall, Exhibition Hall, Grand Hotel, etc. (as shown in picture 1).

1. Application places: Hotel, Meeting Room, Hall, Exhibition Hall, Grand Hotel, etc. (as shown in picture 1).

2. Application places: Hotel, Meeting Room, Hall, Exhibition Hall, Grand Hotel, etc. (as shown in picture 1).

3. Application places: Hotel, Meeting Room, Hall, Exhibition Hall, Grand Hotel, etc. (as shown in picture 1).

4. Application places: Hotel, Meeting Room, Hall, Exhibition Hall, Grand Hotel, etc. (as shown in picture 1).

5. Application places: Hotel, Meeting Room, Hall, Exhibition Hall, Grand Hotel, etc. (as shown in picture 1).

6. Application places: Hotel, Meeting Room, Hall, Exhibition Hall, Grand Hotel, etc. (as shown in picture 1).

7. Application places: Hotel, Meeting Room, Hall, Exhibition Hall, Grand Hotel, etc. (as shown in picture 1).

8. Application places: Hotel, Meeting Room, Hall, Exhibition Hall, Grand Hotel, etc. (as shown in picture 1).

Caution

- Atomization lamp display on screen but the machine would not diffuse when it stops on power time.
- Touch: Tap screen will not operate when Diffuser is in lock status.
- Display: screen not functioning normally, display unclear or program crash. Reset Diffuser, touch "SET" (5 seconds) until "beep".
- Diffuser must be vertical at all times when fragrance is in bottle. When using fan, tap or touch the fan button to stop the fan. This may affect Diffuser efficiency. If not touch or touch is not working, it will be damaged.
- After installation, please keep the machine vertical. Tilting or placing it flat may cause an oil overflow. The machine efficiency may be affected if the oil level is contaminated.

1. Application places: Hotel, Meeting Room, Hall, Exhibition Hall, Grand Hotel, etc. (as shown in picture 1).

2. Application places: Hotel, Meeting Room, Hall, Exhibition Hall, Grand Hotel, etc. (as shown in picture 1).

3. Application places: Hotel, Meeting Room, Hall, Exhibition Hall, Grand Hotel, etc. (as shown in picture 1).

4. Application places: Hotel, Meeting Room, Hall, Exhibition Hall, Grand Hotel, etc. (as shown in picture 1).

5. Application places: Hotel, Meeting Room, Hall, Exhibition Hall, Grand Hotel, etc. (as shown in picture 1).

6. Application places: Hotel, Meeting Room, Hall, Exhibition Hall, Grand Hotel, etc. (as shown in picture 1).

7. Application places: Hotel, Meeting Room, Hall, Exhibition Hall, Grand Hotel, etc. (as shown in picture 1).

8. Application places: Hotel, Meeting Room, Hall, Exhibition Hall, Grand Hotel, etc. (as shown in picture 1).

9. Application places: Hotel, Meeting Room, Hall, Exhibition Hall, Grand Hotel, etc. (as shown in picture 1).

10. Application places: Hotel, Meeting Room, Hall, Exhibition Hall, Grand Hotel, etc. (as shown in picture 1).