

## Partial FCC Test Report (Part 24 – WCDMA B2, LTE B2/B25)

**Report No.:** RFCDVB-WTW-P22100073-1

**FCC ID:** QYLLN920V

**Test Model:** LN920A12-WW

**Received Date:** Oct. 11, 2022

**Test Date:** Oct. 27 ~ Oct. 31, 2022

**Issued Date:** Dec. 27, 2022

**Applicant:** Getac Technology Corporation.

**Address:** 5F., Building A, No. 209, Sec.1, Nangang Rd., Nangang Dist., Taipei City  
11568, Taiwan, R.O.C.

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Lin Kou Laboratories

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**Test Location:** No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City  
33383, TAIWAN

**FCC Registration /** 788550 / TW0003  
**Designation Number:**



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

## Table of Contents

|                                                                   |           |
|-------------------------------------------------------------------|-----------|
| <b>Release Control Record .....</b>                               | <b>3</b>  |
| <b>1 Certificate of Conformity .....</b>                          | <b>4</b>  |
| <b>2 Summary of Test Results .....</b>                            | <b>5</b>  |
| 2.1 Measurement Uncertainty .....                                 | 5         |
| 2.2 Test Site and Instruments .....                               | 6         |
| <b>3 General Information .....</b>                                | <b>7</b>  |
| 3.1 General Description of EUT .....                              | 7         |
| 3.2 Configuration of System under Test .....                      | 11        |
| 3.2.1 Description of Support Units .....                          | 11        |
| 3.3 Test Mode Applicability and Tested Channel Detail .....       | 12        |
| 3.4 EUT Operating Conditions .....                                | 15        |
| 3.5 General Description of Applied Standards and References ..... | 15        |
| <b>4 Test Types and Results .....</b>                             | <b>16</b> |
| 4.1 Output Power Measurement .....                                | 16        |
| 4.1.1 Limits of Output Power Measurement .....                    | 16        |
| 4.1.2 Test Procedures .....                                       | 16        |
| 4.1.3 Test Setup .....                                            | 16        |
| 4.1.4 Test Results .....                                          | 17        |
| 4.2 Radiated Emission Measurement .....                           | 43        |
| 4.2.1 Limits of Radiated Emission Measurement .....               | 43        |
| 4.2.2 Test Procedure .....                                        | 43        |
| 4.2.3 Deviation from Test Standard .....                          | 43        |
| 4.2.4 Test Setup .....                                            | 44        |
| 4.2.5 Test Results .....                                          | 45        |
| <b>5 Pictures of Test Arrangements .....</b>                      | <b>65</b> |
| <b>Appendix – Information of the Testing Laboratories .....</b>   | <b>66</b> |

### Release Control Record

| Issue No.              | Description      | Date Issued   |
|------------------------|------------------|---------------|
| RFCDVB-WTW-P22100073-1 | Original release | Dec. 27, 2022 |

## 1 Certificate of Conformity

**Product:** Radio Module

**Brand:** Getac

**Test Model:** LN920A12-WW

**Sample Status:** Engineering sample

**Applicant:** Getac Technology Corporation.

**Test Date:** Oct. 27 ~ Oct. 31, 2022

**Standards:** FCC Part 24, Subpart E

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

**Prepared by :** Celine Chou , **Date:** Dec. 27, 2022  
Celine Chou / Senior Specialist

**Approved by :** Jeremy Lin , **Date:** Dec. 27, 2022  
Jeremy Lin / Project Engineer

## 2 Summary of Test Results

| Applied Standard: FCC Part 24 & Part 2 |                                        |        |                                                                                        |
|----------------------------------------|----------------------------------------|--------|----------------------------------------------------------------------------------------|
| FCC Clause                             | Test Item                              | Result | Remarks                                                                                |
| 2.1046<br>24.232                       | Effective Isotropically Radiated Power | Pass   | Meet the requirement of limit.                                                         |
| 2.1046<br>24.232<br>(d)                | Peak To Average Ratio                  | N/A    | Refer to Note                                                                          |
| 2.1047                                 | Modulation Characteristics             | N/A    | Refer to Note                                                                          |
| 2.1055<br>24.235                       | Frequency Stability                    | N/A    | Refer to Note                                                                          |
| 2.1049                                 | Occupied Bandwidth                     | N/A    | Refer to Note                                                                          |
| 24.238                                 | Band Edge Measurements                 | N/A    | Refer to Note                                                                          |
| 2.1051<br>24.238                       | Conducted Spurious Emissions           | N/A    | Refer to Note                                                                          |
| 2.1053<br>24.238                       | Radiated Spurious Emissions            | Pass   | Meet the requirement of limit.<br>Minimum passing margin is<br>-17.94dB at 3765.00MHz. |

### Note:

1. This report is a Class II change partial report. Therefore, only test item of Radiated Spurious Emissions tests and Effective Isotropically Radiated Power were performed for this report. Other testing data please refer to SGS Taiwan Ltd. report no.: TERF2206000792ER and TERF2206000793ER for module (Brand: Telit, Model: LN920A12-WW).
2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement                    | Frequency        | Expanded Uncertainty (k=2) (±) |
|--------------------------------|------------------|--------------------------------|
| Radiated Emissions up to 1 GHz | 9kHz ~ 30MHz     | 3.59 dB                        |
|                                | 30MHz ~ 200MHz   | 3.63 dB                        |
|                                | 200MHz ~ 1000MHz | 3.64 dB                        |
| Radiated Emissions above 1 GHz | 1GHz ~ 18GHz     | 2.29 dB                        |
|                                | 18GHz ~ 40GHz    | 2.29 dB                        |

## 2.2 Test Site and Instruments

| Description & Manufacturer                 | Model No.                      | Serial No.                   | Cal. Date     | Cal. Due      |
|--------------------------------------------|--------------------------------|------------------------------|---------------|---------------|
| Test Receiver<br>R&S                       | ESCI                           | 100424                       | Dec. 30, 2021 | Dec. 29, 2022 |
| Spectrum Analyzer<br>R&S                   | FSW43                          | 101582                       | Apr. 13, 2022 | Apr. 12, 2023 |
| Loop Antenna<br>TESEQ                      | HLA 6121                       | 45745                        | Jul. 27, 2022 | Jul. 26, 2023 |
| Pre-amplifier<br>EMCI                      | EMC001340                      | 980201                       | Sep. 23, 2022 | Sep. 22, 2023 |
| RF Coaxial Cable<br>EMCI                   | 5D-NM-BM                       | 140903+140902                | Jan. 15, 2022 | Jan. 14, 2023 |
| Preamplifier<br>Agilent                    | 8447D                          | 2944A10631                   | May 14, 2022  | May 13, 2023  |
| BILOG Antenna<br>SCHWARZBECK               | VULB9168                       | 9168-155                     | Nov. 01, 2021 | Oct. 31, 2022 |
| RF Coaxial Cable<br>EMCI                   | EMC102-KM-KM-3000              | 150929                       | Jul. 09, 2022 | Jul. 08, 2023 |
| RF Coaxial Cable<br>EMCI                   | EMC102-KM-KM-600               | 150928                       | Jul. 09, 2022 | Jul. 08, 2023 |
| HORN Antenna<br>SCHWARZBECK                | BBHA 9170                      | BBHA9170241                  | Oct. 20, 2022 | Oct. 19, 2023 |
| Preamplifier<br>KEYSIGHT                   | 83017A                         | MY53270295                   | May 14, 2022  | May 13, 2023  |
| RF signal cable<br>HUBER+SUHNER            | SUCOFLEX 104                   | MY 13380+295012/04           | May 14, 2022  | May 13, 2023  |
| RF signal cable<br>HUBER+SUHNER            | SUCOFLEX 104                   | Cable-CH4-03 (250724)        | May 14, 2022  | May 13, 2023  |
| Pre-Amplifier<br>EMCI                      | EMC 184045                     | 980116                       | Oct. 01, 2022 | Sep. 30, 2023 |
| RF Coaxial Cable<br>HUBER+SUHNER&EMCI      | SUCOFLEX 104& EMC104-SM-SM8000 | CABLE-CH9-02 (248780+171006) | Jan. 15, 2022 | Jan. 14, 2023 |
| RF Coaxial Cable<br>HUBER+SUHNER           | SUCOFLEX 104                   | CABLE-CH9-(250795/4)         | Jan. 15, 2022 | Jan. 14, 2023 |
| Software<br>BV ADT                         | ADT_Radiated_V7.6.15.9.5       | NA                           | NA            | NA            |
| Antenna Tower<br>inn-co GmbH               | MA 4000                        | 010303                       | NA            | NA            |
| Turn Table<br>BV ADT                       | TT100                          | TT93021705                   | NA            | NA            |
| Turn Table Controller<br>BV ADT            | SC100                          | SC93021705                   | NA            | NA            |
| Boresight antenna tower<br>fixture<br>BV   | BAF-02                         | 5                            | NA            | NA            |
| Radio Communication<br>Analyzer<br>Anritsu | MT8820C                        | 6201300640                   | Aug. 26, 2021 | Aug. 22, 2023 |

Note: 1. The calibration interval of the above test instruments is 12/24 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. The test was performed in HY - 966 chamber 3.

### 3 General Information

#### 3.1 General Description of EUT

|                     |                                                                            |                       |
|---------------------|----------------------------------------------------------------------------|-----------------------|
| Product             | Radio Module                                                               |                       |
| Brand               | Getac                                                                      |                       |
| Test Model          | LN920A12-WW                                                                |                       |
| Sample Status       | Engineering sample                                                         |                       |
| Power Supply Rating | 3.3Vdc                                                                     |                       |
| Modulation Type     | WCDMA: BPSK, QPSK<br>HSDPA: BPSK<br>HSUPA: QPSK<br>LTE: QPSK, 16QAM, 64QAM |                       |
| Operating Frequency | WCDMA Band 2                                                               | 1852.4MHz ~ 1907.6MHz |
|                     | LTE Band 2 (Channel Bandwidth 1.4MHz)                                      | 1850.7MHz ~ 1909.3MHz |
|                     | LTE Band 2 (Channel Bandwidth 3MHz)                                        | 1851.5MHz ~ 1908.5MHz |
|                     | LTE Band 2 (Channel Bandwidth 5MHz)                                        | 1852.5MHz ~ 1907.5MHz |
|                     | LTE Band 2 (Channel Bandwidth 10MHz)                                       | 1855.0MHz ~ 1905.0MHz |
|                     | LTE Band 2 (Channel Bandwidth 15MHz)                                       | 1857.5MHz ~ 1902.5MHz |
|                     | LTE Band 2 (Channel Bandwidth 20MHz)                                       | 1860.0MHz ~ 1900.0MHz |
|                     | LTE Band 25 (Channel Bandwidth 1.4MHz)                                     | 1850.7MHz ~ 1914.3MHz |
|                     | LTE Band 25 (Channel Bandwidth 3MHz)                                       | 1851.5MHz ~ 1913.5MHz |
|                     | LTE Band 25 (Channel Bandwidth 5MHz)                                       | 1852.5MHz ~ 1912.5MHz |
|                     | LTE Band 25 (Channel Bandwidth 10MHz)                                      | 1855.0MHz ~ 1910.0MHz |
|                     | LTE Band 25 (Channel Bandwidth 15MHz)                                      | 1857.5MHz ~ 1907.5MHz |
|                     | LTE Band 25 (Channel Bandwidth 20MHz)                                      | 1860.0MHz ~ 1905.0MHz |

|                   |                                        |                         |                         |                         |
|-------------------|----------------------------------------|-------------------------|-------------------------|-------------------------|
| Max. EIRP Power   | WCDMA Band 2                           | 275.423mW (24.40dBm)    |                         |                         |
|                   |                                        | QPSK                    | 16QAM                   | 64QAM                   |
|                   | LTE Band 2 (Channel Bandwidth 1.4MHz)  | 215.278mW<br>(23.33dBm) | 167.494mW<br>(22.24dBm) | 124.738mW<br>(20.96dBm) |
|                   | LTE Band 2 (Channel Bandwidth 3MHz)    | 213.796mW<br>(23.30dBm) | 167.494mW<br>(22.24dBm) | 125.893mW<br>(21.00dBm) |
|                   | LTE Band 2 (Channel Bandwidth 5MHz)    | 215.278mW<br>(23.33dBm) | 166.725mW<br>(22.22dBm) | 124.738mW<br>(20.96dBm) |
|                   | LTE Band 2 (Channel Bandwidth 10MHz)   | 215.774mW<br>(23.34dBm) | 164.816mW<br>(22.17dBm) | 125.026mW<br>(20.97dBm) |
|                   | LTE Band 2 (Channel Bandwidth 15MHz)   | 215.774mW<br>(23.34dBm) | 164.816mW<br>(22.17dBm) | 125.603mW<br>(20.99dBm) |
|                   | LTE Band 2 (Channel Bandwidth 20MHz)   | 216.272mW<br>(23.35dBm) | 168.267mW<br>(22.26dBm) | 126.765mW<br>(21.03dBm) |
|                   | LTE Band 25 (Channel Bandwidth 1.4MHz) | 217.270mW<br>(23.37dBm) | 168.267mW<br>(22.26dBm) | 132.434mW<br>(21.22dBm) |
|                   | LTE Band 25 (Channel Bandwidth 3MHz)   | 216.272mW<br>(23.35dBm) | 169.434mW<br>(22.29dBm) | 132.739mW<br>(21.23dBm) |
|                   | LTE Band 25 (Channel Bandwidth 5MHz)   | 214.783mW<br>(23.32dBm) | 168.655mW<br>(22.27dBm) | 132.434mW<br>(21.22dBm) |
|                   | LTE Band 25 (Channel Bandwidth 10MHz)  | 215.774mW<br>(23.34dBm) | 169.824mW<br>(22.30dBm) | 130.918mW<br>(21.17dBm) |
|                   | LTE Band 25 (Channel Bandwidth 15MHz)  | 213.796mW<br>(23.30dBm) | 170.216mW<br>(22.31dBm) | 131.826mW<br>(21.20dBm) |
|                   | LTE Band 25 (Channel Bandwidth 20MHz)  | 222.331mW<br>(23.47dBm) | 170.608mW<br>(22.32dBm) | 133.660mW<br>(21.26dBm) |
| Antenna Type      | Refer to Note as below                 |                         |                         |                         |
| Antenna Connector | Refer to Note as below                 |                         |                         |                         |
| Accessory Device  | NA                                     |                         |                         |                         |
| Cable Supplied    | NA                                     |                         |                         |                         |

Note:

1. The EUT is authorized for use in specific End-product.

| Product  | Brand | Model                                                                                  | Difference            |
|----------|-------|----------------------------------------------------------------------------------------|-----------------------|
| Notebook | Getac | V110                                                                                   | For marketing purpose |
|          |       | V110G7                                                                                 |                       |
|          |       | V110Y (Y= 10 characters, Y can be 0 to 9, A to Z, a to z, "/", "\", "-", " " or blank) |                       |

\* The model of the V110G7 was chosen for final test.

2. The End-product contains following accessory devices.

| Part          | Brand                 | Model         | Specification                                                                                                    |
|---------------|-----------------------|---------------|------------------------------------------------------------------------------------------------------------------|
| Adapter 1     | FSP                   | FSP065-RBBN3  | I/P: 100-240Vac, 50-60Hz, 1.5A<br>O/P: 19.0Vdc, 3.42A<br>1.5m DC power cable with one core attached on adapter   |
| Adapter 2     | Getac                 | MTA190474W4   | I/P: 100-240Vac, 50-60Hz, 1.6A<br>O/P: 19.0Vdc, 4.74A<br>1.55m DC power cable with two cores attached on adapter |
| Battery       | Getac                 | BP3S1P2100-S  | Rating: 11.1Vdc, 2040mAh, 23Wh<br>Typical name: 2100mAh, 24Wh                                                    |
| Digitizer Pen | EMpen Technology Corp | DIGITIZER PEN | -                                                                                                                |

3. The End-product has three SKUs for sale, after pre-test. SKU 2 was chosen for final test and presented in the test report.


| Part             | Brand     | Model       | Specification       | Configuration |       |       |
|------------------|-----------|-------------|---------------------|---------------|-------|-------|
|                  |           |             |                     | SKU 1         | SKU 2 | SKU 3 |
| CPU              | Intel     | Alder Lake  | i5-1235U (Non Vpro) | V             |       | V     |
|                  |           |             | i7-1265U (Vpro)     |               | V     |       |
| DDR              | Kingston  | ---         | 16GB (8GB+8GB)      | V             |       |       |
|                  |           | ---         | 32GB (16GB+16GB)    |               | V     |       |
|                  |           | ---         | 64GB (32GB+32GB)    |               |       | V     |
| SSD              | SSSTC     | ---         | 256GB               | V             |       |       |
|                  |           | ---         | 512GB               |               | V     |       |
|                  |           | ---         | 1TB                 |               |       | V     |
| LCD Panel        | AUO       | G116HAN01   | 11.6"               | V             | V     | V     |
| Touchscreen      | Getac     | ---         | ---                 | V             | V     | V     |
| Finger Print     | Egistec   | ---         | ---                 | V             | V     | V     |
| WLAN Module      | Intel     | AX211NGW    | ---                 | V             | V     | V     |
| WWAN Module      | Telit     | LN920A12-WW | ---                 | V             | V     | V     |
| GPS              | GlobalSat | MC1010G     | ---                 | V             | V     | V     |
| RFID Module      | NXP       | PN-7462     | ---                 |               | V     | V     |
| Digitizer Module | Getac     | EMR116-UA00 | ---                 |               | V     | V     |
| Bottom Camera    | FOXLINK   | FN80AF-443H | ---                 | V             | V     | V     |
|                  | Chicony   | CKAM816     | ---                 | V             | V     | V     |
| Camera           | FOXLINK   | FN20FF-679H | ---                 | V             | V     | V     |
| IR Camera        | FOXLINK   | FN23FF-678H | ---                 |               | V     | V     |
| Option Bay       | Honeywell | N6703       | Barcode             | V             |       | V     |
|                  | Getac     | ---         | SD Card reader      |               | V     |       |
|                  | Getac     | ---         | Smart Card          |               | V     |       |

4. The following antennas were provided to the End-product.


| Ant.              | Type | Connector | Gain (dBi) |          |          |         |         |         |         |         |         |
|-------------------|------|-----------|------------|----------|----------|---------|---------|---------|---------|---------|---------|
|                   |      |           | WCDMA B2   | WCDMA B4 | WCDMA B5 | LTE B2  | LTE B4  | LTE B5  | LTE B7  | LTE B12 | LTE B13 |
| Main<br>(TX / RX) | PIFA | I-PEX     | 2.48       | 2.28     | -0.69    | 2.48    | 2.28    | -0.69   | 1.92    | 3.16    | 0.87    |
|                   |      |           | LTE B14    | LTE B25  | LTE B26  | LTE B38 | LTE B41 | LTE B48 | LTE B66 | LTE B71 |         |
|                   |      |           | 0.78       | 2.48     | -0.69    | 2.15    | 2.82    | -1.30   | 2.28    | 2.65    |         |
| Ant.              | Type | Connector | Gain (dBi) |          |          |         |         |         |         |         |         |
|                   |      |           | WCDMA B2   | WCDMA B4 | WCDMA B5 | LTE B2  | LTE B4  | LTE B5  | LTE B7  | LTE B12 | LTE B13 |
| Aux<br>(RX only)  | PIFA | I-PEX     | 4.17       | 2.69     | -1.49    | 4.17    | 2.69    | -1.49   | -0.11   | -3.06   | 0.60    |
|                   |      |           | LTE B14    | LTE B25  | LTE B26  | LTE B38 | LTE B41 | LTE B48 | LTE B66 | LTE B71 |         |
|                   |      |           | 0.82       | 4.17     | -1.49    | 0.48    | 1.31    | -0.99   | 2.89    | -4.84   |         |

\* Detail antenna specification please refer to antenna datasheet an antenna gain measurement report.

### 3.2 Configuration of System under Test



Remote site



#### 3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| ID | Product                      | Brand   | Model No.    | Serial No.   | FCC ID | Remarks                  |
|----|------------------------------|---------|--------------|--------------|--------|--------------------------|
| A. | Notebook                     | Getac   | V110G7       | NA           | NA     | Provided by manufacturer |
| B. | Adapter                      | FSP     | FSP065-RBBN3 | NA           | NA     | Provided by manufacturer |
| C. | USB Flash x 3                | SanDisk | SDDDC3-032G  | NA           | NA     | -                        |
| D. | Monitor                      | ASUS    | VA24EHE      | LCLMTF243824 | NA     | -                        |
| E. | Earphone                     | Apple   | MB77PFEB     | NA           | NA     | -                        |
| F. | Load                         | NA      | NA           | NA           | NA     | -                        |
| G. | Radio Communication Analyzer | Anritsu | MT8820C      | 6201300640   | NA     | -                        |

Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item G acted as a communication partner to transfer data.

| ID | Descriptions   | Qty. | Length (m) | Shielding (Yes/No) | Cores (Qty.) | Remarks                                         |
|----|----------------|------|------------|--------------------|--------------|-------------------------------------------------|
| 1. | DC Power Cable | 1    | 1.5        | N                  | 1            | Provided by manufacturer<br>Attached on adapter |
| 2. | HDMI Cable     | 1    | 1.0        | Y                  | 0            | -                                               |
| 3. | Earphone Cable | 1    | 1.5        | N                  | 0            | -                                               |
| 4. | RJ45 Cable     | 1    | 1.5        | N                  | 0            | -                                               |

Note: The core(s) is(are) originally attached to the cable(s).

### 3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, NB mode and tablet mode. The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

| Band         | Radiated Emission |
|--------------|-------------------|
| WCDMA Band 2 | NB mode           |
| LTE Band 2   | NB mode           |
| LTE Band 25  | NB mode           |

#### WCDMA Band 2

| EUT Configure Mode | Test Item                       | Available Channel | Tested Channel                                             | Mode                |
|--------------------|---------------------------------|-------------------|------------------------------------------------------------|---------------------|
| -                  | EIRP                            | 9262 to 9538      | 9262 (1852.4MHz),<br>9400 (1880.0MHz),<br>9538 (1907.6MHz) | WCDMA, HSDPA, HSUPA |
| -                  | Radiated Emission<br>Below 1GHz | 9262 to 9538      | 9262 (1852.4MHz)                                           | WCDMA               |
| -                  | Radiated Emission<br>Above 1GHz | 9262 to 9538      | 9262 (1852.4MHz),<br>9400 (1880.0MHz),<br>9538 (1907.6MHz) | WCDMA               |

Note: For radiated emission below 1GHz, select the worst radiated emission channel (above 1GHz) for final testing.

## LTE Band 2

| EUT<br>Configure<br>Mode | Test item                          | Available channel | Tested Channel                                                | Channel<br>Bandwidth | Modulation              | Mode              |
|--------------------------|------------------------------------|-------------------|---------------------------------------------------------------|----------------------|-------------------------|-------------------|
| -                        | EIRP                               | 18607 to 19193    | 18607 (1850.7MHz),<br>18900 (1880.0MHz),<br>19193 (1909.3MHz) | 1.4MHz               | QPSK / 16QAM /<br>64QAM | 1<br>Half<br>Full |
|                          |                                    | 18615 to 19185    | 18615 (1851.5MHz),<br>18900 (1880.0MHz),<br>19185 (1908.5MHz) | 3MHz                 | QPSK / 16QAM /<br>64QAM | 1<br>Half<br>Full |
|                          |                                    | 18625 to 19175    | 18625 (1852.5MHz),<br>18900 (1880.0MHz),<br>19175 (1907.5MHz) | 5MHz                 | QPSK / 16QAM /<br>64QAM | 1<br>Half<br>Full |
|                          |                                    | 18650 to 19150    | 18650 (1855.0MHz),<br>18900 (1880.0MHz),<br>19150 (1905.0MHz) | 10MHz                | QPSK / 16QAM /<br>64QAM | 1<br>Half<br>Full |
|                          |                                    | 18675 to 19125    | 18675 (1857.5MHz),<br>18900 (1880.0MHz),<br>19125 (1902.5MHz) | 15MHz                | QPSK / 16QAM /<br>64QAM | 1<br>Half<br>Full |
|                          |                                    | 18700 to 19100    | 18700 (1860.0MHz),<br>18900 (1880.0MHz),<br>19100 (1900.0MHz) | 20MHz                | QPSK / 16QAM /<br>64QAM | 1<br>Half<br>Full |
| -                        | Radiated<br>Emission<br>Below 1GHz | 18700 to 19100    | 19100 (1900.0MHz)                                             | 20MHz                | QPSK                    | 1                 |
| -                        | Radiated<br>Emission<br>Above 1GHz | 18607 to 19193    | 18607 (1850.7MHz),<br>18900 (1880.0MHz),<br>19193 (1909.3MHz) | 1.4MHz               | QPSK                    | 1                 |
|                          |                                    | 18625 to 19175    | 18625 (1852.5MHz),<br>18900 (1880.0MHz),<br>19175 (1907.5MHz) | 5MHz                 | QPSK                    | 1                 |
|                          |                                    | 18700 to 19100    | 18700 (1860.0MHz),<br>18900 (1880.0MHz),<br>19100 (1900.0MHz) | 20MHz                | QPSK                    | 1                 |

### Note:

1. This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.
2. For radiated emission below 1GHz, select the worst radiated emission channel (above 1GHz) for final testing.
3. For radiated emission above 1GHz, according to 3GPP 36.521 Section 6.6.3.1.4, choose the lowest, 5MHz & highest channel bandwidth for final test.

# LTE Band 25

| EUT Configure Mode | Test item                    | Available channel | Tested Channel                                                | Channel Bandwidth | Modulation           | Mode              |
|--------------------|------------------------------|-------------------|---------------------------------------------------------------|-------------------|----------------------|-------------------|
| -                  | EIRP                         | 26047 to 26683    | 26047 (1850.7MHz),<br>26365 (1882.5MHz),<br>26683 (1914.3MHz) | 1.4MHz            | QPSK / 16QAM / 64QAM | 1<br>Half<br>Full |
|                    |                              | 26055 to 26675    | 26055 (1851.5MHz),<br>26365 (1882.5MHz),<br>26675 (1913.5MHz) | 3MHz              | QPSK / 16QAM / 64QAM | 1<br>Half<br>Full |
|                    |                              | 26065 to 26665    | 26065 (1852.5MHz),<br>26365 (1882.5MHz),<br>26665 (1912.5MHz) | 5MHz              | QPSK / 16QAM / 64QAM | 1<br>Half<br>Full |
|                    |                              | 26090 to 26640    | 26090 (1855.0MHz),<br>26365 (1882.5MHz),<br>26640 (1910.0MHz) | 10MHz             | QPSK / 16QAM / 64QAM | 1<br>Half<br>Full |
|                    |                              | 26115 to 26615    | 26115 (1857.5MHz),<br>26365 (1882.5MHz),<br>26615 (1907.5MHz) | 15MHz             | QPSK / 16QAM / 64QAM | 1<br>Half<br>Full |
|                    |                              | 26140 to 26590    | 26140 (1860.0MHz),<br>26365 (1882.5MHz),<br>26590 (1905.0MHz) | 20MHz             | QPSK / 16QAM / 64QAM | 1<br>Half<br>Full |
| -                  | Radiated Emission Below 1GHz | 26140 to 26590    | 26365 (1882.5MHz)                                             | 20MHz             | QPSK                 | 1                 |
| -                  | Radiated Emission Above 1GHz | 26047 to 26683    | 26047 (1850.7MHz),<br>26365 (1882.5MHz),<br>26683 (1914.3MHz) | 1.4MHz            | QPSK                 | 1                 |
|                    |                              | 26065 to 26665    | 26065 (1852.5MHz),<br>26365 (1882.5MHz),<br>26665 (1912.5MHz) | 5MHz              | QPSK                 | 1                 |
|                    |                              | 26140 to 26590    | 26140 (1860.0MHz),<br>26365 (1882.5MHz),<br>26590 (1905.0MHz) | 20MHz             | QPSK                 | 1                 |

## Note:

1. This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.
2. For radiated emission below 1GHz, select the worst radiated emission channel (above 1GHz) for final testing.
3. For radiated emission above 1GHz, according to 3GPP 36.521 Section 6.6.3.1.4, choose the lowest, 5MHz & highest channel bandwidth for final test.

## Test Condition:

| Test Item         | Environmental Conditions            | Input Power           | Tested By   |
|-------------------|-------------------------------------|-----------------------|-------------|
| EIRP              | 25deg. C, 60%RH                     | 120Vac, 60Hz (System) | Willy Cheng |
| Radiated Emission | 23deg. C, 68%RH,<br>24deg. C, 68%RH | 120Vac, 60Hz (System) | Luis Lee    |

### **3.4 EUT Operating Conditions**

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

### **3.5 General Description of Applied Standards and References**

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

#### **Test Standard:**

**FCC 47 CFR Part 2**

**FCC 47 CFR Part 24**

**ANSI/TIA/EIA-603-E 2016**

ANSI 63.26-2015

#### **References Test Guidance:**

**KDB 971168 D01 Power Meas License Digital Systems v03r01**

All test items have been performed and recorded as per the above standards.

## 4 Test Types and Results

### 4.1 Output Power Measurement

#### 4.1.1 Limits of Output Power Measurement

Mobile / Portable station are limited to 2 watts e.i.r.p.

#### 4.1.2 Test Procedures

##### Conducted Power Measurement:

The EUT was set up for the maximum power with WCDMA, LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

##### Maximum EIRP / ERP

The relevant equation for determining the maximum ERP or EIRP from the measured RF output power is given in Equation as follows:

$$\text{EIRP} = P_{\text{Meas}} + G_T$$

$$\text{ERP} = P_{\text{Meas}} + G_T - 2.15$$

where

ERP or EIRP effective radiated power or equivalent isotropically radiated power, respectively  
(expressed in the same units as  $P_{\text{Meas}}$ , e.g., dBm or dBW)

$P_{\text{Meas}}$  measured transmitter output power or PSD, in dBm or dBW

$G_T$  gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP)

#### 4.1.3 Test Setup

Conducted Power Measurement:



#### 4.1.4 Test Results

##### Conducted Output Power (dBm)

| Band               | WCDMA II |       |        |
|--------------------|----------|-------|--------|
| TX Channel         | 9262     | 9400  | 9538   |
| Frequency          | 1852.4   | 1880  | 1907.6 |
| RMC 12.2K          | 21.83    | 21.85 | 21.92  |
| HSDPA Subtest-1    | 20.68    | 20.91 | 20.95  |
| HSDPA Subtest-2    | 20.65    | 20.96 | 20.93  |
| HSDPA Subtest-3    | 20.18    | 20.46 | 20.47  |
| HSDPA Subtest-4    | 20.26    | 20.41 | 20.40  |
| DC-HSDPA Subtest-1 | 20.63    | 20.87 | 20.85  |
| DC-HSDPA Subtest-2 | 20.58    | 20.82 | 20.80  |
| DC-HSDPA Subtest-3 | 20.07    | 20.37 | 20.38  |
| DC-HSDPA Subtest-4 | 20.00    | 20.34 | 20.34  |
| HSUPA Subtest-1    | 20.65    | 20.88 | 20.89  |
| HSUPA Subtest-2    | 18.61    | 18.89 | 18.79  |
| HSUPA Subtest-3    | 19.65    | 19.91 | 19.89  |
| HSUPA Subtest-4    | 18.65    | 18.84 | 18.99  |
| HSUPA Subtest-5    | 20.55    | 20.71 | 20.77  |

| LTE Band 2 |           |                 |           |       |              |       |
|------------|-----------|-----------------|-----------|-------|--------------|-------|
| BW         | MCS Index | RB Size         | RB Offset | Low   | Mid          | High  |
|            |           | Channel         |           | 18700 | 18900        | 19100 |
|            |           | Frequency (MHz) |           | 1860  | 1880         | 1900  |
| 20M        | QPSK      | 1               | 0         | 20.78 | <b>20.87</b> | 20.84 |
|            |           | 1               | 50        | 20.72 | 20.84        | 20.76 |
|            |           | 1               | 99        | 20.65 | 20.81        | 20.73 |
|            |           | 50              | 0         | 19.78 | 19.85        | 19.84 |
|            |           | 50              | 25        | 19.67 | 19.84        | 19.76 |
|            |           | 50              | 50        | 19.81 | 19.81        | 19.81 |
|            |           | 100             | 0         | 19.69 | 19.79        | 19.74 |
| 20M        | 16QAM     | 1               | 0         | 19.64 | 19.78        | 19.70 |
|            |           | 1               | 50        | 19.62 | 19.76        | 19.70 |
|            |           | 1               | 99        | 19.64 | 19.75        | 19.66 |
|            |           | 50              | 0         | 18.56 | 18.67        | 18.63 |
|            |           | 50              | 25        | 18.49 | 18.00        | 18.58 |
|            |           | 50              | 50        | 18.46 | 18.64        | 18.51 |
|            |           | 100             | 0         | 18.54 | 18.61        | 18.55 |
| 20M        | 64QAM     | 1               | 0         | 18.45 | 18.55        | 18.48 |
|            |           | 1               | 50        | 18.42 | 18.49        | 18.45 |
|            |           | 1               | 99        | 18.45 | 18.51        | 18.48 |
|            |           | 50              | 0         | 17.70 | 17.88        | 17.79 |
|            |           | 50              | 25        | 17.74 | 17.81        | 17.78 |
|            |           | 50              | 50        | 17.59 | 17.76        | 17.66 |
|            |           | 100             | 0         | 17.65 | 17.75        | 17.69 |

| LTE Band 2 |           |                 |           |        |       |        |
|------------|-----------|-----------------|-----------|--------|-------|--------|
| BW         | MCS Index | RB Size         | RB Offset | Low    | Mid   | High   |
|            |           | Channel         |           | 18675  | 18900 | 19125  |
|            |           | Frequency (MHz) |           | 1857.5 | 1880  | 1902.5 |
| 15M        | QPSK      | 1               | 0         | 20.81  | 20.86 | 20.81  |
|            |           | 1               | 37        | 20.75  | 20.80 | 20.76  |
|            |           | 1               | 74        | 20.71  | 20.79 | 20.76  |
|            |           | 36              | 0         | 19.68  | 19.80 | 19.80  |
|            |           | 36              | 19        | 19.67  | 19.80 | 19.76  |
|            |           | 36              | 39        | 19.73  | 19.73 | 19.74  |
|            |           | 75              | 0         | 19.61  | 19.74 | 19.66  |
| 15M        | 16QAM     | 1               | 0         | 19.62  | 19.69 | 19.64  |
|            |           | 1               | 37        | 19.60  | 19.69 | 19.60  |
|            |           | 1               | 74        | 19.55  | 19.68 | 19.57  |
|            |           | 36              | 0         | 18.37  | 18.57 | 18.45  |
|            |           | 36              | 19        | 18.52  | 18.58 | 18.56  |
|            |           | 36              | 39        | 18.40  | 18.56 | 18.54  |
|            |           | 75              | 0         | 18.46  | 18.60 | 18.54  |
| 15M        | 64QAM     | 1               | 0         | 18.38  | 18.51 | 18.44  |
|            |           | 1               | 37        | 18.35  | 18.46 | 18.43  |
|            |           | 1               | 74        | 18.42  | 18.47 | 18.46  |
|            |           | 36              | 0         | 17.60  | 17.88 | 17.72  |
|            |           | 36              | 19        | 17.70  | 17.74 | 17.73  |
|            |           | 36              | 39        | 17.51  | 17.67 | 17.57  |
|            |           | 75              | 0         | 17.63  | 17.68 | 17.67  |

| LTE Band 2 |           |                 |           |       |       |       |
|------------|-----------|-----------------|-----------|-------|-------|-------|
| BW         | MCS Index | RB Size         | RB Offset | Low   | Mid   | High  |
|            |           | Channel         |           | 18650 | 18900 | 19150 |
|            |           | Frequency (MHz) |           | 1855  | 1880  | 1905  |
| 10M        | QPSK      | 1               | 0         | 20.86 | 20.77 | 20.79 |
|            |           | 1               | 24        | 20.82 | 20.77 | 20.82 |
|            |           | 1               | 49        | 20.78 | 20.74 | 20.77 |
|            |           | 25              | 0         | 19.77 | 19.82 | 19.82 |
|            |           | 25              | 12        | 19.65 | 19.77 | 19.75 |
|            |           | 25              | 25        | 19.76 | 19.75 | 19.79 |
|            |           | 50              | 0         | 19.64 | 19.79 | 19.73 |
| 10M        | 16QAM     | 1               | 0         | 19.61 | 19.69 | 19.62 |
|            |           | 1               | 24        | 19.61 | 19.67 | 19.63 |
|            |           | 1               | 49        | 19.57 | 19.68 | 19.66 |
|            |           | 25              | 0         | 18.36 | 18.52 | 18.41 |
|            |           | 25              | 12        | 18.56 | 18.62 | 18.59 |
|            |           | 25              | 25        | 18.42 | 18.64 | 18.54 |
|            |           | 50              | 0         | 18.49 | 18.51 | 18.47 |
| 10M        | 64QAM     | 1               | 0         | 18.39 | 18.46 | 18.47 |
|            |           | 1               | 24        | 18.39 | 18.41 | 18.39 |
|            |           | 1               | 49        | 18.42 | 18.49 | 18.47 |
|            |           | 25              | 0         | 17.65 | 17.87 | 17.69 |
|            |           | 25              | 12        | 17.68 | 17.74 | 17.69 |
|            |           | 25              | 25        | 17.55 | 17.73 | 17.63 |
|            |           | 50              | 0         | 17.57 | 17.72 | 17.68 |

| LTE Band 2 |           |                 |           |        |       |        |
|------------|-----------|-----------------|-----------|--------|-------|--------|
| BW         | MCS Index | RB Size         | RB Offset | Low    | Mid   | High   |
|            |           | Channel         |           | 18625  | 18900 | 19175  |
|            |           | Frequency (MHz) |           | 1852.5 | 1880  | 1907.5 |
| 5M         | QPSK      | 1               | 0         | 20.85  | 20.77 | 20.76  |
|            |           | 1               | 12        | 20.77  | 20.75 | 20.78  |
|            |           | 1               | 24        | 20.77  | 20.73 | 20.71  |
|            |           | 12              | 0         | 19.71  | 19.82 | 19.80  |
|            |           | 12              | 6         | 19.60  | 19.80 | 19.67  |
|            |           | 12              | 13        | 19.76  | 19.75 | 19.71  |
|            |           | 25              | 0         | 19.67  | 19.76 | 19.73  |
| 5M         | 16QAM     | 1               | 0         | 19.62  | 19.74 | 19.62  |
|            |           | 1               | 12        | 19.52  | 19.72 | 19.64  |
|            |           | 1               | 24        | 19.63  | 19.72 | 19.62  |
|            |           | 12              | 0         | 18.41  | 18.51 | 18.50  |
|            |           | 12              | 6         | 18.52  | 18.66 | 18.61  |
|            |           | 12              | 13        | 18.41  | 18.59 | 18.49  |
|            |           | 25              | 0         | 18.44  | 18.59 | 18.55  |
| 5M         | 64QAM     | 1               | 0         | 18.37  | 18.48 | 18.45  |
|            |           | 1               | 12        | 18.41  | 18.43 | 18.37  |
|            |           | 1               | 24        | 18.39  | 18.43 | 18.45  |
|            |           | 12              | 0         | 17.61  | 17.88 | 17.73  |
|            |           | 12              | 6         | 17.65  | 17.81 | 17.68  |
|            |           | 12              | 13        | 17.52  | 17.71 | 17.66  |
|            |           | 25              | 0         | 17.64  | 17.75 | 17.68  |

| LTE Band 2 |           |                 |           |        |       |        |
|------------|-----------|-----------------|-----------|--------|-------|--------|
| BW         | MCS Index | RB Size         | RB Offset | Low    | Mid   | High   |
|            |           | Channel         |           | 18615  | 18900 | 19185  |
|            |           | Frequency (MHz) |           | 1851.5 | 1880  | 1908.5 |
| 3M         | QPSK      | 1               | 0         | 20.79  | 20.80 | 20.77  |
|            |           | 1               | 7         | 20.79  | 20.76 | 20.82  |
|            |           | 1               | 14        | 20.73  | 20.74 | 20.79  |
|            |           | 8               | 0         | 19.77  | 19.86 | 19.81  |
|            |           | 8               | 3         | 19.63  | 19.81 | 19.73  |
|            |           | 8               | 7         | 19.78  | 19.76 | 19.78  |
|            |           | 15              | 0         | 19.62  | 19.76 | 19.69  |
| 3M         | 16QAM     | 1               | 0         | 19.60  | 19.70 | 19.67  |
|            |           | 1               | 7         | 19.54  | 19.76 | 19.64  |
|            |           | 1               | 14        | 19.64  | 19.75 | 19.56  |
|            |           | 8               | 0         | 18.38  | 18.59 | 18.47  |
|            |           | 8               | 3         | 18.55  | 18.65 | 18.58  |
|            |           | 8               | 7         | 18.48  | 18.60 | 18.48  |
|            |           | 15              | 0         | 18.48  | 18.60 | 18.55  |
| 3M         | 64QAM     | 1               | 0         | 18.38  | 18.52 | 18.47  |
|            |           | 1               | 7         | 18.34  | 18.48 | 18.44  |
|            |           | 1               | 14        | 18.37  | 18.51 | 18.41  |
|            |           | 8               | 0         | 17.60  | 17.78 | 17.78  |
|            |           | 8               | 3         | 17.70  | 17.76 | 17.68  |
|            |           | 8               | 7         | 17.50  | 17.68 | 17.65  |
|            |           | 15              | 0         | 17.59  | 17.68 | 17.69  |

| LTE Band 2 |           |                 |           |        |       |        |
|------------|-----------|-----------------|-----------|--------|-------|--------|
| BW         | MCS Index | RB Size         | RB Offset | Low    | Mid   | High   |
|            |           | Channel         |           | 18607  | 18900 | 19193  |
|            |           | Frequency (MHz) |           | 1850.7 | 1880  | 1909.3 |
| 1.4M       | QPSK      | 1               | 0         | 20.82  | 20.85 | 20.83  |
|            |           | 1               | 2         | 20.78  | 20.75 | 20.79  |
|            |           | 1               | 5         | 20.75  | 20.79 | 20.80  |
|            |           | 3               | 0         | 19.71  | 19.77 | 19.79  |
|            |           | 3               | 1         | 19.67  | 19.80 | 19.74  |
|            |           | 3               | 3         | 19.77  | 19.80 | 19.75  |
|            |           | 6               | 0         | 19.63  | 19.78 | 19.71  |
| 1.4M       | 16QAM     | 1               | 0         | 19.56  | 19.76 | 19.62  |
|            |           | 1               | 2         | 19.62  | 19.71 | 19.67  |
|            |           | 1               | 5         | 19.59  | 19.75 | 19.57  |
|            |           | 3               | 0         | 18.45  | 18.60 | 18.49  |
|            |           | 3               | 1         | 18.51  | 18.63 | 18.61  |
|            |           | 3               | 3         | 18.46  | 18.64 | 18.51  |
|            |           | 6               | 0         | 18.50  | 18.59 | 18.47  |
| 1.4M       | 64QAM     | 1               | 0         | 18.40  | 18.48 | 18.39  |
|            |           | 1               | 2         | 18.37  | 18.44 | 18.34  |
|            |           | 1               | 5         | 18.31  | 18.48 | 18.27  |
|            |           | 3               | 0         | 18.36  | 18.36 | 18.34  |
|            |           | 3               | 1         | 18.23  | 18.31 | 18.21  |
|            |           | 3               | 3         | 18.21  | 18.26 | 18.14  |
|            |           | 6               | 0         | 17.68  | 17.78 | 17.64  |

| LTE Band 25 |           |                 |           |       |              |       |
|-------------|-----------|-----------------|-----------|-------|--------------|-------|
| BW          | MCS Index | RB Size         | RB Offset | Low   | Mid          | High  |
|             |           | Channel         |           | 26140 | 26365        | 26590 |
|             |           | Frequency (MHz) |           | 1860  | 1882.5       | 1905  |
| 20M         | QPSK      | 1               | 0         | 20.97 | <b>20.99</b> | 20.98 |
|             |           | 1               | 50        | 20.95 | 20.96        | 20.95 |
|             |           | 1               | 99        | 20.93 | 20.94        | 20.92 |
|             |           | 50              | 0         | 19.81 | 19.93        | 19.90 |
|             |           | 50              | 25        | 19.76 | 19.89        | 19.83 |
|             |           | 50              | 50        | 19.80 | 19.87        | 19.87 |
|             |           | 100             | 0         | 19.73 | 19.86        | 19.83 |
| 20M         | 16QAM     | 1               | 0         | 19.72 | 19.84        | 19.81 |
|             |           | 1               | 50        | 19.75 | 19.83        | 19.81 |
|             |           | 1               | 99        | 19.66 | 19.81        | 19.71 |
|             |           | 50              | 0         | 18.67 | 18.79        | 18.73 |
|             |           | 50              | 25        | 18.70 | 18.77        | 18.74 |
|             |           | 50              | 50        | 18.74 | 18.75        | 18.75 |
|             |           | 100             | 0         | 18.59 | 18.71        | 18.62 |
| 20M         | 64QAM     | 1               | 0         | 18.64 | 18.78        | 18.69 |
|             |           | 1               | 50        | 18.64 | 18.73        | 18.69 |
|             |           | 1               | 99        | 18.58 | 18.68        | 18.59 |
|             |           | 50              | 0         | 17.77 | 17.85        | 17.85 |
|             |           | 50              | 25        | 17.78 | 17.81        | 17.81 |
|             |           | 50              | 50        | 17.69 | 17.76        | 17.72 |
|             |           | 100             | 0         | 17.71 | 17.79        | 17.73 |

| LTE Band 25 |           |                 |           |        |        |        |
|-------------|-----------|-----------------|-----------|--------|--------|--------|
| BW          | MCS Index | RB Size         | RB Offset | Low    | Mid    | High   |
|             |           | Channel         |           | 26115  | 26365  | 26615  |
|             |           | Frequency (MHz) |           | 1857.5 | 1882.5 | 1907.5 |
| 15M         | QPSK      | 1               | 0         | 20.81  | 20.82  | 20.79  |
|             |           | 1               | 37        | 20.77  | 20.81  | 20.82  |
|             |           | 1               | 74        | 20.82  | 20.80  | 20.82  |
|             |           | 36              | 0         | 19.75  | 19.86  | 19.87  |
|             |           | 36              | 19        | 19.67  | 19.85  | 19.81  |
|             |           | 36              | 39        | 19.71  | 19.80  | 19.85  |
|             |           | 75              | 0         | 19.64  | 19.80  | 19.82  |
| 15M         | 16QAM     | 1               | 0         | 19.67  | 19.78  | 19.72  |
|             |           | 1               | 37        | 19.74  | 19.83  | 19.75  |
|             |           | 1               | 74        | 19.58  | 19.72  | 19.62  |
|             |           | 36              | 0         | 18.64  | 18.69  | 18.69  |
|             |           | 36              | 19        | 18.69  | 18.74  | 18.64  |
|             |           | 36              | 39        | 18.72  | 18.68  | 18.75  |
|             |           | 75              | 0         | 18.55  | 18.65  | 18.61  |
| 15M         | 64QAM     | 1               | 0         | 18.54  | 18.72  | 18.68  |
|             |           | 1               | 37        | 18.59  | 18.69  | 18.68  |
|             |           | 1               | 74        | 18.54  | 18.63  | 18.54  |
|             |           | 36              | 0         | 17.71  | 17.82  | 17.84  |
|             |           | 36              | 19        | 17.76  | 17.74  | 17.73  |
|             |           | 36              | 39        | 17.59  | 17.67  | 17.64  |
|             |           | 75              | 0         | 17.68  | 17.79  | 17.68  |

| LTE Band 25 |           |                 |           |       |        |       |
|-------------|-----------|-----------------|-----------|-------|--------|-------|
| BW          | MCS Index | RB Size         | RB Offset | Low   | Mid    | High  |
|             |           | Channel         |           | 26090 | 26365  | 26640 |
|             |           | Frequency (MHz) |           | 1855  | 1882.5 | 1910  |
| 10M         | QPSK      | 1               | 0         | 20.83 | 20.79  | 20.86 |
|             |           | 1               | 24        | 20.79 | 20.76  | 20.76 |
|             |           | 1               | 49        | 20.80 | 20.78  | 20.75 |
|             |           | 25              | 0         | 19.73 | 19.92  | 19.85 |
|             |           | 25              | 12        | 19.68 | 19.87  | 19.77 |
|             |           | 25              | 25        | 19.77 | 19.80  | 19.80 |
|             |           | 50              | 0         | 19.71 | 19.76  | 19.78 |
| 10M         | 16QAM     | 1               | 0         | 19.67 | 19.77  | 19.76 |
|             |           | 1               | 24        | 19.67 | 19.82  | 19.74 |
|             |           | 1               | 49        | 19.57 | 19.73  | 19.62 |
|             |           | 25              | 0         | 18.63 | 18.77  | 18.69 |
|             |           | 25              | 12        | 18.67 | 18.73  | 18.65 |
|             |           | 25              | 25        | 18.72 | 18.71  | 18.75 |
|             |           | 50              | 0         | 18.57 | 18.68  | 18.61 |
| 10M         | 64QAM     | 1               | 0         | 18.61 | 18.69  | 18.64 |
|             |           | 1               | 24        | 18.59 | 18.67  | 18.65 |
|             |           | 1               | 49        | 18.56 | 18.62  | 18.55 |
|             |           | 25              | 0         | 17.70 | 17.84  | 17.77 |
|             |           | 25              | 12        | 17.73 | 17.80  | 17.75 |
|             |           | 25              | 25        | 17.63 | 17.75  | 17.71 |
|             |           | 50              | 0         | 17.61 | 17.76  | 17.73 |

| LTE Band 25 |           |                 |           |        |        |        |
|-------------|-----------|-----------------|-----------|--------|--------|--------|
| BW          | MCS Index | RB Size         | RB Offset | Low    | Mid    | High   |
|             |           | Channel         |           | 26065  | 26365  | 26665  |
|             |           | Frequency (MHz) |           | 1852.5 | 1882.5 | 1912.5 |
| 5M          | QPSK      | 1               | 0         | 20.84  | 20.84  | 20.81  |
|             |           | 1               | 12        | 20.84  | 20.78  | 20.80  |
|             |           | 1               | 24        | 20.81  | 20.79  | 20.73  |
|             |           | 12              | 0         | 19.71  | 19.86  | 19.86  |
|             |           | 12              | 6         | 19.71  | 19.85  | 19.74  |
|             |           | 12              | 13        | 19.70  | 19.85  | 19.85  |
|             |           | 25              | 0         | 19.63  | 19.81  | 19.80  |
| 5M          | 16QAM     | 1               | 0         | 19.65  | 19.76  | 19.78  |
|             |           | 1               | 12        | 19.71  | 19.76  | 19.73  |
|             |           | 1               | 24        | 19.66  | 19.79  | 19.61  |
|             |           | 12              | 0         | 18.62  | 18.77  | 18.69  |
|             |           | 12              | 6         | 18.63  | 18.70  | 18.69  |
|             |           | 12              | 13        | 18.70  | 18.69  | 18.66  |
|             |           | 25              | 0         | 18.49  | 18.67  | 18.59  |
| 5M          | 64QAM     | 1               | 0         | 18.59  | 18.74  | 18.60  |
|             |           | 1               | 12        | 18.64  | 18.69  | 18.61  |
|             |           | 1               | 24        | 18.53  | 18.61  | 18.55  |
|             |           | 12              | 0         | 17.71  | 17.83  | 17.78  |
|             |           | 12              | 6         | 17.77  | 17.71  | 17.80  |
|             |           | 12              | 13        | 17.67  | 17.70  | 17.65  |
|             |           | 25              | 0         | 17.67  | 17.69  | 17.71  |

| LTE Band 25 |           |                 |           |        |        |        |
|-------------|-----------|-----------------|-----------|--------|--------|--------|
| BW          | MCS Index | RB Size         | RB Offset | Low    | Mid    | High   |
|             |           | Channel         |           | 26055  | 26365  | 26675  |
|             |           | Frequency (MHz) |           | 1851.5 | 1882.5 | 1913.5 |
| 3M          | QPSK      | 1               | 0         | 20.80  | 20.87  | 20.83  |
|             |           | 1               | 7         | 20.85  | 20.81  | 20.84  |
|             |           | 1               | 14        | 20.81  | 20.83  | 20.77  |
|             |           | 8               | 0         | 19.81  | 19.93  | 19.82  |
|             |           | 8               | 3         | 19.68  | 19.87  | 19.77  |
|             |           | 8               | 7         | 19.78  | 19.77  | 19.82  |
|             |           | 15              | 0         | 19.67  | 19.77  | 19.78  |
| 3M          | 16QAM     | 1               | 0         | 19.66  | 19.81  | 19.71  |
|             |           | 1               | 7         | 19.73  | 19.75  | 19.72  |
|             |           | 1               | 14        | 19.60  | 19.74  | 19.63  |
|             |           | 8               | 0         | 18.65  | 18.79  | 18.65  |
|             |           | 8               | 3         | 18.62  | 18.72  | 18.68  |
|             |           | 8               | 7         | 18.67  | 18.75  | 18.73  |
|             |           | 15              | 0         | 18.53  | 18.69  | 18.59  |
| 3M          | 64QAM     | 1               | 0         | 18.63  | 18.75  | 18.60  |
|             |           | 1               | 7         | 18.55  | 18.66  | 18.67  |
|             |           | 1               | 14        | 18.58  | 18.61  | 18.59  |
|             |           | 8               | 0         | 17.69  | 17.75  | 17.85  |
|             |           | 8               | 3         | 17.74  | 17.74  | 17.72  |
|             |           | 8               | 7         | 17.66  | 17.76  | 17.67  |
|             |           | 15              | 0         | 17.69  | 17.73  | 17.67  |

| LTE Band 25 |           |                 |           |        |        |        |
|-------------|-----------|-----------------|-----------|--------|--------|--------|
| BW          | MCS Index | RB Size         | RB Offset | Low    | Mid    | High   |
|             |           | Channel         |           | 26047  | 26365  | 26683  |
|             |           | Frequency (MHz) |           | 1850.7 | 1882.5 | 1914.3 |
| 1.4M        | QPSK      | 1               | 0         | 20.78  | 20.89  | 20.85  |
|             |           | 1               | 2         | 20.79  | 20.82  | 20.79  |
|             |           | 1               | 5         | 20.82  | 20.83  | 20.77  |
|             |           | 3               | 0         | 19.74  | 19.90  | 19.89  |
|             |           | 3               | 1         | 19.67  | 19.85  | 19.83  |
|             |           | 3               | 3         | 19.70  | 19.77  | 19.85  |
|             |           | 6               | 0         | 19.65  | 19.76  | 19.74  |
| 1.4M        | 16QAM     | 1               | 0         | 19.69  | 19.78  | 19.75  |
|             |           | 1               | 2         | 19.74  | 19.74  | 19.76  |
|             |           | 1               | 5         | 19.63  | 19.71  | 19.61  |
|             |           | 3               | 0         | 18.64  | 18.76  | 18.67  |
|             |           | 3               | 1         | 18.70  | 18.67  | 18.68  |
|             |           | 3               | 3         | 18.65  | 18.61  | 18.74  |
|             |           | 6               | 0         | 18.55  | 18.58  | 18.53  |
| 1.4M        | 64QAM     | 1               | 0         | 18.64  | 18.74  | 18.68  |
|             |           | 1               | 2         | 18.55  | 18.68  | 18.61  |
|             |           | 1               | 5         | 18.54  | 18.63  | 18.60  |
|             |           | 3               | 0         | 18.59  | 18.66  | 18.66  |
|             |           | 3               | 1         | 18.55  | 18.60  | 18.60  |
|             |           | 3               | 3         | 18.43  | 18.56  | 18.52  |
|             |           | 6               | 0         | 17.70  | 17.78  | 17.73  |

**EIRP Power (dBm)**

| Band               | WCDMA II |       |        |
|--------------------|----------|-------|--------|
| TX Channel         | 9262     | 9400  | 9538   |
| Frequency          | 1852.4   | 1880  | 1907.6 |
| RMC 12.2K          | 24.31    | 24.33 | 24.40  |
| HSDPA Subtest-1    | 23.16    | 23.39 | 23.43  |
| HSDPA Subtest-2    | 23.13    | 23.44 | 23.41  |
| HSDPA Subtest-3    | 22.66    | 22.94 | 22.95  |
| HSDPA Subtest-4    | 22.74    | 22.89 | 22.88  |
| DC-HSDPA Subtest-1 | 23.11    | 23.35 | 23.33  |
| DC-HSDPA Subtest-2 | 23.06    | 23.30 | 23.28  |
| DC-HSDPA Subtest-3 | 22.55    | 22.85 | 22.86  |
| DC-HSDPA Subtest-4 | 22.48    | 22.82 | 22.82  |
| HSUPA Subtest-1    | 23.13    | 23.36 | 23.37  |
| HSUPA Subtest-2    | 21.09    | 21.37 | 21.27  |
| HSUPA Subtest-3    | 22.13    | 22.39 | 22.37  |
| HSUPA Subtest-4    | 21.13    | 21.32 | 21.47  |
| HSUPA Subtest-5    | 23.03    | 23.19 | 23.25  |

\*EIRP (dBm) = Conducted Output Power (dBm) + Antenna Gain (dBi)

| LTE Band 2 |           |                 |           |       |       |       |
|------------|-----------|-----------------|-----------|-------|-------|-------|
| BW         | MCS Index | RB Size         | RB Offset | Low   | Mid   | High  |
|            |           | Channel         |           | 18700 | 18900 | 19100 |
|            |           | Frequency (MHz) |           | 1860  | 1880  | 1900  |
| 20M        | QPSK      | 1               | 0         | 23.26 | 23.35 | 23.32 |
|            |           | 1               | 50        | 23.20 | 23.32 | 23.24 |
|            |           | 1               | 99        | 23.13 | 23.29 | 23.21 |
|            |           | 50              | 0         | 22.26 | 22.33 | 22.32 |
|            |           | 50              | 25        | 22.15 | 22.32 | 22.24 |
|            |           | 50              | 50        | 22.29 | 22.29 | 22.29 |
|            |           | 100             | 0         | 22.17 | 22.27 | 22.22 |
| 20M        | 16QAM     | 1               | 0         | 22.12 | 22.26 | 22.18 |
|            |           | 1               | 50        | 22.10 | 22.24 | 22.18 |
|            |           | 1               | 99        | 22.12 | 22.23 | 22.14 |
|            |           | 50              | 0         | 21.04 | 21.15 | 21.11 |
|            |           | 50              | 25        | 20.97 | 20.48 | 21.06 |
|            |           | 50              | 50        | 20.94 | 21.12 | 20.99 |
|            |           | 100             | 0         | 21.02 | 21.09 | 21.03 |
| 20M        | 64QAM     | 1               | 0         | 20.93 | 21.03 | 20.96 |
|            |           | 1               | 50        | 20.90 | 20.97 | 20.93 |
|            |           | 1               | 99        | 20.93 | 20.99 | 20.96 |
|            |           | 50              | 0         | 20.18 | 20.36 | 20.27 |
|            |           | 50              | 25        | 20.22 | 20.29 | 20.26 |
|            |           | 50              | 50        | 20.07 | 20.24 | 20.14 |
|            |           | 100             | 0         | 20.13 | 20.23 | 20.17 |

\*EIRP (dBm) = Conducted Output Power (dBm) + Antenna Gain (dBi)

| LTE Band 2 |           |                 |           |        |       |        |
|------------|-----------|-----------------|-----------|--------|-------|--------|
| BW         | MCS Index | RB Size         | RB Offset | Low    | Mid   | High   |
|            |           | Channel         |           | 18675  | 18900 | 19125  |
|            |           | Frequency (MHz) |           | 1857.5 | 1880  | 1902.5 |
| 15M        | QPSK      | 1               | 0         | 23.29  | 23.34 | 23.29  |
|            |           | 1               | 37        | 23.23  | 23.28 | 23.24  |
|            |           | 1               | 74        | 23.19  | 23.27 | 23.24  |
|            |           | 36              | 0         | 22.16  | 22.28 | 22.28  |
|            |           | 36              | 19        | 22.15  | 22.28 | 22.24  |
|            |           | 36              | 39        | 22.21  | 22.21 | 22.22  |
|            |           | 75              | 0         | 22.09  | 22.22 | 22.14  |
| 15M        | 16QAM     | 1               | 0         | 22.10  | 22.17 | 22.12  |
|            |           | 1               | 37        | 22.08  | 22.17 | 22.08  |
|            |           | 1               | 74        | 22.03  | 22.16 | 22.05  |
|            |           | 36              | 0         | 20.85  | 21.05 | 20.93  |
|            |           | 36              | 19        | 21.00  | 21.06 | 21.04  |
|            |           | 36              | 39        | 20.88  | 21.04 | 21.02  |
|            |           | 75              | 0         | 20.94  | 21.08 | 21.02  |
| 15M        | 64QAM     | 1               | 0         | 20.86  | 20.99 | 20.92  |
|            |           | 1               | 37        | 20.83  | 20.94 | 20.91  |
|            |           | 1               | 74        | 20.90  | 20.95 | 20.94  |
|            |           | 36              | 0         | 20.08  | 20.36 | 20.20  |
|            |           | 36              | 19        | 20.18  | 20.22 | 20.21  |
|            |           | 36              | 39        | 19.99  | 20.15 | 20.05  |
|            |           | 75              | 0         | 20.11  | 20.16 | 20.15  |

\*EIRP (dBm) = Conducted Output Power (dBm) + Antenna Gain (dBi)

| LTE Band 2 |           |                 |           |       |       |       |
|------------|-----------|-----------------|-----------|-------|-------|-------|
| BW         | MCS Index | RB Size         | RB Offset | Low   | Mid   | High  |
|            |           | Channel         |           | 18650 | 18900 | 19150 |
|            |           | Frequency (MHz) |           | 1855  | 1880  | 1905  |
| 10M        | QPSK      | 1               | 0         | 23.34 | 23.25 | 23.27 |
|            |           | 1               | 24        | 23.30 | 23.25 | 23.30 |
|            |           | 1               | 49        | 23.26 | 23.22 | 23.25 |
|            |           | 25              | 0         | 22.25 | 22.30 | 22.30 |
|            |           | 25              | 12        | 22.13 | 22.25 | 22.23 |
|            |           | 25              | 25        | 22.24 | 22.23 | 22.27 |
|            |           | 50              | 0         | 22.12 | 22.27 | 22.21 |
| 10M        | 16QAM     | 1               | 0         | 22.09 | 22.17 | 22.10 |
|            |           | 1               | 24        | 22.09 | 22.15 | 22.11 |
|            |           | 1               | 49        | 22.05 | 22.16 | 22.14 |
|            |           | 25              | 0         | 20.84 | 21.00 | 20.89 |
|            |           | 25              | 12        | 21.04 | 21.10 | 21.07 |
|            |           | 25              | 25        | 20.90 | 21.12 | 21.02 |
|            |           | 50              | 0         | 20.97 | 20.99 | 20.95 |
| 10M        | 64QAM     | 1               | 0         | 20.87 | 20.94 | 20.95 |
|            |           | 1               | 24        | 20.87 | 20.89 | 20.87 |
|            |           | 1               | 49        | 20.90 | 20.97 | 20.95 |
|            |           | 25              | 0         | 20.13 | 20.35 | 20.17 |
|            |           | 25              | 12        | 20.16 | 20.22 | 20.17 |
|            |           | 25              | 25        | 20.03 | 20.21 | 20.11 |
|            |           | 50              | 0         | 20.05 | 20.20 | 20.16 |

\*EIRP (dBm) = Conducted Output Power (dBm) + Antenna Gain (dBi)

| LTE Band 2 |           |                 |           |        |       |        |
|------------|-----------|-----------------|-----------|--------|-------|--------|
| BW         | MCS Index | RB Size         | RB Offset | Low    | Mid   | High   |
|            |           | Channel         |           | 18625  | 18900 | 19175  |
|            |           | Frequency (MHz) |           | 1852.5 | 1880  | 1907.5 |
| 5M         | QPSK      | 1               | 0         | 23.33  | 23.25 | 23.24  |
|            |           | 1               | 12        | 23.25  | 23.23 | 23.26  |
|            |           | 1               | 24        | 23.25  | 23.21 | 23.19  |
|            |           | 12              | 0         | 22.19  | 22.30 | 22.28  |
|            |           | 12              | 6         | 22.08  | 22.28 | 22.15  |
|            |           | 12              | 13        | 22.24  | 22.23 | 22.19  |
|            |           | 25              | 0         | 22.15  | 22.24 | 22.21  |
| 5M         | 16QAM     | 1               | 0         | 22.10  | 22.22 | 22.10  |
|            |           | 1               | 12        | 22.00  | 22.20 | 22.12  |
|            |           | 1               | 24        | 22.11  | 22.20 | 22.10  |
|            |           | 12              | 0         | 20.89  | 20.99 | 20.98  |
|            |           | 12              | 6         | 21.00  | 21.14 | 21.09  |
|            |           | 12              | 13        | 20.89  | 21.07 | 20.97  |
|            |           | 25              | 0         | 20.92  | 21.07 | 21.03  |
| 5M         | 64QAM     | 1               | 0         | 20.85  | 20.96 | 20.93  |
|            |           | 1               | 12        | 20.89  | 20.91 | 20.85  |
|            |           | 1               | 24        | 20.87  | 20.91 | 20.93  |
|            |           | 12              | 0         | 20.09  | 20.36 | 20.21  |
|            |           | 12              | 6         | 20.13  | 20.29 | 20.16  |
|            |           | 12              | 13        | 20.00  | 20.19 | 20.14  |
|            |           | 25              | 0         | 20.12  | 20.23 | 20.16  |

\*EIRP (dBm) = Conducted Output Power (dBm) + Antenna Gain (dBi)

| LTE Band 2 |           |                 |           |        |       |        |
|------------|-----------|-----------------|-----------|--------|-------|--------|
| BW         | MCS Index | RB Size         | RB Offset | Low    | Mid   | High   |
|            |           | Channel         |           | 18615  | 18900 | 19185  |
|            |           | Frequency (MHz) |           | 1851.5 | 1880  | 1908.5 |
| 3M         | QPSK      | 1               | 0         | 23.27  | 23.28 | 23.25  |
|            |           | 1               | 7         | 23.27  | 23.24 | 23.30  |
|            |           | 1               | 14        | 23.21  | 23.22 | 23.27  |
|            |           | 8               | 0         | 22.25  | 22.34 | 22.29  |
|            |           | 8               | 3         | 22.11  | 22.29 | 22.21  |
|            |           | 8               | 7         | 22.26  | 22.24 | 22.26  |
|            |           | 15              | 0         | 22.10  | 22.24 | 22.17  |
| 3M         | 16QAM     | 1               | 0         | 22.08  | 22.18 | 22.15  |
|            |           | 1               | 7         | 22.02  | 22.24 | 22.12  |
|            |           | 1               | 14        | 22.12  | 22.23 | 22.04  |
|            |           | 8               | 0         | 20.86  | 21.07 | 20.95  |
|            |           | 8               | 3         | 21.03  | 21.13 | 21.06  |
|            |           | 8               | 7         | 20.96  | 21.08 | 20.96  |
|            |           | 15              | 0         | 20.96  | 21.08 | 21.03  |
| 3M         | 64QAM     | 1               | 0         | 20.86  | 21.00 | 20.95  |
|            |           | 1               | 7         | 20.82  | 20.96 | 20.92  |
|            |           | 1               | 14        | 20.85  | 20.99 | 20.89  |
|            |           | 8               | 0         | 20.08  | 20.26 | 20.26  |
|            |           | 8               | 3         | 20.18  | 20.24 | 20.16  |
|            |           | 8               | 7         | 19.98  | 20.16 | 20.13  |
|            |           | 15              | 0         | 20.07  | 20.16 | 20.17  |

\*EIRP (dBm) = Conducted Output Power (dBm) + Antenna Gain (dBi)

| LTE Band 2 |           |                 |           |        |       |        |
|------------|-----------|-----------------|-----------|--------|-------|--------|
| BW         | MCS Index | RB Size         | RB Offset | Low    | Mid   | High   |
|            |           | Channel         |           | 18607  | 18900 | 19193  |
|            |           | Frequency (MHz) |           | 1850.7 | 1880  | 1909.3 |
| 1.4M       | QPSK      | 1               | 0         | 23.30  | 23.33 | 23.31  |
|            |           | 1               | 2         | 23.26  | 23.23 | 23.27  |
|            |           | 1               | 5         | 23.23  | 23.27 | 23.28  |
|            |           | 3               | 0         | 22.19  | 22.25 | 22.27  |
|            |           | 3               | 1         | 22.15  | 22.28 | 22.22  |
|            |           | 3               | 3         | 22.25  | 22.28 | 22.23  |
|            |           | 6               | 0         | 22.11  | 22.26 | 22.19  |
| 1.4M       | 16QAM     | 1               | 0         | 22.04  | 22.24 | 22.10  |
|            |           | 1               | 2         | 22.10  | 22.19 | 22.15  |
|            |           | 1               | 5         | 22.07  | 22.23 | 22.05  |
|            |           | 3               | 0         | 20.93  | 21.08 | 20.97  |
|            |           | 3               | 1         | 20.99  | 21.11 | 21.09  |
|            |           | 3               | 3         | 20.94  | 21.12 | 20.99  |
|            |           | 6               | 0         | 20.98  | 21.07 | 20.95  |
| 1.4M       | 64QAM     | 1               | 0         | 20.88  | 20.96 | 20.87  |
|            |           | 1               | 2         | 20.85  | 20.92 | 20.82  |
|            |           | 1               | 5         | 20.79  | 20.96 | 20.75  |
|            |           | 3               | 0         | 20.84  | 20.84 | 20.82  |
|            |           | 3               | 1         | 20.71  | 20.79 | 20.69  |
|            |           | 3               | 3         | 20.69  | 20.74 | 20.62  |
|            |           | 6               | 0         | 20.16  | 20.26 | 20.12  |

\*EIRP (dBm) = Conducted Output Power (dBm) + Antenna Gain (dBi)

| LTE Band 25 |           |                 |           |       |        |       |
|-------------|-----------|-----------------|-----------|-------|--------|-------|
| BW          | MCS Index | RB Size         | RB Offset | Low   | Mid    | High  |
|             |           | Channel         |           | 26140 | 26365  | 26590 |
|             |           | Frequency (MHz) |           | 1860  | 1882.5 | 1905  |
| 20M         | QPSK      | 1               | 0         | 23.45 | 23.47  | 23.46 |
|             |           | 1               | 50        | 23.43 | 23.44  | 23.43 |
|             |           | 1               | 99        | 23.41 | 23.42  | 23.40 |
|             |           | 50              | 0         | 22.29 | 22.41  | 22.38 |
|             |           | 50              | 25        | 22.24 | 22.37  | 22.31 |
|             |           | 50              | 50        | 22.28 | 22.35  | 22.35 |
|             |           | 100             | 0         | 22.21 | 22.34  | 22.31 |
| 20M         | 16QAM     | 1               | 0         | 22.20 | 22.32  | 22.29 |
|             |           | 1               | 50        | 22.23 | 22.31  | 22.29 |
|             |           | 1               | 99        | 22.14 | 22.29  | 22.19 |
|             |           | 50              | 0         | 21.15 | 21.27  | 21.21 |
|             |           | 50              | 25        | 21.18 | 21.25  | 21.22 |
|             |           | 50              | 50        | 21.22 | 21.23  | 21.23 |
|             |           | 100             | 0         | 21.07 | 21.19  | 21.10 |
| 20M         | 64QAM     | 1               | 0         | 21.12 | 21.26  | 21.17 |
|             |           | 1               | 50        | 21.12 | 21.21  | 21.17 |
|             |           | 1               | 99        | 21.06 | 21.16  | 21.07 |
|             |           | 50              | 0         | 20.25 | 20.33  | 20.33 |
|             |           | 50              | 25        | 20.26 | 20.29  | 20.29 |
|             |           | 50              | 50        | 20.17 | 20.24  | 20.20 |
|             |           | 100             | 0         | 20.19 | 20.27  | 20.21 |

\*EIRP (dBm) = Conducted Output Power (dBm) + Antenna Gain (dBi)

| LTE Band 25 |           |                 |           |        |        |        |
|-------------|-----------|-----------------|-----------|--------|--------|--------|
| BW          | MCS Index | RB Size         | RB Offset | Low    | Mid    | High   |
|             |           | Channel         |           | 26115  | 26365  | 26615  |
|             |           | Frequency (MHz) |           | 1857.5 | 1882.5 | 1907.5 |
| 15M         | QPSK      | 1               | 0         | 23.29  | 23.30  | 23.27  |
|             |           | 1               | 37        | 23.25  | 23.29  | 23.30  |
|             |           | 1               | 74        | 23.30  | 23.28  | 23.30  |
|             |           | 36              | 0         | 22.23  | 22.34  | 22.35  |
|             |           | 36              | 19        | 22.15  | 22.33  | 22.29  |
|             |           | 36              | 39        | 22.19  | 22.28  | 22.33  |
|             |           | 75              | 0         | 22.12  | 22.28  | 22.30  |
| 15M         | 16QAM     | 1               | 0         | 22.15  | 22.26  | 22.20  |
|             |           | 1               | 37        | 22.22  | 22.31  | 22.23  |
|             |           | 1               | 74        | 22.06  | 22.20  | 22.10  |
|             |           | 36              | 0         | 21.12  | 21.17  | 21.17  |
|             |           | 36              | 19        | 21.17  | 21.22  | 21.12  |
|             |           | 36              | 39        | 21.20  | 21.16  | 21.23  |
|             |           | 75              | 0         | 21.03  | 21.13  | 21.09  |
| 15M         | 64QAM     | 1               | 0         | 21.02  | 21.20  | 21.16  |
|             |           | 1               | 37        | 21.07  | 21.17  | 21.16  |
|             |           | 1               | 74        | 21.02  | 21.11  | 21.02  |
|             |           | 36              | 0         | 20.19  | 20.30  | 20.32  |
|             |           | 36              | 19        | 20.24  | 20.22  | 20.21  |
|             |           | 36              | 39        | 20.07  | 20.15  | 20.12  |
|             |           | 75              | 0         | 20.16  | 20.27  | 20.16  |

\*EIRP (dBm) = Conducted Output Power (dBm) + Antenna Gain (dBi)

| LTE Band 25 |           |                 |           |       |        |       |
|-------------|-----------|-----------------|-----------|-------|--------|-------|
| BW          | MCS Index | RB Size         | RB Offset | Low   | Mid    | High  |
|             |           | Channel         |           | 26090 | 26365  | 26640 |
|             |           | Frequency (MHz) |           | 1855  | 1882.5 | 1910  |
| 10M         | QPSK      | 1               | 0         | 23.31 | 23.27  | 23.34 |
|             |           | 1               | 24        | 23.27 | 23.24  | 23.24 |
|             |           | 1               | 49        | 23.28 | 23.26  | 23.23 |
|             |           | 25              | 0         | 22.21 | 22.40  | 22.33 |
|             |           | 25              | 12        | 22.16 | 22.35  | 22.25 |
|             |           | 25              | 25        | 22.25 | 22.28  | 22.28 |
|             |           | 50              | 0         | 22.19 | 22.24  | 22.26 |
| 10M         | 16QAM     | 1               | 0         | 22.15 | 22.25  | 22.24 |
|             |           | 1               | 24        | 22.15 | 22.30  | 22.22 |
|             |           | 1               | 49        | 22.05 | 22.21  | 22.10 |
|             |           | 25              | 0         | 21.11 | 21.25  | 21.17 |
|             |           | 25              | 12        | 21.15 | 21.21  | 21.13 |
|             |           | 25              | 25        | 21.20 | 21.19  | 21.23 |
|             |           | 50              | 0         | 21.05 | 21.16  | 21.09 |
| 10M         | 64QAM     | 1               | 0         | 21.09 | 21.17  | 21.12 |
|             |           | 1               | 24        | 21.07 | 21.15  | 21.13 |
|             |           | 1               | 49        | 21.04 | 21.10  | 21.03 |
|             |           | 25              | 0         | 20.18 | 20.32  | 20.25 |
|             |           | 25              | 12        | 20.21 | 20.28  | 20.23 |
|             |           | 25              | 25        | 20.11 | 20.23  | 20.19 |
|             |           | 50              | 0         | 20.09 | 20.24  | 20.21 |

\*EIRP (dBm) = Conducted Output Power (dBm) + Antenna Gain (dBi)

| LTE Band 25 |           |                 |           |        |        |        |
|-------------|-----------|-----------------|-----------|--------|--------|--------|
| BW          | MCS Index | RB Size         | RB Offset | Low    | Mid    | High   |
|             |           | Channel         |           | 26065  | 26365  | 26665  |
|             |           | Frequency (MHz) |           | 1852.5 | 1882.5 | 1912.5 |
| 5M          | QPSK      | 1               | 0         | 23.32  | 23.32  | 23.29  |
|             |           | 1               | 12        | 23.32  | 23.26  | 23.28  |
|             |           | 1               | 24        | 23.29  | 23.27  | 23.21  |
|             |           | 12              | 0         | 22.19  | 22.34  | 22.34  |
|             |           | 12              | 6         | 22.19  | 22.33  | 22.22  |
|             |           | 12              | 13        | 22.18  | 22.33  | 22.33  |
|             |           | 25              | 0         | 22.11  | 22.29  | 22.28  |
| 5M          | 16QAM     | 1               | 0         | 22.13  | 22.24  | 22.26  |
|             |           | 1               | 12        | 22.19  | 22.24  | 22.21  |
|             |           | 1               | 24        | 22.14  | 22.27  | 22.09  |
|             |           | 12              | 0         | 21.10  | 21.25  | 21.17  |
|             |           | 12              | 6         | 21.11  | 21.18  | 21.17  |
|             |           | 12              | 13        | 21.18  | 21.17  | 21.14  |
|             |           | 25              | 0         | 20.97  | 21.15  | 21.07  |
| 5M          | 64QAM     | 1               | 0         | 21.07  | 21.22  | 21.08  |
|             |           | 1               | 12        | 21.12  | 21.17  | 21.09  |
|             |           | 1               | 24        | 21.01  | 21.09  | 21.03  |
|             |           | 12              | 0         | 20.19  | 20.31  | 20.26  |
|             |           | 12              | 6         | 20.25  | 20.19  | 20.28  |
|             |           | 12              | 13        | 20.15  | 20.18  | 20.13  |
|             |           | 25              | 0         | 20.15  | 20.17  | 20.19  |

\*EIRP (dBm) = Conducted Output Power (dBm) + Antenna Gain (dBi)

| LTE Band 25 |           |                 |           |        |        |        |
|-------------|-----------|-----------------|-----------|--------|--------|--------|
| BW          | MCS Index | RB Size         | RB Offset | Low    | Mid    | High   |
|             |           | Channel         |           | 26055  | 26365  | 26675  |
|             |           | Frequency (MHz) |           | 1851.5 | 1882.5 | 1913.5 |
| 3M          | QPSK      | 1               | 0         | 23.28  | 23.35  | 23.31  |
|             |           | 1               | 7         | 23.33  | 23.29  | 23.32  |
|             |           | 1               | 14        | 23.29  | 23.31  | 23.25  |
|             |           | 8               | 0         | 22.29  | 22.41  | 22.30  |
|             |           | 8               | 3         | 22.16  | 22.35  | 22.25  |
|             |           | 8               | 7         | 22.26  | 22.25  | 22.30  |
|             |           | 15              | 0         | 22.15  | 22.25  | 22.26  |
| 3M          | 16QAM     | 1               | 0         | 22.14  | 22.29  | 22.19  |
|             |           | 1               | 7         | 22.21  | 22.23  | 22.20  |
|             |           | 1               | 14        | 22.08  | 22.22  | 22.11  |
|             |           | 8               | 0         | 21.13  | 21.27  | 21.13  |
|             |           | 8               | 3         | 21.10  | 21.20  | 21.16  |
|             |           | 8               | 7         | 21.15  | 21.23  | 21.21  |
|             |           | 15              | 0         | 21.01  | 21.17  | 21.07  |
| 3M          | 64QAM     | 1               | 0         | 21.11  | 21.23  | 21.08  |
|             |           | 1               | 7         | 21.03  | 21.14  | 21.15  |
|             |           | 1               | 14        | 21.06  | 21.09  | 21.07  |
|             |           | 8               | 0         | 20.17  | 20.23  | 20.33  |
|             |           | 8               | 3         | 20.22  | 20.22  | 20.20  |
|             |           | 8               | 7         | 20.14  | 20.24  | 20.15  |
|             |           | 15              | 0         | 20.17  | 20.21  | 20.15  |

\*EIRP (dBm) = Conducted Output Power (dBm) + Antenna Gain (dBi)

| LTE Band 25 |           |                 |           |        |        |        |
|-------------|-----------|-----------------|-----------|--------|--------|--------|
| BW          | MCS Index | RB Size         | RB Offset | Low    | Mid    | High   |
|             |           | Channel         |           | 26047  | 26365  | 26683  |
|             |           | Frequency (MHz) |           | 1850.7 | 1882.5 | 1914.3 |
| 1.4M        | QPSK      | 1               | 0         | 23.26  | 23.37  | 23.33  |
|             |           | 1               | 2         | 23.27  | 23.30  | 23.27  |
|             |           | 1               | 5         | 23.30  | 23.31  | 23.25  |
|             |           | 3               | 0         | 22.22  | 22.38  | 22.37  |
|             |           | 3               | 1         | 22.15  | 22.33  | 22.31  |
|             |           | 3               | 3         | 22.18  | 22.25  | 22.33  |
|             |           | 6               | 0         | 22.13  | 22.24  | 22.22  |
| 1.4M        | 16QAM     | 1               | 0         | 22.17  | 22.26  | 22.23  |
|             |           | 1               | 2         | 22.22  | 22.22  | 22.24  |
|             |           | 1               | 5         | 22.11  | 22.19  | 22.09  |
|             |           | 3               | 0         | 21.12  | 21.24  | 21.15  |
|             |           | 3               | 1         | 21.18  | 21.15  | 21.16  |
|             |           | 3               | 3         | 21.13  | 21.09  | 21.22  |
|             |           | 6               | 0         | 21.03  | 21.06  | 21.01  |
| 1.4M        | 64QAM     | 1               | 0         | 21.12  | 21.22  | 21.16  |
|             |           | 1               | 2         | 21.03  | 21.16  | 21.09  |
|             |           | 1               | 5         | 21.02  | 21.11  | 21.08  |
|             |           | 3               | 0         | 21.07  | 21.14  | 21.14  |
|             |           | 3               | 1         | 21.03  | 21.08  | 21.08  |
|             |           | 3               | 3         | 20.91  | 21.04  | 21.00  |
|             |           | 6               | 0         | 20.18  | 20.26  | 20.21  |

\*EIRP (dBm) = Conducted Output Power (dBm) + Antenna Gain (dBi)

## 4.2 Radiated Emission Measurement

### 4.2.1 Limits of Radiated Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. The emission limit equal to  $-13\text{dBm}$ .

### 4.2.2 Test Procedure

- a. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- c. Perform a field strength measurement and record the worse read value, is the field strength value via a spectrum reading obtained corrected for antenna factor, cable loss and pre-amplifier factor and then mathematically convert the measured field strength level to EIRP/ERP level.
- d. Following C63.26 section 5.5 and 5.2.7.  
 $\text{EIRP (dBm)} = E (\text{dB}\mu\text{V/m}) + 20\log(D) - 104.8$ ; where D is the measurement distance (in the far field region) in m.  
 $\text{ERP (dBm)} = E (\text{dB}\mu\text{V/m}) + 20\log(D) - 104.8 - 2.15$ ; where D is the measurement distance (in the far field region) in m.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.
2. The emission levels were against the limit of frequency range 9 kHz ~ 30 MHz:  
The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

### 4.2.3 Deviation from Test Standard


No deviation.

#### 4.2.4 Test Setup

For radiated emission 30MHz to 1GHz



For radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.5 Test Results

Below 1GHz


WCDMA Band 2

|                          |                                |                 |                       |
|--------------------------|--------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 9262<br>(1852.4MHz) | Frequency Range | Below 1000 MHz        |
| Environmental Conditions | 23deg. C, 68%RH                | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                       |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |            |             |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|------------|-------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 185.20          | -58.17     | -13.00      | -45.17      | 1.00 H             | 175                  | 47.66            | -105.83                  |
| 2                                                    | 377.26          | -60.99     | -13.00      | -47.99      | 1.49 H             | 40                   | 40.37            | -101.36                  |
| 3                                                    | 421.88          | -59.04     | -13.00      | -46.04      | 1.00 H             | 167                  | 41.56            | -100.60                  |
| 4                                                    | 513.06          | -51.81     | -13.00      | -38.81      | 1.49 H             | 323                  | 47.42            | -99.23                   |
| 5                                                    | 559.62          | -45.27     | -13.00      | -32.27      | 1.49 H             | 144                  | 53.19            | -98.46                   |
| 6                                                    | 662.44          | -56.37     | -13.00      | -43.37      | 1.00 H             | 6                    | 39.62            | -95.99                   |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.




|                          |                                |                 |                       |
|--------------------------|--------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 9262<br>(1852.4MHz) | Frequency Range | Below 1000 MHz        |
| Environmental Conditions | 23deg. C, 68%RH                | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                       |                 |                       |

| Antenna Polarity & Test Distance : Vertical at 3 m |                    |               |                |                |                          |                            |                        |                                |
|----------------------------------------------------|--------------------|---------------|----------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| No                                                 | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                  | 115.36             | -59.41        | -13.00         | -46.41         | 1.01 V                   | 212                        | 47.18                  | -106.59                        |
| 2                                                  | 185.20             | -60.29        | -13.00         | -47.29         | 1.01 V                   | 318                        | 45.54                  | -105.83                        |
| 3                                                  | 237.58             | -61.74        | -13.00         | -48.74         | 1.50 V                   | 247                        | 43.39                  | -105.13                        |
| 4                                                  | 317.12             | -60.97        | -13.00         | -47.97         | 1.50 V                   | 6                          | 41.26                  | -102.23                        |
| 5                                                  | 396.66             | -59.98        | -13.00         | -46.98         | 1.50 V                   | 313                        | 41.24                  | -101.22                        |
| 6                                                  | 536.34             | -53.63        | -13.00         | -40.63         | 1.01 V                   | 161                        | 45.22                  | -98.85                         |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.




# LTE Band 2, Channel Bandwidth 20MHz

|                          |                                 |                 |                       |
|--------------------------|---------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 19100<br>(1900.0MHz) | Frequency Range | Below 1000 MHz        |
| Environmental Conditions | 23deg. C, 68%RH                 | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                        |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |            |             |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|------------|-------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 95.96           | -43.52     | -13.00      | -30.52      | 1.50 H             | 186                  | 65.83            | -109.35                  |
| 2                                                    | 204.60          | -41.47     | -13.00      | -28.47      | 1.50 H             | 189                  | 65.23            | -106.70                  |
| 3                                                    | 297.72          | -47.72     | -13.00      | -34.72      | 1.50 H             | 90                   | 55.05            | -102.77                  |
| 4                                                    | 466.50          | -51.61     | -13.00      | -38.61      | 1.50 H             | 231                  | 48.25            | -99.86                   |
| 5                                                    | 635.28          | -50.45     | -13.00      | -37.45      | 1.50 H             | 124                  | 45.84            | -96.29                   |
| 6                                                    | 745.86          | -45.36     | -13.00      | -32.36      | 1.01 H             | 16                   | 48.31            | -93.67                   |

## Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.




|                          |                                 |                 |                       |
|--------------------------|---------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 19100<br>(1900.0MHz) | Frequency Range | Below 1000 MHz        |
| Environmental Conditions | 23deg. C, 68%RH                 | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                        |                 |                       |

| Antenna Polarity & Test Distance : Vertical at 3 m |                    |               |                |                |                          |                            |                        |                                |
|----------------------------------------------------|--------------------|---------------|----------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| No                                                 | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                  | 92.08              | -54.99        | -13.00         | -41.99         | 1.00 V                   | 249                        | 54.43                  | -109.42                        |
| 2                                                  | 196.84             | -45.41        | -13.00         | -32.41         | 1.00 V                   | 213                        | 61.25                  | -106.66                        |
| 3                                                  | 243.40             | -52.33        | -13.00         | -39.33         | 1.49 V                   | 284                        | 52.34                  | -104.67                        |
| 4                                                  | 394.72             | -52.73        | -13.00         | -39.73         | 1.49 V                   | 284                        | 48.48                  | -101.21                        |
| 5                                                  | 460.68             | -50.24        | -13.00         | -37.24         | 1.00 V                   | 248                        | 49.62                  | -99.86                         |
| 6                                                  | 538.28             | -52.80        | -13.00         | -39.80         | 1.00 V                   | 249                        | 46.00                  | -98.80                         |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.




# LTE Band 25, Channel Bandwidth 20MHz

|                          |                              |                 |                       |
|--------------------------|------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 26365 (1882.5MHz) | Frequency Range | Below 1000 MHz        |
| Environmental Conditions | 23deg. C, 68%RH              | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                     |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |            |             |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|------------|-------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 97.90           | -47.38     | -13.00      | -34.38      | 1.01 H             | 187                  | 61.44            | -108.82                  |
| 2                                                    | 152.22          | -60.78     | -13.00      | -47.78      | 1.01 H             | 263                  | 42.99            | -103.77                  |
| 3                                                    | 241.46          | -58.33     | -13.00      | -45.33      | 1.01 H             | 83                   | 46.46            | -104.79                  |
| 4                                                    | 319.06          | -42.69     | -13.00      | -29.69      | 1.50 H             | 134                  | 59.50            | -102.19                  |
| 5                                                    | 344.28          | -56.49     | -13.00      | -43.49      | 1.50 H             | 132                  | 45.57            | -102.06                  |
| 6                                                    | 509.18          | -46.71     | -13.00      | -33.71      | 1.50 H             | 131                  | 52.54            | -99.25                   |

## Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.




|                          |                                 |                 |                       |
|--------------------------|---------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 26365<br>(1882.5MHz) | Frequency Range | Below 1000 MHz        |
| Environmental Conditions | 23deg. C, 68%RH                 | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                        |                 |                       |

| Antenna Polarity & Test Distance : Vertical at 3 m |                 |            |             |             |                    |                      |                  |                          |
|----------------------------------------------------|-----------------|------------|-------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                 | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                  | 101.78          | -52.76     | -13.00      | -39.76      | 1.00 V             | 13                   | 55.42            | -108.18                  |
| 2                                                  | 237.58          | -56.09     | -13.00      | -43.09      | 1.00 V             | 95                   | 49.04            | -105.13                  |
| 3                                                  | 315.18          | -54.77     | -13.00      | -41.77      | 1.00 V             | 115                  | 47.51            | -102.28                  |
| 4                                                  | 532.46          | -50.34     | -13.00      | -37.34      | 1.49 V             | 114                  | 48.58            | -98.92                   |
| 5                                                  | 617.82          | -56.09     | -13.00      | -43.09      | 1.49 V             | 16                   | 40.42            | -96.51                   |
| 6                                                  | 771.08          | -49.43     | -13.00      | -36.43      | 1.49 V             | 16                   | 43.58            | -93.01                   |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.



Above 1GHz  
WCDMA Band 2

|                          |                                |                 |                       |
|--------------------------|--------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 9262<br>(1852.4MHz) | Frequency Range | 1GHz ~ 20GHz          |
| Environmental Conditions | 24deg. C, 68%RH                | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                       |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                    |               |                |                |                          |                            |                        |                                |
|------------------------------------------------------|--------------------|---------------|----------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3704.80            | -38.59        | -13.00         | -25.59         | 1.01 H                   | 67                         | 49.42                  | -88.01                         |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                    |               |                |                |                          |                            |                        |                                |
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3704.80            | -33.83        | -13.00         | -20.83         | 1.00 V                   | 299                        | 54.18                  | -88.01                         |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

|                          |                                |                 |                       |
|--------------------------|--------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 9400<br>(1880.0MHz) | Frequency Range | 1GHz ~ 20GHz          |
| Environmental Conditions | 24deg. C, 68%RH                | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                       |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                    |               |                |                |                          |                            |                        |                                |
|------------------------------------------------------|--------------------|---------------|----------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3760.00            | -46.24        | -13.00         | -33.24         | 1.06 H                   | 77                         | 41.81                  | -88.05                         |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                    |               |                |                |                          |                            |                        |                                |
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3760.00            | -41.50        | -13.00         | -28.50         | 1.00 V                   | 303                        | 46.55                  | -88.05                         |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

|                          |                                |                 |                       |
|--------------------------|--------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 9538<br>(1907.6MHz) | Frequency Range | 1GHz ~ 20GHz          |
| Environmental Conditions | 24deg. C, 68%RH                | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                       |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                    |               |                |                |                          |                            |                        |                                |
|------------------------------------------------------|--------------------|---------------|----------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3815.20            | -38.11        | -13.00         | -25.11         | 1.05 H                   | 62                         | 49.88                  | -87.99                         |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                    |               |                |                |                          |                            |                        |                                |
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3815.20            | -33.70        | -13.00         | -20.70         | 1.00 V                   | 298                        | 54.29                  | -87.99                         |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

LTE Band 2, Channel Bandwidth 1.4MHz

|                          |                                 |                 |                       |
|--------------------------|---------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 18607<br>(1850.7MHz) | Frequency Range | 1GHz ~ 20GHz          |
| Environmental Conditions | 24deg. C, 68%RH                 | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                        |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                    |               |                |                |                          |                            |                        |                                |
|------------------------------------------------------|--------------------|---------------|----------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3701.40            | -41.40        | -13.00         | -28.40         | 1.10 H                   | 73                         | 46.61                  | -88.01                         |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                    |               |                |                |                          |                            |                        |                                |
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3701.40            | -33.50        | -13.00         | -20.50         | 1.01 V                   | 293                        | 54.51                  | -88.01                         |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

|                          |                                 |                 |                       |
|--------------------------|---------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 18900<br>(1880.0MHz) | Frequency Range | 1GHz ~ 20GHz          |
| Environmental Conditions | 24deg. C, 68%RH                 | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                        |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                    |               |                |                |                          |                            |                        |                                |
|------------------------------------------------------|--------------------|---------------|----------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3760.00            | -41.77        | -13.00         | -28.77         | 1.00 H                   | 66                         | 46.28                  | -88.05                         |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                    |               |                |                |                          |                            |                        |                                |
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3760.00            | -33.28        | -13.00         | -20.28         | 1.00 V                   | 298                        | 54.77                  | -88.05                         |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

|                          |                                 |                 |                       |
|--------------------------|---------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 19193<br>(1909.3MHz) | Frequency Range | 1GHz ~ 20GHz          |
| Environmental Conditions | 24deg. C, 68%RH                 | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                        |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                    |               |                |                |                          |                            |                        |                                |
|------------------------------------------------------|--------------------|---------------|----------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3818.60            | -41.56        | -13.00         | -28.56         | 1.13 H                   | 66                         | 46.41                  | -87.97                         |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                    |               |                |                |                          |                            |                        |                                |
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3818.60            | -33.37        | -13.00         | -20.37         | 1.00 V                   | 295                        | 54.60                  | -87.97                         |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

LTE Band 2, Channel Bandwidth 5MHz

|                          |                                 |                 |                       |
|--------------------------|---------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 18625<br>(1852.5MHz) | Frequency Range | 1GHz ~ 20GHz          |
| Environmental Conditions | 24deg. C, 68%RH                 | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                        |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |            |             |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|------------|-------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 3705.00         | -41.50     | -13.00      | -28.50      | 1.14 H             | 73                   | 46.51            | -88.01                   |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |            |             |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 3705.00         | -33.30     | -13.00      | -20.30      | 1.01 V             | 295                  | 54.71            | -88.01                   |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

|                          |                                 |                 |                       |
|--------------------------|---------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 18900<br>(1880.0MHz) | Frequency Range | 1GHz ~ 20GHz          |
| Environmental Conditions | 24deg. C, 68%RH                 | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                        |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |            |             |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|------------|-------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 3760.00         | -41.57     | -13.00      | -28.57      | 1.12 H             | 68                   | 46.48            | -88.05                   |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |            |             |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 3760.00         | -33.55     | -13.00      | -20.55      | 1.05 V             | 299                  | 54.50            | -88.05                   |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

|                          |                                 |                 |                       |
|--------------------------|---------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 19175<br>(1907.5MHz) | Frequency Range | 1GHz ~ 20GHz          |
| Environmental Conditions | 24deg. C, 68%RH                 | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                        |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                    |               |                |                |                          |                            |                        |                                |
|------------------------------------------------------|--------------------|---------------|----------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3815.00            | -41.59        | -13.00         | -28.59         | 1.11 H                   | 71                         | 46.40                  | -87.99                         |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                    |               |                |                |                          |                            |                        |                                |
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3815.00            | -33.52        | -13.00         | -20.52         | 1.00 V                   | 299                        | 54.47                  | -87.99                         |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

LTE Band 2, Channel Bandwidth 20MHz

|                          |                                 |                 |                       |
|--------------------------|---------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 18700<br>(1860.0MHz) | Frequency Range | 1GHz ~ 20GHz          |
| Environmental Conditions | 24deg. C, 68%RH                 | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                        |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                    |               |                |                |                          |                            |                        |                                |
|------------------------------------------------------|--------------------|---------------|----------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3720.00            | -41.78        | -13.00         | -28.78         | 1.13 H                   | 71                         | 46.24                  | -88.02                         |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                    |               |                |                |                          |                            |                        |                                |
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3720.00            | -33.73        | -13.00         | -20.73         | 1.03 V                   | 299                        | 54.29                  | -88.02                         |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

|                          |                                 |                 |                       |
|--------------------------|---------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 18900<br>(1880.0MHz) | Frequency Range | 1GHz ~ 20GHz          |
| Environmental Conditions | 24deg. C, 68%RH                 | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                        |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                    |               |                |                |                          |                            |                        |                                |
|------------------------------------------------------|--------------------|---------------|----------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3760.00            | -41.72        | -13.00         | -28.72         | 1.10 H                   | 73                         | 46.33                  | -88.05                         |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                    |               |                |                |                          |                            |                        |                                |
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3760.00            | -33.69        | -13.00         | -20.69         | 1.01 V                   | 293                        | 54.36                  | -88.05                         |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

|                          |                                 |                 |                       |
|--------------------------|---------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 19100<br>(1900.0MHz) | Frequency Range | 1GHz ~ 20GHz          |
| Environmental Conditions | 24deg. C, 68%RH                 | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                        |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                    |               |                |                |                          |                            |                        |                                |
|------------------------------------------------------|--------------------|---------------|----------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3800.00            | -41.75        | -13.00         | -28.75         | 1.13 H                   | 71                         | 46.33                  | -88.08                         |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                    |               |                |                |                          |                            |                        |                                |
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3800.00            | -33.17        | -13.00         | -20.17         | 1.09 V                   | 298                        | 54.91                  | -88.08                         |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

LTE Band 25, Channel Bandwidth 1.4MHz

|                          |                                 |                 |                       |
|--------------------------|---------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 26047<br>(1850.7MHz) | Frequency Range | 1GHz ~ 20GHz          |
| Environmental Conditions | 24deg. C, 68%RH                 | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                        |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |            |             |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|------------|-------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 3701.40         | -35.15     | -13.00      | -22.15      | 1.04 H             | 61                   | 52.86            | -88.01                   |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |            |             |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 3701.40         | -31.48     | -13.00      | -18.48      | 1.00 V             | 291                  | 56.53            | -88.01                   |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

|                          |                                 |                 |                       |
|--------------------------|---------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 26365<br>(1882.5MHz) | Frequency Range | 1GHz ~ 20GHz          |
| Environmental Conditions | 24deg. C, 68%RH                 | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                        |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |            |             |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|------------|-------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 3765.00         | -35.45     | -13.00      | -22.45      | 1.09 H             | 63                   | 52.60            | -88.05                   |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |            |             |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 3765.00         | -31.04     | -13.00      | -18.04      | 1.03 V             | 293                  | 57.01            | -88.05                   |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

|                          |                                 |                 |                       |
|--------------------------|---------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 26683<br>(1914.3MHz) | Frequency Range | 1GHz ~ 20GHz          |
| Environmental Conditions | 24deg. C, 68%RH                 | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                        |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                    |               |                |                |                          |                            |                        |                                |
|------------------------------------------------------|--------------------|---------------|----------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3828.60            | -35.04        | -13.00         | -22.04         | 1.03 H                   | 60                         | 52.86                  | -87.90                         |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                    |               |                |                |                          |                            |                        |                                |
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3828.60            | -30.98        | -13.00         | -17.98         | 1.02 V                   | 296                        | 56.92                  | -87.90                         |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

LTE Band 25, Channel Bandwidth 5MHz

|                          |                                 |                 |                       |
|--------------------------|---------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 26065<br>(1852.5MHz) | Frequency Range | 1GHz ~ 20GHz          |
| Environmental Conditions | 24deg. C, 68%RH                 | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                        |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                    |               |                |                |                          |                            |                        |                                |
|------------------------------------------------------|--------------------|---------------|----------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3705.00            | -34.97        | -13.00         | -21.97         | 1.04 H                   | 63                         | 53.04                  | -88.01                         |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                    |               |                |                |                          |                            |                        |                                |
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3705.00            | -31.22        | -13.00         | -18.22         | 1.08 V                   | 291                        | 56.79                  | -88.01                         |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

|                          |                                 |                 |                       |
|--------------------------|---------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 26365<br>(1882.5MHz) | Frequency Range | 1GHz ~ 20GHz          |
| Environmental Conditions | 24deg. C, 68%RH                 | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                        |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                    |               |                |                |                          |                            |                        |                                |
|------------------------------------------------------|--------------------|---------------|----------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3765.00            | -35.12        | -13.00         | -22.12         | 1.08 H                   | 59                         | 52.93                  | -88.05                         |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                    |               |                |                |                          |                            |                        |                                |
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3765.00            | -31.65        | -13.00         | -18.65         | 1.06 V                   | 290                        | 56.40                  | -88.05                         |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

|                          |                                 |                 |                       |
|--------------------------|---------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 26665<br>(1912.5MHz) | Frequency Range | 1GHz ~ 20GHz          |
| Environmental Conditions | 24deg. C, 68%RH                 | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                        |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                    |               |                |                |                          |                            |                        |                                |
|------------------------------------------------------|--------------------|---------------|----------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3825.00            | -35.20        | -13.00         | -22.20         | 1.09 H                   | 61                         | 52.72                  | -87.92                         |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                    |               |                |                |                          |                            |                        |                                |
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3825.00            | -31.21        | -13.00         | -18.21         | 1.08 V                   | 294                        | 56.71                  | -87.92                         |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

LTE Band 25, Channel Bandwidth 20MHz

|                          |                                 |                 |                       |
|--------------------------|---------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 26140<br>(1860.0MHz) | Frequency Range | 1GHz ~ 20GHz          |
| Environmental Conditions | 24deg. C, 68%RH                 | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                        |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                    |               |                |                |                          |                            |                        |                                |
|------------------------------------------------------|--------------------|---------------|----------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3720.00            | -35.09        | -13.00         | -22.09         | 1.08 H                   | 65                         | 52.93                  | -88.02                         |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                    |               |                |                |                          |                            |                        |                                |
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3720.00            | -31.09        | -13.00         | -18.09         | 1.06 V                   | 295                        | 56.93                  | -88.02                         |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

|                          |                                 |                 |                       |
|--------------------------|---------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 26365<br>(1882.5MHz) | Frequency Range | 1GHz ~ 20GHz          |
| Environmental Conditions | 24deg. C, 68%RH                 | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                        |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                    |               |                |                |                          |                            |                        |                                |
|------------------------------------------------------|--------------------|---------------|----------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3765.00            | -35.52        | -13.00         | -22.52         | 1.12 H                   | 59                         | 52.53                  | -88.05                         |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                    |               |                |                |                          |                            |                        |                                |
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| <b>1</b>                                             | <b>3765.00</b>     | <b>-30.94</b> | <b>-13.00</b>  | <b>-17.94</b>  | <b>1.03 V</b>            | <b>297</b>                 | <b>57.11</b>           | <b>-88.05</b>                  |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

|                          |                                 |                 |                       |
|--------------------------|---------------------------------|-----------------|-----------------------|
| Mode                     | TX channel 26590<br>(1905.0MHz) | Frequency Range | 1GHz ~ 20GHz          |
| Environmental Conditions | 24deg. C, 68%RH                 | Input Power     | 120Vac, 60Hz (System) |
| Tested By                | Luis Lee                        |                 |                       |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                    |               |                |                |                          |                            |                        |                                |
|------------------------------------------------------|--------------------|---------------|----------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3810.00            | -34.87        | -13.00         | -21.87         | 1.09 H                   | 59                         | 53.15                  | -88.02                         |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                    |               |                |                |                          |                            |                        |                                |
| No                                                   | Frequency<br>(MHz) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Antenna<br>Height<br>(m) | Table<br>Angle<br>(Degree) | Raw<br>Value<br>(dBuV) | Correction<br>Factor<br>(dB/m) |
| 1                                                    | 3810.00            | -31.05        | -13.00         | -18.05         | 1.02 V                   | 297                        | 56.97                  | -88.02                         |

Remarks:

1.  $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2.  $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3.  $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

### **Lin Kou EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

### **Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

### **Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---