

SAR EVALUATION REPORT

IEEE Std 1528-2013 IEC/IEEE 62209-1528:2020

For
Low Power Digital Device Transmitter

FCC ID: IPH-04883 Model Name: A04883

Report Number: R15485855-S13 Issue Date: 2024-09-24

Prepared for Garmin International Inc 1200 E 151st St Olathe, KS, 66062-3426, US

Prepared by UL LLC 12 LABORATORY DR RTP, NC 27709, U.S.A. TEL: (919) 549-1400



Revision History

Rev.	Date	Revisions	Revised By
V1	2024-09-24	Initial Issue	

Table of Contents

1.	Attestation of Test Results	5
2.	Test Specification, Methods and Procedures	6
3.	Facilities and Accreditation	7
4.	SAR Measurement System & Test Equipment	8
4.1.	SAR Measurement System	8
4.2.	SAR Scan Procedures	9
4.3.	Test Equipment	11
5.	Measurement Uncertainty	12
6.	Device Under Test (DUT) Information	13
6.1.	DUT Description	13
6.2.	Wireless Technologies	14
7.	RF Exposure Conditions (Test Configurations)	15
8.	Dielectric Property Measurements & System Check	16
8.1.	Dielectric Property Measurements	16
8.2.	System Check	18
9.	Conducted Output Power Measurements	20
9.1.	Bluetooth LE	20
9.2.	ANT/ANT+	20
9.3.	NFC	21
10.	Measured and Reported (Scaled) SAR Results	22
10.1	1. NFC	22
10.2	2. Standalone SAR Test Exclusion Considerations & Estimated SAR	22
11.	Simultaneous Transmission Conditions	23
11.1	1. Simultaneous transmission SAR test exclusion considerations	23
11.2	2. Estimated SAR for Simultaneous Transmission SAR Analysis	23
11.3	3. Sum of SAR for DSS & DXX	24
Apper	ndixes	25
Арр	endix A: SAR Setup Photos	25
Арр	endix B: SAR System Check Plots	25
Арр	endix C: SAR Highest Test Plots	25
Арр	endix D: SAR Tissue Ingredients	25
Арр	endix E: SAR Probe Certificates	25

Page 3 of 25

pendix F: SAR CLA Certificate

1. Attestation of Test Results

Applicant Name	Garmin International Inc			
FCC ID	IPH-04883			
Model Name	A04883			
Applicable Standards	Published RF exposure KDB procedures. IEEE Std 1528-2013 IEC/IEEE 62209-1528:2020			
	SAR Limi	ts (W/Kg)		
Exposure Category	Extremities (hands, wrists, ankles, etc.) (10g of tissue)			
General population / Uncontrolled exposure	4			
PE Exposure Conditions	Equipment Class - Highest Reported SAR (W/kg)			
	DSS	DXX		
Extremity	0.067	0.000		
Simultaneous TX	0.067 0.067			
Date Tested	2024-09-16			
Test Results	Pass			

UL LLC tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested can demonstrate compliance with the requirements as documented in this report.

This report contains data provided by the customer which can impact the validity of results. UL LLC is only responsible for the validity of results after the integration of the data provided by the customer.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to ensure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not considered unless noted otherwise.

This document may not be altered or revised in any way unless done so by UL LLC and all revisions are noted in the revisions section. Any alteration of this document not carried out by UL LLC will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by A2LA, NIST, or any agency of the U.S. Government, or any agency of the U.S. government.

Approved & Released By:	Prepared By:		
Richard Jankeouries	Ahm		
Richard Jankovics	Sarah Kuhaneck		
Staff Engineer	Engineer Project Associate		
UL LLC	UL LLC		

2. Test Specification, Methods and Procedures

The tests documented in this report were performed in accordance with FCC 47 CFR § 2.1093, IEEE 1528-2013, IEC/IEEE 62209-1528:2020, the following FCC Published RF exposure <u>KDB</u> procedures:

- o 447498 D01 General RF Exposure Guidance v06
- 447498 D03 Supplement C Cross-Reference v01
- 865664 D02 RF Exposure Reporting v01r02

In addition to the above, the following information was used:

- o <u>TCB Workshop</u> October 2016; RF Exposure Procedures (DUT Holder Perturbations)
- o <u>TCB Workshop</u> April 2019; RF Exposure Procedures (Tissue Simulating Liquids (TSL))

3. Facilities and Accreditation

UL LLC is accredited by A2LA, cert. # 0751.06 for all testing performed within the scope of this report. Testing was performed at the locations noted below.

The test sites and measurement facilities used to collect data are located at 2800 Perimeter Park Dr, Morrisville, NC, USA.

• SAR Lab 1A

	Address	ISED CABID	ISED Company Number	FCC Registration
	Building: 12 Laboratory Dr RTP, NC 27709, U.S.A	US0067	2180C	825374
\boxtimes	Building: 2800 Perimeter Park Dr. Suite B Morrisville, NC 27560, U.S.A	US0067	27265	825374

4. SAR Measurement System & Test Equipment

4.1. SAR Measurement System

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, ADconversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running Win10 and the DASY8¹ software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

¹ DASY8 software used: DASY16.4.0 and older generations.

4.2. SAR Scan Procedures

Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. The minimum distance of probe sensors to surface is 2.1 mm. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEC/IEEE 62209-1528, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan). If only one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of Zoom Scans has to be increased accordingly.

Area Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

	\leq 3 GHz	> 3 GHz	
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	$5 \pm 1 \text{ mm}$	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$	
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ\pm1^\circ$	$20^\circ\pm1^\circ$	
	\leq 2 GHz: \leq 15 mm 2 - 3 GHz: \leq 12 mm	$\begin{array}{l} 3-4 \ \mathrm{GHz:} \leq 12 \ \mathrm{mm} \\ 4-6 \ \mathrm{GHz:} \leq 10 \ \mathrm{mm} \end{array}$	
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be \leq the corresponding x or y dimension of the test device with at least one measurement point on the test device.		

Step 3: Zoom Scan

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The Zoom Scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1 g and 10 g and displays these values next to the job's label.

			\leq 3 GHz > 3 GHz	
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}				
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		\leq 5 mm	$3 - 4$ GHz: ≤ 4 mm $4 - 5$ GHz: ≤ 3 mm $5 - 6$ GHz: ≤ 2 mm
	graded grid grid be po	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	\leq 4 mm	$3 - 4$ GHz: ≤ 3 mm $4 - 5$ GHz: ≤ 2.5 mm $5 - 6$ GHz: ≤ 2 mm
		∆z _{Zoom} (n>1): between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume x, y, z		$ \ge 30 \text{ mm} \qquad \qquad 3 - 4 \text{ GHz:} \ge 28 \text{ m} \\ 4 - 5 \text{ GHz:} \ge 25 \text{ m} \\ 5 - 6 \text{ GHz:} \ge 22 \text{ m} \\ \end{cases} $		
Note: δ is the penetration	on denth o	f a plane-wave at norma	l incidence to the tissue mediu	m: see draft standard IEEE

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

When zoom scan is required and the <u>reported</u> SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is \leq 1.4 W/kg, \leq 8 mm, \leq 7 mm and \leq 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

Step 4: Power drift measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the last Power Reference Measurement. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

4.3. Test Equipment

The measuring equipment used to perform the tests documented in this report has been calibrated in accordance with the manufacturers' recommendations, and is traceable to recognized national standards.

Dielectric Property Measurements

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Date	Cal. Due Date
Netw ork Analyzer	Keysight	E5063A	MY54100681	2024-07-31	2025-07-31
Dielectric Probe	SPEAG	DAKS-12	1037	2024-03-11	2025-03-11
Shorting Block	SPEAG	DAK-12 Short	2044	2024-03-11	2025-03-11
Thermometer	Fisher Scientific	15-078-181	181705017	2023-03-30	2025-03-30

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Date	Cal. Due Date
Signal Generator	Keysight	N5181A	MY 50140788	2024-08-01	2025-08-01
3-Path Diode Pow er Sensor	Rohde & Schw arz	NRP8S	112236	2024-07-12	2025-07-12
3-Path Diode Pow er Sensor	Rohde & Schw arz	NRP8S	112237	2024-07-12	2025-07-12
Dual Directional Coupler	Werlatone	C5100-10	92249		N/A

Lab Equipment

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Date	Cal. Due Date
E-Field Probe	SPEAG	EX3DV4	7710	2024-01-16	2025-01-16
Data Acquisition Electronics	SPEAG	DA E4	1715	2024-02-12	2025-02-12
System Validation Dipole	SPEAG	CLA13	1017	2024-03-07	2025-03-07
Environmental Indicator	Control Company	06-662-4	240072459	2024-01-24	2026-01-24

5. Measurement Uncertainty

Per KDB 865664 D01, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be < 30%, for a confidence interval of k = 2. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval.

Therefore, the measurement uncertainty is not required.

6. Device Under Test (DUT) Information

6.1. DUT Description

Device Dimension	Overall (Length x Width x Thickness): 57 mm x 52 mm x 15 mm This is a an extremity wrist-worn wearable device	
Back Cover	The Back Cover is not removable	
Battery Options	The rechargeable battery is not user accessible.	
Test sample information	S/N	Notes
	477207650	Radiated NFC
Hardware Version	A04883	
Software Version	408	

6.2. Wireless Technologies

Wireless technologies	Frequency bands	Operating mode	Duty Cycle used for SAR testing
Bluetooth	2.4 GHz	LE	N/A ²
ANT/ANT+	2.4 GHz	GFSK	N/A ²
NFC	13.56 MHz	Туре А/В	100% (Type A) ¹

Notes:

1. 2.

Duty cycle for NFC is referenced from §9.3 Measured Duty Cycle is not required due to SAR test exemption.

7. RF Exposure Conditions (Test Configurations)

Refer to "SAR Photos and Ant locations" Appendix for the specific details of the antenna-to-antenna and antenna-to-edge(s) distances.

	Wireless technologies	RF Exposure Conditions	DUT-to-User Separation	Test Position	Antenna-to- edge/surface	SAR Required	Note
	Bluetooth LE	Extremity	0	Back	N/A	No	1
	ANT/ANT+	Extremity	0	Back	N/A	No	1
	NFC	Extremity	0	Back	N/A	Yes	
N	lotos:						

Notes:

SAR is not required per KDB 447498 D01 §4.2.3

SAR Test Exclusion Calculations for WLAN

Antennas < 50mm to adjacent edges

Tx	Frequency	Output	Power	Separation Distances (mm)	Calculated Threshold Value
Interface	(1917)	dBm	mW	Back	Back
Bluetooth LE	2480	6.00	4	0	1.3 -EXEMPT-
ANT/ANT+	2480	6.00	4	0	1.3 -EXEMPT-

Note(s):

According to KDB 447498, if the calculated threshold value is >7.5 then SAR testing is required.

8. Dielectric Property Measurements & System Check

8.1. Dielectric Property Measurements

The temperature of the tissue-equivalent medium used during measurement must also be within 18° C to 25° C and within $\pm 2^{\circ}$ C of the temperature when the tissue parameters are characterized.

The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3 - 4 days of use; or earlier if the dielectric parameters can become out of tolerance; for example, when the parameters are marginal at the beginning of the measurement series.

Tissue dielectric parameters were measured at the low, middle and high frequency of each operating frequency range of the test device.

The dielectric constant (ϵ r) and conductivity (σ) of typical tissue-equivalent media recipes are expected to

be within \pm 5% of the required target values; but for SAR measurement systems that have implemented the SAR error compensation algorithms documented in IEC/IEEE 62209-1528:2020, to automatically compensate the measured SAR results for deviations between the measured and required tissue dielectric parameters, the tolerance for ϵ r and σ may be relaxed to \pm 10%. This is limited to frequencies \leq 3 GHz.

Tissue Dielectric Parameters IEC/IEEE 62209-1528

Frequency	Real part of the complex relative permittivity, c'	Conductivity, σ	Penetration depth (E-field), δ
MHz		S/m	mm
4	55,0	0,75	293,0
13	55,0	0,75	165,5
30	55,0	0,75	112,8
150	52,3	0,76	62,0
300	45,3	0,87	46,1
450	43,5	0,87	43,0
750	41,9	0,89	39,8
835	41,5	0,90	39,0
900	41,5	0,97	36,2
1 450	40,5	1,20	28,6
1 800	40,0	1,40	24,3
1 900	40,0	1,40	24,3
1 950	40,0	1,40	24,3
2 000	40,0	1,40	24,3
2 100	39,8	1,49	22,8
2 450	39,2	1,80	18,7
2 600	39,0	1,96	17,2
3 000	38,5	2,40	14,0
3 500	37,9	2,91	11,4
4 000	37,4	3,43	10,0
4 500	36,8	3,94	9,7
Frequency	Real part of the complex relative permittivity, c'	Conductivity, σ	Penetration depth (E-field), δ
MHz		S/m	mm
5 000	36,2	4,45	1,5
5 200	36,0	4,66	8,4
5 400	35,8	4,86	8,1
5 600	35,5	5,07	7,5
5 800	35,3	5,27	7,3
6 000	35,1	5,48	7,0
6 500	34,5	6,07	6,7
7 000	33,9	6,65	6,4
7 500	33,3	7,24	6,1
8 000	32,7	7,84	5,9
8 500	32,1	8,46	5,3
9 000	31,6	9,08	4,8
9 500	31,0	9,71	4,4

Table 2 – Dielectric properties of the tissue-equivalent medium

Page 16 of 25

Dielectric Property Measurements Results:

					Relative Permittivity (cr)			Conductivity (σ)		
SAR Lab	Date	Tissue Type	Band (MHz)	Freq. (MHz)	Measured	Target	Delta	Measured	Target	Delta
			13	13	52.8	55.0	-3.95%	0.72	0.75	-4.48%
SAR 1A	2024-09-16	Head		12	52.8	55.0	-3.96%	0.72	0.75	-4.49%
				14	52.8	55.0	-3.98%	0.72	0.75	-4.47%

8.2. System Check

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device. The same SAR probe(s) and tissue-equivalent media combinations used with each specific SAR system for system verification must be used for device testing. When multiple probe calibration points are required to cover substantially large transmission bands, independent system verifications are required for each probe calibration point. A system verification must be performed before each series of SAR measurements using the same probe calibration point and tissue-equivalent medium. Additional system verification should be considered according to the conditions of the tissue-equivalent medium and measured tissue dielectric parameters, typically every three to four days when the liquid parameters are re-measured or sooner when marginal liquid parameters are used at the beginning of a series of measurements.

System Performance Check Measurement Conditions:

- The measurements were performed in the flat section of the TWIN SAM or ELI phantom, shell thickness: 2.0 ±0.2 mm (bottom plate) filled with Body or Head simulating liquid of the following parameters.
- The depth of tissue-equivalent liquid in a phantom must be ≥ 15.0 cm for SAR measurements ≤ 3 GHz and ≥ 10.0 cm for measurements > 3 GHz.
- The DASY system with an E-Field Probe was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 10 mm (above 1 GHz) and 15 mm (below 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 15 mm was aligned with the dipole. For 5 GHz band - The coarse grid with a grid spacing of 10 mm was aligned with the dipole.
- Special 7x7x7 (below 3 GHz) and/or 8x8x7 (above 3 GHz) fine cube was chosen for the cube.
- Distance between probe sensors and phantom surface was set to 3 mm.
 For 5 GHz band Distance between probe sensors and phantom surface was set to 2.5 mm
- The dipole/CLA input power (forward power) was recorded.
- The results are normalized to 1 W input power.

System Check Results

The 1-g and 10-g SAR measured with a reference dipole, using the required tissue-equivalent medium at the test frequency, must be within $\pm 10\%$ of the manufacturer calibrated dipole SAR target. Refer to Appendix B for the SAR System Check Plots.

		Dinolo Typo		Innut		Measured results for 1-g SAR				Measured results for 10-g SAR			
SAR Lab	R Lab Date & Serial Number	Dipole Cal. Due Date	Power (dBm)	Meas. Zoom Scan	Normalize to 1 W	Target (Ref. Value)	Delta ±10%	Meas. Zoom Scan	Normalize to 1 W	Target (Ref. Value)	Delta ±10%	Plot No.	
1A	2024-09-16	CLA13 SN: 1017	2025-03-07	16.0	0.020	0.502	0.548	-8.33%	0.013	0.327	0.342	-4.52%	1

9. Conducted Output Power Measurements

9.1. Bluetooth LE

Maximum Output Power (Tune-up Limit) for Bluetooth LE

Maximum tune-up tolerance limit is 6 dBm. This power level qualifies for exclusion of SAR testing. Please refer to section 10.2. Standalone SAR Test Exclusion Considerations & Estimated SAR.

Band	Mode	Channel	Frequency (MHz)	Tune-up Pow erLimit (dBm)
Blueteeth		0	2402	6.0
2.4 GHz	LE	19	2440	6.0
		39	2480	6.0

9.2. ANT/ANT+

Maximum Output Power (Tune-up Limit) for ANT/ANT+

Maximum tune-up tolerance limit is 6 dBm. This power level qualifies for exclusion of SAR testing. Please refer to section 10.2. Standalone SAR Test Exclusion Considerations & Estimated SAR.

Band	Mode	Frequency (MHz)	Tune-up Pow erLimit (dBm)
ANT/ANT+ 2.4 GHz		2402	6.0
	GFSK	2440	6.0
		2480	6.0

9.3. NFC

Conducted output power cannot be measured for NFC, therefore a 2 dB scaling factor shall be used to account for potential variations between samples.

Duty Factor Measured Results

Mode	T on (ms)	Period (ms)	Duty Cycle	Crest Factor (1/duty cycle)
Type A	1.000	1.000	100.0%	1.00

Note(s):

Duty Cycle = (T on / period) * 100%

Duty Cycle plots

Type A

AP2022	2.8.16,,									
Ref -6	dBm		Atten	10 dB						
#Avg										
LOG 10										
dB/										
	c									
	Len	er								
	13.5	6000	1000	MHz						
PAvg										
W1 S2										
53 FS										
E(f)										
FTun										
Center	13.560	0 MHz							Spa	n 0 Hz´
Res BW	1 1 MHz			V	3W 1 MH	lz	S	weep 10	0 s (60	1 pts)

10. Measured and Reported (Scaled) SAR Results

SAR Test Reduction criteria are as follows:

• Reported SAR(W/kg) for NFC = Measured SAR * Tune-up scaling factor (2 dB)

10.1. NFC

Conditions Type A 0 Back 13.56 0.000 0.000	RF Exposure	Mada	Dist.	Dist.		10-g SA	Plot	
Extremity Type A 0 Back 13.56 0.000 0.000	Conditions	Mode	(mm)	Test Position	Fieq. (IVIEZ)	Meas.	Scaled	No.
	Extremity	Туре А	0	Back	13.56	0.000	0.000	1

Note(s):

Conducted output power measurements for NFC are not practical, therefore a 2 dB scaling factor shall be used to account for potential variations between samples.

10.2. Standalone SAR Test Exclusion Considerations & Estimated SAR

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)]·[$\sqrt{f}(GHz)$] \leq 3.0, for 1-g SAR and \leq 7.5 for 10-g extremity SAR, where

- $f_{(GHz)}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is \leq 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

When the standalone SAR test exclusion is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)]·[√f_(GHz)/x] W/kg for test separation distances ≤ 50 mm;

where x = 7.5 for 1-g SAR, and x = 18.75 for 10-g SAR.

• 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm.

RF Air interface	RF Exposure Conditions	Frequency (GHz)	Max. tune-ւ Pov	ıp tolerance v er	Min. test separation distance (mm)	SAR test exclusion Result*	Estimated 10-g SAR (W/kg)
			(dBm)	(mW)			
Bluetooth LE	Extremity	2.480	6.0	4	5	1.3	0.067
ANT/ANT+	Extremity	2.480	6.0	4	5	1.3	0.067

Conclusion:

*: The computed value is \leq 7.5; therefore, this qualifies for Standalone SAR test exclusion.

11. Simultaneous Transmission Conditions

RF Exposure Condition Ite		Capable Transmit Configurations				
Extremity	1	DSS	+	DXX		

11.1. Simultaneous transmission SAR test exclusion considerations

KDB 447498 D01 General RF Exposure Guidance provides two procedures for determining simultaneous transmission SAR test exclusion: Sum of SAR and SAR to Peak Location Ratio (SPLSR)

Sum of SAR

To qualify for simultaneous transmission SAR test exclusion based upon Sum of SAR the sum of the reported standalone SARs for all simultaneously transmitting antennas shall be below the applicable standalone SAR limit. If the sum of the SARs is above the applicable limit then simultaneous transmission SAR test exclusion may still apply if the requirements of the SAR to Peak Location Ratio (SPLSR) evaluation are met.

11.2. Estimated SAR for Simultaneous Transmission SAR Analysis

Considerations for SAR estimation

- 1. When standalone SAR test exclusion applies, standalone SAR must also be estimated to determine simultaneous transmission SAR test exclusion.
- 2. Dedicated Host Approach criteria for SAR test exclusion is likewise applied to SAR estimation, with certain distinctions between test exclusion and SAR estimation:
 - When the separation distance from the antenna to an adjacent edge is \leq 5 mm, a distance of 5 mm is applied for SAR estimation; this is the same between test exclusion and SAR estimation calculations.
 - When the separation distance from the antenna to an adjacent edge is > 5 mm but \leq 50 mm, the actual antenna-to-edge separation distance is applied for SAR estimation.
 - When the minimum test separation distance is > 50 mm, the estimated SAR value is 0.4 W/kg
- Please refer to <u>Estimated SAR Tables</u> to see which test positions are inherently compliant as they consist of only estimated SAR values for all applicable transmitters and consequently will always have sum of SAR values < 1.2 W/kg. Simultaneous transmission SAR analysis was therefore not performed for these test positions.

Estimated SAR for Bluetooth LE:

RF Air interface	RF Exposure Conditions	Frequency (GHz)	Max.tune-u Pov	ıp tolerance v er	Min. test separation distance (mm)	Estimated 10-g SAR (W/kg)
			(dBm)	(mW)		
Bluetooth LE	Extremity	2.480	6.0	4	5	0.067

Estimated SAR for Bluetooth LE:

RF Air interface	RF Exposure Conditions	Frequency (GHz)	Max. tune-u Pov	ıp tolerance v er	Min. test separation distance (mm)	Estimated 10-g SAR (W/kg)
			(dBm)	(mW)		
ANT/ANT+	Extremity	2.480	6.0	4	5	0.067

11.3. Sum of SAR for DSS & DXX

RF Exposure conditions	Test Position	Sta	ndalone SAR (W	∑ 1-g SAR (W/kg)		
		1	2	2	1+3	2+3
		Bluetooth LE	ANT/ANT+	NFC		
Extremity	Back	0.067	0.067	0.000	0.067	0.067

Appendixes

Refer to separated files for the following appendixes.

- Appendix A: SAR Setup Photos
- Appendix B: SAR System Check Plots
- Appendix C: SAR Highest Test Plots
- Appendix D: SAR Tissue Ingredients
- Appendix E: SAR Probe Certificates
- Appendix F: SAR CLA Certificate

END OF REPORT