# 7. RADIO FREQUENCY EXPOSURE

### 7.1. Limit

According to §1.1310 and §2.1091 RF exposure is calculated.

**Table: Limits for General Population/Uncontrolled Exposure** 

Frequency Range	Power Density (S)	
(MHz)	(mW/cm2)	
0.3–1.34	*(100)	
1.34-30	*(180/f <sup>2</sup> )	
30–300	0.2	
300-1500	f/1500	
1500–100,000	1.0	

F = frequency in MHz

## Maximum Permissible Exposure

The MPE was calculated at 20cm to show compliance with the power density limit.

 $S = PG/4\pi R^2$ 

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna.

#### Note:

- 1. Manufacturer declared that the maximum antenna gain is 2.0dBi(Max.).
- 2. Manufacturer declared that the nearest distance between human and the EUT is 20cm.
- 3. Only record worst case data.

<sup>\* =</sup> Plane-wave equivalent power density

Test Mode	Channel	Frequency (MHz)	Power (dBm, Average)	Power Tune Up (dBm)
802.11b	Low	2412	15.53	$16.0\pm1.0$
	Middle	2437	15.41	$16.0\pm1.0$
	High	2462	15.58	$16.0\pm1.0$
802.11g	Low	2412	14.78	$14.0\pm1.0$
	Middle	2437	14.69	$14.0\pm1.0$
	High	2462	14.81	$14.0\pm1.0$

## 7.2 Test Results

Test Mode	Channel	Max. Tune Up Power (dBm, Average)	Max. Tune Up Power (mW)	MPE (mW/cm²)	Limit (mW/cm²)
802.11b	Low	17.0	50.12	0.0158	1.0
	Middle	17.0	50.12	0.0158	1.0
	High	17.0	50.12	0.0158	1.0
802.11g	Low	15.0	31.62	0.0100	1.0
	Middle	15.0	31.62	0.0100	1.0
	High	15.0	31.62	0.0100	1.0

Antenna Gain (typical): 2.0dBi, 1.585(numeric)

Prediction distance: >=20cm

The power density level worst case at 20 cm is below the uncontrolled exposure limit.