



TESTING LABORATORY  
CERTIFICATE #4820.01



## FCC PART 15.247

### TEST REPORT

For

### HONG KONG IPRO TECHNOLOGY CO.,LIMITED

FLAT/RM A3, 9/F SILVERCORP INT TOWER, 707-713 NATHAN RD MONGKOK,  
HONGKONG, China

**FCC ID:PQ4IPRORUBY5S**

<b>Report Type:</b> Original Report	<b>Product Name:</b> Mobile Phone
<b>Report Number:</b> <u>RDG190307005-00B</u>	
<b>Report Date:</b>	<u>2019-04-25</u>
<b>Reviewed By:</b>	Jerry Zhang EMC Manager
<b>Test Laboratory:</b> Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>	

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA\* or any agency of the Federal Government. \* This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk \*\*.

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE .....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY .....	4
MEASUREMENT UNCERTAINTY .....	5
TEST FACILITY .....	5
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION .....	6
EUT EXERCISE SOFTWARE .....	6
EQUIPMENT MODIFICATIONS .....	6
SUPPORT CABLE LIST AND DETAILS .....	6
BLOCK DIAGRAM OF TEST SETUP .....	6
<b>SUMMARY OF TEST RESULTS .....</b>	<b>7</b>
<b>FCC §15.247 (i) &amp; §1.1310 &amp; §2.1093- RF EXPOSURE.....</b>	<b>8</b>
APPLICABLE STANDARD .....	8
<b>FCC §15.203- ANTENNA REQUIREMENT.....</b>	<b>9</b>
APPLICABLE STANDARD .....	9
ANTENNA CONNECTOR CONSTRUCTION .....	9
<b>FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS .....</b>	<b>10</b>
APPLICABLE STANDARD .....	10
EUT SETUP .....	10
EMI TEST RECEIVER SETUP.....	10
TEST PROCEDURE .....	10
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	11
TEST EQUIPMENT LIST AND DETAILS.....	11
TEST DATA .....	11
<b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS.....</b>	<b>14</b>
APPLICABLE STANDARD .....	14
EUT SETUP .....	14
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....	15
TEST PROCEDURE .....	15
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	15
TEST EQUIPMENT LIST AND DETAILS.....	16
TEST DATA .....	16
<b>FCC §15.247(a) (1) - CHANNEL SEPARATION TEST .....</b>	<b>22</b>
APPLICABLE STANDARD .....	22
TEST EQUIPMENT LIST AND DETAILS.....	22
TEST PROCEDURE .....	22
TEST DATA .....	22
<b>FCC §15.247(a) (1)-BANDWIDTH TESTING.....</b>	<b>29</b>
APPLICABLE STANDARD .....	29
TEST PROCEDURE .....	29
TEST EQUIPMENT LIST AND DETAILS.....	29
TEST DATA .....	29

<b>FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST .....</b>	<b>36</b>
APPLICABLE STANDARD .....	36
TEST PROCEDURE .....	36
TEST EQUIPMENT LIST AND DETAILS.....	36
TEST DATA .....	36
<b>FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....</b>	<b>39</b>
APPLICABLE STANDARD .....	39
TEST PROCEDURE .....	39
TEST EQUIPMENT LIST AND DETAILS.....	39
TEST DATA .....	39
<b>FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT.....</b>	<b>45</b>
APPLICABLE STANDARD .....	45
TEST PROCEDURE .....	45
TEST EQUIPMENT LIST AND DETAILS.....	45
TEST DATA .....	45
<b>FCC §15.247(d)- BAND EDGES TESTING .....</b>	<b>47</b>
APPLICABLE STANDARD .....	47
TEST PROCEDURE .....	47
TEST EQUIPMENT LIST AND DETAILS.....	47
TEST DATA .....	48

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

<b>EUT Name:</b>		Mobile Phone
<b>EUT Model:</b>		Ruby5S
<b>Operation Frequency:</b>		2402-2480 MHz
<b>Output Power(Conducted):</b>		-0.05dBm
<b>Modulation Type:</b>		GFSK, $\pi/4$ -DQPSK, 8-DPSK
<b>Rated Input Voltage:</b>		DC3.8V from Battery or DC5V from adapter
<b>Adapter Information</b>	<b>Model:</b>	NTR-S01
	<b>Input:</b>	AC 100-240V, 50/60Hz, 0.2A
	<b>Output:</b>	DC5V, 1000mA
<b>External Dimension:</b>		138mm(L)*66mm(W)*10mm(H)
<b>Serial Number:</b>		190307005
<b>EUT Received Date:</b>		2019.04.09

### Objective

This report is prepared on behalf of *HONG KONG IPRO TECHNOLOGY CO.,LIMITED* in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules.

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Rules Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID:PQ4IPRORUBY5S.  
FCC Part 15C DTS submissions with FCC ID:PQ4IPRORUBY5S.  
FCC Part 22H, 24E PCE submissions with FCC ID:PQ4IPRORUBY5S.

### Test Methodology

All measurements detailed in this test report were performed in accordance with ANSI C63.10-2013 "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices".

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

## Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB, 200M~1GHz: 5.92 dB, 1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

## Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier : CN0022.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in engineering mode.

### EUT Exercise Software

The Engineering Mode configured the maximum power level as default setting.


### Equipment Modifications

No modification was made to the EUT.

### Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From	To
USB cable	No	No	1.0	Adapter	EUT
Earphone cable	No	No	1.2	Earphone	EUT

### Block Diagram of Test Setup



## SUMMARY OF TEST RESULTS

Rules	Description of Test	Result
FCC§15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
FCC§15.203	Antenna Requirement	Compliance
FCC§15.207 (a)	Conducted Emissions	Compliance
FCC§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
FCC§15.247 (a)(1)	Bandwidth Test	Compliance
FCC§15.247(a)(1)	Channel Separation Test	Compliance
FCC§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
FCC§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
FCC§15.247(b)(1)	Peak Output Power Measurement	Compliance
FCC§15.247(d)	Band Edges	Compliance

## FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

### Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

### Measurement Result

The max conducted power including tune-up tolerance is 0.5 dBm (1.12 mW).

$$[(\text{max. power of channel, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] = 1.12 / 5 * (\sqrt{2.480}) = 0.4 < 3.0$$

**So the stand-alone SAR evaluation is not necessary.**

## FCC §15.203- ANTENNA REQUIREMENT

### Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

### Antenna Connector Construction

The EUT has one internal FPC antenna arrangement for BT/WLAN, fulfill the requirement of this section. Please refer to the EUT photos.

Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range
FPC	50	0.5 dBi/2.4~2.5GHz


**Result:** Compliance.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC§15.207(a).

### EUT Setup



- Note:**
1. Support units were connected to second LISN.
  2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main LISN with a 120 V/60 Hz AC power source.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

### Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

## Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_c + VDF$$

Herein,

$V_C$ : corrected voltage amplitude

$V_R$ : reading voltage amplitude

$A_c$ : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The “Margin” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	101121	2019-03-23	2020-03-23
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-01	2018-09-05	2019-09-05
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A
R&S	Two-line V-network	ENV 216	101614	2018-12-10	2019-12-10

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

## Test Data


### Environmental Conditions

<b>Temperature:</b>	25.7 °C
<b>Relative Humidity:</b>	67 %
<b>ATM Pressure:</b>	101.4 kPa

*The testing was performed by Ade Xiao on 2019-03-14.*


**Test Mode:** Transmitting

**AC120V, 60 Hz, Line:**



Frequency (MHz)	QuasiPeak (dB $\mu$ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.172421	39.1	9.000	L1	10.9	25.7	64.8
0.461750	35.6	9.000	L1	9.9	21.1	56.7
0.505009	43.2	9.000	L1	9.9	12.8	56.0
0.546852	37.9	9.000	L1	9.9	18.1	56.0
0.592163	36.0	9.000	L1	9.8	20.0	56.0
0.628593	35.4	9.000	L1	9.8	20.6	56.0

Frequency (MHz)	Average (dB $\mu$ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.466367	32.4	9.000	L1	9.9	14.2	46.6
0.505009	40.9	9.000	L1	9.9	5.1	46.0
0.546852	35.6	9.000	L1	9.9	10.4	46.0
0.592163	34.1	9.000	L1	9.8	11.9	46.0
0.634879	25.6	9.000	L1	9.8	20.4	46.0
1.013434	29.6	9.000	L1	9.8	16.4	46.0

**AC120V, 60 Hz, Neutral:**

Frequency (MHz)	QuasiPeak (dB $\mu$ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.157652	42.0	9.000	N	11.1	23.6	65.6
0.471031	36.8	9.000	N	9.9	19.7	56.5
0.505009	43.2	9.000	N	9.9	12.8	56.0
0.541438	37.2	9.000	N	9.8	18.8	56.0
0.580495	38.0	9.000	N	9.8	18.0	56.0
0.622369	36.1	9.000	N	9.8	19.9	56.0

Frequency (MHz)	Average (dB $\mu$ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.466367	26.3	9.000	N	9.9	20.3	46.6
0.505009	34.7	9.000	N	9.9	11.3	46.0
0.546852	29.5	9.000	N	9.8	16.5	46.0
0.580495	28.3	9.000	N	9.8	17.7	46.0
0.622369	23.9	9.000	N	9.8	22.1	46.0
1.013434	23.9	9.000	N	9.8	22.1	46.0


## FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

### Applicable Standard


FCC §15.247 (d); §15.209; §15.205.

### EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission below 1GHz tests were performed in the 10 meters chamber test site, above 1GHz tests were performed in the 3 meters chamber test site A, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

## EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

According to FCC public notice: DA-00-705, During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations :

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	AV

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2018-12-10	2019-12-10
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Sunol Sciences	Antenna	JB3	A060611-3	2017-07-21	2019-07-21
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-02	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2018-09-24	2019-09-24
Sonoma	Amplifier	310N	185914	2018-10-13	2019-10-13
R&S	Spectrum Analyzer	FSP 38	100478	2018-12-10	2019-12-10
TDK RF	Horn Antenna	HRN-0118	130 084	2018-10-12	2021-10-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2016-11-18	2019-11-18
MICRO-COAX	Coaxial Cable	UFA147-1-2362-100100	64639 231029-001	2019-02-24	2020-02-24
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2018-09-05	2019-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2018-06-27	2019-06-27
E-Microwave	Band-stop Filters	OBSF-2400-2483.5-S	OE01601525	2018-06-16	2019-06-16
Micro-tronics	High Pass Filter	HPM50111	S/N-G217	2018-06-16	2019-06-16

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

## Test Data

### Environmental Conditions


<b>Temperature:</b>	24.4~26.4 °C
<b>Relative Humidity:</b>	64~65%
<b>ATM Pressure:</b>	100.6~ 101.6kPa

\* The testing was performed by Neil Liao, Sunny Cen on 2019-04-15 & 2019-04-20


Test Mode: Transmitting

**1) 30MHz-1GHz(GFSK Low channel was the worst)**

**Horizontal:**



Frequency (MHz)	Receiver Reading (dB $\mu$ V)	Detector	Correction Factor (dB/m)	Cord. Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
30.0000	24.93	peak	-7.95	16.98	40.00	23.02
89.1700	33.36	peak	-18.84	14.52	43.50	28.98
162.8900	36.14	peak	-12.88	23.26	43.50	20.24
256.0100	29.80	peak	-12.98	16.82	46.00	29.18
366.5900	25.51	peak	-8.93	16.58	46.00	29.42
546.0400	24.64	peak	-4.29	20.35	46.00	25.65

**Vertical:**

Frequency (MHz)	Receiver Reading (dB $\mu$ V)	Detector	Correction Factor (dB/m)	Cord. Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
30.9700	28.90	peak	-8.40	20.50	40.00	19.50
91.1100	34.33	peak	-18.67	15.66	43.50	27.84
162.8900	32.42	peak	-12.88	19.54	43.50	23.96
290.9300	26.48	peak	-11.35	15.13	46.00	30.87
360.7700	26.74	peak	-9.12	17.62	46.00	28.38
543.1300	24.85	peak	-4.42	20.43	46.00	25.57




**2) 1GHz-25GHz:**

*BDR Mode (GFSK) was worst*

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	Reading (dB $\mu$ V)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2402 MHz									
2402.00	56.71	PK	H	24.82	3.34	0.00	84.87	N/A	N/A
2402.00	44.96	AV	H	24.82	3.34	0.00	73.12	N/A	N/A
2402.00	63.05	PK	V	24.82	3.34	0.00	91.21	N/A	N/A
2402.00	50.37	AV	V	24.82	3.34	0.00	78.53	N/A	N/A
2390.00	24.41	PK	V	24.80	3.33	0.00	52.54	74.00	21.46
2390.00	11.67	AV	V	24.80	3.33	0.00	39.80	54.00	14.20
4804.00	39.65	PK	V	29.71	4.58	27.36	46.58	74.00	27.42
4804.00	26.10	AV	V	29.71	4.58	27.36	33.03	54.00	20.97
7206.00	38.56	PK	V	33.93	5.59	27.19	50.89	74.00	23.11
7206.00	26.47	AV	V	33.93	5.59	27.19	38.80	54.00	15.20
Middle Channel: 2441 MHz									
2441.00	55.82	PK	H	24.89	3.36	0.00	84.07	N/A	N/A
2441.00	43.79	AV	H	24.89	3.36	0.00	72.04	N/A	N/A
2441.00	61.35	PK	V	24.89	3.36	0.00	89.60	N/A	N/A
2441.00	49.12	AV	V	24.89	3.36	0.00	77.37	N/A	N/A
4882.00	38.93	PK	V	29.86	4.56	27.56	45.79	74.00	28.21
4882.00	25.41	AV	V	29.86	4.56	27.56	32.27	54.00	21.73
7323.00	38.70	PK	V	34.12	5.69	27.26	51.25	74.00	22.75
7323.00	25.36	AV	V	34.12	5.69	27.26	37.91	54.00	16.09
High Channel: 2480 MHz									
2480.00	54.15	PK	H	24.96	3.38	0.00	82.49	N/A	N/A
2480.00	41.98	AV	H	24.96	3.38	0.00	70.32	N/A	N/A
2480.00	60.64	PK	V	24.96	3.38	0.00	88.98	N/A	N/A
2480.00	47.97	AV	V	24.96	3.38	0.00	76.31	N/A	N/A
2483.50	23.48	PK	V	24.97	3.38	0.00	51.83	74.00	22.17
2483.50	11.98	AV	V	24.97	3.38	0.00	40.33	54.00	13.67
4960.00	38.82	PK	V	30.02	4.58	27.37	46.05	74.00	27.95
4960.00	24.60	AV	V	30.02	4.58	27.37	31.83	54.00	22.17
7440.00	39.62	PK	V	34.30	5.79	27.22	52.49	74.00	21.51
7440.00	25.06	AV	V	34.30	5.79	27.22	37.93	54.00	16.07




**Worst plots (GFSK Low channel)****Horizontal**

Fundamental  
Test with Band  
Rejection Filter



**Vertical**

Fundamental Test with Band Rejection Filter



## FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

### Applicable Standard

According to FCC §15.247(a) (1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace.
3. Measure the channel separation.

### Test Data

#### Environmental Conditions

Temperature:	25.5 °C
Relative Humidity:	55%
ATM Pressure:	100.6kPa

\* The testing was performed by Carrie He on 2019-04-17

**Test Result:** Compliance.

Please refer to following tables and plots


*Test Mode: Transmitting*

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)
<i>BDR (GFSK)</i>	Low	2402	1.002	$\geq 0.62$
	Middle	2441	1.002	$\geq 0.62$
	High	2480	1.002	$\geq 0.61$
<i>EDR (<math>\pi/4</math>-DQPSK)</i>	Low	2402	1.002	$\geq 0.83$
	Middle	2441	1.002	$\geq 0.83$
	High	2480	1.002	$\geq 0.83$
<i>EDR (8-DPSK)</i>	Low	2402	0.998	$\geq 0.83$
	Middle	2441	1.002	$\geq 0.83$
	High	2480	1.002	$\geq 0.84$


*Note: Limit =  $(2/3) \times 20\text{dB bandwidth}$*


BDR Mode (GFSK):

### Low Channel




### Middle Channel




**High Channel**

*EDR Mode ( $\pi/4$ -DQPSK):*


**Low Channel**

### Middle Channel



Date: 17.APR.2019 09:39:38


### High Channel




Date: 17.APR.2019 09:40:13


EDR Mode (8-DPSK):

### Low Channel



### Middle Channel



**High Channel**

## FCC §15.247(a) (1)–BANDWIDTH TESTING

### Applicable Standard

According to FCC §15.247(a) (1):

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

Temperature:	25.5 °C
Relative Humidity:	55%
ATM Pressure:	100.6kPa

\* The testing was performed by Carrie He on 2019-04-17

**Test Result:** Compliance.


Please refer to following tables and plots

*Test Mode: Transmitting*


<b>Mode</b>	<b>Channel</b>	<b>Frequency (MHz)</b>	<b>20 dB Bandwidth (MHz)</b>
BDR Mode (GFSK)	Low	2402	0.928
	Middle	2441	0.924
	High	2480	0.920
EDR Mode ( $\pi/4$ -DQPSK)	Low	2402	1.248
	Middle	2441	1.252
	High	2480	1.252
EDR Mode (8-DPSK)	Low	2402	1.252
	Middle	2441	1.252
	High	2480	1.256

*BDR Mode (GFSK):*


### Low Channel



### Middle Channel




### High Channel




*EDR Mode ( $\pi/4$ -DQPSK):*


### Low Channel



### Middle Channel




### High Channel





*EDR Mode (8-DPSK):*

### Low Channel



### Middle Channel



**High Channel**

## FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

### Applicable Standard

According to FCC §15.247(a) (1) (iii)

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

Temperature:	25.5 °C
Relative Humidity:	55%
ATM Pressure:	100.6kPa

\* The testing was performed by Carrie He on 2019-04-17


**Test Result:** Compliance.

Please refer to following tables and plots


*Test Mode: Transmitting*

Mode	Frequency Range (MHz)	Number of Hopping Channel	Limit
GFSK	2400-2483.5	79	$\geq 15$
$\pi/4$ -DQPSK	2400-2483.5	79	$\geq 15$
8-DPSK	2400-2483.5	79	$\geq 15$


### BDR Mode (GFSK):Number of Hopping Channels



### EDR Mode ( $\pi/4$ -DQPSK): Number of Hopping Channels



### EDR Mode (8-DPSK):Number of Hopping Channels



## FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

### Applicable Standard

According to FCC §15.247(a) (1) (iii):

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### Test Procedure

The EUT was worked in channel hopping; the time of single pulses was tested.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

Temperature:	25.5 °C
Relative Humidity:	55%
ATM Pressure:	100.6kPa

\* The testing was performed by Carrie He on 2019-04-17


**Test Result:** Compliance.

Please refer to following tables and plots



*Test Mode: Transmitting*

Mode	Packet type	Channel	Frequency (MHz)	Pulse width (ms)	Result (s)	Limit (s)
GFSK	DH1	Middle	2441	0.394	0.126	0.4
	DH3	Middle	2441	1.657	0.265	
	DH5	Middle	2441	2.929	0.312	
$\pi/4$ -DQPSK	2DH1	Middle	2441	0.395	0.126	0.4
	2DH3	Middle	2441	1.674	0.268	
	2DH5	Middle	2441	2.916	0.311	
8-DPSK	3DH1	Middle	2441	0.403	0.129	0.4
	3DH3	Middle	2441	1.668	0.267	
	3DH5	Middle	2441	2.934	0.313	

Note:  
DH1:Dwell time=Pulse time (ms) × (1600/2/79) ×31.6 s  
DH3:Dwell time=Pulse time (ms) × (1600/4/79) ×31.6 s  
DH5:Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s


*BDR Mode (GFSK):***DH1: Middle Channel**

Date: 17.APR.2019 10:31:59

**DH3: Middle Channel****DH5: Middle Channel**


*EDR Mode ( $\pi/4$ -DQPSK):*

### 2DH1: Middle Channel







Date: 17.APR.2019 10:36:20

### 2DH3: Middle Channel



Date: 17.APR.2019 10:37:21

**2DH5: Middle Channel***EDR Mode (8-DPSK):***3DH1: Middle Channel**

**3DH3: Middle Channel****3DH5: Middle Channel**

## FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

### Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

### Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A
Agilent	USB Wideband Power Sensor	U2022XA	MY5417006	2018-12-10	2019-12-10

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

Temperature:	25.5 °C
Relative Humidity:	55%
ATM Pressure:	100.6kPa

\* The testing was performed by Carrie He on 2019-04-17&2019-04-25

**Test Result:** Compliance.

*Test Mode: Transmitting*

Mode	Frequency (MHz)	Peak Conducted Output power (dBm)	Limit (dBm)
BDR Mode (GFSK)	2402	-0.08	21
	2441	-0.61	21
	2480	-1.47	21
EDR Mode ( $\pi/4$ -DQPSK)	2402	-0.41	21
	2441	-0.79	21
	2480	-1.68	21
EDR Mode (8-DPSK)	2402	-0.05	21
	2441	-0.43	21
	2480	-1.23	21

Note: The data above was tested in conducted mode and the antenna gain is 0.5 dBi

## FCC §15.247(d)- BAND EDGES TESTING

### Applicable Standard

According to FCC §15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW/ VBW of spectrum analyzer to 100/300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

## Test Data

### Environmental Conditions


<b>Temperature:</b>	25.5 °C
<b>Relative Humidity:</b>	55%
<b>ATM Pressure:</b>	100.6kPa

\* The testing was performed by Carrie He on 2019-04-17

**Test Result:** Compliance


*Single mode:  
BDR Mode (GFSK):*

### Band Edge, Left Side



Date: 17.APR.2019 10:12:31


### Band Edge, Right Side



Date: 17.APR.2019 10:11:16


*EDR Mode ( $\pi/4$ -DQPSK):*

### Band Edge, Left Side




Date: 17.APR.2019 10:13:46

### Band Edge, Right Side




Date: 17.APR.2019 10:15:17

*EDR Mode (8-DPSK):*




*Hopping mode:  
BDR Mode (GFSK):*

### Band Edge, Left Side



Date: 17.APR.2019 10:18:43


### Band Edge, Right Side




Date: 17.APR.2019 10:28:04

*EDR Mode ( $\pi/4$ -DQPSK):*

### Band Edge, Left Side




### Band Edge, Right Side




*EDR Mode (8-DPSK):*

### Band Edge, Left Side



### Band Edge, Right Side



\*\*\*\*\* END OF REPORT \*\*\*\*\*