

TEST REPORT

Reference No...... : WTX24X07170578W002
FCC ID..... : 2ACGT-MSMB
Applicant..... : GUANGZHOU SHANGKE INFORMATION TECHNOLOGY CO., LTD
Address..... : Room 1205-1212, R&F To-Win Building, No.30 Huaxia Road, Tianhe District, Guangzhou, Guangdong Province, China
Manufacturer..... : The same as Applicant
Address..... : The same as Applicant
Product Name..... : PC Motherboard
Model No...... : MS-Challenger B760ITX D5 WIFI
Standards..... : FCC Part 15.247
Date of Receipt sample..... : 2024-07-19
Date of Test..... : 2024-07-19 to 2024-08-30
Date of Issue..... : 2024-08-30
Test Report Form No...... : WTX_Part 15_247W
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.


Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:



Mike Shi

Approved by:



Jason Su

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
1.2 TEST STANDARDS	6
1.3 TEST METHODOLOGY	6
1.4 TEST FACILITY	6
1.5 EUT SETUP AND TEST MODE	7
1.6 MEASUREMENT UNCERTAINTY	8
1.7 TEST EQUIPMENT LIST AND DETAILS	9
2. SUMMARY OF TEST RESULTS	12
3. ANTENNA REQUIREMENT	13
3.1 STANDARD APPLICABLE	13
3.2 EVALUATION INFORMATION	13
4. POWER SPECTRAL DENSITY	14
4.1 STANDARD APPLICABLE	14
4.2 TEST SETUP BLOCK DIAGRAM	14
4.3 TEST PROCEDURE	14
4.4 SUMMARY OF TEST RESULTS/PLOTS	14
5. DTS BANDWIDTH	15
5.1 STANDARD APPLICABLE	15
5.2 TEST SETUP BLOCK DIAGRAM	15
5.3 TEST PROCEDURE	15
5.4 SUMMARY OF TEST RESULTS/PLOTS	15
6. RF OUTPUT POWER	16
6.1 STANDARD APPLICABLE	16
6.2 TEST SETUP BLOCK DIAGRAM	16
6.3 TEST PROCEDURE	16
6.4 SUMMARY OF TEST RESULTS/PLOTS	16
7. FIELD STRENGTH OF SPURIOUS EMISSIONS	17
7.1 STANDARD APPLICABLE	17
7.2 TEST PROCEDURE	17
7.3 CORRECTED AMPLITUDE & MARGIN CALCULATION	19
7.4 SUMMARY OF TEST RESULTS/PLOTS	19
8. OUT OF BAND EMISSIONS	26
8.1 STANDARD APPLICABLE	26
8.2 TEST PROCEDURE	26
8.3 SUMMARY OF TEST RESULTS/PLOTS	27
9. CONDUCTED EMISSIONS	40
9.1 TEST PROCEDURE	40
9.2 BASIC TEST SETUP BLOCK DIAGRAM	40
9.3 TEST RECEIVER SETUP	40
9.4 SUMMARY OF TEST RESULTS/PLOTS	40
APPENDIX PHOTOGRAPHS	43

Report version

Version No.	Date of issue	Description
Rev.00	2024-08-30	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	PC Motherboard
Trade Name:	/
Model No.:	MS-Challenger B760ITX D5 WIFI
Adding Model(s):	MS-iCraft Z890 VERTEX, MS-iCraft Z890 ARCTIC, MS-iCraft Z890 PACIFIC, MS-Terminator Z890-A WIFI, MS-Terminator Z890M GKD5 WIFI, MS-Terminator Z890M GKD5 ICE, MS-iCraft Z890ITX WIFI, MS-ESPORT Z890M WIFI, MS-Challenger Z890M WIFI, MS-iCraft B860M CROSS, MS-Terminator B860M WIFI, MS-Terminator B860M WIFI6E, MS-Terminator B860M GKD5 WIFI, MS-Terminator B860M GKD5 ICE, MS-ESPORT B860M Sniper WIFI, MS-ESPORT B860M Gank WIFI, MS-ESPORT B860M ACE WIFI, MS-Challenger H810ITX WIFI, MS-Challenger B860BKB WIFI, MS-Terminator B860YTX WIFI, MS-Terminator B860ITX WIFI, MS-ESPORT H810M Gank WIFI, MS-Challenger H810ITX WIFI, MS-Terminator B850M WIFI, MS-Terminator B850ITX WIFI, MS-Challenger B850M WIFI ICE, MS-iCraft Z790 WiFi V2, MS-iCraft Z790ITX WIFI, MS-Terminator Z790-A WIFI6, MS-Terminator Z790M D5 ICE, MS-iCraft B760M CROSS, MS-Terminator B760M D5 WIFI6E, MS-Terminator H770YTX D5 WIFI, MS-Terminator B760M GKD5 ICE, MS-Terminator B760M D5 WIFI, MS-Terminator B760M D4 ICE, MS-Terminator B760M D4 WIFI6E, MS-Terminator B760M D4 WIFI, MS-Terminator B760ITX D4 WIFI V2, MS-Challenger B760M D5 WIFI, MS-B760M GAMING WIFI ACE, MS-B760M GAMING WIFI GANK, MS-Challenger H610ITX 2LAN, MS-H610M 666 WiFi6 D5, MS-H610M 666 WiFi6 ARGB, MS-H610M 666 WiFi6, MS-eSport B650M WIFI6 ICE, MS-eSport B650ITX WIFI ICE, MS-Terminator B650M WIFI6, MS-Challenger B650M WIFI ICE, MS-Challenger B650M WIFI, MS-Challenger A520M-K WIFI, MS-MoDT 12450H ITX WIFI F, MS-MoDT 12650H ITX WIFI F, MS-MoDT 13420H ITX WIFI F, MS-MoDT 13620H ITX WIFI F, ADV-MoDT 12450H ITX WIFI F, ADV-MoDT 12500H ITX WIFI F, ADV-MoDT 12600H ITX WIFI F, ADV-MoDT 12650H ITX WIFI F, ADV-MoDT 12700H ITX WIFI F, ADV-MoDT 12800H ITX WIFI F, ADV-MoDT 12900H ITX WIFI F, ADV-MoDT 12900HK ITX WIFI F, ADV-MoDT 13420H ITX WIFI F, ADV-MoDT 13500H ITX WIFI F, ADV-MoDT 13600H ITX WIFI F, ADV-MoDT 13620H ITX WIFI F, ADV-MoDT 13700H ITX WIFI F, ADV-MoDT 13800H ITX WIFI F,

	ADV-MoDT 13900H ITX WIFI F, ADV-MoDT 13900HK ITX WIFI F, ADV-MoDT 13420H ITX D5 F, ADV-MoDT 13500H ITX D5 F, ADV-MoDT 13600H ITX D5 F, ADV-MoDT 13620H ITX D5 F, ADV-MoDT 13700H ITX D5 F, ADV-MoDT 13800H ITX D5 F, ADV-MoDT 13900H ITX D5 F, ADV-MoDT 13900HK ITX D5 F, MS-MoDT ADL-P ITX WIFI F, ADV-MoDT ADL-P ITX WIFI F, ADV-MoDT RPL-P ITX D5, ADV-MoDT RPL-HX MATX D4, ADV-MoDT MTL-H ITX LPD5
Rated Voltage:	DC12V
Power Adapter Model:	/
<i>Note: The test data is gathered from a production sample provided by the manufacturer. The appearance of others models listed in the report is different from main-test model MS-Challenger B760ITX D5 WIFI, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n, 802.11ax
Frequency Range:	2412-2462MHz for 802.11b/g/n/ax(HT/HE20) 2422-2452MHz for 802.11n/ax(HT/HE40)
RF Output Power:	Antenna 0: 16.36dBm (Conducted) Antenna 1: 16.28dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Quantity of Channels:	11 for 802.11b/g/n/ax(HT/HE20); 7 for 802.11n/ax(HT/HE40)
Channel Separation:	5MHz
Type of Antenna:	External antenna
Antenna Gain:	3.13dBi
<i>Note The Antenna Gain is provided by the customer and can affect the validity of results.</i>	

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz.

558074 D01 15.247 Meas Guidance v05r02: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under section 15.247 of the Fcc rules.

662911 D01 Multiple Transmitter Output v02r01: Emissions Testing of Transmitters with Multiple Outputs in the Same Band.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 662911 D01 Multiple Transmitter Output v02r01.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM2	802.11g	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM3	802.11n-HT20	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM4	802.11ax-HE20	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM5	802.11n-HT40	Low:2422MHz, Middle:2437MHz,High:2452MHz
TM6	802.11ax-HT40	Low:2422MHz, Middle:2437MHz,High:2452MHz
Note: The 2.4GHz WIFI has two antennas and support Multiple Outputs for 802.11n/ac/ax mode for this report; Antenna 0 Gain is 3.13dBi; Antenna 1 Gain is 3.13dBi; For this function is belong to Correlated Categorization equipment According to KDB 662911, for same directional gain. Directional gain = $G_{ANT} + 10 \log(N_{ANT})$ dBi = $3.13 + 10 \log(2)$ dBi = 6.14dBi		

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	45~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
AC Cable	1.5	Unshielded	Without Ferrite

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Computer	/	/	/
Display	ASUS	VG28U	M9LMTF126416

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-26GHz $\pm 3.92\text{dB}$

1.7 Test Equipment List and Details

Fixed asset Number	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
WTXE1041A 1001	Communication Tester	Rohde & Schwarz	CMW500	148650	2024-02-24	2025-02-23
WTXE1005A 1005	Spectrum Analyzer	Agilent	N9020A	US471401 02	2024-03-19	2025-03-18
WTXE1084A 1001	Spectrum Analyzer	Agilent	N9020A	MY543205 48	2024-02-24	2025-02-23
WTXE1004A 1-001	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2024-02-27	2025-02-26
☐ Chamber A: Below 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2024-02-24	2025-02-23
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2024-03-19	2025-03-18
WTXE1007A 1001	Amplifier	HP	8447F	2805A034 75	2024-02-24	2025-02-23
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2025-02-25
WTXE1010A 1006	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2024-02-24	2025-02-23
☐ Chamber A: Above 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2024-02-24	2025-02-23
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2024-03-19	2025-03-18
WTXE1065A 1001	Amplifier	C&D	PAP-1G18	2002	2024-02-27	2025-02-26
WTXE1010A 1005	Horn Antenna	ETS	3117	00086197	2024-02-26	2025-02-25
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2025-03-16
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2024-02-29	2025-02-28
☐ Chamber B:Below 1GHz						
WTXE1010A 1006	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2024-03-17	2027-03-16
WTXE1038A 1001	Amplifier	Agilent	8447D	2944A104 57	2024-02-24	2025-02-23

WTXE1001A 1002	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2024-02-24	2025-02-23
☒ Chamber C: Below 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2024-02-27	2025-02-26
WTXE1010A 1013-1	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2024-04-18	2027-04-17
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2025-02-25
WTXE1007A 1002	Amplifier	HP	8447F	2944A038 69	2024-02-24	2025-02-23
☒ Chamber C: Above 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2024-02-27	2025-02-26
WTXE1103A 1005	Horn Antenna	POAM	RTF-118A	1820	2023-03-10	2026-03-09
WTXE1103A 1006	Amplifier	Tonscend	TAP01018050	AP22E806 235	2024-02-27	2025-02-26
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2025-03-16
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2024-02-29	2025-02-28
☐ Conducted Room 1#						
WTXE1104A 1029	EMI Test Receiver	Rohde & Schwarz	ESCI	100525	2023-12-12	2024-12-11
WTXE1002A 1001	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2024-02-24	2025-02-23
WTXE1003A 1001	AC LISN	Schwarz beck	NSLK8126	8126-279	2024-02-24	2025-02-23
☒ Conducted Room 2#						
WTXE1001A 1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2024-02-24	2025-02-23
WTXE1003A 1003	LISN	Rohde & Schwarz	ENV 216	100097	2024-02-24	2025-02-23

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission Room 1#)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission Room 2#)*	SKET	EMC-I	V2.0

*Remark: indicates software version used in the compliance certification testing.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203; §15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	DTS Bandwidth	Compliant
§15.247(b)(3)	RF Output Power	Compliant
§15.209(a)	Radiated Emission	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: Not applicable.

3. Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Evaluation Information

This product has two External antennas, fulfill the requirement of this section.

4. Power Spectral Density

4.1 Standard Applicable

According to 15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

4.2 Test Setup Block Diagram



4.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.10.3, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{kHz}$.
- Set VBW $\geq 3 \times \text{RBW}$.
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$.
- Sweep time = auto couple.
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.
- If measured value exceeds limit, reduce RBW (no less than 3kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

4.4 Summary of Test Results/Plots

Please refer to Appendix D

5. DTS Bandwidth

5.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928MHz, 2400–2483.5MHz, and 5725–5850MHz bands. The minimum 6dB bandwidth shall be at least 500kHz.

5.2 Test Setup Block Diagram



5.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:

- a) Set RBW = 100kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

5.4 Summary of Test Results/Plots


Please refer to Appendix A

6. RF Output Power

6.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928MHz, 2400–2483.5MHz, and 5725–5850MHz bands: 1 Watt.

6.2 Test Setup Block Diagram



6.3 Test Procedure

According to the KDB-558074 D01 v05r02 Subclause 8.3.2.2 and ANSI C63.10-2013 Subclause 11.9.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth

- Set span to at least 1.5 times the OBW.
- Set RBW = 1-5% of the OBW, not to exceed 1MHz.
- Set VBW $\geq 3 \times$ RBW.
- Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$. (This gives bin-to-bin spacing $\leq \text{RBW}/2$, so that narrowband signals are not lost between frequency bins.)
- Sweep time = auto.
- Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- If transmit duty cycle $< 98\%$, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run”.
- Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

6.4 Summary of Test Results/Plots

Please refer to Appendix C

7. Field Strength of Spurious Emissions

7.1 Standard Applicable

According to §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

7.2 Test Procedure


The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1GHz.



Frequency :9kHz-30MHz	Frequency :30MHz-1GHz	Frequency :Above 1GHz
RBW=10KHz,	RBW=120KHz,	RBW=1MHz,
VBW =30KHz	VBW=300KHz	VBW=3MHz(Peak), 10Hz(AV)
Sweep time= Auto	Sweep time= Auto	Sweep time= Auto
Trace = max hold	Trace = max hold	Trace = max hold
Detector function = peak	Detector function = peak, QP	Detector function = peak, AV

7.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

7.4 Summary of Test Results/Plots

*Note: 1.This EUT was tested in 3 orthogonal positions and the worst case position data was reported.
All test modes (different data rate and different modulation) are performed, but only the worst case(802.11b_11Mbps) is recorded in this report.*


- Spurious Emissions Below 1GHz
- Antenna 0

802.11b_11Mbps(worst case)			
Test Channel	Low(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	45.4131	29.08	-7.92	21.16	40.00	-18.84	-	-	peak
2	116.4476	38.78	-10.39	28.39	43.50	-15.11	-	-	peak
3	171.3890	31.79	-8.51	23.28	43.50	-20.22	-	-	peak
4	259.4434	40.62	-9.31	31.31	46.00	-14.69	-	-	peak
5	355.9397	36.54	-6.95	29.59	46.00	-16.41	-	-	peak
6	739.2136	33.33	-0.09	33.24	46.00	-12.76	-	-	peak

802.11b_11Mbps			
Test Channel	Low(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	32.4109	45.43	-9.34	36.09	40.00	-3.91	-	-	peak
2	42.0350	41.72	-7.95	33.77	40.00	-6.23	-	-	peak
3	101.8932	46.03	-11.82	34.21	43.50	-9.29	-	-	peak
4	116.4476	46.54	-10.39	36.15	43.50	-7.35	-	-	peak
5	172.5976	44.04	-8.68	35.36	43.50	-8.14	-	-	peak
6	373.8862	33.65	-6.62	27.03	46.00	-18.97	-	-	peak

➤ Antenna 1

802.11b_11Mbps(worst case)


Test Channel	Low(worst case)	Polarity:	Horizontal
--------------	-----------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	115.6322	38.71	-10.47	28.24	43.50	-15.26	-	-	peak
2	171.3890	36.67	-8.51	28.16	43.50	-15.34	-	-	peak
3	257.6266	37.69	-9.38	28.31	46.00	-17.69	-	-	peak
4	353.4472	34.37	-7.00	27.37	46.00	-18.63	-	-	peak
5	403.9335	35.70	-6.18	29.52	46.00	-16.48	-	-	peak
6	793.0281	31.38	0.88	32.26	46.00	-13.74	-	-	peak

802.11b_11Mbps(worst case)

Test Channel	Low(worst case)	Polarity:	Vertical
--------------	-----------------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	39.4588	38.12	-8.07	30.05	40.00	-9.95	-	-	peak
2	96.3230	43.21	-12.21	31.00	43.50	-12.50	-	-	peak
3	116.4476	44.71	-10.39	34.32	43.50	-9.18	-	-	peak
4	171.3890	41.22	-8.51	32.71	43.50	-10.79	-	-	peak
5	421.3287	31.11	-5.81	25.30	46.00	-20.70	-	-	peak
6	925.6132	32.59	2.72	35.31	46.00	-10.69	-	-	peak

Remark: '-' Means the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

- Spurious Emissions Above 1GHz
- Test Mode: 802.11b_11Mbps (worst case)
- Antenna 0

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2412MHz							
4824.000	60.00	-12.64	47.36	74	-26.64	H	PK
7236.000	58.01	-6.29	51.72	74	-22.28	H	PK
4824.000	60.49	-12.64	47.85	74	-26.15	V	PK
7236.000	58.81	-6.29	52.52	74	-21.48	V	PK
Middle Channel-2437MHz							
4874.000	60.79	-12.58	48.21	74	-25.79	H	PK
7311.000	58.34	-6.48	51.86	74	-22.14	H	PK
4874.000	60.98	-12.58	48.4	74	-25.6	V	PK
7311.000	58.2	-6.48	51.72	74	-22.28	V	PK
High Channel-2462MHz							
4924.000	60.53	-12.5	48.03	74	-25.97	H	PK
7386.000	58.35	-6.68	51.67	74	-22.33	H	PK
4924.000	60.75	-12.5	48.25	74	-25.75	V	PK
7386.000	58.14	-6.68	51.46	74	-22.54	V	PK

- Spurious Emissions Above 1GHz
- Test Mode: 802.11b_11Mbps (worst case)
- Antenna 1

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2412MHz							
4824.000	60.00	-12.64	47.36	74	-26.64	H	PK
7236.000	58.01	-6.29	51.72	74	-22.28	H	PK
4824.000	60.49	-12.64	47.85	74	-26.15	V	PK
7236.000	58.81	-6.29	52.52	74	-21.48	V	PK
Middle Channel-2437MHz							
4874.000	60.79	-12.58	48.21	74	-25.79	H	PK
7311.000	58.34	-6.48	51.86	74	-22.14	H	PK
4874.000	60.98	-12.58	48.4	74	-25.6	V	PK
7311.000	58.2	-6.48	51.72	74	-22.28	V	PK
High Channel-2462MHz							
4924.000	60.53	-12.5	48.03	74	-25.97	H	PK
7386.000	58.35	-6.68	51.67	74	-22.33	H	PK
4924.000	60.75	-12.5	48.25	74	-25.75	V	PK
7386.000	58.14	-6.68	51.46	74	-22.54	V	PK

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

8. Out of Band Emissions

8.1 Standard Applicable

According to §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

8.2 Test Procedure

According to the KDB 558074D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission

must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9.
- b) VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

Table 9—RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1000 MHz	100 kHz to 120 kHz
>1000 MHz	1 MHz


If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

8.3 Summary of Test Results/Plots


- Radiated test
- Antenna 0(worst case)

802.11b_11Mbps			
Test Channel	Low	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.36	0.33	43.69	54.00	-10.31	Average Detector
	2310.000	56.17	0.33	56.50	74.00	-17.50	Peak Detector
2	2390.000	44.76	0.51	45.27	54.00	-8.73	Average Detector
	2390.000	56.53	0.51	57.04	74.00	-16.96	Peak Detector
3	2412.926	103.13	0.56	103.69	/	/	Average Detector
	2413.407	107.82	0.56	108.38	/	/	Peak Detector

802.11b_11Mbps			
Test Channel	High	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2462.725	102.16	0.67	102.83	/	/	Average Detector
	2463.427	106.79	0.67	107.46	/	/	Peak Detector
2	2483.500	43.96	0.71	44.67	54.00	-9.33	Average Detector
	2483.500	55.56	0.71	56.27	74.00	-17.73	Peak Detector
3	2500.000	43.74	0.75	44.49	54.00	-9.51	Average Detector
	2500.000	55.29	0.75	56.04	74.00	-17.96	Peak Detector

802.11g_54Mbps			
Test Channel	Low	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.42	0.33	43.75	54.00	-10.25	Average Detector
	2310.000	54.96	0.33	55.29	74.00	-18.71	Peak Detector
2	2390.000	44.85	0.51	45.36	54.00	-8.64	Average Detector
	2390.000	58.44	0.51	58.95	74.00	-15.05	Peak Detector
3	2414.369	100.06	0.56	100.62	/	/	Average Detector
	2415.090	110.52	0.56	111.08	/	/	Peak Detector

802.11g_54Mbps			
Test Channel	High	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2465.030	98.77	0.66	99.43	/	/	Average Detector
	2463.828	109.75	0.67	110.42	/	/	Peak Detector
2	2483.500	44.00	0.71	44.71	54.00	-9.29	Average Detector
	2483.500	56.61	0.71	57.32	74.00	-16.68	Peak Detector
3	2500.000	43.57	0.75	44.32	54.00	-9.68	Average Detector
	2500.000	55.47	0.75	56.22	74.00	-17.78	Peak Detector

➤ Antenna 0+Antenna1


802.11n-HT20_MCS7

Test Channel	Low	Polarity:	Horizontal(worst case)
--------------	-----	-----------	------------------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.51	0.33	43.84	54.00	-10.16	Average Detector
	2310.000	55.96	0.33	56.29	74.00	-17.71	Peak Detector
2	2390.000	45.33	0.51	45.84	54.00	-8.16	Average Detector
	2390.000	56.85	0.51	57.36	74.00	-16.64	Peak Detector
3	2414.850	99.81	0.56	100.37	/	/	Average Detector
	2414.609	110.40	0.56	110.96	/	/	Peak Detector

802.11n-HT20_MCS7			
Test Channel	High	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2464.429	98.64	0.66	99.30	/	/	Average Detector
	2465.531	109.56	0.66	110.22	/	/	Peak Detector
2	2483.500	44.26	0.71	44.97	54.00	-9.03	Average Detector
	2483.500	56.48	0.71	57.19	74.00	-16.81	Peak Detector
3	2500.000	43.63	0.75	44.38	54.00	-9.62	Average Detector
	2500.000	56.22	0.75	56.97	74.00	-17.03	Peak Detector

802.11ax-HE20_MCS7			
Test Channel	Low	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.45	0.33	43.78	54.00	-10.22	Average Detector
	2310.000	54.90	0.33	55.23	74.00	-18.77	Peak Detector
2	2390.000	45.27	0.51	45.78	54.00	-8.22	Average Detector
	2390.000	57.68	0.51	58.19	74.00	-15.81	Peak Detector
3	2415.090	99.34	0.56	99.90	/	/	Average Detector
	2415.090	112.36	0.56	112.92	/	/	Peak Detector

802.11ax-HE20_MCS7			
Test Channel	High	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2464.128	98.00	0.67	98.67	/	/	Average Detector
	2463.126	111.09	0.67	111.76	/	/	Peak Detector
2	2483.500	44.21	0.71	44.92	54.00	-9.08	Average Detector
	2483.500	56.26	0.71	56.97	74.00	-17.03	Peak Detector
3	2500.000	43.19	0.75	43.94	54.00	-10.06	Average Detector
	2500.000	55.77	0.75	56.52	74.00	-17.48	Peak Detector

802.11n-HT40_MCS7			
Test Channel	Low	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.30	0.33	43.63	54.00	-10.37	Average Detector
	2310.000	55.56	0.33	55.89	74.00	-18.11	Peak Detector
2	2390.000	45.06	0.51	45.57	54.00	-8.43	Average Detector
	2390.000	57.45	0.51	57.96	74.00	-16.04	Peak Detector
3	2418.577	95.82	0.57	96.39	/	/	Average Detector
	2416.052	107.36	0.57	107.93	/	/	Peak Detector

802.11n-HT40_MCS7			
Test Channel	High	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2441.222	95.77	0.62	96.39	/	/	Average Detector
	2441.924	106.89	0.62	107.51	/	/	Peak Detector
2	2483.500	47.02	0.71	47.73	54.00	-6.27	Average Detector
	2483.500	58.91	0.71	59.62	74.00	-14.38	Peak Detector
3	2500.000	44.52	0.75	45.27	54.00	-8.73	Average Detector
	2500.000	56.59	0.75	57.34	74.00	-16.66	Peak Detector

802.11ax-HE40_MCS7			
Test Channel	Low	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.50	0.33	43.83	54.00	-10.17	Average Detector
	2310.000	55.57	0.33	55.90	74.00	-18.10	Peak Detector
2	2390.000	44.95	0.51	45.46	54.00	-8.54	Average Detector
	2390.000	57.21	0.51	57.72	74.00	-16.28	Peak Detector
3	2418.016	95.51	0.57	96.08	/	/	Average Detector
	2412.685	109.08	0.56	109.64	/	/	Peak Detector

802.11ax-HE40_MCS7			
Test Channel	High	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2443.327	95.20	0.63	95.83	/	/	Average Detector
	2441.082	108.59	0.62	109.21	/	/	Peak Detector
2	2483.500	45.72	0.71	46.43	54.00	-7.57	Average Detector
	2483.500	60.18	0.71	60.89	74.00	-13.11	Peak Detector
3	2500.000	44.32	0.75	45.07	54.00	-8.93	Average Detector
	2500.000	58.59	0.75	59.34	74.00	-14.66	Peak Detector

➤ Conducted test
Please refer to Appendix G


9. Conducted Emissions

9.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

9.2 Basic Test Setup Block Diagram




9.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency.....	150kHz
Stop Frequency.....	30MHz
Sweep Speed.....	Auto
IF Bandwidth.....	10kHz
Quasi-Peak Adapter Bandwidth.....	9kHz
Quasi-Peak Adapter Mode.....	Normal


9.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Delta dB	Detector
1	210.000kHz	27.8	9.5	37.3	63.2	-25.9	QP
2	522.000kHz	31.7	9.7	41.4	56.0	-14.6	QP
3	1.114MHz	29.0	9.6	38.6	56.0	-17.4	QP
4	4.894MHz	32.4	9.6	42.0	56.0	-14.0	QP
5	6.454MHz	34.5	9.7	44.2	60.0	-15.8	QP
6	11.730MHz	30.2	9.8	40.0	60.0	-20.0	QP
7*	226.000kHz	27.0	9.6	36.6	52.6	-15.9	AV
8*	374.000kHz	27.3	9.6	36.9	48.4	-11.5	AV
9*	514.000kHz	27.6	9.7	37.3	46.0	-8.7	AV
10*	654.000kHz	28.4	9.7	38.1	46.0	-7.9	AV
11*	4.470MHz	28.7	9.6	38.3	46.0	-7.7	AV
12*	6.454MHz	33.2	9.7	42.9	50.0	-7.1	AV

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Delta dB	Detector
1	226.000kHz	28.5	9.6	38.1	62.6	-24.5	QP
2	378.000kHz	29.5	9.6	39.1	58.3	-19.3	QP
3	682.000kHz	29.9	9.7	39.6	56.0	-16.4	QP
4	1.114MHz	26.1	9.6	35.7	56.0	-20.3	QP
5	4.038MHz	32.8	9.6	42.4	56.0	-13.6	QP
6	12.706MHz	29.2	9.8	39.0	60.0	-21.0	QP
7*	226.000kHz	27.2	9.6	36.8	52.6	-15.8	AV
8*	382.000kHz	29.9	9.6	39.5	48.2	-8.7	AV
9*	666.000kHz	24.6	9.7	34.3	46.0	-11.7	AV
10*	3.478MHz	27.5	9.6	37.1	46.0	-8.9	AV
11*	6.458MHz	32.3	9.7	42.0	50.0	-8.0	AV
12*	7.450MHz	32.1	9.7	41.8	50.0	-8.2	AV

APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

***** END OF REPORT *****