



CH9




CH12




Peak Power Output


CH 1




CH4




CH5




CH8



CH9



CH12



6.4 PEAK POWER EXCURSION MEASUREMENT

6.4.1 LIMITS OF PEAK POWER EXCURSION MEASUREMENT

FREQUENCY BAND	LIMIT
5.15 – 5.25GHz	13dB
5.25 – 5.35GHz	13dB
5.725 – 5.825GHz	13dB

6.4.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug.12, 2004

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


6.4.3 TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer.
2. Set the spectrum bandwidth span to view the entire spectrum.
3. Using peak detector and Max-hold function for Trace 1 (RB=1MHz, VB=3MHz) and 2 (RB=1MHz, VB=300kHz).
4. The largest difference between Trace 1 and Trace 2 in any 1MHz band on any frequency was recorded.

6.4.4 DEVIATION FROM TEST STANDARD

No deviation

6.4.5 TEST SETUP



6.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.




6.4.7 TEST RESULTS


EUT	Wireless LAN 11a/g mini-PCI Adapter	MODEL	WMIB-111AG
ENVIRONMENTAL CONDITIONS	25deg.C, 60%RH, 991hPa	INPUT POWER (SYSTEM)	120Vac, 60Hz
TESTED BY: Steven Lu			

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER EXCURSION (dB)	PEAK to AVERAGE EXCURSION LIMIT (dB)	PASS/FAIL
1	5180	6.99	13	PASS
4	5240	6.82	13	PASS
5	5260	6.74	13	PASS
8	5320	7.49	13	PASS
9	5745	6.41	13	PASS
12	5805	6.68	13	PASS


CH1




CH4




CH 5




CH 8



CH 9



CH 12



6.5 PEAK POWER SPECTRAL DENSITY MEASUREMENT

6.5.1 LIMITS OF PEAK POWER SPECTRAL DENSITY MEASUREMENT

FREQUENCY BAND	LIMIT
5.15 – 5.25GHz	4dBm
5.25 – 5.35GHz	11dBm
5.725 – 5.825GHz	17dBm

6.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug.12, 2004
SPECTRUM ANALYZER	8564EC	4208A00660	Nov. 20, 2003

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

6.5.3 TEST PROCEDURES

1. The transmitter output was connected to the spectrum analyzer.
2. Set RBW=1MHz, VBW=3MHz. The PPSD is the highest level found across the emission in any 1MHz band.

6.5.4 DEVIATION FROM TEST STANDARD

No deviation

6.5.5 TEST SETUP



6.5.6 EUT OPERATING CONDITIONS

Same as 5.3.6



6.5.7 TEST RESULTS

EUT	Wireless LAN 11a/g mini-PCI Adapter	MODEL	WMIB-111AG
ENVIRONMENTAL CONDITIONS	25deg.C, 60%RH, 991hPa	INPUT POWER (SYSTEM)	120Vac, 60Hz
TESTED BY: Steven Lu			

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 1MHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	5180	-1.95	4	PASS
4	5240	-2.10	4	PASS
5	5260	-2.70	11	PASS
8	5320	-2.10	11	PASS
9	5745	-2.34	17	PASS
12	5805	-2.36	17	PASS