

47 C.F.R. Part 1, Subpart I, Section 1.1310
47 C.F.R. Part 2, Subpart J, Section 2.1091
Maximum Permissible Exposure Calculations

FCC ID: OMD803-001

EUT Device Category = General Population/Uncontrolled Exposure

EUT consists of one radio transmitting operating at a frequency of:
72.10 MHz, 72.9 MHz, or 75.9 MHz

MPE Summary:

According subpart 1.1307 (b)(1) and 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure					
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (Minutes)	
0.3-1.34	614	1.63	*(100)	30	
1.34-30	824/f	2.19/f	*(180/f ²)	30	
30-300	27.5	0.073	0.2	30	
300-1500	/	/	f/1500	30	
1500-100,000	/	/	1.0	30	

f = frequency in MHz; * = Plane-wave equivalent power density

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

PG = EIRP

MPE and Limit are calculated as follows:

f (MHz)	Field Strength (dBuV/m)	EIRP (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Δ
72.1	96.0	1.19	0.000237	0.2	0.1998
75.9	93.6	0.69	0.000137	0.2	0.1999

Result: The device meets FCC MPE limit at 20 cm for General Population/Uncontrolled Exposure as specified in 47 CFR §1.1310 and §2.1091.