

FCC PART 22 and 90 TEST REPORT

For

Sepura plc

Radio House, St. Andrews Road, Cambridge CB4 1GR UK

FCC ID: XX6SER8040

Report Type: Class II permissive change		Product Type: DMR Repeater	
Test Engineer:	Dean Liu		Dean Lau
Report Number:	RDG150921004	4-00A1	
Report Date:	2015-11-16		
Reviewed By:	Sula Huang RF Leader		Solo Hugh
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn		orp. (Dongguan) Zone, na

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

Bay Area Compliance Laboratories Corp. (Dongguan)

TABLE OF CONTENTS

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
Objective	3
RELATED SUBMITTAL(S)/GRANT(S)	3
Test Methodology	3
Test Facility	4
SYSTEM TEST CONFIGURATION	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
SUMMARY OF TEST RESULTS	6
ECC 81 1210 MAVIMUM DEDMISSIDI E EVDOSUDE (MDE)	7
FCC §1.1510 - MAAIMUMI FERMISSIBLE EAFOSURE (MFE)	
APPLICABLE STANDARD	7
FCC §1.1510 - MAXIMUM FERMISSIBLE EXPOSURE (MFE) APPLICABLE STANDARD	
APPLICABLE STANDARD	
FCC §1.1510 - MAAIMUM FERMISSIBLE EAFOSURE (MFE) Applicable Standard FCC §2.1046 &§ 22.727 & §90.205- RF OUTPUT POWER Applicable Standard Test Procedure	
FCC §1.1510 - MAXIMUM FERMISSIBLE EXPOSURE (MFE) APPLICABLE STANDARD FCC §2.1046 &§ 22.727 & §90.205- RF OUTPUT POWER APPLICABLE STANDARD Test Procedure Test Equipment List and Details	7
FCC §1.1510 - MAAIMUM FERMISSIBLE EAFOSURE (MFE) APPLICABLE STANDARD FCC §2.1046 &§ 22.727 & §90.205- RF OUTPUT POWER APPLICABLE STANDARD Test Procedure Test Equipment List and Details Test Data	
FCC §1.1510 - MAXIMUM FERMISSIBLE EXFOSURE (MFE) APPLICABLE STANDARD FCC §2.1046 &§ 22.727 & §90.205- RF OUTPUT POWER APPLICABLE STANDARD Test Procedure Test Procedure Test Equipment List and Details Test Data FCC §2.1049& §22.357 & § 22.731 &§90.209 & §90.210 – OCCUPIED BANDWIDTH & EMISSIO	7
 FCC §1.1510 - MAXIMUM FERMISSIBLE EXFOSURE (MFE)	7
FCC §1.1510 - MAXIMUM FERMISSIBLE EXFOSURE (MFE) APPLICABLE STANDARD FCC §2.1046 &§ 22.727 & §90.205- RF OUTPUT POWER APPLICABLE STANDARD TEST PROCEDURE TEST PROCEDURE TEST EQUIPMENT LIST AND DETAILS TEST DATA FCC §2.1049& §22.357 & § 22.731 &§90.209 & §90.210 – OCCUPIED BANDWIDTH & EMISSIO APPLICABLE STANDARD TEST EQUIPMENT LIST AND DETAILS	7
FCC §1.1510 - MAXIMUM FERMISSIBLE EXFOSURE (MFE) APPLICABLE STANDARD FCC §2.1046 &§ 22.727 & §90.205- RF OUTPUT POWER APPLICABLE STANDARD TEST PROCEDURE TEST EQUIPMENT LIST AND DETAILS TEST DATA FCC §2.1049& §22.357 & § 22.731 &§90.209 & §90.210 – OCCUPIED BANDWIDTH & EMISSIO APPLICABLE STANDARD TEST EQUIPMENT LIST AND DETAILS TEST DATA	7

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

Sepura plc's product, model number: SER8040 (*FCC ID: XX6SER8040*) the "EUT" in this report is a *DMR Repeater*, which was measured approximately:48.5 cm(L) x 33.5 cm (W) x 13.0 cm(H), rated input voltage: 120 VAC or 13.6 VDC.

* All measurement and test data in this report was gathered from production sample serial number: 7PR531538GE0016(assigned by applicant). The EUT was received on 2015-09-24.

Objective

This test report is prepared on behalf of *Sepura plc* in accordance with Part 2, and Part 90 of the Federal Communications Commission rules.

This is the CIIPC application of the device. The difference between the original device and new device is as follows:

1. Adding the low power level 5W.

2. Updated the emission designator.

3. Updated MPE evaluation

Please refer to the Permissive Change Declaration Letter.

According to the changes, it will impact the test results of RF power output and Occupied bandwidth&Emission mask, so in this report, we update the test data of RF power output & Occupied bandwidth&Emission mask and updated MPE evaluation.

Related Submittal(s)/Grant(s)

Original submission with FCC ID: XX6SER8040 which is granted on 2014-06-25.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of federal Regulations Title 47 Part 2, Sub-part J as well as the following individual parts:

Part 22 – Public Mobile Service Part 90 – Private Land Mobile Radio Service

Applicable Standards: TIA-603-D.

Bay Area Compliance Laboratories Corp. (Dongguan)

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 05, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a test mode.

Specfication:

Operating Frequency Band	400-470MHz
Modulation Mode	FM/4FSK
Channel Spacing	12.5 kHz
Conducted Output Power	High power level:40W; Low power level:5W

Equipment Modifications

No modifications were made to the unit tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
FCC §1.1310	Maximum Permissible Expoure(MPE)	Compliance
\$2.1046; \$ 22.727;\$90.205	RF Output Power	Compliance
§2.1047;§90.207	Modulation Characteristic	Compliance*
§2.1049;§22.357;§ 22. 731;§90.209; §90.210	Occupied Bandwidth & Emission Mask	Compliance
\$2.1051; \$22.861;\$90.210	Spurious Emission at Antenna Terminal	Compliance*
\$2.1053; \$22.861;\$90.210	Spurious Radiated Emissions	Compliance*
\$2.1055; \$ 22.355;\$90.213	Frequency Stability	Compliance*
§90.214	Transient Frequency Behavior	Compliance*

Compliance*: Please refer to the report number R2DG13115009-00 granted on 2014-06-25, with FCC ID: XX6SER8040.

FCC §1.1310 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to 1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for Occupational/Controlled Exposure					
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E , H or S (minutes)	
0.3-3.0	614	1.63	(100)*	6	
3.0 - 30	1842/f	4.89/f	$(900/f^2)^*$	6	
30-300	61.4	0.163	1.0	6	
300-1500	/	/	f/300	6	
1500-100,000	/	/	5	6	

f = frequency in MHz

* = Plane-wave equivalent power density

MPE Calculation

Predication of MPE limit at a given distance

 $S = PG/4\pi R^2$

Where: S = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Frequency	Max Target Output Power	Typical Antenna Gain		Distance	Power Density	Limits
MHz	mW	dBi	numeric	cm	mW/cm2	mW/cm ²
435	43000	0	1.0	49	1.43	1.45

Radio Exposure Statement:

Using the parameters given in the above calculation, a minimum antenna to person distance of 49 cm is required to meet the limits for occupational/controlled exposure.

Result: Compliance

FCC §2.1046 &§ 22.727 & §90.205- RF OUTPUT POWER

Applicable Standard

FCC §2.1046, § 22.727 and §90.205.

Test Procedure

Conducted RF Output Power:

TIA-603-D section 2.2.1

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

Spectrum Analyzer setting:

RBW	Video B/W
100 kHz	300 kHz

Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSEM	DE31388	201505-07	2016-05-06
Weinschel Corp	Attenuator(20dB)	53-20-34	LN749	2015-05-08	2016-05-08
AA-MCS	Attenuator(40dB)	CAT-50-40- 200-Nm-Nf	0602-010	2015-05-08	2016-05-08
E-Microwave	DC Blocking	EMDCB- 00036	0E01201047	2015-05-06	2016-05-06

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	23.8 °C
Relative Humidity:	40 %
ATM Pressure:	101.2 kPa

The testing was performed by Dean Liu on 2015-09-26.

Bay Area Compliance Laboratories Corp. (Dongguan)

Test Mode: Transmitting

Test Result: Compliance.

Please refer to following tables.

FCC Part 90:

Modulation Mode	Channel Speeing	f _c	Conducted	Output Power W)
	Channel Spacing	MHz	Low Power Level	High Power Level
FM		400.0125	5.03	39.45
	12 5 1 11	435	5.07	39.54
		469.9875	5.01	39.63
4FSK	12.3 KHZ	400.0125	5.04	39.36
		435	5.08	39.45
		469.9875	5.05	39.26

FCC Part 22:

Modulation Mode	Channel Speeing	f _c	Conducted Output Power (W) Low Power Level Level		
	Channel Spacing	MHz	Low Power Level High Powe Level		
FM	12 5 1 11	458	5.04	39.36	
4FSK	12.3 KHZ	458	5.02	39.54	

FCC §2.1049& §22.357 & § 22.731 & §90.209 & §90.210 – OCCUPIED BANDWIDTH & EMISSION MASK

Applicable Standard

FCC §2.1049, §22.357, § 22.731, §90.209 and §90.210

Frequency band (MHz)	Mask for equipment with audio low pass filter	Mask for equipment without audio low pass filter
Below 25	A or B	A or C
25-50	В	С
72-76	В	С
150-174	B, D, or E	C, D or E
150 paging only	В	С
220-222	F	F
421-512	B, D, or E	C, D, or E
450 paging only	В	G
806-809/851-854	В	Н
809-824/854-869	В	G
896-901/935-940	I	J
902-928	K	K
929-930	В	G
4940-4990 MHz	L or M	L or M
5850-5925		
All other bands	В	С

Emission Mask D—12.5 kHz channel bandwidth equipment. For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

(1) On any frequency from the center of the authorized bandwidth f0 to 5.625 kHz removed from f0: Zero dB.

(2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 5.625 kHz but no more than 12.5 kHz: At least 7.27(fd-2.88 kHz) dB.

(3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 12.5 kHz: At least $50 + 10 \log (P) dB$ or 70 dB, whichever is the lesser attenuation.

(4) The reference level for showing compliance with the emission mask shall be established using a resolution bandwidth sufficiently wide (usually two or three times the channel bandwidth) to capture the true peak emission of the equipment under test. In order to show compliance with the emission mask up to and including 50 kHz removed from the edge of the authorized bandwidth, adjust the resolution bandwidth to 100 Hz with the measuring instrument in a peak hold mode. A sufficient number of sweeps must be measured to insure that the emission profile is developed. If video filtering is used, its bandwidth must not be less than the instrument resolution bandwidth. For emissions beyond 50 kHz from the edge of the authorized bandwidth, see paragraph (o) of this section. If it can be shown that use of the above instrumentation settings do not accurately represent the true interference potential of the equipment under test, an alternate procedure may be used provided prior Commission approval is obtained.

FCC Part 22 and 90

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09
Mini-Circuits	Attenuator	UNAT-10 ⁺	15542	2015-05-06	2016-05-06
Weinschel Corp	Attenuator(20dB)	53-20-34	LN749	2015-05-08	2016-05-08
AA-MCS	Attenuator(40dB)	CAT-50-40- 200-Nm-Nf	0602-010	2015-05-08	2016-05-08
E-Microwave	DC Blocking	EMDCB- 00036	0E01201047	2015-05-06	2016-05-06
Pasternack	RF Coaxial Cable	RF-01(30cm)	/	2015-05-06	2016-05-06
Pasternack	RF Coaxial Cable	RF-02(30cm)	/	2015-05-06	2016-05-06

Test Equipment List and Details

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.8~27.1°C		
Relative Humidity:	51~59 %		
ATM Pressure:	99.8~101.1 kPa		

The testing was performed by Dean Liu from 2015-09-28 to 2015-10-09.

FCC Part 90:

Modulation	Channel Spacing	f _c	99% Occupied Bandwidth (kHz)		f _c 99% Occupied Bandwidth 26 dB Band (kHz) (kHz)		ndwidth Hz)
Mode	kHz MHz		Lowest Power Level	Highest Power Level	Lowest Power Level	Highest Power Level	
FM	12.5	435	10.10	10.10	10.30	10.40	
4FSK		435	7.40	7.40	9.80	10.00	

FCC Part 22:

Modulation	Channel Spacing	f _c	99% Occupied Bandwidth (kHz)		99% Occupied Bandwidth (kHz) 26 dB Bandwidth (kHz)	
Mode	kHz	MHz	Lowest Power Level	Highest Power Level	Lowest Power Level	Highest Power Level
FM	12.5	458	10.00	9.90	10.30	10.30
4FSK		458	7.30	7.30	9.80	9.90

Emission Designator

Per CFR 47 §2.201& §2.202&, Bn = 2M + 2D

For FM Mode (Channel Spacing: 12.5 kHz)

Emission Designator 11K0F3E In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation. $BW = 2(M+D) = 2*(3.0 \text{ kHz} + 2.5 \text{ kHz}) = 11 \text{ kHz} = \rightarrow 11K0$ F3E portion of the designator represents an FM voice transmission Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.

For Digital Mode (Channel Spacing: 12.5 kHz)

Emission Designator 7K60FXD and 7K60FXW

The 99% energy rule (title 47CFR 2.1049) was used for digital mode. It basically states that 99% of the modulation energy falls within X kHz, in this case, 7.40 kHz. The emission mask was obtained from 47CFR 90.210(d).

FXD and FXW portion of the designator indicates digital information.

Therefore, the entire designator for 12.5 kHz channel spacing digital mode is 7K60FXD and 7K60FXW.

Lowest Power Level:



FCC Part 22 and 90

Page 13 of 18



Occupied Bandwidth, 435 MHz, 4FSK mode

FCC Part 22 and 90

Page 14 of 18



PART 22

FCC Part 22 and 90

Page 15 of 18

Highest Power Level:



PART 90

Date: 9.0CT.2015 18:24:19

FCC Part 22 and 90

Page 16 of 18



Occupied Bandwidth, 435 MHz, 4FSK mode

FCC Part 22 and 90

Page 17 of 18

DELTA MARKER 1 Delta 1 [T1] *RBW 100 Hz . 2.57 dB 10.3 kHz Ref 50 dBm *VBW 1 kHz SWT 6 s *Att 40 dB 10.30000000 kHz OBW 9.900000000 kHz Marker 1 [T1 50 Offset 41 dB D1 44.54 dBm 14 21 dBn A. 40 457.995100000 MHz 1 PK Maxh Temp 1 [T1 OBW] 457.995300000 MHz Temp 2 [T1 OBW] 20 - 54 458.005200000 MHz SDB a, N w 6 www.hundulharm ykindum Mighten with 40 50 Center 458 MHz 5 kHz/ Span 50 kHz 9.0CT.2015 18:28:00 Date: Occupied Bandwidth, 458MHz, 4FSK mode DELTA MARKER 1 *RBW 100 Hz Delta 1 [T1] X -0.85 dB 9.9 kHz •VBW 1 kHz Ref 50 dBm *Att 40 dB SWT 6 s 9.900000000 kHz 50 Offset 41 dB OBW 7.300000000 kHz Marker 1 (T1 41. 40 14 08 dBr 457.995300000 MHz 1 PK MAXH [T1 OBW] Temp 1 457.996600000 MHz Temp 2 [T1 OBW] 29.67 dBm -D2 15.24 dE 458.003900000 MHz 3DB aly all a second and a second a Wilmy Minter an Willow 4(50 Center 458 MHz 5 kHz/ Span 50 kHz 9.0CT.2015 17:56:59 Date:

Occupied Bandwidth, 458 MHz, FM mode

*****END OF REPORT*****

FCC Part 22 and 90

Page 18 of 18