

EMC TEST REPORT

Applicant:	Borqs BeiJing Ltd.
Address:	Tower A, Building B23, Universal Business Park, No. 10 Jiuxianqiao Road, Chaoyang District Beijing, 100015 China

Manufacturer or Supplier:	Borqs BeiJing Ltd.
Address:	Tower A, Building B23, Universal Business Park, No. 10 Jiuxianqiao Road, Chaoyang District Beijing, 100015 China
Product:	SKYBOX
Brand Name:	SkyCentrics
Model Name:	MA01-WBNA (Low Voltage with LTE), MA01-EP-WBNA (High Voltage with LTE)
FCC ID:	2ABDK-MA01
Date of tests:	Nov. 27, 2023 ~ Dec. 05, 2023

The submitted sample of the above equipment has been tested for according to the requirements of the following standards:

- ☐ FCC Part 15, Subpart B, Class A
☒ FCC Part 15, Subpart B, Class B
☒ ANSI C63.4:2014

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Chao Wu Engineer / Mobile Department	Approved by Peibo Sun Manager / Mobile Department
 Date: Dec. 05, 2023	 Date: Dec. 05, 2023

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1 GENERAL INFORMATION	4
1.1 GENERAL DESCRIPTION OF EUT.....	4
1.2 SUMMARY OF TEST RESULTS	5
1.3 MEASUREMENT UNCERTAINTY	5
1.4 DESCRIPTION OF TEST MODES.....	6
1.5 DESCRIPTION OF SUPPORT UNITS.....	7
2 EMISSION TEST	8
2.1 CONDUCTED EMISSION MEASUREMENT.....	8
2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	8
2.1.2 TEST INSTRUMENTS.....	8
2.1.3 TEST PROCEDURES	9
2.1.4 DEVIATION FROM TEST STANDARD	9
2.1.5 TEST SETUP.....	9
2.1.6 EUT OPERATING CONDITIONS	10
2.1.7 TEST RESULTS	11
2.2 RADIATED EMISSION MEASUREMENT.....	13
2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	13
2.2.2 TEST INSTRUMENTS.....	14
2.2.3 TEST PROCEDURE.....	15
2.2.4 DEVIATION FROM TEST STANDARD	16
2.2.5 TEST SETUP.....	17
2.2.6 EUT OPERATING CONDITIONS	17
2.2.7 TEST RESULTS	18
3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	22



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
W7L-231123W001EM01	Original release	Dec. 05, 2023

1 GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF EUT

PRODUCT	SKYBOX	
BRAND NAME	SkyCentrics	
MODEL NAME	MA01-WBNA (Low Voltage with LTE), MA01-EP-WBNA (High Voltage with LTE)	
NOMINAL VOLTAGE	24Vac (MA01-WBNA) 120Vac (MA01-EP-WBNA)	
MODULATION TYPE	LTE	QPSK/16QAM
OPERATING FREQUENCY	LTE	1850.7MHz ~ 1909.3MHz (FOR LTE Band2) 1710.7MHz ~ 1754.3MHz (FOR LTE Band4) 824.7MHz ~ 848.3MHz (FOR LTE Band5) 699.7MHz ~ 715.3MHz (FOR LTE Band12) 779.5MHz ~ 784.5MHz (FOR LTE Band13) 1850.7MHz ~ 1914.3MHz (FOR LTE Band25) 814.7MHz ~ 848.3MHz (FOR LTE Band26)
HW VERSION	DVT	
SW VERSION	fft_PICO_KITE_20230828	
I/O PORTS	Refer to user's manual	
CABLE SUPPLIED	Power cable: non-shielded cable, with w/o ferrite core, 1.8 meter	

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
- The difference of MA01-WBNA and MA01-EP-WBNA is as follows:

No	Model	Difference Description
1	MA01-EP-WBNA	High Voltage: 120 V _{AC} through Power Entry Module
2	MA01-WBNA	Low Voltage: 24 V _{AC} through terminal block header

List of Accessory:

ACCESSORIES	BRAND	MODEL	SPECIFICATION
Power cable	YuanSong	YS-301+SVT18/ 3CBK+ YS-302	1.8M

1.2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart B		
Standard Section	Test Item	Result
FCC Part 15, Subpart B, Class B ANSI C63.4:2014	Conducted Test	Compliance
	Radiated Emission Test (30MHz ~ 1GHz)	Compliance
	Radiated Emission Test (Above 1GHz)	Compliance

1.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz ~ 30MHz	±2.70dB
Radiated emissions	30MHz~1GHz	±4.98dB
	1GHz ~6GHz	±4.70dB
	6GHz ~18GHz	±4.60dB
	18GHz ~40GHz	±4.12dB

1.4 DESCRIPTION OF TEST MODES

Test Mode	Test Condition
Radiated emission test	
1	LTE Band 5 Idle+ PC Link RS485 and USB+ LAN+ AC Cable+ EUT (MA01-EP-WBNA)
2	LTE Band 12 Idle+ PC Link RS485 and USB+ LAN+ AC Cable+ EUT (MA01-EP-WBNA)
3	LTE Band 13 Idle+ PC Link RS485 and USB+ LAN+ AC Cable+ EUT (MA01-EP-WBNA)
4	LTE Band 26 Idle+ PC Link RS485 and USB+ LAN+ AC Cable+ EUT (MA01-EP-WBNA)
5	LTE Band 5 Idle+ PC Link RS485 and USB+ LAN+ AC Adapter+ EUT (MA01-WBNA)
6	LTE Band 12 Idle+ PC Link RS485 and USB+ LAN+ AC Adapter+ EUT (MA01-WBNA)
7	LTE Band 13 Idle+ PC Link RS485 and USB+ LAN+ AC Adapter+ EUT (MA01-WBNA)
8	LTE Band 26 Idle+ PC Link RS485 and USB+ LAN+ AC Adapter+ EUT (MA01-WBNA)

Conducted emission test	
1	LTE Band 5 Idle+ PC Link RS485 and USB+ LAN+ AC Cable+ EUT (MA01-EP-WBNA)
2	LTE Band 12 Idle+ PC Link RS485 and USB+ LAN+ AC Cable+ EUT (MA01-EP-WBNA)
3	LTE Band 13 Idle+ PC Link RS485 and USB+ LAN+ AC Cable+ EUT (MA01-EP-WBNA)
4	LTE Band 26 Idle+ PC Link RS485 and USB+ LAN+ AC Cable+ EUT (MA01-EP-WBNA)
5	LTE Band 5 Idle+ PC Link RS485 and USB+ LAN+ AC Adapter+ EUT (MA01-WBNA)
6	LTE Band 12 Idle+ PC Link RS485 and USB+ LAN+ AC Adapter+ EUT (MA01-WBNA)
7	LTE Band 13 Idle+ PC Link RS485 and USB+ LAN+ AC Adapter+ EUT (MA01-WBNA)
8	LTE Band 26 Idle+ PC Link RS485 and USB+ LAN+ AC Adapter+ EUT (MA01-WBNA)

NOTE:

1. For conducted emission test, Pre-scan all mode, mode 2 was the worst case and only this mode was presented in this report.
2. For radiated emission test, Pre-scan all mode, test mode 4 was the worst case and only this mode was presented in this report

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

FOR ALL TESTS

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Laptop	Lenovo	Thinkpad L440	R90FTFKP	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	USB Line: Shielded, Detachable 0.5m;

2 EMISSION TEST

2.1 CONDUCTED EMISSION MEASUREMENT

2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

TEST STANDARD: FCC PART 15, SUBPART B (SECTION: 15.107 A CLASS B)

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

TEST STANDARD: FCC PART 15, SUBPART B (SECTION: 15.107 B CLASS A)

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	79	66
0.5 ~ 30	73	60

NOTE: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

2.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	101900	Feb. 14,23	Feb. 13,24
EMC32 test software	Rohde&Schwarz	EMC32	NA	NA	NA
LISN network	Rohde&Schwarz	ENV216	101922	Mar. 10,23	Mar. 09,24

NOTE: 1. The test was performed in CE shielded room.

2.1.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

2.1.4 DEVIATION FROM TEST STANDARD

No deviation.

2.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80
from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

2.1.6 EUT OPERATING CONDITIONS

- Turned on the power and connected of all equipment.
- EUT was operated according to the use type described in the manufacturer's specifications or the user's manual.


2.1.7 TEST RESULTS

TEST VOLTAGE	Input 120 Vac, 60 Hz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
ENVIRONMENTAL CONDITIONS	26deg. C, 51%RH	TESTED BY	Carl xie

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Line	Filter	Corr. (dB)
0.520000	---	31.32	46.00	14.68	L1	ON	9.8
0.520000	46.38	---	56.00	9.62	L1	ON	9.8
0.724000	---	36.73	46.00	9.27	L1	ON	9.8
0.724000	52.56	---	56.00	3.44	L1	ON	9.8
1.768000	---	28.29	46.00	17.71	L1	ON	9.8
1.768000	44.09	---	56.00	11.91	L1	ON	9.8
1.972000	---	28.69	46.00	17.31	L1	ON	9.8
1.972000	43.92	---	56.00	12.08	L1	ON	9.8
3.220000	---	27.59	46.00	18.41	L1	ON	9.8
3.220000	43.13	---	56.00	12.87	L1	ON	9.8
4.468000	---	26.54	46.00	19.46	L1	ON	9.7
4.468000	42.63	---	56.00	13.37	L1	ON	9.7

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Limit value - Emission level
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.

Full Spectrum




TEST VOLTAGE	Input 120 Vac, 60 Hz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
ENVIRONMENTAL CONDITIONS	26deg. C, 51%RH	TESTED BY	Carl xie

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Line	Filter	Corr. (dB)
0.520000	---	29.08	46.00	16.92	N	ON	9.7
0.520000	45.48	---	56.00	10.52	N	ON	9.7
0.724000	---	35.93	46.00	10.07	N	ON	9.7
0.724000	52.12	---	56.00	3.88	N	ON	9.7
1.768000	---	28.50	46.00	17.50	N	ON	9.8
1.768000	44.10	---	56.00	11.90	N	ON	9.8
1.972000	---	28.84	46.00	17.16	N	ON	9.8
1.972000	43.79	---	56.00	12.21	N	ON	9.8
3.220000	---	26.45	46.00	19.55	N	ON	9.8
3.220000	42.52	---	56.00	13.48	N	ON	9.8
4.468000	---	26.53	46.00	19.47	N	ON	9.7
4.468000	42.38	---	56.00	13.62	N	ON	9.7

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Limit value - Emission level
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.

Full Spectrum



2.2 RADIATED EMISSION MEASUREMENT

2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

TEST STANDARD: FCC PART 15, SUBPART B (SECTION: 15.109)

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 3 meters (dB μ V/m)		
Frequencies (MHz)	FCC 15B, Class A	FCC 15B, Class B
30-88	49	40
88-216	53.5	43.5
216-960	56	46
960-1000	59.5	54
Above 1000	Avg: 59.5 Peak: 79.5	Avg: 54 Peak: 74

Frequency Range (For unintentional radiators)

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5 th harmonic of the highest frequency or 40GHz, whichever is lower

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. Emission level (dB μ V/m) = 20 log Emission level (μ V/m).
 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
 4. QP detector shall be applied if not specified.

2.2.2 TEST INSTRUMENTS

Frequency range below 1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	May. 22, 23	May. 21,26
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Feb. 18,23	Feb. 17,24
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 28,23	Mar. 27,24
Signal Pre-Amplifier	EMSI	EMC 9135	980249	May. 06,23	May. 05,24
E3 Test Software	E3	V 9.160323	N/A	N/A	N/A

Frequency range above 1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	May. 22, 23	May. 21,26
Horn Antenna	ETS-LINDGREN	3117	00168728	Nov. 30,22	Nov. 29,23
Horn Antenna	ETS-LINDGREN	3117	00168728	Nov. 29,23	Nov. 28,24
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-00361	15433	Sep.04, 23	Sep.03, 24
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 28,23	Mar. 27,24
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	May.10,23	May.09,24
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Feb. 17,23	Feb. 16,24
E3 Test Software	E3	V 9.160323	N/A	N/A	N/A

NOTE: 1. The test was performed in 3m chamber.
2. The FCC Site Registration No. is 434559; The Designation No. is CN1325

2.2.3 TEST PROCEDURE

<Frequency Range below 1GHz>

The basic test procedure was in accordance with ANSI C63.4:2014 (section 12).

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from 1 meter to 4 meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.

NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. $\text{Emission level(dBuV/m)} = \text{Raw Value(dBuV)} + \text{Correction Factor(dB/m)}$
3. $\text{Correction Factor(dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)}$ (if the raw value not contains the amplifier);
4. $\text{Correction Factor(dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)} - \text{Amplifier Gain(dB)}$ (if the raw value contains the amplifier).
5. $\text{Margin value} = \text{Emission level} - \text{Limit value}$

<Frequency Range above 1GHz>

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter fully-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. The bore sight should be used during the test above 1GHz.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz

NOTE:


- . The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- . The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth of test receiver/spectrum analyzer is 1Hz for Average detection (AV) at frequency above 1GHz.
- . For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the receiver antenna.
- . $\text{Emission level(dBuV/m)} = \text{Raw Value(dBuV)} + \text{Correction Factor(dB/m)}$
- . $\text{Correction Factor(dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)}$ (if the raw value not contains the amplifier);
- . $\text{Correction Factor(dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)} - \text{Amplifier Gain(dB)}$ (if the raw value contains the amplifier)
- . $\text{Margin value} = \text{Emission level} - \text{Limit value}$

2.2.4 DEVIATION FROM TEST STANDARD


No deviation.

2.2.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

depends on the EUT height and the antenna 3dB bandwidth both, refer to section 7.3 of CISPR 16-2-3.

2.2.6 EUT OPERATING CONDITIONS

Same as item 2.1.6.

2.2.7 TEST RESULTS


Acceleromete alternative worst case:

TEST VOLTAGE	Input 120 Vac, 60 Hz	FREQUENCY RANGE	30-1000 MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120 kHz
TESTED BY	Jace Hu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m		
1	30.000	25.48	36.32	40.00	-14.52	-10.84	Peak	Horizontal
2	109.540	26.25	48.31	43.50	-17.25	-22.06	Peak	Horizontal
3	163.860	30.59	48.24	43.50	-12.91	-17.65	Peak	Horizontal
4	250.190	40.13	55.99	46.00	-5.87	-15.86	Peak	Horizontal
5 PP	375.320	42.61	55.71	46.00	-3.39	-13.10	Peak	Horizontal
6	500.450	39.06	49.47	46.00	-6.94	-10.41	Peak	Horizontal

- REMARKS:** 1. Emission level(dBuV/m)=Read Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)- Amplifier Gain
3. The other emission levels were very low against the limit.
4. Margin value = Emission level - Limit value




TEST VOLTAGE	Input 120 Vac, 60 Hz	FREQUENCY RANGE	30-1000 MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70% RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak , 120 kHz
TESTED BY	Jace Hu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m		
1 PP	34.850	36.45	49.65	40.00	-3.55	-13.20	Peak	Vertical
2	57.160	33.69	56.87	40.00	-6.31	-23.18	Peak	Vertical
3	99.840	32.61	54.32	43.50	-10.89	-21.71	Peak	Vertical
4	250.190	35.16	50.62	46.00	-10.84	-15.46	Peak	Vertical
5	375.320	38.99	51.41	46.00	-7.01	-12.42	Peak	Vertical
6	450.010	41.91	52.55	46.00	-4.09	-10.64	Peak	Vertical

- REMARKS:
1. Emission level(dBuV/m)=Read Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) -Amplifier Gain
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level - Limit value.




TEST VOLTAGE	Input 120 Vac, 60 Hz	FREQUENCY RANGE	1-18 GHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Peak/Average, 1 MHz
TESTED BY	Jace Hu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m		
1	2020.000	42.89	50.96	74.00	-31.11	-8.07	Peak	Horizontal
2	2020.000	30.42	38.49	54.00	-23.58	-8.07	Average	Horizontal
3 PP	4961.000	62.51	63.90	74.00	-11.49	-1.39	Peak	Horizontal
4	4961.000	39.13	40.52	54.00	-14.87	-1.39	Average	Horizontal
5	7205.000	50.27	48.03	74.00	-23.73	2.24	Peak	Horizontal
6 AV	7205.000	41.73	39.49	54.00	-12.27	2.24	Average	Horizontal

- REMARKS:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
 2. Negative sign (-) in the margin column signify levels below the limit.
 3. Frequency range scanned: 1GHz to 5th harmonic of the highest frequency or 40GHz, whichever is lower .For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet.
 4. Only emissions significantly above equipment noise floor are reported.




TEST VOLTAGE	Input 120 Vac, 60 Hz	FREQUENCY RANGE	1-18 GHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Peak/Average, 1 MHz
TESTED BY	Jace Hu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m		
1	2020.000	43.99	51.86	74.00	-30.01	-7.87	Peak	Vertical
2	2020.000	32.39	40.26	54.00	-21.61	-7.87	Average	Vertical
3	2479.000	49.31	55.57	74.00	-24.69	-6.26	Peak	Vertical
4	2479.000	35.36	41.62	54.00	-18.64	-6.26	Average	Vertical
5 PK	7205.000	54.63	52.29	74.00	-19.37	2.34	Peak	Vertical
6 PP	7205.000	42.52	40.18	54.00	-11.48	2.34	Average	Vertical

- REMARKS:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
 2. Negative sign (-) in the margin column signify levels below the limit.
 3. Frequency range scanned: 1GHz to 5th harmonic of the highest frequency or 40GHz, whichever is lower .For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet.
 4. Only emissions significantly above equipment noise floor are reported.



3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

---END---