

TEST REPORT

- APPLICANT : Nubia Technology Co.,Ltd
- PRODUCT NAME : wearable phone
- MODEL NAME : SW1002
- **BRAND NAME** : NUBIA
- STANDARD(S) : 47 CFR Part 15 Subpart B
- FCC ID : 2AHJO-SW1002
- **RECEIPT DATE** : 2019-02-20
- **TEST DATE** : 2019-02-28 to 2019-03-01
- **ISSUE DATE** : 2019-03-18

Edited by:

Lv Shangrong

Lv Shangrong(Rapporteur)

Approved by:

Andy Yeh(Technical Director)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.



SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd. FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555 Fax: 86-755-36698525 Http://www.morlab.cn





DIRECTORY

1. Technical Information	3
1.1. Applicant and Manufacturer Information	3
1.2. Equipment Under Test (EUT) Description	3
2. Test Results	5
2.1. Applied Reference Documents	5
2.2. EUT Setup and Operating Conditions	6
3. 47 CFR Part 15B Requirements	7
3.1. Conducted Emission	7
3.2. Radiated Disturbance 1	3
Annex A Test Uncertainty 2	4
Annex B Testing Laboratory Information 2	5

Change History						
Version	Date	Reason for change				
1.0	2019-03-18	First edition				





Note: Provide by applicant

1.1. Applicant and Manufacturer Information

Applicant:	Nubia Technology Co.,Ltd			
Applicant Address: 10/F, Tower A, Hans Innovation Mansion, North Ring Rd.,				
	No.9018, High-Tech Park, Nanshan District, Shenzhen, China			
Manufacturer:	Nubia Technology Co.,Ltd			
Manufacturer Address: 10/F, Tower A, Hans Innovation Mansion, North Ring Ro				
	No.9018, High-Tech Park, Nanshan District, Shenzhen, China			

1.2. Equipment Under Test (EUT) Description

EUT Type:	wearable phone					
Serial No:	(N/A, marked #1 by test site)					
Hardware Version:	SW1002MB_C					
Software Version:	SW1002_ENCommon_	V1.00				
Frequency Range:	Bluetooth: 2402 MHz ~	2480 MHz				
	802.11b/g/n-20: 2412 N	1Hz ~ 2462 MHz				
	GPS: 1559 MHz ~ 1610) MHz				
Ancillary	Battery					
Equipment:	Brand Name:	ATL				
	Model No.:	Li3905T44P6h292752				
	Serial No.:	(N/A, marked #1 by test site)				
	Capacity:	500mAh				
	Rated Voltage:	3.85V				
	Charge Limit:	4.4V				
	AC Adapter					
	Brand Name:	nubia				
	Model No.: STC-A51A-Z					
	Serial No.: (N/A, marked #1 by test site)					
	Rated Input:	100-240V ~ 50/60Hz 0.25A				
	Rated Output:	5V1A				

Note:





1. For a more detailed description, please refer to specification or user's manual supplied by the applicant and/or manufacturer.



SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd. FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China
 Tel: 86-755-36698555
 Fax: 86-755-36698525

 Http://www.morlab.cn
 E-mail: service@morlab.cn



2.1. Applied Reference Documents

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

No.	Identity	Document Title		
1	47 CFR Part 15	Radio Frequency Devices		

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result
1	15.107	Conducted Emission	2019.02.28	Wu Zhongwen	PASS
2	15.109	Radiated Emission	2019.03.01	Wu Zhongwen	PASS

NOTE: The tests were performed according to the method of measurements prescribed in ANSI C63.4-2014.





2.2. EUT Setup and Operating Conditions

Test Iten	า	
Radiated	ΙE	mission
Mode 1	:	EUT + USB Cable + Base + Adapter + Camera + Bluetooth Idle + WIFI Idle
Mode 2	:	EUT + USB Cable + Base + Adapter + GPS Rx + Bluetooth Idle + WIFI Idle
Mode 3	:	EUT + USB Cable + Base + Adapter + Bluetooth Rx
Mode 4	:	EUT + USB Cable + Base + Adapter + WIFI Rx
Mode 5	:	EUT + USB Cable + PC + Bluetooth Idle + WIFI Idle (Transmitting Data)
Conduct	ed	Emission
Mode 1	:	EUT + USB Cable + Base + Adapter + Camera + Bluetooth Idle + WIFI Idle
Mode 2	:	EUT + USB Cable + Base + Adapter + GPS Rx + Bluetooth Idle + WIFI Idle
Mode 3	:	EUT + USB Cable + Base + Adapter + Bluetooth Rx
Mode 4	:	EUT + USB Cable + Base + Adapter + WIFI Rx
Mode 5	:	EUT + USB Cable + PC + Bluetooth Idle + WIFI Idle (Transmitting Data)
Remark:		
The abov	/e t	est modes in boldface (Mode 1, Mode 5) were the worst cases of conducted emission,
radiated	em	ission tests; only the test data of these modes were reported.

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 - 60
Atmospheric Pressure (kPa):	86 - 106





3. 47 CFR Part 15B Requirements

3.1. Conducted Emission

3.1.1. Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50μ H/50 Ω line impedance stabilization network (LISN).

Frequency range	Conducted Limit (dBµV)			
(MHz)	Quasi-peak	Average		
0.15 - 0.50	66 to 56	56 to 46		
0.50 - 5	56	46		
5 - 30	60	50		

NOTE:

a) The limit subjects to the Class B digital device.

b) The lower limit shall apply at the band edges.

c) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.1.2. Test Setup

Please refer to Annex A for the photographs of the Test Configuration.





SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd. FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

 Tel: 86-755-36698555
 Fax: 86-755-36698525

 Http://www.morlab.cn
 E-mail: service@morlab.cn



The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides $50\Omega/50\mu$ H of coupling impedance for the measuring instrument. A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.

The power strip or extension cord has been investigated to make sure that the LISN integrity in maintained with respect to the impedance characteristics as prescribed in ANSI C63.4-2014 at Clause 4.3.

3.1.3. Test Result

The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.







A. Test Plot and Suspicious Points:

(Plot A:L Phase)									
Fre. Emission Level (dBµV) Limit (dBµV)									
NO.	(MHz)	Quai-peak	Average	Quai-peak	Average	Power-line	verdict		
1	0.1771	34.76	25.36	64.62	54.62		PASS		
2	0.2084	35.58	26.33	63.27	53.27		PASS		
3	0.3480	34.04	25.41	59.01	49.01		PASS		
4	0.4021	33.80	25.42	57.81	47.81	Line	PASS		
5	0.8652	33.38	25.38	56.00	46.00		PASS		
6	6.7073	37.58	28.87	60.00	50.00		PASS		

Mode 1







NO.	Fre.	Emission Level (dBµV)		Limit (dBµV)		Dowor line	Verdiet
	(MHz)	Quai-peak	Average	Quai-peak	Average	Power-line	verdict
1	0.1949	35.42	24.65	63.82	53.82		PASS
2	0.2672	34.73	24.03	61.20	51.20		PASS
3	0.6628	32.84	23.17	56.00	46.00	Noutrol	PASS
4	0.9955	32.97	23.07	56.00	46.00	Neutrai	PASS
5	6.5195	38.45	27.56	60.00	50.00		PASS
6	21.059	36.16	25.92	60.00	50.00		PASS



MORL

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd. FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China
 Tel: 86-755-36698555
 Fax: 86-755-36698525

 Http://www.morlab.cn
 E-mail: service@morlab.cn



Mode 5



NO.	Fre.	re. Emission Level (dBµV)		Limit (dBµV)		Power line	Vardiat
	(MHz)	Quai-peak	Average	Quai-peak	Average	Power-line	verdict
1	0.1500	53.92	39.50	66.00	56.00		PASS
2	0.1590	53.94	37.97	65.52	55.52		PASS
3	0.1817	51.12	39.32	64.41	54.41	Line	PASS
4	0.2176	46.55	33.85	62.91	52.91	Line	PASS
5	0.3977	41.13	33.47	57.90	47.90		PASS
6	1.3157	34.17	26.79	56.00	46.00		PASS







	Fre.	Fre. Emission Level (dBµV)		Limit (o	dBμV)	Dewer line	Vordiat
NU.	(MHz)	Quai-peak	Average	Quai-peak	Average	Power-line	verdict
1	0.1679	51.87	36.44	65.06	55.06		PASS
2	0.1860	50.13	38.48	64.21	54.21		PASS
3	0.1948	49.18	36.35	63.83	53.83	Noutrol	PASS
4	0.2308	45.88	33.68	62.42	52.42	Neutrai	PASS
5	0.9726	34.65	25.72	56.00	46.00		PASS
6	1.1758	34.06	24.76	56.00	46.00		PASS



MORL



3.2. Radiated Disturbance

3.2.1. Requirement

According to FCC section 15.109 (a), the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency	y Field Strength Limitation at 3m Measuremen				
range (MHz)	(μV/m)	(dBµV/m)			
30.0 - 88.0	100	20log 100			
88.0 - 216.0	150	20log 150			
216.0 - 960.0	200	20log 200			
Above 960.0	500	20log 500			

As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

Note:

- 1) The tighter limit shall apply at the boundary between two frequency range.
- 2) Limitation expressed in dB μ V/m is calculated by 20log Emission Level(μ V/m).

3.2.2. Frequency range of measurement

According to 15.33(b)(1), the frequency range of radiated measurement for the EUT is listed in the following table:

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measure- ment range (MHz)
Below 1.705 1.705–108 108–500 500–1000 Above 1000	30. 1000. 2000. 5000. 5th harmonic of the highest frequency or 40 GHz, whichever is lower.





3.2.3. Test Setup

1) For radiated emissions from 30MHz to1GHz



2) For radiated emissions above 1GHz



MORLAB

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd. FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China



The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted onavariable-height antenna master tower.

For the test Antenna:

In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

3.2.4. Test Result

The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.

The amplitude of emissions which (6GHz-12.5GHz) are attenuated more than 20 dB below the permissible value need not be reported.

Note: All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.





Mode 1



No	Fre.	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV		Vardiat
NO.	MHz	dBµV/m	dBµV/m	dBµV/m	dBµV/m	dBµV/m	dBµV/m	ANT	verdict
1	35.8258	29.43	N.A	N.A	N.A	40.00	N.A	V	PASS
2	43.5936	27.92	N.A	N.A	N.A	40.00	N.A	V	PASS
3	53.3033	26.63	N.A	N.A	N.A	40.00	N.A	V	PASS
4	104.7648	24.35	N.A	N.A	N.A	43.50	N.A	V	PASS
5	122.2422	22.85	N.A	N.A	N.A	43.50	N.A	V	PASS
6	279.5395	23.87	N.A	N.A	N.A	46.00	N.A	V	PASS









No.	Fre. MHz	Pk dBµV/m	QP dBµV/m	AV dBµV/m	Limit-PK dBµV/m	Limit-QP dBµV/m	Limit-AV dBµV/m	ANT	Verdict
1	1086.0172	33.43	N.A	N.A	74.00	N.A	54.00	V	PASS
2	1228.0456	33.38	N.A	N.A	74.00	N.A	54.00	V	PASS
3	1546.1092	34.60	N.A	N.A	74.00	N.A	54.00	V	PASS
4	2324.2649	37.03	N.A	N.A	74.00	N.A	54.00	V	PASS
5	3197.4395	38.88	N.A	N.A	74.00	N.A	54.00	V	PASS
6	5608.9218	41.94	N.A	N.A	74.00	N.A	54.00	V	PASS



SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd. FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China





No.	Fre. MHz	Pk dBµV/m	QP dBµV/m	AV dBµV/m	Limit-PK dBµV/m	Limit-QP dBµV/m	Limit-AV dBµV/m	ANT	Verdict
1	34.8549	32.12	N.A	N.A	N.A	40.00	N.A	Н	PASS
2	43.5936	27.58	N.A	N.A	N.A	40.00	N.A	Н	PASS
3	55.2452	26.29	N.A	N.A	N.A	40.00	N.A	Н	PASS
4	95.0551	23.74	N.A	N.A	N.A	43.50	N.A	Н	PASS
5	104.7648	26.65	N.A	N.A	N.A	43.50	N.A	Н	PASS
6	360.1301	24.58	N.A	N.A	N.A	46.00	N.A	Н	PASS









No.	Fre.	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	ANT	Verdict
	MHz	dBµV/m	dBµV/m	dBµV/m	dBµV/m	dBµV/m	dBµV/m		
1	1061.0122	32.80	N.A	N.A	74.00	N.A	54.00	н	PASS
2	1577.1154	35.51	N.A	N.A	74.00	N.A	54.00	Н	PASS
3	2150.2300	36.50	N.A	N.A	74.00	N.A	54.00	Н	PASS
4	3207.4415	39.19	N.A	N.A	74.00	N.A	54.00	Н	PASS
5	4308.6617	40.94	N.A	N.A	74.00	N.A	54.00	н	PASS
6	5408.8818	41.58	N.A	N.A	74.00	N.A	54.00	Н	PASS





Mode 4



No.	Fre.	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	ANT	Verdict
	MHZ	aBhr/w	aBhr/w	aBhr/w	aBhr/w	aBhr/w	aBhr/w		
1	35.8258	29.89	N.A	N.A	N.A	40.00	N.A	V	PASS
2	43.5936	28.39	N.A	N.A	N.A	40.00	N.A	V	PASS
3	54.2743	26.69	N.A	N.A	N.A	40.00	N.A	V	PASS
4	105.7357	24.92	N.A	N.A	N.A	43.50	N.A	V	PASS
5	203.8038	27.56	N.A	N.A	N.A	43.50	N.A	V	PASS
6	723.2733	36.51	N.A	N.A	N.A	46.00	N.A	V	PASS









No.	Fre. MHz	Pk dBuV/m	QP dBuV/m	AV dBuV/m	Limit-PK dBuV/m	Limit-QP dBuV/m	Limit-AV dBuV/m	ANT	Verdict
1	1159.0318	36.05	N.A	N.A	74.00	N.A	54.00	V	PASS
2	1466.0932	34.88	N.A	N.A	74.00	N.A	54.00	V	PASS
3	1920.1840	36.51	N.A	N.A	74.00	N.A	54.00	V	PASS
4	2718.3437	39.12	N.A	N.A	74.00	N.A	54.00	V	PASS
5	3832.5665	42.31	N.A	N.A	74.00	N.A	54.00	V	PASS
6	5202.8406	42.17	N.A	N.A	74.00	N.A	54.00	V	PASS







No.	Fre. MHz	Pk dBµV/m	QP dBµV/m	AV dBµV/m	Limit-PK dBµV/m	Limit-QP dBµV/m	Limit-AV dBµV/m	ANT	Verdict
1	33.8839	31.32	N.A	N.A	N.A	40.00	N.A	Н	PASS
2	45.5355	29.31	N.A	N.A	N.A	40.00	N.A	Н	PASS
3	201.8619	29.01	N.A	N.A	N.A	43.50	N.A	Н	PASS
4	254.2943	33.54	N.A	N.A	N.A	46.00	N.A	Н	PASS
5	323.2332	35.35	N.A	N.A	N.A	46.00	N.A	Н	PASS
6	720.3604	37.58	N.A	N.A	N.A	46.00	N.A	Н	PASS



SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd. FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China







No.	Fre.	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	ANT	Verdict
	INIHZ	αθμν/m	αβμν/m	αβμν/m	αβήλ/μ	αβμν/m	αβμν/m		
1	1132.0264	36.04	N.A	N.A	74.00	N.A	54.00	Н	PASS
2	1680.1360	39.99	N.A	N.A	74.00	N.A	54.00	Н	PASS
3	2186.2372	37.24	N.A	N.A	74.00	N.A	54.00	Н	PASS
4	2760.3521	38.04	N.A	N.A	74.00	N.A	54.00	Н	PASS
5	3658.5317	41.60	N.A	N.A	74.00	N.A	54.00	н	PASS
6	5450.8902	42.81	N.A	N.A	74.00	N.A	54.00	Н	PASS





Annex A Test Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Conducted Emission Measurement

Measuring Uncertainty for	9kHz-150kHz	±4.1 dB
a Level of Confidence of	150kHz-30MHz	±3.7dB
95%(U=2Uc(y))		

Uncertainty of Radiated Emission Measurement

Measuring Uncertainty for	30MHz-200MHz	±5.06dB
a Level of Confidence of	200MHz-1000MHz	±5.24dB
95%(U=2Uc(y))	1GHz-6GHz	±5.18dB
	6GHz-18GHz	±5.48dB





Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.		
	Morlab Laboratory		
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang		
	Road, Block 67, BaoAn District, ShenZhen, GuangDong		
	Province, P. R. China		
Telephone:	+86 755 36698555		
Facsimile:	+86 755 36698525		

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.	
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang	
	Road, Block 67, BaoAn District, ShenZhen, GuangDong	
	Province, P. R. China	

3. Accreditation Certificate

Accredited Testing	The FCC designation number is CN1192.	
Laboratory:	Test firm registration number is 226174.	
	(Shenzhen Morlab Communications Technology Co., Ltd.)	

4. Test Software Utilized

Model	Version Number	Producer	
JS32-RE	Version 2.0.2.0	Tonscend	
TS+ -[JS32-CE]	Version2.5.0.0	Tonscend	





5. Test Equipments Utilized

Description	Manufacturer	Model	Serial No.	Cal. Date	Due. Date
MXE EMI Receiver	Agilent	N9038A	MY54130016	2018.08.04	2019.08.03
Test Receiver	R&S	ESPI	101052	2018.08.04	2019.08.03
LISN	Schwarzbeck	NSLK 8127	812744	2018.05.08	2019.05.07
Pulse Limiter (20dB)	VTSD	9561D	9537	2018.05.08	2019.05.07
Test Antenna - Bi-Log	Schwarzbeck	VULB 9163	9163-519	2018.05.08	2019.05.07
Test Antenna - Horn	Schwarzbeck	BBHA 9120D	1774	2018.05.18	2019.05.17
Radiated Disturbance Preamplifier	rflight	S020180L320 3	61171/61172	2018.07.12	2019.07.11
Radiated Disturbance Preamplifier	rflight	S10M100L38 02	46732	2018.07.12	2019.07.11
Semi-Anechoic Chamber	CRT	9m*6m*6m	N/A	2017.01.12	2020.01.11
PC Adapter	LITE-ON POW ER TECHNOLOG Y(DONGGUA N) Co., LTD	A1374	C517271EA1 000085	N/A	N/A
PC	Apple	A1370	C02FQ2PYD DQW	N/A	N/A

_____ END OF REPORT ____

