



Issue Date : July 15, 2002  
Page 1 of 1

## Declaration of compliance

### Exposure of Humans to RF Fields Requirements

---

Applicant : Toshiba Corporation  
Type of Equipment : SDIO Card Bluetooth™  
Model No. : SD-BT2  
FCC ID : CJ6MSDB01

---

Regulations Applied : CFR 47 FCC 15.247(b)(5)  
References Documents : CFR 47 FCC 1.1307(b), 1.1310, 2.1093 and  
OET65 Supplement C

#### RF Exposure Calculations :

The following minimum separation distance between the EUT's antenna and the human body was calculated in accordance with FCC OET65 Appendix B Table(B) "Limit for General Population / Uncontrolled Exposure".

The maximum permissible exposure level is defined with 1mW/cm<sup>2</sup>.

The minimum separation distance where the exposure level reaches the permitted level can be calculated as bellow:

$$\text{Where:} \quad S = P * G / 4\pi R^2 \quad \therefore R = \sqrt{P * G / 4\pi S}$$

R = minimum separation distance in cm

P = 0.713 mW (Max. conducted output power at antenna terminal)

G = 1.31(numeric gain) = 1.17 dBi(Max. antenna Gain)

S = 1.0 mW/cm<sup>2</sup> for 2.4 GHz (Max. permissible exposure level)

Then minimum separation distance is 0.273 cm.

#### Summary:

The EUT complies with the RF exposure requirement of the above regulation.

#### Additional information:

The following warning statement is placed in user manual:

"This device and its antenna(s) must not be co-located or operating in conjunction with any other antenna or transmitter.

End user can not modify this transmitter device.

Any unauthorized modification made on the device could avoid the user's authority to operate this device."

Masaaki Takahashi  
Senior Manager  
JQA EMC Engineering Dept.