



RF Exposure Report

Report No.: SA150226E05

FCC ID: PPD-QCA9008-TBD1

Test Model: QCA9008-TBD1

Received Date: Feb. 26, 2015

Test Date: June 18 to 23, 2015

Issued Date: July 31, 2015

Applicant: Qualcomm Atheros, Inc.

Address: 1700 Technology Drive, San Jose, CA 95110

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

Test Location (1): No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

Test Location (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.



Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Antenna Gain	6
4 Calculation Result Of Maximum Conducted Power	7



A D T

Release Control Record

Issue No.	Description	Date Issued
SA150226E05	Original release.	July 31, 2015

1 Certificate of Conformity

Product: 802.11abgn/ac/ad+BT module

Brand: Qualcomm Atheros

Test Model: QCA9008-TBD1

Sample Status: ENGINEERING SAMPLE

Applicant: Qualcomm Atheros, Inc.

Test Date: June 18 to 23, 2015

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D03

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :


Lori Chung / Specialist

Date:

July 31, 2015

Approved by :


May Chen / Manager

Date:

July 31, 2015

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

So, this device is classified as **Mobile Device**.

3 Antenna Gain

The antenna gain was declared by client; please refer to the following table:

Transmitter Circuit	Brand	Model	Ant. Type	2.4GHz Gain with cable loss (dBi)	5GHz Gain with cable loss (dBi)	2.4GHz Cable Loss (dBi)	5GHz Cable Loss (dBi)	Connector Type	Cable Length (mm)
Chain (0)	WNC	81-EBJ15.005	PIFA	3.00	5.15~5.35GHz: 2.56	1.15	5.15~5.35GHz: 1.70	IPEX	300
					5.47~5.725GHz: 4.76		5.47~5.725GHz: 1.74		
					5.725~5.85GHz: 4.76		5.725~5.85GHz: 1.79		
Chain (1)	WNC	81-EBJ15.005	PIFA	3.62	5.15~5.35GHz: 3.08	1.15	5.15~5.35GHz: 1.70	IPEX	300
					5.47~5.725GHz: 3.31		5.47~5.725GHz: 1.74		
					5.725~5.85GHz: 2.42		5.725~5.85GHz: 1.79		

Note: 1. Above antenna gains of antenna are Total (H+V).

For testing, we select the highest gain on each frequency band for calculation and testing
The detail information as below:

Transmitter Circuit	Brand	Model	Ant. Type	2.4GHz Gain with cable loss (dBi)	5GHz Gain with cable loss (dBi)	2.4GHz Cable Loss (dBi)	5GHz Cable Loss (dBi)	Connector Type	Cable Length (mm)
Chain (0)+(1)	WNC	81-EBJ15.005	PIFA	3.62	5.15~5.35GHz: 3.08	1.15	5.15~5.35GHz: 1.70	IPEX	300
					5.47~5.725GHz: 4.76		5.47~5.725GHz: 1.74		
					5.725~5.85GHz: 4.76		5.725~5.85GHz: 1.79		

4 Calculation Result Of Maximum Conducted Power

For WLAN: 15.247 (2.4GHz):

802.11b

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2472	294.47	6.63	20	0.26963	1

NOTE: 1. Directional gain = 3.62dBi + 10log(2) = 6.63dBi

802.11g

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2472	430.629	6.63	20	0.39431	1

NOTE: 1. Directional gain = 3.62dBi + 10log(2) = 6.63dBi

VHT20

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2472	439.601	6.63	20	0.40252	1

NOTE: 1. Directional gain = 3.62dBi + 10log(2) = 6.63dBi

VHT40

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2422-2462	416.898	6.63	20	0.38173	1

NOTE: 1. Directional gain = 3.62dBi + 10log(2) = 6.63dBi

For WLAN: 15.407 (5GHz):

802.11a

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
5180 - 5240, 5260 - 5320	70.001	6.09	20	0.05660	1
5500 - 5720	65.547	7.77	20	0.07803	1
5745 - 5825	71.132	7.77	20	0.08468	1

NOTE: 1. 5150~5350MHz: Directional gain = 3.08dBi + 10log(2) = 6.09dBi
2. 5470~5725MHz: Directional gain = 4.76dBi + 10log(2) = 7.77dBi
3. 5725~5850MHz: Directional gain = 4.76dBi + 10log(2) = 7.77dBi

802.11ac (VHT20)

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
5180 - 5240, 5260 - 5320	75.315	6.09	20	0.06090	1
5500 - 5720	69.781	7.77	20	0.08307	1
5745 - 5825	68.244	7.77	20	0.08124	1

NOTE: 1. 5150~5350MHz: Directional gain = 3.08dBi + 10log(2) = 6.09dBi
2. 5470~5725MHz: Directional gain = 4.76dBi + 10log(2) = 7.77dBi
3. 5725~5850MHz: Directional gain = 4.76dBi + 10log(2) = 7.77dBi

802.11ac (VHT40)

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
5190 - 5230, 5270 - 5310	57.081	6.09	20	0.04616	1
5510 - 5710	54.646	7.77	20	0.06506	1
5755 - 5795	44.084	7.77	20	0.05248	1

NOTE: 1. 5150~5350MHz: Directional gain = 3.08dBi + 10log(2) = 6.09dBi
2. 5470~5725MHz: Directional gain = 4.76dBi + 10log(2) = 7.77dBi
3. 5725~5850MHz: Directional gain = 4.76dBi + 10log(2) = 7.77dBi

802.11ac (VHT80)

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
5210 - 5290	11.56	6.09	20	0.05660	1
5530 - 5690	15.66	7.77	20	0.07803	1
5775	11.26	7.77	20	0.08468	1

NOTE: 1. 5150~5350MHz: Directional gain = 3.08dBi + 10log(2) = 6.09dBi
2. 5470~5725MHz: Directional gain = 4.76dBi + 10log(2) = 7.77dBi
3. 5725~5850MHz: Directional gain = 4.76dBi + 10log(2) = 7.77dBi

For Bluetooth:

Frequency Band (MHz)	Max power (dBm)	Max power (mW)	Antenna gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2402-2480	11.02	12.647	3.62	20	0.00579	1.00

For WLAN (60GHz):

Max EIRP (mW)	Separation Distance (cm)	Power Density (mW/cm ²)	FCC Limit (mW/cm ²)
835.620	20	0.16624	1

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

WLAN (5GHz) + Bluetooth + WLAN (60GHz) = 0.08468 + 0.00579 + 0.16624 = 0.257

WLAN (2.4GHz) + WLAN (60GHz) = 0.40252 + 0.16624 = 0.569

Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ---