



Industrial Internet Innovation Center (Shanghai) Co.,Ltd.

SRD TEST REPORT

PRODUCT	Smart label printing scale
BRAND	SUNMI
MODEL	ACS-F2531,ACS-F2532
APPLICANT	Shanghai Sunmi Technology Co.,Ltd.
FCC ID	2AH25S2LCC
IC	22621-S2LCC
ISSUE DATE	October 16, 2024
STANDARD(S)	FCC Part15C, RSS-Gen Issue 5, RSS-247 Issue 3

Prepared by: *Tao Lingyan*

Reviewed by: *Yang Fan*

Approved by: *Zhang Min*

陶玲艳

杨帆

张曼

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

CONTENTS

1. SUMMARY OF TEST REPORT	3
1.1 TEST STANDARD(S)	3
1.2 REFERENCE DOCUMENTS.....	3
1.3 SUMMARY OF TEST RESULTS.....	3
1.4 DATA PROVIDED BY APPLICANT.....	4
2. GENERAL INFORMATION OF THE LABORATORY	5
2.1 TESTING LABORATORY	5
2.2 LABORATORY ENVIRONMENTAL REQUIREMENTS.....	5
2.3 PROJECT INFORMATION	5
3. GENERAL INFORMATION OF THE CUSTOMER	6
3.1 APPLICANT	6
3.2 MANUFACTURER	6
4. GENERAL INFORMATION OF THE PRODUCT.....	7
4.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	7
4.2 INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	7
4.3 ADDITIONAL INFORMATION	7
5. TEST CONFIGURATION INFORMATION	9
5.1 LABORATORY ENVIRONMENTAL CONDITIONS.....	9
5.2 TEST EQUIPMENTS UTILIZED.....	9
5.3 MEASUREMENT UNCERTAINTY	11
6. TEST RESULTS	13
6.1 DUTY CYCLE	13
6.2 99% OCCUPIED BANDWIDTH.....	15
6.3 OUTPUT POWER-CONDUCTED	17
6.4 TRANSMITTER SPURIOUS EMISSION-RADIATED	20
6.5 AC POWERLINE CONDUCTED EMISSION	37
ANNEX A: REVISED HISTORY	40
ANNEX B: ACCREDITATION CERTIFICATE.....	41

1. Summary of Test Report

1.1 Test Standard(s)

No.	Test Standard	Title	Version
1	FCC Part15C	FCC CFR 47, Part 15, Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.247 Operation within the bands 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz.	--
2	RSS-Gen Issue 5	General Requirements for Compliance of Radio Apparatus	2021
3	RSS-247 Issue 3	Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSS) and Licence-Exempt Local Area Network (LE- LAN) Devices	2023

1.2 Reference Documents

No.	Test Standard	Title	Version
1	ANSI C63.10	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices	2013
2	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for Performing Compliance Measurements on Frequency Hopping Spread Spectrum systems (DSS) Operating Under §15.247	--
3	KDB 484596 D01 Referencing Test Data v02r03	Test Reductions Via Data Referencing	--

NOTE: The standard of KDB 558074 D01 15.247 Meas Guidance v05r02 and KDB 484596 D01 Referencing Test Data v02r03 have not been accredited by A2LA.

1.3 Summary of Test Results

No.	Measurement Items	FCC Rules	IC Rules	Verdict
1	Maximum Peak Output Power	15.247(b)	RSS-247 5.4	Pass (Note 3)
2	Peak Power Spectral Density	15.247(e)	RSS-247 5.2	Pass (Note 4)
3	6dB Occupied Bandwidth	15.247(a)	RSS-247 5.2	Pass (Note 4)
4	99% Occupied Bandwidth	N/A	RSS-GEN 6.7	Pass (Note 4)
5	Band Edges Compliance	15.247(d)	RSS-247 5.5	Pass (Note 3)
6	Transmitter Spurious Emission- Conducted	15.247(d)	RSS-247 5.5	Pass (Note 4)
7	Transmitter Spurious Emission- Radiated	15.247/15.205/15.209	RSS-GEN 8.9, 8.10	Pass (Note 3)
8	AC Powerline Conducted Emission	15.207	RSS-GEN 8.8	Pass (Note 3)
9	Antenna requirement	15.203/15.247(c)	RSS Gen 6.8, RSS-247 5.4	Pass (Note 2)

Note 1:

The ACS-F2531,ACS-F2532 manufactured by Shanghai Sunmi Technology Co.,Ltd. is a variant product for testing.

This project is a variant project based on the original report 23T04I30142-SRD02-V00 with below changes:

SOFTWARE MODIFICATIONS:

Other changes detailed: Optimize functions, solve bugs, and iterate software versions. Iterative software upgrades do not affect RF performance.

HARDWARE MODIFICATIONS:

PCB Layout changes: Yes(Only printer)

Components on PCB changes: Yes

MECHANICAL MODIFICATIONS:

Use new metal front/back cover or keypad: YES

Mechanical shell changes: YES

There are two configurations Mainly Supply(S01aa) and Secondary Supply(S05aa) in this project. According to the Product Change Description, we verified the worst mode of Maximum Output Power, Radiated Spurious Emission and AC Powerline Conducted Emission of Mainly Supply(S01aa) and Secondary Supply(S05aa). All test data was recorded in this report.

The description of the differences between Mainly Supply(S01aa) and Secondary Supply(S05aa) are as follows:

Product	S2CC(Original Report)	S2LCC(This Report)
Type	15.6" 15.6"+15.6" 15.6"+10.1"	15.6"(Mainly Supply) 15.6"+15.6"(Secondary Supply)
Difference	Base 58 Printer	Base 60 Printer

Industrial Internet Innovation Center (Shanghai) Co., Ltd. only performed test cases which identified with Pass/Fail/Inc result in section 1.3.

Industrial Internet Innovation Center (Shanghai) Co., Ltd. has verified that the compliance of the tested device specified in section 4 of this test report is successfully evaluated according to the procedure and test methods as defined in type certification requirement listed in section 1 of this test report.

Note 2:

2.4G WLAN used a FPC antenna with max Gain 1.58 dBi that complied with 15.203 Requirements.

Note 3:

The test data refer to the original report, and the data in this report is spot check data,The verification datameets the KDB484596 reauirements within 3dB.

Note 4:

The test verdict of this item come from the original report.

1.4 Data Provided by Applicant

No.	Item(s)	Data
1	Antenna gain of EUT	1.58 dBi

Note: The data of antenna gain is provided by the Antenna specification may affect the validity of the test results in this report, and the impact and consequences of this shall be undertaken by the customer.

2. General Information of The Laboratory

2.1 Testing Laboratory

Lab Name	Industrial Internet Innovation Center (Shanghai) Co.,Ltd.
Address	Building 4, No. 766, Jingang Road, Pudong, Shanghai, China
Telephone	021-68866880
FCC Registration No.	708870
FCC Designation No.	CN1364
IC Designation No.	10766A
CAB identifier	CN0067

2.2 Laboratory Environmental Requirements

Temperature	15°C~35°C
Relative Humidity	86kPa~106kPa
Atmospheric Pressure	86kPa~106kPa

2.3 Project Information

Project Manager	Gao Hongning
Test Date	August 13,2024 to September 19,2024

3. General Information of The Customer

3.1 Applicant

Company	Shanghai Sunmi Technology Co.,Ltd.
Address	Room 505, No.388,Song Hu Road, Yang Pu District, Shanghai, China
Telephone	+86 17302160204

3.2 Manufacturer

Company	Shanghai Sunmi Technology Co.,Ltd.
Address	Room 505, No.388,Song Hu Road, Yang Pu District, Shanghai, China
Telephone	+86 17302160204

4. General Information of The Product

4.1 Product Description for Equipment under Test (EUT)

Product Name	Smart label printing scale
Model name	ACS-F2531,ACS-F2532
Date of Receipt	S07aa/S01aa/S05aa:August 13,2024
EUT ID*	S07aa/S01aa/S05aa
SN/IMEI	S07aa: SF01P36940197 S01aa: SF02P47540169 S05aa: SF01P36940168
Supported Radio Technology and Bands	BT 4.2 BR/EDR/BLE WLAN 802.11b/g/n WLAN 802.11a/n/ac
Hardware Version	RK3568 MB V2.0
Software Version	3.0.11
FCC ID	2AH25S2LCC
IC	22621-S2LCC
NOTE1: EUT ID is the internal identification code of the laboratory.	
NOTE2: Samples in the test report are provided by the customer. The test results are only applicable to the samples received by the laboratory.	

4.2 Internal Identification of AE used during the test

AE ID*	Description	Model	SN/Remark
CA01	Adapter	CYSE65-240250	Jiangsu chenyangElectron Co.. Ltd. 24V,2.5A
UA01	AC Cable	N/A	N/A
AE1	Notebook PC	DELL Latitude E6510	N/A
NOTE1: AE ID is the internal identification code of the laboratory.			

4.3 Additional Information

WLAN Frequency	2412MHz-2462MHz
WLAN Channel	CH1-11
WLAN type of modulation	802.11b: DSSS 802.11g/n: OFDM

Test frequency list:

BW_20M	Channel	1	6	11
	Freq. (MHz)	2412	2437	2462
BW_40M	Channel	3	6	9
	Freq. (MHz)	2422	2437	2452

Note: This report is for 2.4G WLAN only.

5. Test Configuration Information

5.1 Laboratory Environmental Conditions

5.1.1 Permanent Facilities

Relative Humidity	Min. = 45 %, Max. = 55 %		
Atmospheric Pressure	101kPa		
Temperature	Normal	Minimum	Maximum
	25°C	-10°C	40°C
Working Voltage of EUT	Normal	Minimum	Maximum
	230V	207V	253V

5.2 Test Equipments Utilized

5.2.1 Conducted Test System

No.	Name	Model	S/N	SW Version	HW Version	Manufacturer	Cal. Date	Cal. Interval
1	Test Software	TS1120	10671	V3.2.22	N/A	Tonsce nd	N/A	N/A
2	Automatic control unit	JS0806-2	2218060621	N/A	N/A	Tonsce nd	2024-03-25	1 year
3	Wireless communication comprehensive tester	CMW270	100919	V3.5.137	N/A	R&S	2024-07-25	1 year
4	Spectrum Analyzer	FSQ40	200063	V4.75	N/A	R&S	2023-10-16	1 year
5	Vector Signal Generator	SMU200A	104684	V03.20.286.21	N/A	R&S	2024-07-25	1 year
6	Vector Signal Generator	SMBV100A	257904	V4.15.125.49	N/A	R&S	2023-12-19	1 Year
7	Programmable Power Supply	Keithley 2303	4039070	N/A	N/A	Keithley	2024-06-07	1 Year
8	Temperature box	B-TF-107C	BTF107C-201804107	N/A	N/A	Boyi	2024-06-07	1 Year
9	Network test unit AP	GT-AXE11000	N2IG0X401637KWF	V3.0.0.4.386_45940	N/A	ASUS	N/A	N/A
10	Vector Signal Generator	SMBV100A	257904	V4.15.125.49	N/A	R&S	2023-10-16	1 Year

5.2.2 Radiated Emission Test System

No	Name	Model	S/N	SW Version	HW Version	Manufacturer	Cal. Date	Cal. Interval
1	Universal Radio Communication Tester	CMU200	123126	V5.2.1	B12	R&S	2023-10-16	1 Year
2	Universal Radio Communication Tester	CMW500	104178	V3.7.20	1206.0600.00	R&S	2023-10-16	1 Year
3	EMI Test Receiver	ESU40	100307	V5.1-24-3	01	R&S	2023-12-19	1 Year
4	TRILOG Broadband Antenna	VULB9163	01345	N/A	N/A	Schwarzbeck	2024-03-29	1 Year
5	Double-ridged Waveguide Antenna	ETS-3117	00135890	N/A	N/A	ETS	2024-03-16	1 Years
6	EMI Test Software	EMC32 V10.35.02	N/A	V10.35.02	N/A	R&S	N/A	N/A
7	Horn Antenna	3160-09	LM6321	N/A	N/A	R&S	2024-08-03	1 Year
8	Horn Antenna	3160-10	LM5942	N/A	N/A	R&S	2024-08-03	1 Year
9	Preamplifier	SCU08F1	8320024	N/A	N/A	R&S	2023-10-16	1 Year
10	Preamplifier	SCU18	10155	N/A	N/A	R&S	2023-10-16	1 Year
11	Preamplifier	SCU26	10025	N/A	N/A	R&S	2023-10-16	1 Year
12	Preamplifier	SCU40	10020	N/A	N/A	R&S	2023-10-16	1 Year
13	2-Line V-Network	ENV216	101380	N/A	N/A	R&S	2023-12-19	1 Year
14	EMI Test Software	EMC32 V10.35.02	N/A	N/A	N/A	R&S	N/A	N/A
15	Test Receiver	ESCI	101235	V5.1-24-3	0	R&S	2023-12-19	1 Year
16	Antenna Tower	TPMDC-LF	N/A	N/A	N/A	Top Precision	N/A	N/A
17	Antenna Tower	TPMDC-HF	N/A	N/A	N/A	Top Precision	N/A	N/A

5.2.3 Test Environment

Shielding Room1 (6.0 meters×3.0 meters×2.7 meters) did not exceed following limits along the conducted RF performance testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	> 100 dB
Ground system resistance	< 0.5 Ω
Temperature	Min. = 15 °C, Max. = 35 °C

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber1 (9.8 meters×6.7 meters×6.7 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 25 %, Max. = 75 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
VSWR	Between 0 and 6 dB, from 1GHz to 18GHz
Site Attenuation Deviation	Between -4 and 4 dB, 30MHz to 1GHz

5.3 Measurement Uncertainty

Measurement Uncertainty of Conduction test

Item(s)	Frequency range	Confidence Level	Uncertainty
DTS Bandwidth	2400–2483.5MHz	95%	±1.9%
Maximum Conducted Output Power	2400–2483.5MHz	95%	± 1.18 dB
Maximum Power Spectral Density Level	2400–2483.5MHz	95%	±0.98 dB
Band-edge Compliance	2400–2483.5MHz	95%	±1.21dB
Unwanted Emissions In Non-restricted Freq Bands	9kHz-7GHz	95%	9kHz-7GHz:±1.21dB

	7GHz-40GHz	95%	7GHz-40GHz:±3.31dB
--	------------	-----	--------------------

Measurement Uncertainty of Radiation test

Measurement Items	Uncertainty(dB)
Radiated Emission 30MHz-1000MHz	±5.10
Radiated Emission 1000MHz-18000MHz	±5.66
Radiated Emission 18000MHz-40000MHz	±5.22
AC Powerline Conducted Emission	±4.38

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

6. Test Results

6.1 Duty cycle

6.1.1 Measurement Limit

Standard	Limit (dBm)
FCC 47 Part 15.247(b)	NA
RSS-247 5.4	N/A

6.1.2 Test Procedure

This measurement is according to ANSI C63.10 clause 11.6


Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

- A diode detector and an oscilloscope that together have a sufficiently short response time to permit accurate measurements of the ON and OFF times of the transmitted signal.
- The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:
 - Set the center frequency of the instrument to the center frequency of the transmission.
 - Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
 - Set $VBW \geq RBW$. Set detector = peak or average.
- The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

6.1.3 Measurement Results

TestMode	Antenna	Frequency[MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]	Factor
11B	Ant1	2412	12.44	12.52	99.36	0.03
11B	Ant1	2437	12.44	12.56	99.04	0.04
11B	Ant1	2462	12.44	12.60	98.73	0.06

Test Graphs



6.2 99% Occupied Bandwidth

6.2.1 Measurement Limit


Standard	Limit
FCC 47 Part 15.247(b)	N/A
RSS-Gen 6.7	N/A

6.2.2 Test procedures

The measurement is according to ANSI C63.10 clause 6.9.3.

1. The output power of EUT was connected to the spectrum analyzer. The path loss was compensated to the results for each measurement.
2. Enable EUT transmitter maximum power continuously.
3. Set RBW shall be in the range of 1% to 5% of the OBW.
4. Set the VBW $\geq [3 \times \text{RBW}]$.
5. Detector = peak.
6. Trace mode = max hold.
7. Sweep = auto couple.
8. Allow the trace to stabilize.
9. The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission.


6.2.3 Test setup



6.2.4 Measurement Result

TestMode	Antenna	Channel Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	15.08	2404.4400	2419.5200	---	---
11B	Ant1	2437	15.08	2429.4400	2444.5200	---	---
11B	Ant1	2462	15.08	2454.4400	2469.5200	---	---

Test Graphs



6.3 Output Power-Conducted

6.3.1 Measurement Limit

Standard	Conducted Limit(dBm)	EIRP Limit(dBm)
FCC 47 Part 15.247(b)(3)	<30	N/A
RSS-247 5.4(d)	<30	<36


Note: Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.3.2 Test Procedure

The measurement is according to ANSI C63.10 clause 11.9.

1. Measure the duty cycle D of the transmitter output signal as described in 11.6.
2. Set span to at least 1.5 times the OBW.
3. Set RBW = 1% to 5% of the OBW, not to exceed 1 MHz.
4. Set VBW $\geq [3 \times \text{RBW}]$.
5. Number of points in sweep $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
6. Sweep time = auto.
7. Detector = RMS (i.e., power averaging), if available. Otherwise, use the sample detector mode.
8. Do not use sweep triggering. Allow the sweep to “free run.”
9. Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed such that the average accurately represents the true average over the ON and OFF periods of the transmitter.
10. Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function with band limits set equal to the OBW band edges. If the instrument does not have a band power function, then sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.
11. Add $[10 \log (1 / D)]$, where D is the duty cycle, to the measured power to compute the average power during the actual transmission times (because the measurement represents an average over both the ON and OFF times of the transmission). For example, add $[10 \log (1/0.25)] = 6 \text{ dB}$ if the duty cycle is 25%.

6.3.3 Test setup



6.3.4 Measurement Results

TestMode	Frequenc y[MHz]	Set Power	Original Power [dBm]	Validation Power [dBm]	d_{dB}^{Note4}	Conducted Limit[dBm]	EIRP [dBm]	EIRP Limit [dBm]	Verdict
11B	2412	42	17.45	17.97	0.52	≤ 30.00	19.55	≤ 36.00	PASS
11B	2437	42	17.51	18.03	0.52	≤ 30.00	19.61	≤ 36.00	PASS
11B	2462	42	17.33	17.65	0.32	≤ 30.00	19.23	≤ 36.00	PASS

Note1: The Duty Cycle Factor is compensated in the graph.


Note2: In the graph, the Center frequency = (Low frequency of 99% OBW + High frequency of 99% OBW) / 2.


Note3: The verified power is still in the tune-up power range and meets the requirements of KDB484596 D01 data reference. The power listed in the original certificate still applies to this case.

Note4: $d_{dB} = |\text{Verified}_{dB} - \text{original}_{dB}|$

In the graph, the Center frequency = (Low frequency of 99% OBW + High frequency of 99% OBW) / 2.

Test Graphs





6.4 Transmitter Spurious Emission-Radiated

6.4.1 Measurement Limit

Standard	Limit
FCC 47 Part 15.247,15.205,15.209	20dB below peak output power
RSS-Gen 8.9, 8.10	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in 25.205(a), must also comply with the radiated emission limits specified in 15.209(a)(see 15.205(c)).

The measurement is according to ANSI C63.10 clause 11.11 and 11.12.

6.4.2 Limit in restricted band

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
0.009~0.49	2400/F (kHz)	129-94
0.49~1.705	24000/F (kHz)	74-63
1.705~30	30	70
30~88	100	40
88~216	150	43.5
216~960	200	46
Above 960	500	54

6.4.3 Test procedures

The measurement is according to ANSI C63.10 clause 11.11 and 11.12.

Portable, small, lightweight, or modular devices that may be handheld, worn on the body, or placed on a table during operation shall be positioned on a non-conducting platform, the top of which is 80 cm above the reference ground plane. The preferred area occupied by the EUT arrangement is 1 m by 1.5 m, For emissions testing at or below 1 GHz, the table height shall be 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m. but it may be larger or smaller to accommodate various sized EUTs. For testing purposes, ceiling- and wall-mounted devices also shall be positioned on a tabletop (see also ANSI C63.10-2013 section 6.3.4 and 6.3.5). In making any tests involving handheld, body-worn, or ceiling-mounted equipment, it is essential to recognize that the measured levels may be dependent on the orientation (attitude) of the three orthogonal axes of the EUT. Thus, exploratory tests as specified in 8.3.1 shall be carried out for various axes orientations to determine the attitude having maximum or near-maximum emission level.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height varied from 1m to 4m and the EUT azimuth were varied from 0° to 360° in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Test Settings – Below 1GHz (Quasi-Peak Field Strength Measurements)

1. Set the center frequency and span to encompass frequency range to be measured.
2. Set the RBW = 100 kHz.
3. Set the VBW = 300 kHz.
4. Detector = quasi-peak.

5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Trace was allowed to stabilize.

Test Settings – Above 1GHz (Peak Field Strength Measurements)

1. Set the center frequency and span to encompass frequency range to be measured.
2. Set the RBW = 1MHz.
3. Set the VBW = 3MHz.
4. Detector = peak
5. Trace mode = max hold
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces.


Test Settings – Above 1GHz (Average Field Strength Measurements)

1. Set the center frequency and span to encompass frequency range to be measured.
2. Set the RBW = 1MHz.
3. Set the VBW = 3MHz.
4. Detector = power average (RMS).
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span} \backslash \text{RBW}$)
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces.


Frequency of emission	RBW/VBW	Sweep Time (s)
0.009~30	9KHz/30KHz	Auto
30~1000	100KHz/300KHz	5
1000~4000	1MHz/3MHz	15
4000~18000	1MHz/3MHz	40
18000~26500	1MHz/3MHz	20

6.4.4 Test Setup


Below 30MHz Test Setup



Below 1GHz Test Setup



Above 1GHz Test Setup



6.4.5 Measurement Results

A "reference path loss" is established and A_{Rpi} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss.


P_{Mea} is the field strength recorded from the instrument.


The measurement results are obtained as described below:

A_{Rpi} = Cable loss + Antenna Factor-Preamplifier gain


Result = P_{Mea} + Cable loss + Antenna Factor-Preamplifier gain = P_{Mea} + A_{Rpi} .

Mainly Supply (S01aa)







Bandedge





Secondary supply (S05aa)





Bandedge





Note:

1. The out-of-limit signal in the picture is the main frequency signal.
2. Only data in worst mode is provided.
3. Sweep the whole frequency band through the range from 30MHz to the 10th harmonic of the carrier, the Emissions in the frequency band 18GHz-26.5GHz is more than 20dB below the limit are not report.
4. The test data below 30MHz is more than 20dB lower than the limit value, so it is not provided in the report.
5. Horizontal and vertical polarity is all have been tested, the result of them is synthesized in the above data diagram.

Mainly Supply (S01aa)
RSE-11N(40M)-CH3-30MHz-1GHz

Frequency (MHz)	QuasiPeak(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
84.0	32.4	-17	49.4	7.60	40.00	V
96.0	34.53	-14	48.53	8.97	43.50	V
108.0	35.54	-13	48.54	7.96	43.50	V
144.0	34.96	-17	51.96	8.54	43.50	V
156.0	35.54	-16	51.54	7.96	43.50	H
180.0	39.93	-14	53.93	3.57	43.50	H

RSE-11N(40M)-CH3-1GHz-3GHz

Frequency (MHz)	MaxPeak(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
1033.0	40.03	2	38.03	33.97	74.00	V
1159.1	49.85	3	46.85	24.15	74.00	V
1407.3	50.24	6	44.24	23.76	74.00	H
1712.0	55.06	9	46.06	18.94	74.00	H
1738.9	52.7	9	43.7	21.30	74.00	H
2658.9	54.9	9	45.9	19.10	74.00	H

RSE-11N(40M)-CH3-1GHz-3GHz

Frequency (MHz)	Average(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
1033.0	27.26	2	25.26	26.74	54.00	V
1159.1	42.99	3	39.99	11.01	54.00	V
1407.3	38.95	6	32.95	15.05	54.00	H
1712.0	33.45	9	24.45	20.55	54.00	H
1738.9	44	9	35	10.00	54.00	H
2658.9	41.85	9	32.85	12.15	54.00	H

RSE-11N(40M)-CH3-3GHz-18GHz

Frequency (MHz)	MaxPeak(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
6458.5	45.81	-2	47.81	28.19	74.00	V
11647.0	45.31	3	42.31	28.69	74.00	H

17708.5	50.14	10	40.14	23.86	74.00	H
---------	-------	----	-------	-------	-------	---

RSE-11N(40M)-CH3-3GHz-18GHz

Frequency (MHz)	Average(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
6458.5	37.78	-2	39.78	16.22	54.00	V
11647.0	32.72	3	29.72	21.28	54.00	H
17708.5	36.06	10	26.06	17.94	54.00	H

RSE-11N(40M)-CH6-30MHz-1GHz

Frequency (MHz)	QuasiPeak(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
41.3	27.92	-13	40.92	12.08	40.00	V
84.0	32.78	-17	49.78	7.22	40.00	V
108.0	34.86	-13	47.86	8.64	43.50	V
144.0	35.59	-17	52.59	7.91	43.50	V
156.0	35.24	-16	51.24	8.26	43.50	H
180.0	39.99	-14	53.99	3.51	43.50	H

RSE-11N(40M)-CH6-1GHz-3GHz

Frequency (MHz)	MaxPeak(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
1024.0	39.24	2	37.24	34.76	74.00	V
1159.1	50.35	3	47.35	23.65	74.00	H
1249.9	43.64	5	38.64	30.36	74.00	V
1407.3	50.91	6	44.91	23.09	74.00	H
1738.7	53.11	6	47.11	20.89	74.00	H
2575.3	54.04	6	48.04	19.96	74.00	H

RSE-11N(40M)-CH6-1GHz-3GHz

Frequency (MHz)	Average(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
1024.0	26.54	2	24.54	27.46	54.00	V
1159.1	43.58	3	40.58	10.42	54.00	H
1249.9	30.53	5	25.53	23.47	54.00	V
1407.3	39.57	6	33.57	14.43	54.00	H
1738.7	44.85	6	38.85	9.15	54.00	H

2575.3	41.45	6	35.45	12.55	54.00	H
--------	-------	---	-------	-------	-------	---

RSE-11N(40M)-CH6-3GHz-18GHz

Frequency (MHz)	MaxPeak(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
4481.8	43.83	-4	47.83	30.17	74.00	V
7799.5	47.69	-2	49.69	26.31	74.00	H
17864.1	48.57	11	37.57	25.43	74.00	H

RSE-11N(40M)-CH6-3GHz-18GHz

Frequency (MHz)	Average(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
4481.8	32.8	-4	36.8	21.20	54.00	V
7799.5	36.1	-2	38.1	17.90	54.00	H
17864.1	35.65	11	24.65	18.35	54.00	H

RSE-11N(40M)-CH9-30MHz-1GHz

Frequency (MHz)	QuasiPeak(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
41.9	28.24	-13	41.24	11.76	40.00	V
96.0	34.97	-14	48.97	8.53	43.50	V
144.0	35.84	-17	52.84	7.66	43.50	V
156.0	35.67	-16	51.67	7.83	43.50	V
180.0	40.82	-14	54.82	2.68	43.50	H
204.0	37.47	-13	50.47	6.03	43.50	H

RSE-11N(40M)-CH9-1GHz-3GHz

Frequency (MHz)	MaxPeak(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
1086.3	41.01	3	38.01	32.99	74.00	V
1127.5	41.24	3	38.24	32.76	74.00	V
1159.1	47	3	44	27.00	74.00	V
1329.4	43.27	6	37.27	30.73	74.00	V
1712.0	46.06	6	40.06	27.94	74.00	V
2652.5	54.36	6	48.36	19.64	74.00	H

RSE-11N(40M)-CH9-1GHz-3GHz

Frequency (MHz)	Average(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
-----------------	-----------------	-----------	---------------	------------	---------------	----------

1086.3	28.36	3	25.36	25.64	54.00	V
1127.5	28.18	3	25.18	25.82	54.00	V
1159.1	38.92	3	35.92	15.08	54.00	V
1329.4	30.53	6	24.53	23.47	54.00	V
1712.0	33.31	6	27.31	20.69	54.00	V
2652.5	41.88	6	35.88	12.12	54.00	H

RSE-11N(40M)-CH9-3GHz-18GHz

Frequency (MHz)	MaxPeak(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
7799.5	45.14	-2	47.14	28.86	74.00	H
11655.5	45.6	3	42.6	28.40	74.00	V
16693.6	48.48	10	38.48	25.52	74.00	V

RSE-11N(40M)-CH9-3GHz-18GHz

Frequency (MHz)	Average(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
7799.5	32.74	-2	34.74	21.26	54.00	H
11655.5	32.79	3	29.79	21.21	54.00	V
16693.6	35.87	10	25.87	18.13	54.00	V

Secondary supply (S05aa)
RSE-11N(40M)-CH3-30MHz-1GHz

Frequency (MHz)	QuasiPeak(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
96.1	34.09	-14	48.09	9.41	43.50	V
144.0	37.05	-17	54.05	6.45	43.50	H
156.0	38.2	-16	54.2	5.30	43.50	H
168.0	34.1	-15	49.1	9.40	43.50	H
180.0	41.87	-14	55.87	1.63	43.50	H
202.6	36.4	-13	49.4	7.10	43.50	V

RSE-11N(40M)-CH3-1GHz-3GHz

Frequency (MHz)	MaxPeak(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
1091.1	41.24	3	38.24	32.76	74.00	V
1112.2	41.61	3	38.61	32.39	74.00	V
1147.2	41.35	3	38.35	32.65	74.00	V
1421.9	44.06	6	38.06	29.94	74.00	V
1511.4	44.61	6	38.61	29.39	74.00	V
2756.7	54.15	6	48.15	19.85	74.00	H

RSE-11N(40M)-CH3-1GHz-3GHz

Frequency (MHz)	Average(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
1091.1	28.57	3	25.57	25.43	54.00	V
1112.2	28.47	3	25.47	25.53	54.00	V
1147.2	28.71	3	25.71	25.29	54.00	V
1421.9	31.1	6	25.1	22.90	54.00	V
1511.4	32.3	6	26.3	21.70	54.00	V
2756.7	41.57	6	35.57	12.43	54.00	H

RSE-11N(40M)-CH3-3GHz-18GHz

Frequency (MHz)	MaxPeak(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
4847.9	44.23	-3	47.23	29.77	74.00	H
7799.5	47.78	-2	49.78	26.22	74.00	H

11606.8	46.03	4	42.03	27.97	74.00	H
16713.2	48.12	10	38.12	25.88	74.00	H

RSE-11N(40M)-CH3-3GHz-18GHz

Frequency (MHz)	Average(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
4847.9	30.33	-3	33.33	23.67	54.00	H
7799.5	35.27	-2	37.27	18.73	54.00	H
11606.8	32.86	4	28.86	21.14	54.00	H
16713.2	35.88	10	25.88	18.12	54.00	H

RSE-11N(40M)-CH6-30MHz-1GHz

Frequency (MHz)	QuasiPeak(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
96.0	34.29	-14	48.29	9.21	43.50	V
108.0	32.72	-13	45.72	10.78	43.50	V
144.0	36.01	-17	53.01	7.49	43.50	V
156.0	39.89	-16	55.89	3.61	43.50	H
179.9	41.57	-14	55.57	1.93	43.50	H
828.0	34.26	0	34.26	11.74	46.00	H

RSE-11N(40M)-CH6-1GHz-3GHz

Frequency (MHz)	MaxPeak(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
1027.6	39.74	2	37.74	34.26	74.00	V
1048.5	40.54	3	37.54	33.46	74.00	V
1208.2	41.4	4	37.4	32.60	74.00	V
1269.6	43.08	5	38.08	30.92	74.00	V
2132.3	49.83	5	44.83	24.17	74.00	V
2693.8	53.76	5	48.76	20.24	74.00	V

RSE-11N(40M)-CH6-1GHz-3GHz

Frequency (MHz)	Average(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
1027.6	27.07	2	25.07	26.93	54.00	V
1048.5	27.9	3	24.9	26.10	54.00	V
1208.2	29.01	4	25.01	24.99	54.00	V

1269.6	30.56	5	25.56	23.44	54.00	V
2132.3	37.09	5	32.09	16.91	54.00	V
2693.8	41.49	5	36.49	12.51	54.00	V

RSE-11N(40M)-CH6-3GHz-18GHz

Frequency (MHz)	MaxPeak(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
4875.0	44.13	-3	47.13	29.87	74.00	H
7313.4	44.99	-2	46.99	29.01	74.00	H
10388.4	44.99	1	43.99	29.01	74.00	H
16498.6	47.62	10	37.62	26.38	74.00	H

RE-11N(40M)-CH6-3GHz-18GHz

Frequency (MHz)	Average(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
4875.0	31	-3	34	23.00	54.00	H
7313.4	32.02	-2	34.02	21.98	54.00	H
10388.4	31.39	1	30.39	22.61	54.00	H
16498.6	35.21	10	25.21	18.79	54.00	H

RSE-11N(40M)-CH9-30MHz-1GHz

Frequency (MHz)	QuasiPeak(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
95.9	34.26	-14	48.26	9.24	43.50	V
108.0	32.99	-13	45.99	10.51	43.50	V
144.0	36.84	-17	53.84	6.66	43.50	V
155.9	38.25	-16	54.25	5.25	43.50	V
180.0	42	-14	56	1.50	43.50	H
204.0	35.18	-13	48.18	8.32	43.50	V

RSE-11N(40M)-CH9-1GHz-3GHz

Frequency (MHz)	MaxPeak(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
1028.2	39.29	2	37.29	34.71	74.00	V
1063.8	41.18	3	38.18	32.82	74.00	V
1110.8	41.1	3	38.1	32.90	74.00	V

1170.4	41.29	4	37.29	32.71	74.00	V
1200.2	41.6	4	37.6	32.40	74.00	V
1263.0	42.31	4	38.31	31.69	74.00	V

RSE-11N(40M)-CH9-1GHz-3GHz

Frequency (MHz)	Average(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
1028.2	26.76	2	24.76	27.24	54.00	V
1063.8	28.17	3	25.17	25.83	54.00	V
1110.8	28.33	3	25.33	25.67	54.00	V
1170.4	28.55	4	24.55	25.45	54.00	V
1200.2	28.81	4	24.81	25.19	54.00	V
1263.0	30.31	4	26.31	23.69	54.00	V

RSE-11N(40M)-CH9-3GHz-18GHz

Frequency (MHz)	MaxPeak(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
3133.6	38.57	-7	45.57	35.43	74.00	V
3921.6	39.01	-6	45.01	34.99	74.00	V
5593.6	41.68	-3	44.68	32.32	74.00	H
7799.5	47.04	-2	49.04	26.96	74.00	H
16082.8	48.85	9	39.85	25.15	74.00	H

RSE-11N(40M)-CH9-3GHz-18GHz

Frequency (MHz)	Average(dBμV/m)	ARpl (dB)	PMea (dBμV/m)	Margin(dB)	Limit(dBμV/m)	Polarity
3133.6	26.32	-7	33.32	27.68	54.00	V
3921.6	26.67	-6	32.67	27.33	54.00	V
5593.6	29.06	-3	32.06	24.94	54.00	H
7799.5	34.86	-2	36.86	19.14	54.00	H
16082.8	35.64	9	26.64	18.36	54.00	H


6.5 AC Powerline Conducted Emission

6.5.1 Method of Measurement: ANSI C63.10-2013-clause 6.2

1. The one EUT cable configuration and arrangement and mode of operation that produced the emission with the highest amplitude relative to the limit is selected for the final measurement, while applying the appropriate modulating signal to the EUT.
2. If the EUT is relocated from an exploratory test site to a final test site, the highest emissions shall be remaximized at the final test location before final ac power-line conducted emission measurements are performed.
3. The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment in the system) is then performed for the full frequency range for which the EUT is being tested for compliance without further variation of the EUT arrangement, cable positions, or EUT mode of operation.
4. If the EUT is comprised of equipment units that have their own separate ac power connections, e.g., floor-standing equipment with independent power cords for each shelf that are able to connect directly to the ac power network, each current-carrying conductor of one unit is measured while the other units are connected to a second (or more) LISN(s). All units shall be separately measured. If a power strip is provided by the manufacturer, to supply all of the units making up the EUT, only the conductors in the power cord of the power strip shall be measured.

If the EUT uses a detachable antenna, these measurements shall be made with a suitable dummy load connected to the antenna output terminals; otherwise, the tests shall be made with the antenna connected and, if adjustable, fully extended. When measuring the ac conducted emissions from a device that operates between 150 kHz and 30 MHz a non-detachable antenna may be replaced with a dummy load for the measurements within the fundamental emission band of the transmitter, but only for those measurements.³⁶ Record the six highest EUT emissions relative to the limit of each of the current-carrying conductors of the power cords of the equipment that comprises the EUT over the frequency range specified by the procuring or regulatory agency. Diagram or photograph the test setup that was used. See Clause 8 for full reporting requirements.

6.5.2 Test Setup



6.5.3 Test Condition

Voltage (V)	Frequency (Hz)
120	60


6.5.4 Measurement limit

(Quasi-peak-average Limit)

Frequency range (MHz)	Quasi-peak Limit (dBμV)	Average Limit (dBμV)	Conclusion
0.15 to 0.5	66 to 56	56 to 46	P
0.5 to 5	56	46	
5 to 30	60	50	

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

6.5.5 Measurement Result



Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas.Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.153731	---	42.37	55.80	13.42	15000.0	9.000	L1	ON	9.6
0.153731	56.76	---	65.80	9.03	15000.0	9.000	L1	ON	9.6
0.176119	---	35.98	54.67	18.69	15000.0	9.000	L1	ON	9.6
0.176119	51.95	---	64.67	12.71	15000.0	9.000	L1	ON	9.6
0.187313	---	33.56	54.16	20.60	15000.0	9.000	L1	ON	9.6
0.187313	49.59	---	64.16	14.57	15000.0	9.000	L1	ON	9.6
0.202238	---	29.78	53.52	23.74	15000.0	9.000	L1	ON	9.6
0.202238	47.66	---	63.52	15.86	15000.0	9.000	L1	ON	9.6
3.586481	---	24.02	46.00	21.98	15000.0	9.000	L1	ON	9.6
3.586481	35.12	---	56.00	20.88	15000.0	9.000	L1	ON	9.6
15.664538	---	22.82	50.00	27.18	15000.0	9.000	L1	ON	9.9
15.664538	29.79	---	60.00	30.21	15000.0	9.000	L1	ON	9.9

Note: All modes have been tested and only the worst mode is recorded in the report.

Annex A: Revised History

Version	Revised Content
V0	Initial

Annex B: Accreditation Certificate



END OF REPORT