

RADIATED EMISSIONS DATA SHEET

FA260NF

DATE: 7/07/00 TESTED BY: S. J. J. J. APPROVED BY: _____

TEST SAMPLE (model): ADEMCO Receiver (unit 1)

TEST METHOD: ANSI C63.4 - 1992

TEST SPECIFICATION: FCC Part 15, Subpart C

NOTES: 1) $F_c = 345$ MHz, 2) Detector = Peak, 3) Frequency range scanned to

4 GHz. Emissions not reported were more than 20 dB below the specified limit.

4) Conv. reading = $10^{\frac{(\text{Meter reading} + \text{Cable/Amp factor} + \text{Antenna factor})}{20}}$

5) Corr. reading = Conv. reading X Duty cycle

FREQUENCY (MHz)	POLARITY (V / H)	METER READING (dB uV)	CABLE/AMP FACTOR (dB)	ANTENNA FACTOR (dB/M)	CONV. READING (uV/M)	DUTY CYCLE (%)	CORR. READING (uV/M)	LIMIT @ 3M (uV/M)
	H					NONE		
30								
↓								↓
334.3		16.0	1.4	16	46.77		46.77	200
↓								↓
668.5		5.8	1.8	21.1	27.22		27.22	200
↓								↓
1002.9		1.69	2.1	25.2	28.15		28.15	500
↓								↓
1337.2		0.85	2.5	28.8	40.05		40.05	500
↓								↓
1671.5	V	0.3	3.0	31.2	53.088		53.088	500
↓						↓		↓

®ADEMCO

Alarm Device Manufacturing Company
A Division of Pittway Corporation
165 Eileen way
Syosset, NY 11791