

# **FCC RF Exposure Report**

FCC ID : 188WAC5302D-S

Equipment : 802.11ac Wall-Plate Unified Access Point

Model No. : WAC5302D-S

Brand Name : ZYXEL

Applicant : Zyxel Communications Corporation

Address : No.2 Industry East RD. IX, Hsinchu Science

Park, Hsinchu 30075, Taiwan

Standard : 47 CFR FCC Part 2.1091

Received Date : Aug. 24, 2016

Tested Date : Sep. 07 ~ Oct. 17, 2016

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: Approved by:

Along Cherd/ Assistant Manager Gary Chang / Manager

Testing Laboratory

Report No.: FA682405 Page: 1 of 6



# **Table of Contents**

1	MPE EVALUATION OF MOBILE DEVICES	4
	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE	
	MPE EVALUATION FORMULA	
1.3	MPE EVALUATION RESULTS	5
2	TEST LABORATORY INFORMATION	6

Report No.: FA682405

Page : 2 of 6



# **Release Record**

Report No.	Version	Description	Issued Date
FA682405	Rev. 01	Initial issue	Feb. 10, 2017

Report No.: FA682405 Page: 3 of 6



## 1 MPE EVALUATION OF MOBILE DEVICES

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

## 1.1 LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

Frequency Range (MHz)	Power Density (mW /cm²)	Averaging Time (minutes)
300~1500	F/1500	30
1500~100000	1.0	30

## 1.2 MPE EVALUATION FORMULA

$$Pd = \frac{Pt}{4*Pi*R^2}$$

Where

Pd= Power density in mW/cm<sup>2</sup>

Pt= EIRP in mW

Pi= 3.1416

R= Measurement distance

Report No.: FA682405 Page: 4 of 6



## 1.3 MPE EVALUATION RESULTS

#### **MPE Evaluation of Single Transmission**

#### Non-beamforming mode

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
2412~2462	18.56	5.82	20	0.055	1
5150~5250	19.35	5	20	0.054	1
5745~5825	19.57	5	20	0.057	1

#### Beamforming mode

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm²)
5180~5240	19.22	8.01	20	0.105	1
5745~5825	19.38	8.01	20	0.109	1

**Note:** Directional gain =  $5+10* \log(2/1) = 8.01 \text{ dBi}$ 

#### **MPE Evaluation of Simultaneous Transmission**

2.4 and 5GHz can transmit at the same time, MPE evaluation is as below formula

PD1 / Limit1 + PD2 / Limit 2 + ..... < 1, PD = Power density

#### Non-beamforming mode

MPE Evaluation = Maximum MPE of 2.4GHz + Maximum MPE of 5 GHz = 0.055 / 1 + 0.057 / 1 = 0.112 < 1

#### Beamforming mode

MPE Evaluation = Maximum MPE of 2.4GHz + Maximum MPE of 5 GHz = 0.055 / 1 + 0.109 / 1 = 0.164 < 1

#### Conclusion

MPE evaluations of single and simultaneous transmission meet the requirement of standard.

Report No.: FA682405 Page: 5 of 6



# 2 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <a href="http://www.icertifi.com.tw">http://www.icertifi.com.tw</a>.

#### Linkou

Tel: 886-2-2601-1640 No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C.

#### Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

#### Kwei Shan Site II

Tel: 886-3-271-8640 No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC\_Service@icertifi.com.tw

==END==

Report No.: FA682405 Page: 6 of 6