



TEST REPORT

Applicant: Shenzhen Baishi Internet Technology Co. , Ltd.
Address of Applicant: Floor 5, Building 1, Baichuanda Industrial Park, No. 102, Longlan Avenue, Dalang Street, Longhua District, Shenzhen, Guangdong China
Manufacturer: Shenzhen Baishi Internet Technology Co. , Ltd.
Address of Manufacturer: Floor 5, Building 1, Baichuanda Industrial Park, No. 102, Longlan Avenue, Dalang Street, Longhua District, Shenzhen, Guangdong China
Product Name: LCD Projector
Model No.: BL360,BL400,Gimbal A2,Gimbal A2 Pro,Gimbal A2 Mini, Gimbal A2S,BL360 PRO,BL360 PLUS,B11,P5
Trade Mark: N/A
FCC ID: 2BADK-BL360
Applicable standards: FCC CFR Title 47 Part 15 Subpart E Section 15.407
Date of Test: Feb.12, 2025-Feb.26, 2025
Date of report issued: Feb.27, 2025

Remark:

The results shown in this test report refer only to the sample(s) tested , this test report cannot be reproduced, except in full without prior written permission of the company.

The report would be invalid without specific stamp of test institute and the signatures of compiler and approver

Prepared By

Shenzhen ETR Standard Technology Co., Ltd.

Address: No.103, No.10, Phase I, Zone 3, Xinxing Industrial Park, Xinhe, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Compiled by:

Reviewed by:

Approved by:

Project Engineer

Project Manager

Authorized Signature



Report Revision History		
Report No.	Description	Issue Date
ET-25020206E03	Original	Feb.27, 2025

Contents

Page

1	TEST SUMMARY	4
1.1	MEASUREMENT UNCERTAINTY	4
2	GENERAL INFORMATION	5
2.1	GENERAL DESCRIPTION OF EUT	5
2.2	TEST MODE	7
2.3	DESCRIPTION OF SUPPORT UNITS	8
2.4	DEVIATION FROM STANDARDS.....	8
2.5	ABNORMALITIES FROM STANDARD CONDITIONS.....	8
2.6	TEST FACILITY	8
2.7	TEST LOCATION	8
2.8	ADDITIONAL INSTRUCTIONS.....	8
3	TEST INSTRUMENTS LIST	9
4	TEST RESULTS AND MEASUREMENT DATA	10
4.1	ANTENNA REQUIREMENT	10
4.2	CONDUCTED EMISSIONS	11
4.3	DUTY CYCLE.....	14
4.4	CONDUCTED OUTPUT POWER.....	20
4.5	BANDWIDTH &99% OCCUPY BANDWIDTH.....	23
4.6	POWER SPECTRAL DENSITY	37
4.7	BAND EDGE.....	48
4.7.1	Conducted test Method	48
4.8	SPURIOUS EMISSION	57
4.8.1	Radiated Emission Method	57
4.8.2	Conducted Emission Method	67
4.9	FREQUENCY STABILITY	76
5	TEST SETUP PHOTO	82
6	EUT CONSTRUCTIONAL DETAILS.....	82

1 Test Summary

Test Item	Section in CFR 47	Result	Test by
Antenna requirement	15.203	Pass	/
AC Power Line Conducted Emission	15.207	Pass	Jason Huang
Conducted Output Power	15.407 (a)(1)/(a)(3)	Pass	Kara Wu
26dB Bandwidth and 99% Occupied Bandwidth	15.407 (a)(12)	Pass	Kara Wu
6dB Bandwidth	15.407 (e)	Pass	Kara Wu
Power Spectral Density	15.407(a)(1)/(a)(3)	Pass	Kara Wu
Band Edge	15.407(b)(1)/(b)(4)	Pass	Kara Wu
Spurious Emission	15.205/15.209 15.407(b)(1)/(b)(4)/(b)(8)	Pass	Jason Huang
Frequency Stability	15.407(g)	Pass	Kara Wu

Remarks:

1. Pass: The EUT complies with the essential requirements in the standard.
2. Test according to ANSI C63.10:2013
3. Note: Compliance determination rules
 - 1).The Compliance determination of test results does not take into account measurement uncertainty. Measurement results are determined based on regulatory limitations or requirements specified by the applicant/manufacture. If measurement uncertainty is taken into account, the applicant/manufacture will bear all possible risks of non-compliance.
 - 2).The measurement uncertainty please refer to each test result in the "Measurement Uncertainty"

1.1 Measurement Uncertainty

Test Item	Measurement Uncertainty	Notes
Occupied Channel Bandwidth	$\pm 0.55\%$	(1)
RF output power, conducted	$\pm 0.99\text{dB}$	(1)
Power Spectral Density, conducted	$\pm 0.61\text{dB}$	(1)
Unwanted Emissions, conducted	$\pm 0.64\text{dB}$	(1)
AC Power Line Conducted Emission	$\pm 2.64\text{ dB}$	(1)
Radiated emissions 9K-30MHz	$\pm 3.98\text{dB}$	(1)
Radiated emissions 30M- 1GHz	$\pm 4.32\text{dB}$	(1)
Radiated emissions 1GHz-18GHz	$\pm 4.56\text{dB}$	(1)
Radiated emissions 18GHz-40GHz	$\pm 4.59\text{ dB}$	(1)
Frequency error	$U_c=1 \times 10^{-7}$	(1)

Note (1): The measurement uncertainty is for coverage factor of $k=2$ and a level of confidence of 95%.

2 General Information

2.1 General Description of EUT

Product Name:	LCD Projector
Model No.:	BL360,BL400,Gimbal A2,Gimbal A2 Pro,Gimbal A2 Mini, Gimbal A2S,BL360 PRO,BL360 PLUS,B11,P5
Difference of model(s)	All the model are the same circuit and RF module, except the model names.
Test Model:	BL360
Hardware Version:	N/A
Software Version:	N/A
Sample(s) Status:	Engineer sample
Operation Frequency:	☒ 5180-5240MHz for 802.11a/n(HT20)/ac20/ax20; 5190-5230MHz for 802.11n(HT40)/ac40/ax40; 5210MHz for 802.11 ac80;/ax80 ☒ 5745-5825 MHz for 802.11a/n(HT20)/ac20/ax20; 5755-5795 MHz for 802.11n(HT40)/ac40/ax20; 5775MHz for 802.11 ac80 ;/ax80
Channel numbers:	☒ 4 channels for 802.11a/n20/ac20/ax20 in the 5180-5240MHz band; 2 channels for 802.11 n40/ac40/ax40 in the 5190-5230MHz band ; 1 channels for 802.11 ac80/ax80 in the 5210MHz band ; ☒ 5 channels for 802.11a/n20/ac20/ax20 in the 5745-5825MHz band ; 2 channels for 802.11 n40/ac40/ax40 in the 5755-5795MHz band ; 1 channels for 802.11 ac80/ax80 in the 5775MHz band
Channel bandwidth:	802.11a/802.11n(HT20)/ 802.11ac(VHT20) / 802.11ax(HE20): 20MHz 802.11n(HT40)/ 802.11ac(VHT40) / 802.11ax(HE40): 40MHz 802.11ac(VHT80)/ax(HE80) : 80MHz
Data Rate	802.11a: 6,9,12,18,24,36,48,54Mbps; 802.11n(HT20/HT40):MCS0-MCS15; 802.11ac(VHT/20/40/80):NSS1, MCS0-MCS9 802.11ax(HE/20/40/80):NSS1, MCS0-MCS9
Modulation technology:	Orthogonal Frequency Division Multiplexing (OFDM) with BPSK/QPSK/16QAM/64QAM/256QAM/1024QAM
Antenna Type:	FPCB antenna
Antenna gain:	3.46dBi (Note: Antenna information is provided by applicant, Testing lab is not responsible for the accuracy of the information.)
Battery	N/A
Power supply:	AC100-240V 50/60Hz 2A
Adapter Model:	N/A

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180MHz	38	5190MHz	40	5200MHz	42	5210MHz
44	5220MHz	46	5230MHz	48	5240MHz	/	/
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
149	5745MHz	151	5755MHz	153	5765MHz	155	5775MHz
157	5785MHz	159	5795MHz	161	5805MHz	/	/
165	5825MHz	/					

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)		
	802.11 a /n(HT20)/ac(VHT20) /ax(HE20)	802.11 n(HT40)/ac(VHT40) /ax(HE20)	802.11ac(VHT80) /ax(HE80)
Lowest channel	5180	5190	5210
Middle channel	5200	X	
Highest channel	5240		

Test channel	Frequency (MHz)		
	802.11 a /n(HT20)/ac(VHT20) /ax(HE20)	802.11 n(HT40)/ac(VHT40) /ax(HE20)	802.11ac(VHT80) /ax(HE80)
Lowest channel	5745	5755	5775
Middle channel	5785	X	
Highest channel	5825		

2.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode(or with a duty cycle $\geq 98\%$)
<i>Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Pretest Mode	Description
Mode 1	802.11a / n 20/ac 20/ax 20 CH36/ CH40/ CH 48 802.11a / n 20/ac 20/ax 20 CH149/ CH157/ CH 165
Mode 2	802.11n 40/ax 40 CH38/ CH 46 802.11n 40/ax 40 CH 151 / CH 159
Mode 3	802.11 ac80 CH 42/CH 155 802.11 ax80 CH 42/CH 155
Mode 4	/
Mode 5	Link Mode

Conducted Emission	
Final Test Mode	Description
Mode 5	Link Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11a / n 20/ac 20/ax 20 CH36/ CH40/ CH 48 802.11a / n 20/ac 20/ax 20 CH149/ CH157/ CH 165
Mode 2	802.11n 40/ax 40 CH38/ CH 46 802.11n 40/ax 40 CH 151 / CH 159
Mode 3	802.11 ac80 CH 42/CH 155 802.11 ax80 CH 42/CH 155
Mode 4	/

Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

2.3 Description of Support Units

No.	Description	Manufacturer	Model	Serial Number
1	Notebook computer	DELL	Vostro 3520	/

2.4 Deviation from Standards

None.

2.5 Abnormalities from Standard Conditions

None.

2.6 Test Facility

Test laboratory: Shenzhen ETR Standard Technology Co., Ltd.
CNAS Registration Number: L11864
A2LA Certificate Number: 6640.01
FCC Designation Number: CN1326
FCC Test Firm Registration: 183064

2.7 Test Location

All tests were performed at:

Laboratory location: No.103, No.10, Phase I, Zone 3, Xinxing Industrial Park, Xinhe, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone: +86 755 85259392

2.8 Additional Instructions

Test Software	ADB serial port command
Power level setup	Default

3 Test Instruments list

Conducted Emission

Item	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	EMI Test Receiver	Rohde&schwarz	ESCI3	100605	2024.3.12	2025.3.11
2	Artificial power network	schwarabeck	NSLK8127	8127483	2024.3.12	2025.3.11
3	Artificial power network	ETS	3186/2NM	1132	2024.3.12	2025.3.11
4	10dB attenuator	HUBER+SUHNER	10dB	/	2024.3.12	2025.3.11
5	Cable 4	HUBER SUNNER	3M	/	2024.3.12	2025.3.11
6	Absorbing Clamp	schwarabeck	MDS21	D69250	2024.3.12	2025.3.11

Radiated Emission & RF Conducted test:

Item	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101032	2024.3.12	2025.3.11
2	Broadband antenna	schwarabeck	VULB9168	1064	2024.3.19	2026.3.21
3	Horn antenna	schwarabeck	BBHA9120D	9120D-1145	2024.3.19	2026.3.21
4	Amplifier	EMtrace	RP01A	50117	2024.3.12	2025.3.11
5	Amplifier	Space-Dtronic	EWLAN0118G-P40	19113001	2024.3.12	2025.3.11
6	Spectrum analyzer	KEYSIGHT	N9020A	MY55370280	2024.3.12	2025.3.11
7	Power detector meter	MWRFTtest	MW100-PSB	MW201020JYT	2024.3.12	2025.3.11
8	Signal generator	Agilent	N5182A	MY49060455	2024.3.12	2025.3.11
9	Spectrum analyzer	Rohde&schwarz	FSU40	1166.1660K43	2024.3.12	2025.3.11
10	Amplifier	SKET	LNPA_1840-50	SK2019040302	2024.3.12	2025.3.11
11	Horn antenna	schwarabeck	BBHA 9170	946	2024.3.19	2026.3.21
12	Loop antenna	schwarabeck	FMZB 1519 B	1519	2024.3.19	2026.3.21
13	Cable 6	HUBER SUNNER	0.5M	/	2024.3.12	2025.3.11
14	Cable7	HUBER SUNNER	2.0M	/	2024.3.12	2025.3.11
15	Cable8	HUBER SUNNER	6.0M	/	2024.3.12	2025.3.11
16	Filter	Xin bo	XBLBQ-GTA29	210410-3-2	2024.3.12	2025.3.11
17	Power meter	Rohde&Schwarz	NRP-Z11	1138.3004.02-117725-vh	2024.3.12	2025.3.11
18	Temp. & Humidity Chamber	Jiecheng Instrument	QA-LP-80	20160705001	2024/4/23	2025/4/22

Note: the calibration interval of the above test instruments is 12 or 24 months and the calibrations are traceable to international system unit (SI).

Software Name	Manufacturer	Model	Version
RF test software	MWRFTtest	MTS 8310	V2.0.0.0
Conducted test software	EZ-EMC	Farad	Ver.EMC-CON 3A1.1
Radiated test software	EZ-EMC	Farad	Ver.FA-03A2 RE

4 Test results and Measurement Data

4.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203
<i>15.203 requirement:</i> <i>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</i>	
E.U.T Antenna:	
<i>The antennas are FPCB Antenna, the best case gain of the antennas are 3.46dBi, reference to the appendix II for details</i>	

4.2 Conducted Emissions


Test Requirement:	FCC Part15 C Section 15.207						
Test Method:	ANSI C63.10:2013						
Test Frequency Range:	150KHz to 30MHz						
Class / Severity:	Class B						
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto						
Limit:	Frequency range (MHz)		Limit (dBuV)				
			Quasi-peak		Average		
	0.15-0.5		66 to 56*		56 to 46*		
	0.5-5		56		46		
	5-30		60		50		
* Decreases with the logarithm of the frequency.							
Test setup:	Reference Plane 40cm LISN AUX Equipment E.U.T 80cm LISN Filter AC power EMI Receiver Test table/Insulation plane Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m						
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.						
Test Instruments:	Refer to section 3.0 for details						
Test mode:	Refer to section 2.2 for details						
Test environment:	Temp.:	22.6°C	Humid.:	46%	Press.:	1012mbar	
Test voltage:	AC 120V						
Test results:	Pass						

Remark:

1. Both high voltage and low voltage have been tested, and the report only shows the worst case data with AC 120V/60Hz.
2. All mode have been tested, the report only shows the worst mode (802.11n20 5180MHz)


Measurement Result

Line:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1952	46.24	9.81	56.05	63.81	-7.76	QP
2	0.1952	36.86	9.81	46.67	53.81	-7.14	AVG
3	0.4964	42.29	9.94	52.23	56.06	-3.83	QP
4	0.4964	25.22	9.94	35.16	46.06	-10.90	AVG
5	0.6128	40.26	9.94	50.20	56.00	-5.80	QP
6	0.6128	28.76	9.94	38.70	46.00	-7.30	AVG
7	1.1624	40.16	9.94	50.10	56.00	-5.90	QP
8	1.1624	26.68	9.94	36.62	46.00	-9.38	AVG
9	2.9805	39.88	9.85	49.73	56.00	-6.27	QP
10	2.9805	28.37	9.85	38.22	46.00	-7.78	AVG
11	29.9130	45.12	9.49	54.61	60.00	-5.39	QP
12	29.9130	33.34	9.49	42.83	50.00	-7.17	AVG

Neutral:




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1859	50.22	9.81	60.03	64.22	-4.19	QP
2	0.1859	34.30	9.81	44.11	54.22	-10.11	AVG
3	0.2630	43.53	9.83	53.36	61.34	-7.98	QP
4	0.2630	30.27	9.83	40.10	51.34	-11.24	AVG
5	0.6900	37.47	9.94	47.41	56.00	-8.59	QP
6	0.6900	17.92	9.94	27.86	46.00	-18.14	AVG
7	16.3410	44.28	9.73	54.01	60.00	-5.99	QP
8	16.3410	32.04	9.73	41.77	50.00	-8.23	AVG
9	18.4375	41.96	9.70	51.66	60.00	-8.34	QP
10	18.4375	31.01	9.70	40.71	50.00	-9.29	AVG
11	24.3779	44.54	9.59	54.13	60.00	-5.87	QP
12	24.3779	31.92	9.59	41.51	50.00	-8.49	AVG

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

4.3 Duty cycle

Test Method :	ANSI C63.10:2013	
Limit:	/	
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. The table is supported by two vertical legs. Below the table is a Ground Reference Plane.	
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 22.9°C	Humid.: 46%RH
Test voltage:	AC120	
Test results:	Pass	

Measurement Result

5180-5240MHz

Mode	Duty cycle (%)	Correction Factor (dB)
TX 802.11a Mode	97.75	0.1
TX 802.11n20 Mode	93.09	0.31
TX 802.11ac20 Mode	93.4	0.3
TX 802.11ax20 Mode	93.2	0.31
TX 802.11n40 Mode	95.02	0.22
TX 802.11a40 Mode	95.12	0.22
TX 802.11ax40 Mode	87.86	0.56
TX 802.11ac80 Mode	90.66	0.43
TX 802.11ax80 Mode	81.18	0.91


5745-5825 MHz

Mode	Duty cycle (%)	Correction Factor (dB)
TX 802.11a Mode	97.2	0.12
TX 802.11n20 Mode	95.83	0.18
TX 802.11ac20 Mode	94.12	0.26
TX 802.11ax20 Mode	93.09	0.31
TX 802.11n40 Mode	89.29	0.49
TX 802.11a40 Mode	85.71	0.67
TX 802.11ax40 Mode	81.4	0.89
TX 802.11ac80 Mode	87.5	0.58
TX 802.11ax80 Mode	81.4	0.89


Test plot

5180-5240MHz


(802.11a) plot




(802.11 n20) plot




(802.11ac20) plot




(802.11 ax20) plot




(802.11 n40) plot




(802.11 ac40) plot




(802.11ax40) plot



(802.11ac80) plot



(802.11ax80) plot




5745-5825 MHz


(802.11a) plot




(802.11 n20) plot




(802.11ac20) plot




(802.11 ax20) plot




(802.11 n40) plot




(802.11 ac40) plot




(802.11ax40) plot




(802.11ac80) plot



(802.11ax80) plot



4.4 Conducted Output Power

Test Requirement:	FCC Part15 E Section 15.407 (a)(1)/(a)(3)	
Test Method:	ANSI C63.10:2013 and KDB 789033 D02 General U-NII Test Procedures New Rules v02r01	
Limit:	5150-5250MHz : 250mW 5725~5850MHz : 1W	
Test setup:	 The diagram illustrates the test setup. A 'Power Meter' is connected to an 'E.U.T' (Equipment Under Test) by a red cable. Both components are placed on a 'Non-Conducted Table'. Below the table is a 'Ground Reference Plane'.	
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 22.9°C	Humid.: 46%RH
Test voltage:	AC120	
Test results:	Pass	

Measurement Result


5180-5240MHz

Test Channel	Frequency	Correction Factor	Maximum output power	Total Power	LIMIT	Result
	(MHz)	(dB)	(dBm)	(dBm)	dBm	
TX 802.11a Mode						
CH36	5180	0.10	13.77	13.87	23.98	Pass
CH40	5200	0.10	13.63	13.73	23.98	Pass
CH48	5240	0.10	12.90	13.00	23.98	Pass
TX 802.11 n20 Mode						
CH36	5180	0.31	13.64	13.95	23.98	Pass
CH40	5200	0.31	13.43	13.74	23.98	Pass
CH48	5240	0.31	12.71	13.02	23.98	Pass
TX 802.11 ac20 Mode						
CH36	5180	0.30	13.56	13.86	23.98	Pass
CH40	5200	0.30	13.43	13.73	23.98	Pass
CH48	5240	0.30	13.02	13.32	23.98	Pass
TX 802.11 ax20 Mode						
CH36	5180	0.31	13.03	13.34	23.98	Pass
CH40	5200	0.31	13.04	13.35	23.98	Pass
CH48	5240	0.31	13.01	13.32	23.98	Pass
TX 802.11 n40 Mode						
CH38	5190	0.22	12.54	12.76	23.98	Pass
CH46	5230	0.22	11.90	12.12	23.98	Pass
TX 802.11 ac40 Mode						
CH38	5190	0.22	12.53	12.75	23.98	Pass
CH46	5230	0.22	12.87	13.09	23.98	Pass
TX 802.11 ax40 Mode						
CH38	5190	0.56	12.50	13.06	23.98	Pass
CH46	5230	0.56	12.33	12.89	23.98	Pass
TX 802.11 ac80 Mode						
CH42	5210	0.43	11.62	12.05	23.98	Pass
TX 802.11 ax80 Mode						
CH42	5210	0.91	11.69	12.60	23.98	Pass

5745-5825 MHz

Test Channel	Frequency	Correction Factor	Maximum output power	Total Power	LIMIT	Result
	(MHz)	(dB)	(dBm)	(dBm)	dBm	
TX 802.11a Mode						
CH149	5745	0.12	13.16	13.28	30	Pass
CH157	5785	0.12	13.54	13.66	30	Pass
CH165	5825	0.12	13.44	13.56	30	Pass
TX 802.11 n20 Mode						
CH149	5745	0.18	13.20	13.38	30	Pass
CH157	5785	0.18	13.33	13.51	30	Pass
CH165	5825	0.18	13.23	13.41	30	Pass
TX 802.11 ac20 Mode						
CH149	5745	0.26	13.14	13.40	30	Pass
CH157	5785	0.26	13.29	13.55	30	Pass
CH165	5825	0.26	13.28	13.54	30	Pass
TX 802.11 ax20 Mode						
CH149	5745	0.31	12.80	13.11	30	Pass
CH157	5785	0.31	13.06	13.37	30	Pass
CH165	5825	0.31	13.02	13.33	30	Pass
TX 802.11 n40 Mode						
CH151	5755	0.49	12.47	12.96	30	Pass
CH159	5795	0.49	12.45	12.94	30	Pass
TX 802.11 ac40 Mode						
CH151	5755	0.67	12.58	13.25	30	Pass
CH159	5795	0.67	12.49	13.16	30	Pass
TX 802.11 ax40 Mode						
CH151	5755	0.89	12.06	12.95	30	Pass
CH159	5795	0.89	12.09	12.98	30	Pass
TX 802.11 ac80 Mode						
CH155	5775	0.58	11.06	11.64	30	Pass
TX 802.11 ax80 Mode						
CH155	5775	0.89	11.00	11.89	30	Pass

4.5 Bandwidth & 99% Occupy Bandwidth

Test Requirement:	FCC Part15 E Section 15.407(a)(12)&15.407(e)	
Test Method:	ANSI C63.10:2013 and KDB 789033 D02 General U-NII Test Procedures New Rules v02r01	
Limit:	Measurements in the 5.725-5.85 GHz band, the minimum bandwidth 6 dB bandwidth of U-NII devices shall be at least 500KHz. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.	
Test setup:		
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 22.9°C	Humid.: 46%RH
Test voltage:	AC120	
Test results:	Pass	

Measurement Result


5180-5240MHz

Test CH	-26dB Channel Bandwidth (MHz)									Result
	802.11a	802.11n (HT20)	802.11ac (VHT20)	802.11ax (HE20)	802.11n (HT40)	802.11ac (VHT40)	802.11ax (HE40)	802.11ac (HT80)	802.11ax (HE80)	
Lowest	20.01	20.29	20.29	20.08	39.75	39.29	39.49	--	--	Pass
Middle	20.07	20.16	20.07	20.15	--	--	--	79.35	79.54	
Highest	19.87	20.01	20.19	20.42	39.69	40.21	39.68	--	--	


Test CH	99% Occupy Bandwidth (MHz)									Result
	802.11a	802.11n (HT20)	802.11ac (VHT20)	802.11ax (HE20)	802.11n (HT40)	802.11ac (VHT40)	802.11ax (HE40)	802.11ac (HT80)	802.11ax (HE80)	
Lowest	16.378	17.513	17.544	17.538	35.898	35.940	35.969	--	--	Pass
Middle	16.375	17.505	17.556	17.537	--	--	--	75.275	75.200	
Highest	16.404	17.520	17.536	17.563	35.913	35.945	35.948	--	--	

Test plot -26dB Channel Bandwidth


(802.11a) plot on channel 36




(802.11 n20) plot on channel 36




(802.11a) plot on channel 40




(802.11 n20) plot on channel 40



(802.11a) plot on channel 48




(802.11 n20) plot on channel 48




Test plot


(802.11ac20) plot on channel 36




(802.11ax20) plot on channel 36




(802.11ac20) plot on channel 40




(802.11ax20) plot on channel 40



(802.11ac20) plot on channel 48




(802.11ax20) plot on channel 48




Test plot


(802.11n40) plot on channel 38




(802.11ac40) plot on channel 38




(802.11n40) plot on channel 46




(802.11ac40) plot on channel 46




(802.11ax40) plot on channel 38




(802.11ac80) plot on channel 42



(802.11ax40) plot on channel 46




(802.11ax80) plot on channel 42




Test plot 99% Occupy Bandwidth


(802.11a) plot on channel 36




(802.11 n20) plot on channel 36




(802.11a) plot on channel 40




(802.11 n20) plot on channel 40



(802.11a) plot on channel 48




(802.11 n20) plot on channel 48




Test plot


(802.11ac20) plot on channel 36




(802.11ax20) plot on channel 36




(802.11ac20) plot on channel 40




(802.11ax20) plot on channel 40



(802.11ac20) plot on channel 48




(802.11ax20) plot on channel 48




Test plot


(802.11n40) plot on channel 38




(802.11ac40) plot on channel 38




(802.11n40) plot on channel 46




(802.11ac40) plot on channel 46




(802.11ax40) plot on channel 38




(802.11ac80) plot on channel 42



(802.11ax40) plot on channel 46



(802.11ax80) plot on channel 42




5745-5825MHz

Test CH	-6dB Channel Bandwidth (MHz)									Limit (KHz)	Result
	802.11a	802.11n (HT20)	802.11ac (VHT20)	802.11ax (HE20)	802.11n (HT40)	802.11ac (VHT40)	802.11ax (HE40)	802.11ac (HT80)	802.11ax (HE80)	>500	Pass
Lowest	15.26	15.09	15.11	15.11	35.10	35.08	35.10	--	--		
Middle	13.14	15.10	15.12	15.13	--	--	--	75.07	75.09		
Highest	15.25	15.12	15.11	15.09	35.11	35.12	35.10	--	--		


Remark: "---"is not applicable

Test plot


(802.11a) plot on channel 149




(802.11 n20) plot on channel 149




(802.11a) plot on channel 157




(802.11 n20) plot on channel 157



(802.11a) plot on channel 165




(802.11 n20) plot on channel 165




Test plot


(802.11ac20) plot on channel 149




(802.11ax20) plot on channel 149




(802.11ac20) plot on channel 157




(802.11ax20) plot on channel 157



(802.11ac20) plot on channel 165




(802.11ax20) plot on channel 165




Test plot


(802.11 n40) plot on channel 151




(802.11 ac40) plot on channel 151




(802.11 n40) plot on channel 159




(802.11 ac40) plot on channel 159




(802.11 ax40) plot on channel 151




(802.11 ac80) plot on channel 155




(802.11 ax40) plot on channel 159



(802.11 ax80) plot on channel 155



4.6 Power Spectral Density


Test Requirement:	FCC Part15 E Section 15.407(a)(1)/ (a)(3)	
Test Method:	ANSI C63.10:2013 and KDB 789033 D02 General U-NII Test Procedures New Rules v02r01	
Limit:	Frequency band (MHz)	Limit
	5150-5250	≤17dBm/1MHz for master device
		≤11dBm/1MHz for client device
	5250-5350	≤11dBm/1MHz for client device
	5470-5725	≤11dBm/1MHz for client device
	5725-5850	≤30dBm/500kHz
Test setup:		
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 22.9°C	Humid.: 46%RH
Test voltage:	AC 120V	
Test results:	Pass	

Measurement Result


5180-5240MHz

Mode	Frequency	Measured Power Density (dBm/MHz)	Correction Factor (dB)	Total Measured Power Density (dBm/MHz)	Limit (dBm/MHz)
802.11 a	5180 MHz	7.094	0.100	7.194	11
	5200 MHz	7.177	0.100	7.277	11
	5240 MHz	5.764	0.100	5.864	11
802.11 n20	5180 MHz	7.312	0.310	7.622	11
	5200 MHz	6.333	0.310	6.643	11
	5240 MHz	6.166	0.310	6.476	11
802.11 ac20	5180 MHz	6.658	0.300	6.958	11
	5200 MHz	6.292	0.300	6.592	11
	5240 MHz	6.144	0.300	6.444	11
802.11 ax20	5180 MHz	6.172	0.310	6.482	11
	5200 MHz	7.051	0.310	7.361	11
	5240 MHz	5.693	0.310	6.003	11
802.11 n40	5190 MHz	2.860	0.220	3.080	11
	5230 MHz	2.730	0.220	2.950	11
802.11 ac40	5190 MHz	3.602	0.220	3.822	11
	5230 MHz	3.698	0.220	3.918	11
802.11 ax40	5190 MHz	2.485	0.560	3.045	11
	5230 MHz	3.194	0.560	3.754	11
802.11 ac80	5210 MHz	-1.018	0.430	-0.588	11
802.11 ax80	5210 MHz	-1.279	0.910	-0.369	11


(802.11a) PSD plot on channel 36




(802.11n20) PSD plot on channel 36




(802.11a) PSD plot on channel 40




(802.11n20) PSD plot on channel 40




(802.11a) PSD plot on channel 48




(802.11n20) PSD plot on channel 48




(802.11ac20) PSD plot on channel 36




(802.11ax20) PSD plot on channel 36




(802.11ac20) PSD plot on channel 40




(802.11ax20) PSD plot on channel 40




(802.11ac20) PSD plot on channel 48




(802.11ax20) PSD plot on channel 48




(802.11n40) PSD plot on channel 38



(802.11ac40) PSD plot on channel 38



(802.11n40) PSD plot on channel 46



(802.11ac40) PSD plot on channel 46

