

## FCC 47 CFR MPE REPORT

INNOVATIVE TECHNOLOGY ELECTRONICS LLC

MINI STEREO SYSTEM WITH BLUETOOTH

Model Number:VS-115

Additional Model: VS-115XXXX

(Variables X can be 0-9, A-Z or blank, which means appearance colour or pattern)

FCC ID:2AFHW-VS115

|                          |                                                                     |
|--------------------------|---------------------------------------------------------------------|
| Prepared for:            | INNOVATIVE TECHNOLOGY ELECTRONICS LLC                               |
|                          | 1 CHANNEL DRIVE,PORT WASHINGTON,New York 11050,United States.       |
|                          |                                                                     |
| Prepared By:             | EST Technology Co., Ltd.                                            |
|                          | Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China |
| Tel: 86-769-83081888-808 |                                                                     |

|                 |                         |
|-----------------|-------------------------|
| Report Number:  | ESTE-R1902038           |
| Date of Test:   | Jan. 28 ~ Feb. 26, 2019 |
| Date of Report: | Feb. 28, 2019           |

## Maximum Permissible Exposure

### 1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### (a)、Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   2 ,   H   2 or S (minutes) |
|-----------------------|----------------------------------|-----------------------------------|-----------------------------------------|--------------------------------------------------|
| 0.3-3.0               | 614                              | 1.63                              | (100)*                                  | 6                                                |
| 3.0-30                | 1842/f                           | 4.89/f                            | (900/f)*                                | 6                                                |
| 30-300                | 61.4                             | 0.163                             | 1.0                                     | 6                                                |
| 300-1500              |                                  |                                   | F/300                                   | 6                                                |
| 1500-10000            |                                  |                                   | 5                                       | 6                                                |

#### (b)、Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   2 ,   H   2 or S (minutes) |
|-----------------------|----------------------------------|-----------------------------------|-----------------------------------------|--------------------------------------------------|
| 0.3-1.34              | 614                              | 1.63                              | (100)*                                  | 30                                               |
| 1.34-30               | 824/f                            | 2.19/f                            | (180/f)*                                | 30                                               |
| 30-300                | 27.5                             | 0.073                             | 0.2                                     | 30                                               |
| 300-1500              |                                  |                                   | F/1500                                  | 30                                               |
| 1500-10000            |                                  |                                   | 1.0                                     | 30                                               |

Note: f=frequency in MHz; \*Plane-wave equivalent power density

### 2、MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5} / d \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

**3、Conducted Power Result**

| Mode   | Frequency<br>(MHz) | Peak output power<br>(dBm) | Peak output power<br>(mW) | Target<br>power<br>( dBm ) | Antenna gain |          |
|--------|--------------------|----------------------------|---------------------------|----------------------------|--------------|----------|
|        |                    |                            |                           |                            | (dBi)        | (Linear) |
| GFSK   | 2402               | -3.827                     | 0.414                     | $-4 \pm 1$                 | 0            | 1        |
|        | 2441               | -4.295                     | 0.372                     | $-5 \pm 1$                 | 0            | 1        |
|        | 2480               | -4.647                     | 0.343                     | $-5 \pm 1$                 | 0            | 1        |
| 8-DPSK | 2402               | -3.890                     | 0.408                     | $-4 \pm 1$                 | 0            | 1        |
|        | 2441               | -4.349                     | 0.367                     | $-5 \pm 1$                 | 0            | 1        |
|        | 2480               | -4.718                     | 0.337                     | $-5 \pm 1$                 | 0            | 1        |

**4、Calculated Result and Limit**

| Mode   | Target<br>power<br>( dBm ) | Antenna gain |          | Power<br>Density<br>(S)<br>(mW<br>/cm <sup>2</sup> ) | Limited<br>of<br>Power<br>Density<br>(S)<br>(mW<br>/cm <sup>2</sup> ) | Test<br>Result |
|--------|----------------------------|--------------|----------|------------------------------------------------------|-----------------------------------------------------------------------|----------------|
|        |                            | (dBi)        | (Linear) |                                                      |                                                                       |                |
| GFSK   | -3                         | 0            | 1        | <b>0.00010</b>                                       | 1                                                                     | Compiles       |
| 8-DPSK | -3                         | 0            | 1        | <b>0.00010</b>                                       | 1                                                                     | Compiles       |