


# TEST REPORT

**Applicant:** COOSEA GROUP (HK) COMPANY LIMITED  
**Address:** UNIT 5-6 16/F MULTIFIELD PLAZA 3-7A PRAT  
AVENUE TSIMSHATSUI KL  
**Equipment Type:** SmartPhone  
**Model Name:** SP545C  
**Brand Name:** Artia  
**FCC ID:** 2A28USL003AS  
**Test Standard:** FCC 47 CFR Part 2.1093  
(refer section 3.1)  
**Maximum SAR:** Head (1 g@0mm): 1.16 W/kg  
Body-worn (1 g@15mm): 0.59 W/kg  
Hotspot (1 g@10mm): 1.19 W/kg  
**Sample Arrival Date:** Nov. 25, 2024  
**Test Date:** Dec. 06, 2024 - Dec. 12, 2024  
**Date of Issue:** Dec. 18, 2024

**ISSUED BY:**

Shenzhen BALUN Technology Co., Ltd.

**Tested by:** Xiong Lining**Checked by:** Xu Rui**Approved by:** Tolan Tu  
(Testing Director)

**Revision History**

| Version        | Issue Date           | Revisions Content    |
|----------------|----------------------|----------------------|
| <u>Rev. 01</u> | <u>Dec. 18, 2024</u> | <u>Initial Issue</u> |

**TABLE OF CONTENTS**

|     |                                                         |    |
|-----|---------------------------------------------------------|----|
| 1   | GENERAL INFORMATION.....                                | 5  |
| 1.1 | Test Laboratory .....                                   | 5  |
| 1.2 | Test Location .....                                     | 5  |
| 1.3 | Test Environment Condition.....                         | 5  |
| 2   | PRODUCT INFORMATION .....                               | 6  |
| 2.1 | Applicant Information .....                             | 6  |
| 2.2 | Manufacturer Information.....                           | 6  |
| 2.3 | General Description for Equipment under Test (EUT)..... | 6  |
| 2.4 | Ancillary Equipment.....                                | 6  |
| 2.5 | Technical Information .....                             | 7  |
| 3   | SUMMARY OF TEST RESULT .....                            | 9  |
| 3.1 | Test Standards .....                                    | 9  |
| 3.2 | Device Category and SAR Limit .....                     | 10 |
| 3.3 | Test Result Summary .....                               | 11 |
| 3.4 | Test Uncertainty .....                                  | 12 |
| 4   | MEASUREMENT SYSTEM .....                                | 13 |
| 4.1 | Specific Absorption Rate (SAR) Definition .....         | 13 |
| 4.2 | DASY SAR System .....                                   | 14 |
| 5   | SYSTEM VERIFICATION .....                               | 21 |
| 5.1 | Purpose of System Check .....                           | 21 |
| 5.2 | System Check Setup .....                                | 21 |
| 6   | TEST POSITION CONFIGURATIONS .....                      | 22 |
| 6.1 | Head Exposure Conditions .....                          | 22 |
| 6.2 | Body-worn Position Conditions .....                     | 24 |

|       |                                                 |    |
|-------|-------------------------------------------------|----|
| 6.3   | Hotspot Mode Exposure Position Conditions ..... | 25 |
| 7     | MEASUREMENT PROCEDURE .....                     | 26 |
| 7.1   | Measurement Process Diagram .....               | 26 |
| 7.2   | SAR Scan General Requirement .....              | 27 |
| 7.3   | Measurement Procedure .....                     | 28 |
| 7.4   | Area & Zoom Scan Procedure .....                | 28 |
| 7.5   | Area & Zoom Scan Procedure .....                | 29 |
| 8     | CONDUCTED RF OUPUT POWER .....                  | 31 |
| 8.1   | GSM .....                                       | 31 |
| 8.2   | WCDMA .....                                     | 31 |
| 8.3   | LTE.....                                        | 31 |
| 8.4   | WIFI.....                                       | 32 |
| 8.5   | Bluetooth .....                                 | 35 |
| 8.6   | Power Reduction List.....                       | 36 |
| 9     | TEST EXCLUSION CONSIDERATION .....              | 37 |
| 10    | TEST RESULT .....                               | 38 |
| 10.1  | GSM 850 .....                                   | 38 |
| 10.2  | GSM 1900 .....                                  | 39 |
| 10.3  | WCDMA Band 2 .....                              | 40 |
| 10.4  | WCDMA Band 4 .....                              | 41 |
| 10.5  | WCDMA Band 5 .....                              | 42 |
| 10.6  | LTE Band 12 (10MHz Bandwidth).....              | 43 |
| 10.7  | LTE Band 25 (20MHz Bandwidth).....              | 44 |
| 10.8  | LTE Band 26 (15MHz Bandwidth).....              | 45 |
| 10.9  | LTE Band 66 (20MHz Bandwidth).....              | 46 |
| 10.10 | LTE Band 71 (20MHz Bandwidth).....              | 47 |
| 10.11 | WIFI 2.4GHz.....                                | 48 |
| 10.13 | Bluetooth .....                                 | 49 |
| 11    | SAR Measurement Variability .....               | 50 |
| 12    | SIMULTANEOUS TRANSMISSION.....                  | 51 |

|         |                                               |     |
|---------|-----------------------------------------------|-----|
| 12.1    | Simultaneous Transmission Mode Consider ..... | 51  |
| 12.2    | Sum SAR of Simultaneous Transmission .....    | 52  |
| 13      | TEST EQUIPMENTS LIST .....                    | 57  |
| ANNEX A | SIMULATING LIQUID VERIFICATION RESULT .....   | 58  |
| ANNEX B | SYSTEM CHECK RESULT .....                     | 59  |
| ANNEX C | TEST DATA.....                                | 66  |
| ANNEX D | EUT EXTERNAL PHOTOS.....                      | 102 |
| ANNEX E | SAR TEST SETUP PHOTOS .....                   | 102 |
| ANNEX F | CALIBRATION REPORT .....                      | 102 |

## 1 GENERAL INFORMATION

### 1.1 Test Laboratory

|              |                                                                                                                              |
|--------------|------------------------------------------------------------------------------------------------------------------------------|
| Name         | Shenzhen BALUN Technology Co., Ltd.                                                                                          |
| Address      | Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China |
| Phone Number | +86 755 6685 0100                                                                                                            |

### 1.2 Test Location

|                           |                                                                                                                                                                                                                                    |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name                      | Shenzhen BALUN Technology Co., Ltd.                                                                                                                                                                                                |
| Location                  | <input type="checkbox"/> Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China                                                                              |
|                           | <input checked="" type="checkbox"/> 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China |
| Accreditation Certificate | The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.                                                                                                   |

### 1.3 Test Environment Condition

|                           |              |
|---------------------------|--------------|
| Ambient Temperature       | 18°C to 25°C |
| Ambient Relative Humidity | 30% to 70%   |

## 2 PRODUCT INFORMATION

### 2.1 Applicant Information

|           |                                                                   |
|-----------|-------------------------------------------------------------------|
| Applicant | COOSEA GROUP (HK) COMPANY LIMITED                                 |
| Address   | UNIT 5-6 16/F MULTIFIELD PLAZA 3-7A PRAT AVENUE<br>TSIMSHATSUI KL |

### 2.2 Manufacturer Information

|              |                                                                   |
|--------------|-------------------------------------------------------------------|
| Manufacturer | COOSEA GROUP (HK) COMPANY LIMITED                                 |
| Address      | UNIT 5-6 16/F MULTIFIELD PLAZA 3-7A PRAT AVENUE<br>TSIMSHATSUI KL |

### 2.3 General Description for Equipment under Test (EUT)

|                                           |                   |
|-------------------------------------------|-------------------|
| EUT Name                                  | SmartPhone        |
| Model Name Under Test                     | SP545C            |
| Series Model Name                         | N/A               |
| Description of Model name differentiation | N/A               |
| Hardware Version                          | 1.0               |
| Software Version                          | SP545C10004       |
| Dimensions (Approx.)                      | 150.7x73.7x10.6mm |
| Weight (Approx.)                          | N/A               |

### 2.4 Ancillary Equipment

|                       |                 |                                         |
|-----------------------|-----------------|-----------------------------------------|
| Ancillary Equipment 1 | Battery         |                                         |
|                       | Brand Name      | N/A                                     |
|                       | Model No.       | BL-A86CT                                |
|                       | Serial No.      | N/A                                     |
|                       | Capacity        | 2000 mAh                                |
|                       | Nominal Voltage | 3.7 V                                   |
|                       | Manufacturer    | Shenzhen Aerospace Electronic Co., Ltd. |

## 2.5 Technical Information

|                                                                                                                                                                                                                                                            |                                                                                                                                                                                             |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network and Wireless connectivity                                                                                                                                                                                                                          | 2G Network GSM/GPRS/EDGE 850/1900<br>3G Network WCDMA/HSDPA/HSUPA Band 2/4/5<br>4G Network FDD LTE Band 2/4/5/12/17/25/26/66/71<br>Bluetooth (BR+EDR+BLE)<br>WIFI 802.11b, 802.11g, 802.11n |
| <b>Note:</b><br>The EUT is a mobile phone, which supports dual SIM card under the same transceiver. Each SIM supports GSM, WCDMA and LTE, and both SIM share the same transmitting electro circuit, NV parameters, so only SIM1 was tested in this report. |                                                                                                                                                                                             |

The requirement for the following technical information of the EUT was tested in this report:

|                                                                                                                                                           |                                                                     |                                              |                     |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------|----------------------------------------------|---------------------|
| Operating Mode                                                                                                                                            | GSM, WCDMA, LTE, 2.4G WIFI, Bluetooth                               |                                              |                     |
| Frequency Range                                                                                                                                           | GSM 850                                                             | TX: 824 ~ 849 MHz                            | RX: 869 ~ 894 MHz   |
|                                                                                                                                                           | GSM 1900                                                            | TX: 1850 ~ 1910 MHz                          | RX: 1930 ~ 1990 MHz |
|                                                                                                                                                           | WCDMA Band 2                                                        | TX: 1850 ~ 1910 MHz                          | RX: 1930 ~ 1990 MHz |
|                                                                                                                                                           | WCDMA Band 4                                                        | TX: 1710 ~ 1755 MHz                          | RX: 2110 ~ 2155 MHz |
|                                                                                                                                                           | WCDMA Band 5                                                        | TX: 824 ~ 849 MHz                            | RX: 869 ~ 894 MHz   |
|                                                                                                                                                           | LTE Band 2                                                          | TX: 1850 ~ 1910 MHz                          | RX: 1930 ~ 1990 MHz |
|                                                                                                                                                           | LTE Band 4                                                          | TX: 1710 ~ 1755 MHz                          | RX: 2110 ~ 2155 MHz |
|                                                                                                                                                           | LTE Band 5                                                          | TX: 824 ~ 849 MHz                            | RX: 869 ~ 894 MHz   |
|                                                                                                                                                           | LTE Band 12                                                         | TX: 699 ~ 716 MHz                            | RX: 729 ~ 746 MHz   |
|                                                                                                                                                           | LTE Band 17                                                         | TX: 704 ~ 716 MHz                            | RX: 734 ~ 746 MHz   |
|                                                                                                                                                           | LTE Band 25                                                         | TX: 1850 ~ 1915 MHz                          | RX: 1930 ~ 1995 MHz |
|                                                                                                                                                           | LTE Band 26                                                         | TX: 814~ 849 MHz                             | RX: 859 ~ 894 MHz   |
|                                                                                                                                                           | LTE Band 66                                                         | TX: 1710 ~ 1780 MHz                          | RX: 2110 ~ 2180 MHz |
|                                                                                                                                                           | LTE Band 71                                                         | TX: 663 ~ 698 MHz                            | RX: 617~ 652 MHz    |
|                                                                                                                                                           | 802.11b/g /n(HT20)                                                  | 2412 ~ 2462 MHz                              |                     |
|                                                                                                                                                           | Bluetooth                                                           | 2402 ~ 2480 MHz                              |                     |
| Antenna Type                                                                                                                                              | WWAN: PIFA Antenna<br>WIFI: PIFA Antenna<br>Bluetooth: PIFA Antenna |                                              |                     |
| DTM                                                                                                                                                       | N/A                                                                 |                                              |                     |
| Hotspot Function                                                                                                                                          | Support                                                             |                                              |                     |
| Power Reduction                                                                                                                                           | Support                                                             |                                              |                     |
| Exposure Category                                                                                                                                         | General Population/Uncontrolled exposure                            |                                              |                     |
| Product Type                                                                                                                                              | Portable Device                                                     |                                              |                     |
| EUT Type                                                                                                                                                  | <input checked="" type="checkbox"/> Production unit                 | <input type="checkbox"/> Identical prototype |                     |
| Note:<br>1. The device utilizes independent power reduction mechanisms for SAR compliance for the 2/3/4G transmitter for held-to-ear exposure conditions. |                                                                     |                                              |                     |

2. The device utilizes independent power reduction mechanisms for SAR compliance for the 2/3/4G transmitter for near to body exposure conditions.
3. The reduction power details please refer section 8.6.

### 3 SUMMARY OF TEST RESULT

#### 3.1 Test Standards

| No. | Identity                 | Document Title                                                                                                                                                                  |
|-----|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1   | 47 CFR Part 2.1093       | Radiofrequency radiation exposure evaluation: portable devices                                                                                                                  |
| 2   | ANSI C95.1-1992          | IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz                                                      |
| 3   | IEEE Std. 1528-2013      | IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate(SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques |
| 4   | KDB 447498 D04 v01       | 447498 D04 Interim General RF Exposure Guidance v01                                                                                                                             |
| 5   | KDB 941225 D01<br>v03r01 | 3G SAR MEAUREMENT PROCEDURES                                                                                                                                                    |
| 6   | KDB 941225 D05<br>v02r05 | SAR Evaluation Considerations for LTE Devices                                                                                                                                   |
| 7   | KDB 941225 D06<br>v02r01 | SAR EVALUATION PROCEDURES FOR PORTABLE DEVICES WITH WIRELESS ROUTER CAPABILITIES                                                                                                |
| 8   | KDB 865664 D01<br>v01r04 | SAR Measurement 100 MHz to 6 GHz                                                                                                                                                |
| 9   | KDB 865664 D02<br>v01r02 | RF Exposure Reporting                                                                                                                                                           |
| 10  | KDB 648474<br>D04 v01r03 | SAR EVALUATION CONSIDERATIONS FOR WIRELESS HANDSETS                                                                                                                             |
| 11  | KDB 248227 D01<br>v02r02 | SAR GUIDANCE FOR IEEE 802.11 (Wi-Fi) TRANSMITTERS                                                                                                                               |

### 3.2 Device Category and SAR Limit

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user.

Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

Table of Exposure Limits:

| Body Position                                                                       | SAR Value (W/Kg)                             |                                     |
|-------------------------------------------------------------------------------------|----------------------------------------------|-------------------------------------|
|                                                                                     | General Population/<br>Uncontrolled Exposure | Occupational/<br>ControlledExposure |
| Whole-Body SAR<br>(averaged over the entire body)                                   | 0.08                                         | 0.4                                 |
| Partial-Body SAR<br>(averaged over any 1 gram of tissue)                            | 1.60                                         | 8.0                                 |
| SAR for hands, wrists, feet and<br>ankles<br>(averaged over any 10 grams of tissue) | 4.0                                          | 20.0                                |

**NOTE:**

**General Population/Uncontrolled Exposure:** Locations where there is the exposure of individuals who have no knowledge or control of their exposure. General population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

**Occupational/Controlled Exposure:** Locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

### 3.3 Test Result Summary

#### 3.3.1 Highest SAR Values

| Equipment Class | Band         | Maximum Scaled SAR (W/kg) |                  |                | Maximum Report SAR (W/kg) |                  |                |
|-----------------|--------------|---------------------------|------------------|----------------|---------------------------|------------------|----------------|
|                 |              | Head (0mm)                | Body-worn (15mm) | Hotspot (10mm) | Head (0mm)                | Body-worn (15mm) | Hotspot (10mm) |
|                 |              | 1g SAR                    |                  |                | 1g SAR                    |                  |                |
| PCE             | GSM 850      | 0.35                      | 0.35             | 0.35           | 1.16                      | 0.59             | 1.19           |
|                 | GSM 1900     | 0.16                      | 0.59             | 1.19           |                           |                  |                |
|                 | WCDMA Band 2 | 0.10                      | 0.44             | 0.90           |                           |                  |                |
|                 | WCDMA Band 4 | 0.13                      | 0.22             | 0.32           |                           |                  |                |
|                 | WCDMA Band 5 | 0.12                      | 0.15             | 0.17           |                           |                  |                |
|                 | LTE Band 12  | 0.08                      | 0.12             | 0.13           |                           |                  |                |
|                 | LTE Band 25  | 0.09                      | 0.27             | 0.43           |                           |                  |                |
|                 | LTE Band 26  | 0.11                      | 0.14             | 0.15           |                           |                  |                |
|                 | LTE Band 66  | 0.14                      | 0.15             | 0.28           |                           |                  |                |
|                 | LTE Band 71  | 0.13                      | 0.11             | 0.10           |                           |                  |                |
| DTS             | 2.4G WIFI    | 1.16                      | 0.34             | 0.36           |                           |                  |                |
| DSS             | Bluetooth    | 0.22                      | 0.01             | 0.04           |                           |                  |                |
| Limit (W/kg)    |              | 1.6                       |                  |                | 1.6                       |                  |                |
| Verdict         |              | PASS                      |                  |                |                           |                  |                |

Note: This device supports both LTE Band 2/4/5/17 and Band 25/66/26/12. Since the supported frequency span for LTE Band 2/4/5/17 falls completely within the supports frequency span for LTE Band 25/66/26/12, both LTE bands have the same target power, and both LTE bands share the same transmission path; therefore, SAR was only assessed for LTE Band 25/66/26/12.

#### 3.3.2 Highest Simultaneous Transmission SAR Values

| Equipment Class | Maximum Scaled SAR (W/kg) |                     |                   |
|-----------------|---------------------------|---------------------|-------------------|
|                 | Head 1g (0mm)             | Body-worn 1g (15mm) | Hotspot 1g (10mm) |
| PCE             | 1.48                      | 0.93                | <b>1.55</b>       |
| DTS             | 1.48                      | 0.93                | 1.55              |
| DSS             | 0.45                      | 0.60                | 1.22              |
| Limit (W/Kg)    | 1.60                      |                     |                   |
| Verdict         | Pass                      |                     |                   |

Note: The highest simultaneous SAR please refer section 12.2

### 3.4 Test Uncertainty

According to KDB 865664 D01, When the highest measured 1 g SAR within a frequency band is  $< 1.5$  W/kg, the extensive SAR measurement uncertainty analysis is not required in SAR reports submitted for equipment approval.

The maximum 1 g SAR for the EUT in this report is 1.19 W/kg, which is lower than 1.5 W/kg, so the extensive SAR measurement uncertainty analysis is not required in this report.

## 4 MEASUREMENT SYSTEM

### 4.1 Specific Absorption Rate (SAR) Definition

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by


$$\text{SAR} = \frac{\sigma E^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,

$\rho$  is the mass density of the tissue and E is the RMS electrical field strength.

## 4.2 DASY SAR System

### 4.2.1 DASY SAR System Diagram



The DASY system for performing compliance tests consists of the following items:

1. A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
2. A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
3. A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
4. A unit to operate the optical surface detector which is connected to the EOC.
5. The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.
6. The DASY measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.
7. DASY5 software and SEMCAD data evaluation software.
8. Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
9. The generic twin phantom enabling the testing of left-hand and right-hand usage.
10. The device holder for handheld mobile phones.
11. Tissue simulating liquid mixed according to the given recipes.
12. System validation dipoles allowing to validate the proper functioning of the system.

#### 4.2.2 Robot

The Dasy SAR system uses the high precision robots. Symmetrical design with triangular core Built-in optical fiber for surface detection system For the 6-axis controller system, Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents). The robot series have many features that are important for our application:



- High precision  
(repeatability  $\pm 0.02$  mm)
- High reliability  
(industrial design)
- Low maintenance costs  
(virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements  
(brush less synchron motors; no stepper motors)
- Low ELF interference  
(motor control \_elds shielded via the closed metallic construction shields)

### 4.2.3 E-Field Probe

The probe is specially designed and calibrated for use in liquids with high permittivities for the measurements the Specific Dosimetric E-Field Probe EX3DV4-SN:7510 with following specifications is used.

|               |                                                                                                                                                                                                                     |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Construction  | Symmetrical design with triangular core Built-in optical fiber for surface detection system<br>Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., glycolether) |
| Calibration   | ISO/IEC 17025 calibration service available                                                                                                                                                                         |
| Frequency     | 4 MHz to 10 GHz; Linearity: $\pm 0.2$ dB                                                                                                                                                                            |
| Directivity   | $\pm 0.2$ dB in HSL (rotation around probe axis) ; $\pm 0.4$ dB in HSL (rotation normal to probe axis)                                                                                                              |
| Dynamic range | 5 $\mu$ W/g to > 100 mW/g; Linearity: $\pm 0.2$ dB                                                                                                                                                                  |
| Dimensions    | Overall length: 337 mm (Tip: 9 mm) Tip diameter: 2.5 mm (Body: 10 mm) Distance from probe tip to dipole centers: 1.0 mm                                                                                             |
| Application   | General dosimetry up to 3 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms (EX3DV4)                                                                                              |



#### E-Field Probe Calibration Process

Probe calibration is realized, in compliance with IEC/IEEE 62209-1528 and IEEE 1528 std, with CALISAR, Antennessa proprietary calibration system. The calibration is performed with the IEC/IEEE 62209-1528 annexe technique using reference guide at the five frequencies.

#### 4.2.4 Data Acquisition Electronics


The data acquisition electronics (DAE) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converte and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.



- Input Impedance: 200M $\Omega$ m
- The Inputs: Symmetrical and Floating
- Commom Mode Rejection: Above 80dB

#### 4.2.5 Phantoms

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.



- Left head
- Right head
- Flat phantom

**Photo of Phantom SN1859**



| Serial Number | Material                           | Length | Height |
|---------------|------------------------------------|--------|--------|
| SN 1859 SAM   | Vinylester, glass fiber reinforced | 1000   | 500    |

#### 4.2.6 Device Holder


The DASY device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of  $65^\circ$ . The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. This device holder is used for standard mobile phones or PDA"s only. If necessary an additional support of polystyrene material is used. Larger DUT"s (e.g. notebooks) cannot be tested using this device holder. Instead a support of bigger polystyrene cubes and thin polystyrene plates is used to position the DUT in all relevant positions to find and measure spots with maximum SAR values. Therefore those devices are normally only tested at the flat part of the SAM.



The positioning system allows obtaining cheek and tilting position with a very good accuracy. Incompliance with CENELEC, the tilt angle uncertainty is lower than  $1^\circ$ .

#### 4.2.7 Simulating Liquid

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5%.

**Head Liquid Depth****Body Liquid Depth**

The following table gives the recipes for tissue simulating liquid.

| TSL           | Manufacturer / Model  | Freq Range (MHz) | Main Ingredients                                                                                         |
|---------------|-----------------------|------------------|----------------------------------------------------------------------------------------------------------|
| Head WideBand | SPEAG HBBL600-10000V6 | 600-10000        | Ethanediol, Sodium petroleum sulfonate, Hexylene Glycol / 2-Methyl-pentane-2.4-diol, Alkoxylated alcohol |


## 5 SYSTEM VERIFICATION

### 5.1 Purpose of System Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

### 5.2 System Check Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



## 6 TEST POSITION CONFIGURATIONS


According to KDB 648474 D04 Handset, handsets are tested for SAR compliance in head, body-worn accessory and other use configurations described in the following subsections.

### 6.1 Head Exposure Conditions

Head exposure is limited to next to the ear voice mode operations. Head SAR compliance is tested according to the test positions defined in IEEE Std 1528-2013 using the SAM phantom illustrated as below.


#### 6.1.1 Two Imaginary Lines on the Handset

- The vertical center line passes through two points on the front side of the handset - the midpoint of the width  $w_t$  of the handset at the level of the acoustic output, and the midpoint of the width  $w_b$  of the bottom of the handset.
- The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical center line is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.



### 6.1.2 Cheek Position

- (a) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- (b) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost.



### 6.1.3 Tilted Position

- (a) To position the device in the “cheek” position described above.
- (b) While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost.




## 6.2 Body-worn Position Conditions

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB 447498 are used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode. When the reported SAR for a body-worn accessory.


Body-worn accessories that do not contain metallic or conductive components may be tested according to worst-case exposure configurations, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics. All body-worn accessories containing metallic components are tested in conjunction with the host device.

Body-worn accessory SAR compliance is based on a single minimum test separation distance for all wireless and operating modes applicable to each body-worn accessory used by the host, and according to the relevant voice and/or data mode transmissions and operations. If a body-worn accessory supports voice only operations in its normal and expected use conditions, testing of data mode for body-worn compliance is not required. A conservative minimum test separation distance for supporting off-the-shelf body-worn accessories that may be acquired by users of consumer handsets is used to test for body-worn accessory SAR compliance. This distance is determined by the handset manufacturer, according to the requirements of Supplement C 01-01. Devices that are designed to operate on the body of users using lanyards and straps, or without requiring additional body-worn accessories, will be tested using a conservative minimum test separation distance  $\leq 5$  mm to support compliance.




### 6.3 Hotspot Mode Exposure Position Conditions

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing functions, the relevant hand and body exposure conditions are tested according to the hotspot SAR procedures in KDB 941225. A test separation distance of 10 mm is required between the phantom and all surfaces and edges with a transmitting antenna located within 25 mm from that surface or edge. When the form factor of a handset is smaller than 9 cm x 5 cm, a test separation distance of 5 mm (instead of 10 mm) is required for testing hotspot mode. When the separation distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).



## 7 MEASUREMENT PROCEDURE

### 7.1 Measurement Process Diagram



## 7.2 SAR Scan General Requirement

Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1 g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2013.

|                                                                                                        |                           |                                                                | ≤3GHz                                                                                                                                                                                                                                                             | >3GHz                                              |
|--------------------------------------------------------------------------------------------------------|---------------------------|----------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------|
| Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface |                           |                                                                | 5±1 mm                                                                                                                                                                                                                                                            | $\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm |
| Maximum probe angle from probe axis to phantom surface normal at the measurement location              |                           |                                                                | 30°±1°                                                                                                                                                                                                                                                            | 20°±1°                                             |
| Maximum area scan spatial resolution: Δx Area , Δy Area                                                |                           |                                                                | ≤ 2 GHz: ≤ 15 mm<br>2 – 3 GHz: ≤ 12 mm                                                                                                                                                                                                                            | 3–4 GHz: ≤ 12 mm<br>4 – 6 GHz: ≤ 10 mm             |
|                                                                                                        |                           |                                                                | When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device. |                                                    |
| Maximum zoom scan spatial resolution: Δx Zoom , Δy Zoom                                                |                           |                                                                | ≤ 2 GHz: ≤ 8 mm<br>2 – 3 GHz: ≤ 5 mm*                                                                                                                                                                                                                             | 3–4 GHz: ≤ 5 mm*<br>4 – 6 GHz: ≤ 4 mm*             |
| Maximum zoom scan spatial resolution, normal to phantom surface                                        | uniform grid: Δz Zoom (n) |                                                                | ≤ 5 mm                                                                                                                                                                                                                                                            | 3–4 GHz: ≤ 4 mm                                    |
|                                                                                                        |                           |                                                                |                                                                                                                                                                                                                                                                   | 4–5 GHz: ≤ 3 mm                                    |
|                                                                                                        |                           |                                                                |                                                                                                                                                                                                                                                                   | 5–6 GHz: ≤ 2 mm                                    |
|                                                                                                        | graded grid               | Δz Zoom (1): between 1st two points closest to phantom surface | ≤ 4 mm                                                                                                                                                                                                                                                            | 3–4 GHz: ≤ 3 mm                                    |
|                                                                                                        |                           |                                                                |                                                                                                                                                                                                                                                                   | 4–5 GHz: ≤ 2.5 mm                                  |
|                                                                                                        |                           | Δz Zoom (n>1): between subsequent points                       | ≤ 1.5·Δz Zoom (n-1)                                                                                                                                                                                                                                               |                                                    |
|                                                                                                        |                           |                                                                | Minimum zoom scan volume                                                                                                                                                                                                                                          | x, y, z                                            |
| 4–5 GHz: ≥ 25 mm                                                                                       |                           |                                                                |                                                                                                                                                                                                                                                                   |                                                    |
| 5–6 GHz: ≥ 22 mm                                                                                       |                           |                                                                |                                                                                                                                                                                                                                                                   |                                                    |

### Note:

1.  $\delta$  is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.
2. \* When zoom scan is required and the reported SAR from the area scan based 1 g SAR estimation procedures of KDB 447498 is  $\leq 1.4$  W/kg,  $\leq 8$  mm,  $\leq 7$  mm and  $\leq 5$  mm zoom scan resolution may be applied, respectively, for 2 GHz to 3GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

### 7.3 Measurement Procedure

The following steps are used for each test position

- a. Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- b. Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- c. Measurement of the SAR distribution with a grid of 8 to 16mm \* 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- d. Around this point, a cube of 30 \* 30 \* 30 mm or 32 \* 32 \* 32 mm is assessed by measuring 5 or 8 \* 5 or 8\*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.


### 7.4 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01v01r04 quoted below.


When the 1 g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

## 7.5 Area & Zoom Scan Procedure

During TDD-LTE SAR testing, the EUT was commanded to transmit on maximum output power and maximum transmitting bandwidth. The uplink and downlink slot configuration as below in one radio frame.



According to 3GPP Per 3GPP TS 36.211. Each radio frame of length ( $T_f = 307200 \cdot T_s = 10\text{ms}$ ) of two half-frames of length ( $153600 \cdot T_s = 5\text{ms}$ ). Each half-frame consists of five sub-frames of length ( $30720 \cdot T_s = 1\text{ms}$ )



And the special sub-frame with the three fields DwPTS, GP and UpPTS.

The length of DwPTS and UpPTS is given by below table subject to the total length of DwPTS, GP and UpPTS being equal to  $30720 \cdot T_s = 1\text{ms}$ .

### Configuration of special sub-frame (lengths of DwPTS/GP/UpPTS)

| Special sub-frame configuration | Normal cyclic prefix in downlink |                                |                                  | Extended cyclic prefix in downlink |                                |                                  |
|---------------------------------|----------------------------------|--------------------------------|----------------------------------|------------------------------------|--------------------------------|----------------------------------|
|                                 | DwPTS                            | UpPTS                          |                                  | DwPTS                              | UpPTS                          |                                  |
|                                 |                                  | Normal cyclic prefix in uplink | Extended cyclic prefix in uplink |                                    | Normal cyclic prefix in uplink | Extended cyclic prefix in uplink |
| 0                               | $6592 \cdot T_s$                 | $2192 \cdot T_s$               | $2560 \cdot T_s$                 | $7680 \cdot T_s$                   | $2192 \cdot T_s$               | $2560 \cdot T_s$                 |
| 1                               | $19760 \cdot T_s$                |                                |                                  | $20480 \cdot T_s$                  |                                |                                  |
| 2                               | $21592 \cdot T_s$                |                                |                                  | $23040 \cdot T_s$                  |                                |                                  |
| 3                               | $24144 \cdot T_s$                |                                |                                  | $25600 \cdot T_s$                  |                                |                                  |
| 4                               | $26336 \cdot T_s$                | $4384 \cdot T_s$               | $5120 \cdot T_s$                 | $7680 \cdot T_s$                   | $2560 \cdot T_s$               | $5120 \cdot T_s$                 |
| 5                               | $6592 \cdot T_s$                 |                                |                                  | $20480 \cdot T_s$                  |                                |                                  |
| 6                               | $19760 \cdot T_s$                |                                |                                  | $23040 \cdot T_s$                  |                                |                                  |
| 7                               | $21592 \cdot T_s$                |                                |                                  | $12800 \cdot T_s$                  | -                              | -                                |
| 8                               | $24144 \cdot T_s$                |                                |                                  | -                                  |                                |                                  |
| 9                               | $13168 \cdot T_s$                |                                |                                  | -                                  | -                              | -                                |

For special sub-frame uplink time we used the largest cyclic prefix for duty cycle calculate;

Maximum uplink time of one special sub-frame=(largest cyclic prefix)/(one sub-frame of length)\* time of one sub-frame= $5120 \cdot T_s / 30720 \cdot T_s \cdot 1\text{ms} = 0.167\text{ms}$

One radio frame with 6 uplink sub-frames and two special sub-frame,

there for the maximum Uplink time in one radio frame is:  **$6 \cdot 1\text{ ms} + 2 \cdot 0.167\text{ ms} = 6.334\text{ms}$**

So, the duty cycle for TDD-LTE is:  **$6.334\text{ms} / 10\text{ms} = 1: 1.58$**

## **8 CONDUCTED RF OUPUT POWER**

### **8.1 GSM**

Please refer the document “BL-SH24B0867-AP Power List.pdf”.

### **8.2 WCDMA**

Please refer the document “BL-SH24B0867-AP Power List.pdf”.

### **8.3 LTE**

Please refer the document “BL-SH24B0867-AP Power List.pdf”.

## 8.4 WIFI

### 8.4.1 2.4G WIFI-Full Power

| Band (GHz) | Mode          | Channel | Freq. (MHz) | AV Power (dBm) | Tune-up Limit (dBm) | SAR Test Require. |
|------------|---------------|---------|-------------|----------------|---------------------|-------------------|
| 2.4        | 802.11b       | 1       | 2412        | <b>19.09</b>   | 20.00               | Yes               |
|            |               | 6       | 2437        | 18.84          | 20.00               | Yes               |
|            |               | 11      | 2462        | 18.86          | 20.00               | Yes               |
|            | 802.11g       | 1       | 2412        | 16.86          | 18.00               | No                |
|            |               | 6       | 2437        | 16.83          | 18.00               | No                |
|            |               | 11      | 2462        | 16.91          | 18.00               | No                |
|            | 802.11n(HT20) | 1       | 2412        | 16.85          | 18.00               | No                |
|            |               | 6       | 2437        | 17.02          | 18.00               | No                |
|            |               | 11      | 2462        | 16.49          | 17.50               | No                |

Note: When multiple channel bandwidth configurations in a frequency band have the same maximum tune-up output power, the test configuration is determined by applying the following steps sequentially.

- 1) The largest channel bandwidth configuration is selected between the multiple configurations in a frequency band with the same maximum tune-up output power.
- 2) When multiple transmission modes (802.11b/g/n) have the same maximum tune-up output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11b is chosen over 802.11g, and 802.11g chosen over 802.11n.
- 3) According KDB 247228, when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg, OFDM SAR test is not required.  
Adjusted SAR =  $0.336 * (63.10\text{mW}/100.00\text{mW}) = 0.212$  W/Kg, so 2.4G OFDM SAR test is not required.

## 8.4.2 2.4G WIFI-Level1&amp;2

| Band (GHz) | Mode          | Channel | Freq. (MHz) | AV Power (dBm) | Tune-up Limit (dBm) | SAR Test Require. |
|------------|---------------|---------|-------------|----------------|---------------------|-------------------|
| 2.4        | 802.11b       | 1       | 2412        | <b>13.28</b>   | 15.00               | Yes               |
|            |               | 6       | 2437        | 13.25          | 15.00               | Yes               |
|            |               | 11      | 2462        | 13.02          | 15.00               | Yes               |
|            | 802.11g       | 1       | 2412        | 11.25          | 13.00               | No                |
|            |               | 6       | 2437        | 11.39          | 13.00               | No                |
|            |               | 11      | 2462        | 11.27          | 13.00               | No                |
|            | 802.11n(HT20) | 1       | 2412        | 11.37          | 13.00               | No                |
|            |               | 6       | 2437        | 11.52          | 13.00               | No                |
|            |               | 11      | 2462        | 11.33          | 12.50               | No                |

Note: When multiple channel bandwidth configurations in a frequency band have the same maximum tune-up output power, the test configuration is determined by applying the following steps sequentially.

1) The largest channel bandwidth configuration is selected between the multiple configurations in a frequency band with the same maximum tune-up output power.

2) When multiple transmission modes (802.11b/g/n) have the same maximum tune-up output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11b is chosen over 802.11g, and 802.11g chosen over 802.11n.

3) According KDB 247228, when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg, OFDM SAR test is not required.

Adjusted SAR =  $1.164 * (19.95\text{mW}/31.62\text{mW}) = 0.734$  W/Kg, so 2.4G OFDM SAR test is not required.

## 8.4.3 2.4G WIFI-Level3&amp;4

| Band (GHz) | Mode          | Channel | Freq. (MHz) | AV Power (dBm) | Tune-up Limit (dBm) | SAR Test Require. |
|------------|---------------|---------|-------------|----------------|---------------------|-------------------|
| 2.4        | 802.11b       | 1       | 2412        | <b>15.28</b>   | 17.00               | Yes               |
|            |               | 6       | 2437        | 15.12          | 17.00               | Yes               |
|            |               | 11      | 2462        | 15.15          | 17.00               | Yes               |
|            | 802.11g       | 1       | 2412        | 12.96          | 15.00               | No                |
|            |               | 6       | 2437        | 13.04          | 15.00               | No                |
|            |               | 11      | 2462        | 13.06          | 15.00               | No                |
|            | 802.11n(HT20) | 1       | 2412        | 12.87          | 15.00               | No                |
|            |               | 6       | 2437        | 12.94          | 15.00               | No                |
|            |               | 11      | 2462        | 12.85          | 14.50               | No                |

Note: When multiple channel bandwidth configurations in a frequency band have the same maximum tune-up output power, the test configuration is determined by applying the following steps sequentially.

1) The largest channel bandwidth configuration is selected between the multiple configurations in a frequency band with the same maximum tune-up output power.

2) When multiple transmission modes (802.11b/g/n) have the same maximum tune-up output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11b is chosen over 802.11g, and 802.11g chosen over 802.11n.

3) According KDB 247228, when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg, OFDM SAR test is not required.

Adjusted SAR =  $0.362 * (31.62\text{mW}/50.12\text{mW}) = 0.228$  W/Kg, so 2.4G OFDM SAR test is not required.

## 8.5 Bluetooth

| Mode                                                                                                                                                                                                                                                                              | GFSK      |             |      | $\pi/4$ -DQPSK |      |      |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|-------------|------|----------------|------|------|
| Channel                                                                                                                                                                                                                                                                           | 0         | 39          | 78   | 0              | 39   | 78   |
| Frequency (MHz)                                                                                                                                                                                                                                                                   | 2402      | 2441        | 2480 | 2402           | 2441 | 2480 |
| AV Power (dBm)                                                                                                                                                                                                                                                                    | 6.60      | <b>7.56</b> | 6.96 | 4.38           | 5.27 | 4.35 |
| Tune-Up Limit (dBm)                                                                                                                                                                                                                                                               | 7.50      | 8.50        | 8.00 | 5.50           | 6.50 | 5.50 |
| SAR Test Require                                                                                                                                                                                                                                                                  | YES       | YES         | YES  | NO             | NO   | NO   |
| Mode                                                                                                                                                                                                                                                                              | 8-DPSK    |             |      | /              |      |      |
| Channel                                                                                                                                                                                                                                                                           | 0         | 39          | 78   | /              | /    | /    |
| Frequency (MHz)                                                                                                                                                                                                                                                                   | 2402      | 2441        | 2480 | /              | /    | /    |
| AV Power (dBm)                                                                                                                                                                                                                                                                    | 4.61      | 5.43        | 4.74 | /              | /    | /    |
| Tune-Up Limit (dBm)                                                                                                                                                                                                                                                               | 5.50      | 6.50        | 5.50 | /              | /    | /    |
| SAR Test Require                                                                                                                                                                                                                                                                  | NO        | NO          | NO   | /              | /    | /    |
| Mode                                                                                                                                                                                                                                                                              | BLE-1Mbps |             |      | BLE-2Mbps      |      |      |
| Channel                                                                                                                                                                                                                                                                           | 0         | 19          | 39   | 1              | 19   | 38   |
| Frequency (MHz)                                                                                                                                                                                                                                                                   | 2402      | 2440        | 2480 | 2404           | 2440 | 2478 |
| AV Power (dBm)                                                                                                                                                                                                                                                                    | 6.52      | 7.31        | 5.57 | 6.93           | 7.20 | 6.90 |
| Tune-Up Limit (dBm)                                                                                                                                                                                                                                                               | 7.50      | 8.50        | 7.50 | 8.00           | 8.00 | 8.00 |
| SAR Test Require                                                                                                                                                                                                                                                                  | NO        | NO          | NO   | NO             | NO   | NO   |
| Note 1: Since bluetooth BR mode is the maximum output power mode, SAR measurements were performed with test software using DH5 modulation, and SAR measurement is not required for the EDR and LE. When the secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode. |           |             |      |                |      |      |

## 8.6 Power Reduction List

1. This mobile phone device supports the receiver detection mechanism .This device uses the receiver to indicate whether the user is making a call in head.
2. When device is making call in head, and the receiver will work, the power reduction will applied for SAR compliance.
3. When there is a voice call (including VOIP), the audio is actively routed through the headset or speaker, and the receiver will not work, which indicating the body exposure conditions will trigger the body/Limbs exposure reduced the power.
4. When this device used data mode only, and the receiver will not work too, the reduced the power are same as body exposure.

**WLAN Reduced power level table**

| Reduced level | Receiver state         | Transmitting            | Antenna | Position                                                        |
|---------------|------------------------|-------------------------|---------|-----------------------------------------------------------------|
|               |                        | conditions              |         |                                                                 |
| Level 1       | On<br>(head scenario)  | Only 2.4GWLAN           | Ant.1   | Head                                                            |
| Level 2       | On<br>(head scenario)  | BT+WWAN; 2.4G WLAN+WWAN | Ant.1   | Head                                                            |
| Level 3       | Off<br>(Body scenario) | Only 2.4GWLAN           | Ant.1   | Front Side;Back Side; Left Edge;Right Edge;Top Edge;Bottom Edge |
| Level 4       | Off<br>(Body scenario) | BT+WWAN; 2.4G WLAN+WWAN | Ant.1   | Front Side;Back Side; Left Edge;Right Edge;Top Edge;Bottom Edge |

| Mode                | Antenna | WLAN Antenna 1 |          |          |
|---------------------|---------|----------------|----------|----------|
|                     |         | Full Power     | Level1&2 | Level3&4 |
| 2.4G WLAN 802.11b   | ANT1    | 20.00          | 15.00    | 17.00    |
| 2.4G WLAN 802.11g   | ANT1    | 18.00          | 13.00    | 15.00    |
| 2.4G WLAN 802.11n20 | ANT1    | 18.00          | 13.00    | 15.00    |

## 9 TEST EXCLUSION CONSIDERATION

For antenna location and support bands please refer the document “BL-SH24B0867-AI EUT internal photo.pdf”.

| Antenna | Front Side(mm) | Back Side(mm) | Left Edge(mm) | Right Edge(mm) | Top Edge(mm) | Bottom Edge(mm) |
|---------|----------------|---------------|---------------|----------------|--------------|-----------------|
| Ant.0   | <25            | <25           | <25           | <25            | >25          | <25             |
| Ant.1   | <25            | <25           | >25           | <25            | <25          | >25             |

Note: 1.Per KDB 941225 D06,When the overall length and width of a device is > 9 cm \*5 cm, a test separation distance of 10 mm is required for hotspot mode SAR measurements and hotspot mode SAR is measured for all edges and surfaces of the device with a transmitting antenna located within 25 mm from that surface or edge.

10 TEST RESULT

10.1GSM 850

| Antenna                                                                        | Mode           | Position    | Dist.<br>(mm) | Ch. | Freq.<br>(MHz) | Power<br>Drift<br>(dB) | 1 g<br>Meas<br>SAR<br>(W/kg) | Meas.<br>Power<br>(dBm) | Max.<br>tune-<br>power<br>(dBm) | Scaling<br>Factor | 1 g<br>Scaled<br>SAR<br>(W/kg) | Meas.<br>No. |
|--------------------------------------------------------------------------------|----------------|-------------|---------------|-----|----------------|------------------------|------------------------------|-------------------------|---------------------------------|-------------------|--------------------------------|--------------|
| Head                                                                           |                |             |               |     |                |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | DATA<br>4slots | Left Cheek  | 0             | 251 | 848.8          | -0.06                  | 0.244                        | 28.83                   | 30.00                           | 1.309             | 0.319                          | /            |
|                                                                                |                | Left Tilt   | 0             | 251 | 848.8          | 0.14                   | 0.152                        | 28.83                   | 30.00                           | 1.309             | 0.199                          | /            |
|                                                                                |                | Right Cheek | 0             | 251 | 848.8          | 0.00                   | 0.269                        | 28.83                   | 30.00                           | 1.309             | 0.352                          | 1#           |
|                                                                                |                | Right Tilt  | 0             | 251 | 848.8          | -0.01                  | 0.158                        | 28.83                   | 30.00                           | 1.309             | 0.207                          | /            |
| Body-worn                                                                      |                |             |               |     |                |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | DATA<br>4slots | Front Side  | 15            | 251 | 848.8          | 0.04                   | 0.155                        | 28.83                   | 30.00                           | 1.309             | 0.203                          | /            |
|                                                                                |                | Back Side   | 15            | 251 | 848.8          | -0.01                  | 0.264                        | 28.83                   | 30.00                           | 1.309             | 0.346                          | 2#           |
| Hotspot                                                                        |                |             |               |     |                |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | DATA<br>4slots | Front Side  | 10            | 251 | 848.8          | -0.07                  | 0.184                        | 28.83                   | 30.00                           | 1.309             | 0.241                          | /            |
|                                                                                |                | Back Side   | 10            | 251 | 848.8          | 0.00                   | 0.267                        | 28.83                   | 30.00                           | 1.309             | 0.350                          | 3#           |
|                                                                                |                | Left Edge   | 10            | 251 | 848.8          | 0.17                   | 0.104                        | 28.83                   | 30.00                           | 1.309             | 0.136                          | /            |
|                                                                                |                | Right Edge  | 10            | 251 | 848.8          | -0.04                  | 0.094                        | 28.83                   | 30.00                           | 1.309             | 0.123                          | /            |
|                                                                                |                | Bottom Edge | 10            | 251 | 848.8          | -0.16                  | 0.044                        | 28.83                   | 30.00                           | 1.309             | 0.058                          | /            |
| Note: Refer to ANNEX C for the detailed test data for each test configuration. |                |             |               |     |                |                        |                              |                         |                                 |                   |                                |              |

10.2GSM 1900

| Antenna                                                                        | Mode           | Position    | Dist.<br>(mm) | Ch. | Freq.<br>(MHz) | Power<br>Drift<br>(dB) | 1 g<br>Meas<br>SAR<br>(W/kg) | Meas.<br>Power<br>(dBm) | Max.<br>tune-<br>power<br>(dBm) | Scaling<br>Factor | 1 g<br>Scaled<br>SAR<br>(W/kg) | Meas.<br>No. |
|--------------------------------------------------------------------------------|----------------|-------------|---------------|-----|----------------|------------------------|------------------------------|-------------------------|---------------------------------|-------------------|--------------------------------|--------------|
| Head                                                                           |                |             |               |     |                |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | DATA<br>4slots | Left Cheek  | 0             | 661 | 1880           | -0.20                  | 0.127                        | 25.88                   | 27.00                           | 1.294             | 0.164                          | 4#           |
|                                                                                |                | Left Tilt   | 0             | 661 | 1880           | 0.05                   | 0.050                        | 25.88                   | 27.00                           | 1.294             | 0.065                          | /            |
|                                                                                |                | Right Cheek | 0             | 661 | 1880           | 0.12                   | 0.069                        | 25.88                   | 27.00                           | 1.294             | 0.089                          | /            |
|                                                                                |                | Right Tilt  | 0             | 661 | 1880           | -0.02                  | 0.036                        | 25.88                   | 27.00                           | 1.294             | 0.047                          | /            |
| Body-worn                                                                      |                |             |               |     |                |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | DATA<br>4slots | Front Side  | 15            | 661 | 1880           | -0.15                  | 0.248                        | 25.88                   | 27.00                           | 1.294             | 0.321                          | /            |
|                                                                                |                | Back Side   | 15            | 661 | 1880           | -0.03                  | 0.457                        | 25.88                   | 27.00                           | 1.294             | 0.591                          | 5#           |
| Hotspot                                                                        |                |             |               |     |                |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | DATA<br>4slots | Front Side  | 10            | 661 | 1880           | -0.09                  | 0.526                        | 25.88                   | 27.00                           | 1.294             | 0.681                          | /            |
|                                                                                |                | Back Side   | 10            | 661 | 1880           | 0.05                   | 0.916                        | 25.88                   | 27.00                           | 1.294             | 1.185                          | 6#           |
|                                                                                |                | Left Edge   | 10            | 661 | 1880           | 0.15                   | 0.072                        | 25.88                   | 27.00                           | 1.294             | 0.093                          | /            |
|                                                                                |                | Right Edge  | 10            | 661 | 1880           | 0.04                   | 0.124                        | 25.88                   | 27.00                           | 1.294             | 0.160                          | /            |
|                                                                                |                | Bottom Edge | 10            | 661 | 1880           | 0.03                   | 0.754                        | 25.88                   | 27.00                           | 1.294             | 0.976                          | /            |
|                                                                                |                | Back Side   | 10            | 512 | 1850.2         | 0.10                   | 0.655                        | 25.66                   | 27.00                           | 1.361             | 0.891                          | /            |
|                                                                                |                | Back Side   | 10            | 810 | 1909.8         | -0.04                  | 0.803                        | 25.52                   | 27.00                           | 1.406             | 1.129                          | /            |
|                                                                                |                | Bottom Edge | 10            | 512 | 1850.2         | -0.16                  | 0.728                        | 25.66                   | 27.00                           | 1.361             | 0.991                          | /            |
|                                                                                |                | Bottom Edge | 10            | 810 | 1909.8         | -0.18                  | 0.692                        | 25.52                   | 27.00                           | 1.406             | 0.973                          | /            |
| Note: Refer to ANNEX C for the detailed test data for each test configuration. |                |             |               |     |                |                        |                              |                         |                                 |                   |                                |              |

10.3WCDMA Band 2

| Antenna                                                                        | Mode | Position    | Dist.<br>(mm) | Ch.  | Freq.<br>(MHz) | Power<br>Drift<br>(dB) | 1 g<br>Meas<br>SAR<br>(W/kg) | Meas.<br>Power<br>(dBm) | Max.<br>tune-<br>power<br>(dBm) | Scaling<br>Factor | 1 g<br>Scaled<br>SAR<br>(W/kg) | Meas.<br>No. |
|--------------------------------------------------------------------------------|------|-------------|---------------|------|----------------|------------------------|------------------------------|-------------------------|---------------------------------|-------------------|--------------------------------|--------------|
| Head                                                                           |      |             |               |      |                |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | RMC  | Left Cheek  | 0             | 9400 | 1880           | -0.03                  | 0.077                        | 23.49                   | 24.50                           | 1.262             | 0.097                          | 7#           |
|                                                                                |      | Left Tilt   | 0             | 9400 | 1880           | -0.11                  | 0.031                        | 23.49                   | 24.50                           | 1.262             | 0.039                          | /            |
|                                                                                |      | Right Cheek | 0             | 9400 | 1880           | -0.01                  | 0.057                        | 23.49                   | 24.50                           | 1.262             | 0.072                          | /            |
|                                                                                |      | Right Tilt  | 0             | 9400 | 1880           | 0.17                   | 0.011                        | 23.49                   | 24.50                           | 1.262             | 0.014                          | /            |
| Body-worn                                                                      |      |             |               |      |                |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | RMC  | Front Side  | 15            | 9400 | 1880           | -0.09                  | 0.226                        | 23.49                   | 24.50                           | 1.262             | 0.285                          | /            |
|                                                                                |      | Back Side   | 15            | 9400 | 1880           | -0.19                  | 0.349                        | 23.49                   | 24.50                           | 1.262             | 0.440                          | 8#           |
| Hotspot                                                                        |      |             |               |      |                |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | RMC  | Front Side  | 10            | 9400 | 1880           | 0.07                   | 0.412                        | 23.49                   | 24.50                           | 1.262             | 0.520                          | /            |
|                                                                                |      | Back Side   | 10            | 9400 | 1880           | 0.01                   | 0.593                        | 23.49                   | 24.50                           | 1.262             | 0.748                          | /            |
|                                                                                |      | Left Edge   | 10            | 9400 | 1880           | -0.13                  | 0.108                        | 23.49                   | 24.50                           | 1.262             | 0.136                          | /            |
|                                                                                |      | Right Edge  | 10            | 9400 | 1880           | 0.14                   | 0.044                        | 23.49                   | 24.50                           | 1.262             | 0.056                          | /            |
|                                                                                |      | Bottom Edge | 10            | 9400 | 1880           | 0.03                   | 0.713                        | 23.49                   | 24.50                           | 1.262             | 0.900                          | 9#           |
|                                                                                |      | Bottom Edge | 10            | 9262 | 1852.4         | -0.08                  | 0.673                        | 23.30                   | 24.50                           | 1.318             | 0.887                          | /            |
|                                                                                |      | Bottom Edge | 10            | 9538 | 1907.6         | -0.18                  | 0.676                        | 23.31                   | 24.50                           | 1.315             | 0.889                          | /            |
| Note: Refer to ANNEX C for the detailed test data for each test configuration. |      |             |               |      |                |                        |                              |                         |                                 |                   |                                |              |

10.4WCDMA Band 4

| Antenna                                                                        | Mode | Position    | Dist.<br>(mm) | Ch.  | Freq.<br>(MHz) | Power<br>Drift<br>(dB) | 1 g<br>Meas<br>SAR<br>(W/kg) | Meas.<br>Power<br>(dBm) | Max.<br>tune-<br>power<br>(dBm) | Scaling<br>Factor | 1 g<br>Scaled<br>SAR<br>(W/kg) | Meas.<br>No. |
|--------------------------------------------------------------------------------|------|-------------|---------------|------|----------------|------------------------|------------------------------|-------------------------|---------------------------------|-------------------|--------------------------------|--------------|
| Head                                                                           |      |             |               |      |                |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | RMC  | Left Cheek  | 0             | 1312 | 1712.4         | 0.18                   | 0.113                        | 23.83                   | 24.50                           | 1.167             | 0.132                          | 10#          |
|                                                                                |      | Left Tilt   | 0             | 1312 | 1712.4         | -0.17                  | 0.071                        | 23.83                   | 24.50                           | 1.167             | 0.083                          | /            |
|                                                                                |      | Right Cheek | 0             | 1312 | 1712.4         | 0.03                   | 0.098                        | 23.83                   | 24.50                           | 1.167             | 0.114                          | /            |
|                                                                                |      | Right Tilt  | 0             | 1312 | 1712.4         | -0.19                  | 0.058                        | 23.83                   | 24.50                           | 1.167             | 0.068                          | /            |
| Body-worn                                                                      |      |             |               |      |                |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | RMC  | Front Side  | 15            | 1312 | 1712.4         | -0.04                  | 0.173                        | 23.83                   | 24.50                           | 1.167             | 0.202                          | /            |
|                                                                                |      | Back Side   | 15            | 1312 | 1712.4         | -0.08                  | 0.190                        | 23.83                   | 24.50                           | 1.167             | 0.222                          | 11#          |
| Hotspot                                                                        |      |             |               |      |                |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | RMC  | Front Side  | 10            | 1312 | 1712.4         | 0.11                   | 0.266                        | 23.83                   | 24.50                           | 1.167             | 0.310                          | /            |
|                                                                                |      | Back Side   | 10            | 1312 | 1712.4         | 0.06                   | 0.278                        | 23.83                   | 24.50                           | 1.167             | 0.324                          | 12#          |
|                                                                                |      | Left Edge   | 10            | 1312 | 1712.4         | -0.13                  | 0.150                        | 23.83                   | 24.50                           | 1.167             | 0.175                          | /            |
|                                                                                |      | Right Edge  | 10            | 1312 | 1712.4         | 0.02                   | 0.062                        | 23.83                   | 24.50                           | 1.167             | 0.072                          | /            |
|                                                                                |      | Bottom Edge | 10            | 1312 | 1712.4         | -0.11                  | 0.198                        | 23.83                   | 24.50                           | 1.167             | 0.231                          | /            |
| Note: Refer to ANNEX C for the detailed test data for each test configuration. |      |             |               |      |                |                        |                              |                         |                                 |                   |                                |              |

10.5WCDMA Band 5

| Antenna                                                                        | Mode | Position    | Dist.<br>(mm) | Ch.  | Freq.<br>(MHz) | Power<br>Drift<br>(dB) | 1 g<br>Meas<br>SAR<br>(W/kg) | Meas.<br>Power<br>(dBm) | Max.<br>tune-<br>power<br>(dBm) | Scaling<br>Factor | 1 g Scaled<br>SAR<br>(W/kg) | Meas.<br>No. |
|--------------------------------------------------------------------------------|------|-------------|---------------|------|----------------|------------------------|------------------------------|-------------------------|---------------------------------|-------------------|-----------------------------|--------------|
| Head                                                                           |      |             |               |      |                |                        |                              |                         |                                 |                   |                             |              |
| Ant.0                                                                          | RMC  | Left Cheek  | 0             | 4182 | 836.4          | 0.08                   | 0.094                        | 23.81                   | 24.50                           | 1.172             | 0.110                       | /            |
|                                                                                |      | Left Tilt   | 0             | 4182 | 836.4          | -0.05                  | 0.062                        | 23.81                   | 24.50                           | 1.172             | 0.073                       | /            |
|                                                                                |      | Right Cheek | 0             | 4182 | 836.4          | -0.11                  | 0.099                        | 23.81                   | 24.50                           | 1.172             | 0.116                       | 13#          |
|                                                                                |      | Right Tilt  | 0             | 4182 | 836.4          | -0.09                  | 0.060                        | 23.81                   | 24.50                           | 1.172             | 0.070                       | /            |
| Body-worn                                                                      |      |             |               |      |                |                        |                              |                         |                                 |                   |                             |              |
| Ant.0                                                                          | RMC  | Front Side  | 15            | 4182 | 836.4          | -0.12                  | 0.073                        | 23.81                   | 24.50                           | 1.172             | 0.086                       | /            |
|                                                                                |      | Back Side   | 15            | 4182 | 836.4          | 0.03                   | 0.124                        | 23.81                   | 24.50                           | 1.172             | 0.145                       | 14#          |
| Hotspot                                                                        |      |             |               |      |                |                        |                              |                         |                                 |                   |                             |              |
| Ant.0                                                                          | RMC  | Front Side  | 10            | 4182 | 836.4          | -0.04                  | 0.077                        | 23.81                   | 24.50                           | 1.172             | 0.090                       | /            |
|                                                                                |      | Back Side   | 10            | 4182 | 836.4          | -0.02                  | 0.144                        | 23.81                   | 24.50                           | 1.172             | 0.169                       | 15#          |
|                                                                                |      | Left Edge   | 10            | 4182 | 836.4          | -0.15                  | 0.048                        | 23.81                   | 24.50                           | 1.172             | 0.056                       | /            |
|                                                                                |      | Right Edge  | 10            | 4182 | 836.4          | 0.19                   | 0.071                        | 23.81                   | 24.50                           | 1.172             | 0.083                       | /            |
|                                                                                |      | Bottom Edge | 10            | 4182 | 836.4          | -0.14                  | 0.011                        | 23.81                   | 24.50                           | 1.172             | 0.013                       | /            |
| Note: Refer to ANNEX C for the detailed test data for each test configuration. |      |             |               |      |                |                        |                              |                         |                                 |                   |                             |              |

10.6LTE Band 12 (10MHz Bandwidth)

| Antenna                                                                        | Mode | Position    | Dist.<br>(mm) | Ch.       | Freq.<br>(MHz) | RB<br>Num. | RB<br>Start | Power<br>Drift<br>(dB) | 1 g<br>Meas<br>SA<br>R(W/kg) | Meas.<br>Power<br>(dBm) | Max.<br>tune-<br>power<br>(dBm) | Scaling<br>Factor | 1 g<br>Scaled<br>SAR<br>(W/kg) | Meas.<br>No. |
|--------------------------------------------------------------------------------|------|-------------|---------------|-----------|----------------|------------|-------------|------------------------|------------------------------|-------------------------|---------------------------------|-------------------|--------------------------------|--------------|
| Head                                                                           |      |             |               |           |                |            |             |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | QPSK | Left Cheek  | 0             | 23095     | 707.5          | 1          | Low         | 0.09                   | 0.066                        | 23.73                   | 24.50                           | 1.194             | <b>0.079</b>                   | 16#          |
|                                                                                |      | Left Tilt   | 0             | 23095     | 707.5          | 1          | Low         | -0.09                  | 0.028                        | 23.73                   | 24.50                           | 1.194             | 0.033                          | /            |
|                                                                                |      | Right Cheek | 0             | 23095     | 707.5          | 1          | Low         | 0.14                   | 0.054                        | 23.73                   | 24.50                           | 1.194             | 0.064                          | /            |
|                                                                                |      | Right Tilt  | 0             | 23095     | 707.5          | 1          | Low         | -0.09                  | 0.012                        | 23.73                   | 24.50                           | 1.194             | 0.014                          | /            |
|                                                                                |      | Left Cheek  | 0             | 23095     | 707.5          | 25         | Low         | -0.02                  | 0.058                        | 22.50                   | 23.50                           | 1.259             | 0.073                          | /            |
|                                                                                |      | Left Tilt   | 0             | 23095     | 707.5          | 25         | Low         | 0.04                   | 0.022                        | 22.50                   | 23.50                           | 1.259             | 0.028                          | /            |
|                                                                                |      | Right Cheek | 0             | 23095     | 707.5          | 25         | Low         | 0.09                   | 0.049                        | 22.50                   | 23.50                           | 1.259             | 0.062                          | /            |
|                                                                                |      | Right Tilt  | 0             | 23095     | 707.5          | 25         | Low         | 0.19                   | 0.018                        | 22.50                   | 23.50                           | 1.259             | 0.023                          | /            |
| Body-worn                                                                      |      |             |               |           |                |            |             |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | QPSK | Front Side  | 15            | 23095     | 707.5          | 1          | Low         | 0.11                   | 0.076                        | 23.73                   | 24.50                           | 1.194             | 0.091                          | /            |
|                                                                                |      | Back Side   | 15            | 23095     | 707.5          | 1          | Low         | 0.00                   | 0.096                        | 23.73                   | 24.50                           | 1.194             | <b>0.115</b>                   | 17#          |
|                                                                                |      | Front Side  | 15            | 23095     | 707.5          | 25         | Low         | 0.13                   | 0.071                        | 22.50                   | 23.50                           | 1.259             | 0.089                          | /            |
|                                                                                |      | Back Side   | 15            | 23095     | 707.5          | 25         | Low         | -0.12                  | 0.090                        | 22.50                   | 23.50                           | 1.259             | 0.113                          | /            |
| Hotspot                                                                        |      |             |               |           |                |            |             |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | QPSK | Front Side  | 10            | 23095.000 | 707.500        | 1          | Low         | -0.08                  | 0.079                        | 23.73                   | 24.50                           | 1.194             | 0.094                          | /            |
|                                                                                |      | Back Side   | 10            | 23095.000 | 707.500        | 1          | Low         | 0.01                   | 0.107                        | 23.73                   | 24.50                           | 1.194             | <b>0.128</b>                   | 18#          |
|                                                                                |      | Left Edge   | 10            | 23095.000 | 707.500        | 1          | Low         | -0.03                  | 0.063                        | 23.73                   | 24.50                           | 1.194             | 0.075                          | /            |
|                                                                                |      | Right Edge  | 10            | 23095.000 | 707.500        | 1          | Low         | 0.04                   | 0.073                        | 23.73                   | 24.50                           | 1.194             | 0.087                          | /            |
|                                                                                |      | Bottom Edge | 10            | 23095.000 | 707.500        | 1          | Low         | -0.09                  | 0.006                        | 23.73                   | 24.50                           | 1.194             | 0.007                          | /            |
|                                                                                |      | Front Side  | 10            | 23095.000 | 707.500        | 25         | Low         | -0.18                  | 0.073                        | 22.50                   | 23.50                           | 1.259             | 0.092                          | /            |
|                                                                                |      | Back Side   | 10            | 23095.000 | 707.500        | 25         | Low         | -0.05                  | 0.099                        | 22.50                   | 23.50                           | 1.259             | 0.125                          | /            |
|                                                                                |      | Left Edge   | 10            | 23095.000 | 707.500        | 25         | Low         | 0.18                   | 0.057                        | 22.50                   | 23.50                           | 1.259             | 0.072                          | /            |
|                                                                                |      | Right Edge  | 10            | 23095.000 | 707.500        | 25         | Low         | -0.17                  | 0.068                        | 22.50                   | 23.50                           | 1.259             | 0.086                          | /            |
|                                                                                |      | Bottom Edge | 10            | 23095.000 | 707.500        | 25         | Low         | 0.03                   | 0.008                        | 22.50                   | 23.50                           | 1.259             | 0.010                          | /            |
| Note: Refer to ANNEX C for the detailed test data for each test configuration. |      |             |               |           |                |            |             |                        |                              |                         |                                 |                   |                                |              |

## 10.7LTE Band 25 (20MHz Bandwidth)

| Antenna                                                                        | Mode | Position    | Dist.<br>(mm) | Ch.   | Freq.<br>(MHz) | RB<br>Num. | RB<br>Start | Power<br>Drift<br>(dB) | 1 g<br>Meas<br>SAR<br>(W/kg) | Meas.<br>Power<br>(dBm) | Max.<br>tune-<br>power<br>(dBm) | Scaling<br>Factor | 1 g<br>Scaled<br>SAR<br>(W/kg) | Meas.<br>No. |
|--------------------------------------------------------------------------------|------|-------------|---------------|-------|----------------|------------|-------------|------------------------|------------------------------|-------------------------|---------------------------------|-------------------|--------------------------------|--------------|
| Head                                                                           |      |             |               |       |                |            |             |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | QPSK | Left Cheek  | 0             | 26365 | 1882.5         | 1          | Low         | -0.04                  | 0.077                        | 23.69                   | 24.50                           | 1.205             | 0.093                          | 19#          |
|                                                                                |      | Left Tilt   | 0             | 26365 | 1882.5         | 1          | Low         | 0.19                   | 0.022                        | 23.69                   | 24.50                           | 1.205             | 0.027                          | /            |
|                                                                                |      | Right Cheek | 0             | 26365 | 1882.5         | 1          | Low         | -0.19                  | 0.053                        | 23.69                   | 24.50                           | 1.205             | 0.064                          | /            |
|                                                                                |      | Right Tilt  | 0             | 26365 | 1882.5         | 1          | Low         | -0.01                  | 0.011                        | 23.69                   | 24.50                           | 1.205             | 0.013                          | /            |
|                                                                                |      | Left Cheek  | 0             | 26365 | 1882.5         | 50         | Low         | -0.11                  | 0.057                        | 22.38                   | 23.50                           | 1.294             | 0.074                          | /            |
|                                                                                |      | Left Tilt   | 0             | 26365 | 1882.5         | 50         | Low         | 0.07                   | 0.021                        | 22.38                   | 23.50                           | 1.294             | 0.027                          | /            |
|                                                                                |      | Right Cheek | 0             | 26365 | 1882.5         | 50         | Low         | 0.03                   | 0.048                        | 22.38                   | 23.50                           | 1.294             | 0.062                          | /            |
|                                                                                |      | Right Tilt  | 0             | 26365 | 1882.5         | 50         | Low         | 0.15                   | 0.016                        | 22.38                   | 23.50                           | 1.294             | 0.021                          | /            |
| Body-worn                                                                      |      |             |               |       |                |            |             |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | QPSK | Front Side  | 15            | 26365 | 1882.5         | 1          | Low         | -0.18                  | 0.158                        | 23.69                   | 24.50                           | 1.205             | 0.190                          | /            |
|                                                                                |      | Back Side   | 15            | 26365 | 1882.5         | 1          | Low         | -0.10                  | 0.225                        | 23.69                   | 24.50                           | 1.205             | 0.271                          | 20#          |
|                                                                                |      | Front Side  | 15            | 26365 | 1882.5         | 50         | Low         | -0.10                  | 0.136                        | 22.38                   | 23.50                           | 1.294             | 0.176                          | /            |
|                                                                                |      | Back Side   | 15            | 26365 | 1882.5         | 50         | Low         | 0.17                   | 0.200                        | 22.38                   | 23.50                           | 1.294             | 0.259                          | /            |
| Hotspot                                                                        |      |             |               |       |                |            |             |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | QPSK | Front Side  | 10            | 26365 | 1882.5         | 1          | Low         | 0.06                   | 0.232                        | 23.69                   | 24.50                           | 1.205             | 0.280                          | /            |
|                                                                                |      | Back Side   | 10            | 26365 | 1882.5         | 1          | Low         | 0.17                   | 0.330                        | 23.69                   | 24.50                           | 1.205             | 0.398                          | /            |
|                                                                                |      | Left Edge   | 10            | 26365 | 1882.5         | 1          | Low         | -0.14                  | 0.063                        | 23.69                   | 24.50                           | 1.205             | 0.076                          | /            |
|                                                                                |      | Right Edge  | 10            | 26365 | 1882.5         | 1          | Low         | 0.10                   | 0.039                        | 23.69                   | 24.50                           | 1.205             | 0.047                          | /            |
|                                                                                |      | Bottom Edge | 10            | 26365 | 1882.5         | 1          | Low         | 0.08                   | 0.355                        | 23.69                   | 24.50                           | 1.205             | 0.428                          | 21#          |
|                                                                                |      | Front Side  | 10            | 26365 | 1882.5         | 50         | Low         | 0.15                   | 0.198                        | 22.38                   | 23.50                           | 1.294             | 0.256                          | /            |
|                                                                                |      | Back Side   | 10            | 26365 | 1882.5         | 50         | Low         | 0.16                   | 0.284                        | 22.38                   | 23.50                           | 1.294             | 0.367                          | /            |
|                                                                                |      | Left Edge   | 10            | 26365 | 1882.5         | 50         | Low         | 0.16                   | 0.055                        | 22.38                   | 23.50                           | 1.294             | 0.071                          | /            |
|                                                                                |      | Right Edge  | 10            | 26365 | 1882.5         | 50         | Low         | 0.02                   | 0.035                        | 22.38                   | 23.50                           | 1.294             | 0.045                          | /            |
|                                                                                |      | Bottom Edge | 10            | 26365 | 1882.5         | 50         | Low         | -0.01                  | 0.279                        | 22.38                   | 23.50                           | 1.294             | 0.361                          | /            |
| Note: Refer to ANNEX C for the detailed test data for each test configuration. |      |             |               |       |                |            |             |                        |                              |                         |                                 |                   |                                |              |

10.8LTE Band 26 (15MHz Bandwidth)

| Antenna                                                                        | Mode | Position    | Dist.<br>(mm) | Ch.   | Freq.<br>(MHz) | RB<br>Num. | RB<br>Start | Power<br>Drift<br>(dB) | 1 g<br>Meas<br>SAR<br>(W/kg) | Meas.<br>Power<br>(dBm) | Max.<br>tune-<br>power<br>(dBm) | Scaling<br>Factor | 1 g<br>Scaled<br>SAR<br>(W/kg) | Meas.<br>No. |
|--------------------------------------------------------------------------------|------|-------------|---------------|-------|----------------|------------|-------------|------------------------|------------------------------|-------------------------|---------------------------------|-------------------|--------------------------------|--------------|
| Head                                                                           |      |             |               |       |                |            |             |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | QPSK | Left Cheek  | 0             | 26865 | 831.5          | 1          | Low         | 0.17                   | 0.094                        | 23.82                   | 24.50                           | 1.169             | 0.110                          | 22#          |
|                                                                                |      | Left Tilt   | 0             | 26865 | 831.5          | 1          | Low         | 0.18                   | 0.067                        | 23.82                   | 24.50                           | 1.169             | 0.078                          | /            |
|                                                                                |      | Right Cheek | 0             | 26865 | 831.5          | 1          | Low         | 0.03                   | 0.092                        | 23.82                   | 24.50                           | 1.169             | 0.108                          | /            |
|                                                                                |      | Right Tilt  | 0             | 26865 | 831.5          | 1          | Low         | -0.16                  | 0.063                        | 23.82                   | 24.50                           | 1.169             | 0.074                          | /            |
|                                                                                |      | Left Cheek  | 0             | 26865 | 831.5          | 36         | Low         | -0.16                  | 0.082                        | 22.71                   | 23.50                           | 1.199             | 0.098                          | /            |
|                                                                                |      | Left Tilt   | 0             | 26865 | 831.5          | 36         | Low         | 0.10                   | 0.057                        | 22.71                   | 23.50                           | 1.199             | 0.068                          | /            |
|                                                                                |      | Right Cheek | 0             | 26865 | 831.5          | 36         | Low         | 0.15                   | 0.086                        | 22.71                   | 23.50                           | 1.199             | 0.103                          | /            |
|                                                                                |      | Right Tilt  | 0             | 26865 | 831.5          | 36         | Low         | -0.03                  | 0.054                        | 22.71                   | 23.50                           | 1.199             | 0.065                          | /            |
| Body-worn                                                                      |      |             |               |       |                |            |             |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | QPSK | Front Side  | 15            | 26865 | 831.5          | 1          | Low         | 0.12                   | 0.083                        | 23.82                   | 24.50                           | 1.169             | 0.097                          | /            |
|                                                                                |      | Back Side   | 15            | 26865 | 831.5          | 1          | Low         | -0.04                  | 0.123                        | 23.82                   | 24.50                           | 1.169             | 0.144                          | 23#          |
|                                                                                |      | Front Side  | 15            | 26865 | 831.5          | 36         | Low         | -0.02                  | 0.065                        | 22.71                   | 23.50                           | 1.199             | 0.078                          | /            |
|                                                                                |      | Back Side   | 15            | 26865 | 831.5          | 36         | Low         | 0.18                   | 0.085                        | 22.71                   | 23.50                           | 1.199             | 0.102                          | /            |
| Hotspot                                                                        |      |             |               |       |                |            |             |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | QPSK | Front Side  | 10            | 26865 | 831.5          | 1          | Low         | -0.10                  | 0.082                        | 23.82                   | 24.50                           | 1.169             | 0.096                          | /            |
|                                                                                |      | Back Side   | 10            | 26865 | 831.5          | 1          | Low         | -0.04                  | 0.129                        | 23.82                   | 24.50                           | 1.169             | 0.151                          | 24#          |
|                                                                                |      | Left Edge   | 10            | 26865 | 831.5          | 1          | Low         | 0.13                   | 0.060                        | 23.82                   | 24.50                           | 1.169             | 0.070                          | /            |
|                                                                                |      | Right Edge  | 10            | 26865 | 831.5          | 1          | Low         | -0.03                  | 0.090                        | 23.82                   | 24.50                           | 1.169             | 0.105                          | /            |
|                                                                                |      | Bottom Edge | 10            | 26865 | 831.5          | 1          | Low         | 0.07                   | 0.018                        | 23.82                   | 24.50                           | 1.169             | 0.021                          | /            |
|                                                                                |      | Front Side  | 10            | 26865 | 831.5          | 36         | Low         | 0.10                   | 0.068                        | 22.71                   | 23.50                           | 1.199             | 0.082                          | /            |
|                                                                                |      | Back Side   | 10            | 26865 | 831.5          | 36         | Low         | 0.02                   | 0.095                        | 22.71                   | 23.50                           | 1.199             | 0.114                          | /            |
|                                                                                |      | Left Edge   | 10            | 26865 | 831.5          | 36         | Low         | -0.04                  | 0.049                        | 22.71                   | 23.50                           | 1.199             | 0.059                          | /            |
|                                                                                |      | Right Edge  | 10            | 26865 | 831.5          | 36         | Low         | 0.04                   | 0.069                        | 22.71                   | 23.50                           | 1.199             | 0.083                          | /            |
|                                                                                |      | Bottom Edge | 10            | 26865 | 831.5          | 36         | Low         | 0.14                   | 0.012                        | 22.71                   | 23.50                           | 1.199             | 0.014                          | /            |
| Note: Refer to ANNEX C for the detailed test data for each test configuration. |      |             |               |       |                |            |             |                        |                              |                         |                                 |                   |                                |              |

## 10.9LTE Band 66 (20MHz Bandwidth)

| Antenna                                                                        | Mode | Position    | Dist.<br>(mm) | Ch.    | Freq.<br>(MHz) | RB<br>Num. | RB<br>Start | Power<br>Drift<br>(dB) | 1 g<br>Meas<br>SAR<br>(W/kg) | Meas.<br>Power<br>(dBm) | Max.<br>tune-<br>power<br>(dBm) | Scaling<br>Factor | 1 g<br>Scaled<br>SAR<br>(W/kg) | Meas.<br>No. |
|--------------------------------------------------------------------------------|------|-------------|---------------|--------|----------------|------------|-------------|------------------------|------------------------------|-------------------------|---------------------------------|-------------------|--------------------------------|--------------|
| Head                                                                           |      |             |               |        |                |            |             |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | QPSK | Left Cheek  | 0             | 132322 | 1745           | 1          | Low         | -0.06                  | 0.115                        | 23.79                   | 24.50                           | 1.178             | 0.135                          | 25#          |
|                                                                                |      | Left Tilt   | 0             | 132322 | 1745           | 1          | Low         | 0.07                   | 0.061                        | 23.79                   | 24.50                           | 1.178             | 0.072                          | /            |
|                                                                                |      | Right Cheek | 0             | 132322 | 1745           | 1          | Low         | -0.15                  | 0.094                        | 23.79                   | 24.50                           | 1.178             | 0.111                          | /            |
|                                                                                |      | Right Tilt  | 0             | 132322 | 1745           | 1          | Low         | -0.19                  | 0.045                        | 23.79                   | 24.50                           | 1.178             | 0.053                          | /            |
|                                                                                |      | Left Cheek  | 0             | 132322 | 1745           | 50         | Low         | -0.12                  | 0.095                        | 22.57                   | 23.50                           | 1.239             | 0.118                          | /            |
|                                                                                |      | Left Tilt   | 0             | 132322 | 1745           | 50         | Low         | 0.12                   | 0.050                        | 22.57                   | 23.50                           | 1.239             | 0.062                          | /            |
|                                                                                |      | Right Cheek | 0             | 132322 | 1745           | 50         | Low         | -0.04                  | 0.078                        | 22.57                   | 23.50                           | 1.239             | 0.097                          | /            |
|                                                                                |      | Right Tilt  | 0             | 132322 | 1745           | 50         | Low         | -0.08                  | 0.016                        | 22.57                   | 23.50                           | 1.239             | 0.020                          | /            |
| Body-worn                                                                      |      |             |               |        |                |            |             |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | QPSK | Front Side  | 15            | 132322 | 1745           | 1          | Low         | -0.20                  | 0.123                        | 23.79                   | 24.50                           | 1.178             | 0.145                          | 26#          |
|                                                                                |      | Back Side   | 15            | 132322 | 1745           | 1          | Low         | 0.02                   | 0.114                        | 23.79                   | 24.50                           | 1.178             | 0.134                          | /            |
|                                                                                |      | Front Side  | 15            | 132322 | 1745           | 50         | Low         | 0.16                   | 0.107                        | 22.57                   | 23.50                           | 1.239             | 0.133                          | /            |
|                                                                                |      | Back Side   | 15            | 132322 | 1745           | 50         | Low         | -0.17                  | 0.101                        | 22.57                   | 23.50                           | 1.239             | 0.125                          | /            |
| Hotspot                                                                        |      |             |               |        |                |            |             |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | QPSK | Front Side  | 10            | 132322 | 1745           | 1          | Low         | -0.11                  | 0.229                        | 23.79                   | 24.50                           | 1.178             | 0.270                          | /            |
|                                                                                |      | Back Side   | 10            | 132322 | 1745           | 1          | Low         | -0.08                  | 0.234                        | 23.79                   | 24.50                           | 1.178             | 0.276                          | 27#          |
|                                                                                |      | Left Edge   | 10            | 132322 | 1745           | 1          | Low         | -0.06                  | 0.117                        | 23.79                   | 24.50                           | 1.178             | 0.138                          | /            |
|                                                                                |      | Right Edge  | 10            | 132322 | 1745           | 1          | Low         | -0.06                  | 0.068                        | 23.79                   | 24.50                           | 1.178             | 0.080                          | /            |
|                                                                                |      | Bottom Edge | 10            | 132322 | 1745           | 1          | Low         | 0.03                   | 0.195                        | 23.79                   | 24.50                           | 1.178             | 0.230                          | /            |
|                                                                                |      | Front Side  | 10            | 132322 | 1745           | 50         | Low         | 0.13                   | 0.195                        | 22.57                   | 23.50                           | 1.239             | 0.242                          | /            |
|                                                                                |      | Back Side   | 10            | 132322 | 1745           | 50         | Low         | 0.17                   | 0.196                        | 22.57                   | 23.50                           | 1.239             | 0.243                          | /            |
|                                                                                |      | Left Edge   | 10            | 132322 | 1745           | 50         | Low         | 0.09                   | 0.106                        | 22.57                   | 23.50                           | 1.239             | 0.131                          | /            |
|                                                                                |      | Right Edge  | 10            | 132322 | 1745           | 50         | Low         | 0.14                   | 0.055                        | 22.57                   | 23.50                           | 1.239             | 0.068                          | /            |
|                                                                                |      | Bottom Edge | 10            | 132322 | 1745           | 50         | Low         | -0.11                  | 0.177                        | 22.57                   | 23.50                           | 1.239             | 0.219                          | /            |
| Note: Refer to ANNEX C for the detailed test data for each test configuration. |      |             |               |        |                |            |             |                        |                              |                         |                                 |                   |                                |              |

## 10.10 LTE Band 71 (20MHz Bandwidth)

| Antenna                                                                        | Mode | Position    | Dist.<br>(mm) | Ch.    | Freq.<br>(MHz) | RB<br>Num. | RB<br>Start | Power<br>Drift<br>(dB) | 1 g<br>Meas<br>SAR<br>(W/kg) | Meas.<br>Power<br>(dBm) | Max.<br>tune-<br>power<br>(dBm) | Scaling<br>Factor | 1 g<br>Scaled<br>SAR<br>(W/kg) | Meas.<br>No. |
|--------------------------------------------------------------------------------|------|-------------|---------------|--------|----------------|------------|-------------|------------------------|------------------------------|-------------------------|---------------------------------|-------------------|--------------------------------|--------------|
| Head                                                                           |      |             |               |        |                |            |             |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | QPSK | Left Cheek  | 0             | 133322 | 683            | 1          | Low         | -0.14                  | 0.112                        | 23.74                   | 24.50                           | 1.191             | 0.133                          | 28#          |
|                                                                                |      | Left Tilt   | 0             | 133322 | 683            | 1          | Low         | 0.03                   | 0.045                        | 23.74                   | 24.50                           | 1.191             | 0.054                          | /            |
|                                                                                |      | Right Cheek | 0             | 133322 | 683            | 1          | Low         | 0.04                   | 0.066                        | 23.74                   | 24.50                           | 1.191             | 0.079                          | /            |
|                                                                                |      | Right Tilt  | 0             | 133322 | 683            | 1          | Low         | 0.05                   | 0.011                        | 23.74                   | 24.50                           | 1.191             | 0.013                          | /            |
|                                                                                |      | Left Cheek  | 0             | 133322 | 683            | 50         | Low         | -0.08                  | 0.062                        | 22.58                   | 23.50                           | 1.236             | 0.077                          | /            |
|                                                                                |      | Left Tilt   | 0             | 133322 | 683            | 50         | Low         | -0.11                  | 0.007                        | 22.58                   | 23.50                           | 1.236             | 0.009                          | /            |
|                                                                                |      | Right Cheek | 0             | 133322 | 683            | 50         | Low         | 0.15                   | 0.053                        | 22.58                   | 23.50                           | 1.236             | 0.066                          | /            |
|                                                                                |      | Right Tilt  | 0             | 133322 | 683            | 50         | Low         | 0.19                   | 0.003                        | 22.58                   | 23.50                           | 1.236             | 0.004                          | /            |
| Body-worn                                                                      |      |             |               |        |                |            |             |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | QPSK | Front Side  | 15            | 133322 | 683            | 1          | Low         | 0.19                   | 0.085                        | 23.74                   | 24.50                           | 1.191             | 0.101                          | /            |
|                                                                                |      | Back Side   | 15            | 133322 | 683            | 1          | Low         | -0.01                  | 0.088                        | 23.74                   | 24.50                           | 1.191             | 0.105                          | 29#          |
|                                                                                |      | Front Side  | 15            | 133322 | 683            | 50         | Low         | 0.05                   | 0.063                        | 22.58                   | 23.50                           | 1.236             | 0.078                          | /            |
|                                                                                |      | Back Side   | 15            | 133322 | 683            | 50         | Low         | -0.03                  | 0.078                        | 22.58                   | 23.50                           | 1.236             | 0.096                          | /            |
| Hotspot                                                                        |      |             |               |        |                |            |             |                        |                              |                         |                                 |                   |                                |              |
| Ant.0                                                                          | QPSK | Front Side  | 10            | 133322 | 683            | 1          | Low         | -0.03                  | 0.070                        | 23.74                   | 24.50                           | 1.191             | 0.083                          | /            |
|                                                                                |      | Back Side   | 10            | 133322 | 683            | 1          | Low         | 0.13                   | 0.085                        | 23.74                   | 24.50                           | 1.191             | 0.101                          | /            |
|                                                                                |      | Left Edge   | 10            | 133322 | 683            | 1          | Low         | 0.15                   | 0.049                        | 23.74                   | 24.50                           | 1.191             | 0.058                          | /            |
|                                                                                |      | Right Edge  | 10            | 133322 | 683            | 1          | Low         | -0.03                  | 0.087                        | 23.74                   | 24.50                           | 1.191             | 0.104                          | 30#          |
|                                                                                |      | Bottom Edge | 10            | 133322 | 683            | 1          | Low         | -0.04                  | 0.006                        | 23.74                   | 24.50                           | 1.191             | 0.007                          | /            |
|                                                                                |      | Front Side  | 10            | 133322 | 683            | 50         | Low         | 0.04                   | 0.055                        | 22.58                   | 23.50                           | 1.236             | 0.068                          | /            |
|                                                                                |      | Back Side   | 10            | 133322 | 683            | 50         | Low         | 0.15                   | 0.071                        | 22.58                   | 23.50                           | 1.236             | 0.088                          | /            |
|                                                                                |      | Left Edge   | 10            | 133322 | 683            | 50         | Low         | 0.10                   | 0.037                        | 22.58                   | 23.50                           | 1.236             | 0.046                          | /            |
|                                                                                |      | Right Edge  | 10            | 133322 | 683            | 50         | Low         | 0.15                   | 0.074                        | 22.58                   | 23.50                           | 1.236             | 0.091                          | /            |
|                                                                                |      | Bottom Edge | 10            | 133322 | 683            | 50         | Low         | 0.15                   | 0.004                        | 22.58                   | 23.50                           | 1.236             | 0.005                          | /            |
| Note: Refer to ANNEX C for the detailed test data for each test configuration. |      |             |               |        |                |            |             |                        |                              |                         |                                 |                   |                                |              |

10.11 WIFI 2.4GHZ

| Antenna                                                                        | Power Reduction | Mode     | Position    | Dist. (mm) | Ch. | Freq. (MHz) | Power Drift (dB) | 1 g Meas SAR (W/kg) | Meas. Power (dBm) | Max. tune-power (dBm) | Scaling Factor | Duty Cycle (%) | Scaling Factor | 1 g Scaled SAR (W/kg) | Meas. No. |
|--------------------------------------------------------------------------------|-----------------|----------|-------------|------------|-----|-------------|------------------|---------------------|-------------------|-----------------------|----------------|----------------|----------------|-----------------------|-----------|
| Head                                                                           |                 |          |             |            |     |             |                  |                     |                   |                       |                |                |                |                       |           |
| Ant.1                                                                          | Level1&2        | 802.11 b | Left Cheek  | 0          | 1   | 2412        | -0.11            | 0.648               | 13.28             | 15.00                 | 1.486          | 98.00          | 1.020          | 0.982                 | /         |
|                                                                                | Level1&2        | 802.11 b | Left Tilt   | 0          | 1   | 2412        | -0.16            | 0.433               | 13.28             | 15.00                 | 1.486          | 98.00          | 1.020          | 0.656                 | /         |
|                                                                                | Level1&2        | 802.11 b | Right Cheek | 0          | 1   | 2412        | -0.16            | 0.122               | 13.28             | 15.00                 | 1.486          | 98.00          | 1.020          | 0.185                 | /         |
|                                                                                | Level1&2        | 802.11 b | Right Tilt  | 0          | 1   | 2412        | -0.07            | 0.113               | 13.28             | 15.00                 | 1.486          | 98.00          | 1.020          | 0.171                 | /         |
|                                                                                | Level1&2        | 802.11 b | Left Cheek  | 0          | 6   | 2437        | -0.16            | 0.763               | 13.25             | 15.00                 | 1.496          | 98.00          | 1.020          | 1.164                 | 31#       |
|                                                                                | Level1&2        | 802.11 b | Left Cheek  | 0          | 11  | 2462        | -0.06            | 0.666               | 13.02             | 15.00                 | 1.578          | 98.00          | 1.020          | 1.072                 | /         |
| Body-worn                                                                      |                 |          |             |            |     |             |                  |                     |                   |                       |                |                |                |                       |           |
| Ant.1                                                                          | Full Power      | 802.11 b | Front Side  | 15         | 1   | 2412        | 0.11             | 0.135               | 19.09             | 20.00                 | 1.233          | 98.00          | 1.020          | 0.170                 | /         |
|                                                                                | Full Power      | 802.11 b | Back Side   | 15         | 1   | 2412        | -0.03            | 0.267               | 19.09             | 20.00                 | 1.233          | 98.00          | 1.020          | 0.336                 | 32#       |
| Hotspot                                                                        |                 |          |             |            |     |             |                  |                     |                   |                       |                |                |                |                       |           |
| Ant.1                                                                          | Level3&4        | 802.11 b | Front Side  | 10         | 1   | 2412        | -0.08            | 0.155               | 15.28             | 17.00                 | 1.486          | 98.00          | 1.020          | 0.235                 | /         |
|                                                                                | Level3&4        | 802.11 b | Back Side   | 10         | 1   | 2412        | -0.04            | 0.239               | 15.28             | 17.00                 | 1.486          | 98.00          | 1.020          | 0.362                 | 33#       |
|                                                                                | Level3&4        | 802.11 b | Right Edge  | 10         | 1   | 2412        | 0.19             | 0.229               | 15.28             | 17.00                 | 1.486          | 98.00          | 1.020          | 0.347                 | /         |
|                                                                                | Level3&4        | 802.11 b | Top Edge    | 10         | 1   | 2412        | -0.10            | 0.100               | 15.28             | 17.00                 | 1.486          | 98.00          | 1.020          | 0.152                 | /         |
| Note: Refer to ANNEX C for the detailed test data for each test configuration. |                 |          |             |            |     |             |                  |                     |                   |                       |                |                |                |                       |           |

10.13 Bluetooth

| Antenna                                                                        | Mode | Position    | Dist.<br>(mm) | Ch. | Freq.<br>(MHz) | Power<br>Drift<br>(dB) | 1 g<br>Meas<br>SAR<br>(W/kg) | Meas.<br>Power<br>(dBm) | Max.<br>tune-<br>power<br>(dBm) | Scaling<br>Factor | Duty<br>Cycle<br>(%) | Scaling<br>Factor | 1 g<br>Scaled<br>SAR<br>(W/kg) | Meas.<br>No. |
|--------------------------------------------------------------------------------|------|-------------|---------------|-----|----------------|------------------------|------------------------------|-------------------------|---------------------------------|-------------------|----------------------|-------------------|--------------------------------|--------------|
| Head                                                                           |      |             |               |     |                |                        |                              |                         |                                 |                   |                      |                   |                                |              |
| Ant.1                                                                          | DH5  | Left Cheek  | 0             | 39  | 2441           | -0.13                  | 0.081                        | 7.56                    | 8.50                            | 1.242             | 46.06                | 2.171             | 0.218                          | 34#          |
|                                                                                | DH5  | Left Tilt   | 0             | 39  | 2441           | 0.19                   | 0.046                        | 7.56                    | 8.50                            | 1.242             | 46.06                | 2.171             | 0.124                          | /            |
|                                                                                | DH5  | Right Cheek | 0             | 39  | 2441           | 0.09                   | 0.022                        | 7.56                    | 8.50                            | 1.242             | 46.06                | 2.171             | 0.059                          | /            |
|                                                                                | DH5  | Right Tilt  | 0             | 39  | 2441           | 0.16                   | 0.013                        | 7.56                    | 8.50                            | 1.242             | 46.06                | 2.171             | 0.035                          | /            |
| Body-worn                                                                      |      |             |               |     |                |                        |                              |                         |                                 |                   |                      |                   |                                |              |
| Ant.1                                                                          | DH5  | Front Side  | 15            | 39  | 2441           | -0.02                  | 0.003                        | 7.56                    | 8.50                            | 1.242             | 46.06                | 2.171             | 0.008                          | /            |
|                                                                                | DH5  | Back Side   | 15            | 39  | 2441           | 0.18                   | 0.005                        | 7.56                    | 8.50                            | 1.242             | 46.06                | 2.171             | 0.013                          | 35#          |
| Hotspot                                                                        |      |             |               |     |                |                        |                              |                         |                                 |                   |                      |                   |                                |              |
| Ant.1                                                                          | DH5  | Front Side  | 10            | 39  | 2441           | -0.11                  | 0.008                        | 7.56                    | 8.50                            | 1.242             | 46.06                | 2.171             | 0.022                          | /            |
|                                                                                | DH5  | Back Side   | 10            | 39  | 2441           | 0.19                   | 0.013                        | 7.56                    | 8.50                            | 1.242             | 46.06                | 2.171             | 0.035                          | 36#          |
|                                                                                | DH5  | Right Edge  | 10            | 39  | 2441           | -0.17                  | 0.006                        | 7.56                    | 8.50                            | 1.242             | 46.06                | 2.171             | 0.016                          | /            |
|                                                                                | DH5  | Top Edge    | 10            | 39  | 2441           | -0.16                  | 0.009                        | 7.56                    | 8.50                            | 1.242             | 46.06                | 2.171             | 0.024                          | /            |
| Note: Refer to ANNEX C for the detailed test data for each test configuration. |      |             |               |     |                |                        |                              |                         |                                 |                   |                      |                   |                                |              |

## 11 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are  $\leq 1.45$  W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is  $\leq 1.10$ , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is  $< 0.80$  W/kg, repeated measurement is not required.
2. When the highest measured SAR is  $\geq 0.80$  W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$ , or when the original or repeated measurement is  $\geq 1.45$  W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ , and the original, first or second repeated measurement is  $\geq 1.5$  W/kg, perform a third repeated measurement.

| Frequency Band (MHz)                                                                                                                                        | Wireless Band | RF Exposure Conditions | Test Position | Highest Measured SAR (W/kg) | Repeated SAR (Yes/No) | Repeated <sup>1st</sup> Measured SAR (W/kg) | Largest to Smallest SAR Radio |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------------------|---------------|-----------------------------|-----------------------|---------------------------------------------|-------------------------------|
| 1900                                                                                                                                                        | GSM           | Hotspot                | Back Side     | 0.916                       | Yes                   | 0.902                                       | 1.02                          |
| 1900                                                                                                                                                        | GSM           | Hotspot                | Back Side     | 0.803                       | Yes                   | 0.790                                       | 1.02                          |
| Note: The ratio of largest to smallest SAR for the original and first repeated measurements is $< 1.20$ , the second repeated measurement. is not required. |               |                        |               |                             |                       |                                             |                               |

## 12 SIMULTANEOUS TRANSMISSION

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR 1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR 1g 1.6 W/kg), SAR test exclusion is determined by the SAR to Peak Location Ratio (SPLSR).

### 12.1 Simultaneous Transmission Mode Consider

| No. | Simultaneous Tx Combination | Head | Body-worn | Hotspot |
|-----|-----------------------------|------|-----------|---------|
| 1   | WWAN+WIFI2.4G               | Yes  | Yes       | Yes     |
| 2   | WWAN+Bluetooth              | Yes  | Yes       | Yes     |

Note:

- WiFi 2.4G and Bluetooth share the same antenna, and can't transmit simultaneously.
- When stand-alone SAR is not required for a side of antenna, its SAR is considered zero in the SAR summing process to assess Multi-band transmission SAR compliance.
- The maximum SAR summation is calculated based on the same configuration and test position.

## 12.2 Sum SAR of Simultaneous Transmission

### 12.2.1 Head Simultaneous Transmission SAR Evaluation for WWAN Antenna with WIFI and Bluetooth

| Band     | Antenna | Position    | Stand alone SAR |          |           | SUM SAR      |       |
|----------|---------|-------------|-----------------|----------|-----------|--------------|-------|
|          |         |             | 1               | 2        | 3         | 1+2          | 1+3   |
|          |         |             | WWAN            | 2.4GWIFI | Bluetooth |              |       |
| GSM 850  | Ant.0   | Left Cheek  | 0.319           | 1.164    | 0.218     | <b>1.483</b> | 0.537 |
|          |         | Left Tilt   | 0.199           | 0.656    | 0.124     | 0.855        | 0.323 |
|          |         | Right Cheek | 0.352           | 0.185    | 0.059     | 0.537        | 0.411 |
|          |         | Right Tilt  | 0.207           | 0.171    | 0.035     | 0.378        | 0.242 |
| GSM 1900 | Ant.0   | Left Cheek  | 0.164           | 1.164    | 0.218     | 1.328        | 0.382 |
|          |         | Left Tilt   | 0.065           | 0.656    | 0.124     | 0.721        | 0.189 |
|          |         | Right Cheek | 0.089           | 0.185    | 0.059     | 0.274        | 0.148 |
|          |         | Right Tilt  | 0.047           | 0.171    | 0.035     | 0.218        | 0.082 |
| WCDMA B2 | Ant.0   | Left Cheek  | 0.097           | 1.164    | 0.218     | 1.261        | 0.315 |
|          |         | Left Tilt   | 0.039           | 0.656    | 0.124     | 0.695        | 0.163 |
|          |         | Right Cheek | 0.072           | 0.185    | 0.059     | 0.257        | 0.131 |
|          |         | Right Tilt  | 0.014           | 0.171    | 0.035     | 0.185        | 0.049 |
| WCDMA B4 | Ant.0   | Left Cheek  | 0.132           | 1.164    | 0.218     | 1.296        | 0.350 |
|          |         | Left Tilt   | 0.083           | 0.656    | 0.124     | 0.739        | 0.207 |
|          |         | Right Cheek | 0.114           | 0.185    | 0.059     | 0.299        | 0.173 |
|          |         | Right Tilt  | 0.068           | 0.171    | 0.035     | 0.239        | 0.103 |
| WCDMA B5 | Ant.0   | Left Cheek  | 0.110           | 1.164    | 0.218     | 1.274        | 0.328 |
|          |         | Left Tilt   | 0.073           | 0.656    | 0.124     | 0.729        | 0.197 |
|          |         | Right Cheek | 0.116           | 0.185    | 0.059     | 0.301        | 0.175 |
|          |         | Right Tilt  | 0.070           | 0.171    | 0.035     | 0.241        | 0.105 |
| LTE B12  | Ant.0   | Left Cheek  | 0.079           | 1.164    | 0.218     | 1.243        | 0.297 |
|          |         | Left Tilt   | 0.033           | 0.656    | 0.124     | 0.689        | 0.157 |
|          |         | Right Cheek | 0.064           | 0.185    | 0.059     | 0.249        | 0.123 |
|          |         | Right Tilt  | 0.023           | 0.171    | 0.035     | 0.194        | 0.058 |
| LTE B25  | Ant.0   | Left Cheek  | 0.093           | 1.164    | 0.218     | 1.257        | 0.311 |
|          |         | Left Tilt   | 0.027           | 0.656    | 0.124     | 0.683        | 0.151 |
|          |         | Right Cheek | 0.064           | 0.185    | 0.059     | 0.249        | 0.123 |
|          |         | Right Tilt  | 0.021           | 0.171    | 0.035     | 0.192        | 0.056 |
| LTE B26  | Ant.0   | Left Cheek  | 0.110           | 1.164    | 0.218     | 1.274        | 0.328 |
|          |         | Left Tilt   | 0.078           | 0.656    | 0.124     | 0.734        | 0.202 |
|          |         | Right Cheek | 0.108           | 0.185    | 0.059     | 0.293        | 0.167 |
|          |         | Right Tilt  | 0.074           | 0.171    | 0.035     | 0.245        | 0.109 |
| LTE B66  | Ant.0   | Left Cheek  | 0.135           | 1.164    | 0.218     | 1.299        | 0.353 |
|          |         | Left Tilt   | 0.072           | 0.656    | 0.124     | 0.728        | 0.196 |
|          |         | Right Cheek | 0.111           | 0.185    | 0.059     | 0.296        | 0.170 |

|         |       |             |       |       |       |       |       |
|---------|-------|-------------|-------|-------|-------|-------|-------|
|         |       | Right Tilt  | 0.053 | 0.171 | 0.035 | 0.224 | 0.088 |
| LTE B71 | Ant.0 | Left Cheek  | 0.133 | 1.164 | 0.218 | 1.297 | 0.351 |
|         |       | Left Tilt   | 0.054 | 0.656 | 0.124 | 0.710 | 0.178 |
|         |       | Right Cheek | 0.079 | 0.185 | 0.059 | 0.264 | 0.138 |
|         |       | Right Tilt  | 0.013 | 0.171 | 0.035 | 0.184 | 0.048 |

Note:

- 1: The simultaneous transmission combinations of the antennas contain combinations of two antennas, so only the worst simultaneous transmission combinations was shown in this table.
- 2: The highest Summed 1g SAR is 1.483 W/Kg <1.6 W/kg, so Simultaneous Transmission SAR test is not required.

## 12.2.2 Body Simultaneous Transmission SAR Evaluation for WWAN Antenna with WIFI and Bluetooth

| Band     | Antenna | Position        | Stand alone SAR |          |           | SUM SAR      |       |
|----------|---------|-----------------|-----------------|----------|-----------|--------------|-------|
|          |         |                 | 1               | 2        | 3         | 1+2          | 1+3   |
|          |         |                 | WWAN            | 2.4GWIFI | Bluetooth |              |       |
| GSM 850  | Ant.0   | Front Side 15mm | 0.203           | 0.170    | 0.008     | 0.373        | 0.211 |
|          |         | Back Side 15mm  | 0.346           | 0.336    | 0.013     | 0.682        | 0.359 |
| GSM 1900 | Ant.0   | Front Side 15mm | 0.321           | 0.170    | 0.008     | 0.491        | 0.329 |
|          |         | Back Side 15mm  | 0.591           | 0.336    | 0.013     | <b>0.927</b> | 0.604 |
| WCDMA B2 | Ant.0   | Front Side 15mm | 0.285           | 0.170    | 0.008     | 0.455        | 0.293 |
|          |         | Back Side 15mm  | 0.440           | 0.336    | 0.013     | 0.776        | 0.453 |
| WCDMA B4 | Ant.0   | Front Side 15mm | 0.202           | 0.170    | 0.008     | 0.372        | 0.210 |
|          |         | Back Side 15mm  | 0.222           | 0.336    | 0.013     | 0.558        | 0.235 |
| WCDMA B5 | Ant.0   | Front Side 15mm | 0.086           | 0.170    | 0.008     | 0.256        | 0.094 |
|          |         | Back Side 15mm  | 0.145           | 0.336    | 0.013     | 0.481        | 0.158 |
| LTE B12  | Ant.0   | Front Side 15mm | 0.091           | 0.170    | 0.008     | 0.261        | 0.099 |
|          |         | Back Side 15mm  | 0.115           | 0.336    | 0.013     | 0.451        | 0.128 |
| LTE B25  | Ant.0   | Front Side 15mm | 0.190           | 0.170    | 0.008     | 0.360        | 0.198 |
|          |         | Back Side 15mm  | 0.271           | 0.336    | 0.013     | 0.607        | 0.284 |
| LTE B26  | Ant.0   | Front Side 15mm | 0.097           | 0.170    | 0.008     | 0.267        | 0.105 |
|          |         | Back Side 15mm  | 0.144           | 0.336    | 0.013     | 0.480        | 0.157 |
| LTE B66  | Ant.0   | Front Side 15mm | 0.145           | 0.170    | 0.008     | 0.315        | 0.153 |
|          |         | Back Side 15mm  | 0.134           | 0.336    | 0.013     | 0.470        | 0.147 |
| LTE B71  | Ant.0   | Front Side 15mm | 0.101           | 0.170    | 0.008     | 0.271        | 0.109 |
|          |         | Back Side 15mm  | 0.105           | 0.336    | 0.013     | 0.441        | 0.118 |

### Note:

1: The simultaneous transmission combinations of the antennas contain combinations of two antennas, so only the worst simultaneous transmission combinations was shown in this table.

2: The highest Combined 1g SAR is 0.927W/Kg < 1.6 W/kg, so Simultaneous Transmission SAR test is not required.

### 12.2.3 Hotspot Simultaneous Transmission SAR Evaluation for WWAN Antenna with WIFI and Bluetooth

| Band     | Antenna | Position         | Stand alone SAR |          |           | SUM SAR      |       |
|----------|---------|------------------|-----------------|----------|-----------|--------------|-------|
|          |         |                  | 1               | 2        | 3         | 1+2          | 1+3   |
|          |         |                  | WWAN            | 2.4GWIFI | Bluetooth |              |       |
| GSM 850  | Ant.0   | Front Side 10mm  | 0.241           | 0.235    | 0.022     | 0.476        | 0.263 |
|          |         | Back Side 10mm   | 0.350           | 0.362    | 0.035     | 0.712        | 0.385 |
|          |         | Left Edge 10mm   | 0.136           | 0.000    | 0.000     | 0.136        | 0.136 |
|          |         | Right Edge 10mm  | 0.123           | 0.347    | 0.016     | 0.470        | 0.139 |
|          |         | Top Edge 10mm    | 0.000           | 0.152    | 0.024     | 0.152        | 0.024 |
|          |         | Bottom Edge 10mm | 0.058           | 0.000    | 0.000     | 0.058        | 0.058 |
| GSM 1900 | Ant.0   | Front Side 10mm  | 0.681           | 0.235    | 0.022     | 0.916        | 0.703 |
|          |         | Back Side 10mm   | 1.185           | 0.362    | 0.035     | <b>1.547</b> | 1.220 |
|          |         | Left Edge 10mm   | 0.093           | 0.000    | 0.000     | 0.093        | 0.093 |
|          |         | Right Edge 10mm  | 0.160           | 0.347    | 0.016     | 0.507        | 0.176 |
|          |         | Top Edge 10mm    | 0.000           | 0.152    | 0.024     | 0.152        | 0.024 |
|          |         | Bottom Edge 10mm | 0.991           | 0.000    | 0.000     | 0.991        | 0.991 |
| WCDMA B2 | Ant.0   | Front Side 10mm  | 0.520           | 0.235    | 0.022     | 0.755        | 0.542 |
|          |         | Back Side 10mm   | 0.748           | 0.362    | 0.035     | 1.110        | 0.783 |
|          |         | Left Edge 10mm   | 0.136           | 0.000    | 0.000     | 0.136        | 0.136 |
|          |         | Right Edge 10mm  | 0.056           | 0.347    | 0.016     | 0.403        | 0.072 |
|          |         | Top Edge 10mm    | 0.000           | 0.152    | 0.024     | 0.152        | 0.024 |
|          |         | Bottom Edge 10mm | 0.900           | 0.000    | 0.000     | 0.900        | 0.900 |
| WCDMA B4 | Ant.0   | Front Side 10mm  | 0.310           | 0.235    | 0.022     | 0.545        | 0.332 |
|          |         | Back Side 10mm   | 0.324           | 0.362    | 0.035     | 0.686        | 0.359 |
|          |         | Left Edge 10mm   | 0.175           | 0.000    | 0.000     | 0.175        | 0.175 |
|          |         | Right Edge 10mm  | 0.072           | 0.347    | 0.016     | 0.419        | 0.088 |
|          |         | Top Edge 10mm    | 0.000           | 0.152    | 0.024     | 0.152        | 0.024 |
|          |         | Bottom Edge 10mm | 0.231           | 0.000    | 0.000     | 0.231        | 0.231 |
| WCDMA B5 | Ant.0   | Front Side 10mm  | 0.090           | 0.235    | 0.022     | 0.325        | 0.112 |
|          |         | Back Side 10mm   | 0.169           | 0.362    | 0.035     | 0.531        | 0.204 |
|          |         | Left Edge 10mm   | 0.056           | 0.000    | 0.000     | 0.056        | 0.056 |
|          |         | Right Edge 10mm  | 0.083           | 0.347    | 0.016     | 0.430        | 0.099 |
|          |         | Top Edge 10mm    | 0.000           | 0.152    | 0.024     | 0.152        | 0.024 |
|          |         | Bottom Edge 10mm | 0.013           | 0.000    | 0.000     | 0.013        | 0.013 |
| LTE B12  | Ant.0   | Front Side 10mm  | 0.094           | 0.235    | 0.022     | 0.329        | 0.116 |
|          |         | Back Side 10mm   | 0.128           | 0.362    | 0.035     | 0.490        | 0.163 |
|          |         | Left Edge 10mm   | 0.075           | 0.000    | 0.000     | 0.075        | 0.075 |
|          |         | Right Edge 10mm  | 0.087           | 0.347    | 0.016     | 0.434        | 0.103 |
|          |         | Top Edge 10mm    | 0.000           | 0.152    | 0.024     | 0.152        | 0.024 |
|          |         | Bottom Edge 10mm | 0.010           | 0.000    | 0.000     | 0.010        | 0.010 |

|         |       |                  |       |       |       |       |       |
|---------|-------|------------------|-------|-------|-------|-------|-------|
| LTE B25 | Ant.0 | Front Side 10mm  | 0.280 | 0.235 | 0.022 | 0.515 | 0.302 |
|         |       | Back Side 10mm   | 0.398 | 0.362 | 0.035 | 0.760 | 0.433 |
|         |       | Left Edge 10mm   | 0.076 | 0.000 | 0.000 | 0.076 | 0.076 |
|         |       | Right Edge 10mm  | 0.047 | 0.347 | 0.016 | 0.394 | 0.063 |
|         |       | Top Edge 10mm    | 0.000 | 0.152 | 0.024 | 0.152 | 0.024 |
|         |       | Bottom Edge 10mm | 0.428 | 0.000 | 0.000 | 0.428 | 0.428 |
| LTE B26 | Ant.0 | Front Side 10mm  | 0.096 | 0.235 | 0.022 | 0.331 | 0.118 |
|         |       | Back Side 10mm   | 0.151 | 0.362 | 0.035 | 0.513 | 0.186 |
|         |       | Left Edge 10mm   | 0.070 | 0.000 | 0.000 | 0.070 | 0.070 |
|         |       | Right Edge 10mm  | 0.105 | 0.347 | 0.016 | 0.452 | 0.121 |
|         |       | Top Edge 10mm    | 0.000 | 0.152 | 0.024 | 0.152 | 0.024 |
|         |       | Bottom Edge 10mm | 0.021 | 0.000 | 0.000 | 0.021 | 0.021 |
| LTE B66 | Ant.0 | Front Side 10mm  | 0.270 | 0.235 | 0.022 | 0.505 | 0.292 |
|         |       | Back Side 10mm   | 0.276 | 0.362 | 0.035 | 0.638 | 0.311 |
|         |       | Left Edge 10mm   | 0.138 | 0.000 | 0.000 | 0.138 | 0.138 |
|         |       | Right Edge 10mm  | 0.080 | 0.347 | 0.016 | 0.427 | 0.096 |
|         |       | Top Edge 10mm    | 0.000 | 0.152 | 0.024 | 0.152 | 0.024 |
|         |       | Bottom Edge 10mm | 0.230 | 0.000 | 0.000 | 0.230 | 0.230 |
| LTE B71 | Ant.0 | Front Side 10mm  | 0.083 | 0.235 | 0.022 | 0.318 | 0.105 |
|         |       | Back Side 10mm   | 0.101 | 0.362 | 0.035 | 0.463 | 0.136 |
|         |       | Left Edge 10mm   | 0.058 | 0.000 | 0.000 | 0.058 | 0.058 |
|         |       | Right Edge 10mm  | 0.104 | 0.347 | 0.016 | 0.451 | 0.120 |
|         |       | Top Edge 10mm    | 0.000 | 0.152 | 0.024 | 0.152 | 0.024 |
|         |       | Bottom Edge 10mm | 0.007 | 0.000 | 0.000 | 0.007 | 0.007 |

Note:

1: The simultaneous transmission combinations of the antennas contain combinations of two antennas, so only the worst simultaneous transmission combinations was shown in this table.

2: The highest Combined 1g SAR is 1.547 W/Kg < 1.6 W/kg, so Simultaneous Transmission SAR test is not required.

## 13 TEST EQUIPMENTS LIST

| Description                     | Manufacturer  | Model       | Serial No./Version | Cal. Date  | Cal. Due   |
|---------------------------------|---------------|-------------|--------------------|------------|------------|
| PC                              | Dell          | N/A         | N/A                | N/A        | N/A        |
| Test Software                   | Speag         | DASY8       | 16.2.2.1588        | N/A        | N/A        |
| 750MHz Validation Dipole        | Speag         | D750V3      | SN: 1208           | 2024/08/19 | 2027/08/18 |
| 835MHz Validation Dipole        | Speag         | D835V2      | SN: 4d187          | 2024/05/08 | 2027/05/07 |
| 1750MHz Validation Dipole       | Speag         | D1750V2     | SN: 1130           | 2024/05/08 | 2027/05/07 |
| 1950MHz Validation Dipole       | Speag         | D1950V3     | SN: 1240           | 2024/08/22 | 2027/08/21 |
| 2450MHz Validation Dipole       | Speag         | D2450V2     | SN: 952            | 2024/05/07 | 2027/05/06 |
| Data Acquisition Electronicsr   | Speag         | DAE4        | SN: 1710           | 2024/01/03 | 2025/01/02 |
| E-Field Probe                   | Speag         | EX3DV4      | SN: 7510           | 2024/06/25 | 2025/06/24 |
| Signal Generator                | R&S           | SMB100A     | 177746             | 2024/04/24 | 2025/04/23 |
| Power Meter                     | R&S           | NRVD-B2     | 835843/014         | 2024/08/08 | 2025/08/07 |
| Power Sensor                    | R&S           | NRV-Z4      | 100381             | 2024/08/08 | 2025/08/07 |
| Power Sensor                    | R&S           | NRV-Z2      | 100211             | 2024/08/08 | 2025/08/07 |
| Wireless Communication Test Set | Anritsu       | MT8820C     | 6201144551         | 2024/05/14 | 2025/05/13 |
| Network Analyzer                | Agilent       | E5071C      | MY46103472         | 2024/09/11 | 2025/09/10 |
| Thermometer                     | Elitech       | RC-4HC      | EF7216002985       | 2024/10/31 | 2025/10/30 |
| Thermometer                     | Elitech       | RC-4HC      | EF720B004811       | 2024/10/31 | 2025/10/30 |
| Power Amplifier                 | Mini-Circuits | ZVA-183W-S+ | 932502132          | N/A        | N/A        |
| Dielectric Probe Kit            | Speag         | DAK3.5      | SN: 1312           | N/A        | N/A        |
| Phantom                         | Speag         | SAM         | SN: 1859           | N/A        | N/A        |
| Attenuator                      | COM-MW        | ZA-S1-31    | 1305003187         | N/A        | N/A        |
| Directional coupler             | AA-MCS        | AAMCS-UDC   | 000272             | N/A        | N/A        |

Note: For dipole antennas, BALUN has adopted 3 years as calibration intervals, and on annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

1. There is no physical damage on the dipole;
2. System validation with specific dipole is within 10% of calibrated value;
3. Return-loss in within 20% of calibrated measurement.
4. Impedance (real or imaginary parts) in within 5 Ohms of calibrated measurement.

## ANNEX A SIMULATING LIQUID VERIFICATION RESULT

The dielectric parameters of the liquids were verified prior to the SAR evaluation using a DAK3.5 Dielectric Probe Kit.

Head Liquid

| Date       | Liquid Type | Fre. (MHz) | Temp. (°C) | Meas. Conductivity ( $\sigma$ ) (S/m) | Meas. Permittivity ( $\epsilon$ ) | Target Conductivity ( $\sigma$ ) (S/m) | Target Permittivity ( $\epsilon$ ) | Conductivity Tolerance (%) | Permittivity Tolerance (%) |
|------------|-------------|------------|------------|---------------------------------------|-----------------------------------|----------------------------------------|------------------------------------|----------------------------|----------------------------|
| 2024.12.6  | Head        | 750        | 21.3       | 0.91                                  | 41.75                             | 0.89                                   | 41.94                              | 2.25                       | -0.45                      |
| 2024.12.7  | Head        | 835        | 21.5       | 0.90                                  | 41.90                             | 0.90                                   | 41.50                              | 0.00                       | 0.96                       |
| 2024.12.9  | Head        | 1750       | 21.4       | 1.38                                  | 40.03                             | 1.37                                   | 40.08                              | 0.73                       | -0.12                      |
| 2024.12.10 | Head        | 1950       | 21.2       | 1.41                                  | 39.05                             | 1.40                                   | 40.00                              | 0.71                       | -2.38                      |
| 2024.12.11 | Head        | 1950       | 21.3       | 1.42                                  | 39.25                             | 1.40                                   | 40.00                              | 1.43                       | -1.88                      |
| 2024.12.12 | Head        | 2450       | 21.3       | 1.80                                  | 39.53                             | 1.80                                   | 39.20                              | 0.00                       | 0.84                       |

Note: The tolerance limit of Conductivity and Permittivity is  $\pm 5\%$ .

## ANNEX B SYSTEM CHECK RESULT

Comparing to the original SAR value provided by SPEAG, the validation data should be within its specification of 10 % (for 1 g).

Head liquid 1g

| Date       | Liquid Type | Freq. (MHz) | Power (mW) | Measured SAR (W/kg) | Normalized SAR (W/kg) | Dipole SAR (W/kg) | Tolerance (%) |
|------------|-------------|-------------|------------|---------------------|-----------------------|-------------------|---------------|
| 2024.12.6  | Head        | 750         | 100        | 0.83                | 8.34                  | 8.46              | -1.42         |
| 2024.12.7  | Head        | 835         | 100        | 0.98                | 9.83                  | 9.74              | 0.92          |
| 2024.12.9  | Head        | 1750        | 100        | 3.73                | 37.30                 | 37.00             | 0.81          |
| 2024.12.10 | Head        | 1950        | 100        | 4.18                | 41.80                 | 41.70             | 0.24          |
| 2024.12.11 | Head        | 1950        | 100        | 4.20                | 42.00                 | 41.70             | 0.72          |
| 2024.12.12 | Head        | 2450        | 100        | 5.34                | 53.40                 | 52.60             | 1.52          |

Note: The tolerance limit of System validation  $\pm 10\%$ .

System Performance Check Data (750MHz)

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band  | Group,<br>UID | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivit<br>y [S/m] | TSL<br>Permittivity | Ambient<br>Temperatur<br>e<br>[°C] | Liquid<br>Temperatur<br>e<br>[°C] |
|----------------------------|---------------------------------------|-------|---------------|------------------------------------------|----------------------|-------------------------------|---------------------|------------------------------------|-----------------------------------|
| Flat,<br>HSL               | FRONT,<br>5.00                        | CD750 | CW,<br>0--    | 750.0,<br>100                            | 10.29                | 0.91                          | 41.8                | 22.4                               | 21.3                              |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-06 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan    | Zoom Scan          |
|---------------------|--------------|--------------------|
| Grid Extents [mm]   | 80.0 x 160.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0  | 8.0 x 8.0 x 5      |
| Sensor Surface [mm] | 3.0          | 1.4                |
| Graded Grid         | Yes          | Yes                |
| Grading Ratio       | 1.5          | 1.5                |
| MAIA                | N/A          | N/A                |
| Surface Detection   | VMS + 6p     | VMS + 6p           |
| Scan Method         | Measured     | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-06    | 2024-12-06    |
| psSAR1g [W/kg]      | 0.840         | 0.834         |
| psSAR10g [W/kg]     | 0.562         | 0.549         |
| Power Drift [dB]    | -0.06         | -0.01         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 86.0          |
| Dist 3dB Peak [mm]  |               | 20.4          |



System Performance Check Data (835MHz)

Exposure Conditions

| Phantom  | Position, | Band  | Group, | Frequency | Conversion | TSL         | TSL          | Ambient    | Liquid     |
|----------|-----------|-------|--------|-----------|------------|-------------|--------------|------------|------------|
| Section, | Test      |       | UID    | [MHz],    | Factor     | Conductivit | Permittivity | Temperatur | Temperatur |
| TSL      | Distance  |       |        | Channel   |            | y [S/m]     |              | e          | e          |
|          | [mm]      |       |        | Number    |            |             |              | [°C]       | [°C]       |
| Flat,    | FRONT,    | CD835 | CW,    | 835.0,    | 9.99       | 0.90        | 41.9         | 22.3       | 21.5       |
| HSL      | 5.00      |       | 0--    | 50        |            |             |              |            |            |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-07 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 180.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5      |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | N/A           | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-07    | 2024-12-07    |
| psSAR1g [W/kg]      | 0.992         | 0.983         |
| psSAR10g [W/kg]     | 0.631         | 0.603         |
| Power Drift [dB]    | -0.00         | 0.00          |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 84.8          |
| Dist 3dB Peak [mm]  |               | 13.2          |



System Performance Check Data (1750MHz)

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band  | Group,<br>UID | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivit<br>y [S/m] | TSL<br>Permittivity | Ambient<br>Temperatur<br>e<br>[°C] | Liquid<br>Temperatur<br>e<br>[°C] |
|----------------------------|---------------------------------------|-------|---------------|------------------------------------------|----------------------|-------------------------------|---------------------|------------------------------------|-----------------------------------|
| Flat,<br>HSL               | FRONT,<br>5.00                        | D1750 | CW,<br>0--    | 1750.0,<br>50                            | 8.67                 | 1.38                          | 40.0                | 22.8                               | 21.4                              |

Hardware Setup


| Phantom                                    | TSL, Measured Date |            | Probe, Calibration Date |            | DAE, Calibration Date |            |
|--------------------------------------------|--------------------|------------|-------------------------|------------|-----------------------|------------|
| Twin-SAM V5.0 (30deg probe<br>tilt) - 1859 | HBBL-600-10000     | 2024-12-09 | EX3DV4 - SN7510,        | 2024-06-25 | DAE4 Sn1710,          | 2024-01-03 |

Scan Setup

|                        | Area Scan   | Zoom Scan          |
|------------------------|-------------|--------------------|
| Grid Extents [mm]      | 80.0 x 80.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]        | 15.0 x 15.0 | 8.0 x 8.0 x 5      |
| Sensor Surface<br>[mm] | 3.0         | 1.4                |
| Graded Grid            | Yes         | Yes                |
| Grading Ratio          | 1.5         | 1.5                |
| MAIA                   | N/A         | N/A                |
| Surface Detection      | VMS + 6p    | VMS + 6p           |
| Scan Method            | Measured    | Measured           |

Measurement Results

|                        | Area Scan     | Zoom Scan     |
|------------------------|---------------|---------------|
| Date                   | 2024-12-09    | 2024-12-09    |
| psSAR1g [W/kg]         | 3.77          | 3.73          |
| psSAR10g<br>[W/kg]     | 2.05          | 1.98          |
| Power Drift [dB]       | -0.06         | -0.01         |
| Power Scaling          | Disabled      | Disabled      |
| Scaling Factor<br>[dB] |               |               |
| TSL Correction         | No correction | No correction |
| M2/M1 [%]              |               | 81.9          |
| Dist 3dB Peak<br>[mm]  |               | 10.7          |



System Performance Check Data (1950MHz)

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band  | Group,<br>UID | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity<br>[S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|-------|---------------|------------------------------------------|----------------------|------------------------------|---------------------|--------------------------------|-------------------------------|
| Flat,<br>HSL               | FRONT,<br>5.00                        | D1950 | CW,<br>0--    | 1950.0,<br>50                            | 8.33                 | 1.41                         | 39.1                | 22.5                           | 21.2                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-10 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 150.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5      |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | N/A           | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-10    | 2024-12-10    |
| psSAR1g [W/kg]      | 4.21          | 4.18          |
| psSAR10g [W/kg]     | 2.24          | 2.15          |
| Power Drift [dB]    | -0.16         | -0.03         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 81.6          |
| Dist 3dB Peak [mm]  |               | 9.6           |



# System Performance Check Data (1950MHz)

## Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band  | Group,<br>UID | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivit<br>y [S/m] | TSL<br>Permittivity | Ambient<br>Temperatur<br>e<br>[°C] | Liquid<br>Temperatur<br>e<br>[°C] |
|----------------------------|---------------------------------------|-------|---------------|------------------------------------------|----------------------|-------------------------------|---------------------|------------------------------------|-----------------------------------|
| Flat,<br>HSL               | FRONT,<br>5.00                        | D1950 | CW,<br>0--    | 1950.0,<br>50                            | 8.33                 | 1.42                          | 39.2                | 22.6                               | 21.3                              |

## Hardware Setup


| Phantom                                    | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|--------------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe<br>tilt) - 1859 | HBBL-600-10000 2024-12-11 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

## Scan Setup

|                        | Area Scan   | Zoom Scan          |
|------------------------|-------------|--------------------|
| Grid Extents [mm]      | 80.0 x 80.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]        | 15.0 x 15.0 | 8.0 x 8.0 x 5      |
| Sensor Surface<br>[mm] | 3.0         | 1.4                |
| Graded Grid            | Yes         | Yes                |
| Grading Ratio          | 1.5         | 1.5                |
| MAIA                   | N/A         | N/A                |
| Surface Detection      | VMS + 6p    | VMS + 6p           |
| Scan Method            | Measured    | Measured           |

## Measurement Results

|                       | Area Scan     | Zoom Scan     |
|-----------------------|---------------|---------------|
| Date                  | 2024-12-11    | 2024-12-11    |
| psSAR1g [W/kg]        | 4.44          | 4.20          |
| psSAR10g<br>[W/kg]    | 2.36          | 2.16          |
| Power Drift [dB]      | -0.34         | -0.03         |
| Power Scaling         | Disabled      | Disabled      |
| Scaling Factor        |               |               |
| [dB]                  |               |               |
| TSL Correction        | No correction | No correction |
| M2/M1 [%]             |               | 81.1          |
| Dist 3dB Peak<br>[mm] |               | 9.6           |



System Performance Check Data (2450MHz)

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band  | Group,<br>UID | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivit<br>y [S/m] | TSL<br>Permittivity | Ambient<br>Temperatur<br>e<br>[°C] | Liquid<br>Temperatur<br>e<br>[°C] |
|----------------------------|---------------------------------------|-------|---------------|------------------------------------------|----------------------|-------------------------------|---------------------|------------------------------------|-----------------------------------|
| Flat,<br>HSL               | FRONT,<br>5.00                        | D2450 | CW,<br>0--    | 2450.0,<br>50                            | 7.75                 | 1.80                          | 39.5                | 22.7                               | 21.3                              |

Hardware Setup


| Phantom                                 | TSL, Measured Date |            | Probe, Calibration Date |            | DAE, Calibration Date |            |
|-----------------------------------------|--------------------|------------|-------------------------|------------|-----------------------|------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000     | 2024-12-12 | EX3DV4 - SN7510,        | 2024-06-25 | DAE4 Sn1710,          | 2024-01-03 |

Scan Setup

|                     | Area Scan   | Zoom Scan          |
|---------------------|-------------|--------------------|
| Grid Extents [mm]   | 80.0 x 80.0 | 30.0 x 30.0 x 30.0 |
| Grid Steps [mm]     | 12.0 x 12.0 | 5.0 x 5.0 x 5.0    |
| Sensor Surface [mm] | 3.0         | 1.4                |
| Graded Grid         | Yes         | Yes                |
| Grading Ratio       | 1.5         | 1.5                |
| MAIA                | N/A         | N/A                |
| Surface Detection   | VMS + 6p    | VMS + 6p           |
| Scan Method         | Measured    | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-12    | 2024-12-12    |
| psSAR1g [W/kg]      | 5.33          | 5.34          |
| psSAR10g [W/kg]     | 2.49          | 2.49          |
| Power Drift [dB]    | -0.02         | 0.00          |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 80.8          |
| Dist 3dB Peak [mm]  |               | 8.9           |



ANNEX C TEST DATA

Meas.1 Head Right Cheek GSM 850 Ch251

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band       | Group,<br>UID     | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity<br>[S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|------------|-------------------|------------------------------------------|----------------------|------------------------------|---------------------|--------------------------------|-------------------------------|
| Right Head,<br>HSL         | CHEEK,<br>0.00                        | GSM<br>850 | GSM,<br>10021-DAC | 848.8,<br>251                            | 9.99                 | 0.91                         | 41.5                | 22.3                           | 21.5                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-07 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 180.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5      |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | N/A           | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-07    | 2024-12-07    |
| psSAR1g [W/kg]      | 0.251         | 0.269         |
| psSAR10g [W/kg]     | 0.173         | 0.204         |
| Power Drift [dB]    | -0.09         | -0.00         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 92.8          |
| Dist 3dB Peak [mm]  |               | > 15.0        |



Meas.2 Body Back Side 15mm GSM850 CH251

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band       | Group,<br>UID     | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity [S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|------------|-------------------|------------------------------------------|----------------------|---------------------------|---------------------|--------------------------------|-------------------------------|
| Flat,<br>HSL               | BACK,<br>15.00                        | GSM<br>850 | GSM,<br>10021-DAC | 848.8,<br>251                            | 9.99                 | 0.91                      | 41.5                | 22.3                           | 21.5                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-07 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 180.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5      |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | N/A           | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-07    | 2024-12-07    |
| psSAR1g [W/kg]      | 0.250         | 0.264         |
| psSAR10g [W/kg]     | 0.175         | 0.200         |
| Power Drift [dB]    | 0.03          | -0.01         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 87.9          |
| Dist 3dB Peak [mm]  |               | > 15.0        |



Meas.3 Hotspot Back Side 10mm GSM850 CH251

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band       | Group,<br>UID     | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity<br>[S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|------------|-------------------|------------------------------------------|----------------------|------------------------------|---------------------|--------------------------------|-------------------------------|
| Flat,<br>HSL               | BACK,<br>10.00                        | GSM<br>850 | GSM,<br>10021-DAC | 848.8,<br>251                            | 9.99                 | 0.91                         | 41.5                | 22.3                           | 21.5                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-07 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 180.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5      |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | N/A           | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-07    | 2024-12-07    |
| psSAR1g [W/kg]      | 0.253         | 0.267         |
| psSAR10g [W/kg]     | 0.178         | 0.203         |
| Power Drift [dB]    | 0.06          | 0.00          |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 86.9          |
| Dist 3dB Peak [mm]  |               | > 15.0        |



Meas.4 Head Left Cheek GSM 1900 Ch661

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band        | Group,<br>UID     | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity<br>[S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|-------------|-------------------|------------------------------------------|----------------------|------------------------------|---------------------|--------------------------------|-------------------------------|
| Left Head,<br>HSL          | CHEEK,<br>0.00                        | PCS<br>1900 | GSM,<br>10021-DAC | 1880.0,<br>661                           | 8.33                 | 1.38                         | 40.0                | 22.5                           | 21.2                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-10 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 150.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | Y             | Y                  |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-10    | 2024-12-10    |
| psSAR1g [W/kg]      | 0.128         | 0.127         |
| psSAR10g [W/kg]     | 0.076         | 0.082         |
| Power Drift [dB]    | -0.11         | -0.20         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 66.7          |
| Dist 3dB Peak [mm]  |               | 15.6          |



Meas.5 Body Back Side 15mm GSM1900 CH661

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band        | Group,<br>UID     | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity<br>[S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|-------------|-------------------|------------------------------------------|----------------------|------------------------------|---------------------|--------------------------------|-------------------------------|
| Flat,<br>HSL               | BACK,<br>15.00                        | PCS<br>1900 | GSM,<br>10021-DAC | 1880.0,<br>661                           | 8.33                 | 1.38                         | 40.0                | 22.5                           | 21.2                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-10 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 150.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5      |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | N/A           | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-10    | 2024-12-10    |
| psSAR1g [W/kg]      | 0.448         | 0.457         |
| psSAR10g [W/kg]     | 0.246         | 0.252         |
| Power Drift [dB]    | 0.11          | -0.03         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 84.5          |
| Dist 3dB Peak [mm]  |               | 11.8          |



Meas.6 Hotspot Back Side 10mm GSM1900 CH661.

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band        | Group,<br>UID     | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity<br>[S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|-------------|-------------------|------------------------------------------|----------------------|------------------------------|---------------------|--------------------------------|-------------------------------|
| Flat,<br>HSL               | BACK,<br>10.00                        | PCS<br>1900 | GSM,<br>10021-DAC | 1880.0,<br>661                           | 8.33                 | 1.38                         | 40.0                | 22.5                           | 21.2                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-10 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 150.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5      |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | N/A           | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-10    | 2024-12-10    |
| psSAR1g [W/kg]      | 0.725         | 0.916         |
| psSAR10g [W/kg]     | 0.407         | 0.445         |
| Power Drift [dB]    | 0.16          | 0.05          |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 51.8          |
| Dist 3dB Peak [mm]  |               | 8.6           |



**Meas.7 Head Left Cheek WCDMA B2 Ch9400**

**Exposure Conditions**

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                    | Group,<br>UID       | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity [S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|-------------------------|---------------------|------------------------------------------|----------------------|---------------------------|---------------------|--------------------------------|-------------------------------|
| Left Head,<br>HSL          | CHEEK,<br>0.00                        | Band 2,<br>UTRA/FD<br>D | WCDMA,<br>10274-CAB | 1880.0,<br>9400                          | 8.33                 | 1.38                      | 40.0                | 22.5                           | 21.2                          |

**Hardware Setup**


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-10 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

**Scan Setup**

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 150.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | Y             | Y                  |
| Surface Detection   | All points    | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

**Measurement Results**

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-10    | 2024-12-10    |
| psSAR1g [W/kg]      | 0.078         | 0.077         |
| psSAR10g [W/kg]     | 0.047         | 0.051         |
| Power Drift [dB]    | 0.13          | -0.03         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 68.9          |
| Dist 3dB Peak [mm]  |               | 18.2          |



**Meas.8 Body Back Side 15mm WCDMA B2 CH9400**

**Exposure Conditions**

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                    | Group,<br>UID       | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity<br>[S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|-------------------------|---------------------|------------------------------------------|----------------------|------------------------------|---------------------|--------------------------------|-------------------------------|
| Flat,<br>HSL               | BACK,<br>15.00                        | Band 2,<br>UTRA/F<br>DD | WCDMA,<br>10274-CAB | 1880.0,<br>9400                          | 8.33                 | 1.38                         | 40.0                | 22.5                           | 21.2                          |

**Hardware Setup**


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-10 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

**Scan Setup**

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 150.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | N/A           | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

**Measurement Results**

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-10    | 2024-12-10    |
| psSAR1g [W/kg]      | 0.337         | 0.349         |
| psSAR10g [W/kg]     | 0.182         | 0.192         |
| Power Drift [dB]    | -0.13         | -0.19         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 83.6          |
| Dist 3dB Peak [mm]  |               | 11.8          |



Meas.9 Hotspot Bottom Side 10mm WCDMA B2 CH9400.

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                    | Group,<br>UID       | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity [S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|-------------------------|---------------------|------------------------------------------|----------------------|---------------------------|---------------------|--------------------------------|-------------------------------|
| Flat,<br>HSL               | EDGE<br>BOTTOM,<br>10.00              | Band 2,<br>UTRA/FD<br>D | WCDMA,<br>10274-CAB | 1880.0,<br>9400                          | 8.33                 | 1.38                      | 40.0                | 22.5                           | 21.2                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-10 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan    | Zoom Scan          |
|---------------------|--------------|--------------------|
| Grid Extents [mm]   | 44.0 x 120.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0  | 8.0 x 8.0 x 5.0    |
| Sensor Surface [mm] | 3.0          | 1.4                |
| Graded Grid         | Yes          | Yes                |
| Grading Ratio       | 1.5          | 1.5                |
| MAIA                | N/A          | N/A                |
| Surface Detection   | VMS + 6p     | VMS + 6p           |
| Scan Method         | Measured     | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-10    | 2024-12-10    |
| psSAR1g [W/kg]      | 0.688         | 0.713         |
| psSAR10g [W/kg]     | 0.345         | 0.354         |
| Power Drift [dB]    | 0.10          | 0.03          |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 53.9          |
| Dist 3dB Peak [mm]  |               | 8.6           |



Meas.10 Head Left Cheek WCDMA B4 Ch1312

Exposure Conditions

| Phantom           | Position,<br>Test | Band                | Group,<br>UID       | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity<br>[S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|-------------------|-------------------|---------------------|---------------------|------------------------------------------|----------------------|------------------------------|---------------------|--------------------------------|-------------------------------|
| Left Head,<br>HSL | CHEEK,<br>0.00    | Band 4,<br>UTRA/FDD | WCDMA,<br>10274-CAB | 1712.4,<br>1312                          | 8.67                 | 1.34                         | 40.6                | 22.8                           | 21.4                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-09 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 150.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | Y             | Y                  |
| Surface Detection   | All points    | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-09    | 2024-12-09    |
| psSAR1g [W/kg]      | 0.111         | 0.113         |
| psSAR10g [W/kg]     | 0.068         | 0.076         |
| Power Drift [dB]    | 0.09          | 0.18          |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 70.2          |
| Dist 3dB Peak [mm]  |               | 19.5          |



**Meas.11 Body Back Side 15mm WCDMA B4 CH1312**

**Exposure Conditions**

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                    | Group,<br>UID       | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity<br>[S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|-------------------------|---------------------|------------------------------------------|----------------------|------------------------------|---------------------|--------------------------------|-------------------------------|
| Flat,<br>HSL               | BACK,<br>15.00                        | Band 4,<br>UTRA/F<br>DD | WCDMA,<br>10274-CAB | 1712.4,<br>1312                          | 8.67                 | 1.34                         | 40.6                | 22.8                           | 21.4                          |

**Hardware Setup**


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-09 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

**Scan Setup**

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 180.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | Y             | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

**Measurement Results**

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-09    | 2024-12-09    |
| psSAR1g [W/kg]      | 0.185         | 0.190         |
| psSAR10g [W/kg]     | 0.118         | 0.123         |
| Power Drift [dB]    | 0.05          | -0.08         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 82.2          |
| Dist 3dB Peak [mm]  |               | > 15.0        |



**Meas.12 Hotspot Back Side 10mm WCDMA B4 CH1312**

**Exposure Conditions**

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                    | Group,<br>UID       | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity<br>[S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|-------------------------|---------------------|------------------------------------------|----------------------|------------------------------|---------------------|--------------------------------|-------------------------------|
| Flat,<br>HSL               | BACK,<br>10.00                        | Band 4,<br>UTRA/F<br>DD | WCDMA,<br>10274-CAB | 1712.4,<br>1312                          | 8.67                 | 1.34                         | 40.6                | 22.8                           | 21.4                          |

**Hardware Setup**


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-09 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

**Scan Setup**

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 180.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | N/A           | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

**Measurement Results**

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-09    | 2024-12-09    |
| psSAR1g [W/kg]      | 0.271         | 0.278         |
| psSAR10g [W/kg]     | 0.166         | 0.169         |
| Power Drift [dB]    | 0.13          | 0.06          |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 57.7          |
| Dist 3dB Peak [mm]  |               | 19.3          |



Meas.13 Head Right Cheek WCDMA B5 Ch4182

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                | Group,<br>UID       | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity<br>[S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|---------------------|---------------------|------------------------------------------|----------------------|------------------------------|---------------------|--------------------------------|-------------------------------|
| Right Head,<br>HSL         | CHEEK,<br>0.00                        | Band 5,<br>UTRA/FDD | WCDMA,<br>10274-CAB | 836.4,<br>4182                           | 9.99                 | 0.90                         | 41.9                | 22.3                           | 21.5                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-07 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 180.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | N/A           | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-07    | 2024-12-07    |
| psSAR1g [W/kg]      | 0.095         | 0.099         |
| psSAR10g [W/kg]     | 0.065         | 0.077         |
| Power Drift [dB]    | -0.14         | -0.11         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 81.6          |
| Dist 3dB Peak [mm]  |               | > 16.0        |



Meas.14 Body Back Side 15mm WCDMA B5 CH4182

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                    | Group,<br>UID       | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity [S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|-------------------------|---------------------|------------------------------------------|----------------------|---------------------------|---------------------|--------------------------------|-------------------------------|
| Flat,<br>HSL               | BACK,<br>15.00                        | Band 5,<br>UTRA/FD<br>D | WCDMA,<br>10274-CAB | 836.4,<br>4182                           | 9.99                 | 0.90                      | 41.9                | 22.3                           | 21.5                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-07 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 180.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | Y             | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-07    | 2024-12-07    |
| psSAR1g [W/kg]      | 0.117         | 0.124         |
| psSAR10g [W/kg]     | 0.082         | 0.095         |
| Power Drift [dB]    | 0.01          | 0.03          |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 89.2          |
| Dist 3dB Peak [mm]  |               | > 15.0        |



Meas.15 Hotspot Back Side 10mm WCDMA B5 CH4182

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                    | Group,<br>UID       | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity [S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|-------------------------|---------------------|------------------------------------------|----------------------|---------------------------|---------------------|--------------------------------|-------------------------------|
| Flat,<br>HSL               | BACK,<br>10.00                        | Band 5,<br>UTRA/FD<br>D | WCDMA,<br>10274-CAB | 836.4,<br>4182                           | 9.99                 | 0.90                      | 41.9                | 22.3                           | 21.5                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-07 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 180.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | N/A           | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-07    | 2024-12-07    |
| psSAR1g [W/kg]      | 0.137         | 0.144         |
| psSAR10g [W/kg]     | 0.097         | 0.110         |
| Power Drift [dB]    | 0.05          | -0.02         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 77.9          |
| Dist 3dB Peak [mm]  |               | > 16.0        |



Meas.16 Head Left Cheek LTE B12 Ch23095

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                           | Group,<br>UID         | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity<br>[S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|--------------------------------|-----------------------|------------------------------------------|----------------------|------------------------------|---------------------|--------------------------------|-------------------------------|
| Left Head,<br>HSL          | CHEEK,<br>0.00                        | Band 12,<br>E-<br>UTRA/F<br>DD | LTE-FDD,<br>10175-CAG | 707.5,<br>23095                          | 10.29                | 0.89                         | 42.3                | 22.4                           | 21.3                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-06 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 150.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | Y             | Y                  |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-06    | 2024-12-06    |
| psSAR1g [W/kg]      | 0.063         | 0.066         |
| psSAR10g [W/kg]     | 0.044         | 0.053         |
| Power Drift [dB]    | 0.13          | 0.09          |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 86.5          |
| Dist 3dB Peak [mm]  |               | > 16.0        |



Meas.17 Body Back Side 15mm LTE B12 CH23095

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                           | Group,<br>UID         | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity<br>[S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|--------------------------------|-----------------------|------------------------------------------|----------------------|------------------------------|---------------------|--------------------------------|-------------------------------|
| Flat,<br>HSL               | BACK,<br>15.00                        | Band 12,<br>E-<br>UTRA/F<br>DD | LTE-FDD,<br>10175-CAG | 707.5,<br>23095                          | 10.29                | 0.89                         | 42.3                | 22.4                           | 21.3                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-06 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 180.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | Y             | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-06    | 2024-12-06    |
| psSAR1g [W/kg]      | 0.091         | 0.096         |
| psSAR10g [W/kg]     | 0.065         | 0.074         |
| Power Drift [dB]    | 0.04          | 0.00          |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 88.7          |
| Dist 3dB Peak [mm]  |               | > 15.0        |



Meas.18 Hotspot Back Side 10mm LTE B12 CH23095.

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                           | Group,<br>UID         | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity<br>[S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|--------------------------------|-----------------------|------------------------------------------|----------------------|------------------------------|---------------------|--------------------------------|-------------------------------|
| Flat,<br>HSL               | BACK,<br>10.00                        | Band 12,<br>E-<br>UTRA/F<br>DD | LTE-FDD,<br>10175-CAG | 707.5,<br>23095                          | 10.29                | 0.89                         | 42.3                | 22.4                           | 21.3                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-06 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 180.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | Y             | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-06    | 2024-12-06    |
| psSAR1g [W/kg]      | 0.101         | 0.107         |
| psSAR10g [W/kg]     | 0.072         | 0.082         |
| Power Drift [dB]    | 0.07          | 0.01          |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 77.0          |
| Dist 3dB Peak [mm]  |               | > 16.0        |



Meas.19 Head Left Cheek LTE B25 Ch26365

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                           | Group,<br>UID         | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivit<br>y [S/m] | TSL<br>Permittivity | Ambient<br>Temperatur<br>e<br>[°C] | Liquid<br>Temperatur<br>e<br>[°C] |
|----------------------------|---------------------------------------|--------------------------------|-----------------------|------------------------------------------|----------------------|-------------------------------|---------------------|------------------------------------|-----------------------------------|
| Left Head,<br>HSL          | CHEEK,<br>0.00                        | Band 25,<br>E-<br>UTRA/F<br>DD | LTE-FDD,<br>10169-CAE | 1882.5,<br>26365                         | 8.33                 | 1.40                          | 39.5                | 22.6                               | 21.3                              |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-11 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 150.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | Y             | Y                  |
| Surface Detection   | VMS + 6p      | All points         |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-11    | 2024-12-11    |
| psSAR1g [W/kg]      | 0.076         | 0.077         |
| psSAR10g [W/kg]     | 0.045         | 0.049         |
| Power Drift [dB]    | -0.11         | -0.04         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 64.3          |
| Dist 3dB Peak [mm]  |               | 15.7          |



Meas.20 Body Back Side 15mm LTE B25 CH26365

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                           | Group,<br>UID         | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivit<br>y [S/m] | TSL<br>Permittivity | Ambient<br>Temperatur<br>e<br>[°C] | Liquid<br>Temperatur<br>e<br>[°C] |
|----------------------------|---------------------------------------|--------------------------------|-----------------------|------------------------------------------|----------------------|-------------------------------|---------------------|------------------------------------|-----------------------------------|
| Flat,<br>HSL               | BACK,<br>15.00                        | Band 25,<br>E-<br>UTRA/F<br>DD | LTE-FDD,<br>10169-CAE | 1882.5,<br>26365                         | 8.33                 | 1.40                          | 39.5                | 22.6                               | 21.3                              |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-11 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 180.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | N/A           | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-11    | 2024-12-11    |
| psSAR1g [W/kg]      | 0.222         | 0.225         |
| psSAR10g [W/kg]     | 0.122         | 0.125         |
| Power Drift [dB]    | 0.12          | -0.10         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 85.7          |
| Dist 3dB Peak [mm]  |               | 12.4          |



Meas.21 Hotspot Bottom Side 10mm LTE B25 Ch26365

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                           | Group,<br>UID         | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity<br>[S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|--------------------------------|-----------------------|------------------------------------------|----------------------|------------------------------|---------------------|--------------------------------|-------------------------------|
| Flat,<br>HSL               | EDGE<br>BOTTOM,<br>10.00              | Band 25,<br>E-<br>UTRA/F<br>DD | LTE-FDD,<br>10169-CAE | 1882.5,<br>26365                         | 8.33                 | 1.40                         | 39.5                | 22.6                           | 21.3                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-11 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan    | Zoom Scan          |
|---------------------|--------------|--------------------|
| Grid Extents [mm]   | 44.0 x 120.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0  | 8.0 x 8.0 x 5.0    |
| Sensor Surface [mm] | 3.0          | 1.4                |
| Graded Grid         | Yes          | Yes                |
| Grading Ratio       | 1.5          | 1.5                |
| MAIA                | N/A          | N/A                |
| Surface Detection   | VMS + 6p     | VMS + 6p           |
| Scan Method         | Measured     | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-11    | 2024-12-11    |
| psSAR1g [W/kg]      | 0.316         | 0.355         |
| psSAR10g [W/kg]     | 0.172         | 0.181         |
| Power Drift [dB]    | 0.11          | 0.08          |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 54.7          |
| Dist 3dB Peak [mm]  |               | 9.6           |



Meas.22 Head Left Cheek LTE B26 Ch26865

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                          | Group,<br>UID         | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivit<br>y [S/m] | TSL<br>Permittivity | Ambient<br>Temperatur<br>e<br>[°C] | Liquid<br>Temperatur<br>e<br>[°C] |
|----------------------------|---------------------------------------|-------------------------------|-----------------------|------------------------------------------|----------------------|-------------------------------|---------------------|------------------------------------|-----------------------------------|
| Left Head,<br>HSL          | CHEEK,<br>0.00                        | Band 26<br>E-<br>UTRA/F<br>DD | LTE-FDD,<br>10181-CAE | 831.5,<br>26865                          | 9.99                 | 0.89                          | 42.0                | 22.3                               | 21.5                              |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-07 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 150.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | N/A           | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-07    | 2024-12-07    |
| psSAR1g [W/kg]      | 0.090         | 0.094         |
| psSAR10g [W/kg]     | 0.062         | 0.074         |
| Power Drift [dB]    | -0.18         | 0.17          |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 85.0          |
| Dist 3dB Peak [mm]  |               | > 16.0        |



Meas.23 Body Back Side 15mm LTE B26 Ch26865

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                          | Group,<br>UID         | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivit<br>y [S/m] | TSL<br>Permittivity | Ambient<br>Temperatur<br>e<br>[°C] | Liquid<br>Temperatur<br>e<br>[°C] |
|----------------------------|---------------------------------------|-------------------------------|-----------------------|------------------------------------------|----------------------|-------------------------------|---------------------|------------------------------------|-----------------------------------|
| Flat,<br>HSL               | BACK,<br>15.00                        | Band 26<br>E-<br>UTRA/F<br>DD | LTE-FDD,<br>10181-CAE | 831.5,<br>26865                          | 9.99                 | 0.89                          | 42.0                | 22.3                               | 21.5                              |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-07 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 180.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | Y             | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-07    | 2024-12-07    |
| psSAR1g [W/kg]      | 0.116         | 0.123         |
| psSAR10g [W/kg]     | 0.082         | 0.093         |
| Power Drift [dB]    | 0.02          | -0.04         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 90.1          |
| Dist 3dB Peak [mm]  |               | > 15.0        |



Meas.24 Hotspot Back Side 10mm LTE B26 Ch26865

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                          | Group,<br>UID         | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivit<br>y [S/m] | TSL<br>Permittivity | Ambient<br>Temperatur<br>e<br>[°C] | Liquid<br>Temperatur<br>e<br>[°C] |
|----------------------------|---------------------------------------|-------------------------------|-----------------------|------------------------------------------|----------------------|-------------------------------|---------------------|------------------------------------|-----------------------------------|
| Flat,<br>HSL               | BACK,<br>10.00                        | Band 26<br>E-<br>UTRA/F<br>DD | LTE-FDD,<br>10181-CAE | 831.5,<br>26865                          | 9.99                 | 0.89                          | 42.0                | 22.3                               | 21.5                              |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-07 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 180.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | N/A           | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-07    | 2024-12-07    |
| psSAR1g [W/kg]      | 0.122         | 0.129         |
| psSAR10g [W/kg]     | 0.086         | 0.099         |
| Power Drift [dB]    | 0.08          | -0.04         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 77.5          |
| Dist 3dB Peak [mm]  |               | > 16.0        |



Meas.25 Head Left Cheek LTE B66 Ch132322

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                           | Group,<br>UID         | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivit<br>y [S/m] | TSL<br>Permittivity | Ambient<br>Temperatur<br>e<br>[°C] | Liquid<br>Temperatur<br>e<br>[°C] |
|----------------------------|---------------------------------------|--------------------------------|-----------------------|------------------------------------------|----------------------|-------------------------------|---------------------|------------------------------------|-----------------------------------|
| Left Head,<br>HSL          | CHEEK,<br>0.00                        | Band 66,<br>E-<br>UTRA/F<br>DD | LTE-FDD,<br>10169-CAE | 1745.0,<br>132322                        | 8.67                 | 1.37                          | 40.1                | 22.8                               | 21.4                              |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-09 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 150.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5      |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | Y             | Y                  |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-09    | 2024-12-09    |
| psSAR1g [W/kg]      | 0.109         | 0.115         |
| psSAR10g [W/kg]     | 0.068         | 0.076         |
| Power Drift [dB]    | -0.05         | -0.06         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 88.8          |
| Dist 3dB Peak [mm]  |               | 16.3          |



Meas.26 Body Front Side 15mm LTE B66 Ch132322

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                           | Group,<br>UID         | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivit<br>y [S/m] | TSL<br>Permittivity | Ambient<br>Temperatur<br>e<br>[°C] | Liquid<br>Temperatur<br>e<br>[°C] |
|----------------------------|---------------------------------------|--------------------------------|-----------------------|------------------------------------------|----------------------|-------------------------------|---------------------|------------------------------------|-----------------------------------|
| Flat,<br>HSL               | FRONT,<br>15.00                       | Band 66,<br>E-<br>UTRA/F<br>DD | LTE-FDD,<br>10169-CAE | 1745.0,<br>132322                        | 8.67                 | 1.37                          | 40.1                | 22.8                               | 21.4                              |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-09 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 180.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5      |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | Y             | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-09    | 2024-12-09    |
| psSAR1g [W/kg]      | 0.121         | 0.123         |
| psSAR10g [W/kg]     | 0.077         | 0.082         |
| Power Drift [dB]    | 0.15          | -0.20         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 82.7          |
| Dist 3dB Peak [mm]  |               | > 15.0        |



Meas.27 Hotspot Back Side 10mm LTE B66 Ch132322

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                           | Group,<br>UID         | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity [S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|--------------------------------|-----------------------|------------------------------------------|----------------------|---------------------------|---------------------|--------------------------------|-------------------------------|
| Flat,<br>HSL               | BACK,<br>10.00                        | Band 66,<br>E-<br>UTRA/F<br>DD | LTE-FDD,<br>10169-CAE | 1745.0,<br>132322                        | 8.67                 | 1.37                      | 40.1                | 22.8                           | 21.4                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-09 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 180.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5      |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | N/A           | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-09    | 2024-12-09    |
| psSAR1g [W/kg]      | 0.224         | 0.234         |
| psSAR10g [W/kg]     | 0.140         | 0.146         |
| Power Drift [dB]    | 0.12          | -0.08         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 78.4          |
| Dist 3dB Peak [mm]  |               | 15.0          |



Meas.28 Head Left Cheek LTE B71 Ch133322

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                           | Group,<br>UID         | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity [S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|--------------------------------|-----------------------|------------------------------------------|----------------------|---------------------------|---------------------|--------------------------------|-------------------------------|
| Left Head,<br>HSL          | CHEEK,<br>0.00                        | Band 71,<br>E-<br>UTRA/F<br>DD | LTE-FDD,<br>10169-CAE | 683.0,<br>133322                         | 10.29                | 0.87                      | 42.4                | 22.4                           | 21.3                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-06 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 150.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5      |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | N/A           | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-06    | 2024-12-06    |
| psSAR1g [W/kg]      | 0.105         | 0.112         |
| psSAR10g [W/kg]     | 0.074         | 0.088         |
| Power Drift [dB]    | 0.05          | -0.14         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 94.8          |
| Dist 3dB Peak [mm]  |               | > 15.0        |



Meas.29 Body Back Side 15mm LTE B71 Ch133322

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                           | Group,<br>UID         | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivit<br>y [S/m] | TSL<br>Permittivity | Ambient<br>Temperatur<br>e<br>[°C] | Liquid<br>Temperatur<br>e<br>[°C] |
|----------------------------|---------------------------------------|--------------------------------|-----------------------|------------------------------------------|----------------------|-------------------------------|---------------------|------------------------------------|-----------------------------------|
| Flat,<br>HSL               | BACK,<br>15.00                        | Band 71,<br>E-<br>UTRA/F<br>DD | LTE-FDD,<br>10169-CAE | 683.0,<br>133322                         | 10.29                | 0.87                          | 42.4                | 22.4                               | 21.3                              |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-06 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 180.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 15.0 x 15.0   | 8.0 x 8.0 x 5      |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | Y             | Y                  |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-06    | 2024-12-06    |
| psSAR1g [W/kg]      | 0.083         | 0.088         |
| psSAR10g [W/kg]     | 0.059         | 0.067         |
| Power Drift [dB]    | 0.03          | -0.01         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 87.6          |
| Dist 3dB Peak [mm]  |               | > 15.0        |



Meas.30 Hotspot Right Side 10mm LTE B71 Ch133322

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                           | Group,<br>UID         | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity<br>[S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|--------------------------------|-----------------------|------------------------------------------|----------------------|------------------------------|---------------------|--------------------------------|-------------------------------|
| Flat,<br>HSL               | EDGE<br>RIGHT,<br>10.00               | Band 71,<br>E-<br>UTRA/F<br>DD | LTE-FDD,<br>10169-CAE | 683.0,<br>133322                         | 10.29                | 0.87                         | 42.4                | 22.4                           | 21.3                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-06 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan    | Zoom Scan          |
|---------------------|--------------|--------------------|
| Grid Extents [mm]   | 44.0 x 180.0 | 32.0 x 32.0 x 30.0 |
| Grid Steps [mm]     | 11.0 x 15.0  | 8.0 x 8.0 x 5      |
| Sensor Surface [mm] | 3.0          | 1.4                |
| Graded Grid         | Yes          | Yes                |
| Grading Ratio       | 1.5          | 1.5                |
| MAIA                | Y            | N/A                |
| Surface Detection   | VMS + 6p     | VMS + 6p           |
| Scan Method         | Measured     | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-06    | 2024-12-06    |
| psSAR1g [W/kg]      | 0.085         | 0.087         |
| psSAR10g [W/kg]     | 0.059         | 0.061         |
| Power Drift [dB]    | 0.02          | -0.03         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 84.7          |
| Dist 3dB Peak [mm]  |               | > 15.0        |



Meas.31 Head Left Cheek WLAN2.4G Ch6

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band           | Group,<br>UID      | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity<br>[S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|----------------|--------------------|------------------------------------------|----------------------|------------------------------|---------------------|--------------------------------|-------------------------------|
| Left Head,<br>HSL          | CHEEK,<br>0.00                        | WLAN<br>2.4GHz | WLAN,<br>10315-AAB | 2437.0,<br>6                             | 7.75                 | 1.79                         | 39.6                | 22.7                           | 21.3                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-12 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 140.0 | 30.0 x 30.0 x 30.0 |
| Grid Steps [mm]     | 10.0 x 10.0   | 5.0 x 5.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | N/A           | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-12    | 2024-12-12    |
| psSAR1g [W/kg]      | 0.786         | 0.763         |
| psSAR10g [W/kg]     | 0.329         | 0.302         |
| Power Drift [dB]    | -0.05         | -0.16         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 47.7          |
| Dist 3dB Peak [mm]  |               | 7.0           |



Meas.32 Body Back Side 15mm WLAN 2.4G Ch1

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band           | Group,<br>UID      | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity<br>[S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|----------------|--------------------|------------------------------------------|----------------------|------------------------------|---------------------|--------------------------------|-------------------------------|
| Flat,<br>HSL               | BACK,<br>15.00                        | WLAN<br>2.4GHz | WLAN,<br>10315-AAB | 2412.0,<br>1                             | 7.75                 | 1.76                         | 39.8                | 22.7                           | 21.3                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-12 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 180.0 | 30.0 x 30.0 x 30.0 |
| Grid Steps [mm]     | 10.0 x 10.0   | 5.0 x 5.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | N/A           | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-12    | 2024-12-12    |
| psSAR1g [W/kg]      | 0.261         | 0.267         |
| psSAR10g [W/kg]     | 0.129         | 0.131         |
| Power Drift [dB]    | -0.04         | -0.03         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 80.4          |
| Dist 3dB Peak [mm]  |               | 10.0          |



Meas.33 Hotspot Back Side 10mm WLAN 2.4G Ch1

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band           | Group,<br>UID      | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity [S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|----------------|--------------------|------------------------------------------|----------------------|---------------------------|---------------------|--------------------------------|-------------------------------|
| Flat,<br>HSL               | BACK,<br>10.00                        | WLAN<br>2.4GHz | WLAN,<br>10315-AAB | 2412.0,<br>1                             | 7.75                 | 1.76                      | 39.8                | 22.7                           | 21.3                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-12 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 180.0 | 30.0 x 30.0 x 30.0 |
| Grid Steps [mm]     | 10.0 x 10.0   | 5.0 x 5.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | N/A           | N/A                |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-12    | 2024-12-12    |
| psSAR1g [W/kg]      | 0.230         | 0.239         |
| psSAR10g [W/kg]     | 0.111         | 0.111         |
| Power Drift [dB]    | -0.17         | -0.04         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 50.5          |
| Dist 3dB Peak [mm]  |               | 9.0           |



Meas.34 Head Left cheek BT Ch39

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                   | Group,<br>UID           | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivit<br>y [S/m] | TSL<br>Permittivity | Ambient<br>Temperatur<br>e<br>[°C] | Liquid<br>Temperatur<br>e<br>[°C] |
|----------------------------|---------------------------------------|------------------------|-------------------------|------------------------------------------|----------------------|-------------------------------|---------------------|------------------------------------|-----------------------------------|
| LeftHead,<br>HSL           | CHEEK,<br>0.00                        | ISM 2.4<br>GHz<br>Band | Bluetooth,<br>10670-AAA | 2441.0,<br>39                            | 7.68                 | 1.79                          | 39.6                | 22.7                               | 21.3                              |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-12 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 140.0 | 30.0 x 30.0 x 30.0 |
| Grid Steps [mm]     | 10.0 x 10.0   | 5.0 x 5.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | Y             | Y                  |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-12    | 2024-12-12    |
| psSAR1g [W/kg]      | 0.080         | 0.081         |
| psSAR10g [W/kg]     | 0.032         | 0.031         |
| Power Drift [dB]    | 0.00          | -0.13         |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 40.7          |
| Dist 3dB Peak [mm]  |               | 6.3           |



Meas.35 Body Back Side 15mm BT CH39

Exposure Conditions

| Phantom<br>Section,<br>TSL | Position,<br>Test<br>Distance<br>[mm] | Band                   | Group,<br>UID           | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivity [S/m] | TSL<br>Permittivity | Ambient<br>Temperature<br>[°C] | Liquid<br>Temperature<br>[°C] |
|----------------------------|---------------------------------------|------------------------|-------------------------|------------------------------------------|----------------------|---------------------------|---------------------|--------------------------------|-------------------------------|
| Flat,<br>HSL               | BACK,<br>15.00                        | ISM 2.4<br>GHz<br>Band | Bluetooth,<br>10670-AAA | 2441.0,<br>39                            | 7.68                 | 1.79                      | 39.6                | 22.7                           | 21.3                          |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-12 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 100.0 x 180.0 | 30.0 x 30.0 x 30.0 |
| Grid Steps [mm]     | 10.0 x 10.0   | 5.0 x 5.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | Y             | Y                  |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-12    | 2024-12-12    |
| psSAR1g [W/kg]      | 0.006         | 0.005         |
| psSAR10g [W/kg]     | 0.003         | 0.001         |
| Power Drift [dB]    | 0.20          | 0.18          |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 88.7          |
| Dist 3dB Peak [mm]  |               | > 15.0        |



Meas.36 Hotspot Back Side 10mm BT CH39

Exposure Conditions

| Phantom      | Position,<br>Test | Band                   | Group,<br>UID           | Frequency<br>[MHz],<br>Channel<br>Number | Conversion<br>Factor | TSL<br>Conductivit<br>y [S/m] | TSL<br>Permittivity | Ambient<br>Temperatur<br>e<br>[°C] | Liquid<br>Temperatur<br>e<br>[°C] |
|--------------|-------------------|------------------------|-------------------------|------------------------------------------|----------------------|-------------------------------|---------------------|------------------------------------|-----------------------------------|
| Flat,<br>HSL | BACK,<br>10.00    | ISM 2.4<br>GHz<br>Band | Bluetooth,<br>10670-AAA | 2441.0,<br>39                            | 7.68                 | 1.79                          | 39.6                | 22.7                               | 21.3                              |

Hardware Setup


| Phantom                                 | TSL, Measured Date        | Probe, Calibration Date     | DAE, Calibration Date   |
|-----------------------------------------|---------------------------|-----------------------------|-------------------------|
| Twin-SAM V5.0 (30deg probe tilt) - 1859 | HBBL-600-10000 2024-12-12 | EX3DV4 - SN7510, 2024-06-25 | DAE4 Sn1710, 2024-01-03 |

Scan Setup

|                     | Area Scan     | Zoom Scan          |
|---------------------|---------------|--------------------|
| Grid Extents [mm]   | 120.0 x 180.0 | 30.0 x 30.0 x 30.0 |
| Grid Steps [mm]     | 10.0 x 10.0   | 5.0 x 5.0 x 5.0    |
| Sensor Surface [mm] | 3.0           | 1.4                |
| Graded Grid         | Yes           | Yes                |
| Grading Ratio       | 1.5           | 1.5                |
| MAIA                | Y             | Y                  |
| Surface Detection   | VMS + 6p      | VMS + 6p           |
| Scan Method         | Measured      | Measured           |

Measurement Results

|                     | Area Scan     | Zoom Scan     |
|---------------------|---------------|---------------|
| Date                | 2024-12-12    | 2024-12-12    |
| psSAR1g [W/kg]      | 0.014         | 0.013         |
| psSAR10g [W/kg]     | 0.007         | 0.005         |
| Power Drift [dB]    | 0.17          | 0.19          |
| Power Scaling       | Disabled      | Disabled      |
| Scaling Factor [dB] |               |               |
| TSL Correction      | No correction | No correction |
| M2/M1 [%]           |               | 50.3          |
| Dist 3dB Peak [mm]  |               | > 15.0        |



## **ANNEX D EUT EXTERNAL PHOTOS**

Please refer the document “BL-SH24B0867-AW.pdf”.

## **ANNEX E SAR TEST SETUP PHOTOS**

Please refer the document “BL-SH24B0867-AS.pdf”.

## **ANNEX F CALIBRATION REPORT**

Please refer the document “BL-SH24B0867-AC.pdf”.

## Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--