



**No. I22Z62236-SEM03**

**For**

**TCL Communication Ltd.**

**Feature phone**

**Model Name: T301**

**with**

**Hardware Version: C685\_MB\_V1.0**

**Software Version:**

**T301P\_CE\_V1.0\_20221108/T301Q\_CE\_V1.1\_20221128**

**FCC ID: ZCASMA145RN**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

**Test Laboratory:**

**CTTL, Telecommunication Technology Labs, CAICT**


No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504


Email: [cttl\\_terminals@caict.ac.cn](mailto:cttl_terminals@caict.ac.cn), website: [www.caict.ac.cn](http://www.caict.ac.cn)




**Picture 1: Constituents of the sample**



**Picture 2: Left Head Touch Cheek Position**



**Picture 3: Left Head Tilt 15° Position**



**Picture 4: Right Head Touch Cheek Position**




**Picture 5: Right Head Tilt 15° Position**

**Test positions for body:**

The Body SAR is tested at the following test positions with the distance =15mm between the EUT and the phantom bottom:





**Picture 6: Front 15mm**



**Picture 7: Rear 15mm**