

2.4GWIFI

DUT: SVP-MC2BS

Communication System: 802.11b ; Frequency: 2437 MHz;Duty Cycle: 1:1
Medium: H2450 Medium parameters used: $f = 2437\text{ MHz}$; $\sigma = 1.776\text{ S/m}$; $\epsilon_r = 40.424$; $\rho = 1000\text{ kg/m}^3$
Ambient Temperature : $22.6\text{ }^\circ\text{C}$; Liquid Temperature : $22.4\text{ }^\circ\text{C}$

- DASY5 Configuration:
- Probe: EX3DV4 - SN3970; ConvF(8.06, 8.06, 8.06); Calibrated: 2023/5/17;
 - Sensor-Surface: 3mm (Mechanical Surface Detection)
 - Electronics: DAE4 Sn1418; Calibrated: 2023/4/25
 - Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
 - Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Front/Area Scan (8x11x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.0881 W/kg

Front/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 3.063 V/m ; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 0.166 W/kg

SAR(1 g) = 0.080 W/kg ; SAR(10 g) = 0.037 W/kg

Maximum value of SAR (measured) = 0.101 W/kg

