

# VARIANT FCC TEST REPORT

## (Part 15, Subpart C)

Applicant:	Xiaomi Communications Co., Ltd.
Address:	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085



Manufacturer or Supplier:	Xiaomi Communications Co., Ltd.
Address:	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
Product:	Tablet Computer
Brand Name:	POCO
Model Name:	2405CPCFBG
FCC ID:	2AFZZCFBG
Date of tests:	Mar. 12, 2024 ~ Apr. 01, 2024

The tests have been carried out according to the requirements of the following standard:

☒ **FCC Part 15, Subpart C, Section 15.247**

☒ **ANSI C63.10-2020**

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

Prepared by Simon Wang Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
 Date: Apr. 16, 2024	 Date: Apr. 16, 2024

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

## TABLE OF CONTENTS

<b>RELEASE CONTROL RECORD .....</b>	<b>5</b>
<b>1 SUMMARY OF TEST RESULTS.....</b>	<b>6</b>
1.1 MEASUREMENT UNCERTAINTY .....	7
<b>2 GENERAL INFORMATION .....</b>	<b>8</b>
2.1 GENERAL DESCRIPTION OF EUT .....	8
2.2 DESCRIPTION OF TEST MODES .....	10
2.2.1 CONFIGURATION OF SYSTEM UNDER TEST .....	11
2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	11
2.3 DUTY CYCLE OF TEST SIGNAL .....	15
2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	16
2.5 DESCRIPTION OF SUPPORT UNITS .....	16
<b>3 TEST TYPES AND RESULTS.....</b>	<b>17</b>
3.1 CONDUCTED EMISSION MEASUREMENT .....	17
3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	17
3.1.2 TEST INSTRUMENTS.....	17
3.1.3 TEST PROCEDURES .....	18
3.1.4 DEVIATION FROM TEST STANDARD .....	18
3.1.5 TEST SETUP .....	19
3.1.6 EUT OPERATING CONDITIONS .....	19
3.1.7 TEST RESULTS .....	20
3.2 RADIATED EMISSION MEASUREMENT .....	22
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT .....	22
3.2.2 TEST INSTRUMENTS.....	23
3.2.3 TEST PROCEDURES .....	24
3.2.4 DEVIATION FROM TEST STANDARD .....	24
3.2.5 TEST SETUP .....	25
3.2.6 EUT OPERATING CONDITIONS .....	26
3.2.7 TEST RESULTS .....	27
3.3 6 DB BANDWIDTH MEASUREMENT .....	91
3.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT .....	91
3.3.2 TEST INSTRUMENTS.....	91
3.3.3 TEST PROCEDURE.....	91
3.3.4 DEVIATION FROM TEST STANDARD .....	92
3.3.5 TEST SETUP .....	92



3.3.6	EUT OPERATING CONDITIONS .....	92
3.3.7	TEST RESULTS .....	93
3.4	CONDUCTED OUTPUT POWER.....	94
3.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT.....	94
3.4.2	TEST SETUP .....	94
3.4.3	TEST INSTRUMENTS.....	94
3.4.4	TEST PROCEDURES .....	94
3.4.5	DEVIATION FROM TEST STANDARD .....	94
3.4.6	EUT OPERATING CONDITIONS .....	94
3.4.7	TEST RESULTS .....	95
3.4.7.1	MAXIMUM PEAK OUTPUT POWER .....	95
3.4.7.2	AVERAGE OUTPUT POWER (FOR REFERENCE).....	96
3.5	POWER SPECTRAL DENSITY MEASUREMENT .....	97
3.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....	97
3.5.2	TEST SETUP .....	97
3.5.3	TEST INSTRUMENTS.....	97
3.5.4	TEST PROCEDURE.....	97
3.5.5	DEVIATION FROM TEST STANDARD .....	97
3.5.6	EUT OPERATING CONDITION .....	97
3.5.7	TEST RESULTS .....	98
3.6	OUT OF BAND EMISSION MEASUREMENT .....	99
3.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT .....	99
3.6.2	TEST SETUP .....	99
3.6.3	TEST INSTRUMENTS.....	99
3.6.4	TEST PROCEDURE.....	99
3.6.5	DEVIATION FROM TEST STANDARD .....	100
3.6.6	EUT OPERATING CONDITION .....	100
3.6.7	TEST RESULTS .....	100
3.7	ANTENNA REQUIREMENTS.....	101
3.7.1	STANDARD APPLICABLE .....	101
3.7.2	ANTENNA CONNECTED CONSTRUCTION .....	101
3.7.3	ANTENNA GAIN .....	101
4	<b>PHOTOGRAPHS OF THE TEST CONFIGURATION .....</b>	<b>102</b>
5	<b>MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB</b>	<b>103</b>
6	<b>APPENDIX 1.....</b>	<b>104</b>



Test Report No.: W7L-P24040006RF02

WLAN .....	104
WLAN_OFDMA.....	257
7 APPENDIX 2 BLE .....	385



**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
W7L-P24030005RF02	Original release	Apr. 01, 2024
W7L-P24040006RF02	Based on the original report changing FCC ID, the model name and band name.	Apr. 16, 2024



**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

## 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)		
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT
15.207	AC Power Conducted Emission	Compliance
15.205 15.209	Radiated Emissions	Compliance
15.247(d)	Out of band Emission Measurement	Compliance
15.247(a)(2)	6dB bandwidth	Compliance
15.247(b)	Conducted Output power	Compliance
15.247(e)	Power Spectral Density	Compliance
15.203	Antenna Requirement	Compliance

- Note :
1. Except RSE, other data please refer to Appendix 1 (for WIFI-2.4G) and Appendix 2 (for BLE).
  2. 802.11 axHE20 26T,52T,106T,and 242T modes tested, 802.11 ax HE40 484T mode tested, 26T,52T,106T,and 242T modes are covered by the HE 20MHz modes
  3. Only the worse data were report



## 1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	±2.70dB
Radiated emissions (9KHz~30MHz)	±2.68dB
Radiated emissions (30MHz~1GHz)	±4.98dB
Radiated emissions (1GHz ~6GHz)	±4.70dB
Radiated emissions (6GHz ~18GHz)	±4.60dB
Radiated emissions (18GHz ~40GHz)	±4.12dB
Conducted emissions	±4.01dB
Occupied Channel Bandwidth	±43.58KHz
Conducted Output power	±2.06dB
Power Spectral Density	±0.85 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .



## 2 GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	Tablet Computer
<b>BRAND NAME</b>	POCO
<b>MODEL NAME</b>	2405CPCFBG
<b>NOMINAL VOLTAGE</b>	5.0Vdc(adapter or host equipment) 3.84Vdc (Li-ion, battery)
<b>MODULATION</b>	DSSS, OFDM, GFSK, OFDMA
<b>TRANSMISSION RATE</b>	802.11b: 11/ 5.5/ 2.0 / 1.0 Mbps 802.11g: 54/ 48/ 36 / 24 / 18 / 9/ 6 Mbps 802.11n(HT20)/ax(HE20): up to 144.4 Mbps 802.11n(HT40)/ax(HE40): up to 300 Mbps BT_LE: 0.125 Mbps /0.5 Mbps /1 Mbps/2 Mbps 802.11ax 20 (RU26/52/106/242): up to 286.8Mbps 802.11ax 40 (RU484): up to 573.5Mbps
<b>OPERATING FREQUENCY</b>	2412-2462MHz for 11b/g/n(HT20/40) /ax(HE20/40) 2402-2480MHz for BT-LE(GFSK) 2412-2462MHz for ax(20M RU26/52/106/242)/ax (40M RU484)
<b>MAX. OUTPUT POWER</b>	WLAN: 518.3mW (Maximum) BT-LE: 1.38mW (Maximum) RU WLAN: 695.93mW (Maximum)
<b>ANTENNA TYPE</b>	ANT 1: PIFA Antenna with -0.7dBi gain for WIFI ANT 2: PIFA Antenna with -0.7dBi gain for WIFI
<b>HW VERSION</b>	13510N83
<b>SW VERSION</b>	Xiaomi HyperOS 1.0
<b>SN CODE</b>	GB409L000006/GB409L000027/GB409L000032
<b>I/O PORTS</b>	Refer to user's manual
<b>CABLE SUPPLIED</b>	USB cable1: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable2: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable3: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable4: non-shielded cable, with w/o ferrite core, 1.0 meter





**Test Report No.: W7L-P24040006RF02**

**NOTE:**

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. The EUT incorporates a MIMO function. Physically, the EUT provides two transmitter and two receiver.

MODULATION MODE	TX/RX FUNCTION
802.11b	2TX /2RX
802.11g	2TX /2RX
802.11n(HT20)/ax(HE20)	2TX /2RX
802.11n(HT40)/ax(HE40)	2TX /2RX
802.11ax (20MHz RU 26/52/106/242)	2TX /2RX
802.11ax (40MHz RU 484)	2TX /2RX
BT_LE(1MHz)	1TX /1RX
BT_LE(2MHz)	1TX /1RX
BT_LE(S2)	1TX /1RX
BT_LE(S8)	1TX /1RX

3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
4. Antenna gain and EUT conducted cable loss are provided by the customer, and the laboratory will record the results based on these items that involve these two parameters.



## 2.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20), 802.11ax20 (HE20); 802.11ax20 (RU 26/52/106/242):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

7 channels are provided for 802.11n (HT40), 802.11ax40 (HE40); 802.11ax40 (RU 484):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422 MHz	7	2442 MHz
4	2427 MHz	8	2447 MHz
5	2432 MHz	9	2452 MHz
6	2437 MHz		

40 channels are provided for BT-LE (GFSK):

CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



## 2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 4 photographs of the test configuration for reference.

## 2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.

The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G**: Radiated Emission below 1GHz

**RE≥1G**: Radiated Emission above 1GHz

**PLC**: Power Line Conducted Emission

**APCM**: Antenna Port Conducted Measurement

**NOTE**: No need to concern of Conducted Emission due to the EUT is powered by battery.

**RADIATED EMISSION TEST (BELOW 1GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	6	DSSS	1.0
BT-LE	1 to 38	19	GFSK	2.0



**RADIATED EMISSION TEST (ABOVE 1GHz):**

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
802.11ax HE20	1 to 11	1, 6, 11	OFDM	MCS0
802.11n HT40	3 to 9	3,6,9	OFDM	MCS0
802.11ax HE40	3 to 9	3,6,9	OFDM	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	0.125&0.5&1.0
BT-LE	1 to 38	1,19, 38	GFSK	2.0
802.11ax 20 (RU 26/52/106/242)	1 to 11	1, 11	OFDMA	MCS0
802.11ax 40 (RU 484)	3 to 9	3, 9	OFDMA	MCS0

**POWER LINE CONDUCTED EMISSION TEST**

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	6	DSSS	1.0



**BANDEDGE MEASUREMENT:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
802.11ax HE20	1 to 11	1, 6, 11	OFDM	MCS0
802.11n HT40	3 to 9	3,6,9	OFDM	MCS0
802.11n HT40	3 to 9	3,6,9	OFDM	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	0.125&0.5&1.0
BT-LE	1 to 38	1,19, 38	GFSK	2.0
802.11ax 20 (RU 26/52/106/242)	1 to 11	1,11	OFDMA	MCS0
802.11ax 40 (RU 484)	3 to 9	3 ,9	OFDMA	MCS0



**ANTENNA PORT CONDUCTED MEASUREMENT:**

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
802.11ax HE20	1 to 11	1, 6, 11	OFDM	MCS0
802.11n HT40	3 to 9	3,6,9	OFDM	MCS0
802.11ax HE40	3 to 9	3,6,9	OFDM	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	0.125&0.5&1.0
BT-LE	1 to 38	1,19, 38	GFSK	2.0
802.11ax 20 (RU 26/52/106/242)	1 to 11	1,11	OFDMA	MCS0
802.11ax 40 (RU 484)	3 to 9	3 ,9	OFDMA	MCS0

**TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	23deg. C, 70%RH	DC 5V By Adapter	Jace Hu
RE≥1G	23deg. C, 70%RH	DC 5V By Adapter	Jace Hu
PLC	25deg. C, 52%RH	DC 5V By Adapter	Carl Xie
APCM	25deg. C, 60%RH	DC 3.84V By DC Supply	James Fu



Test Report No.: W7L-P24040006RF02

## 2.3 DUTY CYCLE OF TEST SIGNAL

Please Refer to Appendix1/2 Of this test report.

## 2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C, Section 15.247**

**KDB 558074 D01 DTS Meas Guidance v05r02**

**ANSI C63.10-2020**

Note :

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

## 2.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Desktop	Lenovo	M73 SFF	PC04GRQV	N/A
2	Desktop	Lenovo	M73 SFF	PC06CS27	N/A
3	Laptop	Lenovo	Thinkpad T450	PC-049PT1	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line: Unshielded, Detachable 1.5m
2	AC Line: Unshielded, Detachable 1.5m
3	AC Line: Unshielded, Detachable 1.5m





### 3 TEST TYPES AND RESULTS

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

**NOTE:** 1.The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

##### 3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	101900	Feb. 14,24	Feb. 13,25
EMC32 test software	Rohde&Schwarz	EMC32	NA	NA	NA
LISN network	Rohde&Schwarz	ENV216	101922	Mar. 10,24	Mar. 09,25

**NOTE:**

1. The test was performed in CE shielded room.

2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



### 3.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

### 3.1.4 DEVIATION FROM TEST STANDARD

No deviation.



### 3.1.5 TEST SETUP



**Note: 1.Support units were connected to second LISN.**

**2.Both of LISNs (AMN) are 80 cm from EUT and at least 80  
from other units and other metal planes**

For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 3.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



## 3.1.7 TEST RESULTS

## CONDUCTED WORST-CASE DATA:

Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	26deg. C, 51%RH
Tested By	Carl Xie		

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
1.068000	---	17.10	46.00	28.90	L1	ON	9.8
1.068000	28.58	---	56.00	27.42	L1	ON	9.8
4.484000	---	24.68	46.00	21.32	L1	ON	9.7
4.484000	31.84	---	56.00	24.16	L1	ON	9.7
9.888000	---	38.56	50.00	11.44	L1	ON	10.4
9.888000	45.00	---	60.00	15.00	L1	ON	10.4
11.584000	---	40.18	50.00	9.82	L1	ON	10.6
11.584000	46.92	---	60.00	13.08	L1	ON	10.6
23.504000	---	32.05	50.00	17.95	L1	ON	11.3
23.504000	41.46	---	60.00	18.54	L1	ON	11.3
27.204000	---	35.83	50.00	14.17	L1	ON	11.3
27.204000	43.09	---	60.00	16.91	L1	ON	11.3

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.


3. The emission levels of other frequencies were very low against the limit.

4. Margin value = Limit value - Emission level

5. Correction factor = Insertion loss + Cable loss

6. Emission Level = Correction Factor + Reading Value.

Full Spectrum





**BUREAU  
VERITAS**


**Test Report No.: W7L-P24040006RF02**

<b>Frequency Range</b>	150KHz ~ 30MHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Quasi-Peak (QP) / Average (AV), 9 kHz
<b>Input Power</b>	120Vac, 60Hz	<b>Environmental Conditions</b>	26deg. C, 51%RH
<b>Tested By</b>	Carl Xie		

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.472000	---	25.01	46.48	21.47	N	ON	9.6
0.472000	33.35	---	56.48	23.13	N	ON	9.6
4.432000	---	24.58	46.00	21.42	N	ON	9.7
4.432000	31.60	---	56.00	24.40	N	ON	9.7
10.320000	---	38.94	50.00	11.06	N	ON	10.4
10.320000	45.55	---	60.00	14.45	N	ON	10.4
10.712000	---	40.41	50.00	9.59	N	ON	10.5
10.712000	46.94	---	60.00	13.06	N	ON	10.5
23.360000	---	32.02	50.00	17.98	N	ON	11.4
23.360000	41.45	---	60.00	18.55	N	ON	11.4
27.692000	---	35.79	50.00	14.21	N	ON	11.4
27.692000	43.40	---	60.00	16.60	N	ON	11.4

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Limit value -Emission level
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.

Full Spectrum



BV 7Layers Communications Technology  
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,  
Zhaoshang Street, Nanshan District Shenzhen,  
Guangdong, People's Republic of China

Tel: +86 755 8869 6566  
Fax: +86 755 8869 6577  
Email: [customerservice.sw@bureauveritas.com](mailto:customerservice.sw@bureauveritas.com)



### 3.2 RADIATED EMISSION MEASUREMENT

#### 3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



### 3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	Nov. 14,23	Nov. 13,26
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Feb. 18,24	Feb. 17,25
Horn Antenna	ETS-LINDGREN	3117	00168692	Feb. 18,24	Feb. 17,25
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-00361	15433	Sep.04, 23	Sep.03, 24
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	JS1120-3	3.2.06	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	N/A	May. 06,24	May. 05,25
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 28,23	Mar. 27,24
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 27,24	Mar. 26,25
Signal Pre-Amplifier	EMSI	EMC 9135	980249	May. 06,23	May. 05,24
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	May.10,23	May.09,24
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Feb. 17,24	Feb. 16,25
DC Source	Kikusui/JP	PMX18-5A	0000001	Aug. 12,23	Aug. 11,24
Power Meter	Anritsu	ML2495A	1506002	Feb. 14,24	Feb. 13,25
Power Sensor	Anritsu	MA2411B	1339352	Feb. 14,24	Feb. 13,25
Loop Antenna	Schwarzbeck	FMZB 1519B	00173	Sep.03,23	Sep.02,24

- NOTE:**
1. The calibration interval of the above test instruments is 12 months or 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
  2. The test was performed in 3m Chamber.
  3. The FCC Site Registration No. is 525120; The Designation No. is CN1171.



### 3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

**Note:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ( $10 \log(1/\text{duty cycle})$ ).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

### 3.2.4 DEVIATION FROM TEST STANDARD

No deviation






**BUREAU  
VERITAS**


Test Report No.: W7L-P24040006RF02

### 3.2.5 TEST SETUP

#### <Frequency Range 9KHz~30MHz >




#### < Frequency Range 30MHz~1GHz >





<Frequency Range above 1GHz>



**Note:** Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 3.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



**BUREAU  
VERITAS**

**Test Report No.: W7L-P24040006RF02**

### 3.2.7 TEST RESULTS

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

#### BELOW 1GHz WORST-CASE DATA:

30 MHz – 1GHz data:

802.11b:


<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz		

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+: QPK Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	45.520	29.49	40.00	10.51	-7.47	H	99.9	2.00
1	61.477	28.05	40.00	11.95	-9.35	H	359	1.00
1	109.055	26.25	43.50	17.25	-9.21	H	355.5	2.00
1	235.931	23.91	46.00	22.09	-7.45	H	355.5	2.00
1	373.865	27.46	46.00	18.54	-3.71	H	302	1.00
1	586.295	30.07	46.00	15.93	-2.18	H	355.5	2.00

#### REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value – Emission level.





**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02


CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+: QPK Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	50.079	29.63	40.00	10.37	-7.54	V	359	1.00
1	67.151	25.99	40.00	14.01	-10.55	V	358.2	1.00
1	109.104	25.40	43.50	18.10	-9.21	V	260.2	1.00
1	212.603	23.01	43.50	20.49	-8.65	V	359	2.00
1	329.488	27.56	46.00	18.44	-4.52	V	260.2	1.00
1	900.090	34.01	46.00	11.99	2.91	V	355.5	2.00

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value – Emission level.





**BUREAU  
VERITAS**

**Test Report No.: W7L-P24040006RF02**

# **ABOVE 1GHz WORST-CASE DATA:**

**Note:** 1. For radiated emissions testing , the full testing range of different modes have been scanned , only the worst case harmonic data is reported in the sheet.

2. All other emissions were greater than 20dB below the limit was not recorded

## **802.11b:**

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

### **ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.567	38.94	54.00	15.06	5.77	H	359	2.00
1	2,390.000	38.33	54.00	15.67	5.77	H	359	2.00
1	2,411.200	96.01			5.92	H	5.6	1.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,346.667	52.11	74.00	21.89	5.58	H	219.6	2.00
1	2,390.000	50.35	74.00	23.65	5.77	H	359	2.00
1	2,413.400	101.28			5.93	H	224	1.00

### **ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.567	38.70	54.00	15.30	5.77	V	359.1	1.00
1	2,390.000	37.99	54.00	16.01	5.77	V	359.1	1.00
1	2,413.030	97.83			5.93	V	0.9	2.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,355.100	53.28	74.00	20.72	5.60	V	293.8	2.00
1	2,390.000	51.80	74.00	22.20	5.77	V	293.8	2.00
1	2,411.200	105.75			5.92	V	355.7	2.00

## **REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value – Emission level.
- 2412MHz: Fundamental frequency.




BUREAU  
VERITAS

Test Report No.: W7L-P24040006RF02

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	4,874.000	51.86	74.00	22.14	41.73	54.00	12.27	4.89	H	359	1.00
3	7,311.000	56.44	74.00	17.56	45.24	54.00	8.76	11.16	H	224.6	1.00






**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+: QPK Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	4,874.000	52.08	74.00	21.92	41.79	54.00	12.21	4.89	V	224.3	1.00
3	7,311.000	55.70	74.00	18.30	44.91	54.00	9.09	11.16	V	359.1	1.00



**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value – Emission level.
2. 2437MHz: Fundamental frequency.
3. For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet.





**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

<b>CHANNEL</b>	TX Channel 11	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,461.000	94.99			5.83	H	1	1.00
2	2,483.500	37.67	54.00	16.33	5.91	H	150.3	2.00
2	2,488.000	39.38	54.00	14.62	5.94	H	150.3	2.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,460.500	99.91			5.83	H	359	1.00
2	2,483.500	50.60	74.00	23.40	5.91	H	151.4	2.00
2	2,488.500	51.07	74.00	22.93	5.95	H	151.4	2.00

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,461.000	104.66			5.83	V	292.6	2.00
2	2,483.500	40.86	54.00	13.14	5.91	V	147.8	2.00
2	2,488.000	40.54	54.00	13.46	5.94	V	355	2.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,460.500	110.37			5.83	V	292.6	2.00
2	2,483.500	53.87	74.00	20.13	5.91	V	5	1.00
2	2,499.500	54.29	74.00	19.71	6.02	V	292.6	2.00

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value – Emission level.
- 2462MHz: Fundamental frequency.





**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

802.11g

<b>CHANNEL</b>	TX Channel 1	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.567	42.56	54.00	11.44	5.77	H	359	2.00
1	2,390.000	43.01	54.00	10.99	5.77	H	359	2.00
1	2,410.100	95.75			5.91	H	359	2.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.567	57.73	74.00	16.27	5.77	H	359	2.00
1	2,390.000	57.42	74.00	16.58	5.77	H	269.5	1.00
1	2,409.730	107.20			5.91	H	359	2.00

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.200	41.15	54.00	12.85	5.76	V	359	1.00
1	2,390.000	42.05	54.00	11.95	5.77	V	359	1.00
1	2,411.200	94.49			5.92	V	4.9	1.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.567	63.64	74.00	10.36	5.77	V	146.7	2.00
1	2,390.000	63.69	74.00	10.31	5.77	V	146.7	2.00
1	2,413.030	110.29			5.93	V	146.7	2.00

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value – Emission level.
- 2412MHz: Fundamental frequency.




**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	4,874.000	51.72	74.00	22.28	40.39	54.00	13.61	4.89	H	132.2	2.00
3	7,311.000	54.40	74.00	19.60	43.97	54.00	10.03	11.16	H	0.9	2.00






**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+: QPK Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	4,874.000	51.37	74.00	22.63	41.08	54.00	12.92	4.89	V	359.1	1.00
3	7,311.000	54.20	74.00	19.80	43.79	54.00	10.21	11.16	V	359.1	1.00



**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value – Emission level.
2. 2437MHz: Fundamental frequency.
3. For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet.



**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

<b>CHANNEL</b>	TX Channel 11	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,463.000	93.39			5.82	H	355.4	1.00
2	2,483.500	43.27	54.00	10.73	5.91	H	71.4	2.00
2	2,484.500	42.54	54.00	11.46	5.92	H	355	2.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,459.500	104.74			5.84	H	291.3	2.00
2	2,483.500	58.00	74.00	16.00	5.91	H	75	2.00
2	2,487.000	58.81	74.00	15.19	5.94	H	145.5	2.00

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,462.500	100.40			5.82	V	291.4	2.00
2	2,483.500	48.39	54.00	5.61	5.91	V	271.9	1.00
2	2,484.000	47.33	54.00	6.67	5.92	V	271.9	1.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,459.500	113.40			5.84	V	85.4	1.00
2	2,483.500	60.83	74.00	13.17	5.91	V	232.4	1.00
2	2,484.500	62.74	74.00	11.26	5.92	V	137.2	2.00

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value – Emission level.
- 2462MHz: Fundamental frequency.



**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

802.11n (20MHz)

<b>CHANNEL</b>	TX Channel 1	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,388.833	40.75	54.00	13.25	5.76	H	359	2.00
1	2,390.000	41.60	54.00	12.40	5.77	H	359	2.00
1	2,409.733	94.76			5.91	H	120.4	2.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.200	56.86	74.00	17.14	5.76	H	1	2.00
1	2,390.000	58.90	74.00	15.10	5.77	H	1	2.00
1	2,409.370	106.32			5.90	H	70.2	2.00

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.567	42.62	54.00	11.38	5.77	V	4.2	1.00
1	2,390.000	43.21	54.00	10.79	5.77	V	4.2	1.00
1	2,410.833	94.05			5.91	V	4.2	1.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.200	65.66	74.00	8.34	5.76	V	144.3	2.00
1	2,390.000	66.44	74.00	7.56	5.77	V	144.3	2.00
1	2,413.400	110.33			5.93	V	144.3	2.00

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value – Emission level.
2. 2412MHz: Fundamental frequency.




**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+: QPK Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	4,874.000	50.62	74.00	23.38	40.32	54.00	13.68	4.89	H	359	1.00
3	7,311.000	54.91	74.00	19.09	43.52	54.00	10.48	11.16	H	359	1.00






**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+: QPK Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	4,874.000	51.00	74.00	23.00	40.27	54.00	13.73	4.89	V	0.9	2.00
3	7,311.000	54.25	74.00	19.75	43.54	54.00	10.46	11.16	V	242.2	1.00



**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value – Emission level.
2. 2437MHz: Fundamental frequency.
3. For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet.





**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

<b>CHANNEL</b>	TX Channel 11	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,463.000	93.55			5.82	H	292.2	1.00
2	2,483.500	42.40	54.00	11.60	5.91	H	67.8	2.00
2	2,484.000	41.51	54.00	12.49	5.92	H	359.1	1.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,464.000	105.62			5.81	H	288.6	1.00
2	2,483.500	59.11	74.00	14.89	5.91	H	70.2	2.00
2	2,484.000	58.24	74.00	15.76	5.92	H	70.2	2.00

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,463.000	99.96			5.82	V	291.4	2.00
2	2,483.500	47.66	54.00	6.34	5.91	V	274.2	1.00
2	2,484.000	47.07	54.00	6.93	5.92	V	274.2	1.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,463.000	112.03			5.82	V	292.6	2.00
2	2,483.500	61.52	74.00	12.48	5.91	V	269.4	1.00
2	2,484.000	62.97	74.00	11.03	5.92	V	269.4	1.00

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value – Emission level.
- 2462MHz: Fundamental frequency.





**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

802.11n (40MHz)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	2,389.000	44.25	54.00	9.75	5.76	H	359	2.00
3	2,390.000	44.14	54.00	9.86	5.77	H	359	2.00
3	2,419.000	94.43			5.96	H	221.7	1.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	2,389.500	60.42	74.00	13.58	5.77	H	359	2.00
3	2,390.000	60.95	74.00	13.05	5.77	H	6.2	2.00
3	2,417.000	104.12			5.96	H	67.8	2.00

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	2,389.500	49.55	54.00	4.45	5.77	V	355	2.00
3	2,390.000	49.56	54.00	4.44	5.77	V	355	2.00
3	2,417.500	96.04			5.96	V	145.1	1.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	2,387.000	64.01	74.00	9.99	5.75	V	139.6	2.00
3	2,390.000	63.10	74.00	10.90	5.77	V	139.6	2.00
3	2,428.000	107.81			5.94	V	5	1.00

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value – Emission level.
- 2422MHz: Fundamental frequency.




**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+: QPK Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	4,874.000	51.42	74.00	22.58	40.15	54.00	13.85	4.89	H	0.9	2.00
3	7,311.000	54.99	74.00	19.01	43.39	54.00	10.61	11.16	H	0.9	2.00






**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	4,874.000	50.95	74.00	23.05	40.42	54.00	13.58	4.89	V	1	2.00
3	7,311.000	54.47	74.00	19.53	43.50	54.00	10.50	11.16	V	359.1	1.00



**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value – Emission level.
2. 2437MHz: Fundamental frequency.
3. For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet.



**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

<b>CHANNEL</b>	TX Channel 9	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	2,454.000	91.92			5.87	H	5.6	1.00
4	2,483.500	44.02	54.00	9.98	5.91	H	5.6	1.00
4	2,484.000	43.88	54.00	10.12	5.92	H	5.6	1.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	2,449.500	104.39			5.89	H	293.4	1.00
4	2,483.500	61.61	74.00	12.39	5.91	H	143.2	2.00
4	2,484.000	62.90	74.00	11.10	5.92	H	143.2	2.00

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	2,454.000	96.34			5.87	V	65.4	2.00
4	2,483.500	47.60	54.00	6.40	5.91	V	246.7	1.00
4	2,484.000	47.45	54.00	6.55	5.92	V	246.7	1.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	2,448.000	108.16			5.90	V	68.6	1.00
4	2,483.500	65.46	74.00	8.54	5.91	V	5	1.00
4	2,484.000	63.96	74.00	10.04	5.92	V	220.5	1.00

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value – Emission level.
- 2452MHz: Fundamental frequency.



**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

802.11ax (20MHz)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.500	46.28	54.00	7.72	5.77	H	355.7	2.00
1	2,390.000	46.72	54.00	7.28	5.77	H	355.7	2.00
1	2,410.500	94.37			5.91	H	224.1	1.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.000	64.55	74.00	9.45	5.76	H	222.8	1.00
1	2,390.000	64.79	74.00	9.21	5.77	H	222.8	1.00
1	2,410.500	109.18			5.91	H	4.9	1.00

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.500	48.80	54.00	5.20	5.77	V	120.4	2.00
1	2,390.000	49.85	54.00	4.15	5.77	V	4.9	1.00
1	2,417.500	97.82			5.96	V	4.9	1.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.500	66.25	74.00	7.75	5.77	V	289	2.00
1	2,390.000	68.39	74.00	5.61	5.77	V	222.8	1.00
1	2,410.500	112.46			5.91	V	137.2	2.00

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value – Emission level.
2. 2412MHz: Fundamental frequency.




BUREAU  
VERITAS

Test Report No.: W7L-P24040006RF02

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+: QPK Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	4,874.000	51.35	74.00	22.65	40.45	54.00	13.55	4.89	H	266.2	1.00
3	7,311.000	54.28	74.00	19.72	43.44	54.00	10.56	11.16	H	266.2	1.00






**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	4,874.000	51.90	74.00	22.10	42.12	54.00	11.88	4.89	V	227.9	1.00
3	7,311.000	54.14	74.00	19.86	43.51	54.00	10.49	11.16	V	359	2.00



**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value – Emission level.
2. 2437MHz: Fundamental frequency.
3. For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet.





**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

<b>CHANNEL</b>	TX Channel 11	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,468.000	93.04			5.82	H	355.6	2.00
2	2,483.500	44.68	54.00	9.32	5.91	H	359	1.00
2	2,484.000	44.05	54.00	9.95	5.92	H	359	1.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,461.000	109.38			5.83	H	271.9	1.00
2	2,483.500	67.55	74.00	6.45	5.91	H	65.4	2.00
2	2,484.000	66.50	74.00	7.50	5.92	H	139.5	2.00

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,462.500	97.89			5.82	V	59.5	2.00
2	2,483.500	49.40	54.00	4.60	5.91	V	71	1.00
2	2,484.000	48.77	54.00	5.23	5.92	V	71	1.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,462.500	113.01			5.82	V	65.4	2.00
2	2,483.500	68.05	74.00	5.95	5.91	V	273.1	1.00
2	2,485.000	67.81	74.00	6.19	5.92	V	71	1.00

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value – Emission level.
2. 2462MHz: Fundamental frequency.





**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

802.11ax (40MHz)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	2,389.500	44.56	54.00	9.44	5.76	H	355	2.00
3	2,390.000	45.23	54.00	8.77	5.77	H	355	2.00
3	2,419.000	90.86			5.96	H	225.2	1.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	2,389.500	62.16	74.00	11.84	5.77	H	4.3	1.00
3	2,390.000	62.49	74.00	11.51	5.77	H	4.3	1.00
3	2,425.500	105.23			5.94	H	357.8	1.00

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	2,389.500	47.13	54.00	6.87	5.77	V	355.1	2.00
3	2,390.000	47.69	54.00	6.31	5.77	V	355.1	2.00
3	2,415.500	96.59			5.95	V	4.9	1.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	2,389.500	63.69	74.00	10.31	5.77	V	5	1.00
3	2,390.000	64.34	74.00	9.66	5.77	V	225.3	1.00
3	2,419.500	110.70			5.96	V	134.8	2.00

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value – Emission level.
- 2422MHz: Fundamental frequency.




BUREAU  
VERITAS

Test Report No.: W7L-P24040006RF02

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+: QPK Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	4,874.000	50.36	74.00	23.64	40.13	54.00	13.87	4.89	H	359	2.00
3	7,311.000	54.29	74.00	19.71	43.36	54.00	10.64	11.16	H	0.9	2.00






**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+: QPK Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	4,874.000	50.77	74.00	23.23	40.72	54.00	13.28	4.89	V	359	2.00
3	7,311.000	54.42	74.00	19.58	43.64	54.00	10.36	11.16	V	359	2.00



**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value – Emission level.
2. 2437MHz: Fundamental frequency.
3. For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet.



**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

<b>CHANNEL</b>	TX Channel 9	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	2,449.000	91.49			5.90	H	355	2.00
4	2,483.500	44.60	54.00	9.40	5.91	H	133.6	2.00
4	2,484.000	44.11	54.00	9.89	5.92	H	133.6	2.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	2,450.500	105.76			5.89	H	133.6	2.00
4	2,484.000	61.64	74.00	12.36	5.92	H	4.9	1.00
4	2,484.500	60.02	74.00	13.98	5.92	H	133.6	2.00

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	2,455.000	97.06			5.86	V	72.2	1.00
4	2,483.500	47.53	54.00	6.47	5.91	V	72.2	1.00
4	2,484.000	46.49	54.00	7.51	5.92	V	72.2	1.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	2,456.000	110.80			5.86	V	72.2	1.00
4	2,483.500	64.22	74.00	9.78	5.91	V	226.4	1.00
4	2,484.000	63.88	74.00	10.12	5.92	V	226.4	1.00

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value – Emission level.
2. 2452MHz: Fundamental frequency.



**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

## 2.4G WIFI-RU

802.11ax (20MHz) (RU26):

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,310.500	38.73	54.00	15.27	5.58	H	248.3	2.00
1	2,390.000	36.65	54.00	17.35	5.77	H	354.4	2.00
1	2,415.500	89.35			5.95	H	225.2	1.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,327.000	52.93	74.00	21.07	5.53	H	5	1.00
1	2,389.500	53.30	74.00	20.70	5.77	H	197	2.00
1	2,412.500	106.27			5.92	H	355	2.00

### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.000	38.05	54.00	15.95	5.76	V	5	1.00
1	2,390.000	38.10	54.00	15.90	5.77	V	5	1.00
1	2,410.500	93.31			5.91	V	124	2.00

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.000	52.35	74.00	21.65	5.76	V	286.6	2.00
1	2,390.000	53.67	74.00	20.33	5.77	V	132.4	2.00
1	2,410.500	108.48			5.91	V	132.4	2.00

## REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value – Emission level.
- 2412MHz: Fundamental frequency.



**BUREAU  
VERITAS**

Test Report No.: W7L-P24040006RF02

<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,874.000	50.05	74.00	23.95	38.65	54.00	15.35	13.53	H	20.6	2.00
2	7,311.000	55.37	74.00	18.63	44.07	54.00	9.93	18.89	H	359	2.00

