



Report No	ED0128-1
Client	Locknetics Security Engineering 575 Birch Street Forestville, CT 06010
Phone	(860) 314-5248
Fax	(860) 314-2452
FRN	0005178298
Models	CM 5600 Series
FCC ID	P2GPX
Equipment Type Equipment Code	Low Power Communication Device Transmitter DXX
Results	As detailed within this report
Prepared by	 Evan Gould – Test Engineer
Authorized by	 Michael Buchholz – EMC Manager
Issue Date	8/11/03
Conditions of issue	This Test Report is issued subject to the conditions stated in ‘terms and conditions’ section of this report.

Curtis-Straus LLC is accredited by the American Association for Laboratory Accreditation for the specific scope of accreditation under Certificate Number 1627-01. This report may contain data which is not covered by the A2LA accreditation.

## Table Of Contents

<i>Summary .....</i>	<i>3</i>
<i>Test Methodology .....</i>	<i>3</i>
<i>EUT Configuration .....</i>	<i>4</i>
<i>Statement of Conformity .....</i>	<i>5</i>
<i>Fundamental and Harmonic Emissions .....</i>	<i>6</i>
<i>AC Line Conducted Emission Measurements .....</i>	<i>7</i>
<i>Voltage Variation.....</i>	<i>8</i>
<i>Test Equipment Used .....</i>	<i>9</i>
<i>Terms And Conditions .....</i>	<i>10</i>
<i>A2LA Accreditation .....</i>	<i>12</i>

## ***Summary***

This report is an application for certification of transmitters operating pursuant to 47 CFR 15.209. The products are the Schlage CM 5600 Series locks with the PX credential type option. The PX specifies the combination of HID proximity and iButton credentials. The specific product tested was the CM 5690 with PX, FSA, and ME options. The difference between the model numbers 5690, 5691, 5693, 5694, and 5696 is purely the mechanical lock assembly. See attached "P2GPX – Model Descriptions" for clarification regarding the different model numbers and options.

## ***Test Methodology***

Radiated emissions testing is performed according to the procedures specified in ANSI C63.4 (2000). Receiving loop antenna was rotated in order to maximize radiated emission measurements.

Frequency range investigated: 9kHz – 1GHz

Measurement distance: 3m

AC Line conducted emissions testing was performed with a 50 $\Omega$ /50 $\mu$ H LISN.

**EUT Configuration**

<b>EUT Configuration</b>				
<b>Work Order:</b> D0128				
<b>Company:</b> Locknetics Security Engineering				
<b>Company Address:</b> 575 Birch Street Forestville, CT 06010				
<b>Contact:</b> Adam O'Day				
<b>Person Present:</b> Adam O'Day				
<b>MN</b>	<b>SN</b>	<b>FCC ID</b>		
<b>EUT:</b> CM5690 (PX, FSA, ME)				
<b>EUT Description:</b> CM5600 Mortise Series				
<b>EUT Max Frequency:</b> 9.8MHz				
<b>Support Equipment:</b>	<b>MN</b>	<b>SN</b>		
OEM 24VDC AC Adaptor	AD-2450	-		
<b>EUT Cables:</b>	<b>Qty</b>	<b>Shielded?</b>	<b>Length</b>	<b>Ferrites</b>
DC Cable	1	no	2m	no
<b>Unpopulated EUT Ports:</b>	<b>Qty</b>	<b>Reason</b>		
	none			
<b>Software / Operating Mode Description:</b>				
Operating normally; locked; oscillators are running				

### ***Statement of Conformity***

The Locknetics CM 5690 has been found to conform with the following parts of the 47 CFR as detailed below:

Part 2	Part 15	Comments
	15.15(b)	The product contains no user accessible controls that increase transmission power above allowable levels.
2.925	15.19	The label is shown in the label exhibit.
	15.21	Information to the user is shown in the instruction manual exhibit.
	15.27	No special accessories are required for compliance.
	15.203	The antenna is not accessible to the user and therefore cannot be easily removed. (The antenna and its connector are underneath the PCB assembly which is in turn professionally installed in the door lock enclosure.)
	15.205 15.209	The fundamental is not in a Restricted band and the spurious and harmonic emissions in the Restricted bands comply with the general emission limits of 15.209.
	15.207	The unit meets the AC line conducted emissions requirements of 15.207.

## Fundamental and Harmonic Emissions

### LIMITS

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

[15.209(a)]

### MEASUREMENTS

Fundamental and Harmonics (9kHz-1GHz)									CurtisStraus LLC		
Date: 19-Feb-03			Engineer: Evan Gould			Work Order: D0128					
Company: Locknetics			EUT: CM5690 (PX, FSA, ME)			Fundamental Frequency: 125kHz					
Test Site: "F"			Cable: 65 ft RG8A/U			Pre-amp: Red					
Antennas: Small Loop (9kHz-30MHz)			Filter/Attenuator: N/A			Analyzer: Black					
Red (30MHz-1GHz)											
Measurement Distance: 3 meters					Resolution BW: 9kHz						
Detector Type: Peak					Video BW: 30kHz						
Notes: No spurious emissions were detected.											
Settings for 30MHz - 1GHz: RBW=120kHz and VBW=300kHz											
Antenna Polarization (0° / 90°)	Frequency (MHz)	Reading (dBμV)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Filter/Attenuator Factor (dB)	Distance Factor (dB)	Adjusted Reading (dBμV/m)	47 CFR 15.209		
									Limit (dBμV/m)	Margin (dB)	Result (Pass/Fail)
0 pk 1m	0.1258	45.2	21.7	62.7	0.0	0.0	99.0	-12.8	25.6	-38.4	Pass
0 pk 1m	0.2515	16.7	22.0	57.7	0.0	0.0	99.0	-46.6	19.6	-66.2	Pass
0 pk 1m	0.3773	20.4	22.0	55.3	0.0	0.0	99.0	-45.3	16.1	-61.4	Pass
noise floor	0.503	9.8	22.1	53.1	0.0	0.0	40.0	0.8	33.6	-32.8	Pass
noise floor	0.6288	31.1	22.1	52.1	0.0	0.0	40.0	21.1	31.6	-10.5	Pass
noise floor	0.7545	15.4	22.0	51.5	0.0	0.0	40.0	4.9	30.0	-25.1	Pass
noise floor	0.8802	16.7	22.0	51.1	0.0	0.0	40.0	5.8	28.7	-22.9	Pass

## AC Line Conducted Emission Measurements

### LIMITS

Frequency of emission (MHz)	Quasi-peak limit (dBμV)	Average limit (dBμV)
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

[47 CFR 15.207(a)]

### MEASUREMENTS

AC Mains Conducted Emissions											Curtis-Straus LLC	
Date: 19-Feb-03			Company: Locknetics					Table No: 2				
Engineer: Evan Gould			EUT Desc: CM5690 (PX, FSA, ME)					Work Order: D0128				
Notes:												
Range: 0.15-30Mhz			LISN(s): Yellow-Black			Other Equipment: ---				Spectrum Analyzer: Yellow		
Frequency (MHz)	Q.P. Readings		Ave. Readings		Impedance Factor	FCC B Applicable until July 12, 2004		FCC/CISPR B		FCC/CISPR B		Overall Result (Pass/Fail)
	QP1 (dBµV)	QP2 (dBµV)	AV1 (dBµV)	AV2 (dBµV)		Limit (dBµV)	Margin dB	qp Limit (dBµV)	qp Margin dB	AVE Limit (dBµV)	AVE Margin dB	
0.22	28.4	28.6	20.0	18.0	20.0	---	---	62.8	-14.2	52.8	-12.8	Pass
2.64	19.4	20.4			20.0	47.9	-7.5	56.0	-15.6	46.0	-5.6	Pass
7.73	15.5	18.4			20.0	47.9	-9.5	60.0	-21.6	50.0	-11.6	Pass
13.60	12.9	14.0			20.0	47.9	-13.9	60.0	-26.0	50.0	-16.0	Pass
25.50	6.8	12.9			20.0	47.9	-15.0	60.0	-27.1	50.0	-17.1	Pass
29.12	10.2	13.7			20.0	47.9	-14.2	60.0	-26.3	50.0	-16.3	Pass
Table Result: Pass by -5.60 dB Worst Freq: 2.64 MHz												

## Voltage Variation

### REQUIREMENT

*"For intentional radiators, measurements of the variation of the...radiated signal level of the fundamental frequency component of the emission...shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage."* [15.31(e)]

### MEASUREMENTS

Voltage Variation			Curtis-Straus LLC					
Date: 12-Aug-03			Engineer: Evan Gould			Work Order: D0128		
Company: Locknetics			EUT: CM 5690			Fundamental Frequency: 125kHz		
Test Site: EMI 1			Antenna: Small loop			Analyzer: Blue		
Measurement Distance: ~30cm			Resolution BW: 9kHz					
Detector Type: Peak			Video BW: 120kHz					
Notes:								
Supply Voltage	Frequency (MHz)	Reading (dBμV)						
102V (85%)	0.1259	52.3						
120V (nominal)	0.1259	51.3						
138V (115%)	0.1259	51.9						

## Test Equipment Used

REV. 8/4/03

SPECTRUM ANALYZERS		RANGE	MN	MFR	SN	ASSET	CALIBRATION DUE
BLUE	9kHz-1.8GHz	8591E	HP	3223A00227	00070	04-SEP-2003	
YELLOW	9kHz-2.9GHz	8594E	HP	3523A01958	00100	08-JUL-2004	
BLACK	9kHz-12.8GHz	8596E	HP	3710A00944	00337	15-JUL-2004	
LISN		RANGE	MN	MFR	SN	ASSET	CALIBRATION DUE
YELLOW-BLACK		10kHz-30MHz	8012-50-R-24-BNC	SOLAR	984735	00248	01-APR-2004
OPEN AREA TEST SITE (OATS)			FCC CODE	IC CODE	VCCI CODE	CALIBRATION DUE	
SITE F			93448	IC 2762-F	R-468	25-MAR-2005	
LINE CONDUCTED TEST SITE			FCC CODE	IC CODE	VCCI CODE	CALIBRATION DUE	
EMI 1			93448	N/A	C-480	01-MAY-2006	
ANTENNAS	RANGE	MN	MFR	SN	ASSET	CALIBRATION DUE	
RED BILOG	30MHz-1GHz	3143	EMCO	1270	00042	17-MAR-2005	
BLUE BILOG	30MHz-1GHz	3143	EMCO	1271	00803	17-MAR-2005	
SMALL LOOP	9kHz-30MHz	PLA-130/A	ARA	1024	00755	27-JAN-2004	
PREAMP	RANGE	MN	MFR	SN	ASSET	CALIBRATION DUE	
RED	0.10-2000MHz	ZFL-1000-LN	C-S	N/A	00798	17-MAR-2004	
RMS VOLTMETERS		MN	MNFR	SN	ASSET	CALIBRATION DUE	
TRUE-RMS VOLTMETER		79III	FLUKE	71700298	00769	03-OCT-2003	

Unless otherwise noted the calibration interval is one year. All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.

## Terms And Conditions

### Paragraph 1. SERVICES. LABORATORY will:

- 1.1 Use the degree of care and skill ordinarily exercised by and consistent with the standards of the profession.
- 1.2 Perform all technical services in substantial accordance with the generally accepted laboratory principles and practices.
- 1.3 Retain all pertinent records relating to the services performed for a period of three (3) years following submission of the report describing such services, during which period the records will be made available to CLIENT upon reasonable request.

### Paragraph 2. CLIENT'S RESPONSIBILITIES. CLIENT or his authorized representative will:

- 2.1 Provide LABORATORY with all plans, schematics, specifications, addenda, change orders, drawings and other information for the proper performance of technical services.
- 2.2 Designate a person to act as CLIENT's representative with respect to LABORATORY's services to be performed on behalf of the CLIENT; such person or firm to have complete authority to transmit instructions, receive information and data, interpret and define CLIENT's policies and decisions with respect to the LABORATORY's work on behalf of the CLIENT and to order, at CLIENT's expense, such technical services as may be required.
- 2.3 Designate a person who is authorized to receive copies of LABORATORY's reports.
- 2.4 Undertake the following:
  - (a) Secure and deliver to LABORATORY, without cost to LABORATORY, preliminary representative samples of the equipment proposed to require technical services, together with any relevant data.
  - (b) Furnish such labor and equipment needed by LABORATORY to handle samples at the LABORATORY and to facilitate the specified technical services.

### Paragraph 3. GENERAL CONDITIONS:

- 3.1 LABORATORY, by the performance of services covered hereunder, does not in any way assume any of those duties or responsibilities customarily vested in the CLIENT, its employees, or any other party, agency or authority.
- 3.2 LABORATORY shall not be responsible for acts of omissions of any other party or parties involved in the design, manufacture or maintenance of the equipment or the failure of any employee, contractor or subcontractor to undertake any aspect of equipment's design, manufacture or maintenance.
- 3.3 LABORATORY is not authorized to revoke, alter, release, enlarge or release any requirement of the equipment's design, manufacture or maintenance unless specifically authorized by CLIENT or his authorized representative.
- 3.4 THE ONLY WARRANTY MADE BY LABORATORY IN CONNECTION WITH ITS SERVICE PERFORMED HEREUNDER IS THAT IT WILL USE THAT DEGREE OF CARE AND SKILL AS SET FORTH IN PARAGRAPH 1 ABOVE. NO OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE OR INTENDED FOR SERVICES PROVIDED HEREUNDER.
- 3.5 Where the LABORATORY indicates that additional testing is advisable to obtain more valid or useful data, and where such testing has not been authorized, CLIENT agrees to view such test reports as inconclusive and preliminary.
- 3.6 The LABORATORY will supply technical service and prepare a report based solely on the sample submitted to the LABORATORY by the CLIENT. The CLIENT understands that application of the data to other devices is highly speculative and should be applied with extreme caution.
- 3.7 The LABORATORY agrees to exercise ordinary care in receiving, preserving and shipping (F.O.B. Littleton, MA) any sample to be tested, but assumes no responsibility for damages, either direct or consequential, which arise from loss, damage or destruction of the samples due to the act of examination, modification or testing, or technical services or circumstances beyond LABORATORY's control.
- 3.8 The LABORATORY will hold samples for thirty (30) days after tests are completed, or until the CLIENT's outstanding debts to the LABORATORY are satisfied, whichever is later.
- 3.9 The CLIENT recognizes that generally accepted error variances apply and agrees to consider such error variances in its use of test data.
- 3.10 It is agreed between LABORATORY and CLIENT that no distribution of any tests, reports or analysis other than that described below shall be made to any third party without the prior written consent of both parties unless such distribution is mandated by operation of law. It is agreed that tests, reports, or analysis results may be disclosed to third party auditors of the laboratory at the laboratory facility in the course of accreditation maintenance audits. No reference to reports or technical services of the LABORATORY shall be made in any advertising or promotional literature without the express written permission of the LABORATORY.
- 3.11 The CLIENT acknowledges that all employees of LABORATORY operate under employment contracts with the LABORATORY and CLIENT agrees not to solicit employment of such employees or to solicit information related to other clients from said employees.
- 3.12 In recognition of the relative risks and benefits of the project to both CLIENT and LABORATORY, the risks have been allocated such that the CLIENT agrees, to the fullest extent permitted by law, to limit the liability of the LABORATORY to the CLIENT for any and all claims, losses, costs, damages of any nature whatsoever or claims expenses from any cause or causes, including attorneys' fees and costs and expert witness fees and costs, so that the total aggregate liability of the LABORATORY to the CLIENT shall not exceed \$100,000, or the LABORATORY'S total fee for services rendered on this project, whichever is greater. It is intended that this limitation apply to any and all liability or cause of action however alleged or arising, unless otherwise prohibited by law.

### Paragraph 4. INSURANCE:

- 4.1 LABORATORY shall secure and maintain throughout the full period of the services provided to the CLIENT adequate insurance to protect it from claims under applicable Workmen's Compensation Acts and also shall maintain one million dollars of general liability coverage to cover claims for bodily injury, death or property damage as may arise from the performance of its services.
- 4.2 The CLIENT hereby warrants that it has sufficient insurance to protect its employees adequately under applicable Workmen's Compensation Acts and for bodily injury, death, or property damage.
- 4.3 No insurance of whatever kind or type, which may be carried by either party is to be considered as in any way limiting any other party's responsibility for damages resulting from their operations or for furnishing work and materials.

---

**Paragraph 5. PAYMENT:**

- 5.1 CLIENT shall pay to LABORATORY such fees for services as previously agreed, orally or in writing, within 30 days of presentment of a bill for such services performed. In the event CLIENT ordered, orally or in writing, services but such services were not assigned a rate for billing, such services shall be billed at the LABORATORY's reasonable and customary rate.
- 5.2 CLIENT shall be responsible for all shipping, customs and other expenses related to services provided by LABORATORY to the CLIENT, and shall fully insure any test sample or other equipment provided to LABORATORY by the CLIENT.
- 5.3 Amounts overdue from CLIENT to LABORATORY shall be charged interest at a rate of 1½% per month.

**Paragraph 6. ISO/IEC GUIDE 17025 ADDITIONS:**

- 6.1 CLIENT agrees that this test report will not be reproduced except in full, without written approval from the LABORATORY.
- 6.2 CLIENT agrees that this test report shall not be used to claim product endorsement by A2LA or ANSI or any agency of the U.S. Government.
- 6.3 CLIENT agrees that test results presented herein relate only to the sample tested by the LABORATORY.

**A2LA Accreditation****SCOPE OF ACCREDITATION TO ISO/IEC 17025-1999**

CURTIS-STRAUS  
527 Great Road  
Littleton, MA 01460  
Jon Curtis Phone: 978-486-8880

**ELECTRICAL**

Valid until: October 31, 2003

Certificate Number: 1627-01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following Electromagnetic Compatibility (EMC), Telecommunications, and Product Safety tests:

***Electromagnetic Compatibility (EMC)***

Radiated emissions testing (electric and magnetic fields); Conducted emissions testing (voltage and current); Electrostatic Discharge testing; Electrical Fast Transient testing; Radiated Immunity testing; Conducted Immunity testing; Lightning Immunity testing; Voltage Dips, Interrupts and Voltage Variations testing; Magnetic Immunity testing; RF Power measurements; Frequency Stability measurements; Longitudinal Induction measurements; Harmonic emissions testing; Light flicker testing; Low frequency disturbance voltage testing; Disturbance Power measurements

EMC Standards Emissions	Title		
CISPR 22 1997 with amendments 1 and 2	Limits and methods of measurement of radio disturbance characteristics of information technology equipment.	CNS 13439 AS/NZS 1053: 1999	Broadcast receiver and associated equipment Limits and methods of measurement of radio interference characteristics of sound and television broadcast receivers and associated equipment.
CNS13438 1994	Limits and methods of measurement of radio interference characteristics of information technology equipment.	CISPR 14 1993	Limits and methods of measurement of radio disturbance characteristics of electrical motor-operated and thermal appliances for household and similar purposes, electric tools and electric apparatus.
EN55022:1994 and 1998	Limits and methods of measurement of radio disturbance characteristics of information technology equipment.	EN 55014 1993, 1997	Limits and methods of measurement of radio disturbance characteristics of electrical motor-operated and thermal appliances for household and similar purposes, electric tools and similar electric apparatus.
SABS CISPR 22:1997	Information technology equipment – Radio disturbance characteristics – Limits and methods of measurement	AS/NZS 1044: 1995	Limits and methods of measurement of radio disturbance characteristics of electrical motor-operated and thermal appliances for household and similar purposes, electric tools and similar electric apparatus.
Canada ICES-003 1997 AS/NZS 3548 1995	Digital apparatus Australian/New Zealand Standard Limits and methods of measurement of radio disturbance characteristics of information technology equipment		
CISPR 11 1990, 1997	Limits and methods of measurement of electromagnetic disturbance characteristics of industrial, scientific and medical (ISM) radio-frequency equipment.	Immunity CNS13783-1 SABS CISPR 14-1 1993	Household Electrical Appliances Electromagnetic compatibility – Requirements for household appliances, electric tools and similar apparatus Part 1: Emission – Product family standard
EN 55011 1991, 1998	Limits and methods of measurement of radio disturbance characteristics of industrial, scientific and medical (ISM) radio-frequency equipment.	SABS CISPR 14-2 1997	Electromagnetic compatibility – Requirements for household appliances, electric tools and similar apparatus Part 2: Immunity – Product family standard
SABS CISPR 11:1997	Industrial, scientific and medical (ISM) radio-frequency equipment – Electromagnetic disturbance characteristics Limits and methods of measurement	CISPR 14-2 1996	Immunity requirements for household appliances, tools and similar apparatus.
Canada ICES-001 1998	Industrial, scientific and medical radio frequency generators	CISPR 20 with amendment 3	Limits and methods of measurement of immunity characteristics of sound and television broadcast receivers and associated equipment.
CNS13803 AS/NZS 2064: 1997	Industrial, Scientific and Medical Instrument Limits and methods of measurement of electromagnetic disturbance characteristics of industrial, scientific and medical (ISM) radio-frequency equipment.	EN 55020 1995	Electromagnetic immunity of broadcast receivers and associated equipment.
CSA C108.8 – M1983	Electromagnetic Emission from Data Processing Equipment and Electronic Office Machines	CISPR 24	Information technology equipment – Immunity characteristics – Limits and methods of measurement
CISPR 13 1996, 1998	Limits and methods of measurement of radio interference characteristics of sound and television broadcast receivers and associated equipment.	SABS CISPR 24 1997	Information technology equipment – Immunity characteristics – Limits and methods of measurement
EN 55013 1990	Sound and television broadcast receivers and associated equipment: Electromagnetic compatibility. Part 1: Specification for limits and methods of measurement of radio disturbance characteristics of broadcast receivers and associated equipment.	AS/NZS 3200.1.2: 1995	Approval and test specification – Medical electrical Equipment – General requirements for safety – Collateral Standard: Electromagnetic compatibility – Requirements and tests.
EN 55013 Amend 12 1994	Limits and methods of measurement of radio disturbance characteristics of broadcast receivers and associated equipment. Amendment 12	European Union Basic EMC Standards EN 61000-4-2 1995, 1999	Electromagnetic compatibility (EMC). Part 4: Testing and measurement techniques. Section 2: Electrostatic discharge immunity test – Basic EMC Publication
SABS CISPR 13: 1996	Limits and methods of measurement of radio interference characteristics of sound and television broadcast receivers and associated equipment.	EN 61000-4-3 1997, 1998 AS/NZS 61000.4.3 1999	Electromagnetic compatibility (EMC). Part 4: Testing and measurement techniques. Section 3: Radiated, radio-frequency, electromagnetic field immunity test

(A2LA Cert. No. 1627-01) Revised 02/21/02

Page 2 of 9

(A2LA Cert. No. 1627-01) Revised 02/21/02

Page 3 of 9

EN 61000-4-4 1995	Electromagnetic compatibility (EMC). Part 4: Testing and measurement techniques. Section 4: Electrical fast transient/burst immunity test – Basic EMC publication	EN 61326 1998	Electrical equipment for measurement, control and laboratory use – EMC requirements
EN 61000-4-5 1995	(EMC) Part 4: Testing and measurement techniques. Section 5: Surge immunity test.	EN 61547 1996	Equipment for general lighting purposes – EMC immunity requirements
EN 61000-4-6 1996	Electromagnetic compatibility (EMC). Part 4: Testing and measurement techniques. Section 6: Immunity to conducted disturbances, induced by radio-frequency fields	EN 50130-4 1996	Alarm Systems. Part 4: Electromagnetic compatibility. Product family standard: Immunity requirements for components of fire, intruder and social alarm systems.
AS/NZS 61000.4.6 1999		EN 55104 1995	Electromagnetic compatibility immunity – requirements for household appliances, tools and similar apparatus. Product family standard.
EN 61000-4-8 1994	Electromagnetic compatibility (EMC). Part 4: Testing and measurement techniques. Section 8: Power frequency magnetic field immunity test.	EN 50083-2 1995	Cabled distribution systems for television and sound signals. Part 2: Electromagnetic compatibility for equipment.
EN 61000-4-11 1994	(EMC) Part 4: Testing and measurement techniques. Section 11: Voltage dips, short interruptions and voltage variations immunity tests.	EN 60601-1-2 1993	Medical electrical equipment Part 1: general requirements for safety Section 2: Collateral standard: Electromagnetic compatibility – requirements and tests
ENV 61000-2-2 1993	Electromagnetic compatibility (EMC). Part 2: Environment, Section 2: Compatibility levels for low-frequency conducted disturbances and signaling in public low-voltage power supply systems (IEC 1000-2-2:1990)	IEC 1800-3 1995	Adjustable speed electrical power drive systems. Part 3: EMC product standard including specific test methods.
<i>EU Product Family Standards</i>		EN 60555 Part 2 1987	Disturbances in supply systems caused by household appliances and similar electrical equipment. Part 2: Harmonics
EN 50081-1 1992	Electromagnetic capability – Generic emission standard. Part 1: Residential, commercial and light industry. (I.S.)	EN 60555 Part 3 1987	Disturbances in supply systems caused by household appliances and similar electrical equipment. Part 3: Voltage fluctuations.
EN 50081-2 1993	Electromagnetic compatibility – Generic emission standard. Part 2: Industrial environment	EN 61000-3-2 1995	Electromagnetic compatibility (EMC). Part 3: Limits
EN 50082-1 1992, 1998	Electromagnetic compatibility – Generic emission standard. Part 1: Residential, commercial and light industry	AS/NZS 61000.3.2 1998	Section 2: Limits for harmonic current emissions
EN 50082-2 1995	Electromagnetic compatibility – Generic immunity Standard. Part 2: Industrial environment	EN 61000-3-3 1995	Electromagnetic compatibility (EMC). Part 3: Limits
EN 61000-6-1 1997	Electromagnetic Compatibility (EMC). Part 6: Generic standards- Section 1: Immunity for residential, commercial and light-industrial environments	AS/NZS 61000.3.3 1999	Section 2: Limitation of voltage fluctuations and flicker in low-voltage supply systems.
EN 61000-6-2 1998	Electromagnetic Compatibility (EMC). Part 6: Generic standards- Section 2: Immunity for industrial environments	ETS 300 386-1 1994	Equipment Engineering (EE); Public telecommunication network equipment electromagnetic compatibility (EMC) requirements Part 1: Product family overview, compliance criteria and test levels
EN 50091-2 1996	Specification for Uninterruptible Power Systems (UPS). Part 2: EMC requirements	ETS EN 300 386-2 1997, 1998	Electromagnetic compatibility and radio spectrum matters (ERM); Telecommunication network equipment; Electromagnetic compatibility (EMC) requirements; Part 2: Product family standard.
EN 55024 1998	Information technology equipment – Immunity Characteristics – Limits and methods of measurement.	ETS 300 132-1 1996	Equipment Engineering (EE); Power supply interface at the input to telecommunications equipment; Part 1: Operated by alternating current (ac) derived from direct current (dc) sources
EN 55103-1 1997	Electromagnetic Compatibility – Product family standard for audio, video, audio-visual and entertainment lighting control apparatus for professional use. Part 1: Emission	ETS 300 132-2 1996	Equipment Engineering (EE); Power supply interface at the input to telecommunications equipment; Part 2: Operated by direct current (dc)
EN 55103-2 1997	Electromagnetic Compatibility – Product family standard for audio, video, audio-visual and entertainment lighting control professional use. Part 2: Immunity	ETR 283 1997	Equipment Engineering (EE); Transient voltages at Interface A on telecommunications direct current (DC) power distributions.
(A2LA Cert. No. 1627-01) Revised 02/21/02	<i>Pete. Hlop-</i> Page 4 of 9	(A2LA Cert. No. 1627-01) Revised 02/21/02	<i>Pete. Hlop-</i> Page 5 of 9
<i>EU radio standards</i>		47 CFR FCC Unlicensed Personal Communications System (PCS) devices	Scope A3
(ETS) EN 300 385 v1.2.1 1998	Electromagnetic compatibility and Radio spectrum matters (ERM); ElectroMagnetic Compatibility (EMC) standard for fixed radio links and ancillary equipment	47 CFR FCC Unlicensed National Information Infrastructure devices and low power transmitters using spread spectrum techniques.	Scope A4
(ETS) EN 300 220-1 v1.2.1 1997	Electromagnetic compatibility and Radio spectrum matters (ERM); Short range devices; Technical characteristics and test methods for radio equipment to be used in the 25 MHz to 1000 MHz frequency range with power levels ranging up to 500 mW; Part 1: Parameters intended for regulatory purposes	47 CFR FCC Personal mobile Radio Services in the following FCC Rule Parts 22, 24, 25, 27.	Scope B1
(ETS) EN 300 220-2 v1.2.1 1997	Electromagnetic compatibility and Radio spectrum matters (ERM); Short range devices; Technical characteristics and test methods for radio equipment to be used in the 25 MHz to 1000 MHz frequency range with power levels ranging up to 500 mW; Part 2: Supplementary parameters not intended for regulatory purposes	47 CFR FCC General Mobile Radio Services in the following FCC Rule Parts 22, 74, 90, 95, 97.	Scope B2
(ETS) EN 300 330 v1.2.1 1998	Electromagnetic compatibility and Radio spectrum matters (ERM); Short range devices (SRD); Technical characteristics and test methods for radio equipment in the range 9 kHz to 25 MHz and inductive loop systems in the frequency range 9 kHz to 30 MHz	47 CFR FCC Maritime and Aviation RadioServices in 47 CFR Parts 80 and 87	Scope B3
ETS 300 328 1996	Radio Equipment and Systems (RES); Wideband transmission systems; Technical characteristics and test conditions for data transmission equipment operating in the 2.4 GHz ISM band and using spread spectrum modulation techniques	47 CFR FCC Microwave Radio Services in 47 CFR Parts 21, 74 and 101.	Scope B4
ETS EN 300 440 v1.2.1 1999	Electromagnetic compatibility and Radio spectrum matters (ERM); Short range devices; Technical characteristics and test methods for radio equipment to be used in the 1 GHz to 40 GHz frequency range	FCC/OST MP-5 1986	FCC (Federal Communications Commission) methods of measurement of radio noise emissions from industrial, scientific and medical equipment.
<i>Canada Radio Standards</i>		GR-1089-CORE 1997, 1999	Bellcore electromagnetic compatibility and electrical safety – Generic criteria for network telecommunications equipment.
Canadian GL-36 1995	Industry Canada – technical requirements for low power Devices in the 2400 – 2483.5 MHz band.	<i>ANSI EMC Standards</i>	
Canadian RSS-119 1996	Industry Canada – Land mobile and fixed radio transmitters and receivers, 27.41 to 960.0 MHz	ANSI C63.4 1992, 1999	American National Standard of methods of measurement of radio-noise emissions for low-voltage electrical and electronic equipment in the range of 9 kHz to 40GHz.
Canadian RSS-134 1996	Industry Canada – 900 MHz narrowband personal communications services	ANSI C63.5 1988	American National Standard for electromagnetic compatibility – radiated emissions measurements in electromagnetic interference (EMI) control – calibration of antennas.
Canadian RSS-210 Issue 3, Feb 5, 2000	Industry Canada – Low power license-exempt radio communication devices	<i>IEEE EMC Standards</i>	
RFS29 1998	Specification for Restricted Radiation Radio Apparatus (New Zealand)	IEEE C62.41 1980	IEEE recommended practice on surge voltages in low-voltage AC power circuits
<i>FCC Standards</i>		<i>Swedish EMC Standards</i>	
47 CFR FCC low power transmitters operating on frequencies below 1 GHz, emergency alert systems, unintentional radiators and ISM devices.	Scope A1	BAKOM 3336.3 1995	Electromagnetic compatibility and electrical safety (EMC & S) for wired terminal equipment. Harmonization documentation information over the OFCOM requirements.
47 CFR FCC low power transmitters operating on frequencies above 1 GHz, with the exception of spread spectrum devices.	Scope A2	<i>South African EMC standards other than CISPR equivalents</i>	
(A2LA Cert. No. 1627-01) Revised 02/21/02	<i>Pete. Hlop-</i> Page 6 of 9	SABS 1718-1: 1996	South African Bureau of Standards: Specification for Gaming equipment. Part 1: Casino equipment.
		<i>Japanese VCCI Standards</i>	
		VCCI V-3/99.05 1999	Technical Requirements
		VCCI V-4/99.05 1999	Instruction for Test Conditions for Requirement under test
		(A2LA Cert. No. 1627-01) Revised 02/21/02	<i>Pete. Hlop-</i> Page 7 of 9

**Telecommunications**

Telecommunications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing; Protocol analysis and Jitter testing.

Telecom Standards	Title		
FCC 47 CFR Part 68 Telephone Terminal Equipment	Connection of terminal equipment to the telephone network. Analog and Digital Equipment. TCB Scope C1.	TBR 013 : 1996	Business TeleCommunications (BTC); 2 048 kbit/s digital structured leased lines (D2048S); Attachment requirements for terminal equipment interface
CS-03 Issue 8 1996 through amendment 3	Specification for terminal equipment, terminal systems, Network protection devices, connection arrangements and hearing aids compatibility. Bulletin Part 68 Rationale and Measurement Guidelines (Feb 1998)	TBR 21 : 1998	Terminal Equipment (TE); Attachment requirements for pan-European approval for connection to the analogue Public Switched Telephone Networks (PSTNs) of TE (excluding TE supporting the voice telephony service) in which network addressing, if provided, is by means of Dual Tone Multi Frequency (DTMF) signaling
TIA/EIA TSB31-B 1998	Attachment requirements for terminal equipment to be connected to circuit switched data networks and leased circuits using a CCITT Recommendation X.21 interface, or at an interface physically, functionally and electrically compatible with CCITT Recommendation X.21 but operating at any data signalling rate up to, and including, 1 984 kbit/s	TBR 24 : 1997	Business TeleCommunications (BTC); 34 Mbit/s digital unstructured and structured leased lines (D34U and D34S); Attachment requirements for terminal equipment interface
TBR 1 : 1995	Attachment requirements for Data Terminal Equipment (DTE) to connect to Packet Switched Public Data Networks (PSPDNs) for CCITT Recommendation X.25 interfaces at data signalling rates up to 1 920 kbit/s utilizing interfaces derived from CCITT Recommendations X.21 and X.21 bis Integrated Services Digital Network (ISDN);	Australia TS 002 : 1997	Analogue Interworking and Non interference Requirements for Customer Equipment Connected to the Public Switched Telephone Network
TBR 2 : 1997	Attachment requirements for terminal equipment to connect to an ISDN using ISDN basic access Integrated Services Digital Network (ISDN);	TS 016 : 1997	General Requirements for Customer Equipment Connected to Hierarchical Digital Interfaces
TBR 3 : 1995 + Amdt : 1997	Attachment requirements for terminal equipment to connect to an ISDN using ISDN primary rate access Business TeleCommunications (BT); Open Network Provision (ONP) technical requirements; 2 048 kbit/s digital unstructured leased line (D2048U) Attachment requirements for terminal equipment	TS 031 : 1997 TS 038 : 1997	Requirements for ISDN Basic Access Interface Requirements for ISDN Primary Rate Access Interface
TBR 4 : 1995 + Amdt : 1997		AS/ACIF S043.2:2001	Requirements for Customer Equipment for connection to a metallic loop interface of a Telecommunications Network – Part 2
TBR 012 : 1993 + Amdt : 1996			Broadband
(A2LA Cert. No. 1627-01) Revised 02/21/02			<i>Pete. Rhye</i> Page 8 of 9

**Product Safety**

General test methods; Input tests; Electric strength tests; Impulse tests; Permanency of marking tests; Accessibility tests; Energy Hazard measurements; Capacitor discharge tests; Humidity conditioning; Earthing tests; Limited power source measurements; Stability tests; Steel ball tests; Lithium Battery Reverse Current measurements; Leakage current tests; Transformer abnormal tests; Telecom leakage tests; Overvoltage/power cross tests.

Product Safety Standards	Title		
<b>Specific Product Safety Standards</b> IEC 950 1991 Includes Amendments 1, 2, 3 and 4 UL 1950 1998	Safety of information technology equipment including electrical business equipment. Safety of information technology equipment, including electrical business equipment.	UL 3111-1 1996 UL 3121-1 1995 IEC 60601-1 1995	Electrical measuring and test equipment. Part 1: General requirements. Medical electrical equipment. Part 1: General requirements for safety.
CSA C22.2 No.950-95	Safety of Information Technology Equipment (UL 1950)	EN 60601-1 UL 2601-1 1997	Medical electrical equipment. Part 1: General Requirements for safety.
UL 60950 2000 IEC 60950 2000 EN 60950 1997, 1998 IEC 60950-1 2001 AS/NZS 3260 1993	Safety of information technology equipment Safety of information technology equipment Safety of information technology equipment, including Electrical business equipment. Approval and test specification – Safety of information technology equipment including electrical business Equipment.	IEC 60065 1998, 2000 ANSI/UL 6500: 1998 CAN/CSA 60065-00 AS/NZS 3250 1995 AS/NZS 60065 2000	Audio, video and similar electronic apparatus – Safety requirements Audio/video and musical instrument apparatus for Household, commercial and similar general use Australian/New Zealand Standard – Approval and test Specification – Mains operated electronic and related Equipment for household and similar general use
AS/NZS 3260 Supp 1 1996	Approval and test specification – Safety of information technology equipment including electrical business equipment – Alphabetical reference index to IEC 950 (Supplement to AS/NZS 3260:1993)	Canadian C22.2 No. 1-94 (1-98) 1994, 1998 EN 60065 1994	Audio, video and similar electronic equipment. Consumer and commercial products Safety requirements for main operated electronic and related apparatus for household and similar general use.
ACA TS 001 1997	Australian Communications Authority – Safety requirements for customer equipment. Telephone Equipment	IEC 60825 1990	Radiation safety of laser products, equipment Classification, requirements and user's guide
UL 1459 1995 IEC 1010-1 1990 IEC 61010-1 1993	Safety requirements for electrical equipment for measurement, control and laboratory use, Part 1: General requirements.	EN 60825-1 1994 IEC 60825-1 2001 IEC 60825-2 2000-5	Safety of laser products Part 1: equipment Classification, requirements and user's guide. Safety of laser products – Part 2: Safety of optical communication systems
EN 61010-1 1993 IEC 61010-1 2000	Safety requirements for electrical equipment for measurement, control and laboratory use, Part 1: General requirements.	IEC 60825-4 1997-11 IEC 60335-1 1995 (Including AM2 – 1997 & AM 12 – 1997)	Safety of laser products – Part 4: Laser guards Safety of household and similar electrical appliances Part 1: General requirements
UL 3101-1 1993 CAN/CSA 1010-1 1999 (Including AM 2)	Electrical equipment for laboratory use Part 1: General requirements.	EN 60335-1 2001 UL 60335-1 1998 CAN/CSA E335-1 1994	
(A2LA Cert. No. 1627-01) Revised 02/21/02			<i>Pete. Rhye</i> Page 9 of 9