

## FCC Test Report (Part 24)

**Report No.:** RF181015C09-1

**FCC ID:** PY318300428

**Test Model:** MR5000

**Received Date:** Oct. 15, 2018

**Test Date:** Oct. 22 ~ Nov. 03, 2018

**Issued Date:** Nov. 15, 2018

**Applicant:** NETGEAR INC.

**Address:** 350 East Plumeria Drive, San Jose, CA 95134, USA

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)

**Test Location:** No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)

**FCC Registration / Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies

## Table of Contents

|                                                          |           |
|----------------------------------------------------------|-----------|
| <b>Release Control Record</b>                            | <b>4</b>  |
| <b>1 Certificate of Conformity</b>                       | <b>5</b>  |
| <b>2 Summary of Test Results</b>                         | <b>6</b>  |
| 2.1 Measurement Uncertainty                              | 6         |
| 2.2 Test Site and Instruments                            | 7         |
| <b>3 General Information</b>                             | <b>8</b>  |
| 3.1 General Description of EUT                           | 8         |
| 3.2 Configuration of System under Test                   | 10        |
| 3.2.1 Description of Support Units                       | 10        |
| 3.3 Test Mode Applicability and Tested Channel Detail    | 11        |
| 3.4 EUT Operating Conditions                             | 13        |
| 3.5 General Description of Applied Standards             | 13        |
| <b>4 Test Types and Results</b>                          | <b>14</b> |
| 4.1 Output Power Measurement                             | 14        |
| 4.1.1 Limits of Output Power Measurement                 | 14        |
| 4.1.2 Test Procedures                                    | 14        |
| 4.1.3 Test Setup                                         | 15        |
| 4.1.4 Test Results                                       | 16        |
| 4.2 Modulation Characteristics Measurement               | 40        |
| 4.2.1 Limits of Modulation Characteristics               | 40        |
| 4.2.2 Test Procedure                                     | 40        |
| 4.2.3 Test Setup                                         | 40        |
| 4.2.4 Test Results                                       | 41        |
| 4.3 Frequency Stability Measurement                      | 42        |
| 4.3.1 Limits of Frequency Stability Measurement          | 42        |
| 4.3.2 Test Procedure                                     | 42        |
| 4.3.3 Test Setup                                         | 42        |
| 4.3.4 Test Results                                       | 43        |
| 4.4 Occupied Bandwidth Measurement                       | 49        |
| 4.4.1 Test Procedure                                     | 49        |
| 4.4.2 Test Setup                                         | 49        |
| 4.4.3 Test Result                                        | 50        |
| 4.5 Band Edge Measurement                                | 53        |
| 4.5.1 Limits of Band Edge Measurement                    | 53        |
| 4.5.2 Test Setup                                         | 53        |
| 4.5.3 Test Procedures                                    | 53        |
| 4.5.4 Test Results                                       | 54        |
| 4.6 Peak to Average Ratio                                | 60        |
| 4.6.1 Limits of Peak to Average Ratio Measurement        | 60        |
| 4.6.2 Test Setup                                         | 60        |
| 4.6.3 Test Procedures                                    | 60        |
| 4.6.4 Test Results                                       | 61        |
| 4.7 Conducted Spurious Emissions                         | 63        |
| 4.7.1 Limits of Conducted Spurious Emissions Measurement | 63        |
| 4.7.2 Test Setup                                         | 63        |
| 4.7.3 Test Procedure                                     | 63        |
| 4.7.4 Test Results                                       | 64        |
| 4.8 Radiated Emission Measurement                        | 82        |
| 4.8.1 Limits of Radiated Emission Measurement            | 82        |
| 4.8.2 Test Procedure                                     | 82        |
| 4.8.3 Deviation from Test Standard                       | 82        |
| 4.8.4 Test Setup                                         | 83        |
| 4.8.5 Test Results                                       | 84        |

|          |                                                                 |           |
|----------|-----------------------------------------------------------------|-----------|
| <b>5</b> | <b>Pictures of Test Arrangements.....</b>                       | <b>96</b> |
|          | <b>Appendix – Information on the Testing Laboratories .....</b> | <b>97</b> |

### Release Control Record

| Issue No.     | Description       | Date Issued   |
|---------------|-------------------|---------------|
| RF181015C09-1 | Original release. | Nov. 15, 2018 |

## 1 Certificate of Conformity

**Product:** 5G MHS Travel Router

**Brand:** Netgear

**Test Model:** MR5000

**Sample Status:** Engineering sample

**Applicant:** NETGEAR INC.

**Test Date:** Oct. 22 ~ Nov. 03, 2018

**Standards:** FCC Part 24, Subpart E

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

**Prepared by :**  , **Date:** Nov. 15, 2018  
Polly Chien / Specialist

**Approved by :**  , **Date:** Nov. 15, 2018  
Bruce Chen / Project Engineer

## 2 Summary of Test Results

| Applied Standard: FCC Part 24 & Part 2 |                              |        |                                                                                  |
|----------------------------------------|------------------------------|--------|----------------------------------------------------------------------------------|
| FCC Clause                             | Test Item                    | Result | Remarks                                                                          |
| 2.1046<br>24.232                       | Effective radiated power     | Pass   | Meet the requirement of limit.                                                   |
| 2.1046<br>24.232(d)                    | Peak To Average Ratio        | Pass   | Meet the requirement of limit.                                                   |
| 2.1047                                 | Modulation characteristics   | Pass   | Meet the requirement                                                             |
| 2.1055<br>24.235                       | Frequency Stability          | Pass   | Meet the requirement of limit.                                                   |
| 2.1049<br>24.238(b)                    | Occupied Bandwidth           | Pass   | Meet the requirement of limit.                                                   |
| 24.238(b)                              | Band Edge Measurements       | Pass   | Meet the requirement of limit.                                                   |
| 2.1051<br>24.238                       | Conducted Spurious Emissions | Pass   | Meet the requirement of limit.                                                   |
| 2.1053<br>24.238                       | Radiated Spurious Emissions  | Pass   | Meet the requirement of limit.<br>Minimum passing margin is -30.2dB at 62.98MHz. |

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement                    | Frequency       | Expanded Uncertainty (k=2) ( $\pm$ ) |
|--------------------------------|-----------------|--------------------------------------|
| Radiated Emissions up to 1 GHz | 30MHz ~ 200MHz  | 3.59 dB                              |
|                                | 200MHz ~1000MHz | 3.60 dB                              |
| Radiated Emissions above 1 GHz | 1GHz ~ 18GHz    | 2.29 dB                              |
|                                | 18GHz ~ 40GHz   | 2.29 dB                              |

## 2.2 Test Site and Instruments

| Description & Manufacturer                    | Model No.                          | Serial No.                      | Cal. Date     | Cal. Due      |
|-----------------------------------------------|------------------------------------|---------------------------------|---------------|---------------|
| Test Receiver<br>KEYSIGHT                     | N9038A                             | MY55420137                      | Apr. 11, 2018 | Apr. 10, 2019 |
| Spectrum Analyzer<br>ROHDE & SCHWARZ          | FSP40                              | 100269                          | May 29, 2018  | May 28, 2019  |
| BILOG Antenna<br>SCHWARZBECK                  | VULB9168                           | 9168-148                        | Dec. 11, 2017 | Dec. 10, 2018 |
| HORN Antenna<br>SCHWARZBECK                   | BBHA 9120 D                        | 9120D-1169                      | Dec. 12, 2017 | Dec. 11, 2018 |
| HORN Antenna<br>SCHWARZBECK                   | BBHA 9170                          | BBHA9170241                     | Dec. 01, 2017 | Nov. 30, 2018 |
| Loop Antenna<br>EMCI                          | EM-6879                            | 269                             | Sep. 07, 2018 | Sep. 06, 2019 |
| Preamplifier<br>Agilent<br>(Below 1GHz)       | 8447D                              | 2944A10638                      | Aug. 08, 2018 | Aug. 07, 2019 |
| Preamplifier<br>Agilent<br>(Above 1GHz)       | 8449B                              | 3008A01638                      | Feb. 22, 2018 | Feb. 21, 2019 |
| RF signal cable<br>HUBER+SUHNER&EMCI          | SUCOFLEX 104 &<br>EMC104-SM-SM8000 | CABLE-CH9-02<br>(248780+171006) | Jan. 15, 2018 | Jan. 14, 2019 |
| RF signal cable<br>HUBER+SUHNER               | SUCOFLEX 104                       | CABLE-CH9-(250795/4)            | Aug. 08, 2018 | Aug. 07, 2019 |
| RF signal cable<br>Woken                      | 8D-FB                              | Cable-CH9-01                    | Jul. 31, 2018 | Jul. 30, 2019 |
| Software<br>BV ADT                            | ADT_Radiated_<br>V7.6.15.9.5       | NA                              | NA            | NA            |
| Antenna Tower<br>EMCO                         | 2070/2080                          | 512.835.4684                    | NA            | NA            |
| Turn Table<br>EMCO                            | 2087-2.03                          | NA                              | NA            | NA            |
| Antenna Tower & Turn<br>BV ADT                | AT100                              | AT93021705                      | NA            | NA            |
| Turn Table<br>BV ADT                          | TT100                              | TT93021705                      | NA            | NA            |
| Turn Table Controller<br>BV ADT               | SC100                              | SC93021705                      | NA            | NA            |
| Boresight Antenna Fixture                     | FBA-01                             | FBA-SIP01                       | NA            | NA            |
| Turn Table Controller<br>BV ADT               | SC100                              | SC93021702                      | NA            | NA            |
| Temperature And Humidity<br>Chamber<br>TERCHY | HRM-120RF                          | 931022                          | Nov. 20, 2017 | Nov. 19, 2018 |
| JFW 20dB attenuation                          | 50HF-020-SMA                       | NA                              | NA            | NA            |
| Radio Communication<br>Analyzer               | MT8821C                            | 6261786083                      | Dec. 21, 2017 | Dec. 20, 2018 |

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 9.
3. The FCC Designation Number is TW0003. The number will be varied with the Lab location and scope as attached.
4. The IC Site Registration No. is 7450F-9.

### 3 General Information

#### 3.1 General Description of EUT

|                     |                                       |                        |                        |                        |
|---------------------|---------------------------------------|------------------------|------------------------|------------------------|
| Product             | 5G MHS Travel Router                  |                        |                        |                        |
| Brand               | Netgear                               |                        |                        |                        |
| Test Model          | MR5000                                |                        |                        |                        |
| Sample Status       | Engineering sample                    |                        |                        |                        |
| Power Supply        | 5.0 Vdc or 9Vdc (adapter)             |                        |                        |                        |
| Rating              | 3.85Vdc (battery)                     |                        |                        |                        |
| Modulation Type     | QPSK, 16QAM, 64QAM                    |                        |                        |                        |
| Operating Frequency | LTE Band 2 (Channel Bandwidth 1.4MHz) | 1850.7MHz ~ 1909.3MHz  |                        |                        |
|                     | LTE Band 2 (Channel Bandwidth 3MHz)   | 1851.5MHz ~ 1908.5MHz  |                        |                        |
|                     | LTE Band 2 (Channel Bandwidth 5MHz)   | 1852.5MHz ~ 1907.5MHz  |                        |                        |
|                     | LTE Band 2 (Channel Bandwidth 10MHz)  | 1855.0MHz ~ 1905.0MHz  |                        |                        |
|                     | LTE Band 2 (Channel Bandwidth 15MHz)  | 1857.5MHz ~ 1902.5MHz  |                        |                        |
|                     | LTE Band 2 (Channel Bandwidth 20MHz)  | 1860.0MHz ~ 1900.0MHz  |                        |                        |
| Max. EIRP Power     |                                       | QPSK                   | 16QAM                  | 64QAM                  |
|                     | LTE Band 2 (Channel Bandwidth 1.4MHz) | 562.341mW<br>(27.5dBm) | 457.088mW<br>(26.6dBm) | 398.107mW<br>(26.0dBm) |
|                     | LTE Band 2 (Channel Bandwidth 3MHz)   | 616.595mW<br>(27.9dBm) | 512.861mW<br>(27.1dBm) | 446.684mW<br>(26.5dBm) |
|                     | LTE Band 2 (Channel Bandwidth 5MHz)   | 588.844mW<br>(27.7dBm) | 457.088mW<br>(26.6dBm) | 426.580mW<br>(26.3dBm) |
|                     | LTE Band 2 (Channel Bandwidth 10MHz)  | 549.541mW<br>(27.4dBm) | 426.580mW<br>(26.3dBm) | 380.189mW<br>(25.8dBm) |
|                     | LTE Band 2 (Channel Bandwidth 15MHz)  | 549.541mW<br>(27.4dBm) | 446.684mW<br>(26.5dBm) | 407.380mW<br>(26.1dBm) |
|                     | LTE Band 2 (Channel Bandwidth 20MHz)  | 588.844mW<br>(27.7dBm) | 467.735mW<br>(26.7dBm) | 407.380mW<br>(26.1dBm) |
| Emission Designator |                                       | QPSK                   | 16QAM                  | 64QAM                  |
|                     | LTE Band 2 (Channel Bandwidth 1.4MHz) | 1M09G7D                | 1M09D7W                | 1M09D7W                |
|                     | LTE Band 2 (Channel Bandwidth 3MHz)   | 2M71G7D                | 2M70D7W                | 2M71D7W                |
|                     | LTE Band 2 (Channel Bandwidth 5MHz)   | 4M49G7D                | 4M49D7W                | 4M49D7W                |
|                     | LTE Band 2 (Channel Bandwidth 10MHz)  | 8M98G7D                | 8M98D7W                | 8M97D7W                |
|                     | LTE Band 2 (Channel Bandwidth 15MHz)  | 13M5G7D                | 13M4D7W                | 13M4D7W                |
|                     | LTE Band 2 (Channel Bandwidth 20MHz)  | 18M0G7D                | 18M0D7W                | 18M0D7W                |
| Antenna Type        | Internal IFA antenna with 2.73dBi     |                        |                        |                        |
| Antenna Connector   | NA                                    |                        |                        |                        |
| Accessory Device    | Adapter, battery                      |                        |                        |                        |
| Data Cable Supplied | 0.95m shielded USB cable without core |                        |                        |                        |


Note:

1. The EUT consumes power from the following adapter and battery.

| Adapter |                            |
|---------|----------------------------|
| Brand   | NETGEAR                    |
| Model   | AD2122F20                  |
| P/N     | 332-11106-01               |
| Input   | 100-240Vac, 50/60Hz, 0.5A  |
| Output  | 5.0Vdc, 2.0A or 9Vdc /1.8A |

| Lithium ion battery |                           |
|---------------------|---------------------------|
| Brand               | NETGEAR                   |
| Model               | W-10a                     |
| P/N                 | 308-10084-01              |
| Rating              | 3.85Vdc, 19.78Wh, 5040mAh |

### 3.2 Configuration of System under Test



#### 3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| ID | Product                    | Brand   | Model No. | Serial No. | FCC ID | Remarks |
|----|----------------------------|---------|-----------|------------|--------|---------|
| A. | Radio Communication Tester | Anritsu | MT8820C   | 6201010284 | NA     | -       |

Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item A acted as a communication partner to transfer data.

### 3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on X-plane. Following channel(s) was (were) selected for the final test as listed below:

#### LTE Band 2

| EUT Configure Mode | Test item                  | Available channel | Tested Channel                                                | Channel Bandwidth | Modulation           | Mode                |
|--------------------|----------------------------|-------------------|---------------------------------------------------------------|-------------------|----------------------|---------------------|
| -                  | EIRP                       | 18607 to 19193    | 18607(1850.70MHz),<br>18900(1880.00MHz),<br>19193(1909.30MHz) | 1.4MHz            | QPSK / 16QAM / 64QAM | 1 RB / 5 RB Offset  |
|                    |                            | 18615 to 19185    | 18615(1851.50MHz),<br>18900(1880.00MHz),<br>19185(1908.50MHz) | 3MHz              | QPSK / 16QAM / 64QAM | 1 RB / 14 RB Offset |
|                    |                            | 18625 to 19175    | 18625(1852.50MHz),<br>18900(1880.00MHz),<br>19175(1907.50MHz) | 5MHz              | QPSK / 16QAM / 64QAM | 1 RB / 24 RB Offset |
|                    |                            | 18650 to 19150    | 18650(1855.00MHz),<br>18900(1880.00MHz),<br>19150(1905.00MHz) | 10MHz             | QPSK / 16QAM / 64QAM | 1 RB / 49 RB Offset |
|                    |                            | 18675 to 19125    | 18675(1857.50MHz),<br>18900(1880.00MHz),<br>19125(1902.50MHz) | 15MHz             | QPSK / 16QAM / 64QAM | 1 RB / 74 RB Offset |
|                    |                            | 18700 to 19100    | 18700(1860.00MHz),<br>18900(1880.00MHz),<br>19100(1900.00MHz) | 20MHz             | QPSK / 16QAM / 64QAM | 1 RB / 99 RB Offset |
| -                  | Modulation characteristics | 18700 to 19100    | 18900(1880.00MHz)                                             | 20MHz             | QPSK / 16QAM / 64QAM | 1 RB / 99 RB Offset |
| -                  | Frequency Stability        | 18607 to 19193    | 18607(1850.70MHz),<br>19193(1909.30MHz)                       | 1.4MHz            | QPSK                 | 1 RB / 5 RB Offset  |
|                    |                            | 18615 to 19185    | 18615(1851.50MHz),<br>19185(1908.50MHz)                       | 3MHz              | QPSK                 | 1 RB / 14 RB Offset |
|                    |                            | 18625 to 19175    | 18625(1852.50MHz),<br>19175(1907.50MHz)                       | 5MHz              | QPSK                 | 1 RB / 24 RB Offset |
|                    |                            | 18650 to 19150    | 18650(1855.00MHz),<br>19150(1905.00MHz)                       | 10MHz             | QPSK                 | 1 RB / 49 RB Offset |
|                    |                            | 18675 to 19125    | 18675(1857.50MHz),<br>19125(1902.50MHz)                       | 15MHz             | QPSK                 | 1 RB / 74 RB Offset |
|                    |                            | 18700 to 19100    | 18700(1860.00MHz),<br>19100(1900.00MHz)                       | 20MHz             | QPSK                 | 1 RB / 99 RB Offset |
| -                  | Occupied Bandwidth         | 18607 to 19193    | 18607(1850.70MHz),<br>18900(1880.00MHz),<br>19193(1909.30MHz) | 1.4MHz            | QPSK / 16QAM / 64QAM | 1 RB / 5 RB Offset  |
|                    |                            | 18615 to 19185    | 18615(1851.50MHz),<br>18900(1880.00MHz),<br>19185(1908.50MHz) | 3MHz              | QPSK / 16QAM / 64QAM | 1 RB / 14 RB Offset |
|                    |                            | 18625 to 19175    | 18625(1852.50MHz),<br>18900(1880.00MHz),<br>19175(1907.50MHz) | 5MHz              | QPSK / 16QAM / 64QAM | 1 RB / 24 RB Offset |
|                    |                            | 18650 to 19150    | 18650(1855.00MHz),<br>18900(1880.00MHz),<br>19150(1905.00MHz) | 10MHz             | QPSK / 16QAM / 64QAM | 1 RB / 49 RB Offset |
|                    |                            | 18675 to 19125    | 18675(1857.50MHz),<br>18900(1880.00MHz),<br>19125(1902.50MHz) | 15MHz             | QPSK / 16QAM / 64QAM | 1 RB / 74 RB Offset |
|                    |                            | 18700 to 19100    | 18700(1860.00MHz),<br>18900(1880.00MHz),<br>19100(1900.00MHz) | 20MHz             | QPSK / 16QAM / 64QAM | 1 RB / 99 RB Offset |

| EUT Configure Mode | Test item                    | Available channel | Tested Channel                                                | Channel Bandwidth | Modulation              | Mode                                                              |
|--------------------|------------------------------|-------------------|---------------------------------------------------------------|-------------------|-------------------------|-------------------------------------------------------------------|
| -                  | Band Edge                    | 18607 to 19193    | 18607(1850.70MHz),<br>19193(1909.30MHz)                       | 1.4MHz            | QPSK                    | 1 RB / 0 RB Offset<br>1 RB / 5 RB Offset<br>6 RB / 0 RB Offset    |
|                    |                              | 18615 to 19185    | 18615(1851.50MHz),<br>19185(1908.50MHz)                       | 3MHz              | QPSK                    | 1 RB / 0 RB Offset<br>1 RB / 14 RB Offset<br>15 RB / 0 RB Offset  |
|                    |                              | 18625 to 19175    | 18625(1852.50MHz),<br>19175(1907.50MHz)                       | 5MHz              | QPSK                    | 1 RB / 0 RB Offset<br>1 RB / 24 RB Offset<br>25 RB / 0 RB Offset  |
|                    |                              | 18650 to 19150    | 18650(1855.00MHz),<br>19150(1905.00MHz)                       | 10MHz             | QPSK                    | 1 RB / 0 RB Offset<br>1 RB / 49 RB Offset<br>50 RB / 0 RB Offset  |
|                    |                              | 18675 to 19125    | 18675(1857.50MHz),<br>19125(1902.50MHz)                       | 15MHz             | QPSK                    | 1 RB / 0 RB Offset<br>1 RB / 74 RB Offset<br>75 RB / 0 RB Offset  |
|                    |                              | 18700 to 19100    | 18700(1860.00MHz),<br>19100(1900.00MHz)                       | 20MHz             | QPSK                    | 1 RB / 0 RB Offset<br>1 RB / 99 RB Offset<br>100 RB / 0 RB Offset |
| -                  | Peak to Average Ratio        | 18607 to 19193    | 18607(1850.70MHz),<br>18900(1880.00MHz),<br>19193(1909.30MHz) | 1.4MHz            | QPSK / 16QAM /<br>64QAM | 1 RB / 5 RB Offset                                                |
|                    |                              | 18615 to 19185    | 18615(1851.50MHz),<br>18900(1880.00MHz),<br>19185(1908.50MHz) | 3MHz              | QPSK / 16QAM /<br>64QAM | 1 RB / 14 RB Offset                                               |
|                    |                              | 18625 to 19175    | 18625(1852.50MHz),<br>18900(1880.00MHz),<br>19175(1907.50MHz) | 5MHz              | QPSK / 16QAM /<br>64QAM | 1 RB / 24 RB Offset                                               |
|                    |                              | 18650 to 19150    | 18650(1855.00MHz),<br>18900(1880.00MHz),<br>19150(1905.00MHz) | 10MHz             | QPSK / 16QAM /<br>64QAM | 1 RB / 49 RB Offset                                               |
|                    |                              | 18675 to 19125    | 18675(1857.50MHz),<br>18900(1880.00MHz),<br>19125(1902.50MHz) | 15MHz             | QPSK / 16QAM /<br>64QAM | 1 RB / 74 RB Offset                                               |
|                    |                              | 18700 to 19100    | 18700(1860.00MHz),<br>18900(1880.00MHz),<br>19100(1900.00MHz) | 20MHz             | QPSK / 16QAM /<br>64QAM | 1 RB / 99 RB Offset                                               |
| -                  | Conducted Emission           | 18607 to 19193    | 18607(1850.70MHz),<br>18900(1880.00MHz),<br>19193(1909.30MHz) | 1.4MHz            | QPSK                    | 1 RB / 5 RB Offset                                                |
|                    |                              | 18615 to 19185    | 18615(1851.50MHz),<br>18900(1880.00MHz),<br>19185(1908.50MHz) | 3MHz              | QPSK                    | 1 RB / 14 RB Offset                                               |
|                    |                              | 18625 to 19175    | 18625(1852.50MHz),<br>18900(1880.00MHz),<br>19175(1907.50MHz) | 5MHz              | QPSK                    | 1 RB / 24 RB Offset                                               |
|                    |                              | 18650 to 19150    | 18650(1855.00MHz),<br>18900(1880.00MHz),<br>19150(1905.00MHz) | 10MHz             | QPSK                    | 1 RB / 49 RB Offset                                               |
|                    |                              | 18675 to 19125    | 18675(1857.50MHz),<br>18900(1880.00MHz),<br>19125(1902.50MHz) | 15MHz             | QPSK                    | 1 RB / 74 RB Offset                                               |
|                    |                              | 18700 to 19100    | 18700(1860.00MHz),<br>18900(1880.00MHz),<br>19100(1900.00MHz) | 20MHz             | QPSK                    | 1 RB / 99 RB Offset                                               |
| -                  | Radiated Emission Below 1GHz | 18607 to 19193    | 18607(1850.70MHz)                                             | 1.4MHz            | QPSK                    | 1 RB / 5 RB Offset                                                |
|                    |                              | 18625 to 19175    | 18625(1852.50MHz)                                             | 5MHz              | QPSK                    | 1 RB / 24 RB Offset                                               |
|                    |                              | 18700 to 19100    | 18700(1860.00MHz)                                             | 20MHz             | QPSK                    | 1 RB / 99 RB Offset                                               |
| -                  | Radiated Emission Above 1GHz | 18607 to 19193    | 18607(1850.70MHz),<br>18900(1880.00MHz),<br>19193(1909.30MHz) | 1.4MHz            | QPSK                    | 1 RB / 5 RB Offset                                                |
|                    |                              | 18625 to 19175    | 18625(1852.50MHz),<br>18900(1880.00MHz),<br>19175(1907.50MHz) | 5MHz              | QPSK                    | 1 RB / 24 RB Offset                                               |
|                    |                              | 18700 to 19100    | 18700(1860.00MHz),<br>18900(1880.00MHz),<br>19100(1900.00MHz) | 20MHz             | QPSK                    | 1 RB / 99 RB Offset                                               |

Note: The conducted output power for QPSK, 16QAM and 64QAM, measured value of QPSK is higher than 16QAM and 64QAM mode. Therefore, only occupied bandwidth and Peak to average ratio items had been tested under QPSK, 16QAM and 64QAM modes, the other test items were performed under QPSK mode only.

Test Condition:

| Test Item                  | Environmental Conditions           | Input Power  | Tested By            |
|----------------------------|------------------------------------|--------------|----------------------|
| EIRP                       | 25deg. C, 66%RH<br>24deg. C, 66%RH | 120Vac, 60Hz | Greg Lin<br>Tim Chen |
| Modulation characteristics | 24deg. C, 64%RH                    | 120Vac, 60Hz | Wayne Huang          |
| Frequency Stability        | 24deg. C, 64%RH                    | 120Vac, 60Hz | Wayne Huang          |
| Occupied Bandwidth         | 24deg. C, 64%RH                    | 120Vac, 60Hz | Wayne Huang          |
| Band Edge                  | 24deg. C, 64%RH                    | 120Vac, 60Hz | Wayne Huang          |
| Peak To Average Ratio      | 24deg. C, 64%RH                    | 120Vac, 60Hz | Wayne Huang          |
| Conducted Emission         | 24deg. C, 64%RH                    | 120Vac, 60Hz | Wayne Huang          |
| Radiated Emission          | 25deg. C, 66%RH                    | 120Vac, 60Hz | Greg Lin             |

### 3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

### 3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC 47 CFR Part 2**

**FCC 47 CFR Part 24**

**KDB 971168 D01 Power Meas License Digital Systems v03r01**

**ANSI/TIA/EIA-603-E 2016**

**ANSI 63.26-2015**

All test items have been performed and recorded as per the above standards.

## 4 Test Types and Results

### 4.1 Output Power Measurement

#### 4.1.1 Limits of Output Power Measurement

Mobile / Portable station are limited to 2 watts e.r.p.

#### 4.1.2 Test Procedures

##### EIRP / ERP Measurement:

- All measurements were done at low, middle and high operational frequency range. RBW and VBW is 10MHz for LTE mode.
- Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m(below or equal 1GHz) and/or 1.5m(above 1GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step b. Record the power level of S.G
- $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$ . E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,  $E.R.P \text{ power} = E.I.R.P \text{ power} - 2.15\text{dB}$ .

Where:

$$ERP/EIRP = P_{Meas} + G_T - L_C$$

$P_{Meas}$  : Measure transmitter output power.

$G_T$  : Gain of the transmitting antenna.

$L_C$  : signal attenuation in the connecting cable between the transmitter and antenna.


##### Conducted Power Measurement:

The EUT was set up for the maximum power with PCS, WCDMA, LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.


### 4.1.3 Test Setup

EIRP / ERP Measurement:

**For Radiated Emission below or equal 1GHz**



**For Radiated Emission above 1GHz**



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Conducted Power Measurement:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.4 Test Results

Conducted Output Power (dBm)

| LTE Band 2 |           |                 |           |       |       |       |
|------------|-----------|-----------------|-----------|-------|-------|-------|
| BW         | MCS Index | RB Size         | RB Offset | Low   | Mid   | High  |
|            |           | Channel         |           | 18700 | 18900 | 19100 |
|            |           | Frequency (MHz) |           | 1860  | 1880  | 1900  |
| 20M        | QPSK      | 1               | 0         | 23.74 | 23.88 | 23.68 |
|            |           | 1               | 50        | 23.38 | 23.47 | 23.31 |
|            |           | 1               | 99        | 23.62 | 23.71 | 23.57 |
|            |           | 50              | 0         | 22.93 | 22.99 | 22.85 |
|            |           | 50              | 25        | 22.92 | 22.96 | 22.82 |
|            |           | 50              | 50        | 22.86 | 22.97 | 22.80 |
|            |           | 100             | 0         | 22.91 | 22.98 | 22.81 |
|            | 16QAM     | 1               | 0         | 22.64 | 22.83 | 22.58 |
|            |           | 1               | 50        | 22.34 | 22.37 | 22.24 |
|            |           | 1               | 99        | 22.57 | 22.68 | 22.51 |
|            |           | 50              | 0         | 21.89 | 21.95 | 21.80 |
|            |           | 50              | 25        | 21.82 | 21.93 | 21.76 |
|            |           | 50              | 50        | 21.84 | 21.89 | 21.71 |
|            |           | 100             | 0         | 21.87 | 21.96 | 21.74 |
|            | 64QAM     | 1               | 0         | 21.64 | 21.83 | 21.60 |
|            |           | 1               | 50        | 21.35 | 21.47 | 21.24 |
|            |           | 1               | 99        | 21.58 | 21.65 | 21.53 |
|            |           | 50              | 0         | 20.84 | 20.97 | 20.79 |
|            |           | 50              | 25        | 20.87 | 20.97 | 20.74 |
|            |           | 50              | 50        | 20.80 | 20.89 | 20.73 |
|            |           | 100             | 0         | 20.91 | 20.91 | 20.71 |

| LTE Band 2 |           |                 |           |        |       |        |
|------------|-----------|-----------------|-----------|--------|-------|--------|
| BW         | MCS Index | RB Size         | RB Offset | Low    | Mid   | High   |
|            |           | Channel         |           | 18675  | 18900 | 19125  |
|            |           | Frequency (MHz) |           | 1857.5 | 1880  | 1902.5 |
| 15M        | QPSK      | 1               | 0         | 23.65  | 23.82 | 23.64  |
|            |           | 1               | 37        | 23.38  | 23.41 | 23.21  |
|            |           | 1               | 74        | 23.61  | 23.69 | 23.56  |
|            |           | 36              | 0         | 22.87  | 22.99 | 22.84  |
|            |           | 36              | 19        | 22.84  | 22.93 | 22.79  |
|            |           | 36              | 39        | 22.83  | 22.90 | 22.79  |
|            |           | 75              | 0         | 22.87  | 22.90 | 22.72  |
|            | 16QAM     | 1               | 0         | 22.59  | 22.74 | 22.60  |
|            |           | 1               | 37        | 22.37  | 22.37 | 22.24  |
|            |           | 1               | 74        | 22.62  | 22.60 | 22.44  |
|            |           | 36              | 0         | 21.76  | 21.97 | 21.72  |
|            |           | 36              | 19        | 21.82  | 21.94 | 21.70  |
|            |           | 36              | 39        | 21.78  | 21.92 | 21.69  |
|            |           | 75              | 0         | 21.89  | 21.86 | 21.71  |
|            | 64QAM     | 1               | 0         | 21.63  | 21.74 | 21.53  |
|            |           | 1               | 37        | 21.36  | 21.42 | 21.18  |
|            |           | 1               | 74        | 21.49  | 21.66 | 21.47  |
|            |           | 36              | 0         | 20.83  | 20.99 | 20.74  |
|            |           | 36              | 19        | 20.80  | 20.92 | 20.65  |
|            |           | 36              | 39        | 20.77  | 20.94 | 20.73  |
|            |           | 75              | 0         | 20.77  | 20.91 | 20.71  |

| LTE Band 2 |           |                 |           |       |       |       |
|------------|-----------|-----------------|-----------|-------|-------|-------|
| BW         | MCS Index | RB Size         | RB Offset | Low   | Mid   | High  |
|            |           | Channel         |           | 18650 | 18900 | 19150 |
|            |           | Frequency (MHz) |           | 1855  | 1880  | 1905  |
| 10M        | QPSK      | 1               | 0         | 23.64 | 23.70 | 23.60 |
|            |           | 1               | 24        | 23.33 | 23.38 | 23.23 |
|            |           | 1               | 49        | 23.52 | 23.68 | 23.48 |
|            |           | 25              | 0         | 22.82 | 22.85 | 22.63 |
|            |           | 25              | 12        | 22.75 | 22.90 | 22.71 |
|            |           | 25              | 25        | 22.75 | 22.82 | 22.58 |
|            |           | 50              | 0         | 22.79 | 22.84 | 22.64 |
|            | 16QAM     | 1               | 0         | 22.59 | 22.73 | 22.57 |
|            |           | 1               | 24        | 22.12 | 22.35 | 22.09 |
|            |           | 1               | 49        | 22.42 | 22.58 | 22.43 |
|            |           | 25              | 0         | 21.82 | 21.89 | 21.73 |
|            |           | 25              | 12        | 21.71 | 21.90 | 21.58 |
|            |           | 25              | 25        | 21.64 | 21.76 | 21.56 |
|            |           | 50              | 0         | 21.71 | 21.67 | 21.58 |
|            | 64QAM     | 1               | 0         | 21.59 | 21.84 | 21.48 |
|            |           | 1               | 24        | 21.18 | 21.18 | 21.11 |
|            |           | 1               | 49        | 21.42 | 21.60 | 21.37 |
|            |           | 25              | 0         | 20.74 | 20.88 | 20.54 |
|            |           | 25              | 12        | 20.73 | 20.97 | 20.53 |
|            |           | 25              | 25        | 20.67 | 20.85 | 20.58 |
|            |           | 50              | 0         | 20.67 | 20.86 | 20.59 |

| LTE Band 2 |           |                 |           |        |       |        |
|------------|-----------|-----------------|-----------|--------|-------|--------|
| BW         | MCS Index | RB Size         | RB Offset | Low    | Mid   | High   |
|            |           | Channel         |           | 18625  | 18900 | 19175  |
|            |           | Frequency (MHz) |           | 1852.5 | 1880  | 1907.5 |
| 5M         | QPSK      | 1               | 0         | 23.68  | 23.71 | 23.58  |
|            |           | 1               | 12        | 23.24  | 23.40 | 23.14  |
|            |           | 1               | 24        | 23.50  | 23.68 | 23.25  |
|            |           | 12              | 0         | 22.79  | 22.90 | 22.55  |
|            |           | 12              | 6         | 22.76  | 22.98 | 22.57  |
|            |           | 12              | 13        | 22.79  | 22.75 | 22.56  |
|            |           | 25              | 0         | 22.81  | 22.81 | 22.56  |
|            | 16QAM     | 1               | 0         | 22.54  | 22.64 | 22.42  |
|            |           | 1               | 12        | 22.33  | 22.30 | 22.15  |
|            |           | 1               | 24        | 22.43  | 22.53 | 22.54  |
|            |           | 12              | 0         | 21.70  | 21.93 | 21.71  |
|            |           | 12              | 6         | 21.66  | 21.77 | 21.59  |
|            |           | 12              | 13        | 21.57  | 21.89 | 21.59  |
|            |           | 25              | 0         | 21.68  | 21.91 | 21.66  |
|            | 64QAM     | 1               | 0         | 21.53  | 21.64 | 21.48  |
|            |           | 1               | 12        | 21.25  | 21.36 | 21.22  |
|            |           | 1               | 24        | 21.41  | 21.59 | 21.46  |
|            |           | 12              | 0         | 20.67  | 20.85 | 20.66  |
|            |           | 12              | 6         | 20.68  | 20.85 | 20.72  |
|            |           | 12              | 13        | 20.64  | 20.78 | 20.69  |
|            |           | 25              | 0         | 20.81  | 20.82 | 20.71  |

| LTE Band 2 |           |                 |           |        |       |        |
|------------|-----------|-----------------|-----------|--------|-------|--------|
| BW         | MCS Index | RB Size         | RB Offset | Low    | Mid   | High   |
|            |           | Channel         |           | 18615  | 18900 | 19185  |
|            |           | Frequency (MHz) |           | 1851.5 | 1880  | 1908.5 |
| 3M         | QPSK      | 1               | 0         | 23.59  | 23.83 | 23.60  |
|            |           | 1               | 7         | 23.31  | 23.33 | 23.19  |
|            |           | 1               | 14        | 23.48  | 23.61 | 23.54  |
|            |           | 8               | 0         | 22.80  | 22.93 | 22.80  |
|            |           | 8               | 3         | 22.78  | 23.00 | 22.74  |
|            |           | 8               | 7         | 22.76  | 22.80 | 22.69  |
|            |           | 15              | 0         | 22.72  | 22.87 | 22.61  |
|            | 16QAM     | 1               | 0         | 22.61  | 22.68 | 22.43  |
|            |           | 1               | 7         | 22.21  | 22.19 | 22.16  |
|            |           | 1               | 14        | 22.52  | 22.51 | 22.48  |
|            |           | 8               | 0         | 21.74  | 21.85 | 21.75  |
|            |           | 8               | 3         | 21.75  | 21.85 | 21.60  |
|            |           | 8               | 7         | 21.71  | 21.89 | 21.74  |
|            |           | 15              | 0         | 21.76  | 21.86 | 21.67  |
|            | 64QAM     | 1               | 0         | 21.63  | 21.65 | 21.51  |
|            |           | 1               | 7         | 21.12  | 21.35 | 21.13  |
|            |           | 1               | 14        | 21.37  | 21.59 | 21.41  |
|            |           | 8               | 0         | 20.77  | 20.82 | 20.67  |
|            |           | 8               | 3         | 20.75  | 20.97 | 20.63  |
|            |           | 8               | 7         | 20.69  | 20.91 | 20.57  |
|            |           | 15              | 0         | 20.75  | 20.79 | 20.63  |

| LTE Band 2 |           |                 |           |        |       |        |
|------------|-----------|-----------------|-----------|--------|-------|--------|
| BW         | MCS Index | RB Size         | RB Offset | Low    | Mid   | High   |
|            |           | Channel         |           | 18607  | 18900 | 19193  |
|            |           | Frequency (MHz) |           | 1850.7 | 1880  | 1909.3 |
| 1.4M       | QPSK      | 1               | 0         | 23.56  | 23.86 | 23.45  |
|            |           | 1               | 2         | 23.26  | 23.38 | 23.14  |
|            |           | 1               | 5         | 23.58  | 23.62 | 23.35  |
|            |           | 3               | 0         | 23.80  | 23.87 | 23.74  |
|            |           | 3               | 1         | 23.71  | 23.85 | 23.62  |
|            |           | 3               | 3         | 23.73  | 23.81 | 23.66  |
|            |           | 6               | 0         | 22.89  | 22.98 | 22.78  |
|            | 16QAM     | 1               | 0         | 22.61  | 22.55 | 22.60  |
|            |           | 1               | 2         | 22.10  | 22.20 | 22.13  |
|            |           | 1               | 5         | 22.41  | 22.54 | 22.42  |
|            |           | 3               | 0         | 22.75  | 22.88 | 22.59  |
|            |           | 3               | 1         | 22.81  | 22.80 | 22.71  |
|            |           | 3               | 3         | 22.67  | 22.88 | 22.65  |
|            |           | 6               | 0         | 21.75  | 21.82 | 21.48  |
|            | 64QAM     | 1               | 0         | 21.47  | 21.69 | 21.60  |
|            |           | 1               | 2         | 21.15  | 21.42 | 21.12  |
|            |           | 1               | 5         | 21.37  | 21.61 | 21.34  |
|            |           | 3               | 0         | 21.80  | 21.98 | 21.74  |
|            |           | 3               | 1         | 21.70  | 21.81 | 21.62  |
|            |           | 3               | 3         | 21.54  | 21.89 | 21.64  |
|            |           | 6               | 0         | 20.65  | 20.83 | 20.60  |

EIRP Power (dBm)

**Modulation Type: QPSK**

LTE Band 2, Channel Bandwidth: 1.4MHz

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18607 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1850.70     | -12.9            | 27.3                  | 0.1                    | 27.4       | 33.0        | -5.6        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1850.70     | -16.5            | 23.9                  | 0.1                    | 24.0       | 33.0        | -9.0        |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18900 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -13.0            | 27.5                  | 0.0                    | 27.5       | 33.0        | -5.5        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -15.9            | 24.7                  | 0.0                    | 24.7       | 33.0        | -8.3        |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 19193 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1909.30     | -13.1            | 27.6                  | -0.1                   | 27.5       | 33.0        | -5.5        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1909.30     | -16.4            | 24.4                  | -0.1                   | 24.3       | 33.0        | -8.7        |

Note: EIRP (dBm) = S.G Power Value (dBm) + Correction Factor (dB).

LTE Band 2, Channel Bandwidth: 3MHz

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18615 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1851.50     | -12.4            | 27.8                  | 0.1                    | 27.9       | 33.0        | -5.1        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1851.50     | -16.1            | 24.3                  | 0.1                    | 24.4       | 33.0        | -8.6        |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18900 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -12.7            | 27.8                  | 0.0                    | 27.8       | 33.0        | -5.2        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -15.6            | 25.0                  | 0.0                    | 25.0       | 33.0        | -8.0        |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 19185 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1908.50     | -12.8            | 27.9                  | -0.1                   | 27.8       | 33.0        | -5.2        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1908.50     | -16.5            | 24.3                  | -0.1                   | 24.2       | 33.0        | -8.8        |

Note: EIRP (dBm) = S.G Power Value (dBm) + Correction Factor (dB).

LTE Band 2, Channel Bandwidth: 5MHz

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18625 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1852.50     | -13.7            | 26.5                  | 0.1                    | 26.6       | 33.0        | -6.4        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1852.50     | -16.4            | 24.0                  | 0.1                    | 24.1       | 33.0        | -8.9        |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18900 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -13.5            | 27.0                  | 0.0                    | 27.0       | 33.0        | -6.0        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -16.0            | 24.6                  | 0.0                    | 24.6       | 33.0        | -8.4        |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 19175 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1907.50     | -12.9            | 27.8                  | -0.1                   | 27.7       | 33.0        | -5.3        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1907.50     | -16.2            | 24.6                  | -0.1                   | 24.5       | 33.0        | -8.5        |

Note: EIRP (dBm) = S.G Power Value (dBm) + Correction Factor (dB).



LTE Band 2, Channel Bandwidth: 15MHz

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18675 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1857.50     | -13.7            | 26.6                  | 0.0                    | 26.6       | 33.0        | -6.4        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1857.50     | -16.2            | 24.3                  | 0.0                    | 24.3       | 33.0        | -8.7        |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18900 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -13.1            | 27.4                  | 0.0                    | 27.4       | 33.0        | -5.6        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -16.6            | 24.0                  | 0.0                    | 24.0       | 33.0        | -9.0        |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 19125 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1902.50     | -13.8            | 26.9                  | -0.1                   | 26.8       | 33.0        | -6.2        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1902.50     | -16.1            | 24.7                  | -0.1                   | 24.6       | 33.0        | -8.4        |

Note: EIRP (dBm) = S.G Power Value (dBm) + Correction Factor (dB).



# Modulation Type: 16QAM

LTE Band 2, Channel Bandwidth: 1.4MHz

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18607 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1850.70     | -13.8            | 26.4                  | 0.1                    | 26.5       | 33.0        | -6.5        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1850.70     | -17.5            | 22.9                  | 0.1                    | 23.0       | 33.0        | -10.0       |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18900 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -13.9            | 26.6                  | 0.0                    | 26.6       | 33.0        | -6.4        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -16.9            | 23.7                  | 0.0                    | 23.7       | 33.0        | -9.3        |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 19193 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1909.30     | -14.1            | 26.6                  | -0.1                   | 26.5       | 33.0        | -6.5        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1909.30     | -17.4            | 23.4                  | -0.1                   | 23.3       | 33.0        | -9.7        |

Note: EIRP (dBm) = S.G Power Value (dBm) + Correction Factor (dB).

LTE Band 2, Channel Bandwidth: 3MHz

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18615 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1851.50     | -13.2            | 27.0                  | 0.1                    | 27.1       | 33.0        | -5.9        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1851.50     | -17.0            | 23.4                  | 0.1                    | 23.5       | 33.0        | -9.5        |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18900 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -13.8            | 26.7                  | 0.0                    | 26.7       | 33.0        | -6.3        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -17.2            | 23.4                  | 0.0                    | 23.4       | 33.0        | -9.6        |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 19185 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1908.50     | -13.8            | 26.9                  | -0.1                   | 26.8       | 33.0        | -6.2        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1908.50     | -17.4            | 23.4                  | -0.1                   | 23.3       | 33.0        | -9.7        |

Note: EIRP (dBm) = S.G Power Value (dBm) + Correction Factor (dB).

LTE Band 2, Channel Bandwidth: 5MHz

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18625 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1852.50     | -14.6            | 25.6                  | 0.1                    | 25.7       | 33.0        | -7.3        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1852.50     | -17.3            | 23.1                  | 0.1                    | 23.2       | 33.0        | -9.8        |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18900 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -14.5            | 26.0                  | 0.0                    | 26.0       | 33.0        | -7.0        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -17.0            | 23.6                  | 0.0                    | 23.6       | 33.0        | -9.4        |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 19175 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1907.50     | -14.0            | 26.7                  | -0.1                   | 26.6       | 33.0        | -6.4        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1907.50     | -17.3            | 23.5                  | -0.1                   | 23.4       | 33.0        | -9.6        |

Note: EIRP (dBm) = S.G Power Value (dBm) + Correction Factor (dB).

LTE Band 2, Channel Bandwidth: 10MHz

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18650 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1855.00     | -14.3            | 26.0                  | 0.0                    | 26.0       | 33.0        | -7.0        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1855.00     | -17.5            | 23.0                  | 0.0                    | 23.0       | 33.0        | -10.0       |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18900 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -14.2            | 26.3                  | 0.0                    | 26.3       | 33.0        | -6.7        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -17.2            | 23.4                  | 0.0                    | 23.4       | 33.0        | -9.6        |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 19150 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1905.00     | -14.3            | 26.4                  | -0.1                   | 26.3       | 33.0        | -6.7        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1905.00     | -17.3            | 23.5                  | -0.1                   | 23.4       | 33.0        | -9.6        |

Note: EIRP (dBm) = S.G Power Value (dBm) + Correction Factor (dB).





# Modulation Type: 64QAM

LTE Band 2, Channel Bandwidth: 1.4MHz

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18607 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1850.70     | -14.5            | 25.7                  | 0.1                    | 25.8       | 33.0        | -7.2        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1850.70     | -18.1            | 22.3                  | 0.1                    | 22.4       | 33.0        | -10.6       |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18900 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -14.5            | 26.0                  | 0.0                    | 26.0       | 33.0        | -7.0        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -17.5            | 23.1                  | 0.0                    | 23.1       | 33.0        | -9.9        |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 19193 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1909.30     | -14.8            | 25.9                  | -0.1                   | 25.8       | 33.0        | -7.2        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1909.30     | -17.9            | 22.9                  | -0.1                   | 22.8       | 33.0        | -10.2       |

Note: EIRP (dBm) = S.G Power Value (dBm) + Correction Factor (dB).

LTE Band 2, Channel Bandwidth: 3MHz

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18615 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1851.50     | -13.8            | 26.4                  | 0.1                    | 26.5       | 33.0        | -6.5        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1851.50     | -17.4            | 23.0                  | 0.1                    | 23.1       | 33.0        | -9.9        |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18900 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -14.3            | 26.2                  | 0.0                    | 26.2       | 33.0        | -6.8        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -17.7            | 22.9                  | 0.0                    | 22.9       | 33.0        | -10.1       |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 19185 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1908.50     | -14.3            | 26.4                  | -0.1                   | 26.3       | 33.0        | -6.7        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1908.50     | -17.9            | 22.9                  | -0.1                   | 22.8       | 33.0        | -10.2       |

Note: EIRP (dBm) = S.G Power Value (dBm) + Correction Factor (dB).

LTE Band 2, Channel Bandwidth: 5MHz

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18625 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1852.50     | -15.2            | 25.0                  | 0.1                    | 25.1       | 33.0        | -7.9        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1852.50     | -17.6            | 22.8                  | 0.1                    | 22.9       | 33.0        | -10.1       |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18900 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -14.9            | 25.6                  | 0.0                    | 25.6       | 33.0        | -7.4        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -17.4            | 23.2                  | 0.0                    | 23.2       | 33.0        | -9.8        |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 19175 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1907.50     | -14.3            | 26.4                  | -0.1                   | 26.3       | 33.0        | -6.7        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1907.50     | -17.8            | 23.0                  | -0.1                   | 22.9       | 33.0        | -10.1       |

Note: EIRP (dBm) = S.G Power Value (dBm) + Correction Factor (dB).

LTE Band 2, Channel Bandwidth: 10MHz

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18650 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1855.00     | -14.8            | 25.5                  | 0.0                    | 25.5       | 33.0        | -7.5        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1855.00     | -18.0            | 22.5                  | 0.0                    | 22.5       | 33.0        | -10.5       |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18900 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -14.7            | 25.8                  | 0.0                    | 25.8       | 33.0        | -7.2        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -17.6            | 23.0                  | 0.0                    | 23.0       | 33.0        | -10.0       |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 19150 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1905.00     | -14.8            | 25.9                  | -0.1                   | 25.8       | 33.0        | -7.2        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1905.00     | -17.8            | 23.0                  | -0.1                   | 22.9       | 33.0        | -10.1       |

Note: EIRP (dBm) = S.G Power Value (dBm) + Correction Factor (dB).

LTE Band 2, Channel Bandwidth: 15MHz

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18675 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1857.50     | -14.9            | 25.4                  | 0.0                    | 25.4       | 33.0        | -7.6        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1857.50     | -18.1            | 22.4                  | 0.0                    | 22.4       | 33.0        | -10.6       |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18900 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -14.4            | 26.1                  | 0.0                    | 26.1       | 33.0        | -6.9        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -18.1            | 22.5                  | 0.0                    | 22.5       | 33.0        | -10.5       |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 19125 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1902.50     | -15.1            | 25.6                  | -0.1                   | 25.5       | 33.0        | -7.5        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1902.50     | -17.7            | 23.1                  | -0.1                   | 23.0       | 33.0        | -10.0       |

Note: EIRP (dBm) = S.G Power Value (dBm) + Correction Factor (dB).

LTE Band 2, Channel Bandwidth: 20MHz

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18700 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1860.00     | -14.8            | 25.5                  | 0.0                    | 25.5       | 33.0        | -7.5        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1860.00     | -17.9            | 22.6                  | 0.0                    | 22.6       | 33.0        | -10.4       |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 18900 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -14.3            | 26.2                  | 0.0                    | 26.2       | 33.0        | -6.8        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1880.00     | -17.8            | 22.8                  | 0.0                    | 22.8       | 33.0        | -10.2       |

|                                                     |             |                  |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|------------------|-----------------------|------------------------|------------|-------------|-------------|
| MODE                                                |             | TX channel 19100 |                       |                        |            |             |             |
| Antenna Polarity & Test Distance: Horizontal at 3 M |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1900.00     | -14.5            | 26.2                  | -0.1                   | 26.1       | 33.0        | -6.9        |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |                  |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm)    | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1900.00     | -18.3            | 22.5                  | -0.1                   | 22.4       | 33.0        | -10.6       |

Note: EIRP (dBm) = S.G Power Value (dBm) + Correction Factor (dB).

## 4.2 Modulation Characteristics Measurement

### 4.2.1 Limits of Modulation Characteristics

N/A


### 4.2.2 Test Procedure

Connect the EUT to Communication Simulator via the antenna connector, The frequency band is set as EUT supported Modulation and Channels, the EUT output is matched with 50 ohm load, the waveform quality and constellation of the EUT was tested.

### 4.2.3 Test Setup



## 4.2.4 Test Results



### 4.3 Frequency Stability Measurement

#### 4.3.1 Limits of Frequency Stability Measurement


1.5 ppm is for base and fixed station. 2.5 ppm is for mobile station.

#### 4.3.2 Test Procedure

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the  $\pm 0.5^{\circ}\text{C}$  during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

#### 4.3.3 Test Setup



#### 4.3.4 Test Results

##### Frequency Error vs. Voltage

| Voltage (Volts) | LTE Band 2                 |                       |                 |                       |
|-----------------|----------------------------|-----------------------|-----------------|-----------------------|
|                 | Channel Bandwidth: 1.4 MHz |                       |                 |                       |
|                 | Low Channel                |                       | High Channel    |                       |
|                 | Frequency (MHz)            | Frequency Error (ppm) | Frequency (MHz) | Frequency Error (ppm) |
| 3.85            | 1850.700001                | 0.000                 | 1909.300000     | 0.000                 |
| 3.23            | 1850.699995                | -0.003                | 1909.299997     | -0.002                |
| 4.37            | 1850.700004                | 0.002                 | 1909.300004     | 0.002                 |

Note: The applicant defined the normal working voltage is from 3.23 Vdc to 4.37 Vdc.

##### Frequency Error vs. Temperature

| Temp. (°C) | LTE Band 2                 |                       |                 |                       |
|------------|----------------------------|-----------------------|-----------------|-----------------------|
|            | Channel Bandwidth: 1.4 MHz |                       |                 |                       |
|            | Low Channel                |                       | High Channel    |                       |
|            | Frequency (MHz)            | Frequency Error (ppm) | Frequency (MHz) | Frequency Error (ppm) |
| -30        | 1850.700008                | 0.004                 | 1909.300009     | 0.005                 |
| -20        | 1850.700006                | 0.003                 | 1909.300005     | 0.003                 |
| -10        | 1850.700004                | 0.002                 | 1909.300004     | 0.002                 |
| 0          | 1850.700001                | 0.001                 | 1909.300002     | 0.001                 |
| 10         | 1850.699999                | 0.000                 | 1909.300001     | 0.000                 |
| 20         | 1850.699997                | -0.001                | 1909.299997     | -0.001                |
| 30         | 1850.699997                | -0.002                | 1909.299996     | -0.002                |
| 40         | 1850.699994                | -0.004                | 1909.299993     | -0.004                |
| 50         | 1850.699992                | -0.004                | 1909.299991     | -0.005                |

### Frequency Error vs. Voltage

| Voltage (Volts) | LTE Band 2               |                       |                 |                       |
|-----------------|--------------------------|-----------------------|-----------------|-----------------------|
|                 | Channel Bandwidth: 3 MHz |                       |                 |                       |
|                 | Low Channel              |                       | High Channel    |                       |
|                 | Frequency (MHz)          | Frequency Error (ppm) | Frequency (MHz) | Frequency Error (ppm) |
| 3.80            | 1851.499999              | 0.000                 | 1907.500001     | 0.000                 |
| 3.23            | 1851.499996              | -0.002                | 1907.499995     | -0.003                |
| 4.37            | 1851.500003              | 0.002                 | 1907.500004     | 0.002                 |

Note: The applicant defined the normal working voltage is from 3.23 Vdc to 4.37 Vdc.

### Frequency Error vs. Temperature

| Temp. (°C) | LTE Band 2               |                       |                 |                       |
|------------|--------------------------|-----------------------|-----------------|-----------------------|
|            | Channel Bandwidth: 3 MHz |                       |                 |                       |
|            | Low Channel              |                       | High Channel    |                       |
|            | Frequency (MHz)          | Frequency Error (ppm) | Frequency (MHz) | Frequency Error (ppm) |
| -30        | 1851.500008              | 0.004                 | 1907.500009     | 0.005                 |
| -20        | 1851.500005              | 0.003                 | 1907.500006     | 0.003                 |
| -10        | 1851.500003              | 0.002                 | 1907.500004     | 0.002                 |
| 0          | 1851.500003              | 0.001                 | 1907.500001     | 0.001                 |
| 10         | 1851.500000              | 0.000                 | 1907.499999     | 0.000                 |
| 20         | 1851.499999              | -0.001                | 1907.499998     | -0.001                |
| 30         | 1851.499996              | -0.002                | 1907.499996     | -0.002                |
| 40         | 1851.499993              | -0.004                | 1907.499994     | -0.003                |
| 50         | 1851.499991              | -0.005                | 1907.499992     | -0.004                |

### Frequency Error vs. Voltage

| Voltage (Volts) | LTE Band 2               |                       |                 |                       |
|-----------------|--------------------------|-----------------------|-----------------|-----------------------|
|                 | Channel Bandwidth: 5 MHz |                       |                 |                       |
|                 | Low Channel              |                       | High Channel    |                       |
|                 | Frequency (MHz)          | Frequency Error (ppm) | Frequency (MHz) | Frequency Error (ppm) |
| 3.80            | 1852.500000              | 0.000                 | 1907.500000     | 0.000                 |
| 3.23            | 1852.499995              | -0.003                | 1907.499995     | -0.003                |
| 4.37            | 1852.500004              | 0.002                 | 1907.500003     | 0.002                 |

Note: The applicant defined the normal working voltage is from 3.23 Vdc to 4.37 Vdc.

### Frequency Error vs. Temperature

| Temp. (°C) | LTE Band 2               |                       |                 |                       |
|------------|--------------------------|-----------------------|-----------------|-----------------------|
|            | Channel Bandwidth: 5 MHz |                       |                 |                       |
|            | Low Channel              |                       | High Channel    |                       |
|            | Frequency (MHz)          | Frequency Error (ppm) | Frequency (MHz) | Frequency Error (ppm) |
| -30        | 1852.500008              | 0.004                 | 1907.500009     | 0.004                 |
| -20        | 1852.500005              | 0.003                 | 1907.500006     | 0.003                 |
| -10        | 1852.500004              | 0.002                 | 1907.500004     | 0.002                 |
| 0          | 1852.500003              | 0.001                 | 1907.500002     | 0.001                 |
| 10         | 1852.499999              | 0.000                 | 1907.500001     | 0.001                 |
| 20         | 1852.499998              | -0.001                | 1907.499998     | -0.001                |
| 30         | 1852.499996              | -0.002                | 1907.499995     | -0.003                |
| 40         | 1852.499993              | -0.004                | 1907.499994     | -0.003                |
| 50         | 1852.499992              | -0.004                | 1907.499992     | -0.004                |

### Frequency Error vs. Voltage

| Voltage (Volts) | LTE Band 2                |                       |                 |                       |
|-----------------|---------------------------|-----------------------|-----------------|-----------------------|
|                 | Channel Bandwidth: 10 MHz |                       |                 |                       |
|                 | Low Channel               |                       | High Channel    |                       |
|                 | Frequency (MHz)           | Frequency Error (ppm) | Frequency (MHz) | Frequency Error (ppm) |
| 3.80            | 1854.999999               | 0.000                 | 1904.999999     | -0.001                |
| 3.23            | 1854.999997               | -0.002                | 1904.999995     | -0.003                |
| 4.37            | 1855.000003               | 0.002                 | 1905.000004     | 0.002                 |

Note: The applicant defined the normal working voltage is from 3.23 Vdc to 4.37 Vdc.

### Frequency Error vs. Temperature

| Temp. (°C) | LTE Band 2                |                       |                 |                       |
|------------|---------------------------|-----------------------|-----------------|-----------------------|
|            | Channel Bandwidth: 10 MHz |                       |                 |                       |
|            | Low Channel               |                       | High Channel    |                       |
|            | Frequency (MHz)           | Frequency Error (ppm) | Frequency (MHz) | Frequency Error (ppm) |
| -30        | 1855.000009               | 0.005                 | 1905.000007     | 0.004                 |
| -20        | 1855.000005               | 0.003                 | 1905.000006     | 0.003                 |
| -10        | 1855.000004               | 0.002                 | 1905.000004     | 0.002                 |
| 0          | 1855.000002               | 0.001                 | 1905.000002     | 0.001                 |
| 10         | 1854.999999               | 0.000                 | 1905.000000     | 0.000                 |
| 20         | 1854.999997               | -0.001                | 1904.999999     | -0.001                |
| 30         | 1854.999995               | -0.003                | 1904.999996     | -0.002                |
| 40         | 1854.999993               | -0.004                | 1904.999993     | -0.004                |
| 50         | 1854.999992               | -0.004                | 1904.999991     | -0.005                |

### Frequency Error vs. Voltage

| Voltage (Volts) | LTE Band 2                |                       |                 |                       |
|-----------------|---------------------------|-----------------------|-----------------|-----------------------|
|                 | Channel Bandwidth: 15 MHz |                       |                 |                       |
|                 | Low Channel               |                       | High Channel    |                       |
|                 | Frequency (MHz)           | Frequency Error (ppm) | Frequency (MHz) | Frequency Error (ppm) |
| 3.80            | 1857.499999               | 0.000                 | 1902.500001     | 0.000                 |
| 3.23            | 1857.499995               | -0.003                | 1902.499996     | -0.002                |
| 4.37            | 1857.500003               | 0.002                 | 1902.500003     | 0.001                 |

Note: The applicant defined the normal working voltage is from 3.23 Vdc to 4.37 Vdc.

### Frequency Error vs. Temperature

| Temp. (°C) | LTE Band 2                |                       |                 |                       |
|------------|---------------------------|-----------------------|-----------------|-----------------------|
|            | Channel Bandwidth: 15 MHz |                       |                 |                       |
|            | Low Channel               |                       | High Channel    |                       |
|            | Frequency (MHz)           | Frequency Error (ppm) | Frequency (MHz) | Frequency Error (ppm) |
| -30        | 1857.500007               | 0.004                 | 1902.500007     | 0.004                 |
| -20        | 1857.500006               | 0.003                 | 1902.500007     | 0.004                 |
| -10        | 1857.500003               | 0.002                 | 1902.500004     | 0.002                 |
| 0          | 1857.500002               | 0.001                 | 1902.500001     | 0.001                 |
| 10         | 1857.500001               | 0.000                 | 1902.500000     | 0.000                 |
| 20         | 1857.499998               | -0.001                | 1902.499998     | -0.001                |
| 30         | 1857.499995               | -0.003                | 1902.499997     | -0.002                |
| 40         | 1857.499994               | -0.003                | 1902.499993     | -0.003                |
| 50         | 1857.499991               | -0.005                | 1902.499993     | -0.004                |

### Frequency Error vs. Voltage

| Voltage (Volts) | LTE Band 2                |                       |                 |                       |
|-----------------|---------------------------|-----------------------|-----------------|-----------------------|
|                 | Channel Bandwidth: 20 MHz |                       |                 |                       |
|                 | Low Channel               |                       | High Channel    |                       |
|                 | Frequency (MHz)           | Frequency Error (ppm) | Frequency (MHz) | Frequency Error (ppm) |
| 3.80            | 1859.999999               | -0.001                | 1900.000000     | 0.000                 |
| 3.23            | 1859.999995               | -0.003                | 1899.999995     | -0.003                |
| 4.37            | 1860.000003               | 0.002                 | 1900.000004     | 0.002                 |

Note: The applicant defined the normal working voltage is from 3.23 Vdc to 4.37 Vdc.

### Frequency Error vs. Temperature


| Temp. (°C) | LTE Band 2                |                       |                 |                       |
|------------|---------------------------|-----------------------|-----------------|-----------------------|
|            | Channel Bandwidth: 20 MHz |                       |                 |                       |
|            | Low Channel               |                       | High Channel    |                       |
|            | Frequency (MHz)           | Frequency Error (ppm) | Frequency (MHz) | Frequency Error (ppm) |
| -30        | 1860.000009               | 0.005                 | 1900.000009     | 0.005                 |
| -20        | 1860.000005               | 0.003                 | 1900.000007     | 0.004                 |
| -10        | 1860.000004               | 0.002                 | 1900.000004     | 0.002                 |
| 0          | 1860.000001               | 0.001                 | 1900.000001     | 0.001                 |
| 10         | 1860.000000               | 0.000                 | 1900.000000     | 0.000                 |
| 20         | 1859.999999               | 0.000                 | 1899.999998     | -0.001                |
| 30         | 1859.999996               | -0.002                | 1899.999996     | -0.002                |
| 40         | 1859.999994               | -0.003                | 1899.999994     | -0.003                |
| 50         | 1859.999992               | -0.004                | 1899.999992     | -0.004                |

## 4.4 Occupied Bandwidth Measurement

### 4.4.1 Test Procedure

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

### 4.4.2 Test Setup



#### 4.4.3 Test Result

| LTE Band 2, Channel Bandwidth: 1.4MHz |                 |                          |       |       |                       |       |       |
|---------------------------------------|-----------------|--------------------------|-------|-------|-----------------------|-------|-------|
| Channel                               | Frequency (MHz) | Occupied Bandwidth (MHz) |       |       | 26dBc Bandwidth (MHz) |       |       |
|                                       |                 | QPSK                     | 16QAM | 64QAM | QPSK                  | 16QAM | 64QAM |
| 18607                                 | 1850.7          | 1.09                     | 1.09  | 1.09  | 1.24                  | 1.22  | 1.23  |
| 18900                                 | 1880.0          | 1.09                     | 1.09  | 1.09  | 1.23                  | 1.22  | 1.23  |
| 19193                                 | 1909.3          | 1.09                     | 1.09  | 1.09  | 1.30                  | 1.23  | 1.24  |
| LTE Band 2, Channel Bandwidth: 3MHz   |                 |                          |       |       |                       |       |       |
| Channel                               | Frequency (MHz) | Occupied Bandwidth (MHz) |       |       | 26dBc Bandwidth (MHz) |       |       |
|                                       |                 | QPSK                     | 16QAM | 64QAM | QPSK                  | 16QAM | 64QAM |
| 18615                                 | 1851.5          | 2.70                     | 2.70  | 2.70  | 2.94                  | 2.95  | 2.95  |
| 18900                                 | 1880.0          | 2.70                     | 2.70  | 2.71  | 2.93                  | 2.94  | 2.93  |
| 19185                                 | 1908.5          | 2.71                     | 2.70  | 2.71  | 3.15                  | 2.98  | 2.99  |
| LTE Band 2, Channel Bandwidth: 5MHz   |                 |                          |       |       |                       |       |       |
| Channel                               | Frequency (MHz) | Occupied Bandwidth (MHz) |       |       | 26dBc Bandwidth (MHz) |       |       |
|                                       |                 | QPSK                     | 16QAM | 64QAM | QPSK                  | 16QAM | 64QAM |
| 18625                                 | 1852.5          | 4.49                     | 4.49  | 4.49  | 4.82                  | 4.81  | 4.82  |
| 18900                                 | 1880.0          | 4.49                     | 4.49  | 4.49  | 4.82                  | 4.82  | 4.81  |
| 19175                                 | 1907.5          | 4.49                     | 4.49  | 4.49  | 4.90                  | 4.83  | 4.87  |
| LTE Band 2, Channel Bandwidth: 10MHz  |                 |                          |       |       |                       |       |       |
| Channel                               | Frequency (MHz) | Occupied Bandwidth (MHz) |       |       | 26dBc Bandwidth (MHz) |       |       |
|                                       |                 | QPSK                     | 16QAM | 64QAM | QPSK                  | 16QAM | 64QAM |
| 18650                                 | 1855.0          | 8.96                     | 8.97  | 8.96  | 9.51                  | 9.51  | 9.50  |
| 18900                                 | 1880.0          | 8.98                     | 8.97  | 8.97  | 9.54                  | 9.53  | 9.52  |
| 19150                                 | 1905.0          | 8.97                     | 8.98  | 8.97  | 9.62                  | 9.55  | 9.55  |
| LTE Band 2, Channel Bandwidth: 15MHz  |                 |                          |       |       |                       |       |       |
| Channel                               | Frequency (MHz) | Occupied Bandwidth (MHz) |       |       | 26dBc Bandwidth (MHz) |       |       |
|                                       |                 | QPSK                     | 16QAM | 64QAM | QPSK                  | 16QAM | 64QAM |
| 18675                                 | 1857.5          | 13.43                    | 13.42 | 13.41 | 14.26                 | 14.23 | 14.24 |
| 18900                                 | 1880.0          | 13.50                    | 13.48 | 13.48 | 14.32                 | 14.29 | 14.30 |
| 19125                                 | 1902.5          | 13.49                    | 13.48 | 13.47 | 14.71                 | 14.34 | 14.35 |
| LTE Band 2, Channel Bandwidth: 20MHz  |                 |                          |       |       |                       |       |       |
| Channel                               | Frequency (MHz) | Occupied Bandwidth (MHz) |       |       | 26dBc Bandwidth (MHz) |       |       |
|                                       |                 | QPSK                     | 16QAM | 64QAM | QPSK                  | 16QAM | 64QAM |
| 18700                                 | 1860.0          | 17.83                    | 17.85 | 17.84 | 18.99                 | 18.98 | 18.99 |
| 18900                                 | 1880.0          | 18.02                    | 18.02 | 18.02 | 19.31                 | 19.13 | 19.12 |
| 19100                                 | 1900.0          | 17.97                    | 17.98 | 17.99 | 19.51                 | 19.12 | 19.09 |

## Occupied Bandwidth Spectrum Plot of Worst Value

1.4MHz / QPSK



3MHz / 64QAM



5MHz / QPSK



10MHz / QPSK



15MHz / QPSK



20MHz / QPSK



26dBc Bandwidth  
Spectrum Plot of Worst Value

1.4MHz / QPSK



3MHz / QPSK



5MHz / QPSK



10MHz / QPSK



15MHz / QPSK



20MHz / QPSK




## 4.5 Band Edge Measurement

### 4.5.1 Limits of Band Edge Measurement

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

### 4.5.2 Test Setup




### 4.5.3 Test Procedures

- All measurements were done at low and high operational frequency range.
- The center frequency of spectrum is the band edge frequency and span is 1.5MHz. RB of the spectrum is 15kHz and VB of the spectrum is 51kHz (LTE Channel Bandwidth 1.4MHz).
- The center frequency of spectrum is the band edge frequency and span is 1.5MHz. RB of the spectrum is 30kHz and VB of the spectrum is 100kHz (LTE Channel Bandwidth 3MHz).
- The center frequency of spectrum is the band edge frequency and span is 1.5MHz. RB of the spectrum is 62kHz and VB of the spectrum is 200kHz (LTE Channel Bandwidth 5MHz).
- The center frequency of spectrum is the band edge frequency and span is 1.5MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (LTE Channel Bandwidth 10MHz).
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 150kHz and VB of the spectrum is 470kHz (LTE Channel Bandwidth 15MHz).
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 200kHz and VB of the spectrum is 1MHz (LTE Channel Bandwidth 20MHz).
- Record the max trace plot into the test report.

## 4.5.4 Test Results

### LTE Band 2, Channel Bandwidth 1.4MHz



# LTE Band 2, Channel Bandwidth 3MHz

Channel 18615  
(1851.50MHz)



QPSK

1 RB / 0 RB Offset

Channel 19185  
(1908.50MHz)

QPSK

1 RB / 14 RB Offset



Channel 18615  
(1851.50MHz)



QPSK

15 RB / 0 RB Offset

Channel 19185  
(1908.50MHz)

QPSK

15 RB / 0 RB Offset



# LTE Band 2, Channel Bandwidth 5MHz

Channel 18625  
(1852.50MHz)



QPSK

1 RB / 0 RB Offset

Channel 19175  
(1907.50MHz)

QPSK

1 RB / 24 RB Offset



Channel 18625  
(1852.50MHz)



QPSK

25 RB / 0 RB Offset

Channel 19175  
(1907.50MHz)

QPSK

25 RB / 0 RB Offset



# LTE Band 2, Channel Bandwidth 10MHz

Channel 18650  
(1855.00MHz)



QPSK

1 RB / 0 RB Offset

Channel 19150  
(1905.00MHz)

QPSK

1 RB / 49 RB Offset



Channel 18650  
(1855.00MHz)



QPSK

50 RB / 0 RB Offset

Channel 19150  
(1905.00MHz)

QPSK

50 RB / 0 RB Offset



# LTE Band 2, Channel Bandwidth 15MHz

Channel 18675  
(1857.50MHz)



QPSK

1 RB / 0 RB Offset

Channel 19125  
(1902.50MHz)

QPSK

1 RB / 74 RB Offset



Channel 18675  
(1857.50MHz)



QPSK

75 RB / 0 RB Offset

Channel 19125  
(1902.50MHz)

QPSK

75 RB / 0 RB Offset



# LTE Band 2, Channel Bandwidth 20MHz

Channel 18700  
(1860.00MHz)



QPSK

1 RB / 0 RB Offset

Channel 19100  
(1900.00 MHz)

QPSK

1 RB / 99 RB Offset



Channel 18700  
(1860.00MHz)



QPSK

100 RB / 0 RB Offset

Channel 19100  
(1900.00 MHz)

QPSK

100 RB / 0 RB Offset




## 4.6 Peak to Average Ratio

### 4.6.1 Limits of Peak to Average Ratio Measurement

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

### 4.6.2 Test Setup



### 4.6.3 Test Procedures


- Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
- Set the number of counts to a value that stabilizes the measured CCDF curve;
- Record the maximum PAPR level associated with a probability of 0.1%.

#### 4.6.4 Test Results

| LTE Band 2, Channel Bandwidth 1.4MHz |                 |                            |       |       |
|--------------------------------------|-----------------|----------------------------|-------|-------|
| Channel                              | Frequency (MHz) | Peak To Average Ratio (dB) |       |       |
|                                      |                 | QPSK                       | 16QAM | 64QAM |
| 18607                                | 1850.7          | 3.55                       | 4.85  | 4.76  |
| 18900                                | 1880.0          | 3.85                       | 5.16  | 5.13  |
| 19193                                | 1909.3          | 3.00                       | 4.21  | 3.99  |
| LTE Band 2, Channel Bandwidth 3MHz   |                 |                            |       |       |
| Channel                              | Frequency (MHz) | Peak To Average Ratio (dB) |       |       |
|                                      |                 | QPSK                       | 16QAM | 64QAM |
| 18615                                | 1851.5          | 3.34                       | 4.71  | 4.58  |
| 18900                                | 1880.0          | 3.52                       | 4.90  | 4.79  |
| 19185                                | 1908.5          | 3.09                       | 4.51  | 4.32  |
| LTE Band 2, Channel Bandwidth 5MHz   |                 |                            |       |       |
| Channel                              | Frequency (MHz) | Peak To Average Ratio (dB) |       |       |
|                                      |                 | QPSK                       | 16QAM | 64QAM |
| 18625                                | 1852.5          | 3.27                       | 4.62  | 4.51  |
| 18900                                | 1880.0          | 3.40                       | 4.76  | 4.79  |
| 19175                                | 1907.5          | 3.43                       | 4.80  | 4.73  |
| LTE Band 2, Channel Bandwidth 10MHz  |                 |                            |       |       |
| Channel                              | Frequency (MHz) | Peak To Average Ratio (dB) |       |       |
|                                      |                 | QPSK                       | 16QAM | 64QAM |
| 18650                                | 1855.0          | 2.90                       | 4.36  | 4.33  |
| 18900                                | 1880.0          | 3.00                       | 4.51  | 4.39  |
| 19150                                | 1905.0          | 3.07                       | 4.50  | 4.44  |
| LTE Band 2, Channel Bandwidth 15MHz  |                 |                            |       |       |
| Channel                              | Frequency (MHz) | Peak To Average Ratio (dB) |       |       |
|                                      |                 | QPSK                       | 16QAM | 64QAM |
| 18675                                | 1857.5          | 2.84                       | 4.27  | 4.25  |
| 18900                                | 1880.0          | 2.90                       | 4.36  | 4.31  |
| 19125                                | 1902.5          | 2.97                       | 4.35  | 4.30  |
| LTE Band 2, Channel Bandwidth 20MHz  |                 |                            |       |       |
| Channel                              | Frequency (MHz) | Peak To Average Ratio (dB) |       |       |
|                                      |                 | QPSK                       | 16QAM | 64QAM |
| 18700                                | 1860.0          | 2.85                       | 4.20  | 4.25  |
| 18900                                | 1880.0          | 2.84                       | 4.20  | 4.26  |
| 19100                                | 1900.0          | 3.07                       | 4.42  | 4.46  |

## Spectrum Plot of Worst Value


1.4MHz / 16QAM



3MHz / 16QAM




5MHz / 16QAM



10MHz / 16QAM



15MHz / 16QAM



20MHz / 64QAM




## 4.7 Conducted Spurious Emissions

### 4.7.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. The emission limit equal to  $-13\text{dBm}$ .

### 4.7.2 Test Setup



### 4.7.3 Test Procedure


- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 9 kHz to 1GHz. 20dB attenuation pad is connected with spectrum. RBW=100kHz and VBW=300kHz is used for conducted emission measurement.
- Measuring frequency range is from 1GHz to 27GHz. 20dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

#### 4.7.4 Test Results


LTE Band 2, Channel Bandwidth 1.4MHz

Channel 18607 (1850.70MHz)


Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~10GHz




Frequency Range : 10GHz~27GHz




LTE Band 2, Channel Bandwidth 1.4MHz

Channel 18900 (1880.00MHz)


Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~10GHz




Frequency Range : 10GHz~27GHz




LTE Band 2, Channel Bandwidth 1.4MHz

Channel 19193 (1909.30MHz)



Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~10GHz




Frequency Range : 10GHz~27GHz




# LTE Band 2, Channel Bandwidth 3MHz

Channel 18615 (1851.50MHz)



Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~10GHz




Frequency Range : 10GHz~27GHz




# LTE Band 2, Channel Bandwidth 3MHz

Channel 18900 (1880.00MHz)



Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~10GHz




Frequency Range : 10GHz~27GHz




# LTE Band 2, Channel Bandwidth 3MHz

Channel 19185 (1908.50MHz)



Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~10GHz




Frequency Range : 10GHz~27GHz




# LTE Band 2, Channel Bandwidth 5MHz

Channel 18625 (1852.50MHz)


Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~10GHz




Frequency Range : 10GHz~27GHz




# LTE Band 2, Channel Bandwidth 5MHz

Channel 18900 (1880.00MHz)


Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~10GHz




Frequency Range : 10GHz~27GHz




# LTE Band 2, Channel Bandwidth 5MHz

Channel 19175 (1907.50MHz)



Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~10GHz




Frequency Range : 10GHz~27GHz




# LTE Band 2, Channel Bandwidth 10MHz

Channel 18650 (1855.00MHz)



Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~10GHz




Frequency Range : 10GHz~27GHz




# LTE Band 2, Channel Bandwidth 10MHz

Channel 18900 (1880.00MHz)



Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~10GHz




Frequency Range : 10GHz~27GHz




# LTE Band 2, Channel Bandwidth 10MHz

Channel 19150 (1905.00MHz)



Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~10GHz




Frequency Range : 10GHz~27GHz




# LTE Band 2, Channel Bandwidth 15MHz

Channel 18675 (1857.50MHz)



Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~10GHz




Frequency Range : 10GHz~27GHz




# LTE Band 2, Channel Bandwidth 15MHz

Channel 18900 (1880.00MHz)



Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~10GHz




Frequency Range : 10GHz~27GHz




# LTE Band 2, Channel Bandwidth 15MHz

Channel 19125 (1902.50MHz)



Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~10GHz




Frequency Range : 10GHz~27GHz




# LTE Band 2, Channel Bandwidth 20MHz

Channel 18700 (1860.00MHz)



Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~10GHz




Frequency Range : 10GHz~27GHz




# LTE Band 2, Channel Bandwidth 20MHz

Channel 18900 (1880.00MHz)



Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~10GHz




Frequency Range : 10GHz~27GHz




# LTE Band 2, Channel Bandwidth 20MHz

Channel 19100 (1900.00MHz)


Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~10GHz



Frequency Range : 10GHz~27GHz



## **4.8 Radiated Emission Measurement**

### **4.8.1 Limits of Radiated Emission Measurement**

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. The emission limit equal to  $-13\text{dBm}$ .

### **4.8.2 Test Procedure**


- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G
- c.  $\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$ .
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,  $\text{E.R.P power} = \text{E.I.R.P power} - 2.15\text{dBi}$ .

NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

### **4.8.3 Deviation from Test Standard**

No deviation.

#### 4.8.4 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.8.5 Test Results

Below 1GHz

LTE Band 2, Channel Bandwidth: 1.4MHz


|                          |                                  |                 |                |
|--------------------------|----------------------------------|-----------------|----------------|
| Mode                     | TX channel 18607<br>(1850.70MHz) | Frequency Range | Below 1000 MHz |
| Environmental Conditions | 25deg. C, 66%RH                  | Input Power     | 120Vac, 60Hz   |
| Tested By                | Greg Lin                         |                 |                |

Antenna Polarity & Test Distance: Horizontal at 3 M

| No. | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
|-----|-------------|---------------|-----------------------|------------------------|------------|-------------|-------------|
| 1   | 35.82       | -55.2         | -35.8                 | -15.9                  | -51.7      | -13.0       | -38.7       |
| 2   | 106.63      | -42.1         | -47.9                 | -2.2                   | -50.1      | -13.0       | -37.1       |
| 3   | 242.43      | -55.3         | -60.8                 | -1.4                   | -62.2      | -13.0       | -49.2       |
| 4   | 458.74      | -68.3         | -71.8                 | 3.5                    | -68.3      | -13.0       | -55.3       |
| 5   | 753.62      | -68.6         | -68.5                 | 3.9                    | -64.6      | -13.0       | -51.6       |
| 6   | 957.32      | -68.6         | -63.9                 | 3.8                    | -60.1      | -13.0       | -47.1       |

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).




|                          |                                  |                 |                |
|--------------------------|----------------------------------|-----------------|----------------|
| Mode                     | TX channel 18607<br>(1850.70MHz) | Frequency Range | Below 1000 MHz |
| Environmental Conditions | 25deg. C, 66%RH                  | Input Power     | 120Vac, 60Hz   |
| Tested By                | Greg Lin                         |                 |                |

| Antenna Polarity & Test Distance: Vertical at 3 M |             |               |                       |                        |            |             |             |
|---------------------------------------------------|-------------|---------------|-----------------------|------------------------|------------|-------------|-------------|
| No.                                               | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                 | 34.85       | -42.2         | -35.9                 | -16.5                  | -52.4      | -13.0       | -39.4       |
| 2                                                 | 180.35      | -45.9         | -46.4                 | -2.9                   | -49.3      | -13.0       | -36.3       |
| 3                                                 | 313.24      | -61.3         | -65.4                 | 4.0                    | -61.4      | -13.0       | -48.4       |
| 4                                                 | 595.51      | -68.5         | -68.9                 | 3.8                    | -65.1      | -13.0       | -52.1       |
| 5                                                 | 835.10      | -68.9         | -65.5                 | 3.8                    | -61.7      | -13.0       | -48.7       |
| 6                                                 | 955.38      | -68.6         | -63.0                 | 3.8                    | -59.2      | -13.0       | -46.2       |

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).




LTE Band 2, Channel Bandwidth: 5MHz

|                          |                                  |                 |                |
|--------------------------|----------------------------------|-----------------|----------------|
| Mode                     | TX channel 18625<br>(1852.50MHz) | Frequency Range | Below 1000 MHz |
| Environmental Conditions | 25deg. C, 66%RH                  | Input Power     | 120Vac, 60Hz   |
| Tested By                | Greg Lin                         |                 |                |

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 30.97       | -49.0         | -26.5                 | -18.8                  | -45.3      | -13.0       | -32.3       |
| 2                                                   | 177.44      | -43.3         | -48.2                 | -3.0                   | -51.2      | -13.0       | -38.2       |
| 3                                                   | 268.62      | -58.9         | -61.5                 | -1.5                   | -63.0      | -13.0       | -50.0       |
| 4                                                   | 538.28      | -68.1         | -71.6                 | 3.8                    | -67.8      | -13.0       | -54.8       |
| 5                                                   | 753.62      | -68.6         | -68.5                 | 3.9                    | -64.6      | -13.0       | -51.6       |
| 6                                                   | 957.32      | -68.6         | -63.9                 | 3.8                    | -60.1      | -13.0       | -47.1       |

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).




|                          |                                  |                 |                |
|--------------------------|----------------------------------|-----------------|----------------|
| Mode                     | TX channel 18625<br>(1852.50MHz) | Frequency Range | Below 1000 MHz |
| Environmental Conditions | 25deg. C, 66%RH                  | Input Power     | 120Vac, 60Hz   |
| Tested By                | Greg Lin                         |                 |                |

| Antenna Polarity & Test Distance: Vertical at 3 M |             |               |                       |                        |            |             |             |
|---------------------------------------------------|-------------|---------------|-----------------------|------------------------|------------|-------------|-------------|
| No.                                               | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                 | 30.00       | -44.8         | -35.3                 | -19.4                  | -54.7      | -13.0       | -41.7       |
| 2                                                 | 172.59      | -47.7         | -48.3                 | -2.9                   | -51.2      | -13.0       | -38.2       |
| 3                                                 | 260.86      | -65.3         | -62.8                 | -1.5                   | -64.3      | -13.0       | -51.3       |
| 4                                                 | 432.55      | -67.6         | -71.3                 | 3.5                    | -67.8      | -13.0       | -54.8       |
| 5                                                 | 649.83      | -68.6         | -66.7                 | 3.6                    | -63.1      | -13.0       | -50.1       |
| 6                                                 | 950.53      | -69.1         | -63.5                 | 3.7                    | -59.8      | -13.0       | -46.8       |

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).




LTE Band 2, Channel Bandwidth: 20MHz

|                          |                                  |                 |                |
|--------------------------|----------------------------------|-----------------|----------------|
| Mode                     | TX channel 18700<br>(1860.00MHz) | Frequency Range | Below 1000 MHz |
| Environmental Conditions | 25deg. C, 66%RH                  | Input Power     | 120Vac, 60Hz   |
| Tested By                | Greg Lin                         |                 |                |

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 32.91       | -49.3         | -28.5                 | -17.7                  | -46.2      | -13.0       | -33.2       |
| 2                                                   | 175.50      | -43.9         | -48.7                 | -2.8                   | -51.5      | -13.0       | -38.5       |
| 3                                                   | 246.31      | -54.8         | -60.1                 | -1.6                   | -61.7      | -13.0       | -48.7       |
| 4                                                   | 541.19      | -68.4         | -71.9                 | 3.9                    | -68.0      | -13.0       | -55.0       |
| 5                                                   | 728.40      | -67.8         | -67.7                 | 3.6                    | -64.1      | -13.0       | -51.1       |
| 6                                                   | 925.31      | -68.0         | -63.5                 | 3.7                    | -59.8      | -13.0       | -46.8       |

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).




|                          |                                  |                 |                |
|--------------------------|----------------------------------|-----------------|----------------|
| Mode                     | TX channel 18700<br>(1860.00MHz) | Frequency Range | Below 1000 MHz |
| Environmental Conditions | 25deg. C, 66%RH                  | Input Power     | 120Vac, 60Hz   |
| Tested By                | Greg Lin                         |                 |                |

| Antenna Polarity & Test Distance: Vertical at 3 M |             |               |                       |                        |            |             |             |
|---------------------------------------------------|-------------|---------------|-----------------------|------------------------|------------|-------------|-------------|
| No.                                               | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                 | 62.98       | -36.5         | -40.8                 | -2.4                   | -43.2      | -13.0       | -30.2       |
| 2                                                 | 176.47      | -43.8         | -44.6                 | -2.9                   | -47.5      | -13.0       | -34.5       |
| 3                                                 | 276.38      | -67.3         | -62.4                 | -1.6                   | -64.0      | -13.0       | -51.0       |
| 4                                                 | 440.31      | -68.2         | -71.7                 | 3.5                    | -68.2      | -13.0       | -55.2       |
| 5                                                 | 692.51      | -67.2         | -65.0                 | 3.6                    | -61.4      | -13.0       | -48.4       |
| 6                                                 | 950.53      | -67.5         | -61.9                 | 3.7                    | -58.2      | -13.0       | -45.2       |

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).



Above 1GHz

LTE Band 2, Channel Bandwidth: 1.4MHz

|                          |                                  |                 |              |
|--------------------------|----------------------------------|-----------------|--------------|
| Mode                     | TX channel 18607<br>(1850.70MHz) | Frequency Range | 1GHz ~ 18GHz |
| Environmental Conditions | 25deg. C, 66%RH                  | Input Power     | 120Vac, 60Hz |
| Tested By                | Han Wu                           |                 |              |

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 3701.40     | -57.5         | -49.0                 | 1.4                    | -47.6      | -13.0       | -34.6       |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 3701.40     | -58.4         | -50.2                 | 1.4                    | -48.8      | -13.0       | -35.8       |

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

|                          |                                  |                 |              |
|--------------------------|----------------------------------|-----------------|--------------|
| Mode                     | TX channel 18900<br>(1880.00MHz) | Frequency Range | 1GHz ~ 18GHz |
| Environmental Conditions | 25deg. C, 66%RH                  | Input Power     | 120Vac, 60Hz |
| Tested By                | Han Wu                           |                 |              |

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 3760.00     | -57.1         | -48.6                 | 1.3                    | -47.3      | -13.0       | -34.3       |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 3760.00     | -58.0         | -49.7                 | 1.3                    | -48.4      | -13.0       | -35.4       |

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

|                          |                                  |                 |              |
|--------------------------|----------------------------------|-----------------|--------------|
| Mode                     | TX channel 19193<br>(1909.30MHz) | Frequency Range | 1GHz ~ 18GHz |
| Environmental Conditions | 25deg. C, 66%RH                  | Input Power     | 120Vac, 60Hz |
| Tested By                | Han Wu                           |                 |              |

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 3818.60     | -57.7         | -49.4                 | 1.4                    | -48.0      | -13.0       | -35.0       |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 3818.60     | -58.4         | -50.2                 | 1.4                    | -48.8      | -13.0       | -35.8       |

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 2, Channel Bandwidth: 5MHz

|                          |                                  |                 |              |
|--------------------------|----------------------------------|-----------------|--------------|
| Mode                     | TX channel 18625<br>(1852.50MHz) | Frequency Range | 1GHz ~ 18GHz |
| Environmental Conditions | 25deg. C, 66%RH                  | Input Power     | 120Vac, 60Hz |
| Tested By                | Han Wu                           |                 |              |

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 3705.00     | -56.9         | -48.4                 | 1.4                    | -47.0      | -13.0       | -34.0       |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 3705.00     | -58.0         | -49.8                 | 1.4                    | -48.4      | -13.0       | -35.4       |

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

|                          |                                  |                 |              |
|--------------------------|----------------------------------|-----------------|--------------|
| Mode                     | TX channel 18900<br>(1880.00MHz) | Frequency Range | 1GHz ~ 18GHz |
| Environmental Conditions | 25deg. C, 66%RH                  | Input Power     | 120Vac, 60Hz |
| Tested By                | Han Wu                           |                 |              |

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 3760.00     | -56.8         | -48.3                 | 1.3                    | -47.0      | -13.0       | -34.0       |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 3760.00     | -58.5         | -50.2                 | 1.3                    | -48.9      | -13.0       | -35.9       |

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

|                          |                                  |                 |              |
|--------------------------|----------------------------------|-----------------|--------------|
| Mode                     | TX channel 19175<br>(1907.50MHz) | Frequency Range | 1GHz ~ 18GHz |
| Environmental Conditions | 25deg. C, 66%RH                  | Input Power     | 120Vac, 60Hz |
| Tested By                | Han Wu                           |                 |              |

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 3815.00     | -57.5         | -49.2                 | 1.4                    | -47.8      | -13.0       | -34.8       |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 3815.00     | -58.3         | -50.1                 | 1.4                    | -48.7      | -13.0       | -35.7       |

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 2, Channel Bandwidth: 20MHz

|                          |                                  |                 |              |
|--------------------------|----------------------------------|-----------------|--------------|
| Mode                     | TX channel 18700<br>(1860.00MHz) | Frequency Range | 1GHz ~ 18GHz |
| Environmental Conditions | 25deg. C, 66%RH                  | Input Power     | 120Vac, 60Hz |
| Tested By                | Han Wu                           |                 |              |

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 3720.00     | -57.1         | -48.6                 | 1.4                    | -47.2      | -13.0       | -34.2       |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 3720.00     | -58.3         | -50.1                 | 1.4                    | -48.7      | -13.0       | -35.7       |

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

|                          |                                  |                 |              |
|--------------------------|----------------------------------|-----------------|--------------|
| Mode                     | TX channel 18900<br>(1880.00MHz) | Frequency Range | 1GHz ~ 18GHz |
| Environmental Conditions | 25deg. C, 66%RH                  | Input Power     | 120Vac, 60Hz |
| Tested By                | Han Wu                           |                 |              |

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 3760.00     | -57.2         | -48.7                 | 1.3                    | -47.4      | -13.0       | -34.4       |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 3760.00     | -58.2         | -49.9                 | 1.3                    | -48.6      | -13.0       | -35.6       |

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

|                          |                                  |                 |              |
|--------------------------|----------------------------------|-----------------|--------------|
| Mode                     | TX channel 19100<br>(1900.00MHz) | Frequency Range | 1GHz ~ 18GHz |
| Environmental Conditions | 25deg. C, 66%RH                  | Input Power     | 120Vac, 60Hz |
| Tested By                | Han Wu                           |                 |              |

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |            |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 3800.00     | -57.5         | -49.1                 | 1.3                    | -47.8      | -13.0       | -34.8       |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |            |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 3800.00     | -58.8         | -50.6                 | 1.3                    | -49.3      | -13.0       | -36.3       |

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

### Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

### Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

### Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---