

RF EXPOSURE REPORT

For

Waylens Inc.

2711 Centerville Road - Suite 400, Wilmington, Delaware, United States 19808

FCC ID: 2AKAF-CAM15

Report Type: Original Report	Product Name: AI Recorder I
Report Number:	<u> RSA240229004-00D </u>
Report Date:	<u> 2024-04-25 </u>
Reviewed By:	<u> Jenny Yang </u> <i>Jenny Yang</i>
Approved By:	<u> Kyle Xu </u> <i>Kyle Xu</i>
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu Province, China Tel: +86-512-86175000 Fax: +86-512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Kunshan). This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, or any agency of the U.S.Government.

TABLE OF CONTENTS

REPORT REVISION HISTORY.....3

GENERAL INFORMATION.....4

 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)4

FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)5

EUT PHOTOGRAPHS7

REPORT REVISION HISTORY

Number of Revisions	Report No.	Version	Issue Date	Description
0	RSHA240229004-00D	R1V1	2024-04-25	Initial Release

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	Waylens Inc.
Product Name:	AI Recorder I
Tested Model:	CAM15
Power Supply:	DC 12V
Maximum Peak Output Power:	Classic BT GFSK: 4.59 dBm $\pi/4$ -DQPSK: 5.47 dBm 8DPSK: 5.91 dBm 2.4G Wi-Fi: 802.11b: 18.90 dBm 802.11g: 22.62 dBm 802.11n20: 21.93 dBm 802.11n40: 22.73 dBm BLE(1Mbps): -16.79dBm
RF Function:	Classic BT; 2.4G Wi-Fi; BLE; LTE
Operating Band/Frequency:	Classic BT/BLE: 2402-2480 MHz 2.4G Wi-Fi: 2412~2462 MHz(802.11b/g/n20), 2422~2452 MHz(802.11n40)
Channel Number:	Classic BT: 79 2.4G Wi-Fi: 11(802.11b/g/n20), 7(802.11n40) BLE: 40
Channel Separation:	Classic BT: 1 MHz 2.4G Wi-Fi: 5 MHz BLE: 2 MHz
Modulation Type:	Classic BT: GFSK, $\pi/4$ -DQPSK, 8DPSK 2.4G Wi-Fi: DSSS, OFDM BLE: GFSK
Antenna Type:	FPC Antenna
★Maximum Antenna Gain:	2.93 dBi

Note: The maximum antenna gain was declared by the manufacturer.

All measurement and test data in this report was gathered from production sample serial number: RSHA240229004-1 (Assigned by the BACL (Kunshan). The EUT supplied by the applicant was received on 2024-02-29.)

FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary

Predication of MPE limit at a given distance

$S = PG/4 \pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Calculated Data:

Mode	Frequency Range (MHz)	Antenna Gain		★Tune-up Output Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)	MPE ratio
		(dBi)	(numeric)	(dBm)	(mW)				
Classic BT	2402~2480	2.93	1.96	6.0	3.98	20	0.0016	1.0	0.0016
BLE	2402~2480	2.93	1.96	-16.5	0.02	20	0.00001	1.0	0.00001
2.4G Wi-Fi	2412~2462	2.93	1.96	23.0	199.53	20	0.0778	1.0	0.0778

Mode	Frequency (MHz)	Antenna Gain		★Tune-up Output Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)	MPE ratio
		(dBi)	(numeric)	(dBm)	(mW)				
LTE Band 2	1850-1910	3.01	2.00	25.0	316.23	20	0.1258	1.0	0.1258
LTE Band 4	1710-1755	1.84	1.53	25.0	316.23	20	0.0961	1.0	0.0961
LTE Band 5	824-849	0.05	1.01	25.0	316.23	20	0.0635	0.5493	0.1156
LTE Band 12	699-716	-3.80	0.42	25.0	316.23	20	0.0262	0.466	0.0562
LTE Band 13	777-787	-0.25	0.94	25.0	316.23	20	0.0594	0.5180	0.1147
LTE Band 66	1710-1780	1.84	1.53	25.0	316.23	20	0.0961	1.0	0.0961

This device contains module (model No.: EG915Q-NA, FCC ID: XMR2023EG915QNA) grant date: 07/25/2023.

Note:

1. For the above tune up power were declared by the manufacturer.
2. Wi-Fi/Classic BT / BLE and LTE can transmit simultaneously, as below:

$$\sum_i \frac{S_i}{S_{Limit,i}} = 0.0778/1.00 + 0.1258/1.00 = 0.0778 + 0.1258 = 0.2036 < 1.0$$

Result: The device meet FCC MPE at 20 cm distance.

EUT PHOTOGRAPHS

Please refer to the attachment EXHIBIT A-EUT EXTERNAL PHOTOGRAPHS and EXHIBIT B-EUT INTERNAL PHOTOGRAPHS.

Declarations

1. The laboratory is not responsible for the authenticity of any information provided by the applicant. Information from the applicant that may affect test results is marked with “★”.
2. The test data was only valid for the test sample(s).
3. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.
4. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
5. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor $k=2$ with the 95.45% confidence interval.

******* END OF REPORT *******