

FCC RADIO TEST REPORT

FCC ID: 2BFHLDIESELHD2

Product : Professional Diagnostic Tool

Trade Mark : 

Model Name : Diesel Handheld 2

Family Model : N/A

Report No. : S24120600504004

Issue Date: Jan. 26, 2025

Prepared for

Diesel Laptops, LLC

7440 Broad River Rd Irmo, SC 29063

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street,
Baoan District, Shenzhen, Guangdong, People's Republic of China

Tel. 0755-23200050 Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's name.....: Diesel Laptops, LLC
Address: 7440 Broad River Rd Irmo, SC 29063
Manufacturer's Name.....: Diesel Laptops, LLC
Address: 7440 Broad River Rd Irmo, SC 29063
Product description
Product name: Professional Diagnostic Tool
Trade Mark: 
Model and/or type reference : Diesel Handheld 2
Family Model.....: N/A
Test Sample number.....: S241206005004
Date of Test: Dec. 06, 2024 ~ Jan. 26, 2025
Standards.....: FCC Part15.407
Test procedure.....: ANSI C63.10-2013 and KDB 789033 D02 General UNII Test Procedures New Rules v02r01

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements/ the Industry Canada requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

Prepared : 
By : Allen Liu
(Project Engineer)

Reviewed : 
By : Aaron Cheng
(Supervisor)

Approved : 
By : Alex Li
(Manager)

Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	6
1.1 FACILITIES AND ACCREDITATIONS	7
1.2 MEASUREMENT UNCERTAINTY	7
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	10
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	12
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	13
3 . TEST REQUIREMENTS	15
3.1 CONDUCTED EMISSION MEASUREMENT	15
3.2 RADIATED EMISSION MEASUREMENT	20
3.3 POWER SPECTRAL DENSITY TEST	35
3.4 26DB & 99% EMISSION BANDWIDTH	38
3.5 MINIMUM 6 DB BANDWIDTH	40
3.6 MAXIMUM CONDUCTED OUTPUT POWER	42
3.7 OUT OF BAND EMISSIONS	44
3.8 SPURIOUS RF CONDUCTED EMISSIONS	46
3.9 FREQUENCY STABILITY MEASUREMENT	47
4. ANTENNA REQUIREMENT	54
4.1 STANDARD REQUIREMENT	54
4.2 EUT ANTENNA	54
5. TEST RESULTS	55
5.1 5.2G WIFI	55
5.1.1 DUTY CYCLE	55
5.1.2 MAXIMUM CONDUCTED OUTPUT POWER	63
5.1.3 -26DB BANDWIDTH	64
5.1.4 OCCUPIED CHANNEL BANDWIDTH	72
5.1.5 MAXIMUM POWER SPECTRAL DENSITY LEVEL	80
5.1.6 BAND EDGE	88
5.1.7 CONDUCTED RF SPURIOUS EMISSION	95
5.2 5.8G WIFI	103
5.2.1 DUTY CYCLE	103
5.2.2 MAXIMUM CONDUCTED OUTPUT POWER	111

Table of Contents

Page

5.2.3 -6DB BANDWIDTH	112
5.2.4 OCCUPIED CHANNEL BANDWIDTH	120
5.2.5 MAXIMUM POWER SPECTRAL DENSITY LEVEL	128
5.2.6 BAND EDGE	136
5.2.7 CONDUCTED RF SPURIOUS EMISSION	142

Revision History

Report No.	Version	Description	Issued Date
S24120600504004	Rev.01	Initial issue of report	Jan. 26, 2025

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart E			
Standard Section	Test Item	Judgment	Remark
15.207	AC Power Line Conducted Emissions	PASS	
15.209(a), 15.407 (b)(1) 15.407 (b)(4)	Spurious Radiated Emissions	PASS	
15.407 (a)(1) 15.407 (a)(3)	26 dB and 99% Emission Bandwidth	PASS	
15.407(e)	Minimum 6 dB bandwidth	PASS	
15.407 (a)(1) 15.407 (a)(3)	Maximum Conducted Output Power	PASS	
15.407(b)(1) 15.407(b)(4)	Band Edge	PASS	
15.407 (a)(1) 15.407 (a)(3)	Power Spectral Density	PASS	
15.407(b)	Spurious Emissions at Antenna Terminals	PASS	
15.203	Antenna Requirement	PASS	
15.407(c)	Automatically discontinue transmission	PASS	Note 2

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

(2) The product is a client device, and the data transmission is limited by the AP.
When the information to be sent is missing or the operation fails,
the device will automatically stop sending and directly connect to the AP correctly again.

1.1 FACILITIES AND ACCREDITATIONS

FACILITIES

All measurement facilities used to collect the measurement data are located at
No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen,
Guangdong, People's Republic of China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab. : The Certificate Registration Number is L5516.

IC-Registration : The Certificate Registration Number is 9270A.
CAB identifier:CN0074

FCC- Accredited : Test Firm Registration Number: 463705.
Designation Number: CN1184

A2LA-Lab. : The Certificate Registration Number is 4298.01
This laboratory is accredited in accordance with the recognized
International Standard ISO/IEC 17025:2005 General requirements for the
competence of testing and calibration laboratories.
This accreditation demonstrates technical competence for a defined
scope and the operation of a laboratory quality management system
(refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).

Name of Firm : Shenzhen NTEK Testing Technology Co., Ltd.

Site Location : No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan
District, Shenzhen, Guangdong, People's Republic of China

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.80\text{dB}$
2	RF power, conducted, PSD	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(30MHz~1GHz)	$\pm 2.64\text{dB}$
5	All emissions, radiated(1GHz~6GHz)	$\pm 2.40\text{dB}$
6	All emissions, radiated(> 6GHz)	$\pm 2.52\text{dB}$
7	Temperature	$\pm 0.5^\circ\text{C}$
8	Humidity	$\pm 2\%$
9	All emissions, radiated(9KHz~30MHz)	$\pm 6\text{dB}$
10	Occupied bandwidth	$\pm 4.7\text{dB}$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Professional Diagnostic Tool	
Trade Mark		
FCC ID	2BFHLDIESELHD2	
Model Name	Diesel Handheld 2	
Family Model	N/A	
Model Difference	N/A	
Product Description	IEEE 802.11 WLAN Mode Supported	☒ 802.11a/n/ac (20MHz channel bandwidth) ☒ 802.11n/ac (40MHz channel bandwidth) ☒ 802.11ac (80MHz channel bandwidth)
	Modulation	OFDM with BPSK/QPSK/16QAM/64QAM/256QAM for 802.11a/n/ac;
	Operating Frequency Range	☒ 5180-5240MHz for 802.11a/n(HT20)/ac(VHT20); 5190-5230MHz for 802.11n(HT40)/ac(VHT40); 5210MHz for 802.11ac(VHT80) ☒ 5745-5825 MHz for 802.11a/n(HT20)/ac(VHT20); 5755-5795 MHz for 802.11n(HT40)/ac(VHT40); 5775MHz for 802.11ac(VHT80)
	Number of Channels	☒ 4 channels for 802.11a/n20/ac20 in the 5180-5240MHz band ; 2 channels for 802.11 n40/ac40 in the 5190-5230MHz band ; 1 channels for 802.11 ac80 in the 5210MHz band ; ☒ 5 channels for 802.11a/n20/ac20 in the 5745-5825MHz band ; 2 channels for 802.11 n40/ac40 in the 5755-5795MHz band ; 1 channels for 802.11 ac80 in the 5775MHz band ;
	Antenna Type	FPC Antenna
	Antenna Gain	4.51dBi
	Based on the application, features, or specification exhibited in User's Manual, More details of EUT technical specification, please refer to the User's Manual.	
Adapter	N/A	
Battery	DC 3.6V, 3000mAh, 10.8Wh	
Power supply	DC 3.6V from battery or DC 5V/1.5A from adapter or DC 24V/0.5A from the vehicle battery	
Connecting I/O Port(s)	Please refer to the User's Manual	
HW Version	N/A	
SW Version	N/A	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2. The product comes with different colored rubber sleeves.
3. Frequency and Channel list for 802.11a/n/ac(20MHz) band I (5180-5240MHz):

802.11a/n/ac(20MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220	-	-	-	-
40	5200	48	5240	-	-	-	-

Frequency and Channel list for 802.11n/ac(40MHz) band I (5190-5230MHz):

802.11n/ac(40MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	-	-	-	-	-	-
46	5230	-	-	-	-	-	-

Frequency and Channel list for 802.11ac(80MHz) band I (5210MHz):

802.11ac(80MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
42	5210	-	-	-	-	-	-

Frequency and Channel list for 802.11a/n/ac(20 MHz) band IV (5745-5825MHz):

802.11a/n/ac(20 MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	153	5765	157	5785	161	5805
165	5825	-	-	-	-	-	-

Frequency and Channel list for 802.11n/ac(40MHz) band IV (5755-5795MHz):

802.11n/ac(40MHz) Carrier Frequency Channel					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	5755	159	5795	-	-

Frequency and Channel list for 802.11ac(80MHz) band IV (5775MHz):

802.11ac(80MHz) Carrier Frequency Channel					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
155	5775			-	-

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11a / n 20 / ac 20 CH36/ CH40/ CH 48 802.11a / n 20 / ac 20 CH149/ CH157/ CH 165
Mode 3	802.11n40 / ac40 CH38/ CH 46 802.11n 40 / ac 40 CH 151 / CH 159
Mode 4	802.11ac80 CH 42 802.11ac 80 CH 155


For Radiated Emission	
Final Test Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11a / n 20 / ac 20 CH36/ CH40/ CH 48 802.11a / n 20 / ac 20 CH149/ CH157/ CH 165
Mode 3	802.11n40 / ac40 CH38/ CH 46 802.11n 40 / ac 40 CH 151 / CH 159
Mode 4	802.11ac80 CH 42 802.11ac 80 CH 155

Note:


- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED


For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note:1.The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.
2.EUT built-in battery-powered, the battery is fully-charged.

2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
AE-1	Adapter	N/A	N/A	Peripherals
AE-2	Smart BOX	N/A	N/A	Peripherals
AE-3	Adapter	N/A	N/A	Peripherals
AE-4	Notebook	N/A	N/A	Peripherals
AE-5	USB Disk	N/A	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	USB Cable	YES	NO	0.8m
C-2	RS232 Cable	YES	NO	1.2m
C-3	DC Cable	YES	NO	0.8m
C-4	USB Cable	YES	NO	0.8m
C-5	RF Cable	YES	NO	0.1m

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4440A	MY41000130	2024.04.26	2025.04.25	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2024.04.25	2025.04.24	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2024.04.25	2025.04.24	1 year
4	Test Receiver	R&S	ESPI7	101318	2024.04.26	2025.04.25	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2024.05.12	2025.05.11	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2024.04.26	2027.04.25	3 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2024.05.12	2027.05.11	3 year
8	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	803	2024.05.12	2027.05.11	3 year
9	Amplifier	EMC	EMC051835SE	980246	2024.04.25	2025.04.24	1 year
10	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	055	2024.05.17	2027.05.16	3 year
11	Power Meter	DARE	RPR3006W	15100041SN084	2024.04.25	2025.04.24	1 year
12	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2023.05.06	2026.05.05	3 year
13	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2023.05.06	2026.05.05	3 year
14	High Test Cable(1G-40G Hz)	N/A	R-03	N/A	2022.06.17	2025.06.16	3 year
15	Filter	TRILTHIC	2400MHz	29	2024.04.26	2027.04.25	3 year
16	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2024.04.26	2025.04.25	1 year
2	LISN	R&S	ENV216	101313	2024.04.25	2025.04.24	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2024.04.25	2025.04.24	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2024.04.26	2027.04.25	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2023.05.06	2026.05.05	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2023.05.06	2026.05.05	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2023.05.06	2026.05.05	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable& Aux Equipment which is scheduled for calibration every 3 years.

Measurement Software

Item	Manufacturer	Software Name	Software Version	Description
1	MWRFTtest	MTS 8310 2.4GHz/5GHz	2.0	RF Conducted Test
2	Farad	EZ-EMC_RE	AIT-03A	RadiatedTest
3	Farad	EZ-EMC_CE	AIT-03A	AC Conducted Test

3. TEST REQUIREMENTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 APPLICABLE STANDARD


According to FCC Part 15.207(a)

3.1.2 CONFORMANCE LIMIT

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
 2. The lower limit shall apply at the transition frequencies
 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3.1.3 TEST CONFIGURATION



3.1.4 TEST PROCEDURE

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.


3.1.5 TEST RESULTS

EUT :	Professional Diagnostic Tool	Model Name :	Diesel Handheld 2
Temperature :	22.3°C	Relative Humidity :	44.2%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.2G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1607	30.84	10.02	40.86	65.43	-24.57	QP
0.1607	20.09	10.02	30.11	55.43	-25.32	AVG
0.2060	29.87	10.12	39.99	63.37	-23.38	QP
0.2060	19.09	10.12	29.21	53.37	-24.16	AVG
0.4260	24.20	10.55	34.75	57.33	-22.58	QP
0.4260	14.78	10.55	25.33	47.33	-22.00	AVG
3.0140	15.72	9.88	25.60	56.00	-30.40	QP
3.0140	5.46	9.88	15.34	46.00	-30.66	AVG
12.0580	37.70	-0.79	36.91	60.00	-23.09	QP
12.0580	27.24	-0.79	26.45	50.00	-23.55	AVG
19.0940	26.10	12.60	38.70	60.00	-21.30	QP
19.0940	15.72	12.60	28.32	50.00	-21.68	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Professional Diagnostic Tool	Model Name :	Diesel Handheld 2
Temperature :	22.3℃	Relative Humidity :	44.2%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.2G)

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1539	36.85	9.44	46.29	65.79	-19.50	QP
0.1539	26.58	9.44	36.02	55.79	-19.77	AVG
0.2340	27.79	9.57	37.36	62.31	-24.95	QP
0.2340	17.65	9.57	27.22	52.31	-25.09	AVG
0.4300	20.79	9.91	30.70	57.25	-26.55	QP
0.4300	10.39	9.91	20.30	47.25	-26.95	AVG
3.0140	18.79	9.14	27.93	56.00	-28.07	QP
3.0140	8.11	9.14	17.25	46.00	-28.75	AVG
12.0620	37.80	-1.58	36.22	60.00	-23.78	QP
12.0620	27.96	-1.58	26.38	50.00	-23.62	AVG
15.0780	26.48	11.06	37.54	60.00	-22.46	QP
15.0780	16.41	11.06	27.47	50.00	-22.53	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Professional Diagnostic Tool	Model Name :	Diesel Handheld 2
Temperature :	22.3 °C	Relative Humidity :	44.2%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.8G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1620	31.18	10.02	41.20	65.36	-24.16	QP
0.1620	21.09	10.02	31.11	55.36	-24.25	AVG
0.2060	29.37	10.12	39.49	63.37	-23.88	QP
0.2060	19.33	10.12	29.45	53.37	-23.92	AVG
0.4380	23.90	10.57	34.47	57.10	-22.63	QP
0.4380	14.01	10.57	24.58	47.10	-22.52	AVG
3.0140	16.22	9.88	26.10	56.00	-29.90	QP
3.0140	6.81	9.88	16.69	46.00	-29.31	AVG
12.0580	39.20	-0.79	38.41	60.00	-21.59	QP
12.0580	29.09	-0.79	28.30	50.00	-21.70	AVG
19.0940	27.60	12.60	40.20	60.00	-19.80	QP
19.0940	17.65	12.60	30.25	50.00	-19.75	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Professional Diagnostic Tool	Model Name :	Diesel Handheld 2
Temperature :	22.3 °C	Relative Humidity :	44.2%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.8G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1539	36.85	9.44	46.29	65.79	-19.50	QP
0.1539	27.00	9.44	36.44	55.79	-19.35	AVG
0.2940	23.53	9.68	33.21	60.41	-27.20	QP
0.2940	13.68	9.68	23.36	50.41	-27.05	AVG
0.4420	20.09	9.91	30.00	57.02	-27.02	QP
0.4420	10.34	9.91	20.25	47.02	-26.77	AVG
3.0140	18.29	9.14	27.43	56.00	-28.57	QP
3.0140	8.88	9.14	18.02	46.00	-27.98	AVG
12.0620	37.30	-1.58	35.72	60.00	-24.28	QP
12.0620	27.32	-1.58	25.74	50.00	-24.26	AVG
17.0860	25.59	11.42	37.01	60.00	-22.99	QP
17.0860	16.24	11.42	27.66	50.00	-22.34	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 APPLICABLE STANDARD

According to FCC Part 15.407(b) and 15.209

3.2.2 CONFORMANCE LIMIT

According to FCC Part 15.407(b)(9)(10): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	24000/F(KHz)	20 log (uV/m)	30
1.705-30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dBuV/m=20 log (uV/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. For Frequency 9kHz~30MHz:

Distance extrapolation factor =40log(Specific distance/ test distance)(dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor.

For Frequency above 30MHz:

Distance extrapolation factor =20log(Specific distance/ test distance)(dB);


Limit line=Specific limits(dBuV) + distance extrapolation factor.

3.2.3 MEASURING INSTRUMENTS


The Measuring equipment is listed in the section 6.3 of this test report.

3.2.4 TEST CONFIGURATION


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



3.2.5 TEST PROCEDURE

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 1MHz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	1 MHz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW [kHz]})$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

3.2.6 TEST RESULTS (9KHz – 30 MHz)

EUT:	Professional Diagnostic Tool	Model Name. :	Diesel Handheld 2
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 3.6V
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	N/A
--	--	--	--	N/A

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


3.2.7 TEST RESULTS (30MHz – 1GHz)

EUT :	Professional Diagnostic Tool	Model Name. :	Diesel Handheld 2
Temperature :	24.7°C	Relative Humidity :	53%
Pressure :	1010 hPa	Test Voltage :	DC 3.6V
Test Mode :	TX(5.2G)- 802.11a (Mid CH)		

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	34.0363	15.22	17.00	32.22	40.00	-7.78	QP
V	139.8505	20.87	14.19	35.06	43.50	-8.44	QP
V	234.9910	16.04	18.01	34.05	46.00	-11.95	QP
V	350.4766	7.35	21.57	28.92	46.00	-17.08	QP
V	480.5276	6.94	23.84	30.78	46.00	-15.22	QP
V	948.7610	7.68	30.63	38.31	46.00	-7.69	QP

Remark:


Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	34.0363	7.17	17.00	24.17	40.00	-15.83	QP
H	72.3375	6.75	14.82	21.57	40.00	-18.43	QP
H	118.1860	16.03	15.65	31.68	43.50	-11.82	QP
H	230.9067	16.68	18.00	34.68	46.00	-11.32	QP
H	350.4766	12.11	21.57	33.68	46.00	-12.32	QP
H	851.0353	6.75	29.75	36.50	46.00	-9.50	QP

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Note(1) "802.11a" mode is the worst mode.


(2) Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

EUT :	Professional Diagnostic Tool	Model Name. :	Diesel Handheld 2
Temperature :	25°C	Relative Humidity :	55%
Pressure :	1010 hPa	Test Voltage :	DC 3.6V
Test Mode :	TX(5.8G)- 802.11a (Mid CH)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	34.1560	16.20	17.02	33.22	40.00	-6.78	QP
V	39.0242	14.74	18.14	32.88	40.00	-7.12	QP
V	71.3300	13.88	15.09	28.97	40.00	-11.03	QP
V	138.3873	23.04	14.19	37.23	43.50	-6.27	QP
V	234.9910	15.54	18.01	33.55	46.00	-12.45	QP
V	480.5276	6.94	23.84	30.78	46.00	-15.22	QP

Remark:


Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	38.0782	5.51	17.95	23.46	40.00	-16.54	QP
H	118.1860	16.53	15.65	32.18	43.50	-11.32	QP
H	230.9067	18.18	18.00	36.18	46.00	-9.82	QP
H	350.4766	15.11	21.57	36.68	46.00	-9.32	QP
H	480.5276	8.77	23.84	32.61	46.00	-13.39	QP
H	851.0353	8.75	29.75	38.50	46.00	-7.50	QP

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Note(1)“802.11a” mode is the worst mode.

(2)Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

3.2.8 TEST RESULTS (1GHz-18GHz)

EUT :	Professional Diagnostic Tool	Model Name. :	Diesel Handheld 2
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.6V
Test Mode :	TX(5.2G) - 802.11a		

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G									
Vertical	3694.10	59.14	5.94	35.40	44.00	56.48	74.00	-17.52	Pk
Vertical	3694.10	39.70	5.94	35.40	44.00	37.04	54.00	-16.96	AV
Vertical	10360.15	60.49	8.46	39.75	44.50	64.20	68.20	-4.00	Pk
Vertical	15540.22	59.64	10.12	38.80	44.10	64.46	74.00	-9.54	Pk
Vertical	15540.22	39.88	10.12	38.80	42.70	46.10	54.00	-7.90	AV
Horizontal	3713.00	59.74	5.94	35.18	44.00	56.86	74.00	-17.14	Pk
Horizontal	3713.00	41.00	5.94	35.18	44.00	38.12	54.00	-15.88	AV
Horizontal	10360.47	60.09	8.46	38.71	44.50	62.76	68.20	-5.44	Pk
Horizontal	15540.38	59.09	10.12	38.38	44.10	63.49	74.00	-10.51	Pk
Horizontal	15540.38	39.73	10.12	38.38	44.10	44.13	54.00	-9.87	AV
Low Channel (5200 MHz)-Above 1G									
Vertical	3624.13	60.23	6.48	36.35	44.05	59.01	74.00	-14.99	Pk
Vertical	3624.13	39.04	6.48	36.35	44.05	37.82	54.00	-16.18	AV
Vertical	10400.09	59.90	8.47	37.88	44.51	61.74	68.20	-6.46	Pk
Vertical	15600.15	60.23	10.12	38.80	44.10	65.05	74.00	-8.95	Pk
Vertical	15600.15	39.50	10.12	38.80	42.70	45.72	54.00	-8.28	AV
Horizontal	4202.14	59.91	6.48	36.37	44.05	58.71	74.00	-15.29	Pk
Horizontal	4202.14	40.98	6.48	36.37	44.05	39.78	54.00	-14.22	AV
Horizontal	10400.14	59.15	8.47	38.64	44.50	61.76	68.20	-6.44	Pk
Horizontal	15600.51	60.63	10.12	38.38	44.10	65.03	74.00	-8.97	Pk
Horizontal	15600.51	40.22	10.12	38.38	44.10	44.62	54.00	-9.38	AV
Low Channel (5240 MHz)-Above 1G									
Vertical	4597.70	59.96	7.10	37.24	43.50	60.80	74.00	-13.20	Pk
Vertical	4597.70	40.28	7.10	37.24	43.50	41.12	54.00	-12.88	AV
Vertical	10480.23	59.21	8.46	37.68	44.50	60.85	68.20	-7.35	Pk
Vertical	15720.15	59.80	10.12	38.80	44.10	64.62	74.00	-9.38	Pk
Vertical	15720.15	39.14	10.12	38.80	42.70	45.36	54.00	-8.64	AV
Horizontal	4589.26	60.75	7.10	37.24	43.50	61.59	74.00	-12.41	Pk
Horizontal	4589.26	40.35	7.10	37.24	43.50	41.19	54.00	-12.81	AV
Horizontal	10480.59	60.56	8.46	38.57	44.50	63.09	68.20	-5.11	Pk
Horizontal	15720.18	59.77	10.12	38.38	44.10	64.17	74.00	-9.83	Pk
Horizontal	15720.18	39.44	10.12	38.38	44.10	43.84	54.00	-10.16	AV

Note:"802.11a" mode is the worst mode.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported. Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

EUT :	Professional Diagnostic Tool	Model Name. :	Diesel Handheld 2
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.6V
Test Mode :	TX (5.8G) -- 802.11a		

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)- Above 1G									
Vertical	5122.51	60.59	5.94	35.40	44.00	57.93	74.00	-16.07	Pk
Vertical	5122.51	39.85	5.94	35.40	44.00	37.19	54.00	-16.81	AV
Vertical	11490.60	60.87	8.46	39.75	44.50	64.58	74.00	-9.42	Pk
Vertical	11490.60	40.72	8.46	39.75	44.50	44.43	54.00	-9.57	AV
Vertical	17235.65	40.39	10.12	38.80	44.10	45.21	68.20	-22.99	Pk
Horizontal	5166.60	60.93	5.94	35.18	44.00	58.05	68.20	-10.15	Pk
Horizontal	11490.47	50.83	8.46	38.71	44.50	53.50	74.00	-20.50	Pk
Horizontal	11490.47	39.29	8.46	38.71	44.50	41.96	54.00	-12.04	AV
Horizontal	17235.47	55.67	10.12	38.38	44.10	60.07	68.20	-8.13	Pk
Low Channel (5785 MHz)- Above 1G									
Vertical	5433.40	59.25	6.48	36.35	44.05	58.03	74.00	-15.97	Pk
Vertical	5433.40	40.33	6.48	36.35	44.05	39.11	54.00	-14.89	AV
Vertical	11570.41	60.86	8.47	37.88	44.51	62.70	74.00	-11.30	Pk
Vertical	11570.41	39.02	8.47	37.88	44.51	40.86	54.00	-13.14	AV
Vertical	17355.84	39.93	10.12	38.80	44.10	44.75	68.20	-23.45	Pk
Horizontal	4866.60	59.13	6.48	36.37	44.05	57.93	74.00	-16.07	Pk
Horizontal	4866.60	40.54	6.48	36.37	44.05	39.34	54.00	-14.66	AV
Horizontal	11570.28	60.56	8.47	38.64	44.50	63.17	74.00	-10.83	Pk
Horizontal	11570.28	39.10	8.47	38.64	44.50	41.71	54.00	-12.29	AV
Horizontal	17355.49	49.99	10.12	38.38	44.10	54.39	68.20	-13.81	Pk
Low Channel (5825 MHz)- Above 1G									
Vertical	5244.48	60.08	7.10	37.24	43.50	60.92	68.20	-7.28	Pk
Vertical	11652.42	59.59	8.46	37.68	44.50	61.23	74.00	-12.77	Pk
Vertical	11652.42	39.95	8.46	37.68	44.50	41.59	54.00	-12.41	AV
Vertical	17473.74	49.13	10.12	38.80	44.10	53.95	68.20	-14.25	Pk
Horizontal	5285.29	59.85	7.10	37.24	43.50	60.69	68.20	-7.51	Pk
Horizontal	11652.67	60.93	8.46	38.57	44.50	63.46	74.00	-10.54	Pk
Horizontal	11652.67	39.37	8.46	38.57	44.50	41.90	54.00	-12.10	AV
Horizontal	17474.68	50.24	10.12	38.38	44.10	54.64	68.20	-13.56	Pk

Note:"802.11a" mode is the worst mode.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported. Emission level (dBuV/m) = 20 log Emission level (uV/m).


Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.2.9 TEST RESULTS (18GHz-40GHz)

EUT :	Professional Diagnostic Tool	Model Name. :	Diesel Handheld 2
Temperature :	24.3°C	Relative Humidity :	50%
Pressure :	1010 hPa	Test Voltage :	DC 3.6V
Test Mode :	TX (5.2G)-802.11a TX (5.8G)-802.11a		


All the modulation modes have been tested, and the worst result was report as below:

Low Channel (5180 MHz)-Above 1G



Measurement Result:

Frequency MHz	Meter Reading dBuV	Antenna Factor dB/m	Level dBuV/m	Limits dBuV/m	Margin (dB)	Detector
39538.000	57.55	11.21	68.76	74.00	-5.24	peak
39538.000	38.14	11.21	49.35	54.00	-4.65	AVG




Measurement Result:

Frequency MHz	Meter Reading dBuV	Antenna Factor dB/m	Level dBuV/m	Limits dBuV/m	Margin (dB)	Detector
39802.000	56.06	11.64	67.70	74.00	-6.30	peak
39802.000	37.94	11.64	49.58	54.00	-4.42	AVG

High Channel (5240 MHz)-Above 1G


Horizontal



Measurement Result:

Frequency MHz	Meter Reading dBuV	Antenna Factor dB/m	Level dBuV/m	Limits dBuV/m	Margin (dB)	Detector
39890.000	56.82	11.77	68.59	74.00	-5.41	peak
39978.000	37.57	11.88	49.45	54.00	-4.55	AVG

Vertical




Measurement Result:

Frequency MHz	Meter Reading dBuV	Antenna Factor dB/m	Level dBuV/m	Limits dBuV/m	Margin (dB)	Detector
39714.000	57.62	11.51	69.13	74.00	-4.87	peak
39714.000	38.71	11.51	50.22	54.00	-3.78	AVG

Low Channel (5745 MHz)-Above 1G


Horizontal



Measurement Result:

Frequency MHz	Meter Reading dBuV	Antenna Factor dB/m	Level dBuV/m	Limits dBuV/m	Margin (dB)	Detector
39934.000	56.10	11.82	67.92	74.00	-6.08	peak
39934.000	37.54	11.82	49.36	54.00	-4.64	AVG

Vertical




Measurement Result:

Frequency MHz	Meter Reading dBuV	Antenna Factor dB/m	Level dBuV/m	Limits dBuV/m	Margin (dB)	Detector
39626.000	58.25	11.36	69.61	74.00	-4.39	peak
39626.000	38.99	11.36	50.35	54.00	-3.65	AVG

High Channel (5825 MHz)-Above 1G


Horizontal



Measurement Result:

Frequency MHz	Meter Reading dBuV	Antenna Factor dB/m	Level dBuV/m	Limits dBuV/m	Margin (dB)	Detector
39802.000	55.66	11.64	67.30	74.00	-6.70	peak
39802.000	38.83	11.64	50.47	54.00	-3.53	AVG

Vertical



Measurement Result:

Frequency MHz	Meter Reading dBuV	Antenna Factor dB/m	Level dBuV/m	Limits dBuV/m	Margin (dB)	Detector
39890.000	57.52	11.77	69.29	74.00	-4.71	peak
39890.000	37.93	11.77	49.70	54.00	-4.30	AVG

3.2.10 Spurious Emission in Restricted Band 4.5GHz~5.150 GHz& 5.350GHz~5460GHz

EUT :	Professional Diagnostic Tool	Model Name. :	Diesel Handheld 2
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.6V
Test Mode :	TX (5.2G)-802.11a		

All the modulation modes have been tested, The report just record the worst data mode.

Frequency	Meter Reading	Cable Loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
Low Channel (5180 MHz)									
4500	62.15	5.2	35.6	44.2	58.75	74	-15.25	Pk	Horizontal
4500	36.51	5.2	35.6	44.2	33.11	54	-20.89	AV	Horizontal
4500	62.19	5.2	35.6	44.2	58.79	74	-15.21	Pk	Horizontal
4500	32.95	5.2	35.6	44.2	29.55	54	-24.45	AV	Horizontal
5150	63.03	5.36	35.66	44.22	59.83	74	-14.17	Pk	Horizontal
5150	32.56	5.36	35.66	44.22	29.36	54	-24.64	AV	Horizontal
5150	63.60	5.36	35.66	44.22	60.40	74	-13.60	Pk	Vertical
5150	43.57	5.36	35.66	44.22	40.37	54	-13.63	AV	Vertical
High Channel (5240 MHz)									
5350	63.13	5.68	35.68	44.22	60.27	74	-13.73	Pk	Vertical
5350	33.49	5.68	35.68	44.22	30.63	54	-23.37	AV	Vertical
5350	62.51	5.68	35.68	44.22	59.65	74	-14.35	Pk	Horizontal
5350	37.09	5.68	35.68	44.22	34.23	54	-19.77	AV	Horizontal

Note: (1) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor

(2) "802.11a" mode is the worst mode. When PK value is lower than the Average value limit, average don't record.

3.3 POWER SPECTRAL DENSITY TEST

3.3.1 Applied procedures / limit

According to FCC §15.407(a)(3)

For the band 5.15-5.25 GHz,

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple colocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz

(3) For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

,

3.3.2 TEST PROCEDURE

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:

- a) Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $VBW \geq 3 RBW$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ KHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since $RBW=100 \text{ KHz}$ is available on nearly all spectrum analyzers.

3.3.3 DEVIATION FROM STANDARD

No deviation.

3.3.4 TEST SETUP



3.3.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

3.3.6 TEST RESULTS

EUT :	Professional Diagnostic Tool	Model Name. :	Diesel Handheld 2
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 3.6V
Test Mode :	TX Frequency Band I (5150-5250MHz), Band IV (5725-5850MHz)		

Test data reference attachment.

3.4 26DB & 99% EMISSION BANDWIDTH

3.4.1 Applied procedures / limit


The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

3.4.2 TEST PROCEDURE

- a) Set RBW = approximately 1% of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.



3.4.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.4.4 TEST RESULTS

EUT :	Professional Diagnostic Tool	Model Name. :	Diesel Handheld 2
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 3.6V
Test Mode :	TX Frequency Band I (5150-5250MHz), Band IV (5725-5850MHz)		

Test data reference attachment.

3.5 MINIMUM 6 DB BANDWIDTH

3.5.1 Applied procedures / limit

According to FCC §15.407(e)

(e) Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

3.5.2 TEST PROCEDURE


Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.5.3 DEVIATION FROM STANDARD

No deviation.

3.5.4 TEST SETUP



3.5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.5.6 TEST RESULTS

EUT :	Professional Diagnostic Tool	Model Name. :	Diesel Handheld 2
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.6V
Test Mode :	TX (5G) Mode Frequency Band IV (5725-5850MHz)		

Test data reference attachment.

3.6 MAXIMUM CONDUCTED OUTPUT POWER

3.6.1 PPLIED PROCEDURES / LIMIT

According to FCC §15.407

The maximum conducted output power should not exceed:

Frequency Band(MHz)	Limit
5150~5250	250mW
5725~5850	1W


3.6.2 TEST PROCEDURE

- Method PM-G is measurement using a gated RF average power meter. Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no dutycycle correction factor is required.

3.6.3 DEVIATION FROM STANDARD

No deviation.

3.6.4 TEST SETUP



3.6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.6.6 TEST RESULTS

EUT :	Professional Diagnostic Tool	Model Name. :	Diesel Handheld 2
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.6V
Test Mode :	TX (5G) Mode Frequency Band I (5150-5250MHz), Band IV (5725-5850MHz)		

Test data reference attachment.

3.7 OUT OF BAND EMISSIONS

3.7.1 Applicable Standard

According to FCC §15.407(b)

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.


3.7.2 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

3.7.3 DEVIATION FROM STANDARD

No deviation.

3.7.4 TEST SETUP



3.7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.7.6 TEST RESULTS

EUT :	Professional Diagnostic Tool	Model Name. :	Diesel Handheld 2
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 3.6V

Test data reference attachment.

3.8 SPURIOUS RF CONDUCTED EMISSIONS

3.8.1 Conformance Limit

According to FCC §15.407(b)(1) (4)

3.8.2 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

3.8.3 Test Setup

Please refer to Section 6.1 of this test report.

3.8.4 Test Procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=1MHz and VBW= 3MHz to measure the peak field strength , and measure frequency range from 30MHz to 40GHz.

3.8.5 Test Results

Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and band edge measurement data.

Test data reference attachment.

3.9 FREQUENCY STABILITY MEASUREMENT


3.9.1 LIMIT

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

3.9.2 TEST PROCEDURES

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f)/f_c \times 10^6 \text{ ppm}$.
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature is $-20^\circ\text{C} \sim 70^\circ\text{C}$.

3.9.3 TEST SETUP LAYOUT



3.9.4 EUT OPERATION DURING TEST

The EUT was programmed to be in continuously un-modulation transmitting mode.

3.9.5 TEST RESULTS

EUT :	Professional Diagnostic Tool	Model Name. :	Diesel Handheld 2
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 3.6V
Test Mode :	TX Frequency Band I (5150-5250MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.6	5180.0097	5180	0.0097	1.8696
		V max (V)	4.14	5180.0011	5180	0.0011	0.2124
		V min (V)	3.06	5180.0052	5180	0.0052	0.9946
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.6	T (°C)	-20	5180.0011	5180	0.0011	0.2142
		T (°C)	-10	5180.0021	5180	0.0021	0.4137
		T (°C)	0	5180.0039	5180	0.0039	0.7461
		T (°C)	10	5180.0073	5180	0.0073	1.4189
		T (°C)	20	5180.0069	5180	0.0069	1.3313
		T (°C)	30	5180.0030	5180	0.0030	0.5846
		T (°C)	40	5180.0064	5180	0.0064	1.2289
		T (°C)	50	5180.0025	5180	0.0025	0.4785
		T (°C)	60	5180.0007	5180	0.0007	0.1435
		T (°C)	70	5180.0038	5180	0.0038	0.7342
Limits				Within 5150-5250MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.6	5200.0088	5200	0.0088	1.6863
		V max (V)	4.14	5200.0077	5200	0.0077	1.4848
		V min (V)	3.06	5200.0098	5200	0.0098	1.8756
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.6	T (°C)	-20	5200.0087	5200	0.0087	1.6680
		T (°C)	-10	5200.0045	5200	0.0045	0.8732
		T (°C)	0	5200.0056	5200	0.0056	1.0800
		T (°C)	10	5200.0035	5200	0.0035	0.6640
		T (°C)	20	5200.0087	5200	0.0087	1.6681
		T (°C)	30	5200.0036	5200	0.0036	0.6926
		T (°C)	40	5200.0028	5200	0.0028	0.5430
		T (°C)	50	5200.0021	5200	0.0021	0.3943
		T (°C)	60	5200.0009	5200	0.0009	0.1735
		T (°C)	70	5200.0093	5200	0.0093	1.7867
Limits				Within 5150-5250MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.6	5240.0093	5240	0.0093	1.7820
		V max (V)	4.14	5240.0088	5240	0.0088	1.6737
		V min (V)	3.06	5240.0046	5240	0.0046	0.8758
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.6	T (°C)	-20	5240.0001	5240	0.0001	0.0180
		T (°C)	-10	5240.0047	5240	0.0047	0.9028
		T (°C)	0	5240.0055	5240	0.0055	1.0558
		T (°C)	10	5240.0067	5240	0.0067	1.2813
		T (°C)	20	5240.0037	5240	0.0037	0.7058
		T (°C)	30	5240.0091	5240	0.0091	1.7286
		T (°C)	40	5240.0039	5240	0.0039	0.7512
		T (°C)	50	5240.0073	5240	0.0073	1.3915
		T (°C)	60	5240.0011	5240	0.0011	0.2164
		T (°C)	70	5240.0029	5240	0.0029	0.5556
Limits				Within 5150-5250MHz			
Result				Complies			

EUT :	Professional Diagnostic Tool	Model Name. :	Diesel Handheld 2
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 3.6V
Test Mode :	TX Frequency(5745-5825MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.6	5745.0048	5745	0.00482	0.8394
		V max (V)	4.14	5745.0059	5745	0.00589	1.0248
		V min (V)	3.06	5745.0011	5745	0.00106	0.1845
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.6	T (°C)	-20	5745.0029	5745	0.00285	0.4961
		T (°C)	-10	5745.0083	5745	0.00828	1.4411
		T (°C)	0	5745.0024	5745	0.00237	0.4123
		T (°C)	10	5745.0050	5745	0.00502	0.8746
		T (°C)	20	5745.0074	5745	0.00736	1.2818
		T (°C)	30	5745.0037	5745	0.00373	0.6498
		T (°C)	40	5745.0029	5745	0.00289	0.5027
		T (°C)	50	5745.0012	5745	0.00123	0.2137
		T (°C)	60	5745.0063	5745	0.00627	1.0917
		T (°C)	70	5745.0076	5745	0.00760	1.3228
Limits				Within 5745-5850MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.6	5785.0027	5785	0.00269	0.4651
		V max (V)	4.14	5785.0096	5785	0.00963	1.6646
		V min (V)	3.06	5785.0015	5785	0.00147	0.2534
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.6	T (°C)	-20	5785.0026	5785	0.00263	0.4555
		T (°C)	-10	5785.0049	5785	0.00487	0.8415
		T (°C)	0	5785.0094	5785	0.00938	1.6208
		T (°C)	10	5785.0065	5785	0.00652	1.1274
		T (°C)	20	5785.0087	5785	0.00874	1.5114
		T (°C)	30	5785.0004	5785	0.00045	0.0776
		T (°C)	40	5785.0002	5785	0.00015	0.0264
		T (°C)	50	5785.0011	5785	0.00107	0.1843
		T (°C)	60	5785.0040	5785	0.00401	0.6938
		T (°C)	70	5785.0063	5785	0.00628	1.0857
Limits				Within 5745-5850MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.6	5825.0010	5825	0.00103	0.1764
		V max (V)	4.14	5825.0082	5825	0.00820	1.4073
		V min (V)	3.06	5825.0081	5825	0.00811	1.3926
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.6	T (°C)	-20	5825.0066	5825	0.00659	1.1312
		T (°C)	-10	5825.0085	5825	0.00846	1.4515
		T (°C)	0	5825.0059	5825	0.00593	1.0186
		T (°C)	10	5825.0017	5825	0.00171	0.2932
		T (°C)	20	5825.0085	5825	0.00847	1.4544
		T (°C)	30	5825.0048	5825	0.00479	0.8215
		T (°C)	40	5825.0086	5825	0.00856	1.4691
		T (°C)	50	5825.0066	5825	0.00656	1.1260
		T (°C)	60	5825.0086	5825	0.00863	1.4823
		T (°C)	70	5825.0019	5825	0.00185	0.3177
Limits				Within 5745-5850MHz			
Result				Complies			

4. ANTENNA REQUIREMENT

4.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

4.2 EUT ANTENNA


The EUT antenna is permanent attached FPC antenna (4.51 dBi;). It comply with the standard requirement.



5. TEST RESULTS


5.1 5.2G WIFI


5.1.1 DUTY CYCLE

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	a	5180	Ant1	94.64	0.24	0.48
NVNT	a	5200	Ant1	95.17	0.21	0.49
NVNT	a	5240	Ant1	95.52	0.2	0.49
NVNT	n20	5180	Ant1	94.66	0.24	0.52
NVNT	n20	5200	Ant1	95.22	0.21	0.52
NVNT	n20	5240	Ant1	95.74	0.19	0.52
NVNT	n40	5190	Ant1	90.47	0.43	1.06
NVNT	n40	5230	Ant1	90.02	0.46	1.05
NVNT	ac20	5180	Ant1	94.62	0.24	0.52
NVNT	ac20	5200	Ant1	94.74	0.23	0.52
NVNT	ac20	5240	Ant1	95.15	0.22	0.52
NVNT	ac40	5190	Ant1	91.54	0.38	1.05
NVNT	ac40	5230	Ant1	90.46	0.44	1.05
NVNT	ac80	5210	Ant1	82.17	0.85	2.17









Duty Cycle NVNT ac20 5180MHz Ant1


Spectrum

Ref Level 30.00 dBm Offset 3.96 dB RBW 10 MHz

Att 40 dB SWT 100 ms VBW 10 MHz

SGL

1Pk Clrw



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1	1		1.8 ms	13.25 dBm		
M2	1		1.87 ms	10.63 dBm		
M3	1		3.8 ms	12.35 dBm		

Duty Cycle NVNT ac20 5200MHz Ant1


Spectrum

Ref Level 30.00 dBm Offset 4.02 dB RBW 10 MHz

Att 40 dB SWT 100 ms VBW 10 MHz



SGL



1Pk Clrw



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1	1		610.0 μs	13.35 dBm		
M2	1		680.0 μs	10.84 dBm		
M3	1		2.61 ms	13.65 dBm		





5.1.2 MAXIMUM CONDUCTED OUTPUT POWER

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	a	5180	Ant1	10.72	24	Pass
NVNT	a	5200	Ant1	10.71	24	Pass
NVNT	a	5240	Ant1	11.53	24	Pass
NVNT	n20	5180	Ant1	10.55	24	Pass
NVNT	n20	5200	Ant1	10.72	24	Pass
NVNT	n20	5240	Ant1	11.15	24	Pass
NVNT	n40	5190	Ant1	10.82	24	Pass
NVNT	n40	5230	Ant1	11.25	24	Pass
NVNT	ac20	5180	Ant1	10.22	24	Pass
NVNT	ac20	5200	Ant1	10.52	24	Pass
NVNT	ac20	5240	Ant1	11.47	24	Pass
NVNT	ac40	5190	Ant1	10.64	24	Pass
NVNT	ac40	5230	Ant1	11.17	24	Pass
NVNT	ac80	5210	Ant1	10.86	24	Pass

5.1.3 -26DB BANDWIDTH

Condition	Mode	Frequency (MHz)	Antenna	-26 dB Bandwidth (MHz)	Verdict
NVNT	a	5180	Ant1	20.586	Pass
NVNT	a	5200	Ant1	19.803	Pass
NVNT	a	5240	Ant1	20.808	Pass
NVNT	n20	5180	Ant1	20.157	Pass
NVNT	n20	5200	Ant1	21.519	Pass
NVNT	n20	5240	Ant1	20.886	Pass
NVNT	n40	5190	Ant1	42.24	Pass
NVNT	n40	5230	Ant1	42.462	Pass
NVNT	ac20	5180	Ant1	20.835	Pass
NVNT	ac20	5200	Ant1	20.988	Pass
NVNT	ac20	5240	Ant1	21.339	Pass
NVNT	ac40	5190	Ant1	42.552	Pass
NVNT	ac40	5230	Ant1	42.54	Pass
NVNT	ac80	5210	Ant1	80.904	Pass


Test Graphs

-26dB Bandwidth NVNT a 5180MHz Ant1

Spectrum

Ref Level 20.00 dBm Offset 3.96 dB RBW 300 kHz
Att 35 dB SWT 25.4 μ s VBW 1 MHz Mode Auto FFT
SGL Count 100/100

1Pk Max






-26dB Bandwidth NVNT a 5200MHz Ant1



Spectrum



Ref Level 20.00 dBm Offset 4.02 dB RBW 300 kHz
Att 35 dB SWT 25.4 μ s VBW 1 MHz Mode Auto FFT
SGL Count 100/100



1Pk Max












-26dB Bandwidth NVNT ac20 5240MHz Ant1

Spectrum

Ref Level 20.00 dBm Offset 4.04 dB RBW 300 kHz
Att 35 dB SWT 25.4 μ s VBW 1 MHz Mode Auto FFT
SGL Count 100/100

1Pk Max






-26dB Bandwidth NVNT ac40 5190MHz Ant1

Spectrum

Ref Level 20.00 dBm Offset 3.96 dB RBW 500 kHz
Att 35 dB SWT 10.1 ms VBW 2 MHz Mode Auto Sweep
SGL Count 100/100



1Pk Max











5.1.4 OCCUPIED CHANNEL BANDWIDTH



Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	a	5180	Ant1	16.57
NVNT	a	5200	Ant1	16.654
NVNT	a	5240	Ant1	16.567
NVNT	n20	5180	Ant1	17.581
NVNT	n20	5200	Ant1	17.632
NVNT	n20	5240	Ant1	17.629
NVNT	n40	5190	Ant1	36.182
NVNT	n40	5230	Ant1	36.23
NVNT	ac20	5180	Ant1	17.587
NVNT	ac20	5200	Ant1	17.581
NVNT	ac20	5240	Ant1	17.608
NVNT	ac40	5190	Ant1	36.188
NVNT	ac40	5230	Ant1	36.284
NVNT	ac80	5210	Ant1	75.304



















5.1.5 MAXIMUM POWER SPECTRAL DENSITY LEVEL

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm)	Duty Factor (dB)	Total PSD (dBm)	Limit (dBm)	Verdict
NVNT	a	5180	Ant1	-2.78	0.24	-2.54	11	Pass
NVNT	a	5200	Ant1	-3.11	0.21	-2.9	11	Pass
NVNT	a	5240	Ant1	-2.45	0.2	-2.25	11	Pass
NVNT	n20	5180	Ant1	-3.96	0.24	-3.72	11	Pass
NVNT	n20	5200	Ant1	-3.34	0.21	-3.13	11	Pass
NVNT	n20	5240	Ant1	-3.36	0.19	-3.17	11	Pass
NVNT	n40	5190	Ant1	-12.57	0.43	-12.14	11	Pass
NVNT	n40	5230	Ant1	-6.8	0.46	-6.34	11	Pass
NVNT	ac20	5180	Ant1	-3.82	0.24	-3.58	11	Pass
NVNT	ac20	5200	Ant1	-3.61	0.23	-3.38	11	Pass
NVNT	ac20	5240	Ant1	-3.09	0.22	-2.87	11	Pass
NVNT	ac40	5190	Ant1	-7.99	0.38	-7.61	11	Pass
NVNT	ac40	5230	Ant1	-7.89	0.44	-7.45	11	Pass
NVNT	ac80	5210	Ant1	-13.99	0.85	-13.14	11	Pass

