



**No. I21Z62312-SEM08**

**For**

**OnePlus Technology (Shenzhen) Co., Ltd.**

**Smart Phone**

**Model Name: GN2200**

**with**

**Hardware Version: 11**

**Software Version: GN2200\_11\_A.02**

**FCC ID: 2ABZ2-AA455**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

**Test Laboratory:**

CTTL, Telecommunication Technology Labs, CAICT


No. 51, Xueyuan Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: [cttl\\_terminals@caict.ac.cn](mailto:cttl_terminals@caict.ac.cn), website: [www.caict.ac.cn](http://www.caict.ac.cn)




**Picture 1: Constituents of the sample**




**Picture 2: Left Head Touch Cheek Position**



**Picture 3: Left Head Tilt 15° Position**



**Picture 4: Right Head Touch Cheek Position**



**Picture 5: Right Head Tilt 15° Position**

**Test positions for body:**

The Body SAR is tested at the following 8 test positions all with the distance =10/15/0/12/13mm between the EUT and the phantom bottom:



**Picture 6: Front 10mm**





**Picture 7: Rear 10mm**



**Picture 8: Left 10mm**




**Picture 9: Right 10mm**




**Picture 10: Top 10mm**



**Picture 11: Bottom 10mm**



**Picture 12: Front 15mm**



**Picture 13: Rear 15mm**



**Picture 14: Rear 0mm**







**Picture 15: Bottom 0mm**



**Picture 16: Top 0mm**



**Picture 17: Rear 13mm**



**Picture 17: Rear 12mm**



**Picture 18: Bottom 10mm**



**Picture 18: Top 15mm**