

# RF Exposure Evaluation

## FCC ID: 2AOSJ-SSP01

### 1. Client Information

**Applicant** : Smlpretty Technology Co., Ltd  
**Address** : Unit 4J, Block B, Central, Xixiang Town, Bao'an District, Shenzhen, China  
**Manufacturer** : Smlpretty Technology Co., Ltd  
**Address** : Unit 4J, Block B, Central, Xixiang Town, Bao'an District, Shenzhen, China

### 2. General Description of EUT

<b>EUT Name</b>	:	Smart Bluetooth Padlock	
<b>Models No.</b>	:	SSP01	
<b>Product Description</b>	:	Operation Frequency:	Bluetooth V4.2(BLE): 2402~2480 MHz
		RF Output Power:	BLE: -0.668dBm
		Antenna Gain:	4dBi PCB Antenna
<b>Power Supply</b>	:	DC Voltage supplied by USB cabel DC Voltage supplied by Li-ion battery	
<b>Power Rating</b>	:	DC 5.0V by USB cable DC 3.6V by 140mAh Li-ion battery	
<b>Connecting I/O Port(S)</b>	:	Please refer to the User's Manual	

**Note:** More test information about the EUT please refer the RF Test Report.

## SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

- (1) Clause 4.3: General SAR test reduction and exclusion guidance

- Sub clause 4.31: Standalone SAR test exclusion considerations

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance  $\leq 5$  mm are determined by:

- [(max. power of channel, including tune-up tolerance, mW)/(min. test separation, mm)] \*  $[\sqrt{f_{\text{(GHz)}}}] \leq 3.0$  for 1-g SAR

- [(max. power of channel, including tune-up tolerance, mW)/(min. test separation, mm)] \*  $[\sqrt{f_{\text{(GHz)}}}] \leq 7.5.0$  for 10-g SAR



## 2. Calculation:

Test separation: 5mm						
BLE Mode (GFSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	-0.688	$-2 \pm 1.5$	-0.5	0.891	0.276	3.0
2.442	-1.989	$-2 \pm 1.5$	-0.5	0.891	0.279	3.0
2.480	-3.111	$-2 \pm 1.5$	-0.5	0.891	0.281	3.0

So standalone SAR measurements are not required.

-----END OF REPORT-----