



**CFR 47 FCC PART 15 SUBPART C
ISED RSS-247 ISSUE 2**

CERTIFICATION TEST REPORT

For

Ms. PAC-MAN™ & GALAGA™ 40TH

MODEL NUMBER: MSP-A-10171

FCC ID: 2APXHMSPGA

IC: 24128-MSPGA

REPORT NUMBER: 4790045229.1-2

ISSUE DATE: August 11, 2021

Prepared for

**WF Tastemakers Trading Limited (FCC)
Unit 05 and unit 06, 6th Floor, Greenfield Tower Concordia Plaza, 1 Science
Museum Road, TST East, Hong Kong**

**WF TASTEMAKERS TRADING LIMITED (ISED)
980 Avenue of the Americas, 3rd Floor New York NY 10018 American Samoa**

Prepared by

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch
Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-
Tech Development Zone Dongguan, 523808, People's Republic of China**

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com



Revision History

| Rev. | Issue Date | Revisions | Revised By |
|------|------------|---------------|------------|
| V0 | 08/11/2021 | Initial Issue | |



| Summary of Test Results | | | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|-------------------------------------------------------------------------------------------------------|--------------|
| Clause | Test Items | FCC/ISED Rules | Test Results |
| 1 | 6dB Bandwidth and 99% Occupied Bandwidth | FCC Part 15.247 (a) (2) RSS-247 Clause 5.2 (a) ISED RSS-Gen Clause 6.7 | Pass |
| 2 | Conducted Output Power | FCC Part 15.247 (b) (3) RSS-247 Clause 5.4 (d) | Pass |
| 3 | Power Spectral Density | FCC Part 15.247 (e) RSS-247 Clause 5.2 (b) | Pass |
| 4 | Conducted Bandedge and Spurious Emission | FCC Part 15.247 (d) RSS-247 Clause 5.5 | Pass |
| 5 | Radiated Bandedge and Spurious Emission | FCC Part 15.247 (d) FCC Part 15.209 FCC Part 15.205 RSS-247 Clause 5.5 RSS-GEN Clause 8.9 | Pass |
| 6 | Conducted Emission Test for AC Power Port | FCC Part 15.207 RSS-GEN Clause 8.8 | Pass |
| 7 | Antenna Requirement | FCC Part 15.203 RSS-GEN Clause 6.8 | Pass |
| <p>Note:</p> <p>1. This test report is only published to and used by the applicant, and it is not for evidence purpose in China.</p> <p>2. The measurement result for the sample received is <Pass> according to < CFR 47 FCC PART 15 SUBPART C >< ISED RSS-247 > when <Accuracy Method> decision rule is applied.</p> | | | |

TABLE OF CONTENTS

| | |
|-----------------------------------------------------------|-----------|
| 1. ATTESTATION OF TEST RESULTS | 6 |
| 2. TEST METHODOLOGY | 8 |
| 3. FACILITIES AND ACCREDITATION | 8 |
| 4. CALIBRATION AND UNCERTAINTY | 9 |
| 4.1. MEASURING INSTRUMENT CALIBRATION | 9 |
| 4.2. MEASUREMENT UNCERTAINTY | 9 |
| 5. EQUIPMENT UNDER TEST | 10 |
| 5.1. DESCRIPTION OF EUT | 10 |
| 5.2. CHANNEL LIST | 10 |
| 5.3. MAXIMUM OUTPUT POWER | 10 |
| 5.4. TEST CHANNEL CONFIGURATION | 10 |
| 5.5. THE WORSE CASE POWER SETTING PARAMETER | 11 |
| 5.6. THE WORSE CASE CONFIGURATIONS | 11 |
| 5.7. DESCRIPTION OF AVAILABLE ANTENNAS | 11 |
| 5.8. DESCRIPTION OF TEST SETUP | 12 |
| 6. MEASURING INSTRUMENT AND SOFTWARE USED | 13 |
| 7. ANTENNA PORT TEST RESULTS | 15 |
| 7.1. ON TIME AND DUTY CYCLE | 15 |
| 7.2. 6 dB DTS BANDWIDTH AND 99 % OCCUPIED BANDWIDTH | 16 |
| 7.3. CONDUCTED OUTPUT POWER | 18 |
| 7.4. POWER SPECTRAL DENSITY | 19 |
| 7.5. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS | 20 |
| 8. RADIATED TEST RESULTS | 22 |
| 8.1. RESTRICTED BANDEDGE | 28 |
| 8.1.1. 802.11b MODE | 28 |
| 8.1.2. 802.11g MODE | 32 |
| 8.1.3. 802.11n HT20 MODE | 36 |
| 8.2. SPURIOUS EMISSIONS (1 GHz ~ 3 GHz) | 42 |
| 8.2.1. 802.11b MODE | 42 |
| 8.3. SPURIOUS EMISSIONS (3 GHz ~ 18 GHz) | 48 |
| 8.3.1. 802.11b MODE | 48 |
| 8.3.2. 802.11g MODE | 54 |
| 8.3.3. 802.11n HT20 MODE | 60 |
| 8.4. SPURIOUS EMISSIONS (18 GHz ~ 26 GHz) | 66 |



| | | |
|------------|----------------------------------------------------------|-----------|
| 8.4.1. | 802.11b MODE | 66 |
| 8.5. | SPURIOUS EMISSIONS (30 MHz ~ 1 GHz) | 68 |
| 8.5.1. | 802.11b MODE | 68 |
| 8.6. | SPURIOUS EMISSIONS BELOW 30 MHz | 70 |
| 8.6.1. | 802.11b MODE | 70 |
| 9. | AC POWER LINE CONDUCTED EMISSIONS | 73 |
| 9.1. | 802.11b SISO MODE | 74 |
| 10. | ANTENNA REQUIREMENTS | 76 |
| 10.1. | Appendix A: DTS Bandwidth | 77 |
| 10.1.1. | Test Result | 77 |
| 10.1.2. | Test Graphs | 78 |
| 10.2. | Appendix B: Occupied Channel Bandwidth | 81 |
| 10.2.1. | Test Result | 81 |
| 10.2.2. | Test Graphs | 82 |
| 10.3. | Appendix C: Maximum average conducted output power | 85 |
| 10.3.1. | Test Result | 85 |
| 10.4. | Appendix D: Maximum power spectral density | 86 |
| 10.4.1. | Test Result | 86 |
| 10.4.2. | Test Graphs | 87 |
| 10.5. | Appendix E: Band edge measurements | 90 |
| 10.5.1. | Test Result | 90 |
| 10.5.2. | Test Graphs | 91 |
| 10.6. | Appendix F: Conducted Spurious Emission | 93 |
| 10.6.1. | Test Result | 93 |
| 10.6.2. | Test Graphs | 94 |
| 10.7. | Appendix G: Duty Cycle | 103 |
| 10.7.1. | Test Result | 103 |
| 10.7.2. | Test Graphs | 104 |



1. ATTESTATION OF TEST RESULTS

FCC

Applicant Information

Company Name: WF Tastemakers Trading Limited
Address: Unit 05 and unit 06, 6th Floor, Greenfield Tower Concordia Plaza,
1 Science Museum Road, TST East, Hong Kong

ISED

Applicant Information

Company Name: WF Tastemakers Trading Limited
Address: 980 Avenue of the Americas, 3rd Floor New York NY 10018
American Samoa

FCC

Manufacturer Information

Company Name: WF Tastemakers Trading Limited
Address: Unit 05 and unit 06, 6th Floor, Greenfield Tower Concordia Plaza,
1 Science Museum Road, TST East, Hong Kong

ISED

Manufacturer Information

Company Name: WF Tastemakers Trading Limited
Address: 980 Avenue of the Americas, 3rd Floor New York NY 10018
American Samoa

EUT Information

EUT Name: Ms. PAC-MAN™ & GALAGA™ 40TH
Model: MSP-A-10171
Brand: ARCADE 1 UP
Sample Received Date: July 30, 2021
Sample Status: Normal
Sample ID: 4109633
Date of Tested: August 2, 2021~ August 6, 2021

| APPLICABLE STANDARDS | |
|------------------------------|--------------|
| STANDARD | TEST RESULTS |
| CFR 47 FCC PART 15 SUBPART C | PASS |
| ISED RSS-247 Issue 2 | PASS |
| ISED RSS-GEN Issue 5 | PASS |



Prepared By:

Denny Huang

Checked By:

Shawn Wen

Denny Huang
Project Engineer
Approved By:

Stephen Guo

Shawn Wen
Laboratory Leader

Stephen Guo
Laboratory Manager



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, CFR 47 FCC Part 15, ANSI C63.10-2013, ISED RSS-247 Issue 2 and ISED RSS-GEN Issue 5.

3. FACILITIES AND ACCREDITATION

| | |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Accreditation Certificate | <p>A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p>FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p>ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. Body Identifier (CABID) is CN0046.</p> <p>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B, the VCCI registration No. is C-20012 and T-20011</p> |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.



4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognize national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| Test Item | Uncertainty |
|-----------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|
| Conduction emission | 3.62 dB |
| Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz) | 2.2 dB |
| Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz) | 4.00 dB |
| Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz) | 5.78 dB (1 GHz ~ 18 GHz) |
| | 5.23 dB (18 GHz ~ 26 GHz) |
| Duty Cycle | ±0.028% |
| DTS and 99% Occupied Bandwidth | ±0.0196% |
| Maximum Conducted Output Power | ±0.686 dB |
| Maximum Power Spectral Density Level | ±0.743 dB |
| Conducted Band-edge Compliance | ±1.328 dB |
| Conducted Unwanted Emissions In Non-restricted Frequency Bands | ±0.746 dB (9 kHz ~ 1 GHz) |
| | ±1.328 dB (1 GHz ~ 26 GHz) |
| Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2. | |



5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

| | |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------|
| EUT Name | Ms. PAC-MAN™ & GALAGA™ 40 TH |
| Model Name | MSP-A-10171 |
| Radio Technology | IEEE802.11b/g/n HT20 |
| Operation frequency | IEEE 802.11b: 2412MHz ~ 2462MHz IEEE 802.11g: 2412MHz ~ 2462MHz IEEE 802.11n HT20: 2412MHz ~ 2462MHz |
| Modulation | IEEE 802.11b: DSSS (CCK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK, BPSK) |
| Rating | DC 12 V |

5.2. CHANNEL LIST

| Channel List for 802.11b/g/n (20 MHz) | | | | | | | |
|---------------------------------------|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 1 | 2412 | 4 | 2427 | 7 | 2442 | 10 | 2457 |
| 2 | 2417 | 5 | 2432 | 8 | 2447 | 11 | 2462 |
| 3 | 2422 | 6 | 2437 | 9 | 2452 | / | / |

5.3. MAXIMUM OUTPUT POWER

| IEEE Std. 802.11 | Frequency (MHz) | Channel Number | Maximum Conducted AVG Output Power (dBm) | Maximum AVG EIRP (dBm) |
|------------------|-----------------|----------------|------------------------------------------|------------------------|
| b | 2412 ~ 2462 | 1-11[11] | 16.58 | 22.58 |
| g | 2412 ~ 2462 | 1-11[11] | 10.53 | 16.53 |
| n HT20 | 2412 ~ 2462 | 1-11[11] | 10.45 | 16.45 |

5.4. TEST CHANNEL CONFIGURATION

| IEEE Std. 802.11 | Test Channel Number | Frequency |
|------------------|-----------------------------------------------------------|------------------------------|
| b | CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel) | 2412 MHz, 2437 MHz, 2462 MHz |
| g | CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel) | 2412 MHz, 2437 MHz, 2462 MHz |
| n HT20 | CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel) | 2412 MHz, 2437 MHz, 2462 MHz |

5.5. THE WORSE CASE POWER SETTING PARAMETER

| The Worse Case Power Setting Parameter under 2400 ~ 2483.5 MHz Band | | | | | | | |
|---------------------------------------------------------------------|-------------------------------|-----------------------------|---------|---------|-------------|------|------|
| Test Software | | putty | | | | | |
| IEEE Std. 802.11 | Transmit Antenna Number | Test Software Setting Value | | | | | |
| | | NCB: 20 MHz | | | NCB: 40 MHz | | |
| | | CH 1 | CH 6 | CH 11 | CH 3 | CH 6 | CH 9 |
| b | 1 | Default | Default | Default | / | | |
| g | 1 | 38 | 38 | 38 | | | |
| n HT20 | 1 | 38 | 38 | 38 | | | |

5.6. THE WORSE CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

Worst-case data rates as provided by the client were:

802.11b mode: 1 Mbps

802.11g mode: 6 Mbps

802.11n HT20 mode: MCS0

The measured additional path loss was included in any path loss calculations for all RF cable used during tested.

5.7. DESCRIPTION OF AVAILABLE ANTENNAS

| Antenna | Frequency (MHz) | Antenna Type | MAX Antenna Gain (dBi) |
|---------|-----------------|----------------|------------------------|
| 1 | 2412-2462 | Dipole Antenna | 6 |

| Test Mode | Transmit and Receive Mode | Description |
|-------------------|---------------------------|------------------------------------------------------|
| IEEE 802.11b | ☒1TX, 1RX | ANT 1 can be used as transmitting/receiving antenna. |
| IEEE 802.11g | ☒1TX, 1RX | ANT 1 can be used as transmitting/receiving antenna. |
| IEEE 802.11n HT20 | ☒1TX, 1RX | ANT 1 can be used as transmitting/receiving antenna. |

Note: The antenna gain was provided by customer.

5.8. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

| Item | Equipment | Brand Name | Model Name | Remarks |
|------|-------------|------------|------------|---------|
| 1 | Laptop | ThinkPad | X230i | / |
| 2 | USB TO UART | / | / | / |
| 3 | Earphone | / | / | / |

I/O CABLES

| Cable No | Port | Connector Type | Cable Type | Cable Length(m) | Remarks |
|----------|------|----------------|------------|-----------------|---------|
| 1 | AUX | / | Unshielded | 1 | / |


ACCESSORIES

| Item | Accessory | Brand Name | Model Name | Description |
|------|------------------------|------------|----------------|--------------------------------------------------------------|
| 1 | Switching Power Supply | Blron | BI36-120300-U2 | Input: AC 100-240 V, 50/60 Hz, 1.2 A Output: DC 12 V, 3 A |

TEST SETUP

The EUT can work in an engineer mode with software through a Laptop.

SETUP DIAGRAM FOR TESTS





6. MEASURING INSTRUMENT AND SOFTWARE USED

| Conducted Emissions | | | | | |
|---------------------------------------|--------------|-----------|--------------|---------------|---------------|
| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Due Date |
| EMI Test Receiver | R&S | ESR3 | 101961 | Nov. 12, 2020 | Nov. 11, 2021 |
| Two-Line V-Network | R&S | ENV216 | 101983 | Nov. 12, 2020 | Nov. 11, 2021 |
| Software | | | | | |
| Description | | | Manufacturer | Name | Version |
| Test Software for Conducted Emissions | | | Farad | EZ-EMC | Ver. UL-3A1 |

| Radiated Emissions | | | | | |
|--------------------------------------|---------------|-------------------------------------|---------------|----------------|----------------|
| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Due Date |
| MXE EMI Receiver | KESIGHT | N9038A | MY56400036 | Nov. 12, 2020 | Nov. 11, 2021 |
| Hybrid Log Periodic Antenna | TDK | HLP-3003C | 130960 | Aug. 11, 2018 | Aug. 10, 2021 |
| Preamplifier | HP | 8447D | 2944A09099 | Nov. 12, 2020 | Nov. 11, 2021 |
| EMI Measurement Receiver | R&S | ESR26 | 101377 | Nov. 12, 2020 | Nov. 11, 2021 |
| Horn Antenna | TDK | HRN-0118 | 130939 | Sept. 17, 2018 | Sept. 17, 2021 |
| Preamplifier | TDK | PA-02-0118 | TRS-305-00067 | Nov. 20, 2020 | Nov. 19, 2021 |
| Horn Antenna | Schwarzbeck | BBHA9170 | #691 | Aug. 11, 2018 | Aug. 11, 2021 |
| Preamplifier | TDK | PA-02-2 | TRS-307-00003 | Nov. 12, 2020 | Nov. 11, 2021 |
| Loop antenna | Schwarzbeck | 1519B | 00008 | Jan.17, 2019 | Jan.17,2022 |
| Preamplifier | Mini-Circuits | ZX60-83LN-S+ | SUP01201941 | Nov. 20, 2020 | Nov. 19, 2021 |
| High Pass Filter | Wi | WHKX10-2700-3000-18000-40SS | 23 | Nov. 12, 2020 | Nov. 11, 2021 |
| Band Reject Filter | Wainwright | WRCJV8-2350-2400-2483.5-2533.5-40SS | 4 | Nov. 12, 2020 | Nov. 11, 2021 |
| Software | | | | | |
| Description | | | Manufacturer | Name | Version |
| Test Software for Radiated Emissions | | | Farad | EZ-EMC | Ver. UL-3A1 |



| Other Instruments | | | | | |
|--------------------------|--------------|---------------------------|------------|--------------|--------------|
| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Next Cal. |
| Spectrum Analyzer | Keysight | N9030A | MY55410512 | Nov.20, 2020 | Nov.19, 2021 |
| Dual Channel Power Meter | Keysight | N1912A | MY55416024 | Nov.20, 2020 | Nov.19, 2021 |
| Power Sensor | Keysight | USB Wideband Power Sensor | MY5100022 | Nov.20, 2020 | Nov.19, 2021 |



7. ANTENNA PORT TEST RESULTS

7.1. ON TIME AND DUTY CYCLE


LIMITS

None; for reporting purposes only

PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

| | | | |
|---------------------|---------|-------------------|---------------|
| Temperature | 22.6 °C | Relative Humidity | 65 % |
| Atmosphere Pressure | 101 kPa | Test Voltage | AC120 V,60 Hz |

RESULTS

Please refer to appendix G.



7.2. 6 dB DTS BANDWIDTH AND 99 % OCCUPIED BANDWIDTH

LIMITS

| CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2 | | | |
|--------------------------------------------------------------|-------------------------|------------------------------|-----------------------|
| Section | Test Item | Limit | Frequency Range (MHz) |
| CFR 47 FCC 15.247(a)(2) ISED RSS-247 5.2 (a) | 6 dB Bandwidth | ≥ 500 kHz | 2400-2483.5 |
| ISED RSS-Gen Clause 6.7 | 99 % Occupied Bandwidth | For reporting purposes only. | 2400-2483.5 |

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.

Connect the EUT to the spectrum analyser and use the following settings:


| | |
|------------------|--------------------------------------------------------------------------------------------------|
| Center Frequency | The center frequency of the channel under test |
| Frequency Span | Between 1.5 times and 5.0 times the OBW |
| Detector | Peak |
| RBW | For 6 dB Bandwidth: 100 kHz For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth |
| VBW | For 6 dB Bandwidth: $\geq 3 \times$ RBW For 99 % Occupied Bandwidth: $\geq 3 \times$ RBW |
| Trace | Max hold |
| Sweep | Auto couple |

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



TEST SETUP



TEST ENVIRONMENT

| | | | |
|---------------------|---------|-------------------|---------------|
| Temperature | 22.6 °C | Relative Humidity | 65 % |
| Atmosphere Pressure | 101 kPa | Test Voltage | AC120 V,60 Hz |

RESULTS

Please refer to appendix A & B.



7.3. CONDUCTED OUTPUT POWER

LIMITS

| CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2 | | | |
|--------------------------------------------------------------|------------------------|------------------|-----------------------|
| Section | Test Item | Limit | Frequency Range (MHz) |
| CFR 47 FCC 15.247(b)(3) ISED RSS-247 5.4 (d) | Conducted Output Power | 1 watt or 30 dBm | 2400-2483.5 |

TEST PROCEDURE


Refer to ANSI C63.10-2013 clause 11.9.2.3.1 Method AVGPM for Maximum conducted (average) output power.

Connect the EUT to a low loss RF cable from the antenna port to the wideband RF power meter with a thermocouple detector.

The EUT is configured to transmit continuously, or to transmit with a constant duty cycle.

Measure the average output power, after any corrections for external attenuators and cables. Adjust the measurement in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle.

TEST SETUP



TEST ENVIRONMENT

| | | | |
|---------------------|---------|-------------------|---------------|
| Temperature | 22.6 °C | Relative Humidity | 65 % |
| Atmosphere Pressure | 101 kPa | Test Voltage | AC120 V,60 Hz |

RESULTS

Please refer to appendix C.



7.4. POWER SPECTRAL DENSITY

LIMITS

| CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2 | | | |
|--------------------------------------------------------------|------------------------|-------------|-----------------------|
| Section | Test Item | Limit | Frequency Range (MHz) |
| CFR 47 FCC §15.247 (e) ISED RSS-247 5.2 (b) | Power Spectral Density | 8 dBm/3 kHz | 2400-2483.5 |

TEST PROCEDURE


Connect the EUT to the spectrum analyser and use the following settings:

| | |
|------------------|------------------------------------------------------|
| Center Frequency | The center frequency of the channel under test |
| Detector | RMS |
| RBW | $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ |
| VBW | $\geq 3 \times \text{RBW}$ |
| Span | 1.5 x DTS bandwidth |
| Trace | Max hold |
| Sweep time | Auto couple |

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



TEST ENVIRONMENT

| | | | |
|---------------------|---------|-------------------|---------------|
| Temperature | 22.6 °C | Relative Humidity | 65 % |
| Atmosphere Pressure | 101 kPa | Test Voltage | AC120 V,60 Hz |

RESULTS

Please refer to appendix D.



7.5. CONDUCTED BANDEGE AND SPURIOUS EMISSIONS

LIMITS

| CFR 47 FCC Part15 (15.247) Subpart C | | |
|--------------------------------------|-------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Section | Test Item | Limit |
| CFR 47 FCC §15.247 (d) | Conducted Bandedge and Spurious Emissions | at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power |

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyser and use the following settings for reference level measurement:

| | |
|------------------|------------------------------------------------|
| Center Frequency | The center frequency of the channel under test |
| Detector | Peak |
| RBW | 100 kHz |
| VBW | $\geq 3 \times \text{RBW}$ |
| Span | 1.5 x DTS bandwidth |
| Trace | Max hold |
| Sweep time | Auto couple. |


Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

| | |
|--------------------|-------------------------------------------------------------------------------|
| Span | Set the center frequency and span to encompass frequency range to be measured |
| Detector | Peak |
| RBW | 100 kHz |
| VBW | $\geq 3 \times \text{RBW}$ |
| measurement points | $\geq \text{span}/\text{RBW}$ |
| Trace | Max hold |
| Sweep time | Auto couple. |

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

TEST SETUP



TEST ENVIRONMENT

| | | | |
|---------------------|---------|-------------------|---------------|
| Temperature | 22.6 °C | Relative Humidity | 65 % |
| Atmosphere Pressure | 101 kPa | Test Voltage | AC120 V,60 Hz |

RESULTS

Please refer to appendix E & F.



8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Please refer to ISSED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

| Emissions radiated outside of the specified frequency bands above 30 MHz | | | |
|--------------------------------------------------------------------------|---------------------------------------|-----------------------------------------|---------|
| Frequency Range (MHz) | Field Strength Limit (uV/m) at 3 m | Field Strength Limit (dBuV/m) at 3 m | |
| | | Quasi-Peak | |
| 30 - 88 | 100 | 40 | |
| 88 - 216 | 150 | 43.5 | |
| 216 - 960 | 200 | 46 | |
| Above 960 | 500 | 54 | |
| Above 1000 | 500 | Peak | Average |
| | | 74 | 54 |

| FCC Emissions radiated outside of the specified frequency bands below 30 MHz | | |
|------------------------------------------------------------------------------|-----------------------------------|-------------------------------|
| Frequency (MHz) | Field strength (microvolts/meter) | Measurement distance (meters) |
| 0.009-0.490 | 2400/F(kHz) | 300 |
| 0.490-1.705 | 24000/F(kHz) | 30 |
| 1.705-30.0 | 30 | 30 |

ISED General field strength limits at frequencies below 30 MHz

| Table 6 – General field strength limits at frequencies below 30 MHz | | |
|---------------------------------------------------------------------|------------------------------------------|--------------------------|
| Frequency | Magnetic field strength (H-Field) (μA/m) | Measurement distance (m) |
| 9 - 490 kHz ^{Note 1} | 6.37/F (F in kHz) | 300 |
| 490 - 1705 kHz | 63.7/F (F in kHz) | 30 |
| 1.705 - 30 MHz | 0.08 | 30 |

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.



ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

| MHz | MHz | GHz |
|---------------------|-----------------------|---------------|
| 0.090 - 0.110 | 149.9 - 150.05 | 9.0 - 9.2 |
| 0.495 - 0.505 | 156.52475 - 156.52525 | 9.3 - 9.5 |
| 2.1735 - 2.1905 | 156.7 - 156.9 | 10.6 - 12.7 |
| 3.020 - 3.026 | 162.0125 - 167.17 | 13.25 - 13.4 |
| 4.125 - 4.128 | 167.72 - 173.2 | 14.47 - 14.5 |
| 4.17725 - 4.17775 | 240 - 285 | 15.35 - 16.2 |
| 4.20725 - 4.20775 | 322 - 335.4 | 17.7 - 21.4 |
| 5.677 - 5.683 | 399.9 - 410 | 22.01 - 23.12 |
| 6.215 - 6.218 | 608 - 614 | 23.6 - 24.0 |
| 6.26775 - 6.26825 | 960 - 1427 | 31.2 - 31.8 |
| 6.31175 - 6.31225 | 1435 - 1626.5 | 36.43 - 36.5 |
| 8.291 - 8.294 | 1645.5 - 1646.5 | Above 38.6 |
| 8.362 - 8.366 | 1660 - 1710 | |
| 8.37625 - 8.38675 | 1718.8 - 1722.2 | |
| 8.41425 - 8.41475 | 2200 - 2300 | |
| 12.29 - 12.293 | 2310 - 2390 | |
| 12.51975 - 12.52025 | 2483.5 - 2500 | |
| 12.57675 - 12.57725 | 2655 - 2900 | |
| 13.36 - 13.41 | 3260 - 3267 | |
| 16.42 - 16.423 | 3332 - 3339 | |
| 16.69475 - 16.69525 | 3345.8 - 3358 | |
| 16.80425 - 16.80475 | 3500 - 4400 | |
| 25.5 - 25.67 | 4500 - 5150 | |
| 37.5 - 38.25 | 5350 - 5460 | |
| 73 - 74.6 | 7250 - 7750 | |
| 74.8 - 75.2 | 8025 - 8500 | |
| 108 - 138 | | |

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):


| MHz | MHz | MHz | GHz |
|--------------------------|---------------------|---------------|------------------|
| 0.090-0.110 | 16.42-16.423 | 399.9-410 | 4.5-5.15 |
| ¹ 0.495-0.505 | 16.69475-16.69525 | 608-614 | 5.35-5.46 |
| 2.1735-2.1905 | 16.80425-16.80475 | 960-1240 | 7.25-7.75 |
| 4.125-4.128 | 25.5-25.67 | 1300-1427 | 8.025-8.5 |
| 4.17725-4.17775 | 37.5-38.25 | 1435-1626.5 | 9.0-9.2 |
| 4.20725-4.20775 | 73-74.6 | 1645.5-1646.5 | 9.3-9.5 |
| 6.215-6.218 | 74.8-75.2 | 1660-1710 | 10.6-12.7 |
| 6.26775-6.26825 | 108-121.94 | 1718.8-1722.2 | 13.25-13.4 |
| 6.31175-6.31225 | 123-138 | 2200-2300 | 14.47-14.5 |
| 8.291-8.294 | 149.9-150.05 | 2310-2390 | 15.35-16.2 |
| 8.362-8.366 | 156.52475-156.52525 | 2483.5-2500 | 17.7-21.4 |
| 8.37625-8.38675 | 156.7-156.9 | 2690-2900 | 22.01-23.12 |
| 8.41425-8.41475 | 162.0125-167.17 | 3260-3267 | 23.6-24.0 |
| 12.29-12.293 | 167.72-173.2 | 3332-3339 | 31.2-31.8 |
| 12.51975-12.52025 | 240-285 | 3345.8-3358 | 36.43-36.5 |
| 12.57675-12.57725 | 322-335.4 | 3600-4400 | (²) |
| 13.36-13.41 | | | |

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST SETUP AND PROCEDURE

Below 30 MHz




The setting of the spectrum analyser

| | |
|-------|------------------------------------------------------------------|
| RBW | 200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz) |
| VBW | 200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz) |
| Sweep | Auto |
| Trace | Max hold |

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 12 mm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377 Ω . For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit

Below 1 GHz and above 30 MHz




The setting of the spectrum analyser

| | |
|----------|----------|
| RBW | 120 kHz |
| VBW | 300 kHz |
| Sweep | Auto |
| Detector | Peak/QP |
| Trace | Max hold |

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 12 mm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1 GHz



The setting of the spectrum analyser

| | |
|----------|--------------------------------|
| RBW | 1 MHz |
| VBW | PEAK: 3 MHz AVG: see note 6 |
| Sweep | Auto |
| Detector | Peak |
| Trace | Max hold |

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1.ON TIME AND DUTY CYCLE.

Note: The manufacturer has recommended that the EUT only be used in the Floor-standing orientation; therefore, all radiated testing was performed in the orientation. The EUT was placed on normal orientation and all radiated emissions were performed with the EUT shown on the setup photo.

**TEST ENVIRONMENT**

| | | | |
|---------------------|---------|-------------------|---------------|
| Temperature | 23.5 °C | Relative Humidity | 62 % |
| Atmosphere Pressure | 101 kPa | Test Voltage | AC120 V,60 Hz |


RESULTS

8.1. RESTRICTED BANDEDGE

8.1.1. 802.11b MODE

RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)


PEAK



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1 | 2384.175 | 27.11 | 33.31 | 60.42 | 74.00 | -13.58 | peak |
| 2 | 2390.000 | 25.81 | 33.35 | 59.16 | 74.00 | -14.84 | peak |


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1 | 2384.175 | 13.33 | 33.31 | 46.64 | 54.00 | -7.36 | AVG |
| 2 | 2390.000 | 12.95 | 33.35 | 46.30 | 54.00 | -7.70 | AVG |


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
4. For the transmitting duration, please refer to clause 7.1.
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)****PEAK**

| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1 | 2483.500 | 25.61 | 33.71 | 59.32 | 74.00 | -14.68 | peak |

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1 | 2483.500 | 13.85 | 33.71 | 47.56 | 54.00 | -6.44 | AVG |


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW = 1/Ton$, where: Ton is the transmitting duration.
4. For the transmitting duration, please refer to clause 7.1.
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: Both horizontal and vertical had been tested, only the worst data was recorded in the report.

8.1.2. 802.11g MODE

RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)


PEAK



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1 | 2390.000 | 29.07 | 33.35 | 62.42 | 74.00 | -11.58 | peak |

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1 | 2390.000 | 14.08 | 33.35 | 47.43 | 54.00 | -6.57 | AVG |

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
4. For the transmitting duration, please refer to clause 7.1.
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)
PEAK



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1 | 2483.500 | 33.50 | 33.71 | 67.21 | 74.00 | -6.79 | peak |
| 2 | 2484.200 | 35.06 | 33.71 | 68.77 | 74.00 | -5.23 | peak |

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1 | 2483.500 | 16.49 | 33.71 | 50.20 | 54.00 | -3.80 | AVG |
| 2 | 2484.200 | 15.92 | 33.71 | 49.63 | 54.00 | -4.37 | AVG |


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
4. For the transmitting duration, please refer to clause 7.1.
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: Both horizontal and vertical had been tested, only the worst data was recorded in the report.

8.1.3. 802.11n HT20 MODE

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)


PEAK



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1 | 2388.775 | 38.86 | 33.34 | 72.20 | 74.00 | -1.80 | peak |
| 2 | 2390.000 | 37.54 | 33.35 | 70.89 | 74.00 | -3.11 | peak |


Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1 | 2388.175 | 12.71 | 33.34 | 46.05 | 74.00 | -27.95 | peak |
| 2 | 2390.000 | 16.57 | 33.35 | 49.92 | 54.00 | -4.08 | AVG |

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
4. For the transmitting duration, please refer to clause 7.1.
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)****PEAK**


| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1 | 2390.000 | 39.48 | 33.35 | 72.83 | 74.00 | -1.17 | peak |

- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**

| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1 | 2390.000 | 19.13 | 33.35 | 52.48 | 54.00 | -1.52 | AVG |


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
4. For the transmitting duration, please refer to clause 7.1.
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)****PEAK**

| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1 | 2390.000 | 33.67 | 33.35 | 67.02 | 74.00 | -6.98 | peak |

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1 | 2390.000 | 15.29 | 33.35 | 48.64 | 54.00 | -5.36 | AVG |


Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
 4. For the transmitting duration, please refer to clause 7.1.
 5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: Both horizontal and vertical had been tested, only the worst data was recorded in the report.

8.2. SPURIOUS EMISSIONS (1 GHz ~ 3 GHz)

8.2.1. 802.11b MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|-------------|
| 1 | 1184.000 | 53.08 | -13.07 | 40.01 | 74.00 | -33.99 | peak |
| 2 | 1298.000 | 51.58 | -12.84 | 38.74 | 74.00 | -35.26 | peak |
| 3 | 1732.000 | 49.93 | -10.56 | 39.37 | 74.00 | -34.63 | peak |
| 4 | 2302.000 | 49.33 | -8.72 | 40.61 | 74.00 | -33.39 | peak |
| 5 | 2412.000 | 53.73 | -8.37 | 45.36 | / | / | Fundamental |
| 6 | 2746.000 | 48.04 | -6.90 | 41.14 | 74.00 | -32.86 | peak |

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|-------------|
| 1 | 1212.000 | 50.10 | -12.97 | 37.13 | 74.00 | -36.87 | peak |
| 2 | 1298.000 | 51.10 | -12.84 | 38.26 | 74.00 | -35.74 | peak |
| 3 | 1920.000 | 50.28 | -10.13 | 40.15 | 74.00 | -33.85 | peak |
| 4 | 2334.000 | 50.70 | -8.61 | 42.09 | 74.00 | -31.91 | peak |
| 5 | 2412.000 | 60.77 | -8.36 | 52.41 | / | / | Fundamental |
| 6 | 2782.000 | 49.19 | -6.67 | 42.52 | 74.00 | -31.48 | peak |

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|-------------|
| 1 | 1028.000 | 51.11 | -13.85 | 37.26 | 74.00 | -36.74 | peak |
| 2 | 1184.000 | 51.94 | -13.07 | 38.87 | 74.00 | -35.13 | peak |
| 3 | 1298.000 | 51.65 | -12.84 | 38.81 | 74.00 | -35.19 | peak |
| 4 | 1732.000 | 49.84 | -10.56 | 39.28 | 74.00 | -34.72 | peak |
| 5 | 2437.000 | 51.41 | -8.33 | 43.08 | / | / | Fundamental |
| 6 | 2756.000 | 50.08 | -6.84 | 43.24 | 74.00 | -30.76 | peak |

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|-------------|
| 1 | 1292.000 | 52.06 | -12.85 | 39.21 | 74.00 | -34.79 | peak |
| 2 | 1920.000 | 50.01 | -10.13 | 39.88 | 74.00 | -34.12 | peak |
| 3 | 2094.000 | 48.13 | -9.65 | 38.48 | 74.00 | -35.52 | peak |
| 4 | 2356.000 | 49.17 | -8.54 | 40.63 | 74.00 | -33.37 | peak |
| 5 | 2437.000 | 55.26 | -8.32 | 46.94 | / | / | Fundamental |
| 6 | 2762.000 | 48.08 | -6.81 | 41.27 | 74.00 | -32.73 | peak |

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|-------------|
| 1 | 1028.000 | 51.23 | -13.85 | 37.38 | 74.00 | -36.62 | peak |
| 2 | 1184.000 | 52.81 | -13.07 | 39.74 | 74.00 | -34.26 | peak |
| 3 | 1292.000 | 50.54 | -12.85 | 37.69 | 74.00 | -36.31 | peak |
| 4 | 1732.000 | 50.17 | -10.56 | 39.61 | 74.00 | -34.39 | peak |
| 5 | 2462.000 | 52.69 | -8.27 | 44.42 | / | / | Fundamental |
| 6 | 2762.000 | 49.53 | -6.81 | 42.72 | 74.00 | -31.28 | peak |

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|-------------|
| 1 | 1292.000 | 51.59 | -12.85 | 38.74 | 74.00 | -35.26 | peak |
| 2 | 1920.000 | 49.26 | -10.13 | 39.13 | 74.00 | -34.87 | peak |
| 3 | 2302.000 | 48.07 | -8.72 | 39.35 | 74.00 | -34.65 | peak |
| 4 | 2462.000 | 55.74 | -8.29 | 47.45 | / | / | Fundamental |
| 5 | 2576.000 | 48.15 | -7.96 | 40.19 | 74.00 | -33.81 | peak |
| 6 | 2778.000 | 48.33 | -6.69 | 41.64 | 74.00 | -32.36 | peak |

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.


5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

Note: All the modes and channels had been tested, but only the worst data was recorded in the report.

8.3. SPURIOUS EMISSIONS (3 GHz ~ 18 GHz)

8.3.1. 802.11b MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 4815.000 | 51.69 | 1.38 | 53.07 | 74.00 | -20.93 | peak |
| 2 | 4815.000 | 41.50 | 1.38 | 42.88 | 54.00 | -11.12 | AVG |
| 3 | 9645.000 | 44.66 | 10.81 | 55.47 | 74.00 | -18.53 | peak |
| 4 | 9645.000 | 36.83 | 10.81 | 47.64 | 54.00 | -6.36 | AVG |
| 5 | 11685.000 | 36.11 | 15.26 | 51.37 | 74.00 | -22.63 | peak |
| 6 | 14760.000 | 33.70 | 17.90 | 51.60 | 74.00 | -22.40 | peak |
| 7 | 16440.000 | 31.67 | 19.68 | 51.35 | 74.00 | -22.65 | peak |
| 8 | 17985.000 | 28.06 | 24.21 | 52.27 | 74.00 | -21.73 | peak |


Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**

| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1 | 4815.000 | 51.47 | 1.38 | 52.85 | 74.00 | -21.15 | peak |
| 2 | 9645.000 | 41.35 | 10.81 | 52.16 | 74.00 | -21.84 | peak |
| 3 | 11700.000 | 35.89 | 15.35 | 51.24 | 74.00 | -22.76 | peak |
| 4 | 13545.000 | 34.67 | 17.16 | 51.83 | 74.00 | -22.17 | peak |
| 5 | 16410.000 | 32.59 | 19.69 | 52.28 | 74.00 | -21.72 | peak |
| 6 | 17985.000 | 28.26 | 24.21 | 52.47 | 74.00 | -21.53 | peak |

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 4875.000 | 44.46 | 1.32 | 45.78 | 74.00 | -28.22 | peak |
| 2 | 9360.000 | 37.16 | 10.75 | 47.91 | 74.00 | -26.09 | peak |
| 3 | 11700.000 | 35.63 | 15.35 | 50.98 | 74.00 | -23.02 | peak |
| 4 | 12615.000 | 35.34 | 15.75 | 51.09 | 74.00 | -22.91 | peak |
| 5 | 13800.000 | 33.76 | 17.61 | 51.37 | 74.00 | -22.63 | peak |
| 6 | 14745.000 | 34.33 | 17.84 | 52.17 | 74.00 | -21.83 | peak |

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 4875.000 | 45.51 | 1.32 | 46.83 | 74.00 | -27.17 | peak |
| 2 | 12615.000 | 35.23 | 15.75 | 50.98 | 74.00 | -23.02 | peak |
| 3 | 13620.000 | 34.11 | 17.19 | 51.30 | 74.00 | -22.70 | peak |
| 4 | 14820.000 | 33.64 | 17.91 | 51.55 | 74.00 | -22.45 | peak |
| 5 | 16860.000 | 30.63 | 21.22 | 51.85 | 74.00 | -22.15 | peak |
| 6 | 17955.000 | 28.21 | 24.10 | 52.31 | 74.00 | -21.69 | peak |

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1 | 4920.000 | 45.41 | 1.45 | 46.86 | 74.00 | -27.14 | peak |
| 2 | 7740.000 | 38.38 | 8.81 | 47.19 | 74.00 | -26.81 | peak |
| 3 | 11820.000 | 35.51 | 15.29 | 50.80 | 74.00 | -23.20 | peak |
| 4 | 13830.000 | 33.91 | 17.59 | 51.50 | 74.00 | -22.50 | peak |
| 5 | 14820.000 | 33.50 | 17.91 | 51.41 | 74.00 | -22.59 | peak |
| 6 | 17205.000 | 29.84 | 22.02 | 51.86 | 74.00 | -22.14 | peak |

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 4920.000 | 44.86 | 1.45 | 46.31 | 74.00 | -27.69 | peak |
| 2 | 8970.000 | 37.03 | 10.70 | 47.73 | 74.00 | -26.27 | peak |
| 3 | 11730.000 | 35.53 | 15.32 | 50.85 | 74.00 | -23.15 | peak |
| 4 | 13965.000 | 33.96 | 17.62 | 51.58 | 74.00 | -22.42 | peak |
| 5 | 14820.000 | 33.82 | 17.91 | 51.73 | 74.00 | -22.27 | peak |
| 6 | 16455.000 | 32.42 | 19.68 | 52.10 | 74.00 | -21.90 | peak |

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



8.3.2. 802.11g MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1 | 4815.000 | 46.54 | 1.38 | 47.92 | 74.00 | -26.08 | peak |
| 2 | 7245.000 | 40.19 | 7.25 | 47.44 | 74.00 | -26.56 | peak |
| 3 | 9645.000 | 41.14 | 10.81 | 51.95 | 74.00 | -22.05 | peak |
| 4 | 12300.000 | 34.88 | 16.09 | 50.97 | 74.00 | -23.03 | peak |
| 5 | 14685.000 | 33.61 | 17.64 | 51.25 | 74.00 | -22.75 | peak |
| 6 | 16920.000 | 30.49 | 21.51 | 52.00 | 74.00 | -22.00 | peak |

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 4815.000 | 42.33 | 0.61 | 42.94 | 74.00 | -31.06 | peak |
| 2 | 8940.000 | 37.68 | 9.99 | 47.67 | 74.00 | -26.33 | peak |
| 3 | 11745.000 | 35.64 | 15.31 | 50.95 | 74.00 | -23.05 | peak |
| 4 | 13920.000 | 33.57 | 16.89 | 50.46 | 74.00 | -23.54 | peak |
| 5 | 16755.000 | 30.83 | 19.69 | 50.52 | 74.00 | -23.48 | peak |
| 6 | 18000.000 | 29.59 | 22.67 | 52.26 | 74.00 | -21.74 | peak |

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 4875.000 | 41.92 | 1.32 | 43.24 | 74.00 | -30.76 | peak |
| 2 | 8115.000 | 37.17 | 10.13 | 47.30 | 74.00 | -26.70 | peak |
| 3 | 9570.000 | 36.62 | 10.88 | 47.50 | 74.00 | -26.50 | peak |
| 4 | 11805.000 | 35.19 | 15.26 | 50.45 | 74.00 | -23.55 | peak |
| 5 | 13920.000 | 33.55 | 17.55 | 51.10 | 74.00 | -22.90 | peak |
| 6 | 16890.000 | 31.03 | 21.49 | 52.52 | 74.00 | -21.48 | peak |

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 5880.000 | 39.78 | 4.31 | 44.09 | 74.00 | -29.91 | peak |
| 2 | 8115.000 | 37.12 | 10.13 | 47.25 | 74.00 | -26.75 | peak |
| 3 | 9345.000 | 37.19 | 10.66 | 47.85 | 74.00 | -26.15 | peak |
| 4 | 12165.000 | 35.24 | 15.74 | 50.98 | 74.00 | -23.02 | peak |
| 5 | 14805.000 | 33.19 | 18.00 | 51.19 | 74.00 | -22.81 | peak |
| 6 | 16935.000 | 31.02 | 21.45 | 52.47 | 74.00 | -21.53 | peak |

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1 | 4920.000 | 42.29 | 1.45 | 43.74 | 74.00 | -30.26 | peak |
| 2 | 8145.000 | 37.50 | 10.01 | 47.51 | 74.00 | -26.49 | peak |
| 3 | 11340.000 | 35.81 | 14.21 | 50.02 | 74.00 | -23.98 | peak |
| 4 | 12165.000 | 34.98 | 15.74 | 50.72 | 74.00 | -23.28 | peak |
| 5 | 14835.000 | 33.38 | 17.80 | 51.18 | 74.00 | -22.82 | peak |
| 6 | 16860.000 | 30.86 | 21.22 | 52.08 | 74.00 | -21.92 | peak |

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 4905.000 | 42.34 | 1.33 | 43.67 | 74.00 | -30.33 | peak |
| 2 | 8985.000 | 37.01 | 10.99 | 48.00 | 74.00 | -26.00 | peak |
| 3 | 11730.000 | 35.16 | 15.32 | 50.48 | 74.00 | -23.52 | peak |
| 4 | 12600.000 | 35.00 | 15.78 | 50.78 | 74.00 | -23.22 | peak |
| 5 | 14865.000 | 33.73 | 17.61 | 51.34 | 74.00 | -22.66 | peak |
| 6 | 16845.000 | 30.70 | 21.10 | 51.80 | 74.00 | -22.20 | peak |

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

8.3.3. 802.11n HT20 MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1 | 4815.000 | 43.55 | 0.61 | 44.16 | 74.00 | -29.84 | peak |
| 2 | 7815.000 | 38.19 | 8.21 | 46.40 | 74.00 | -27.60 | peak |
| 3 | 8940.000 | 37.46 | 9.99 | 47.45 | 74.00 | -26.55 | peak |
| 4 | 11835.000 | 35.10 | 15.56 | 50.66 | 74.00 | -23.34 | peak |
| 5 | 16845.000 | 30.17 | 19.85 | 50.02 | 74.00 | -23.98 | peak |
| 6 | 17085.000 | 30.53 | 20.58 | 51.11 | 74.00 | -22.89 | peak |

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 4815.000 | 41.11 | 0.61 | 41.72 | 74.00 | -32.28 | peak |
| 2 | 6765.000 | 36.74 | 5.56 | 42.30 | 74.00 | -31.70 | peak |
| 3 | 7710.000 | 38.85 | 7.90 | 46.75 | 74.00 | -27.25 | peak |
| 4 | 8940.000 | 37.20 | 9.99 | 47.19 | 74.00 | -26.81 | peak |
| 5 | 12600.000 | 36.05 | 15.29 | 51.34 | 74.00 | -22.66 | peak |
| 6 | 17685.000 | 28.88 | 21.82 | 50.70 | 74.00 | -23.30 | peak |

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 4860.000 | 44.98 | 0.68 | 45.66 | 74.00 | -28.34 | peak |
| 2 | 8340.000 | 37.29 | 8.82 | 46.11 | 74.00 | -27.89 | peak |
| 3 | 8940.000 | 38.00 | 9.99 | 47.99 | 74.00 | -26.01 | peak |
| 4 | 11865.000 | 35.08 | 15.52 | 50.60 | 74.00 | -23.40 | peak |
| 5 | 13890.000 | 34.20 | 16.91 | 51.11 | 74.00 | -22.89 | peak |
| 6 | 17235.000 | 29.24 | 20.99 | 50.23 | 74.00 | -23.77 | peak |

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1 | 4875.000 | 42.10 | 0.71 | 42.81 | 74.00 | -31.19 | peak |
| 2 | 8235.000 | 36.92 | 9.22 | 46.14 | 74.00 | -27.86 | peak |
| 3 | 8940.000 | 37.06 | 9.99 | 47.05 | 74.00 | -26.95 | peak |
| 4 | 11760.000 | 35.07 | 15.40 | 50.47 | 74.00 | -23.53 | peak |
| 5 | 14010.000 | 34.32 | 16.84 | 51.16 | 74.00 | -22.84 | peak |
| 6 | 17205.000 | 30.46 | 21.03 | 51.49 | 74.00 | -22.51 | peak |

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 4905.000 | 44.22 | 0.75 | 44.97 | 74.00 | -29.03 | peak |
| 2 | 8940.000 | 36.85 | 9.99 | 46.84 | 74.00 | -27.16 | peak |
| 3 | 11790.000 | 36.57 | 15.56 | 52.13 | 74.00 | -21.87 | peak |
| 4 | 12690.000 | 35.73 | 15.45 | 51.18 | 74.00 | -22.82 | peak |
| 5 | 16980.000 | 30.39 | 20.18 | 50.57 | 74.00 | -23.43 | peak |
| 6 | 17700.000 | 28.80 | 21.94 | 50.74 | 74.00 | -23.26 | peak |

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1 | 4905.000 | 41.02 | 0.75 | 41.77 | 74.00 | -32.23 | peak |
| 2 | 5655.000 | 39.51 | 2.47 | 41.98 | 74.00 | -32.02 | peak |
| 3 | 8250.000 | 37.35 | 9.17 | 46.52 | 74.00 | -27.48 | peak |
| 4 | 8940.000 | 37.32 | 9.99 | 47.31 | 74.00 | -26.69 | peak |
| 5 | 11835.000 | 34.95 | 15.56 | 50.51 | 74.00 | -23.49 | peak |
| 6 | 17400.000 | 30.78 | 20.73 | 51.51 | 74.00 | -22.49 | peak |

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

8.4. SPURIOUS EMISSIONS (18 GHz ~ 26 GHz)

8.4.1. 802.11b MODE

SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 18144.000 | 50.27 | -5.48 | 44.79 | 74.00 | -29.21 | peak |
| 2 | 20000.000 | 50.81 | -5.45 | 45.36 | 74.00 | -28.64 | peak |
| 3 | 21600.000 | 50.02 | -4.54 | 45.48 | 74.00 | -28.52 | peak |
| 4 | 23064.000 | 48.99 | -3.42 | 45.57 | 74.00 | -28.43 | peak |
| 5 | 24248.000 | 48.32 | -2.83 | 45.49 | 74.00 | -28.51 | peak |
| 6 | 25616.000 | 46.68 | -1.24 | 45.44 | 74.00 | -28.56 | peak |


Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. The preamplifier only effect to the above 18GHz signal and no filter added to the measurement chain.

SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 18528.000 | 50.11 | -5.26 | 44.85 | 74.00 | -29.15 | peak |
| 2 | 19984.000 | 51.21 | -5.44 | 45.77 | 74.00 | -28.23 | peak |
| 3 | 21544.000 | 49.76 | -4.63 | 45.13 | 74.00 | -28.87 | peak |
| 4 | 22976.000 | 48.26 | -3.46 | 44.80 | 74.00 | -29.20 | peak |
| 5 | 24864.000 | 47.53 | -2.23 | 45.30 | 74.00 | -28.70 | peak |
| 6 | 25304.000 | 47.08 | -1.70 | 45.38 | 74.00 | -28.62 | peak |


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The preamplifier only effect to the above 18GHz signal and no filter added to the measurement chain.

Note: All the modes and channels have been tested, but only the worst data was recorded in the report.

8.5. SPURIOUS EMISSIONS (30 MHz ~ 1 GHz)

8.5.1. 802.11b MODE


SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 107.6000 | 56.52 | -20.58 | 35.94 | 43.50 | -7.56 | QP |
| 2 | 216.2400 | 56.29 | -17.84 | 38.45 | 46.00 | -7.55 | QP |
| 3 | 322.9400 | 50.85 | -14.75 | 36.10 | 46.00 | -9.90 | QP |
| 4 | 433.5200 | 51.85 | -12.67 | 39.18 | 46.00 | -6.82 | QP |
| 5 | 649.8300 | 44.91 | -9.06 | 35.85 | 46.00 | -10.15 | QP |
| 6 | 704.1500 | 44.75 | -8.29 | 36.46 | 46.00 | -9.54 | QP |

Note: 1. Result Level = Read Level + Correct Factor.
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1 | 49.4000 | 53.15 | -20.72 | 32.43 | 40.00 | -7.57 | QP |
| 2 | 108.5700 | 53.20 | -20.53 | 32.67 | 43.50 | -10.83 | QP |
| 3 | 215.2700 | 54.91 | -17.76 | 37.15 | 43.50 | -6.35 | QP |
| 4 | 433.5200 | 52.96 | -12.67 | 40.29 | 46.00 | -5.71 | QP |
| 5 | 541.1900 | 48.66 | -10.49 | 38.17 | 46.00 | -7.83 | QP |
| 6 | 649.8300 | 42.89 | -9.06 | 33.83 | 46.00 | -12.17 | QP |

Note: 1. Result Level = Read Level + Correct Factor.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto


Note: All the modes and channels have been tested, but only the worst data was recorded in the report.

8.6. SPURIOUS EMISSIONS BELOW 30 MHz

8.6.1. 802.11b MODE

SPURIOUS EMISSIONS (LOW CHANNEL, LOOP ANTENNA FACE ON TO THE EUT, WORST-CASE CONFIGURATION)

9 kHz~ 150 kHz




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | FCC Result (dBuV/m) | FCC Limit (dBuV/m) | ISED Result (dBuA/m) | ISED Limit (dBuA/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|---------------------------|--------------------------|----------------------------|---------------------------|----------------|--------|
| 1 | 0.0100 | 75.22 | -101.40 | -26.18 | 47.6 | -77.68 | -3.90 | -73.78 | peak |
| 2 | 0.0181 | 68.85 | -101.36 | -32.51 | 42.45 | -84.01 | -9.05 | -74.96 | peak |
| 3 | 0.0279 | 66.17 | -101.38 | -35.21 | 38.69 | -86.71 | -12.81 | -73.90 | peak |
| 4 | 0.0349 | 63.53 | -101.41 | -37.88 | 36.75 | -89.38 | -14.75 | -74.63 | peak |
| 5 | 0.0551 | 60.95 | -101.50 | -40.55 | 32.78 | -92.05 | -18.72 | -73.33 | peak |
| 6 | 0.0981 | 57.77 | -101.78 | -44.01 | 27.77 | -95.51 | -23.73 | -71.78 | peak |

Note: 1. Measurement = Reading Level + Correct Factor

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

4. $\text{dBuA/m} = \text{dBuV/m} - 20\log_{10}(120\pi) = \text{dBuV/m} - 51.5$.

150 kHz ~ 490 kHz

| No. | Frequency | Reading | Correct | FCC Result | FCC Limit | ISED Result | ISED Limit | Margin | Remark |
|-----|-----------|---------|---------|------------|-----------|-------------|------------|--------|--------|
| | (MHz) | (dBuV) | (dB/m) | (dBuV/m) | (dBuV/m) | (dBuA/m) | (dBuA/m) | (dB) | |
| 1 | 0.1554 | 75.27 | -101.65 | -26.38 | 23.77 | -77.88 | -27.73 | -50.15 | peak |
| 2 | 0.1595 | 74.36 | -101.65 | -27.29 | 23.55 | -78.79 | -27.95 | -50.84 | peak |
| 3 | 0.2190 | 66.77 | -101.75 | -34.98 | 20.79 | -86.48 | -30.71 | -55.77 | peak |
| 4 | 0.2442 | 64.53 | -101.79 | -37.26 | 19.85 | -88.76 | -31.65 | -57.11 | peak |
| 5 | 0.3382 | 60.73 | -101.90 | -41.17 | 17.02 | -92.67 | -34.48 | -58.19 | peak |
| 6 | 0.3800 | 59.52 | -101.94 | -42.42 | 16.01 | -93.92 | -35.49 | -58.43 | peak |


Note: 1. Measurement = Reading Level + Correct Factor

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

4. $\text{dBuA/m} = \text{dBuV/m} - 20\log_{10}(120\pi) = \text{dBuV/m} - 51.5$.

490 kHz ~ 30 MHz



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | FCC Result (dBuV/m) | FCC Limit (dBuV/m) | ISED Result (dBuA/m) | ISED Limit (dBuA/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|---------------------------|--------------------------|----------------------------|---------------------------|----------------|--------|
| 1 | 0.5039 | 64.44 | -62.07 | 2.37 | 33.56 | -49.13 | -17.94 | -31.19 | peak |
| 2 | 0.6671 | 63.75 | -62.10 | 1.65 | 31.12 | -49.85 | -20.38 | -29.47 | peak |
| 3 | 1.5564 | 57.18 | -62.02 | -4.84 | 23.76 | -56.34 | -27.74 | -28.60 | peak |
| 4 | 3.7100 | 54.20 | -61.41 | -7.21 | 29.54 | -58.71 | -21.96 | -36.75 | peak |
| 5 | 6.8936 | 54.09 | -61.22 | -7.13 | 29.54 | -58.63 | -21.96 | -36.67 | peak |
| 6 | 16.3959 | 54.17 | -60.96 | -6.79 | 29.54 | -58.29 | -21.96 | -36.33 | peak |

Note: 1. Measurement = Reading Level + Correct Factor

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

4. $\text{dBuA/m} = \text{dBuV/m} - 20\log_{10}(120\pi) = \text{dBuV/m} - 51.5$.

Note: All the modes had been tested, but only the worst data was recorded in the report.

9. AC POWER LINE CONDUCTED EMISSIONS


LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8

| FREQUENCY (MHz) | Quasi-peak | Average |
|-----------------|------------|-----------|
| 0.15 -0.5 | 66 - 56 * | 56 - 46 * |
| 0.50 -5.0 | 56.00 | 46.00 |
| 5.0 -30.0 | 60.00 | 50.00 |

TEST SETUP AND PROCEDURE

Refer to ANSI C63.10-2013 clause 6.2.



The EUT is put on a table of non-conducting material that is 12 mm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.


TEST ENVIRONMENT

| | | | |
|---------------------|---------|-------------------|---------------|
| Temperature | 25.2 °C | Relative Humidity | 63.1 % |
| Atmosphere Pressure | 101 kPa | Test Voltage | AC120 V,60 Hz |

RESULTS

9.1. 802.11b SISO MODE

LINE N RESULTS (LOW CHANNEL, WORST-CASE CONFIGURATION)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB) | Result (dBuV) | Limit (dBuV) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-----------------|------------------|-----------------|----------------|--------|
| 1 | 0.2877 | 40.82 | 9.59 | 50.41 | 60.59 | -10.18 | QP |
| 2 | 0.2877 | 27.36 | 9.59 | 36.95 | 50.59 | -13.64 | AVG |
| 3 | 0.3264 | 39.38 | 9.59 | 48.97 | 59.54 | -10.57 | QP |
| 4 | 0.3264 | 29.40 | 9.59 | 38.99 | 49.54 | -10.55 | AVG |
| 5 | 0.3858 | 42.01 | 9.59 | 51.60 | 58.15 | -6.55 | QP |
| 6 | 0.3858 | 28.54 | 9.59 | 38.13 | 48.15 | -10.02 | AVG |
| 7 | 1.6747 | 35.94 | 9.62 | 45.56 | 56.00 | -10.44 | QP |
| 8 | 1.6747 | 26.04 | 9.62 | 35.66 | 46.00 | -10.34 | AVG |
| 9 | 2.1451 | 33.32 | 9.63 | 42.95 | 56.00 | -13.05 | QP |
| 10 | 2.1451 | 23.39 | 9.63 | 33.02 | 46.00 | -12.98 | AVG |
| 11 | 3.6696 | 29.52 | 9.61 | 39.13 | 56.00 | -16.87 | QP |
| 12 | 3.6696 | 21.47 | 9.61 | 31.08 | 46.00 | -14.92 | AVG |


Note: 1. Result = Reading +Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).

4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

LINE L RESULTS (LOW CHANNEL, WORST-CASE CONFIGURATION)



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB) | Result (dBuV) | Limit (dBuV) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-----------------|------------------|-----------------|----------------|--------|
| 1 | 0.2876 | 40.43 | 9.59 | 50.02 | 60.59 | -10.57 | QP |
| 2 | 0.2876 | 27.55 | 9.59 | 37.14 | 50.59 | -13.45 | AVG |
| 3 | 0.3858 | 42.34 | 9.59 | 51.93 | 58.15 | -6.22 | QP |
| 4 | 0.3858 | 29.32 | 9.59 | 38.91 | 48.15 | -9.24 | AVG |
| 5 | 0.4797 | 37.09 | 9.60 | 46.69 | 56.34 | -9.65 | QP |
| 6 | 0.4797 | 24.96 | 9.60 | 34.56 | 46.34 | -11.78 | AVG |
| 7 | 0.9398 | 37.51 | 9.61 | 47.12 | 56.00 | -8.88 | QP |
| 8 | 0.9398 | 27.61 | 9.61 | 37.22 | 46.00 | -8.78 | AVG |
| 9 | 1.2677 | 35.87 | 9.61 | 45.48 | 56.00 | -10.52 | QP |
| 10 | 1.2677 | 27.07 | 9.61 | 36.68 | 46.00 | -9.32 | AVG |
| 11 | 1.6738 | 37.08 | 9.62 | 46.70 | 56.00 | -9.30 | QP |
| 12 | 1.6738 | 27.04 | 9.62 | 36.66 | 46.00 | -9.34 | AVG |

Note: 1. Result = Reading +Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).

4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes had been tested, but only the worst data was recorded in the report.



10. ANTENNA REQUIREMENTS

APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

RESULTS

Complies



10.1. Appendix A: DTS Bandwidth

10.1.1. Test Result

| Test Mode | Antenna | Channel | DTS BW [MHz] | FL[MHz] | FH[MHz] | Limit[MHz] | Verdict |
|-----------|---------|---------|--------------|----------|----------|------------|---------|
| 11B | Ant1 | 2412 | 10.120 | 2406.920 | 2417.040 | 0.5 | PASS |
| | | 2437 | 10.160 | 2431.920 | 2442.080 | 0.5 | PASS |
| | | 2462 | 10.160 | 2456.920 | 2467.080 | 0.5 | PASS |
| 11G | Ant1 | 2412 | 16.400 | 2403.800 | 2420.200 | 0.5 | PASS |
| | | 2437 | 16.440 | 2428.760 | 2445.200 | 0.5 | PASS |
| | | 2462 | 16.440 | 2453.760 | 2470.200 | 0.5 | PASS |
| 11N20SISO | Ant1 | 2412 | 17.720 | 2403.120 | 2420.840 | 0.5 | PASS |
| | | 2437 | 17.680 | 2428.160 | 2445.840 | 0.5 | PASS |
| | | 2462 | 17.680 | 2453.160 | 2470.840 | 0.5 | PASS |

10.1.2. Test Graphs







**10.2. Appendix B: Occupied Channel Bandwidth****10.2.1. Test Result**

| Test Mode | Antenna | Channel | OCB [MHz] | FL[MHz] | FH[MHz] | Limit[MHz] | Verdict |
|-----------|---------|---------|-----------|----------|----------|------------|---------|
| 11B | Ant1 | 2412 | 15.380 | 2404.284 | 2419.664 | --- | PASS |
| | | 2437 | 15.326 | 2429.324 | 2444.650 | --- | PASS |
| | | 2462 | 15.283 | 2454.342 | 2469.625 | --- | PASS |
| 11G | Ant1 | 2412 | 17.486 | 2403.193 | 2420.679 | --- | PASS |
| | | 2437 | 17.258 | 2428.321 | 2445.579 | --- | PASS |
| | | 2462 | 17.175 | 2453.381 | 2470.556 | --- | PASS |
| 11N20SISO | Ant1 | 2412 | 18.206 | 2402.922 | 2421.128 | --- | PASS |
| | | 2437 | 18.151 | 2427.940 | 2446.091 | --- | PASS |
| | | 2462 | 18.195 | 2452.891 | 2471.086 | --- | PASS |



10.2.2. Test Graphs









10.3. Appendix C: Maximum average conducted output power

10.3.1. Test Result


| Test Mode | Antenna | Channel | Result[dBm] | Limit[dBm] | Verdict |
|-----------|---------|---------|-------------|------------|---------|
| 11B | Ant1 | 2412 | 16.58 | ≤30 | PASS |
| | | 2437 | 16.36 | ≤30 | PASS |
| | | 2462 | 16.27 | ≤30 | PASS |
| 11G | Ant1 | 2412 | 10.53 | ≤30 | PASS |
| | | 2437 | 10.34 | ≤30 | PASS |
| | | 2462 | 10.19 | ≤30 | PASS |
| 11N20SISO | Ant1 | 2412 | 10.45 | ≤30 | PASS |
| | | 2437 | 10.27 | ≤30 | PASS |
| | | 2462 | 10.18 | ≤30 | PASS |


Note: The duty cycle correction factor had already added to the test result, for more information, please refer to clause 10.7.1 about the duty cycle correction factor.


**10.4. Appendix D: Maximum power spectral density****10.4.1. Test Result**

| Test Mode | Antenna | Channel | Result[dBm/3kHz] | Limit[dBm/3kHz] | Verdict |
|-----------|---------|---------|------------------|-----------------|---------|
| 11B | Ant1 | 2412 | -9.18 | ≤8 | PASS |
| | | 2437 | -9.32 | ≤8 | PASS |
| | | 2462 | -9.34 | ≤8 | PASS |
| 11G | Ant1 | 2412 | -16.94 | ≤8 | PASS |
| | | 2437 | -17.12 | ≤8 | PASS |
| | | 2462 | -16.99 | ≤8 | PASS |
| 11N20SISO | Ant1 | 2412 | -15.87 | ≤8 | PASS |
| | | 2437 | -17 | ≤8 | PASS |
| | | 2462 | -15.76 | ≤8 | PASS |

10.4.2. Test Graphs










10.5. Appendix E: Band edge measurements

10.5.1. Test Result

| Test Mode | Antenna | Ch Name | Channel | Ref Level[dBm] | Result[dBm] | Limit[dBm] | Verdict |
|-----------|---------|---------|---------|----------------|-------------|---------------|---------|
| 11B | Ant1 | Low | 2412 | 6.76 | -23.49 | ≤ -23.24 | PASS |
| | | High | 2462 | 6.51 | -45.42 | ≤ -23.49 | PASS |
| 11G | Ant1 | Low | 2412 | -0.79 | -33 | ≤ -30.79 | PASS |
| | | High | 2462 | -1.29 | -46.14 | ≤ -31.29 | PASS |
| 11N20SISO | Ant1 | Low | 2412 | -1.18 | -36.92 | ≤ -31.18 | PASS |
| | | High | 2462 | -1.44 | -45.62 | ≤ -31.44 | PASS |

10.5.2. Test Graphs







10.6. Appendix F: Conducted Spurious Emission


10.6.1. Test Result


| Test Mode | Antenna | Channel | Freq Range [Mhz] | Ref Level [dBm] | Result [dBm] | Limit [dBm] | Verdict |
|-----------|---------|---------|------------------|-----------------|--------------|---------------|---------|
| 11B | Ant1 | 2412 | Reference | 6.71 | 6.71 | --- | PASS |
| | | | 30~1000 | 6.71 | -57.19 | ≤ -23.29 | PASS |
| | | | 1000~26500 | 6.71 | -46.64 | ≤ -23.29 | PASS |
| | | 2437 | Reference | 6.55 | 6.55 | --- | PASS |
| | | | 30~1000 | 6.55 | -57.1 | ≤ -23.45 | PASS |
| | | | 1000~26500 | 6.55 | -46.66 | ≤ -23.45 | PASS |
| | | 2462 | Reference | 6.47 | 6.47 | --- | PASS |
| | | | 30~1000 | 6.47 | -57.57 | ≤ -23.53 | PASS |
| | | | 1000~26500 | 6.47 | -46.32 | ≤ -23.53 | PASS |
| 11G | Ant1 | 2412 | Reference | 4.48 | 4.48 | --- | PASS |
| | | | 30~1000 | 4.48 | -57.35 | ≤ -25.52 | PASS |
| | | | 1000~26500 | 4.48 | -46.37 | ≤ -25.52 | PASS |
| | | 2437 | Reference | -1.02 | -1.02 | --- | PASS |
| | | | 30~1000 | -1.02 | -57.84 | ≤ -31.02 | PASS |
| | | | 1000~26500 | -1.02 | -46.49 | ≤ -31.02 | PASS |
| | | 2462 | Reference | -1.30 | -1.30 | --- | PASS |
| | | | 30~1000 | -1.30 | -57.68 | ≤ -31.3 | PASS |
| | | | 1000~26500 | -1.30 | -46.98 | ≤ -31.3 | PASS |
| 11N20SISO | Ant1 | 2412 | Reference | -2.15 | -2.15 | --- | PASS |
| | | | 30~1000 | -2.15 | -56.95 | ≤ -32.15 | PASS |
| | | | 1000~26500 | -2.15 | -46.42 | ≤ -32.15 | PASS |
| | | 2437 | Reference | -1.26 | -1.26 | --- | PASS |
| | | | 30~1000 | -1.26 | -57.32 | ≤ -31.26 | PASS |
| | | | 1000~26500 | -1.26 | -46.96 | ≤ -31.26 | PASS |
| | | 2462 | Reference | -1.60 | -1.60 | --- | PASS |
| | | | 30~1000 | -1.60 | -57.22 | ≤ -31.6 | PASS |
| | | | 1000~26500 | -1.60 | -45.79 | ≤ -31.6 | PASS |


10.6.2. Test Graphs

























10.7. Appendix G: Duty Cycle

10.7.1. Test Result

| Test Mode | On Time (msec) | Period (msec) | Duty Cycle x (Linear) | Duty Cycle (%) | Duty Cycle Correction Factor (dB) | 1/T Minimum VBW (kHz) | Final setting For VBW (kHz) |
|-----------|-------------------|------------------|-----------------------------|-------------------|--------------------------------------------|--------------------------------|-----------------------------------|
| 11B | 8.39 | 8.46 | 0.9917 | 99.17 | 0.04 | 0.12 | 0.01 |
| 11G | 1.39 | 1.46 | 0.9521 | 95.21 | 0.21 | 0.72 | 1 |
| 11N20SISO | 5.08 | 5.15 | 0.9864 | 98.64 | 0.06 | 0.20 | 0.5 |

Note:

Duty Cycle Correction Factor=10log (1/x).

Where: x is Duty Cycle (Linear)

Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.



10.7.2. Test Graphs



END OF REPORT