

全	开(大度开成品)1160 x 860	(正度开成品)1060 x 760
对	开(大度开成品)860 x 580	(正度开成品)760 x 530
长	对开(大度开成品)1160 x 430	(正度开成品)1060 x 370
三	开(大度开成品)860 x 385	(正度开成品)760 x 340
丁字三开	(大度开成品)720 x 430	(正度开成品)680 x 370
四	开(大度开成品)580 x 430	(正度开成品)530 x 370

1P(磅)=0.353mm, 1英寸=25.4mm≈72P(点), 1英寸=1440bwip(像素), 1cm=567bwip(像素)

Thanks for choosing us!

This product is a 3 in 1 wireless charger, support phone/Airpods/Apple Watch charging at the same time.

Please kindly read the user manual before using and keep it for future reference.

Specification

Input: 5V=3A, 9V=3A, 12V=3A

Output[Phone]: 15W Max

Output[Watch]: 3W

Output[Earbuds]: 5W Max

Charging distance: ≤10mm

Conversion: ≥72%

WIFI: 2.4G

Dimensions: 93*149*163mm

① Make sure the wireless charger dock connect to the power supply.

② Put the smartphone/Airpods/Apple Watch properly on the transmitter.

Charging Mode

- Do not squeeze or collisions.
- Do not disassemble or throw into fire or water, to avoid causing a short circuit leakage.
- Do not use wireless charger in severely hot, humid or corrosive environments, to avoid circuit damage and occurs leakage phenomenon.
- Do not place too close with magnetic stripe or chip card (ID card, bank cards, etc.) to avoid magnetic failure.
- Please keep the distance at least 20cm between implantable medical devices (pacemakers, implantable cochlear, etc.) and the wireless charger, to avoid potential interference with the medical device.
- To take care of the children, to ensure that they won't play the wireless charger as a toy, to avoid unnecessary accidents.

CE

CE Maintenance

1.EUT Operating temperature range: -10° C to 35° C.

2.The device complies with RF specifications when the device used at 20mm from your body.

Declaration of Conformity

Powerli hereby declares that this LM35 Q2 3-in-1 Wireless Charger is in compliance with the essential requirements and other relevant provisions of Directive 2014/53/EU in accordance with Article 10(2) and Article 10(10). This product is allowed to be used in all EU member states.

FCC Warning

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radiofrequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

The FCC certification of this device refers to RF exposure testing performed in typical operating conditions, where a person is no closer than 20 centimeters from the device surface at all times, except for non-repetitive patterns with transient time intervals in the order of a second. Only in the stated conditions, the device is shown to fully comply with the FCC RF Exposure requirements of KDB-447498.

Frequency Band(s):

Coil1: For Phone: 113kHz-205kHz, 360kHz

Coil2: For Earphone: 113kHz-205kHz

Coil3: Watch: 309kHz-359kHz

Corrected Amplitude H-field:

Coil1:113kHz-205kHz: 21.64dBuA/m;

360kHz: 18.01dBuA/m

Coil2: 21.92dBuA/m

Coil3: 21.16 dBuA/m

The involved images are sketch maps, the final product as per the material subjects.

Includes: wireless charger, Power cable , user's manual.

[illegible]