

ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY
SYOSSET, NY 11791

FCC ID # CFS8DL5815

Date : ____ 8/20/2003 Tested by: Greg Barbato

Approved by: Ken Addy

Test Sample (model) : _____ 5815

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30								729
345	H	77.39	1.2	17.91	66834.4	10%	6683.4	7292
690	H	34.70	2	22.81	945.1	10%	94.5	729
1035	H	35.00	2.6	25.69	1460.5	10%	146.0	500
1380	H	29.17	3	25.51	765.6	10%	76.6	500
1725	H	29.17	3.5	26.25	883.1	10%	88.3	729
2070	H	31.00	3.9	28.31	1447.1	10%	144.7	729
2415	H	27.17	4.3	28.57	1004.6	10%	100.5	729
2760	H	26.00	4.7	29.52	1025.7	10%	102.6	729
3105	H	27.49	4.9	30.83	1448.8	10%	144.9	729
3405	H	28.00	5.1	32.4	1883.6	10%	188.4	729
4000								