

RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $Pd = (Pout * G) / (4 * pi * r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

Test Result of RF Exposure Evaluation

WIFI 2.4G

Channel	Output power to antenna (dBm)	Maximum tune-up (dBm)	Maximum tune-up (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
2462MHz	17.27	18	63.10	0.0276	1.0	PASS

Remark: antenna gain=3.42dBi

BT EDR

Channel	Output power to antenna (dBm)	Maximum tune-up (dBm)	Maximum tune-up (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
2480MHz	5.42	6	3.98	0.0017	1.0	PASS

Remark: antenna gain=3.42dBi

BLE

Channel	Output power to antenna (dBm)	Maximum tune-up (dBm)	Maximum tune-up (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
2440MHz	1.72	2	1.58	0.0007	1.0	PASS

Remark: antenna gain=3.42dBi

912.375MHz

Frequency	Field strength (dBuV/m@3m)	P _{conducted} (mW)	P _{conducted} (dBm)	EIRP (dBm)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
912.375MHz	90.33	0.27	-5.69	-4.94	0.0003	0.61	PASS

Remark: antenna gain=0.75dBi

ERP=EIRP-2.15=-4.94-2.15=-7.09dBm(0.2mW)

Simultaneous Transmission:

WIFI+BT EDR+912.375MHz: 0.030<1

WIFI+BLE+912.375MHz: 0.029<1

The max power density is less than MPE exempt limit, so it is compliance.