

TEST REPORT

Applicant Name : Kirisun Communication Co., Ltd.
Address : 3rd Floor, Building A, Tongfang Information Harbour, No.11
Langshan Road Nanshan District, Shenzhen 518057 China
Report Number : SZNS211130-61583E-RF-00
FCC ID: Q5ETP2210H7

Test Standard (s)

FCC PART 90

Sample Description

Product Type: DMR Two Way Radio
Model No.: TP2210-H7
Multiple Model(s) No.: N/A
Date Received: 2021/11/30
Date of Test: 2021/12/09~2022/01/25
Report Date: 2022/01/25

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:



Black Ding
EMC Engineer

Approved By:



Robert Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "★". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
JUSTIFICATION	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE	6
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
TEST EQUIPMENT LIST	8
FCC §1.1307(B) & §2.1093 - RF EXPOSURE INFORMATION	10
APPLICABLE STANDARD	10
TEST RESULT	10
FCC §2.1046 & §90.205 - RF OUTPUT POWER	11
APPLICABLE STANDARD	11
TEST PROCEDURE	11
TEST DATA	11
FCC §2.1047 & §90.207 - MODULATION CHARACTERISTIC	19
APPLICABLE STANDARD	19
TEST PROCEDURE	19
TEST DATA	19
FCC §2.1049 & §90.209 & §90.210 – OCCUPIED BANDWIDTH & EMISSION MASK	25
APPLICABLE STANDARD	25
TEST PROCEDURE	25
TEST DATA	25
FCC §2.1051 & §90.210 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	39
APPLICABLE STANDARD	39
TEST PROCEDURE	39
TEST DATA	39
FCC §2.1053 & §90.210 - RADIATED SPURIOUS EMISSIONS	46
APPLICABLE STANDARD	46
TEST PROCEDURE	46
TEST DATA	46
FCC §2.1055 & §90.213 - FREQUENCY STABILITY	48
APPLICABLE STANDARD	48
TEST PROCEDURE	48
TEST DATA	48

FCC §90.214 - TRANSIENT FREQUENCY BEHAVIOR.....50
 APPLICABLE STANDARD50
 TEST PROCEDURE50
 TEST DATA51

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Frequency Range	450MHz to 520MHz
Rated Transmit Power	4Watts(High), 1Watt(Low)
Channel separation	12.5kHz
Modulation Technique	4FSK/FM
Antenna Specification*	2.15dBi (provided by the applicant)
Voltage Range	DC 7.4V from battery or DC12V from adapter
Sample serial number	SZNS211130-61583E-RF-S1 (Assigned by ATC)
Sample/EUT Status	Good condition
Adapter information	Model: FJ-SW126K1201000DU Input: 100-240V~ 50/60Hz 0.4A Max Output: DC 12.0V, 1000mA

Objective

This test report is in accordance with Part 2, and Part 90 of the Federal Communication Commissions rules.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of federal Regulations Title 47 Part 2, Sub-part J as well as the following individual parts:

Part 90 – Private Land Mobile Radio Service

Applicable Standards: TIA 603-E, ANSI C63.26-2015.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF output power, conducted		±0.73dB
Unwanted Emission, conducted		±1.6dB
RF Frequency		±0.082*10 ⁻⁷
Emissions, Radiated	30MHz - 1GHz	±4.28dB
	1GHz - 18GHz	±4.98dB
	18GHz - 26.5GHz	±5.06dB
Temperature		±1°C
Humidity		±6%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing in a test mode which has been done in the factory.

Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Unknown	Load	Unknown	Unknown

External I/O Cable

Cable Description	Length (m)	From Port	To
/	/	/	

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§1.1307, §2.1093	RF Exposure (SAR)	Compliant
§2.1046; §90.205	RF Output Power	Compliant
§2.1047; §90.207	Modulation Characteristic	Compliant
§2.1049; §90.209; §90.210	Occupied Bandwidth & Emission Mask	Compliant
§2.1051; §90.210	Spurious Emission at Antenna Terminal	Compliant
§2.1053; §90.210	Spurious Radiated Emissions	Compliant
§2.1055; §90.213	Frequency Stability	Compliant
§90.214	Transient Frequency Behavior	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test					
Rohde& Schwarz	Test Receiver	ESR	101817	2020/12/24	2021/12/23
Rohde&Schwarz	Spectrum Analyzer	FSV40	101495	2020/12/24	2021/12/23
SONOMA INSTRUMENT	Amplifier	310 N	186131	2020/12/25	2021/12/24
A.H. Systems, inc.	Preamplifier	PAM-0118P	531	2021/11/09	2022/11/08
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-5m	No.3	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-1m	No.5	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-10m	No.7	2021/11/09	2022/11/08
Unknown	RF Coaxial Cable	N-2m	No.8	2021/11/09	2022/11/08
Unknown	Pass filter	NHP-600+	F-03-EM131	2021/11/29	2022/11/28
Schwarzbeck	Bilog Antenna	VULB9163	9163-194	2020/01/05	2023/01/04
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2020/01/05	2023/01/04
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-655	2020/01/05	2023/01/04
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Unknown	RF Coaxial Cable	N-1m	No.7	2020/12/25	2021/12/24
Anritsu	Signal Generator	68369B	004114	2021/07/31	2022/07/30

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Rohde & Schwarz	SPECTRUM ANALYZER	FSU26	200982	2021/07/06	2022/07/05
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2021/04/24	2022/04/24
E-Microwave	Band Rejector Filter	OBF-ZP-400-470-NF	OE01201051	2021/10/15	2022/10/14
HP Agilent	RF Communication test set	8920B	3325U00859	2021/03/15	2022/03/15
Aeroflex/Weinschel	30dB Attenuator (Input 250W/Output 50W)	58-30-33	PS467	2020/12/25	2021/12/24
Aeroflex/Weinschel	30dB Attenuator (Input 250W/Output 50W)	58-30-33	PS467	2021/12/25	2022/12/24
Mini-Circuits	Power Splitter	DC-18000MHz	SF10944151S	2020/12/25	2021/12/24

* Statement of Traceability: Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307(b) & §2.1093 - RF EXPOSURE INFORMATION

Applicable Standard

FCC§1.1310 and §2.1093.

Test Result

Compliance, please refer to the SAR report: CR21110096-20A.

FCC §2.1046 & §90.205 - RF OUTPUT POWER**Applicable Standard**

FCC §2.1046 and §90.205

Test Procedure

Conducted RF Output Power:

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

Spectrum Analyzer Setting:

R B/W	Video B/W
100 kHz	300 kHz

Test Data**Environmental Conditions**

Temperature:	26.5 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Black Ding from 2021-12-10 to 2021-12-11.

Test Mode: Transmitting

Test Result: *Pass. Please refer to following table.*


Conducted Output Power

Mode	Frequency Spacing (kHz)	Frequency (MHz)	Power level	Output (dBm)	Output Power (W)	Note
Digital	12.5	450.0125	L	30.59	1.15	FCC 90
			H	36.66	4.63	
	12.5	469.9875	L	30.31	1.07	
			H	36.61	4.58	
	12.5	519.9875	L	30.16	1.04	
			H	36.78	4.76	
Analog	12.5	450.0125	L	30.69	1.17	
			H	36.61	4.58	
	12.5	469.9875	L	30.32	1.08	
			H	36.58	4.55	
	12.5	519.9875	L	30.33	1.08	
			H	36.74	4.72	


Rated low power: 1W (Limit: 0.8W~1.2W)

Rated high power: 4W (Limit: 3.2W~4.8W)

Digital:


Frequency 450.0125 MHz, Low Power

Date: 10.DEC.2021 20:42:09

Frequency 450.0125 MHz, High Power


Date: 11.DEC.2021 15:30:20

Frequency 469.9875MHz, Low Power




Date: 10.DEC.2021 20:46:19

Frequency 469.9875MHz, High Power




Date: 11.DEC.2021 15:33:06

Frequency 519.9875 MHz, Low Power



Date: 10.DEC.2021 20:47:20


Frequency 519.9875 MHz, High Power



Date: 11.DEC.2021 15:33:58


Analog

Frequency 450.0125 MHz, Low Power




Date: 10.DEC.2021 20:48:58


Frequency 450.0125 MHz, High Power



Date: 11.DEC.2021 15:34:57


Frequency 469.9875MHz, Low Power

Date: 10.DEC.2021 20:52:17

Frequency 469.9875MHz, High Power


Date: 11.DEC.2021 15:35:59

Frequency 519.9875 MHz, Low Power



Date: 10.DEC.2021 20:53:17

Frequency 519.9875 MHz, High Power



Date: 11.DEC.2021 15:36:49

FCC §2.1047 & §90.207 - MODULATION CHARACTERISTIC

Applicable Standard

FCC§2.1047 and §90.207:

- (a) Equipment which utilizes voice modulated communication shall show the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz. for equipment which is required to have a low pass filter, the frequency response of the filter, or all of the circuitry installed between the modulation limited and the modulated stage shall be supplied.
- (b) Equipment which employs modulation limiting, a curve showing the percentage of modulation versus the modulation input voltage shall be supplied.

Test Procedure

Test Method: ANSI C63.26-2015

Test Data

Environmental Conditions

Temperature:	26.5 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Black Ding from 2021-12-10 to 2021-12-13.


Test Mode: Transmitting

Test Result: *Pass. Please refer to the following tables and plots.*

Analog Modulation:**MODULATION LIMITING**

Carrier Frequency: 469.9875 MHz, Channel Separation=12.5 kHz


Audio Frequency (Hz)	Instantaneous		Steady-state		FCC Limit [kHz]
	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	
300	2.248	0.052	2.254	0.061	2.500
400	2.324	0.067	2.345	0.078	2.500
500	2.059	0.081	2.069	0.089	2.500
600	1.971	0.102	1.985	0.114	2.500
700	1.891	0.115	1.899	0.126	2.500
800	1.785	0.135	1.796	0.154	2.500
900	1.815	0.152	1.836	0.164	2.500
1000	1.865	0.167	1.894	0.187	2.500
1200	1.998	0.206	2.005	0.216	2.500
1400	2.032	0.234	2.037	0.247	2.500
1600	2.036	0.235	2.049	0.254	2.500
1800	2.012	0.296	2.047	0.312	2.500
2000	1.990	0.332	2.021	0.347	2.500
2100	2.009	0.345	2.036	0.359	2.500
2200	2.001	0.362	2.024	0.372	2.500
2300	2.006	0.375	2.026	0.395	2.500
2400	1.991	0.394	2.006	0.399	2.500
2500	1.973	0.405	1.982	0.412	2.500
2600	1.972	0.418	1.981	0.424	2.500
2700	1.961	0.430	1.974	0.435	2.500
2800	1.935	0.441	1.963	0.447	2.500
2900	1.915	0.447	1.932	0.449	2.500
3000	1.881	0.452	1.892	0.456	2.500



Audio Frequency Response

Carrier Frequency: 469.9875MHz, Channel Separation=12.5 kHz


Audio Frequency (Hz)	Response Attenuation (dB)
300	-13.23
400	-9.63
500	-7.01
600	-4.94
700	-3.45
800	-2.11
900	-0.74
1000	0.00
1200	1.77
1400	3.25
1600	4.43
1800	5.46
2000	6.33
2100	6.76
2200	7.14
2300	7.52
2400	7.83
2500	8.16
2600	8.45
2700	8.68
2800	8.86
2900	8.96
3000	9.04



Audio frequency lows pass filter response

Carrier Frequency: 469.9875MHz, Channel Separation=12.5 kHz

Audio Frequency (kHz)	Response Attenuation (dB)	Limit (dB)
1.0	0.0	/
3.0	-20.7	0.0
4.0	-77.4	-12.5
5.0	-85.3	-22.2
6.0	-86.4	-30.1
7.0	-87.4	-36.8
8.0	-87.5	-42.6
9.0	-88.9	-47.7
10.0	-90.8	-52.3
12.0	-93.2	-60.2
14.0	-95.3	-66.9
16.0	-94.1	-72.7
18.0	-91.4	-77.8
20.0	-91.0	-82.5



FCC §2.1049 & §90.209 & §90.210 – OCCUPIED BANDWIDTH & EMISSION MASK

Applicable Standard

FCC §2.1049 and §90.210

Emission Mask D - 12.5 kHz channel bandwidth equipment. For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- 1) For any frequency removed from the center of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 , 0dB.
- 2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5.626 kHz but no more than 12.5 kHz, at least 7.27 ($f_d - 2.88$ kHz) dB.
- 3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz at least: At least $50 + 10 \log (P)$ dB or 70 dB, whichever is the lesser attenuation.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 100 Hz and the spectrum was recorded in the frequency band ± 50 kHz from the carrier frequency.

Test Data

Environmental Conditions

Temperature:	26.5 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Black Ding from 2021-12-10 to 2021-12-27.

Test mode: transimitting

Test Result: *Pass. Please refer to the following tables and plots.*

Modulation	Channel Separation (kHz)	Frequency (MHz)	Power Level	99% Occupied Bandwidth (kHz)	26 dB Emissions Bandwidth (kHz)
Analog	12.5	450.0125	L	9.936	10.256
	12.5		H	9.936	10.240
Digital	12.5	450.0125	L	7.612	10.176
	12.5		H	7.612	9.215

Modulation	Channel Separation (kHz)	Frequency (MHz)	Power Level	99% Occupied Bandwidth (kHz)	26 dB Emissions Bandwidth (kHz)
Analog	12.5	469.9875	L	9.936	10.208
	12.5		H	9.936	10.208
Digital	12.5	469.9875	L	7.612	9.583
	12.5		H	7.612	10.016

Modulation	Channel Separation (kHz)	Frequency (MHz)	Power Level	99% Occupied Bandwidth (kHz)	26 dB Emissions Bandwidth (kHz)
Analog	12.5	519.9875	L	9.856	10.176
	12.5		H	9.936	10.176
Digital	12.5	519.9875	L	7.612	9.615
	12.5		H	7.772	9.936

Note: Emission designator is base on calculation instead of measurement.

Emission Designator Per CFR 47 §2.201& §2.202&, $B_n = 2M + 2D$

For FM Mode (Channel Spacing: 12.5 kHz)

Emission Designator 11K0F3E. In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation. $BW = 2(M+D) = 2*(3.0 \text{ kHz} + 2.5 \text{ kHz}) = 11 \text{ kHz} \rightarrow 11K0$

F3E portion of the designator represents an FM voice transmission Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.

For Digital Mode (Channel Spacing: 12.5 kHz)


Emission Designator 7K60F1D and 7K60F1E

The 99% energy rule (title 47CFR 2.1049) was used for digital mode. It basically states that 99% of the modulation energy falls within X kHz, in this case, 7.60 kHz. The emission mask was obtained from 47CFR 90.210(d).


F1D and F1E portion of the designator indicates digital information.

Therefore, the entire designator for 12.5 kHz channel spacing digital mode is 7K60F1D and 7K60F1E.


Digital:

Frequency 450.0125 MHz: 99% Occupied & 26 dB Bandwidth, Low Power


Date: 11.DEC.2021 00:11:47

Frequency 450.0125 MHz: 99% Occupied & 26 dB Bandwidth, High Power


Date: 10.DEC.2021 23:51:57

Frequency 450.0125MHz: Emission Mask D, Low Power


Date: 10.DEC.2021 22:42:50

Frequency 450.0125 MHz: Emission Mask D, High Power


Date: 10.DEC.2021 23:48:20

Frequency 469.9875MHz: 99% Occupied & 26 dB Bandwidth, Low Power


Date: 11.DEC.2021 00:05:43

Frequency 469.9875 MHz: 99% Occupied & 26 dB Bandwidth, High Power


Date: 10.DEC.2021 23:58:28

Frequency 469.9875 MHz: Emission Mask D, Low Power


Date: 10.DEC.2021 22:53:11

Frequency 469.9875 MHz: Emission Mask D, High Power


Date: 10.DEC.2021 23:43:22

Frequency 519.9875 MHz: 99% Occupied & 26 dB Bandwidth, Low Power


Date: 11.DEC.2021 00:03:16

Frequency 519.9875MHz: 99% Occupied & 26 dB Bandwidth, High Power

Date: 11.DEC.2021 00:00:51

Frequency 519.9875MHz: Emission Mask D, Low Power


Date: 27.DEC.2021 15:22:06

Frequency 519.9875 MHz: Emission Mask D, High Power

Date: 27.DEC.2021 15:20:29


Analog

Frequency 450.0125 MHz: 99% Occupied & 26 dB Bandwidth, Low Power




Date: 11.DEC.2021 00:33:04


Frequency 450.0125 MHz: 99% Occupied & 26 dB Bandwidth, High Power




Date: 11.DEC.2021 00:26:27

Frequency 450.0125MHz: Emission Mask D, Low Power


Date: 11.DEC.2021 00:41:27

Frequency 450.0125MHz: Emission Mask D, High Power


Date: 11.DEC.2021 00:54:22

Frequency 469.9875MHz: 99% Occupied & 26 dB Bandwidth, Low Power


Date: 11.DEC.2021 00:30:35

Frequency 469.9875MHz: 99% Occupied & 26 dB Bandwidth, High Power


Date: 11.DEC.2021 00:23:47

Frequency 469.9875MHz: Emission Mask D, Low Power


Date: 11.DEC.2021 00:44:46

Frequency 469.9875MHz: Emission Mask D, High Power


Date: 11.DEC.2021 00:51:23

Frequency 519.9875MHz: 99% Occupied & 26 dB Bandwidth, Low Power


Date: 11.DEC.2021 00:29:04

Frequency 519.9875 MHz: 99% Occupied & 26 dB Bandwidth, High Power

Date: 11.DEC.2021 00:22:33

Frequency 519.9875 MHz: Emission Mask D, Low Power

Date: 11.DEC.2021 00:46:39

Frequency 519.9875MHz: Emission Mask D, High Power

Date: 11.DEC.2021 00:49:55

FCC §2.1051 & §90.210 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS

Applicable Standard

Emission Mask D—12.5 kHz channel bandwidth equipment. For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- 1) For any frequency removed from the center of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 , 0 dB.
- 2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5.626 kHz but no more than 12.5 kHz, at least 7.27 ($f_d - 2.88$ kHz) dB.
- 3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz: At least $50 + 10 \log (P)$ dB or 70 dB, whichever is the lesser attenuation.

Test Procedure

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100kHz for below 1GHz, and 1MHz for above 1GHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.

Test Data

Environmental Conditions

Temperature:	26.5 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa


The testing was performed by Black Ding on 2021-12-11 and 2022-01-25.

Test Mode: Transmitting, worst case for high power level.

Test Result: *Pass. Please refer to the following plots.*


Digital

30MHz – 1 GHz, - Low Channel




Date: 11.DEC.2021 15:57:26

1 GHz – 5 GHz, - Low Channel




Date: 11.DEC.2021 16:03:04

30MHz – 1 GHz, - Middle Channel




Date: 11.DEC.2021 15:56:45


1 GHz – 5 GHz, Middle Channel



Date: 11.DEC.2021 16:03:31

30MHz – 1 GHz, - High Channel


Date: 25.JAN.2022 10:43:57

1 GHz – 5.5 GHz, High Channel

Date: 25.JAN.2022 10:47:52


Analog

30MHz – 1 GHz, - Low Channel




Date: 11.DEC.2021 15:58:03

1 GHz – 5 GHz, - Low Channel




Date: 11.DEC.2021 16:04:27

30MHz – 1 GHz, - Middle Channel




Date: 11.DEC.2021 15:58:51

1 GHz – 5 GHz, Middle Channel




Date: 11.DEC.2021 16:04:41

30MHz – 1 GHz, - High Channel



Date: 25.JAN.2022 10:44:21

1 GHz – 5.5 GHz, High Channel



Date: 25.JAN.2022 10:48:25

FCC §2.1053 & §90.210 - RADIATED SPURIOUS EMISSIONS

Applicable Standard

FCC §2.1053 and §90.210

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load, which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to teeth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = 10 lg (TXpwr in Watts/0.001)-the absolute level

Spurious attenuation limit in dB = 50 + 10 Log₁₀ (power out in Watts) for EUT with a 12.5 kHz channel bandwidth.

Test Data

Environmental Conditions

Temperature:	25~26.7 °C
Relative Humidity:	46~50 %
ATM Pressure:	101.0 kPa

The testing was performed by Caro Hu on 2021-12-09 for below 1GHz and on 2021-12-16 for above 1GHz.

Test Mode: Transmitting, worst case for high power level.

Test Result: Pass. Please refer to the following tables.

Frequency (MHz)	Receiver Reading (dBm)	Turntable Degree	Rx Antenna		Substituted Factor (dB)	Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)				
Digital								
450.0125MHz								
900.025	-57.63	195	1.8	H	9.6	-48.03	-20	28.03
900.025	-62.33	250	2.2	V	12.6	-49.73	-20	29.73
4500.13	-45.1	197	2	H	10.6	-34.5	-20	14.5
4500.13	-45.1	138	1.8	V	9.9	-35.2	-20	15.2
469.9875 MHz								
939.975	-57.06	254	1.4	H	9.2	-47.86	-20	27.86
939.975	-56.36	136	1	V	11.7	-44.66	-20	24.66
4699.88	-52.7	51	1.9	H	10.9	-41.8	-20	21.8
4699.88	-51.8	269	1.9	V	10	-41.8	-20	21.8
519.9875 MHz								
938.56	-73.79	286	1.6	H	9.2	-64.59	-20	44.59
938.56	-78.68	232	1.1	V	11.7	-66.98	-20	46.98
5199.88	-49.2	265	1.4	H	10.3	-38.9	-20	18.9
5199.88	-44.8	79	1.6	V	9.8	-35	-20	15

Frequency (MHz)	Receiver Reading (dBm)	Turntable Degree	Rx Antenna		Substituted Factor (dB)	Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)				
Analogue								
450.0125MHz								
900.025	-59.13	205	1.3	H	9.6	-49.53	-20	29.53
900.025	-63.03	125	1.2	V	12.6	-50.43	-20	30.43
4500.13	-46.9	338	2	H	10.6	-36.3	-20	16.3
4500.13	-45.7	62	1.5	V	9.9	-35.8	-20	15.8
469.9875 MHz								
939.975	-57.16	335	2.2	H	9.2	-47.96	-20	27.96
939.975	-57.86	39	1.8	V	11.7	-46.16	-20	26.16
4699.88	-52.4	180	1.9	H	10.9	-41.5	-20	21.5
4699.88	-51.5	255	1.8	V	10	-41.5	-20	21.5
519.9875 MHz								
944.59	-74.37	340	1.8	H	9.2	-65.17	-20	45.17
944.59	-77.97	109	1	V	11.7	-66.27	-20	46.27
5199.88	-52.4	320	1.3	H	10.3	-42.1	-20	22.1
5199.88	-47.1	76	1.8	V	9.8	-37.3	-20	17.3

Note:

Absolute Level = Reading Level + Substituted Factor

Substituted Factor contains: SG Level - Cable loss+ Antenna Gain

Margin = Limit - Absolute Level

FCC §2.1055 & §90.213 - FREQUENCY STABILITY

Applicable Standard

FCC §2.1055 and §90.213

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external AC/DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The power cable and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the counter.

Test Data

Environmental Conditions

Temperature:	26.5 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Black Ding from 2021-12-10 to 2021-12-13.

Test Mode: Transmitting, worst case for high power level.

Test Result: Pass. Please refer to the following tables.

For Analog Modulation:

Reference Frequency:469.9875MHz, Limit:2.5 ppm, 12.5kHz			
Environment Temperature (°C)	Power Supplied (Vdc)	Frequency Measure with Time Elapsed	
		MCF (MHz)	PPM Error
50	7.4	469.987512	0.026
40	7.4	469.987531	0.066
30	7.4	469.987527	0.057
20	7.4	469.987508	0.017
10	7.4	469.987523	0.049
0	7.4	469.987509	0.019
-10	7.4	469.987499	-0.002
-20	7.4	469.987482	-0.038
-30	7.4	469.987526	0.055
Frequency Stability Versus Input Voltage			
20	6.5	469.987514	0.030
20	8.4	469.987528	0.060

For Digital Modulation:

Reference Frequency:469.9875MHz, Limit:2.5 ppm, 12.5kHz			
Environment Temperature (°C)	Power Supplied (Vdc)	Frequency Measure with Time Elapsed	
		MCF (MHz)	PPM Error
50	7.4	469.987536	0.077
40	7.4	469.987529	0.062
30	7.4	469.987535	0.074
20	7.4	469.987522	0.047
10	7.4	469.987534	0.072
0	7.4	469.987519	0.040
-10	7.4	469.987516	0.034
-20	7.4	469.987514	0.030
-30	7.4	469.987524	0.051
Frequency Stability Versus Input Voltage			
20	6.5	469.987532	0.068
20	8.4	469.987518	0.038


FCC §90.214 - TRANSIENT FREQUENCY BEHAVIOR

Applicable Standard

Regulations: FCC §90.214
Test method: ANSI C63.26-2015

Test Procedure

- Connect the EUT and test equipment as shown on the following block diagram.
- Set the Spectrum Analyzer to measure FM deviation, and tune the RF frequency to the transmitter assigned frequency.
- Set the signal generator to the assigned transmitter frequency and modulate it with a 1 kHz tone at ± 12.5 kHz deviation and set its output level to -100dBm.
- Turn on the transmitter.
- Supply sufficient attenuation via the RF attenuator to provide an input level to the Spectrum Analyzer that is 40 dB below the maximum allowed input power when the transmitter is operating at its rated power level. Note this power level on the Spectrum Analyzer as P_0 .
- Turn off the transmitter.
- Adjust the RF level of the signal generator to provide RF power equal to P_0 . This signal generator RF level shall be maintained throughout the rest of the measurement.
- Remove the attenuation 1, so the input power to the Spectrum Analyzer is increased by 30 dB when the transmitter is turned on.
- Adjust the vertical amplitude control of the spectrum analyzer to display the 1000 Hz at ± 4 divisions vertically centered on the display. Set trigger mode of the Spectrum Analyzer to "Video", and tune the "trigger level" on suitable level. Then set the "trigger offset" to -10ms for turn on and -15ms for turn off.
- Turn on the transmitter and the transient wave will be captured on the screen of Spectrum Analyzer. Observe the stored display. The instant when the 1 kHz test signal is completely suppressed is considered to be t_{on} . The trace should be maintained within the allowed divisions during the period t_1 and t_2 .
- Then turn off the transmitter, and another transient wave will be captured on the screen of Spectrum Analyzer. The trace should be maintained within the allowed divisions during the period t_3 .




Test Data**Environmental Conditions**

Temperature:	26.5 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa


The testing was performed by Black Ding from 2021-12-13 .

Test Result: Pass. Please refer to the following tables and plots.

Channel Separation (kHz)	Transient Period (ms)	Transient Frequency	Result
12.5	10 (t1)	<+/-12.5 kHz	Pass
	25 (t2)	<+/-6.25 kHz	
	10 (t3)	<+/-12.5 kHz	

Turn on

Turn off



***** END OF REPORT *****