

Asset Tag

AT11 DATASHEET | Model 030-00007



OVERVIEW

The Asset Tag is a compact tracking device built to easily locate, manage, and safeguard small, mission-critical tools and equipment. It features a ruggedized, waterproof enclosure, near real-time location updates via the Samsara Network, and discrete but flexible mounting options.

The Asset Tag enables improved inventory management, loss and theft protection, and field productivity for operations that manage assets at scale.

HIGHLIGHTS

- Samsara Network: Approximate BLE location updates via Samsara's network of gateways
- Inventory management: Prevent service interruptions by maintaining clear visibility of asset inventory with detailed reports
- Mobile-first tools: Locate assets in the field directly from Samsara's Driver or Fleet app
- Easy installation: Discrete, flexible mounting options for quick installation
- Unified platform: Unlocks a wide array of customizable reports, alerts, and mobile apps for workers and admins as part of Samsara's Connected Operations Platform

Technical Specifications

CONNECTIVITY

Data Communications: 2.4GHz ISM Band **Output power:** 20dBm (US), 12dBm (EU)

Operating area: United States, Canada, UK, Mexico, Europe

Secure Communications: All communications are anonymized and authenticated using AES encryption

LOCATION

Approximate geolocation is based on the GPS location of nearby gateways in the Samsara network that detect the Asset Tag 2.4 GHz advertisements.

POWER

The Asset Tag is powered by a high capacity Li-Ion CR2/3AZ battery that is designed to last 4 years under nominal conditions and is not replaceable. Actual battery life may be reduced by extreme temperatures. For questions about the safe use of Li-Ion battery powered devices, please consult your company's safety department.

Rating 3V, 0.5A max

ENCLOSURE

- Material UV-stabilized polycarbonate
- Dimensions 22 x 28 x 65 mm
- Weight 35 g
- Operating Temperature -40°C to 60°C
- IP Rating
 - o IP67 (weatherproof and water resistant up to 1m submerged)
 - o IP69K (highest grade resistance to high pressure and high temperature washdown)

SAMSARA CLOUD SOFTWARE FEATURES

- Approximate GPS based location tracking
- Developer APIs
- Alerts
- Inventory Reports
- Geofence

INSTALL ACCESSORIES

What's Included

1x Double Sided VHB tape per device

Regulatory Information

IC STATEMENT

This device complies with Industry Canada's license-exempt RSSs. Operation is subject to the following two conditions: (1) This device may not cause interference; and (2) This device must accept any interference, including interference that may cause undesired operation of the device.

This equipment complies with Innovation, Science and Economic Development Canada RF exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated to ensure a minimum of 20 cm spacing to any person at all times. CAN ICES-3(A)/NMB-3(A)

IC Radiation Exposure Statement: This equipment complies with Canada radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator and your body

FEDERAL COMMUNICATION COMMISSION INTERFERENCE STATEMENT

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

FCC Caution: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. FCC Caution: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment. FCC Radiation Exposure Statement: This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance 20cm between the radiator & your body. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

For detailed product specifications and important safety information, please refer to the product's installation guide, available at http://samsara.com/at11-install.