

eROU Ant2

- LTE Middle / High-Band Antenna

Data Sheets



AWAVE

[08592] 519~520Ho, 75-15, Gasan digital 1-ro, Geumcheon-gu, Seoul, Republic of Korea

E-mail : awaveantenna@gmail.com



Contents

1.	AWAVE LTE Antenna	.3
2.	Features	.3
3.	Specifications and Interface	.3
4.	Return Loss	.4
5.	Gain and Efficiency	.5
6.	Radiation Patterns	.6
7.	Antenna Dimensions	10

E-mail: awaveantenna@gmail.com

.



1. AWAVE eROU Ant2 Antenna

The AWAVE eROU Ant2 is an LTE Middle/High-Band antenna that operates in 1695-2690 MHz band. It provides high efficient radiation with good cost benefit. The antenna can

be mounted on a customer device by 4 screws and connected to the radio through a MCX connector.

2. Features

- Operates in 1695~2690 MHz bands
- Peak gain : 1.8~4.9dBi
- High efficiency
- MCX (Right angle) connector interface
- Mounted by 2 screws on a metal surface

Standard	LTE Middle/High-Band		
Frequency Range	1695~2690 MHz		
Peak Gain	1.8~4.9 dBi		
VSWR	2:1		
Feed Impedance	50Ω		
Power Handling	30 dBm		
Interface	MCX (Right angle)		
Antenna Dimensions	44.72 mm x 37.89 mm x 19.00 mm (L x W x T)		
Weight	10.83 g		
Temperature Range	Operating: -20° C to +60° C (-4° F to +140° F) Storage: -20° C to +60° C (-4° F to +140° F)		
Humidity Range	Operating: 10% to 85% non-condensing Storage: 5% to 90% non-condensing		

3. Specifications and Interface

E-mail : awaveantenna@gmail.com



4. Return Loss

10/12/2023 9:39:16 PM Tr1 S11 Log Mag 10.00dB/ ▶0.000dB [F2 M] 50.00 1 1.6950000GHz -9.1343dB 2.2000000GHz -19.333dB 2.3050000GHz -17.997dB 2.3600000GHz -16.737dB 2.6900000GHz -10.177dB 2 3 40.00 4 5 30.00 20.00 10.00 0.000 5 -10.00 4 1 4 4 -20.00 -30.00 -40.00 -50.00 1.25G 1.5G 12.75G 2G 242564 2.5G 🌦 75G 3G 3.25G 201 Start 1 GHz 10 kHz 0 dBm Stop 3.5 GHz Lin

E-mail: awaveantenna@gmail.com

The information contained in this document is for reference purpose only, and is subject to change or withdrawal without notice. The contents of this document may not be reproduced in whole or in part in any manner without agreement of AWAVE Corp.

. . .

5. Peak Gain and Efficiency

Frequency (MHz)	Peak Gain (dBi)	Efficiency (dB)	Efficiency (%)
1695	1.86	-1.43	71.9
1780	1.99	-1.22	75.6
1850	2.90	-1.53	70.4
1925	2.28	-1.54	70.1
1995	3.30	-0.62	86.6
2110	2.65	-1.48	71.1
2200	4.86	-0.32	92.9
2305	4.15	-1.30	74.2
2320	4.70	-0.84	82.4
2345	4.85	-0.81	82.9
2360	4.97	-0.73	84.5
2496	4.52	-1.39	72.6
2600	4.80	-1.81	65.9
2690	4.40	-2.22	60.0

E-mail: awaveantenna@gmail.com

The information contained in this document is for reference purpose only, and is subject to change or withdrawal without notice. The contents of this document may not be reproduced in whole or in part in any manner without agreement of AWAVE Corp.

. .

.



6. Radiation Patterns



E-mail: awaveantenna@gmail.com



E1-Plane

E-mail: awaveantenna@gmail.com



E2-Plane

E-mail: awaveantenna@gmail.com



H-Plane

E-mail: awaveantenna@gmail.com



7. Antenna Dimensions



E-mail: awaveantenna@gmail.com