



Report No.	G2115770	
Specifications	FCC Part 15.231, Certification	
Test Method	ANSI C63.4 1992	
Applicant address	10F, No. 403, Chung Shan Rd., Sec. 2, Chung Ho City, Taipei Hsien, Taiwan 235, R.O.C.	
Applicant	POWERTECH INDUSTRIAL CO., LTD.	
Items tested	Remote Control Appliance (Transmitter)	
Model No.	R1G0040R1A, R1G0450R2A (Sample # G21770)	
Results	Compliance (As detailed within this report)	
Date	11/05/2001 (month / day / year)	(Sample received)
	11/27/2001 (month / day / year)	(Test)
Prepared by		Project Engineer
Authorized by		General Manager (Frank Tsai)
Issue date	November 26, 2001	(month / day / year)
Modifications	None	
Tested by	Training Research Co., Ltd.	
Office at	2, Lane 194, Huan-Ho Street, Hsichih, Taipei Hsien 221, Taiwan	
Chamber at	2, Lane 194, Huan-Ho Street, Hsichih, Taipei Hsien 221, Taiwan	

Conditions of issue:

- (1) This test report shall not be reproduced except in full, without written approval of TRC. And the test result contained within this report only relate to the sample submitted for testing.
- (2) This report must not be used by the client to claim product endorsement by NVLAP or any agency of U.S. Government.

★ NVLAP LAB CODE: 200174-0
 ★ FCC ID: NHSPT-456

Table of Contents

Chapter 1 General

1.1 Introduction	3
1.2 Description of EUT	3
1.3 Description of Support Equipment	3
1.4 Test Procedure	4
1.5 Location of the Test Site	4
1.6 General Test Condition	4

Chapter 2 Transmitter Duty Cycle Measurements

2.1 Test Condition and Setup	5
2.2 List of Instruments	5
2.3 Test Configuration	6
2.4 Test Result	6

Chapter 3 Transmitter Bandwidth Measurements

3.1 Test Condition and Setup	9
3.2 Test Result	9

Chapter 4 Conducted Emissions Measurements

4.1 Conducted Emissions Measurements	11
4.2 Test Result	11

Chapter 5 Radiated Emissions Measurements

5.1 General Configuration	12
5.2 Test Condition and Setup	12
5.3 List of Test Instruments	14
5.4 Test Instruments Configuration	15
5.5 Test Result of Radiated Emissions	17

Table

Table 1 Open Field Radiated Emissions for 30MHz ~ 1GHz [HORIZONTAL]	17
Table 2 Open Field Radiated Emissions for 30MHz ~ 1GHz [VERTICAL]	18
Table 3 Open Field Radiated Emissions for 1GHz ~ 4GHz [HORIZONTAL]	19
Table 4 Open Field Radiated Emissions for 1GHz ~ 4GHz [VERTICAL]	20

Chapter 1 General

1.1 Introduction

The following measurement report is submitted on behalf of applicant in support of an International Periodic Radiator certification with Part 2 Subpart J and Part 15 Subpart A and C of the Commission's Rules and Regulations.

1.2 Description of EUT

EUT	:	Remote Control Appliance (Transmitter)
Model No.	:	R1G0040R1A, R1G0040R2A
FCC ID	:	NHSPT-456
Frequency Range	:	Operated in 314.925 MHz
Power Type	:	Powered by 12V/23A battery
Applicant	:	Powertech Industrial Co., Ltd. 10F, No. 403, Chung Shan Rd., Sec. 2, Chung Ho City, Taipei Hsien, Taiwan 235, R.O.C.

The fundamental frequency of transmitter emitted is due to a press on button of the EUT. **The emitting time of fundamental frequency is less than 5 seconds** pursuant to FCC Part 15.231(a). There are security codes for avoiding the possibility of duplicating codes in adjacent systems. The coding must be matching with the companion receiver.

While testing the EUT was adjusted at a position which transmit the maximum emission.

1.3 Description of Support Equipment

The EUT itself forms a system. No support equipment is required for its normal operation.

1.4 Test Procedure

All measurements contained in this report were performed according to the techniques described in measurement procedure of ANSI C63.4 1992 section 13

1.5 Location of the Test Site

The radiated emissions measurements required by the rules were performed on the **three-meter, Anechoic Chamber (Registration Number: 93906)** maintained by *Training Research Co., Ltd.* 1F, No. 2, Lane 194, Huan-Ho Street, Hsichih, Taipei Hsien 221, Taiwan, R.O.C. Complete description and measurement data have been placed on file with the commission. The conducted power line emissions tests and other test items were performed in a anechoic chamber also located at Training Research Co., Ltd.

No. 2, Lane 194, Huan-Ho Street, Hsichih, Taipei Hsien 221, Taiwan, R.O.C. *Training Research Co., Ltd.* is listed by the FCC as a facility available to do measurement work for others on a contract basis.

1.6 General Test Condition

The conditions under which the EUT operates were varied to determine their effect on the equipment's emission characteristics. The final configuration of the test system and the mode of operation used during these tests were chosen as that which produced highest emission levels. However, only those conditions that the EUT was considered likely encounter in normal use were investigated.

Chapter 2 Transmitter Duty Cycle Measurements

2.1 Test Condition and Setup

The duty cycle measurements were performed in a shielded enclosure. The EUT was placed on a wooded table which is 0.8 meters height and a bi-log periodic antenna was used distance about 3 meters for receiving. While testing EUT was set to transmit continuously. Various key configurations were also investigated to find the maximum duty cycle.

The resolution bandwidth and video bandwidth of the spectrum analyzer was all set to 1MHz to encompass all significant spectral components during the test. The analyzer operated in linear scale and zero span mode after tuning to the transmitter carrier frequency. The spectrum analyzer measured pulses width. The pulse width was determined by the difference between the two half voltage points on a pulse.

The duty cycle was determined by the following equation:

$$\text{Duty Cycle (\%)} = \frac{\text{Total on interval in a complete pulse train}}{\text{Length of a complete pulse train}} \times 100\%$$


To calculate the actual field intensity, the duty cycle correction factor in decibel is needed for later use and be obtained from following conversion:

$$\text{Duty Cycle Correction Factor (dB)} = 20 \times \log_{10} \text{Duty Cycle}$$

2.2 List of Test Instruments

Instrument Name	Model No.	Brand	Serial No.	Last time	Next time
EMI Receiver	8546A	H P	3520A00242	06/29/01	06/29/02
RF Filter Section	85460A	H P	3448A00217	06/29/01	06/29/02
Bi-log Antenna	CBL6141A	Schaffner	4206	03/09/01	03/09/02

2.3 Test Instruments Configuration



2.4 Test Result

Following is the test result, which produce maximum duty cycle:

Total on interval in a complete pulse train = 38.000 ms


Length of a complete pulse train = 31.500 ms


Duty Cycle (%) = $31.500 \text{ ms} / 38.000 \text{ ms} * 100\% = 0.823529$

Duty Cycle Correction Factor (dB) = $20 * \text{Log} (0.823529) = -1.686$

A plot is attached on the following page.

Picture of the Duty Cycle Test





Chapter 3 Transmitter Bandwidth Measurements, FCC Part 15.231(c)

3.1 Test Condition & Setup

The test setup used to transmitter bandwidth measurement was the same with duty cycle test, except there is no need for digital oscilloscope in the bandwidth test. For detailed description, please reference to section 2.1, 2.2 and 2.3 on page 6 and 7 of this report.

The resolution bandwidth of the spectrum analyzer was set to 100KHz, which is greater 5 percent of the maximum permitted bandwidth that required by the ANSI C63.4 section13. Bandwidth is determined at the point 20dB down from the modulator carrier. The maximum permitted bandwidth specified by the rule was 0.25% of the center frequency of the EUT, e.g. $314.925\text{MHz} * 0.25\% = 787.312\text{kHz}$. The detector function was set to peak and hold mode to clearly observe the components.


3.2 Test Result

Measured Transmitter Bandwidth: 475kHz

Permitted Maximum Bandwidth: 787.312kHz

A plot attached on the following page.

Plot of the Transmitter Bandwidth Measurement



Chapter 4 Conducted Emissions Measurements

4.1 Test Condition

The EUT operates solely by the battery. According to the rule of section 15.207(c). The EUT exempt to the power line conducted test.

4.1 Test Result

Test Result: N/A (not applicable)

Chapter 5 Radiated Emissions Measurements

5.1 General Configuration

Prior to open-field testing, the EUT was placed in a shielded enclosure and scanned at a close distance to determine its emission characteristics. The physical arrangement of the EUT was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude, directivity, and frequency. The exact system configuration that produced the highest emissions was noted so it could be reproduced later during the final tests. This was done to ensure that the final measurements would demonstrate the worst-case interference potential of the EUT.

5.2 Test Condition and Setup

Final radiation measurements were made on a three-meter, anechoic chamber. The EUT was placed on a nonconductive turntable that is 0.8 meters height, top surface 1.0 x 1.5 meter. The spectrum was examined from 30MHz to 18GHz order to check the whole spectrum that could be generated from the EUT. During the test, EUT was set to transmit continuously and the switch was positioned to yield the maximum duty cycle that had measured before radiated emissions test. The test battery was a totally brand-new one.

A nonconductive material surrounded the EUT to supporting the EUT for standing on three orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarizations.

Note: Setting the EUT to transmit continuously was just for the testing

The field strength below 1GHz was measured by Schaffner Bi-Log Periodic Antenna (model: CBL6141A) at 3 meter, and the EMCO Double Ridged Guide Antenna (model: 3115) was used in frequencies 1 ~ 18GHz at a distance of 1 meter. All test results were extrapolated equivalent signal at 3 meters utilizing an inverse linear distance extrapolated factor (20dB/decade).

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. No post-detector video filters were used in the test. The spectrum analyzer's 6dB bandwidth was set to 3 M and the spectrum was operated in the peak detection mode, for frequencies both below and up 1GHz. The peak levels were obtained by subtracting the duty cycle correction factor from the peak readings.

The following procedures were used to convert the emission levels measured in decibels referenced to 1 micro-volt (dBμV) into field intensity in micro-volts per meter (μV/m).

- (1) The actual field intensity in decibels referenced to 1 micro-volt per meter (dBμV/m) is determined by algebraically adding the measured reading in dBμV, the correction factor (dB), duty cycle correction factor (dB), and distance extrapolation factor (dB) at the appropriate frequency:

30 MHz ~ 1GHz:

Correction factor = Antenna factor + (Cable Loss – Amplitude gain)

Corrected Amplitude = Reading Amplitude – Correction Factors

(For example: 30MHz correction factor = 15.5 + (-15.26) = 0.24 dB/m)

Above 1GHz

Correction Factors = Antenna Factor + Cable Loss – Distance Extrapolation

Factor (9.54dB) – Amplifier Gain

Peak Amplitude + Correction Factor = Corrected

- (2) The field intensity in micro-volts per meter can then be determined by the following equation:

$$FI(\mu V / m) = 10^{FI (dB\mu V / m) / 20}$$

The FCC specified emission limits were calculated according the EUT operating frequency and obtained by following linear interpolation equations:

(a) For fundamental frequency:

$$f_{\text{EUT}} : \text{EUT Operating Frequency Emission Limit } (\mu\text{V/m})$$

$$= [f_{\text{EUT}}(\text{MHz}) - 260(\text{MHz})] \times \frac{12500(\mu\text{V/m}) - 3750(\mu\text{V/m})}{470(\text{MHz}) - 260(\text{MHz})} + 3750(\mu\text{V/m})$$

(b) For spurious frequencies:


$$f_{\text{EUT}} : \text{EUT Operating Frequency Emission Limit } (\mu\text{V/m})$$

$$= [f_{\text{EUT}}(\text{MHz}) - 260(\text{MHz})] \times \frac{1250(\mu\text{V/m}) - 375(\mu\text{V/m})}{470(\text{MHz}) - 260(\text{MHz})} + 375(\mu\text{V/m})$$

5.3 List of Test Instruments

Instrument Name	Model No.	Brand	Serial No.	Last time	Next time
EMI Receiver	8546A	H P	3520A00242	06/29/01	06/29/02
RF Filter Section	85460A	H P	3448A00217	06/29/01	06/29/02
Bi-log Antenna	CBL6141A	Schaffner	4206	03/09/01	03/09/02
Switch/Control Unit	3488A	HP	N/A	11/20/00	11/20/01
(> 30MHz)					
Auto Switch Box	ASB-01	TRC	9904-01	11/20/00	11/20/01
(> 30MHz)					
Spectrum Analyzer	8564E	HP	US36433002	08/01/01	08/01/02
Microwave Preamplifier	83051A	HP	3232A00347	08/01/01	08/01/02
Horn Antenna	3115	EMCO	9704 – 5178	08/01/01	08/01/02
Anechoic Chamber (cable calibrated together)				05/20/01	05/20/02

5.4 Test Instruments Configuration



Radiated Test Placement: (Photographs)



5.5 Test Result of Radiated Emissions

The highest peak values of radiated emissions from the EUT at various antenna heights, antenna polarization, EUT orientation, etc. are recorded on the following.

Test Conditions: Testing Room: Temperature: 26 ° C Humidity: 73 % RH

Table 1 Open Field Radiated Emissions for 30MHz to 1GHz [Horizontal, X-axis]

Radiated Emission				Correction Factors	Corrected Amplitude	FCC Class B (3 M)	
Frequency (MHz)	Amplitude (dBμV/m)	Ant. H. (m)	Table (°)	(dB)	(dBμV/m)	Limit (dBμV/m)	Margin (dB)
314.925	56.72	1.00	105	-17.29	74.01	75.61	-1.60
629.850	30.13	1.00	46	-23.41	53.54	55.61	-2.07
944.775	23.13	1.00	70	-28.48	51.61	55.61	-4.00

Note:

1. Margin = Amplitude – limit, *if margin is minus means under limit.*
2. Corrected Amplitude = Reading Amplitude – Correction Factors
3. Correction factor = Antenna factor + (Cable Loss – Amplitude gain)

Table 2 Open Field Radiated Emissions for 30MHz to 1GHz [Vertical, X-axis]

Radiated Emission				Correction Factors	Corrected Amplitude	FCC Class B (3 M)	
Frequency (MHz)	Amplitude (dBμV/m)	Ant. H. (m)	Table (°)	(dB)	(dBμV/m)	Limit (dBμV/m)	Margin (dB)
314.925	38.38	1.00	141	-17.42	55.80	75.61	-19.81
629.850	20.08	1.00	8	-23.64	43.72	55.61	-11.89
944.775	15.30	2.44	49	-30.01	45.31	55.61	-10.30

Note:

1. Margin = Amplitude – limit, *if margin is minus means under limit.*
2. Corrected Amplitude = Reading Amplitude – Correction Factors
3. Correction factor = Antenna factor + (Cable Loss – Amplitude gain)

Table 3 Open Field Radiated Emissions for 1GHz to 4GHz [Horizontal, Y-axis]

Radiated Emission				Correction Factors	Corrected Amplitude (dBμV/m)	FCC Class B (3 M)	
Frequency (GHz)	Amplitude (dBμV/m)	Ant. H. (m)	Table (°)	(dB)		Limit (dBμV/m)	Margin (dB)
3.149	44.89	1.00	265	-5.64	39.25	55.61	-16.36

Note:

1. Margin = Corrected – Limit.
2. Peak Amplitude + Correction Factor = Corrected
3. The “ * “ means restricted bands

Table 4 Open Field Radiated Emissions For 1GHz to 4GHz [Vertical, Z-axis]

Radiated Emission				Correction Factors	Corrected Amplitude (dBμV/m)	FCC Class B (3 M)	
Frequency (GHz)	Amplitude (dBμV/m)	Ant. H. (m)	Table (°)	(dB)		Limit (dBμV/m)	Margin (dB)
3.149	44.89	1.00	77	-5.64	39.25	55.61	-16.36

Note:

1. Margin = Corrected – Limit.
2. Peak Amplitude + Correction Factor + Duty Cycle = Corrected
3. The “ * “ means restricted bands