


RF Exposure Evaluation Report

APPLICANT : Sony Mobile Communications Inc.
EQUIPMENT : Bluetooth device
BRAND NAME : SONY
FCC ID : PY7-87507R
STANDARD : 47 CFR Part 2.1093
FCC KDB 447498 D01 v06

We, SPORTON INTERNATIONAL INC., would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1093, and pass the limit. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Eric Huang / Manager



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1.	Administration Data	3
2.	General Information	4
2.1	Description of Device Under Test (DUT)	4
3.	Maximum RF output power among production units	4
4.	RF Exposure Evaluation	5

Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA730107	Rev. 01	Initial issue of report	Apr. 13, 2017

**1. Administration Data**

Testing Laboratory	
Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978

Applicant	
Company Name	Sony Mobile Communications Inc.
Address	4-12-3 Higashi-shinagawa, Shinagawa-ku, Tokyo, 140-0002, Japan

Manufacturer	
Company Name	Sony Mobile Communications Inc.
Address	4-12-3 Higashi-shinagawa, Shinagawa-ku, Tokyo, 140-0002, Japan

2. General Information

2.1 Description of Device Under Test (DUT)

Product Feature & Specification	
DUT Type	Bluetooth device
Brand Name	SONY
FCC ID	PY7-87507R
Wireless Technology and Frequency Range	Bluetooth: 2402 MHz ~ 2480 MHz
Mode	Bluetooth BR/EDR/LE
Antenna Type	FPCB Pattern Antenna
HW Version	A
SW Version	v1.0.1
DUT Stage	Identical Prototype

Remark: The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

3. Maximum RF output power among production units

Band / Mode	Average Power (dBm)			
	BR / EDR			LE
	1M	2M	3M	GFSK
Bluetooth	5	1	1	3



4. RF Exposure Evaluation

Bluetooth Max Power (dBm)	mW	Separation Distance (mm)	Frequency (GHz)	Exclusion Thresholds
5	3	5	2.48	0.94

Note:

1. Per KDB 447498 D01v06 the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Conclusion: Per KDB 447498 D01v06, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 0.94 which is ≤ 3 , SAR testing is not required.