### **PCTEST**



7185 Oakland Mills Road, Columbia, MD 21046 USA Tel. 410.290.6652 / Fax 410.290.6654 http://www.pctest.com



# **HEARING AID COMPATIBILITY**

**Applicant Name:** 

Samsung Electronics Co., Ltd. 129, Samsung-ro, Maetan dong, Yeongtong-gu, Suwon-si Gyeonggi-do 16677, Korea **Date of Testing:** 

10/19/2020 - 11/14/2020 Test Site/Location: PCTEST, Columbia, MD, USA Test Report Serial No.: 1M2009230152-21-R2.A3L

**Date of Issue:** 12/10/2020

FCC ID: A3LSMG998U

APPLICANT: SAMSUNG ELECTRONICS CO., LTD.

Scope of Test: Audio Band Magnetic Testing (T-Coil)

Application Type: Certification
FCC Rule Part(s): CFR §20.19(b)
HAC Standard: ANSI C63.19-2011

CTIA Test Plan for Hearing Aid Compatibility Rev 3.1.1, May 2017

285076 D01 HAC Guidance v05

285076 D02 T-Coil testing for CMRS IP v03

DUT Type:Portable HandsetModel:SM-G998UAdditional Model(s):SM-G998U1

**Test Device Serial No.:** Pre-Production Sample [S/N: 0769M]

C63.19-2011 HAC Category: T3 (SIGNAL TO NOISE CATEGORY)

Note: This revised Test Report (S/N: 1M2009230152-21-R2.A3L) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be hearing-aid compatible under the above rated category, specified in ANSI/IEEE Std. C63.19-2011 and has been tested in accordance with the specified measurement procedures. Test results reported herein relate only to the item(s) tested. Hearing-Aid Compatibility is based on the assumption that all production units will be designed electrically identical to the device tested in this report. North American Bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.





Authorized Test Lab





FCC ID: A3LSMG998U	PCTEST: Houd to be part of @ consumer	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 1 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 1 of 97

© 2020 PCTEST REV 3.4 8/18/20

# TABLE OF CONTENTS

1.	INTRODUCTION	3
2.	DUT DESCRIPTION	4
3.	ANSI C63.19-2011 PERFORMANCE CATEGORIES	6
4.	METHOD OF MEASUREMENT	8
5.	VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION	18
6.	VOWIFI TEST SYSTEM SETUP AND DUT CONFIGURATION	22
7.	OTT VOIP TEST SYSTEM AND DUT CONFIGURATION	26
8.	FCC 3G MEASUREMENTS	34
9.	T-COIL TEST SUMMARY	36
10.	MEASUREMENT UNCERTAINTY	50
11.	EQUIPMENT LIST	51
12.	TEST DATA	52
13.	CALIBRATION CERTIFICATES	85
14.	CONCLUSION	92
15.	REFERENCES	93
16.	TEST SETUP PHOTOGRAPHS	95

FCC ID: A3LSMG998U	PCTEST Thought to be port of the reserver	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 0 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 2 of 97

#### 1. INTRODUCTION

On July 10, 2003, the Federal Communications Commission (FCC) adopted new rules requiring wireless manufacturers and service providers to provide digital wireless phones that are compatible with hearing aids. The FCC has modified the exemption for wireless phones under the Hearing Aid Compatibility Act of 1998 (HAC Act) in WT Docket 01-309 RM-86581 to extend the benefits of wireless telecommunications to individuals with hearing disabilities. These benefits encompass business, social and emergency communications, which increase the value of the wireless network for everyone. An estimated more than 10% of the population in the United States show signs of hearing impairment and of that fraction, almost 80% use hearing aids. Approximately 500 million people worldwide and 30 million people in the United States suffer from hearing loss.

## Compatibility Tests Involved:

The standard calls for wireless communications devices to be measured for:

- RF Electric-field emissions
- T-coil mode, magnetic-signal strength in the audio band
- T-coil mode, magnetic-signal frequency response through the audio band
- T-coil mode, magnetic-signal and noise articulation index

The hearing aid must be measured for:

- RF immunity in microphone mode
- RF immunity in T-coil mode

In the following tests and results, this report includes the evaluation for a wireless communications device.



Figure 1-1 Hearing Aid in-vitu

<sup>1</sup> FCC Rule & Order, WT Docket 01-309 RM-8658

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 3 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 3 of 97

© 2020 PCTEST

# 2. DUT DESCRIPTION



FCC ID: A3LSMG998U

Applicant: Samsung Electronics Co., Ltd.

129, Samsung-ro, Maetan dong,

Yeongtong-gu, Suwon-si Gyeonggi-do 16677, Korea

Model(s): SM-G998U
Additional Model(s): SM-G998U1
Serial Number: 0769M
HW Version: REV1.0

SW Version: G998USQU0ATK9
Antenna: Internal Antenna
DUT Type: Portable Handset

### I. LTE Band Selection

This device supports the following pairs of LTE bands with similar frequencies: LTE B4 & B66 and B38 & B41. Each pair of LTE bands has the same target power and shares the same transmission path. Since the supported frequency spans for the smaller LTE bands are completely covered by the larger LTE bands, only the larger LTE bands (LTE B66 and B41) were evaluated for hearing-aid compliance. LTE B5 and B2 are LTE anchor bands for dual connectivity (EN-DC) scenarios between LTE and NR so they were additionally evaluated as independent LTE bands.

### II. NR Band Selection

This device supports the following pair of NR bands with similar frequencies: NR n25 & n2. This pair of NR bands has the same target power and shares the same transmission path. Since the supported frequency span for the smaller NR band is completely covered by the larger NR band, only the larger NR band (n25) was evaluated for hearing-aid compliance.

FCC ID: A3LSMG998U	PCTEST Total to be part of Security	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 4 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 4 01 97

### Table 2-1 A3LSMG998U HAC Air Interfaces

			AJL	SMG998U HAC Air Interfa	1	I
Air-Interface	Band (MHz)	Type Transport	HAC Tested	Simultaneous But Not Tested	Name of Voice Service	Audio Codec Evaluated
CDMA	835 1900	vo	Yes	Yes: WIFI or BT	CMRS Voice <sup>1</sup>	EVRC
	EvDO	VD	Yes	Yes: WIFI or BT	Google Duo <sup>2</sup>	OPUS
	850					
GSM	1900	vo	Yes	Yes: WIFI or BT	CMRS Voice <sup>1</sup>	EFR
	GPRS/EDGE	VD	Yes	Yes: WIFI or BT	Google Duo <sup>2</sup>	OPUS
	850				9	
	1700	VD	Yes	Yes: WIFI or BT	CMRS Voice <sup>1</sup>	NB AMR
UMTS	1900					
	HSPA	VD	Yes	Yes: WIFI or BT	Google Duo²	OPUS
	680 (B71)		Yes³			
	700 (B12)					
	780 (B13)					
	790 (B14)					
	850 (B5)					
()	850 (B26)					Volte: NB AMR, WB AMR, EVS
LTE (FDD)	1700 (B4)	VD	Yes	Yes: WIFI or BT	VoLTE <sup>1</sup> , Google Duo <sup>2</sup>	Google Duo: OPUS
	1700 (B66)					
	1900 (B2)					
	1900 (B25)					
	2300 (B30)					
	2500 (B7)					
	2600 (B38)					
LTE (TDD)	2600 (B41)	VD	Yes	Yes: WIFI or BT	VoLTE¹, Google Duo²	Volte: NB AMR, WB AMR, EVS Google Duo: OPUS
	3600 (B48)					Google Duo. OPO3
	680 (n71)		Yes <sup>3,4</sup>			
	700 (n12)					
	850 (n5)					
NR (FDD)	1700 (n66)	VD	Yes <sup>4</sup>	Yes: WIFI or BT	Google Duo²	OPUS
	1900 (n2)		res			
	1900 (n25)					
	2300 (n30)					
	2600 (n41)		Yes <sup>4</sup>			
NR (TDD)	3750 (n77)	VD	163	Yes: WIFI or BT	Google Duo <sup>2</sup>	OPUS
(.55)	28000 (n261)		No <sup>5</sup>		Google Buo	0.05
	39000 (n260)		110			
	2450					
	5200 (U-NII 1)					
	5300 (U-NII 2A)		Yes			
	5500 (U-NII 2C)					VoWIFI: NB AMR, WB AMR, EVS
WIFI	5800 (U-NII 3)	VD		Yes: CDMA, GSM, UMTS, LTE, or NR	VoWIFI <sup>2</sup> , Google Duo <sup>2</sup>	Google Duo: OPUS
	6175 (U-NII 5)					
	6475 (U-NII 6)		No <sup>6</sup>			
	6700 (U-NII 7)					
BT	7000 (U-NII 8) 2450	DT	No	Yes: CDMA, GSM, UMTS, LTE, or NR	N/A	N/A
Type Transport		51	Notes:	. ES. CONTA, CONT., CIVITO, ETE, OF WA	IV/A	IV/A
VO = Voice Onl	у		1. Reference l	evel in accordance with 7.4.2.1 of ANSI C63.19-20		tation.
	ta - Not intended for			evel is -20dBm0 in accordance with FCC KDB 285		tionally tasted as
AD = CIVIK2 and	VD = CMRS and/or IP Voice over Data Transport  3. LTE B71 and NR n71, while outside the scope of ANSI C63.19 and FCC HAC regulations, were additionally tested according existing HAC procedures with currently available test equipment.				tionally tested according to the	
4. NR was evaluated using an interim procedure outlined in Section 7.II.5.						
	5. n260 and n261 were not evaluated due to equipment limitations and being outside the scope of ANSI C63.19 and FCC HAC				NSI C63.19 and FCC HAC	
	regulations.  6. WIFI U-NII bands 5 through 8 were not evaluated due to equipment limitations and being outside the scope of ANSI C63.19				the scope of ANSI C63 19 and	
			FCC HAC regu		,	

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 5 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 5 of 97

#### ANSI C63.19-2011 PERFORMANCE CATEGORIES 3.

#### I. MAGNETIC COUPLING

### **Axial and Radial Field Intensity**

All orientations of the magnetic field, in the axial and radial position along the measurement plane shall be  $\geq$  -18 dB(A/m) at 1 kHz in a 1/3 octave band filter per §8.3.1.

## Frequency Response

The frequency response of the axial component of the magnetic field shall follow the response curve specified in EIA RS-504-1983, over the frequency range 300 Hz - 3000 Hz per §8.3.2.




Figure 3-1 Magnetic field frequency response for Wireless Devices with an axial field ≤-15 dB(A/m) at 1 kHz




Figure 3-2 Magnetic Field frequency response for wireless devices with an axial field that exceeds -15 dB(A/m) at 1 kHz

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 6 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage o oi 97

© 2020 PCTEST REV 3.4.M

# **Signal Quality**

The table below provides the signal quality requirement for the intended audio magnetic signal from a wireless device. Only the RF immunity of the hearing aid is measured in T-coil mode. It is assumed that a hearing aid can have no immunity to an interference signal in the audio band, which is the intended reception band for this mode. The only criterion that can be measured is the RF immunity in T-coil mode. This is measured using the same procedure as the audio coupling mode at the same levels.

The signal quality of the axial and radial components of the magnetic field was used to determine the T-coil mode category.

Catagory	Telephone RF Parameters		
Category	Wireless Device Signal Quality [(Signal + Noise)-to-noise ratio in dB]		
T1	0 to 10 dB		
T2	10 to 20 dB		
Т3	20 to 30 dB		
T4	> 30 dB		
Table 3-1  Magnetic Coupling Parameters			

Note: The FCC limit for SNNR is 20dB and the test data margins will indicate a margin from the FCC limit for compliance.

FCC ID: A3LSMG998U	PCTEST:	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 7 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 7 of 97

# 4. METHOD OF MEASUREMENT

# I. Test Setup

The equipment was connected as shown in an acoustic/RF hemi-anechoic chamber:




Figure 4-1
Validation Setup with Helmholtz Coil




Figure 4-2 T-Coil Test Setup

FCC ID: A3LSMG998U	PCTEST Thought to be port of the received	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 8 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage o oi 91

# II. Scanning Mechanism

Manufacturer: TEM

Accuracy: ± 0.83 cm/meter

Minimum Step Size: 0.1 mm

Maximum speed 6.1 cm/sec

Line Voltage: 115 VAC

Line Frequency: 60 Hz

Material Composite: Delrin (Acetal)

Data Control: Parallel Port

Dynamic Range (X-Y-Z): 45 x 31.75 x 47 cm

Dimensions: 36" x 25" x 38" Operating Area: 36" x 49" x 55"

Reflections: < -20 dB (in anechoic chamber)




Figure 4-3 RF Near-Field Scanner

# III. 3GPP2 Normal Test Signal (Speech)

Manufacturer: 3GPP2 (TIA 1042 §3.3.1)

Modified-IRS weighted, multi-talker speech signal, 4 Male and 4

Stimulus Type: Female speakers (alternating)

Single Sample Duration: 51.62 seconds

Activity Level: 77.4%





Figure 4-4
Temporal Characteristic of Normal Test Signal

FCC ID: A3LSMG998U	PCTEST Thought to be post of the received	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 0 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 9 of 97



ABM2 Measurement Block Diagram:



Figure 4-5 Magnetic Measurement Processing Steps

## IV. Test Procedure

- 1. Ambient Noise Check per C63.19 §7.3.1
  - Ambient interference was monitored using a Real-Time Analyzer between 100-10,000 Hz with 1/3 octave filtering.
  - b. "A-weighting" and Half-Band Integration was applied to the measurements.
  - c. Since this measurement was measured in the same method as ABM2 measurements, this level was verified to be more than 10 dB below the lowest measurement signal (which is the highest ABM2 measurement for a T4 WD). Therefore the maximum noise level for a T4 WD with an ABM1 = -18 dBA/m is:

- 2. Measurement System Validation(See Figure 4-1)
  - a. The measurement system including the probe, pre-amplifier and acquisition system were validated as an entire system to ensure the reliability of test measurements.
  - b. ABM1 Validation The magnetic field at the center of the Helmholtz coil is given by the equation (per C63.19 Annex D.10.1):

$$H_c = \frac{NI}{r\sqrt{1.25^3}} = \frac{N(\frac{V}{R})}{r\sqrt{1.25^3}}$$

Where H<sub>c</sub> = magnetic field strength in amperes per meter N = number of turns per coil

For the Helmholtz Coil, N=20; r=0.08m; R=10.2Ω and using V=18mV:

$$H_c = \frac{20 \cdot (\frac{0.018}{10.2})}{0.08 \cdot \sqrt{1.25^3}} = 0.316 A/m \approx -10 dB (A/m)$$

Therefore a pure tone of 1kHz was applied into the coils such that 18mV was observed across the resistor. The voltmeter used for measurement was verified to be capable of measurements in the audio band range. This theoretically generates an expected field of  $-10 \, \text{dB}(A/m)$  in the center of the Helmholtz coil which was used to validate the probe measurement at  $-10 \, \text{dB}(A/m)$ . This was verified to be within  $\pm 0.5 \, \text{dB}$  of the  $-10 \, \text{dB}(A/m)$  value (see Page 48).

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 10 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 10 01 97

# c. Frequency Response Validation

The frequency response through the Helmholtz Coil was verified to be within 0.5 dB relative to 1kHz, between 300 – 3000 Hz using the Normal signal as shown below:



Figure 4-6 Frequency Response Validation

### d. ABM2 Measurement Validation

WD noise measurements are filtered with A-weighting and Half-Band Integration over a frequency range of 100Hz – 10kHz to process ABM2 measurements. Below is the verification of the system processing A-weighting and Half-Band integration between system input to output within 0.5 dB of the theoretical result:

Table 4-1
ABM2 Frequency Response Validation

	HBI, A -	HBI, A -	
f (Hz)	Measured	Theoretical	dB Var.
	(dB re 1kHz)	(dB re 1kHz)	
100	-16.180	-16.170	-0.010
125	-13.257	-13.250	-0.007
160	-10.347	-10.340	-0.007
200	-8.017	-8.010	-0.007
250	-5.925	-5.920	-0.005
315	-4.045	-4.040	-0.005
400	-2.405	-2.400	-0.005
500	-1.212	-1.210	-0.002
630	-0.349	-0.350	0.001
800	0.071	0.070	0.001
1000	0.000	0.000	0.000
1250	-0.503	-0.500	-0.003
1600	-1.513	-1.510	-0.003
2000	-2.778	-2.780	0.002
2500	-4.316	-4.320	0.004
3150	-6.166	-6.170	0.004
4000	-8.322	-8.330	0.008
5000	-10.573	-10.590	0.017
6300	-13.178	-13.200	0.022
8000	-16.241	-16.270	0.029
10000	-19.495	-19.520	0.025

FCC ID: A3LSMG998U	PCTEST Thought to be post of the received	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 11 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 11 of 97







Figure 4-7
ABM2 Frequency Response Validation

The ABM2 result is a power sum from 100Hz to 10kHz with half-band integration and A-weighting. To verify the power sum measurement, a power sum over the full band was measured and verified to track with the source level (See Figure 4-8). Therefore the setup in this step was used to verify the power sum post-processing for ABM2 measurements. See below block diagram:



The power summed output results for a known input were compared to the multi-meter results to verify any deviation in the post-processing implemented with the power-sum.

Table 4-2
ABM2 Power Sum Validation

WN Input (dBV)	Power Sum (dBV)	Multimeter-Full (dBV)	Dev (dB)
-60	-60.36	-60.2	0.16
-50	-50.19	-50.13	0.06
-40	-40.14	-40.03	0.11
-30	-30.13	-30.01	0.12
-20	-20.12	-20	0.12
-10	-10.14	-10	0.14

FCC ID: A3LSMG998U	PCTEST:	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 10 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 12 of 97

© 2020 PCTEST REV 3.4.M 8/18/2020





Figure 4-9 **ABM2 Power Sum Validation** 

### 3. Measurement Test Setup

- a. Fine scan above the WD (TEM)
  - i. A multitone signal was applied to the handset such that the phone acoustic output was stable within 1dB over the probe settling time and with the acoustic output level at the C63.19 specified levels (below). The measurement step size was in 2 mm increments at a distance of 10 mm between the surface of the wireless device as shown below (note that in Figure 4-11, the grid is not to scale but merely a graphical representation of the coordinate system in use):



- ii. After scanning, the planar field maximum point was determined. The position of the probe was moved to this location to setup the test using the SoundCheck system.
- iii. These steps were repeated for all T-coil orientations (axial and radial) per Figure 4-13 after a T-coil orientation was fully measured with the SoundCheck system.
- b. Speech Signal Setup to Base Station Simulator
  - i. C63.19 Table 7-1 states audio reference input levels for various technologies:

Standard	Technology	Input Level (dBm0)
TIA/EIA/IS-2000	CDMA	-18
J-STD-007	GSM (217)	-16
T1/T1P1/3GPP	UMTS (WCDMA)	-16

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 12 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 13 of 97

- ii. See Section 5 and 6 for more information regarding CMW500 audio level settings for Voice Over LTE (VoLTE), and Voice Over WIFI (VoWIFI) testing.
- iii. See Section 7 for more information regarding audio level settings for Over-The-Top (OTT) Voice Over IP (VoIP) Testing.
- c. Real-Time Analyzer (RTA)
  - i. The Real-Time Analyzer was configured to analyze measurements using 1/3 Octave band weighted filtering.
- d. WD Radio Configuration Selection
  - i. The device was chosen to be tested in the worst-case ABM2 condition (See Section 8 for more information regarding worst-case configurations for CDMA and UMTS. LTE configuration information can be found in Section 5 and 7. NR configuration information can be found in Section 7. WIFI configuration information can be found in Section 6 and 7.)
  - ii. Supported GSM vocoders were investigated for the worst-case ABM2 condition. GSM-EFR was deemed the worst-case condition for the GSM air interface.
- 4. Signal Quality Data Analysis
  - a. Narrow-band Magnetic Intensity
    - i. The standard specifies a 1kHz 1/3 octave band minimum field intensity for a sine tone. The ABM1 measurements were evaluated at 1kHz with 1/3 octave band filtering over an averaged period of 10 seconds.
  - b. Frequency Response
    - i. The appropriate frequency response curve was measured to curves in Figure 3-1 or Figure 3-2 between 300 3000 Hz using digital linear averaging (limit lines chosen according to measurement found in step 4a). A linear average over 3x the length of the artificial voice signal (3x sampling) was performed. A 10 second delay was configured in the measurement process of the stimulus to ensure handset vocoder latency effects and echo cancellation devices (if any) were appropriately stabilized during measurements.
    - ii. The appropriate post-processing was applied according to the system processing chain illustrated in Figure 4-6. All R10 frequencies were plotted with respect to 0dB at 1kHz value and aligned with respect to the EIA-504 mask.
    - iii. The margin is represented by the closest measured data point on the curve to the EIA-504 limit lines, in dB.
  - c. Signal Quality Index
    - i. Ensuring the WD was at maximum RF power, maximum volume, backlight off, display on, maximum contrast setting, keypad lights on (when possible) with no audio signal through the vocoder, the WD was measured over at least 100 Hz 10,000 Hz, maximized over 5 seconds with a 50ms sample time for the ABM2 measurement (5 second time period is used in noise measurements under standards such as IEEE 269, etc.).
    - ii. After applying half-band integration and A-weighting to the result, a power sum was applied over each 1/3 octave bandwidth frequency for an ABM2 value.
    - iii. This result was subtracted from the ABM1 result in step 4.a, to obtain the Signal Quality.

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 14 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 14 01 97

#### V. **Test Setup**




Figure 4-12 **Audio Magnetic Field Test Setup** 

Environmental conditions such as temperature and relative humidity are monitored to ensure there are no impacts on system specifications. Proper voltage and power line frequency conditions are maintained with three phase power sources. Environmental noise and reflections are monitored through system checks.

#### VI. **Deviation from C63.19 Test Procedure**

Non-conducted RF connection due to inaccessible RF ports.

# VII. Air Interface Technologies Tested

All air interfaces which support voice capabilities over a managed CMRS or pre-installed OTT VoIP applications were tested for T-coil unless otherwise noted. See Table 2-1 for more details regarding which modes were tested.

FCC ID: A3LSMG998U	PCTEST* Proof to be part of ® secured	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 15 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 15 of 97

## VIII. Wireless Device Channels and Frequencies

### 1. 2G/3G Modes

The frequencies listed in the table below are those that lie in the center of the bands used for cellular telephony. Low, middle and high channels were tested in each band for FCC compliance evaluation to ensure the maximum emission is captured across the entire band. Only middle channels were evaluated for data modes.

Table 4-3
Center Channels and Frequencies

Test frequencies & associated channels			
rest frequencies & associated t	inamers		
Channel	Frequency (MHz)		
Secondary Cellular 8	20		
564 (CDMA)	820.10		
Cellular 850			
384 (CDMA)	836.52		
190 (GSM)	836.60		
4183 (UMTS)	836.60		
AWS 1750			
1412 (UMTS)	1730.40		
PCS 1900			
600 (CDMA)	1880		
661 (GSM)	1880		
9400 (UMTS)	1880		

### 2. 4G (LTE) Modes

The middle channel for every band and bandwidth combination was tested for each probe orientation. The band and bandwidth combination from each probe orientation resulting in the worst-case SNNR was additionally tested using low and high channels for that band and bandwidth combination. Low-mid and mid-high channels are additionally tested for LTE TDD. The middle channel and supported bandwidths from the worst-case band according to Tables 7-6 & 7-7 were additionally evaluated with OTT VoIP for each probe orientation. See Tables 9-5 to 9-18 and Tables 9-27 & 9-28 for LTE bandwidths and channels.

### 3. 5G (NR)

The middle channel and supported bandwidths from the worst-case NR FDD band and NR TDD band according to Tables 7-12 & 7-13 was evaluated with OTT VoIP for each probe orientation. The band and bandwidth combination from each probe orientation resulting in the worst-case SNNR was additionally tested using low and high channels for that band and bandwidth combination. Low-mid and mid-high channels are additionally tested for NR TDD. See Tables 9-29 and 9-31 for NR bandwidths and channels.

#### 4. WIFI

The middle channel for each IEEE 802.11 standard was tested for each probe orientation. The 2.4GHz IEEE 802.11 standard from each probe orientation resulting in the worst-case SNNR was additionally tested using low and high channels. The 5GHz IEEE 802.11 standard from each probe orientation resulting in the worst-case SNNR was additionally tested on higher U-NII bands as well as applicable low and high channels. See Tables 9-19 to 9-23 and Tables 9-33 to 9-37 for WIFI standards and channels.

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 16 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 10 01 97

#### IX. **Test Flow**

The flow diagram below was followed (From C63.19):




Figure 4-13 **C63.19 T-Coil Signal Test Process** 

FCC ID: A3LSMG998U	PCTEST Thought to be port of the received	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 17 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 17 01 97

© 2020 PCTEST **REV 3.4.M** 

# 5. VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION

# I. Test System Setup for VoLTE over IMS T-coil Testing

## 1. Equipment Setup

The general test setup used for VoLTE over IMS is shown below. The callbox used when performing VoLTE over IMS T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.




Figure 5-1
Test Setup for VoLTE over IMS T-Coil Measurements

## 2. Audio Level Settings

According to the July 2012 interpretations by the C63 Committee regarding the appropriate audio levels to be used for VoLTE over IMS T-coil testing, -16dBm0 shall be used for the normal speech input level\*. The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -16dBm0 speech input level to the DUT for the VoLTE over IMS connection.

\* http://c63.org/documents/misc/posting/new\_interpretations.htm

FCC ID: A3LSMG998U	PCTEST:	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 10 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 18 of 97

© 2020 PCTEST REV 3.4.M

# II. DUT Configuration for VoLTE over IMS T-coil Testing

# 1. Radio Configuration

An investigation was performed to determine the modulation and RB configuration to be used for testing. The effects of modulation and RB configuration were found to be independent of band and bandwidth; therefore, only one band and bandwidth were used for this investigation. 16QAM, 1RB, 99%RB offset was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different radio configurations:

Table 5-1
VoLTE over IMS SNNR by Radio Configuration

	VOLIL OVER INIO SHARK BY Radio Configuration										
Band	Frequency	Channel	Bandwidth	Modulation	RB Size	RB Offset	ABM1	ABM2	SNNR		
	[MHz]		[MHz]		112 0.20	112 011001	[dB(A/m)]	[dB(A/m)]	[dB]		
66	1745.0	132322	20	QPSK	1	0	0.94	-54.92	55.86		
66	1745.0	132322	20	QPSK	1	50	0.92	-54.88	55.80		
66	1745.0	132322	20	QPSK	1	99	0.93	-54.90	55.83		
66	1745.0	132322	20	QPSK	50	0	0.91	-55.07	55.98		
66	1745.0	132322	20	QPSK	50	25	0.90	-54.94	55.84		
66	1745.0	132322	20	QPSK	50	50	0.88	-54.97	55.85		
66	1745.0	132322	20	QPSK	100	0	0.89	-55.04	55.93		
66	1745.0	132322	20	16QAM	1	0	0.88	-54.30	55.18		
66	1745.0	132322	20	16QAM	1	50	0.89	-54.24	55.13		
66	1745.0	132322	20	16QAM	1	99	0.87	-54.12	54.99		
66	1745.0	132322	20	16QAM	50	0	0.85	-54.87	55.72		
66	1745.0	132322	20	16QAM	50	25	0.86	-54.88	55.74		
66	1745.0	132322	20	16QAM	50	50	0.85	-54.97	55.82		
66	1745.0	132322	20	16QAM	100	0	0.85	-54.83	55.68		
66	1745.0	132322	20	64QAM	1	0	1.13	-54.33	55.46		
66	1745.0	132322	20	64QAM	1	50	1.04	-54.23	55.27		
66	1745.0	132322	20	64QAM	1	99	1.02	-54.55	55.57		
66	1745.0	132322	20	64QAM	50	0	1.02	-55.04	56.06		
66	1745.0	132322	20	64QAM	50	25	1.03	-54.91	55.94		
66	1745.0	132322	20	64QAM	50	50	1.02	-54.84	55.86		
66	1745.0	132322	20	64QAM	100	0	1.02	-54.80	55.82		
66	1745.0	132322	20	256QAM	1	0	1.03	-54.66	55.69		
66	1745.0	132322	20	256QAM	1	50	1.04	-54.70	55.74		
66	1745.0	132322	20	256QAM	1	99	1.01	-54.74	55.75		
66	1745.0	132322	20	256QAM	50	0	1.03	-54.89	55.92		
66	1745.0	132322	20	256QAM	50	25	1.02	-54.96	55.98		
66	1745.0	132322	20	256QAM	50	50	1.02	-54.88	55.90		
66	1745.0	132322	20	256QAM	100	0	1.03	-54.92	55.95		

### 2. Codec Configuration

An investigation was performed to determine the audio codec configuration to be used for testing. The effects of codec configuration were found to be independent of radio configuration; therefore, only one radio configuration was used for this investigation. The EVS Primary NB 24.4kbps setting was used for the audio codec on the CMW500 for VoLTE over IMS T-coil testing. See below table for comparisons between different codecs and codec data rates:

Table 5-2
AMR Codec Investigation – VoLTE over IMS

Codec Setting:	WB AMR 23.85kbps	WB AMR 6.60kbps	NB AMR 12.2kbps	NB AMR 4.75kbps	Orientation	Band / BW	Channel
ABM1 (dBA/m)	5.67	4.66	1.60	1.36			132322
ABM2 (dBA/m)	-54.40	-54.12	-53.95	-54.29	Axial	Band 66 20MHz	
Frequency Response	Pass	Pass	Pass	Pass	Axiai		
S+N/N (dB)	60.07	58.78	55.55	55.65			

FCC ID: A3LSMG998U	PCTEST*	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 10 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 19 of 97

Table 5-3
EVS Codec Investigation - VoLTE over IMS

Codec Setting:	EVS Primary SWB 128kbps	EVS Primary SWB 9.6kbps	EVS Primary WB 128kbps	EVS Primary WB 5.9kbps	EVS Primary NB 24.4kbps	EVS Primary NB 5.9kbps	Orientation	Band / BW	Channel
ABM1 (dBA/m)	3.58	2.99	5.75	5.44	1.28	1.98			
ABM2 (dBA/m)	-53.33	-53.83	-54.04	-53.87	-53.66	-53.19	Axial	Band 66 20MHz	132322
Frequency Response	Pass	Pass	Pass	Pass	Pass	Pass	Axiai		
S+N/N (dB)	56.91	56.82	59.79	59.31	54.94	55.17			

- Mute on; Backlight off; Max Volume; Max Contrast
- TPC = "Max Power"




Figure 5-2
Audio Band Magnetic Curve Measurement Block Diagram

## 3. LTE TDD Uplink-Downlink Configuration Investigation for VoLTE over IMS

An investigation was performed to determine the worst-case Uplink-Downlink configuration for VoLTE over IMS T-Coil testing.

Per 3GPP TS 36.211, the total frame length for each TDD radio frame of length  $T_f$  = 307200  $\cdot$   $T_s$  = 10 ms, where  $T_s$  is a number of time units equal to 1/(15000 x 2048) seconds. Additionally, each radio frame consists of 10 subframes, each of length 30720  $\cdot$   $T_s$  = 1 ms, and subframes can be designated as uplink (U), downlink (D), or special subframe (S), depending on the Uplink-Downlink configuration as indicated in Table 4.2-2 of 3GPP TS 36.211. In the transmission duty factor calculation, the special subframe configuration with the shortest UpPTS duration within the special subframe is used and will be applied for measurement. From 3GPP TS 36.211 Table 4.2-1, the shortest UpPTS is 2192  $\cdot$  Ts which occurs in the normal cyclic prefix and special subframe configuration 4.

See table below outlining the calculated transmission duty cycles for each Uplink-Downlink configuration:

Table 5-4
Uplink-Downlink Configurations for Type 2 Frame Structures

Uplink-downlink	Downlink-to-Uplink Switch-point periodicity	Subframe number									Calculated Transmission	
configuration	Switch-point periodicity	0	1	2	3	4	5	6	7	8	9	Duty Cycle (%)
0	5 ms	D	S	U	J	U	D	S	U	U	U	61.4%
1	5 ms	D	S	U	J	D	D	S	U	U	D	41.4%
2	5 ms	D	S	U	D	D	D	S	U	D	D	21.4%
3	10 ms	D	S	U	J	U	D	D	D	D	D	30.7%
4	10 ms	D	S	U	J	D	D	D	D	D	D	20.7%
5	10 ms	D	S	U	D	D	D	D	D	D	D	10.7%
6	5 ms	D	S	U	U	U	D	S	U	U	D	51.4%

FCC ID: A3LSMG998U	PCTEST:	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 20 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 20 of 97

### a. Power Class 3 Uplink-Downlink Configuration Investigation

Power Class 3 was evaluated with the following radio configuration: channel 40620, 20MHz BW, 16QAM, 1RB, 99RB Offset. For Power Class 3, all configurations (0-6) are supported. The configuration which resulted in the worst SNNR was used for full testing. Uplink-Downlink configuration 0 was used as the worst-case configuration for Power Class 3 VoLTE over IMS T-Coil testing. See table below for the SNNR comparison between each Uplink-Downlink configuration:

Table 5-5
Power Class 3 VoLTE over IMS SNNR by UL-DL Configuration

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	UL-DL Configuration	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
2593.0	40620	20	16QAM	1	99	0	0.87	-49.01	49.88
2593.0	40620	20	16QAM	1	99	1	0.82	-49.16	49.98
2593.0	40620	20	16QAM	1	99	2	0.88	-49.49	50.37
2593.0	40620	20	16QAM	1	99	3	0.87	-51.35	52.22
2593.0	40620	20	16QAM	1	99	4	0.87	-51.42	52.29
2593.0	40620	20	16QAM	1	99	5	0.86	-51.24	52.10
2593.0	40620	20	16QAM	1	99	6	0.90	-49.22	50.12

### b. Power Class 2 Uplink-Downlink Configuration Investigation

Power Class 2 was evaluated with the following radio configuration: channel 40620, 20MHz BW, 16QAM, 1RB, 99RB Offset. For Power Class 2, configurations 1-5 are supported. The configuration which resulted in the worst SNNR was used for full testing. Uplink-Downlink configuration 1 was used as the worst-case configuration for Power Class 2 VoLTE over IMS T-Coil testing. See table below for the SNNR comparison between each Uplink-Downlink configuration:

Table 5-6
Power Class 2 VoLTE over IMS SNNR by UL-DL Configuration

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	UL-DL Configuration	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
IMUZI		INIUTE					[UB(A/III)]	[UD(AVIII)]	IUDI
2593.0	40620	20	16QAM	1	99	1	0.76	-46.10	46.86
2593.0	40620	20	16QAM	1	99	2	0.70	-46.25	46.95
2593.0	40620	20	16QAM	1	99	3	0.73	-47.73	48.46
2593.0	40620	20	16QAM	1	99	4	0.76	-48.03	48.79
2593.0	40620	20	16QAM	1	99	5	0.71	-48.29	49.00

Note: LTE TDD B41 Power Class 2 only supports UL-DL configurations 1-5, not 0 or 6.

### c. Conclusion

Per the investigations above, UL-DL Configuration 0 was used to evaluate Power Class 3 VoLTE over IMS and UL-DL Configuration 1 was used to evaluate Power Class 2 VoLTE over IMS.

FCC ID: A3LSMG998U	PCTEST*	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 21 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 21 01 97

# 6. VOWIFI TEST SYSTEM SETUP AND DUT CONFIGURATION

# I. Test System Setup for VoWIFI over IMS T-coil Testing

## 1. Equipment Setup

The general test setup used for VoWIFI over IMS, or CMRS WIFI Calling, is shown below. The callbox used when performing VoWIFI over IMS T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.




Figure 6-1
Test Setup for VoWIFI over IMS T-Coil Measurements

### 2. Audio Level Settings

According to KDB 285076 D02 released by the FCC OET regarding the appropriate audio levels to be used for VoWIFI over IMS T-Coil testing, -20dBm0 shall be used for the normal speech input level<sup>2</sup>. The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -20dBm0 speech input level to the DUT for the VoWIFI over IMS connection.

<sup>2</sup> FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017

1 00 Office of Engineer	ing and recimology RDD, 200	DOTO DOZ 1-OON TOSKING TO OWNTO II	voo, ocpicilisci io, z	2017
FCC ID: A3LSMG998U	PCTEST*	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 22 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 22 01 91

© 2020 PCTEST REV 3.4.M

# II. DUT Configuration for VoWIFI over IMS T-coil Testing

# 1. Radio Configuration

An investigation was performed on all applicable data rates and modulations to determine the radio configuration to be used for testing. See tables below for SNNR comparison between radio configurations in each IEEE 802.11 standard:

Table 6-1
IEEE 802.11b SNNR by Radio Configuration

Mode	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
IEEE 802.11b	6	DSSS	1	-2.67	-49.18	46.51
IEEE 802.11b	6	DSSS	2	-2.53	-49.07	46.54
IEEE 802.11b	6	CCK	5.5	-2.55	-48.20	45.65
IEEE 802.11b	6	CCK	11	-2.54	-47.32	44.78

Table 6-2 IEEE 802.11g/a SNNR by Radio Configuration

Mode	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
IEEE 802.11g	6	BPSK	6	-2.56	-48.48	45.92
IEEE 802.11g	6	BPSK	9	-2.43	-46.43	44.00
IEEE 802.11g	6	QPSK	12	-2.47	-46.44	43.97
IEEE 802.11g	6	QPSK	18	-2.51	-46.45	43.94
IEEE 802.11g	6	16QAM	24	-2.51	-46.90	44.39
IEEE 802.11g	6	16QAM	36	-2.49	-46.80	44.31
IEEE 802.11g	6	64QAM	48	-2.52	-46.56	44.04
IEEE 802.11g	6	64QAM	54	-2.52	-46.80	44.28

Table 6-3
IEEE 802.11n/ac 20MHz BW SNNR by Radio Configuration

			rtaare comigaration				
Mode	Bandwidth [MHz]	Channel	Modulation	MCS Index	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
IEEE 802.11n	20	40	BPSK	0	-2.54	-46.26	43.72
IEEE 802.11n	20	40	QPSK	1	-2.55	-46.13	43.58
IEEE 802.11n	20	40	QPSK	2	-2.53	-46.92	44.39
IEEE 802.11n	20	40	16QAM	3	-2.54	-46.65	44.11
IEEE 802.11n	20	40	16QAM	4	-2.51	-46.63	44.12
IEEE 802.11n	20	40	64QAM	5	-2.48	-46.87	44.39
IEEE 802.11n	20	40	64QAM	6	-2.53	-46.08	43.55
IEEE 802.11n	20	40	64QAM	7	-2.54	-46.21	43.67
IEEE 802.11ac	20	40	256QAM	8	-2.56	-46.56	44.00

Table 6-4
IEEE 802.11ax SU 20MHz BW SNNR by Radio Configuration

	izzz odz. i tak od zomi iz bit ottitk by tadio domigaration											
Mode	Bandwidth [MHz]	Channel	Modulation	MCS Index	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]					
IEEE 802.11ax SU	20	40	BPSK	0	-2.73	-46.07	43.34					
IEEE 802.11ax SU	20	40	QPSK	1	-2.69	-46.02	43.33					
IEEE 802.11ax SU	20	40	QPSK	2	-2.68	-46.47	43.79					
IEEE 802.11ax SU	20	40	16QAM	3	-2.69	-45.89	43.20					
IEEE 802.11ax SU	20	40	16QAM	4	-2.65	-46.10	43.45					
IEEE 802.11ax SU	20	40	64QAM	5	-2.71	-45.20	42.49					
IEEE 802.11ax SU	20	40	64QAM	6	-2.70	-46.47	43.77					
IEEE 802.11ax SU	20	40	64QAM	7	-2.68	-45.98	43.30					
IEEE 802.11ax SU	20	40	256QAM	8	-2.71	-45.99	43.28					
IEEE 802.11ax SU	20	40	256QAM	9	-2.72	-45.57	42.85					
IEEE 802.11ax SU	20	40	1024QAM	10	-2.72	-46.64	43.92					
IEEE 802.11ax SU	20	40	1024QAM	11	-2.68	-46.33	43.65					

FCC ID: A3LSMG998U	PCTEST* Proof to be part of ® secured	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 22 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 23 of 97

Table 6-5 IEEE 802.11ax RU 20MHz BW SNNR by Radio Configuration

	in the second se										
Mode	Bandwidth [MHz]	Channel	Modulation	MCS Index	RU Index	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]			
IEEE 802.11ax RU	20	40	64QAM	5	0	-2.68	-45.62	42.94			
IEEE 802.11ax RU	20	40	64QAM	5	8	-2.83	-47.88	45.05			
IEEE 802.11ax RU	20	40	64QAM	5	37	-2.83	-45.72	42.89			
IEEE 802.11ax RU	20	40	64QAM	5	40	-2.83	-45.79	42.96			
IEEE 802.11ax RU	20	40	64QAM	5	53	-2.80	-46.10	43.30			
IEEE 802.11ax RU	20	40	64QAM	5	54	-2.77	-46.52	43.75			
IEEE 802.11ax RU	20	40	64QAM	5	61	-2.76	-46.42	43.66			

Table 6-6 IEEE 802.11n/ac 40MHz BW SNNR by Radio Configuration

11-	LL 002. I	III/ac 40	Radio Comiguration				
Mode	Bandwidth [MHz]	Channel	Modulation	MCS Index	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
IEEE 802.11n	40	38	BPSK	0	-2.60	-46.70	44.10
IEEE 802.11n	40	38	QPSK	1	-2.59	-46.50	43.91
IEEE 802.11n	40	38	QPSK	2	-2.60	-46.05	43.45
IEEE 802.11n	40	38	16QAM	3	-2.66	-45.92	43.26
IEEE 802.11n	40	38	16QAM	4	-2.84	-46.66	43.82
IEEE 802.11n	40	38	64QAM	5	-2.59	-46.10	43.51
IEEE 802.11n	40	38	64QAM	6	-2.85	-45.97	43.12
IEEE 802.11n	40	38	64QAM	7	-2.71	-47.71	45.00
IEEE 802.11ac	40	38	256QAM	8	-2.74	-47.54	44.80
IEEE 802.11ac	40	38	256QAM	9	-2.69	-46.24	43.55

Table 6-7 IEEE 802.11ax SU 40MHz BW SNNR by Radio Configuration

Mode	Bandwidth [MHz]	Channel	Modulation	MCS Index	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
IEEE 802.11ax SU	40	38	BPSK	0	-2.67	-46.25	43.58
IEEE 802.11ax SU	40	38	QPSK	1	-2.66	-45.38	42.72
IEEE 802.11ax SU	40	38	QPSK	2	-2.66	-45.56	42.90
IEEE 802.11ax SU	40	38	16QAM	3	-2.63	-45.68	43.05
IEEE 802.11ax SU	40	38	16QAM	4	-2.64	-46.29	43.65
IEEE 802.11ax SU	40	38	64QAM	5	-2.59	-45.75	43.16
IEEE 802.11ax SU	40	38	64QAM	6	-2.64	-45.98	43.34
IEEE 802.11ax SU	40	38	64QAM	7	-2.63	-46.09	43.46
IEEE 802.11ax SU	40	38	256QAM	8	-2.62	-45.66	43.04
IEEE 802.11ax SU	40	38	256QAM	9	-2.63	-46.61	43.98
IEEE 802.11ax SU	40	38	1024QAM	10	-2.62	-45.82	43.20
IEEE 802.11ax SU	40	38	1024QAM	11	-2.63	-46.60	43.97

Table 6-8 IEEE 802.11ax RU 40MHz BW SNNR by Radio Configuration

Mode	Bandwidth [MHz]	Channel	Modulation	MCS Index	RU Index	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]		
IEEE 802.11ax RU	40	38	QPSK	1	0	-2.61	-45.80	43.19		
IEEE 802.11ax RU	40	38	QPSK	1	17	-2.63	-45.89	43.26		
IEEE 802.11ax RU	40	38	QPSK	1	37	-2.59	-45.76	43.17		
IEEE 802.11ax RU	40	38	QPSK	1	44	-2.63	-46.13	43.50		
IEEE 802.11ax RU	40	38	QPSK	1	53	-2.72	-46.23	43.51		
IEEE 802.11ax RU	40	38	QPSK	1	56	-2.92	-46.34	43.42		
IEEE 802.11ax RU	40	38	QPSK	1	61	-2.73	-45.99	43.26		
IEEE 802.11ax RU	40	38	QPSK	1	62	-2.68	-45.70	43.02		
IEEE 802.11ax RU	40	38	QPSK	1	65	-2.82	-45.64	42.82		

FCC ID: A3LSMG998U	PCTEST:	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 24 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 24 of 97

### 2. Codec Configuration

An investigation was performed to determine the audio codec configuration to be used for testing. The effects of codec configuration were found to be independent of radio configuration; therefore, only one radio configuration was used for this investigation. The EVS Primary NB 24.4kbps setting was used for the audio codec on the CMW500 for VoWIFI over IMS T-coil testing. See below table for comparisons between different codecs and codec data rates:

> Table 6-9 AMR Codec Investigation - VoWIFI over IMS

7 mint ocaco invoctigation vovin i ovoi imo												
Codec Setting:	WB AMR 23.85kbps	WB AMR 6.60kbps	NB AMR 12.2kbps	NB AMR 4.75kbps	Orientation	Band	Standard	Channel				
ABM1 (dBA/m)	1.78	0.29	-2.47	-2.81								
ABM2 (dBA/m)	-49.92	-49.05	-49.02	-49.76	Axial	2.4GHz						
Frequency Response	Pass	Pass	Pass	Pass	Axiai	2.46П2	IEEE 802.11b	6				
S+N/N (dB)	51.70	49.34	46.55	46.95								

**Table 6-10 EVS Codec Investigation – VoWIFI over IMS** 

Codec Setting:	EVS Primary SWB 128kbps	EVS Primary SWB 9.6kbps	EVS Primary WB 128kbps	EVS Primary WB 5.9kbps	EVS Primary NB 24.4kbps	EVS Primary NB 5.9kbps	Orientation	Band	Standard	Channel
ABM1 (dBA/m)	-0.42	-0.91	1.85	1.57	-2.78	-2.27			IEEE 802.11b	
ABM2 (dBA/m)	-49.23	-49.87	-49.87	-49.94	-49.03	-49.43	Axial	2.401 -		6
Frequency Response	Pass	Pass	Pass	Pass	Pass	Pass	Axiai	2.4GHz		
S+N/N (dB)	48.81	48.96	51.72	51.51	46.25	47.16				

Mute on; Backlight off; Max Volume; Max Contrast




Figure 6-2 **Audio Band Magnetic Curve Measurement Block Diagram** 

FCC ID: A3LSMG998U	PCTEST .  Road to be post of ® enement	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager	
Filename:	Test Dates:	DUT Type:		Page 25 of 97	
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 20 01 97	

#### 7. OTT VOIP TEST SYSTEM AND DUT CONFIGURATION

#### Test System Setup for OTT VoIP T-Coil Testing I.

## 1. OTT VoIP Application

Google Duo is a pre-installed application on the DUT which allows for VoIP calls in a held-to-ear scenario. Duo uses the OPUS audio codec and supports a bitrate range of 6kb/s to 75kb/s. All air interfaces capable of a data connection were evaluated with Google Duo.

## 2. Equipment Setup

A CMW500 callbox was used to perform OTT VoIP T-coil measurements. The Data Application Unit (DAU) of the CMW500 was connected to the internet and allowed for an IP data connection on the DUT. An auxiliary VoIP unit was used to initiate an OTT VoIP call to the DUT. The auxiliary VoIP unit allowed for the configuration and monitoring of the OTT VoIP codec bitrate during a call. Both high and low bitrate settings were evaluated in to determine the worst-case configuration.

### 3. Audio Level Settings

According to KDB 285076 D02, the average speech level of -20dBm0 shall be used for protocols not specifically listed in Table 7.1 of ANSI C63.19-2011 or the ANSI C63.19-2011 VoLTE interpretation<sup>3</sup>. The auxiliary VoIP unit allowed for monitoring the signal input level to ensure that the settings for speech input and full scale levels resulted in the -20dBm0 speech input level to the DUT for the OTT VoIP call.

Note: The green highlighted text is approved by FCC under the TCB PAG Re-Use Policy 388624 D01 IV. D. for T-Coil Testing for WI-FI calling and Google Duo.

#### II. **DUT Configuration for OTT VolP T-Coil Testing**

## 1. Codec Configuration

An investigation was performed for each applicable data mode to determine the audio codec configuration to be used for testing. The effects of codec configuration were found to be independent of radio configuration; therefore, only one radio configuration for each applicable data mode was used for these investigations. The 6kbps codec setting was used for the audio codec on the auxiliary VoIP unit for OTT VoIP T-Coil testing. See below tables for comparisons between codec data rates on all applicable data modes:

> Table 7-1 Codec Investigation - OTT VoIP (EvDO)

	····					
Codec Setting:	75kbps	6kbps	Orientation	Channel		
ABM1 (dBA/m)	11.94	11.52				
ABM2 (dBA/m)	-49.09	-49.23	المشاء	600		
Frequency Response	Pass	Pass	Axial	600		
S+N/N (dB)	61.03	60.75				

<sup>3</sup> FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017

T 00 Office of Engineer	ing and recimology RDB, 20	OUTO DOZ T OOR TOOKING IOI OMITO II	voo, ooptember 10, 2	2017
FCC ID: A3LSMG998U	PCTEST* Road to be port of ® remove	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename: 1M2009230152-21-R2.A3L	Test Dates: 10/19/2020 - 11/14/2020	DUT Type: Portable Handset		Page 26 of 97

Table 7-2 Codec Investigation - OTT VoIP (EDGE)

Codec III	vestigatic	/// - O i i	VOII (LDC	JL)		
Codec Setting:	75kbps	6kbps	Orientation	Channel		
ABM1 (dBA/m)	11.98	11.73				
ABM2 (dBA/m)	-44.49	-43.91	Axial	661		
Frequency Response	Pass	Pass	Allai			
S+N/N (dB)	56.47	55.64				

Table 7-3 Codec Investigation - OTT VoIP (HSPA)

	· · · · · · · · · · · · · · · · · · ·					
Codec Setting:	75kbps	6kbps	Orientation	Channel		
ABM1 (dBA/m)	11.84	11.76				
ABM2 (dBA/m)	-50.97	-50.41	Axial	9400		
Frequency Response	Pass	Pass	Axiai	9400		
S+N/N (dB)	62.81	62.17				


Table 7-4 Codec Investigation - OTT VoIP (LTE)

Codec Setting:	75kbps	6kbps	Orientation	Band / BW	Channel	
ABM1 (dBA/m)	11.86	11.58				
ABM2 (dBA/m)	-49.67	-49.61	Axial	Band 66	132322	
Frequency Response	Pass	Pass	Axiai	20MHz	132322	
S+N/N (dB)	61.53	61.19				

Table 7-5 Codec Investigation - OTT VoIP (WIFI)

	O G G G G	ivestigati	· · ·	VOII (VVII	• • • •	
Codec Setting:	75kbps 6kbps		Orientation	Band	Standard	Channel
ABM1 (dBA/m)	12.11	11.93				
ABM2 (dBA/m)	-50.27	-50.27 -49.71		2.4GHz	IEEE 802.11b	6
Frequency Response	Pass	Pass	Axial	2.4602	IEEE 802.11D	0
S+N/N (dB)	62.38	61.64				

- Mute on; Backlight off; Max Volume; Max Contrast
- Radio Configurations can be found in Section 9.II.H



**Audio Band Magnetic Curve Measurement Block Diagram** 

FCC ID: A3LSMG998U	PCTEST .  Road to be post of ® enement	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 27 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 27 01 97

### 2. Radio Configuration for OTT VoIP (LTE)

An investigation was performed to determine the worst-case LTE FDD band to be used for OTT VoIP testing. LTE FDD Band 71 was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different LTE FDD bands:

Table 7-6
OTT VoIP (LTE FDD) SNNR by LTE Band

Band	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	Modulation RB Size		ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
71	680.5	133297	20	16QAM	1	99	11.79	-48.90	60.69
12	707.5	23095	10	16QAM	1	49	11.70	-50.41	62.11
13	782.0	23230	10	16QAM	1	49	11.66	-49.26	60.92
14	793.0	23330	10	16QAM	1	49	11.78	-48.96	60.74
26	831.5	26865	15	16QAM	1	74	11.72	-49.89	61.61
5	836.5	20525	10	16QAM	1	49	11.67	-49.06	60.73
66	1745.0	132322	20	16QAM	1	99	11.54	-49.36	60.90
2	1880.0	18900	20	16QAM	1	99	11.80	-49.45	61.25
25	1882.5	26365	20	16QAM	1	99	11.80	-49.54	61.34
30	2310.0	27710	10	16QAM	1	49	11.72	-50.74	62.46
7	2535.0	21100	20	16QAM	1	99	11.78	-50.25	62.03

An investigation was performed to determine the worst-case LTE TDD band to be used for OTT VoIP testing. LTE TDD Band 41 (PC2) was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different LTE TDD bands:

Table 7-7
OTT VoIP (LTE TDD) SNNR by LTE Band

Band	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
41 (PC3)	2593.0	40620	20	16QAM	1	99	11.81	-44.85	56.66
41 (PC2)	2593.0	40620	20	16QAM	1	99	11.42	-42.87	54.29
48	3625.0	55990	20	16QAM	1	99	11.72	-45.08	56.80

### 3. LTE FDD Uplink Carrier Aggregation for OTT VolP

LTE FDD ULCA was evaluated to ensure LTE FDD standalone was the worst-case scenario. The configurations in Table 7-8 were determined from Table 7-6 and satisfy the configuration requirements as defined in 3GPP 36.101.

Table 7-8
LTE FDD SNNR for OTT VoIP Uplink Carrier Aggregation

			_		D 011			• • •	Opin	iiv Ou		'99' C	guuoi	•			
				PCC							SCC						
Combination	PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	SCC Band	SCC Bandwidth [MHz]	SCC (UL) Channel	SCC (UL) Frequency [MHz]	Modulation	SCC UL# RB	SCC UL RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
CA_5B	LTE B5	10	20525	836.5	16QAM	1	0	LTE B5	5	20453	829.3	16QAM	1	24	11.62	-52.67	64.29
CA_66B	LTE B66	10	132322	1745.0	16QAM	1	0	LTE B66	10	132223	1735.1	16QAM	1	49	11.50	-51.99	63.49
CA_66C	LTE B66	20	132322	1745.0	16QAM	1	0	LTE B66	20	132124	1725.5	16QAM	1	99	11.68	-51.43	63.11

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 28 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 20 01 91

# 4. LTE TDD Uplink Carrier Aggregation for OTT VoIP

LTE TDD ULCA was evaluated to ensure LTE TDD standalone was the worst-case scenario. The configurations in Table 7-9 were determined from Table 7-7 and satisfy the configuration requirements as defined in 3GPP 36.101.

Table 7-9
LTE TDD SNNR for OTT VoIP Uplink Carrier Aggregation

				PCC					SCC								
Combination	PCC Band	PCC Bandwidth [MHz]	PCC (UL/DL) Channel	PCC (UL/DL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	SCC Band	SCC Bandwidth [MHz]	SCC (UL/DL) Channel	SCC (UL/DL) Frequency [MHz]	Modulation	SCC UL# RB	SCC UL RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
CA_41C (PC3)	LTE B41	20	40620	2593.0	16QAM	1	0	LTE B41	20	40422	2573.2	16QAM	1	99	11.49	-45.46	56.95
CA_41C (PC2)	LTE B41	20	40620	2593.0	16QAM	1	0	LTE B41	20	40422	2573.2	16QAM	1	99	11.40	-42.94	54.34
CA_48C	LTE B48	20	55990	3625.0	16QAM	1	0	LTE B48	20	55792	3605.2	16QAM	1	99	11.68	-45.45	57.13

FCC ID: A3LSMG998U	PCTEST: Noted to be part of @ secured	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 20 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 29 of 97

### 5. Interim Procedure for evaluation OTT VoIP (NR)

The following procedure is used to evaluate OTT VoIP (NR) given equipment limitations.

- a. This procedure is applicable for OTT VoIP (NR) voice calls that use the same protocol, codec(s), and reference level as OTT VoIP (LTE) (i.e. -20dBm0).
- Establish the ABM1<sub>NR</sub> value by using the ABM1<sub>LTE</sub> magnetic intensity for an LTE call using a correlating LTE band through existing procedures and test equipment.
- Establish an ABM2<sub>NR</sub> value using factory test mode (FTM) to simulate a NR connection for the desired NR band and channel under test.
- d. The following information is documented in Section 9:
  - i. ABM2<sub>LTE</sub> and ABM2<sub>NR</sub> for respective tests.
  - ii. Calculate SNNR:
    - 1. ABM1 = ABM1<sub>LTE</sub>
    - 2.  $ABM2 = ABM2_{NR}$
    - 3.  $SNNR_{NR} = [ABM1_{LTE} ABM2_{NR}] 3dB$ 
      - a. A 3dB margin is built in to ensure conservative results with this interim procedure.

The above is only applicable for OTT VoIP scenarios, this device does not support VoNR over IMS.

The manufacturer has confirmed the handset as designed is expected to exhibit similar audio intensity levels between an OTT VoIP call placed over a 4G LTE and a 5G Sub-6GHz data connection.

FCC ID: A3LSMG998U	PCTEST:	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 20 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 30 of 97

## 6. Radio Configuration for OTT VoIP (NR)

An investigation was performed to determine the waveform, modulation, and RB configuration to be used for testing. Due to equipment limitations, the procedure outlined in 7.II.5 was used to evaluate the SNNR for each radio configuration below. DFT-s-OFDM 16QAM, 1RB, 99%RB offset was determined to be the worst-case configuration for the handset and will be used for full testing in Section 9.

Table 7-10
NR OTT VoIP SNNR by Radio Configuration (CP-OFDM)

Band	Frequency [MHz]	Channel	Bandwidth [MHz]	Waveform	Modulation	RB Size	RB Offset	ABM1 <sub>LTE</sub> [dB(A/m)]	ABM2 <sub>NR</sub> [dB(A/m)]	SNNR <sub>NR</sub> [dB]
n66	1745.0	349000	40	CP-OFDM	QPSK	1	1	11.54	-48.99	60.53
n66	1745.0	349000	40	CP-OFDM	QPSK	1	108	11.54	-49.83	61.37
n66	1745.0	349000	40	CP-OFDM	QPSK	1	215	11.54	-50.08	61.62
n66	1745.0	349000	40	CP-OFDM	QPSK	108	1	11.54	-49.11	60.65
n66	1745.0	349000	40	CP-OFDM	QPSK	108	54	11.54	-48.18	59.72
n66	1745.0	349000	40	CP-OFDM	QPSK	108	108	11.54	-47.51	59.05
n66	1745.0	349000	40	CP-OFDM	QPSK	216	0	11.54	-48.66	60.20
n66	1745.0	349000	40	CP-OFDM	16QAM	1	1	11.54	-47.47	59.01
n66	1745.0	349000	40	CP-OFDM	16QAM	1	108	11.54	-48.59	60.13
n66	1745.0	349000	40	CP-OFDM	16QAM	1	215	11.54	-47.67	59.21
n66	1745.0	349000	40	CP-OFDM	16QAM	108	1	11.54	-48.33	59.87
n66	1745.0	349000	40	CP-OFDM	16QAM	108	54	11.54	-49.90	61.44
n66	1745.0	349000	40	CP-OFDM	16QAM	108	108	11.54	-51.24	62.78
n66	1745.0	349000	40	CP-OFDM	16QAM	216	0	11.54	-49.95	61.49
n66	1745.0	349000	40	CP-OFDM	64QAM	1	1	11.54	-48.13	59.67
n66	1745.0	349000	40	CP-OFDM	64QAM	1	108	11.54	-48.97	60.51
n66	1745.0	349000	40	CP-OFDM	64QAM	1	215	11.54	-50.22	61.76
n66	1745.0	349000	40	CP-OFDM	64QAM	108	1	11.54	-50.45	61.99
n66	1745.0	349000	40	CP-OFDM	64QAM	108	54	11.54	-50.24	61.78
n66	1745.0	349000	40	CP-OFDM	64QAM	108	108	11.54	-50.09	61.63
n66	1745.0	349000	40	CP-OFDM	64QAM	216	0	11.54	-50.10	61.64
n66	1745.0	349000	40	CP-OFDM	256QAM	1	1	11.54	-50.00	61.54
n66	1745.0	349000	40	CP-OFDM	256QAM	1	108	11.54	-49.23	60.77
n66	1745.0	349000	40	CP-OFDM	256QAM	1	215	11.54	-49.05	60.59
n66	1745.0	349000	40	CP-OFDM	256QAM	108	1	11.54	-50.20	61.74
n66	1745.0	349000	40	CP-OFDM	256QAM	108	54	11.54	-50.11	61.65
n66	1745.0	349000	40	CP-OFDM	256QAM	108	108	11.54	-50.36	61.90
n66	1745.0	349000	40	CP-OFDM	256QAM	216	0	11.54	-49.38	60.92

FCC ID: A3LSMG998U	PCTEST* Houd to be part of @ secure	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 24 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 31 of 97

Table 7-11
NR OTT VoIP SNNR by Radio Configuration (DFT-s-OFDM)

The state of the s							CNIND			
Band	Frequency [MHz]	Channel	Bandwidth [MHz]	Waveform	Modulation	RB Size	RB Offset	ABM1 <sub>LTE</sub> [dB(A/m)]	ABM2 <sub>NR</sub> [dB(A/m)]	SNNR <sub>NR</sub> [dB]
n66	1745.0	349000	40	DFT-s-OFDM	π/2-BPSK	1	1	11.54	-49.63	61.17
n66	1745.0	349000	40	DFT-s-OFDM	π/2-BPSK	1	108	11.54	-49.95	61.49
n66	1745.0	349000	40	DFT-s-OFDM	π/2-BPSK	1	214	11.54	-48.86	60.40
n66	1745.0	349000	40	DFT-s-OFDM	π/2-BPSK	108	0	11.54	-50.33	61.87
n66	1745.0	349000	40	DFT-s-OFDM	π/2-BPSK	108	54	11.54	-50.24	61.78
n66	1745.0	349000	40	DFT-s-OFDM	π/2-BPSK	108	108	11.54	-50.04	61.58
n66	1745.0	349000	40	DFT-s-OFDM	π/2-BPSK	216	0	11.54	-50.31	61.85
n66	1745.0	349000	40	DFT-s-OFDM	QPSK	1	1	11.54	-48.43	59.97
n66	1745.0	349000	40	DFT-s-OFDM	QPSK	1	108	11.54	-48.41	59.95
n66	1745.0	349000	40	DFT-s-OFDM	QPSK	1	214	11.54	-50.20	61.74
n66	1745.0	349000	40	DFT-s-OFDM	QPSK	108	0	11.54	-50.00	61.54
n66	1745.0	349000	40	DFT-s-OFDM	QPSK	108	54	11.54	-49.56	61.10
n66	1745.0	349000	40	DFT-s-OFDM	QPSK	108	108	11.54	-49.30	60.84
n66	1745.0	349000	40	DFT-s-OFDM	QPSK	216	0	11.54	-50.22	61.76
n66	1745.0	349000	40	DFT-s-OFDM	16QAM	1	1	11.54	-47.84	59.38
n66	1745.0	349000	40	DFT-s-OFDM	16QAM	1	108	11.54	-48.39	59.93
n66	1745.0	349000	40	DFT-s-OFDM	16QAM	1	214	11.54	-47.43	58.97
n66	1745.0	349000	40	DFT-s-OFDM	16QAM	108	0	11.54	-47.76	59.30
n66	1745.0	349000	40	DFT-s-OFDM	16QAM	108	54	11.54	-48.26	59.80
n66	1745.0	349000	40	DFT-s-OFDM	16QAM	108	108	11.54	-49.71	61.25
n66	1745.0	349000	40	DFT-s-OFDM	16QAM	216	0	11.54	-48.88	60.42
n66	1745.0	349000	40	DFT-s-OFDM	64QAM	1	1	11.54	-49.43	60.97
n66	1745.0	349000	40	DFT-s-OFDM	64QAM	1	108	11.54	-49.39	60.93
n66	1745.0	349000	40	DFT-s-OFDM	64QAM	1	214	11.54	-49.34	60.88
n66	1745.0	349000	40	DFT-s-OFDM	64QAM	108	0	11.54	-49.56	61.10
n66	1745.0	349000	40	DFT-s-OFDM	64QAM	108	54	11.54	-49.22	60.76
n66	1745.0	349000	40	DFT-s-OFDM	64QAM	108	108	11.54	-49.11	60.65
n66	1745.0	349000	40	DFT-s-OFDM	64QAM	216	0	11.54	-49.00	60.54
n66	1745.0	349000	40	DFT-s-OFDM	256QAM	1	1	11.54	-50.08	61.62
n66	1745.0	349000	40	DFT-s-OFDM	256QAM	1	108	11.54	-49.04	60.58
n66	1745.0	349000	40	DFT-s-OFDM	256QAM	1	214	11.54	-48.93	60.47
n66	1745.0	349000	40	DFT-s-OFDM	256QAM	108	0	11.54	-49.51	61.05
n66	1745.0	349000	40	DFT-s-OFDM	256QAM	108	54	11.54	-49.50	61.04
n66	1745.0	349000	40	DFT-s-OFDM	256QAM	108	108	11.54	-48.91	60.45
n66	1745.0	349000	40	DFT-s-OFDM	256QAM	216	0	11.54	-49.81	61.35

An investigation was performed to determine the worst-case NR FDD band to be used for OTT VoIP testing. NR n30 was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different NR FDD bands:

Table 7-12
OTT VoIP (NR FDD) SNNR by Band

Band	Frequency [MHz]	Channel	Bandwidth [MHz]	Waveform	Modulation	RB Size	RB Offset	ABM1 <sub>LTE</sub> [dB(A/m)]	ABM2 <sub>NR</sub> [dB(A/m)]	SNNR <sub>NR</sub> [dB]
n71	680.5	136100	20	DFT-s-OFDM	16QAM	1	104	11.79	-46.84	58.63
n12	707.5	141500	15	DFT-s-OFDM	16QAM	1	77	11.70	-49.36	61.06
n5	836.5	167300	20	DFT-s-OFDM	16QAM	1	104	11.67	-48.78	60.45
n66 (Ant A)	1745.0	349000	40	DFT-s-OFDM	16QAM	1	214	11.54	-47.26	58.80
n66 (Ant E)	1745.0	349000	40	DFT-s-OFDM	16QAM	1	214	11.54	-47.52	59.06
n25 (Ant A)	1880.0	376500	40	DFT-s-OFDM	16QAM	1	214	11.80	-48.48	60.28
n25 (Ant E)	1882.5	376500	40	DFT-s-OFDM	16QAM	1	214	11.80	-47.57	59.37
n30	2310.0	462000	10	DFT-s-OFDM	16QAM	1	50	11.72	-46.43	58.15

FCC ID: A3LSMG998U	PCTEST: Noted to be part of @ secured	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 22 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 32 of 97

An investigation was performed to determine the worst-case NR TDD band to be used for OTT VoIP testing. NR n41 (PC2) ANT E was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different NR TDD bands:

> **Table 7-13** OTT VolP (NR TDD) SNNR by Band

Band	Frequency [MHz]	Channel	Bandwidth [MHz]	Waveform	Modulation	RB Size	RB Offset	ABM1 <sub>LTE</sub> [dB(A/m)]	ABM2 <sub>NR</sub> [dB(A/m)]	SNNR <sub>NR</sub> [dB]
n41 (PC3) ANT B	2593.0	518598	100	DFT-s-OFDM	16QAM	1	271	11.81	-34.32	46.13
n41 (PC2) ANT E	2593.0	518598	100	DFT-s-OFDM	16QAM	1	271	11.42	-31.68	43.10
n77	3750.0	650000	100	DFT-s-OFDM	16QAM	1	271	13.87	-38.20	52.07

FCC ID: A3LSMG998U	PCTEST:	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 22 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 33 of 97

# 8. FCC 3G MEASUREMENTS

# I. CDMA Test Configurations

Radio Configuration 1, Service Option 68 was used for the testing according to the CTIA Test Plan and also as one of the worst-case configuration for the handset due to vocoder gating from the EVRC logic. See below plot for an example of ABM noise comparison between operational field service options and radio configurations for a CDMA2000 handset:





Figure 8-1
CDMA Audio Band Magnetic Noise

Table 8-1 FCC 3G ABM Measurements for A3LSMG998U (CDMA)

Configuration:	RC1/SO68	RC3/SO68	RC4/SO68	Orientation	Channel
ABM1 (dBA/m)	0.50	0.57	0.58		600
ABM2 (dBA/m)	-51.64	-52.95	-53.14	Axial	
Frequency Response	Pass	Pass	Pass	Axiai	
S+N/N (dB)	52.14	53.52	53.72		

- Mute on; Backlight off; Max Volume; Max Contrast
- Power Control Bits = "All Up"



Audio Band Magnetic Curve Measurement Block Diagram

FCC ID: A3LSMG998U	PCTEST Hood to be part of & rement	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 24 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 34 of 97

#### **UMTS Test Configurations** II.

AMR at 12.2kbps, 13.6kbps SRB was used for the testing as the worst-case configuration for the handset. See below plot for ABM noise comparison between vocoder rates:




Figure 8-3 **UMTS Audio Band Magnetic Noise** 

Table 8-2 Codec Investigation - UMTS

Gode investigation - On 10										
Codec Setting:	AMR 12.2kbps	AMR 7.95kbps	AMR 4.75kbps	Orientation	Channel					
ABM1 (dBA/m)	1.66	1.62	1.46		9400					
ABM2 (dBA/m)	-54.69	-54.90	-55.11	Axial						
Frequency Response	Pass	Pass	Pass	Axiai						
S+N/N (dB)	56.35	56.52	56.57							

- Mute on; Backlight off; Max Volume; Max Contrast
- TPC="All 1s"



**Audio Band Magnetic Curve Measurement Block Diagram** 

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager		
Filename:	Test Dates:	DUT Type:		Page 35 of 97		
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 35 of 97		

Table 9-1 **Consolidated Tabled Results** 

_		COIIS	Ullua	ieu i	abiec	ı Nes	นแจ		
		Freq. Response Margin		Magnetic Intensity Verdict		FCC SNNR Verdict		Margin from FCC Limit	C63.19-2011
		8.3	3.2	8.	3.1	8.	3.4	(dB)	Rating
C63.19	9 Section	Axial	Radial	Axial	Radial	Axial	Radial	( )	
	Secondary Cellular	PASS	NA	PASS	PASS	PASS	PASS		
CDMA	Cellular	PASS	NA NA	PASS	PASS	PASS	PASS	-15.96	T4
CDIMA								-15.56	14
	PCS	PASS	NA	PASS	PASS	PASS	PASS		
EvDO	Secondary Cellular	PASS	NA	PASS	PASS	PASS	PASS		
(OTT VoIP)	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-32.72	T4
,	PCS	PASS	NA	PASS	PASS	PASS	PASS		
	Cellular	PASS	NA	PASS	PASS	PASS	PASS		
GSM	PCS	PASS	NA	PASS	PASS	PASS	PASS	-3.20	Т3
EDGE	Cellular	PASS	NA	PASS	PASS	PASS	PASS		
(OTT VoIP)	PCS	PASS	NA	PASS	PASS	PASS	PASS	-14.51	T4
	Cellular	PASS	NA.	PASS	PASS	PASS	PASS		
UMTS	AWS	PASS	NA NA	PASS	PASS	PASS	PASS	-28.79	T4
UNIS								-20.79	14
	PCS	PASS	NA	PASS	PASS	PASS	PASS		
псь	Cellular	PASS	NA	PASS	PASS	PASS	PASS		
HSPA (OTT VoIP)	AWS	PASS	NA	PASS	PASS	PASS	PASS	-34.17	T4
(270)	PCS	PASS	NA	PASS	PASS	PASS	PASS		
	B71	PASS	NA	PASS	PASS	PASS	PASS		
	B12	PASS	NA	PASS	PASS	PASS	PASS		
	B13	PASS	NA NA	PASS	PASS	PASS	PASS		
									Т4
	B14	PASS	NA	PASS	PASS	PASS	PASS		
	B26	PASS	NA	PASS	PASS	PASS	PASS		
LTE FDD	B5	PASS	NA	PASS	PASS	PASS	PASS	-19.57	
	B66	PASS	NA	PASS	PASS	PASS	PASS		
	B2	PASS	NA	PASS	PASS	PASS	PASS		
	B25	PASS	NA	PASS	PASS	PASS	PASS		
	B30	PASS	NA	PASS	PASS	PASS	PASS		
	B7	PASS	NA	PASS	PASS	PASS	PASS		
	Di .	17.00	164	17400	1700	1700	1700		
LTE FDD (OTT VoIP)	B71	PASS	NA	PASS	PASS	PASS	PASS	-30.22	T4
	B41 (PC3)	PASS	NA	PASS	PASS	PASS	PASS		
LTE TDD	B41 (PC2)	PASS	NA	PASS	PASS	PASS	PASS	-7.67	Т3
2.2.00	B48	PASS	NA.	PASS	PASS	PASS	PASS		
	D40	1700	INA	FAUG	1700	1700	1700		
LTE TDD (OTT VoIP)	B41 (PC2)	PASS	NA	PASS	PASS	PASS	PASS	-19.77	T4
NR FDD (OTT VoIP)	n30	NA	NA	PASS	PASS	PASS	PASS	-25.37	T4
NR TDD (OTT VoIP)	n41 (PC2) ANT E	NA	NA	PASS	PASS	PASS	PASS	-5.92	Т3
	IEEE 802.11b	PASS	NA	PASS	PASS	PASS	PASS		
	IEEE 802.11g	PASS	NA NA	PASS	PASS	PASS	PASS		
10/1 441								-13.44	T4
WLAN	IEEE 802.11n	PASS	NA	PASS	PASS	PASS	PASS	-13.44	14
	IEEE 802.11ax SU	PASS	NA	PASS	PASS	PASS	PASS		
	IEEE 802.11ax RU	PASS	NA	PASS	PASS	PASS	PASS		
	IEEE 802.11b	PASS	NA	PASS	PASS	PASS	PASS		
	IEEE 802.11g	PASS	NA	PASS	PASS	PASS	PASS	-27.82	Т4
WLAN (OTT VoIP)	IEEE 802.11n	PASS	NA	PASS	PASS	PASS	PASS		
(OTT VOIP)	IEEE 802.11ax SU	PASS	NA	PASS	PASS	PASS	PASS		
	IEEE 802.11ax RU	PASS	NA.	PASS	PASS	PASS	PASS		
	IEEE 802.11a	PASS	NA NA	PASS	PASS	PASS	PASS		
U-NII	IEEE 802.11n	PASS	NA	PASS	PASS	PASS	PASS	-12.68	T.
	IEEE 802.11ac	PASS	NA	PASS	PASS	PASS	PASS		T4
	IEEE 802.11ax SU	PASS	NA	PASS	PASS	PASS	PASS		
	IEEE 802.11ax RU	PASS	NA	PASS	PASS	PASS	PASS		
	IEEE 802.11a	PASS	NA	PASS	PASS	PASS	PASS		
	IEEE 002.11a						DAGG	1	
	IEEE 802.11a	PASS	NA	PASS	PASS	PASS	PASS		
U-NII	IEEE 802.11n	PASS PASS						-26 46	T4
U-NII (OTT VoIP)	IEEE 802.11n	PASS	NA	PASS	PASS	PASS	PASS	-26.46	Т4
	IEEE 802.11n							-26.46	T4

FCC ID: A3LSMG998U	PCTEST Thought to be port of the received	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager		
Filename:	Test Dates:	DUT Type:		Page 36 of 97		
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 36 01 97		

© 2020 PCTEST REV 3.4.M

### I. Raw Handset Data

Table 9-2 **Raw Data Results for CDMA** 

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		476	0.38	-49.73		2.00	50.11	20.00	-30.11	T4	
	Axial	564	0.34	-49.64	-63.82	2.00	49.98	20.00	-29.98	T4	1.4, 1.2
Secondary		684	0.41	-49.86		2.00	50.27	20.00	-30.27	T4	
Cellular		476	-6.79	-43.88			37.09	20.00	-17.09	T4	l
	Radial	564	-6.94	-44.21	-63.87	N/A	37.27	20.00	-17.27	T4	1.4, 0.4
		684	-6.92	-44.46			37.54	20.00	-17.54	T4	
		1013	0.29	-49.48		2.00	49.77	20.00	-29.77	T4	]
	Axial	384	0.51	-49.40	-63.82	2.00	49.91	20.00	-29.91	T4	1.4, 1.2
Cellular		777	0.31	-48.83		2.00	49.14	20.00	-29.14	T4	
Celiulai		1013	-6.63	-44.83			38.20	20.00	-18.20	T4	
	Radial	384	-6.96	-44.46	-63.87	N/A	37.50	20.00	-17.50	T4	1.4, 0.4
		777	-6.40	-43.30			36.90	20.00	-16.90	T4	
		25	0.55	-51.72		2.00	52.27	20.00	-32.27	T4	
	Axial	600	0.67	-51.99	-63.82	2.00	52.66	20.00	-32.66	T4	1.4, 1.2
PCS		1175	0.48	-51.62		2.00	52.10	20.00	-32.10	T4	
FCS		25	-6.29	-43.20			36.91	20.00	-16.91	T4	
	Radial	600	-6.56	-43.26	-63.87	N/A	36.70	20.00	-16.70	T4	1.4, 0.4
		1175	-6.92	-42.88			35.96	20.00	-15.96	T4	

Table 9-3 **Raw Data Results for GSM** 

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		128	1.91	-38.77		2.00	40.68	20.00	-20.68	T4	
	Axial	190	1.79	-38.62	-63.82	2.00	40.41	20.00	-20.41	T4	1.4, 1.2
GSM850		251	1.86	-39.39		2.00	41.25	20.00	-21.25	T4	
GSIVIOSU	Radial	128	-5.76	-29.31			23.55	20.00	-3.55	Т3	
	Radial	190	-5.74	-28.94	-63.87	N/A	23.20	20.00	-3.20	Т3	1.6, 0.0
		251	-5.80	-29.13			23.33	20.00	-3.33	Т3	
		512	1.62	-42.83		2.00	44.45	20.00	-24.45	T4	
	Axial	661	1.69	-42.80	-63.82	1.95	44.49	20.00	-24.49	T4	1.4, 1.2
GSM1900		810	1.63	-42.92		2.00	44.55	20.00	-24.55	T4	
G3W1900		512	-4.55	-31.43			26.88	20.00	-6.88	T3	
	Radial	661	-4.58	-30.92	-63.87	N/A	26.34	20.00	-6.34	T3	1.4, 0.4
		810	-4.58	-31.03			26.45	20.00	-6.45	T3	

Table 9-4 **Raw Data Results for UMTS** 

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		4132	1.16	-55.05		2.00	56.21	20.00	-36.21	T4	
	Axial	4183	1.17	-54.84	-63.82	2.00	56.01	20.00	-36.01	T4	1.4, 1.2
UMTS V		4233	1.17	-54.97		2.00	56.14	20.00	-36.14	T4	
OWISV		4132	-4.75	-53.89			49.14	20.00	-29.14	T4	
	Radial	4183	-4.75	-53.80	-63.87	N/A	49.05	20.00	-29.05	T4	1.4, 0.4
		4233	-4.75	-53.54			48.79	20.00	-28.79	T4	
		1312	1.20	-54.92		2.00	56.12	20.00	-36.12	T4	
	Axial	1412	1.19	-54.98	-63.82	2.00	56.17	20.00	-36.17	T4	1.4, 1.2
		1513	1.18	-55.13		2.00	56.31	20.00	-36.31	T4	
UMTS IV		1312	-4.74	-54.00			49.26	20.00	-29.26	T4	
	Radial	1412	-4.75	-54.24	-63.87	N/A	49.49	20.00	-29.49	T4	1.4, 0.4
		1513	-4.75	-53.84			49.09	20.00	-29.09	T4	
		9262	1.24	-55.01		2.00	56.25	20.00	-36.25	T4	
	Axial	9400	1.24	-55.06	-63.82	2.00	56.30	20.00	-36.30	T4	1.4, 1.2
		9538	1.21	-54.95		2.00	56.16	20.00	-36.16	T4	
UMTS II		9262	-4.72	-54.06			49.34	20.00	-29.34	T4	
	Radial	9400	-4.71	-54.07	-63.87	N/A	49.36	20.00	-29.36	T4	1.4, 0.4
		9538	-4.72	-53.81			49.09	20.00	-29.09	T4	, 0.4

FCC ID: A3LSMG998U	PCTEST*	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Daga 27 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 37 of 97
© 2020 PCTEST		·		REV 3.4.M

# Table 9-5 Raw Data Results for LTE B71

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates			
		20MHz	133297	0.70	-50.51		2.00	51.21	20.00	-31.21	T4				
	Avial	15MHz	133297	0.73	-50.12	-63.82	2.00	50.85	20.00	-30.85	T4	1.4. 1.2			
Axial	10MHz	133297	0.62	-49.43	-03.02	2.00	50.05	20.00	-30.05	T4	1.4, 1.2				
I TE Band 71	LTE Rand 71	5MHz	133297	0.67	-49.54		2.00	50.21	20.00	-30.21	T4				
LIE Ballu / I	LTE Band 71	20MHz	133297	-5.69	-49.79			44.10	20.00	-24.10	T4				
	Radial	15MHz	133297	-5.69	-48.68	-63.87	-63.87	62.07	8 -63.87 N/A	NI/A	42.99	20.00	-22.99	T4	1.4. 0.4
		10MHz	133297	-5.69	-49.06			IWA	43.37	20.00	-23.37	T4	1.4, 0.4		
		5MHz	133297	-5.70	-48.41			42.71	20.00	-22.71	T4				

# Table 9-6 Raw Data Results for LTE B12

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates	
		10MHz	23095	0.76	-50.06		2.00	50.82	20.00	-30.82	T4		
	Avial	5MHz	23095	0.76	-50.61	-63.82	2.00	51.37	20.00	-31.37	T4	1.4. 1.2	
	Axial  LTE Band 12	3MHz	23095	0.87	-51.45	-03.02	2.00	52.32	20.00	-32.32	T4	1.4, 1.2	
I TE Band 12		1.4MHz	23095	0.80	-52.60		2.00	53.40	20.00	-33.40	T4		
LIE Ballu 12		10MHz	23095	-5.50	-50.06			44.56	20.00	-24.56	T4		
	Radial	5MHz	23095	-5.54	-49.14	62.07	N/A	43.60	20.00	-23.60	T4	1.4. 0.4	
	Radiai	3MHz	23095	-5.52	-48.93	-63.87	-63.87 N/A	NVA	43.41	20.00	-23.41	T4	1.4, 0.4
		1.4MHz	23095	-5.68	-48.72			43.04	20.00	-23.04	T4		

# Table 9-7 Raw Data Results for LTE B13

	Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
			10MHz	23230	0.70	-49.23		2.00	49.93	20.00	-29.93	T4	
	Axial  LTE Band 13  Radial	5MHz	23255	0.78	-48.65	-63.82	2.00	49.43	20.00	-29.43	T4	1.4. 1.2	
		5MHz	23230	0.74	-48.49		2.00	49.23	20.00	-29.23	T4	1.4, 1.2	
-		5MHz	23205	0.82	-49.80		2.00	50.62	20.00	-30.62	T4		
		10MHz	23230	-5.69	-49.47	00.07	-63.87 N/A	N/A	43.78	20.00	-23.78	T4	1.4. 0.4
		Naulai	5MHz	23230	-5.69	-50.61		7 N/A	44.92	20.00	-24.92	T4	1.4, 0.4

# Table 9-8 Raw Data Results for LTE B14

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
	Axial	10MHz	23330	0.75	-49.22	-63.82	2.00	49.97	20.00	-29.97	T4	1.4. 1.2
I TE Bond 14		5MHz	23330	0.72	-49.54	-03.02	2.00	50.26	20.00	-30.26	T4	1.4, 1.2
LIE Ballu 14	LTE Band 14	10MHz	23330	-5.69	-50.41	-63.87	N/A	44.72	20.00	-24.72	T4	1.4. 0.4
	radial	5MHz	23330	-5.70	-49.46	-03.07	IWA	43.76	20.00	-23.76	T4	1.4, 0.4

# Table 9-9 Raw Data Results for LTE B26

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		15MHz	26865	0.80	-49.73		2.00	50.53	20.00	-30.53	T4	
		10MHz	26865	0.81	-50.24		2.00	51.05	20.00	-31.05	T4	
	Axial	5MHz	26865	0.79	-50.02	-63.82	1.97	50.81	20.00	-30.81	T4	1.4, 1.2
		3MHz	26865	0.82	-50.44		2.00	51.26	20.00	-31.26	T4	
LTE Band 26		1.4MHz	26865	0.76	-52.38		2.00	53.14	20.00	-33.14	T4	
LIE Ballu 20		15MHz	26865	-5.75	-49.10			43.35	20.00	-23.35	T4	
		10MHz	26865	-5.72	-49.14			43.42	20.00	-23.42	T4	
	Radial	5MHz	26865	-5.73	-48.88	-63.87	N/A	43.15	20.00	-23.15	T4	1.4, 0.4
		3MHz	26865	-5.71	-49.69			43.98	20.00	-23.98	T4	
		1.4MHz	26865	-5.78	-49.62			43.84	20.00	-23.84	T4	

# Table 9-10 Raw Data Results for LTE B5

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		10MHz	20525	0.79	-51.49		2.00	52.28	20.00	-32.28	T4	
	Avial	5MHz	20525	0.73	-52.22	-63.82	2.00	52.95	20.00	-32.95	T4	1.4. 1.2
	Axial  LTE Band 5	3MHz	20525	0.83	-52.58	-03.02	2.00	53.41	20.00	-33.41	T4	1.4, 1.2
LTE Dead 6		1.4MHz	20525	0.76	-52.61	1 [	2.00	53.37	20.00	-33.37	T4	
LIE Band 5		10MHz	20525	-5.72	-49.74	-63.87		44.02	20.00	-24.02	T4	
	Radial	5MHz	20525	-5.71	-49.34		CO 07	43.63	20.00	-23.63	T4	1.4. 0.4
	radial	3MHz	20525	-5.74	-49.44		-63.87 N/A	IWA	43.70	20.00	-23.70	T4
		1.4MHz	20525	-5.73	-48.99			43.26	20.00	-23.26	T4	

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 38 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 30 01 97

# Table 9-11 Raw Data Results for LTE B66

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates		
		20MHz	132322	1.02	-54.33		2.00	55.35	20.00	-35.35	T4			
		15MHz	132322	0.99	-54.34		2.00	55.33	20.00	-35.33	T4	1		
	Axial	10MHz	132322	1.06	-53.70	-63.82	2.00	54.76	20.00	-34.76	T4	1.4, 1.2		
	Axiai	5MHz	132322	1.04	-54.35	-03.02	2.00	55.39	20.00	-35.39	T4	1.4, 1.2		
		3MHz	132322	1.09	-53.97		2.00	55.06	20.00	-35.06	T4	Ī		
LTE Band 66	TT D	1.4MHz	132322	0.82	-54.43		2.00	55.25	20.00	-35.25	T4			
LIE Band 66		20MHz	132322	-5.76	-48.69			42.93	20.00	-22.93	T4			
		15MHz	132322	-5.73	-47.36			41.63	20.00	-21.63	T4	1		
	Radial	10MHz	132322	-5.75	-49.30	-63.87	-63.87 N/A	62.07	NUA	43.55	20.00	-23.55	T4	1.4. 0.4
	Radiai	5MHz	132322	-5.75	-48.87			NVA	43.12	20.00	-23.12	T4	1.4, 0.4	
		3MHz	132322	-5.74	-48.90				43.16	20.00	-23.16	T4	1	
		1.4MHz	132322	-5.74	-49.80			44.06	20.00	-24.06	T4			

# Table 9-12 Raw Data Results for LTE B25

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	26365	0.86	-54.07		2.00	54.93	20.00	-34.93	T4	
		15MHz	26365	0.84	-54.10		2.00	54.94	20.00	-34.94	T4	
	Axial	10MHz	26365	0.78	-54.35	-63.82	2.00	55.13	20.00	-35.13	T4	1.4, 1.2
	Axidi	5MHz	26365	0.93	-53.92	-03.02	2.00	54.85	20.00		T4	
		3MHz	26365	0.84	-54.23		2.00	55.07 <b>20.00</b>	20.00	-35.07	T4	
LTE Band 25		1.4MHz	26365	0.80	-54.61		2.00	55.41	20.00	-35.41	T4	
LIE Band 25		20MHz	26365	-5.74	-49.23			43.49	20.00	-23.49	T4	
		15MHz	26365	-5.77	-49.45			43.68	20.00	-34.93 -34.94 -35.13 -34.85 -35.07 -35.41	T4	
	Destini	10MHz	26365	-5.78	-49.58	62.07	N//A	43.80	20.00	-23.80	T4	4404
	Radial	5MHz	26365	-5.80	-48.30	-63.87	N/A	42.50	20.00	-22.50	T4	1.4, 0.4
		3MHz	26365	-5.78	-49.42	2		43.64	20.00	-23.64	T4	
		1.4MHz	26365	-5.77	-49.16			43.39	20.00	-23.39	T4	

# Table 9-13 Raw Data Results for LTE B2

	ARM4 ARM2 Ambient Noice Frequency Salvis ECC Limit Margin from C52 49 2041 Tort													
Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates		
		20MHz	18900	1.29	-54.06		2.00	55.35	20.00	-35.35	T4			
		15MHz	18900	0.93	-54.39		2.00	55.32	20.00	-35.32	T4			
	Axial	10MHz	18900	0.89	-54.28	-63.82	2.00	55.17	20.00	-35.17	T4	1.4, 1.2		
	Axiai	5MHz	18900	0.89	-53.71	-03.02	2.00	54.60	20.00	20.00 -35.17 T 20.00 -34.60 T 20.00 -34.78 T 20.00 -35.33 T	T4	1.4, 1.2		
		3MHz	18900	0.90	-53.88		2.00	54.78	20.00	-34.78	T4			
LTE Band 2		1.4MHz	18900	0.84	-54.49		2.00	55.33	20.00	-35.33	T4			
LIE Band 2		20MHz	18900	-5.73	-49.05			43.32	20.00	-23.32	T4			
		15MHz	18900	-5.77	-49.38			43.61	20.00	-35.35 -35.32 -35.17 -34.60 -34.78 -35.33	T4			
	Radial	10MHz	18900	-5.74	-49.77	-63.87	N/A	44.03	20.00	-24.03	T4	1.4. 0.4		
	radial	5MHz	18900	-5.82	-48.78	-03.07	IVA	42.96		-22.96	T4	1.4, 0.4		
		3MHz	18900	-5.77	-49.41			43.64	20.00	-23.64	T4			
		1.4MHz	18900	-5.74	-49.78			44.04	20.00	-24.04	T4			

# Table 9-14 Raw Data Results for LTE B30

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
	Axial	10MHz	27710	0.81	-53.23	-63.82	1.95	54.04	20.00	-34.04	T4	1.4, 1.2
LTE Ban		5MHz	27710	0.75	-53.71	-03.02	2.00	54.46	20.00	-34.46	T4	
LIEBan	Radial	10MHz	27710	-5.75	-46.46	62.07	NVA	40.71	20.00	-20.71	T4	1.4. 0.4
	Radiai	5MHz	27710	-5.77	-48.94	-63.87	87 N/A	43.17	20.00	-23.17	T4	1.4, 0.4

# Table 9-15 Raw Data Results for LTE B7

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	21100	0.81	-52.78		2.00	53.59	20.00	-33.59	T4	
	Axial	15MHz	21100	0.80	-52.90	-63.82	2.00	53.70	20.00	-33.70	T4	1.4. 1.2
	Axidi	10MHz	21100	0.84	-52.89	-03.02	2.00		20.00	-33.73	T4	1.4, 1.2
		5MHz	21100	0.81	-52.57		1.95	53.38	20.00	-33.38	T4	
LTE Band 7		20MHz	21100	-5.77	-46.63			40.86	53.38 <b>20.00</b> 40.86 <b>20.00</b> 40.08 <b>20.00</b>	-20.86	T4	
LIE Ballu /		15MHz	21100	-5.76	-45.84			40.08	20.00	FCC Limit (dB) -33.59 -33.70 -33.73 -33.38	T4	
	D-4:-I	10MHz	21100	-5.75	-46.31	62.07	N/A	40.56	20.00	-20.56	T4	1.4. 0.4
	Radial	5MHz	21425	-5.77	-45.34	-63.87	N/A	39.57	20.00	-19.57	T4	1.4, 0.4
		5MHz	21100	-5.77	-45.44			39.67	20.00	-19.67	T4	
		5MHz	20775	-5.80	-46.30			40.50	20.00	-20.50	T4	

FCC ID: A3LSMG998U	PCTEST* Proof to be part of ® secured	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Daga 20 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 39 of 97

# Table 9-16 Raw Data Results for LTE B41 Power Class 3

										_		
Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	40620	0.69	-48.90		2.00	49.59	20.00	-29.59	T4	
	Axial	15MHz	40620	0.64	-49.07	-63.82	2.00	49.71	20.00	-29.71	T4	1.4. 1.2
	Axiai	10MHz	40620	0.71	-48.37	-03.02	2.00	49.08	20.00	-29.08	T4	1.4, 1.2
LTE Band 41		5MHz	40620	0.63	-48.83		2.00	49.46	20.00	-29.46	T4	
LIE Ballu 41	Radial	20MHz	40620	-5.70	-38.65	-63.87	N/A	32.95	20.00	-12.95	T4	
		15MHz	40620	-5.71	-38.51			32.80	20.00	-12.80	T4	1.4. 0.4
	Radiai	10MHz	40620	-5.74	-38.67	-03.07	IWA	32.93	20.00	-12.93	T4	1.4, 0.4
		5MHz	40620	-5.75	-38.41	-		32.66	20.00	-12.66	T4	

# Table 9-17 Raw Data Results for LTE B41 Power Class 2

					ADMA ADMA ADMA FEGUREY SAND FEGUREY Margin from Cos 40 2004 Taul													
Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates						
		20MHz	40620	0.74	-46.10		2.00	46.84	20.00	-26.84	T4							
		15MHz	40620	0.71	-45.66		2.00	46.37	20.00	-26.37	T4	1						
		10MHz	40620	0.70	-45.72		2.00	46.42	20.00	-26.42	T4							
	Axial	5MHz	41490	0.75	-44.25	-63.82	2.00	45.00	20.00	-25.00	T4	4440						
	Axiai	5MHz	41055	0.81	-46.82	-03.02	2.00	47.63	20.00	-27.63	T4	1.4, 1.2						
		5MHz	40620	0.73	-45.59		2.00	46.32	20.00	0 -25.00 0 -27.63 0 -26.32 0 -27.72 0 -25.71 0 -9.29	T4	1						
		5MHz	40185	0.81	-46.91		2.00	47.72	20.00	-27.72	T4							
LTE Band 41	-	5MHz	39750	0.79	-44.92		2.00	45.71	20.00	-25.71	T4							
LIE Ballu 41		20MHz	40620	-5.76	-35.05		2.00	29.29	20.00	-9.29	Т3							
		15MHz	41490	-5.76	-33.43			27.67	20.00	t FCC Limit (6B) (6B) (78 ming) (78	Т3	1						
		15MHz	41055	-5.72	-35.93			30.21	20.00		T4							
	Radial	15MHz	40620	-5.77	-34.63	-63.87	N/A	28.86	20.00	-8.86	Т3	1.4. 0.4						
	radial	15MHz	40185	-5.77	-36.08	-03.07	IVA	30.31	20.00	-10.31	T4	1.4, 0.4						
		15MHz	39750	-5.75	-35.74			29.99	20.00	-9.99	T3	]						
		10MHz	40620	-5.77	-34.77	77		29.00	20.00	-9.00	Т3							
		5MHz	40620	-5.72	-34.68			28.96	20.00	-8.96	T3	1						

# Table 9-18 Raw Data Results for LTE B48

	Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response	S+N/N (dB)	FCC Limit	FCC Limit	C63.19-2011	Test Coordinates
							1	Margin (dB)			(dB)		
			20MHz	55990	0.76	-46.31		2.00	47.07	20.00	-27.07	T4	
	LTE Band 48	Axial	15MHz	55990	0.80	-46.13	-63.82	2.00	46.93	20.00	-26.93	T4	1.4. 1.2
		_	10MHz	55990	0.81	-46.09		2.00	46.90	20.00	-26.90	T4	1.4, 1.2
			5MHz	55990	0.78	-46.07		2.00	46.85	20.00	-26.85	T4	
			20MHz	55990	-5.80	-37.18		N/A	31.38	20.00	-11.38	T4	
			15MHz	55990	-5.80	-36.89			31.09	20.00	-11.09	T4	1.4. 0.4
		Naulai	10MHz	55990	-5.80	-37.07	-03.67	INA	31.27		-11.27	T4	1.4, 0.4
			5MHz	55990	-5.81	-37.13			31.32	20.00	-11.32	T4	

# Table 9-19 Raw Data Results for 2.4GHz WIFI

RAW DAILA RESUITS TOT 2.4GFIZ VVIFT													
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates		
IEEE	Axial	6	-2.80	-47.86	-64.49	2.00	45.06	20.00	-25.06	T4	1.4, 1.2		
802.11b	Radial	6	-10.22	-45.64	-62.99	N/A	35.42	20.00	-15.42	T4	1.4, 0.4		
IEEE	Axial	6	-2.86	-47.31	-64.49	2.00	44.45	20.00	-24.45	T4	1.4, 1.2		
802.11g	Radial	6	-10.31	-44.86	-62.99	N/A	34.55	20.00	-14.55	T4	1.4, 0.4		
		1	-2.71	-45.98		2.00	43.27	20.00	-23.27	T4			
IEEE	Axial	6	-2.84	-46.18	-64.49	2.00	43.34	20.00	-23.34	T4	1.4, 1.2		
802.11n		11	-2.98	-46.78		2.00	43.80	20.00	-23.80	T4			
	Radial	6	-10.36	-45.08	-62.99	N/A	34.72	20.00	-14.72	T4	1.4, 0.4		
IEEE	Axial	6	-2.86	-46.73	-64.49	2.00	43.87	20.00	-23.87	T4	1.4, 1.2		
802.11ax SU	Radial	6	-10.40	-44.66	-62.99	N/A	34.26	20.00	-14.26	T4	1.4, 0.4		
	Axial	6	-2.69	-46.26	-64.49	2.00	43.57	20.00	-23.57	T4	1.4, 1.2		
IEEE		1	-10.62	-44.88			34.26	20.00	-14.26	T4			
802.11ax RU	Radial	6	-10.52	-43.96	-62.99	N/A	33.44	20.00	-13.44	T4	1.4, 0.4		
		11	-10.64	-44.95			34.31	20.00	-14.31	T4			

# Table 9-20 Raw Data Results for 5GHz WIFI IEEE 802.11a

Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
	Axial	20MHz	1	40	-2.38	-47.87	-64.49	1.95	45.49	20.00	-25.49	T4	1.4, 1.2
IEEE 802.11	a												
	Radial	20MHz	1	40	-10.56	-45.74	-62.99	N/A	35.18	20.00	-15.18	T4	1.4, 0.4

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 40 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 40 01 97

# Table 9-21 Raw Data Results for 5GHz WIFI IEEE 802.11n

	Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates	
ı		Avial	40MHz	1	38	-2.59	-45.68	64.40	2.00	43.09	20.00	-23.09	T4	1.4. 1.2	
١	IEEE	Axial	20MHz	1	40	-2.49	-46.33	-64.49	1.96	43.84	20.00	-23.84	T4	1.4, 1.2	
١															
	002.1111	02.11n Radial	40MHz	1	38	-10.63	-45.13	-62.99	NA	34.50	20.00	-14.50	T4	1.4. 0.4	
	Radi	Raulai	20MHz	1	40	-10.65	-45.24	-02.99	IVA	34.59	20.00	-14.59	T4	1.4, 0.4	

# Table 9-22 Raw Data Results for 5GHz WIFI IEEE 802.11ac

	Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		Axial	40MHz	1	38	-2.36	-45.64	-64.49	2.00	43.28	20.00	-23.28	T4	1.4. 1.2
	urer.	Axiai	20MHz	1	40	-2.40	-47.38	-04.49	2.00	44.98	20.00	-24.98	T4	1.4, 1.2
	802.11ac													
		Radial	40MHz	1	38	-10.69	-45.63	-62.99	NA	34.94	20.00	-14.94	T4	1.4. 0.4
		radial	20MHz	1	40	-10.61	-43.59	-02.99	IVA	32.98	20.00	-12.98	T4	1.4, 0.4

Table 9-23
Raw Data Results for 5GHz WIFI IEEE 802.11ax

Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		40MHz	- 1	38	-2.95	-46.03		2.00	43.08	20.00	-23.08	T4	
		20MHz	1	36	-2.95	-46.78		2.00	43.83	20.00	-23.83	T4	
		20MHz	1	40	-2.94	-45.13		2.00	42.19	20.00	-22.19	T4	
		20MHz	1	48	-2.77	-46.33		2.00	43.56	20.00	-23.56	T4	
	Axial	40MHz	2A	54	-2.94	-45.92	-64.49	2.00	42.98	20.00	-22.98	T4	1.4, 1.2
IEEE	Axiai	20MHz	2A	56	-2.90	-46.23	-04.49	2.00	43.33	20.00	-23.33	T4	1.4, 1.2
802.11ax SU		40MHz	2C	118	-2.91	-45.32		2.00	42.41	20.00	-22.41	T4	
002.11ax 30		20MHz	2C	120	-2.73	-46.58		2.00	43.85	20.00	-23.85	T4	
		40MHz	3	151	-2.93	-46.75		2.00	43.82	20.00	-23.82	T4	
		20MHz	3	157	-2.78	-45.73		2.00	42.95	20.00	-22.95	T4	
	Radial	40MHz	1	38	-10.58	-44.38	-62.99	N/A	33.80	20.00	-13.80	T4	1.4. 0.4
	Raulai	20MHz	1	40	-10.48	-44.81	-02.99	IVA	34.33	20.00	-14.33	T4	1.4, 0.4
	Axial	40MHz	1	38	-2.96	-45.97	-64.49	2.00	43.01	20.00	-23.01	T4	1.4, 1.2
	AXIdi	20MHz	1	40	-2.95	-46.15	-04.49	2.00	43.20	20.00	-23.20	T4	1.4, 1.2
		40MHz	1	38	-10.55	-43.32			32.77	20.00	-12.77	T4	
		40MHz	1	46	-10.68	-43.36			32.68	20.00	-12.68	T4	
IEEE		20MHz	1	40	-10.55	-44.68			34.13	20.00	-14.13	T4	
802.11ax RU		40MHz	2A	54	-10.57	-44.11			33.54	20.00	-13.54	T4	
	Radial	20MHz	2A	56	-10.57	-45.04	-62.99	N/A	34.47	20.00	-14.47	T4	1.4, 0.4
		40MHz	2C	118	-10.69	-44.52			33.83	20.00	-13.83	T4	
		20MHz	2C	120	-10.57	-45.44			34.87	20.00	-14.87	T4	
		40MHz	3	151	-10.69	-44.03			33.34	20.00	-13.34	T4	
		20MHz	3	157	-10.63	-44.68			34.05	20.00	-14.05	T4	l

# Table 9-24 Raw Data Results for EvDO (OTT VoIP)

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates		
Secondary Cellular	Axial	564	11.62	-51.82	-64.26	1.56	63.44	20.00	-43.44	T4	1.4, 1.2		
EvDO	Radial	564	3.42	-50.42	-62.99	N/A	53.84	20.00	-33.84	T4	1.4, 0.4		
Cellular	Axial	384	11.77	-50.97	-64.26	1.32	62.74	20.00	-42.74	T4	1.4, 1.2		
EvDO	Radial	384	3.23	-50.88	-62.99	N/A	54.11	20.00	-34.11	T4	1.4, 0.4		
PCS	Axial	600	11.91	-48.87	-64.26	1.23	60.78	20.00	-40.78	T4	1.4, 1.2		
EvDO	Radial	600	3.29	-49.43	-62.99	N/A	52.72	20.00	-32.72	T4	1.4, 0.4		

# Table 9-25 Raw Data Results for EDGE (OTT VolP)

11411 2 414 114 414 114 114 114 114 114													
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates		
EDGE850	Axial	190	11.57	-40.78	-64.26	1.56	52.35	20.00	-32.35	T4	1.4, 1.2		
EDGE030	Radial	190	3.39	-31.12	-62.99	N/A	34.51	20.00	-14.51	T4	1.4, 0.4		
EDGE1900	Axial	661	11.62	-43.68	-64.26	1.48	55.30	20.00	-35.30	T4	1.4, 1.2		
EDGE1900	Radial	661	3.50	-35.43	-62.99	N/A	38.93	20.00	-18.93	T4	1.4, 0.4		

FCC ID: A3LSMG998U	Y Houd to be part of Sections		SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 41 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		raye 41 01 97

Table 9-26
Raw Data Results for HSPA (OTT VoIP)

	Naw Bata Nesalts for Hot A (CTT Voll)													
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates			
HSPA V	Axial	4183	11.53	-50.46	-64.26	1.50	61.99	20.00	-41.99	T4	1.4, 1.2			
пога у	Radial	4183	3.43	-50.91	-62.99	N/A	54.34	20.00	-34.34	T4	1.4, 0.4			
HSPA IV	Axial	1412	11.58	-51.88	-64.26	1.48	63.46	20.00	-43.46	T4	1.4, 1.2			
H3FA IV	Radial	1412	3.40	-50.77	-62.99	N/A	54.17	20.00	-34.17	T4	1.4, 0.4			
HSPA II	Axial	9400	11.73	-50.39	-64.26	1.76	62.12	20.00	-42.12	T4	1.4, 1.2			
HOFAII	Radial	9400	3.48	-50.71	-62.99	N/A	54.19	20.00	-34.19	T4	1.4, 0.4			

Table 9-27
Raw Data Results for LTE B71 (OTT VoIP)

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	133297	11.73	-49.07		1.52	60.80	20.00	-40.80	T4	
		15MHz	133297	11.50	-48.63		1.31	60.13	20.00	-40.13	T4	
	Axial	10MHz	133297	11.64	-48.86	-64.26	1.42	60.50	20.00	-40.50	T4	1.4. 1.2
	Axiai	5MHz	133447	11.42	-48.53	-04.20	1.57	59.95	20.00	-39.95	T4	1.4, 1.2
		5MHz	133297	11.62	-47.36		1.36	58.98	20.00	-38.98	T4	
LTE Band 71		5MHz	133147	11.66	-48.13		1.77	59.79	20.00	-39.79	T4	
LIE Band /1		20MHz	133297	3.46	-46.97			50.43	20.00	-30.43	T4	
		15MHz	133297	3.32	-47.77	1		51.09	20.00	-31.09	T4	
	Radial	10MHz	133422	3.40	-47.56	-62.99	N/A	50.96	20.00	-30.96	T4	1.4. 0.4
	radiai	10MHz	133297	3.34	-46.88	-62.99	N/A	50.22	20.00	-30.22	T4	1.4, 0.4
		10MHz	133172	3.32	-47.07			50.39	20.00	-30.39	T4	
		5MHz	133297	3.38	-47.52			50.90	20.00	-30.90	T4	

Table 9-28
Raw Data Results for LTE B41 Power Class 2 (OTT VoIP)

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	41490	11.39	-42.36		1.60	53.75	20.00	-33.75	T4	
		20MHz	41055	11.31	-42.67		1.80	53.98	20.00	-33.98	T4	
		20MHz	40620	11.44	-42.66		1.75	54.10	20.00	-34.10	T4	1
	Axial	20MHz	40185	11.33	-43.89	-64.26	1.55	55.22	20.00	-35.22	T4	1.4, 1.2
	Axidi	20MHz	39750	11.38	-43.64	-04.20	1.38	55.02	20.00	-35.02	T4	1.4, 1.2
		15MHz	40620	11.37	-42.85		1.41	54.22	20.00	-34.22	T4	
		10MHz	40620	11.30	-42.93		1.49	54.23	20.00	-34.23	T4	
LTE Band 41		5MHz	40620	11.39	-42.98		1.22	54.37	20.00	-34.37	T4	1
LIE Band 41		20MHz	40620	3.39	-37.74			41.13	20.00	-21.13	T4	
		15MHz	40620	3.52	-38.19			41.71	20.00	-21.71	T4	i
		10MHz	40620	3.59	-37.77			41.36	20.00	-21.36	T4	1
	Destini	5MHz	41490	3.42	-36.35	60.00	NIA	39.77	20.00	-19.77	T4	4404
	Radial	5MHz	41055	3.39	-38.64	-62.99	N/A	42.03	20.00	-22.03	T4	1.4, 0.4
		5MHz	40620	3.49	-37.59			41.08	20.00	-21.08	T4	1
		5MHz	40185	3.38	-38.55			41.93	20.00	-21.93	T4	
		5MHz	39750	3.43	-37.88			41.31	20.00	-21.31	T4	1

# Table 9-29 Raw Data Results for NR n30 (OTT VolP)

	Mode Orientation Bandwidth Channel ABM1.u: ABM2.u: ABM2.u: Ambient Noise Response S+NIN <sub>MX</sub> S+NIN <sub>MX</sub> 3-d B FCC Limit FCC Limi														
Mode	Orientation	Bandwidth	Channel	ABM1 <sub>LTE</sub> [dB(A/m)]	ABM2 <sub>NR</sub> [dB(A/m)]	ABM2 <sub>LTE</sub> [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N <sub>NR</sub> (dB)	S+N/N <sub>NR</sub> - 3 dB (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates	
		10MHz	462000	11.46	-46.53	-52.16			57.99	54.99	20.00	-34.99	T4		
	Axial	5MHz	462500	11.46	-44.61	-52.16	#N/A	N/A	56.07	53.07	20.00	-33.07	T4	1.4. 1.2	
	Axiai	5MHz	462000	11.46	-46.46	-52.16	#IN/A	N/A	57.92	54.92	20.00	-34.92	T4	1.4, 1.2	
NR n30		5MHz	461500	11.46	-47.13	-52.16			58.59	55.59	20.00	-35.59	T4		
NK IISU		10MHz	462000	3.33	-45.20	-48.29			48.53	45.53	20.00	-25.53	T4		
	Radial	5MHz	462500	3.33	-43.40	-48.29	#N/A	N/A	46.73	43.73	20.00	-23.73	T4	1.4. 0.4	
	Nadiai	5MHz	462000	3.33	-45.04	-48.29	#IVA	INA	48.37	45.37	20.00	-25.37	T4	134,034	
		5MHz	461500	3.33	-47.34	-48.29			50.67	47.67	20.00	-27.67	T4		

# **Table 9-30**

# Raw Data Results for LTE B30 (OTT VoIP – Additional Measurements for NR)

Mode	Orientation	Bandwidth	Channel	ABM1 <sub>LTE</sub> [dB(A/m)]	ABM2 <sub>NR</sub> [dB(A/m)]	ABM2 <sub>LTE</sub> [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N <sub>LTE</sub> (dB)	S+N/N <sub>NR</sub> -3 dB (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
LTE Band	Axial	10MHz	27710	11.46	N/A	-52.16	-64.49	N/A	62.55	N/A	20.00	-42.55	T4	1.4, 1.2
30	Radial	10MHz	27710	3.33	IVA	-48.29	-63.14	IVA	51.99	NA .	20.00	-31.99	T4	1.4, 0.4

FCC ID: A3LSMG998U	PCTEST*	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 42 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 42 01 97

**Table 9-31** Raw Data Results for NR n41 (OTT VoIP)

				Du.		Juito	101 14	· · · · ·	, Ο		,			
Mode	Orientation	Bandwidth	Channel	ABM1 <sub>LTE</sub> [dB(A/m)]	ABM2 <sub>NR</sub> [dB(A/m)]	ABM2 <sub>LTE</sub> [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N <sub>NR</sub> (dB)	S+N/N <sub>NR</sub> -3 dB (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		100MHz	518598	11.44	-31.77	-43.72			43.21	40.21	20.00	-20.21	T4	
		90MHz	518598	11.44	-31.44	-43.72	I		42.88	39.88	20.00	-19.88	T4	
		80MHz	518598	11.44	-31.32	-43.72			42.76	39.76	20.00	-19.76	T4	
		60MHz	518598	11.44	-30.90	-43.72	I		42.34	39.34	20.00	-19.34	T4	
		50MHz	532998	11.44	-33.96	-43.72	I		45.40	42.40	20.00	-22.40	T4	
	Axial	50MHz	525798	11.44	-31.67	-43.72	-64.49	N/A	43.11	40.11	20.00	-20.11	T4	1.4, 1.2
	Avidi	50MHz	518598	11.44	-30.02	-43.72	-04.45	INA	41.46	38.46	20.00	-18.46	T4	1.4, 1.2
		50MHz	511398	11.44	-34.95	-43.72			46.39	43.39	20.00	-23.39	T4	
		50MHz	504204	11.44	-34.35	-43.72	I		45.79	42.79	20.00	-22.79	T4	
		40MHz	518598	11.44	-30.35	-43.72			41.79	38.79	20.00	-18.79	T4	
		30MHz	518598	11.44	-30.53	-43.72			41.97	38.97	20.00	-18.97	T4	
NR n41		20MHz	518598	11.44	-30.93	-43.72			42.37	39.37	20.00	-19.37	T4	
NIC III		100MHz	518598	3.43	-26.80	-38.20			30.23	27.23	20.00	-7.23	T4	
		90MHz	518598	3.43	-26.28	-38.20	I		29.71	26.71	20.00	-6.71	T3	
		80MHz	518598	3.43	-27.46	-38.20			30.89	27.89	20.00	-7.89	T4	
		60MHz	518598	3.43	-25.58	-38.20			29.01	26.01	20.00	-6.01	T3	
		50MHz	518598	3.43	-25.67	-38.20	I		29.10	26.10	20.00	-6.10	T3	
	Radial	40MHz	534000	3.43	-25.49	-38.20	-63.14	N/A	28.92	25.92	20.00	-5.92	T3	1.4. 0.4
	, codidi	40MHz	526302	3.43	-26.97	-38.20	-55.14		30.40	27.40	20.00	-7.40	T4	1.4, 0.4
		40MHz	518598	3.43	-25.55	-38.20			28.98	25.98	20.00	-5.98	T3	
		40MHz	510900	3.43	-28.48	-38.20			31.91	28.91	20.00	-8.91	T4	
		40MHz	503202	3.43	-27.60	-38.20	I		31.03	28.03	20.00	-8.03	T4	
		30MHz	518598	3.43	-25.64	-38.20	I		29.07	26.07	20.00	-6.07	T3	
		20MHz	518598	3.43	-26.12	-38.20			29.55	26.55	20.00	-6.55	T3	Ì

# **Table 9-32**

# Raw Data Results for LTE B41 Power Class 2 (OTT VoIP – Additional Measurements for NR)

Mode	Orientation	Bandwidth	Channel	ABM1 <sub>LTE</sub> [dB(A/m)]	ABM2 <sub>NR</sub> [dB(A/m)]	ABM2 <sub>LTE</sub> [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N <sub>LTE</sub> (dB)	S+N/N <sub>NR</sub> -3 dB (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
LTE B41	Axial	20MHz	40620	11.44		-43.72	-64.49		54.35		20.00	-34.35	T4	1.4, 1.2
LIE B41	Radial	20MHz	40620	3.43	N/A	-38.20	-63.14	N/A	41.38	N/A	20.00	-21.38	T4	1.4, 0.4

### **Table 9-33** Raw Data Results for 2 4GHz WIFL (OTT VolP)

Raw Data Results for 2.4GHZ WIFT (OTT VOIP)											
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
IEEE	Axial	6	11.46	-49.96	-64.26	1.28	61.42	20.00	-41.42	T4	1.4, 1.2
802.11b	Radial	6	3.55	-46.45	-62.99	N/A	50.00	20.00	-30.00	T4	1.4, 0.4
IEEE	Axial	6	11.79	-48.72	-64.26	1.48	60.51	20.00	-40.51	T4	1.4, 1.2
802.11g	Radial	6	3.50	-45.06	-62.99	N/A	48.56	20.00	-28.56	T4	1.4, 0.4
		1	11.47	-49.22		1.35	60.69	20.00	-40.69	T4	
IEEE	Axial	6	11.96	-48.39	-64.26	1.36	60.35	20.00	-40.35	T4	1.4, 1.2
802.11n		11	11.81	-48.06		1.36	59.87	20.00	-39.87	T4	
	Radial	6	3.41	-46.34	-62.99	N/A	49.75	20.00	-29.75	T4	1.4, 0.4
IEEE	Axial	6	11.92	-48.65	-64.26	1.52	60.57	20.00	-40.57	T4	1.4, 1.2
802.11ax SU	Radial	6	3.51	-45.10	-62.99	N/A	48.61	20.00	-28.61	T4	1.4, 0.4
	Axial	6	11.67	-49.06	-64.26	1.52	60.73	20.00	-40.73	T4	1.4, 1.2
IEEE		1	3.63	-45.77		_	49.40	20.00	-29.40	T4	
802.11ax RU	Radial	6	3.40	-44.65	-62.99	N/A	48.05	20.00	-28.05	T4	1.4, 0.4
		11	3.39	-44.43			47.82	20.00	-27.82	T4	

# **Table 9-34** Raw Data Results for 5GHz WIFI IEEE 802.11a (OTT VoIP)

	Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
ſ	IEEE	Axial	20MHz	1	40	11.89	-47.86	-64.26	1.55	59.75	20.00	-39.75	T4	1.4, 1.2
	802.11a													
	002.114	Radial	20MHz	1	40	3.37	-48.40	-62.99	N/A	51.77	20.00	-31.77	T4	1.4, 0.4

# **Table 9-35** Raw Data Results for 5GHz WIFI IEEE 802.11n (OTT VoIP)

м	lode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		Axial	40MHz	1	38	11.86	-47.16	-64.26	1.32	59.02	20.00	-39.02	T4	1.4. 1.2
	IEEE	Axidi	20MHz	1	40	11.90	-48.00	-04.20	1.53	59.90	20.00	-39.90	T4	1.4, 1.2
	2.11n													
002		Radial	40MHz	1	38	3.37	-47.87	-62.99	NΑ	51.24	20.00	-31.24	T4	1.4, 0.4
		Naulai	20MHz	1	40	3.39	-47.81	-02.99	IVA	51.20	20.00	-31.20	T4	1.4, 0.4

FCC ID: A3LSMG998U	PCTEST Thought to be port of the received	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 43 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 43 01 91

**Table 9-36** Raw Data Results for 5GHz WIFI IEEE 802.11ac (OTT VoIP)

Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
	Axial	40MHz	1	38	11.85	-48.35	-64.26	1.47	60.20	20.00	-40.20	T4	1.4. 1.2
IEEE	Avidi	20MHz	1	40	11.74	-47.72	-04.20	1.42	59.46	20.00	-39.46	T4	1.4, 1.2
802.11ac													
002.11ac	Radial	40MHz	1	38	3.29	-46.50	00.00	NVA	49.79	20.00	-29.79	T4	1.4. 0.4
	radial	20MHz	1	40	3.39	-46.64	-62.99	-62.99 N/A	50.03	20.00	-30.03	T4	1.4, 0.4

**Table 9-37** Raw Data Results for 5GHz WIFI IEEE 802.11ax (OTT VoIP)

	170	w Dat	ane	รอนแอ	101 30	31 1Z V	AILI IEI		L. I Iax	(0)	ı von	7	
Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
	Axial	40MHz	1	38	11.91	-47.33	-64.26	1.55	59.24	20.00	-39.24	T4	1.4, 1.2
IEEE	Axiai	20MHz	1	40	11.63	-47.31	-04.20	1.54	58.94	20.00	-38.94	T4	1.4, 1.2
802.11ax SU													
002.11ax 00	D- d-l	40MHz	1	38	3.25	-44.44	-62.99	N/A	47.69	20.00	-27.69	T4	1.4. 0.4
	Radial	20MHz	1	40	3.18	-46.12	-02.99	NA	49.30	20.00	-29.30	T4	1.4, 0.4
		40MHz	1	38	11.81	-46.95		1.43	58.76	20.00	-38.76	T4	
		20MHz	1	40	11.59	-47.28		1.26	58.87	20.00	-38.87	T4	
		40MHz	2A	54	11.80	-47.75		1.34	59.55	20.00	-39.55	T4	
		20MHz	2A	52	11.65	-48.13	]	1.38	59.78	20.00	-39.78	T4	
	Axial	20MHz	2A	56	11.76	-45.93	-64.26	1.53	57.69	20.00	-37.69	T4	1.4. 1.2
	7 Olicii	20MHz	2A	64	11.73	-47.47	54.25	1.42	59.20	20.00	-39.20	T4	13-4, 13-2
		40MHz	2C	118	11.77	-46.78		1.46	58.55	20.00	-38.55	T4	
		20MHz	2C	120	11.69	-47.66		1.55	59.35	20.00	-39.35	T4	
		40MHz	3	151	11.59	-47.29		1.47	58.88	20.00	-38.88	T4	
IEEE		20MHz	3	157	11.57	-46.42		1.51	57.99	20.00	-37.99	T4	
802.11ax RU		401411							40.00				
		40MHz	1	38	3.31	-43.46			46.77	20.00	-26.77	T4	
		20MHz	1	40	3.47	-44.87	4		48.34	20.00	-28.34	T4	
		40MHz	2A	54	3.16	-43.30	-		46.46	20.00	-26.46	T4	
	Radial	40MHz 20MHz	2A 2A	62 56	3.40	-43.40 -46.18	-62.99	N/A	46.80 49.41	20.00	-26.80	T4 T4	1.4, 0.4
	Radiai	40MHz	2C	118	3.32		-02.99	NA	46.85	20.00	-29.41 -26.85	T4	1.4, 0.4
		20MHz	2C	120	3.43	-43.53 -43.95		47.38	20.00	-27.38	T4		
		40MHz	3	151	3.40			46.99	20.00	-26.99	T4		
		20MHz	3	157	3.58	-45.43	-43.59 -45.43		49.01	20.00	-29.01	T4	
		LOWINE	J	.07	0.00	-10.40			70.01	20.00	20.01		

### II. **Test Notes**

## A. General

- 1. Phone Condition: Mute on; Backlight off; Max Volume; Max Contrast
- 2. 'Radial' orientation refers to radial transverse.
- Hearing Aid Mode (Phone→Settings→Other Call Settings→Hearing aid Comaptibility) was set to ON for Frequency Response compliance
- 4. Speech Signal: 3GPP2 Normal Test Signal
- 5. Bluetooth and WIFI were disabled while testing 2G/3G/4G/5G modes.
- 6. Licensed data modes and Bluetooth were disabled while testing WIFI modes.
- 7. The Margin from FCC limit column indicates a margin from the FCC limit for compliance (T3).

# B. CDMA

- 1. Power Configuration: Power Control Bits = "All Up"
- 2. Vocoder Configuration: RC1/SO68 (CDMA EVRC–B)

## C. GSM

- 1. Power Configuration: GSM850: PCL=5, GSM1900: PCL=0;
- 2. Vocoder Configuration: EFR (GSM);

## D. UMTS

- 1. Power Configuration: TPC= "All 1s";
- 2. Vocoder Configuration: AMR 12.2 kbps (UMTS);

FCC ID: A3LSMG998U	PCTEST:	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 44 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		raye 44 01 97

## E. LTE FDD

- 1. Power Configuration: TPC = "Max Power"
- 2. Radio Configuration: 16QAM, 1RB, 99%RB offset
- 3. Vocoder Configuration: EVS Primary NB 24.4kbps
- 4. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low and high channels for those combinations. LTE Band 13 at 5MHz is the worst-case for the Axial probe orientation. LTE Band 7 at 5MHz bandwidth is the worst-case for the Radial probe orientation.

## F. LTE TDD

- 1. Power Configuration: TPC = "Max Power"
- 2. Radio Configuration: 16QAM, 1RB, 99%RB offset
- 3. Power Class 3 Uplink-Downlink configuration: 0
- 4. Power Class 2 Uplink-Downlink configuration: 1
- 5. Vocoder Configuration: EVS Primary NB 24.4kbps
- 6. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low, low-mid, high-mid, and high channels for those combinations. LTE Band 41 (Power Class 2) at 5MHz is the worst-case for the Axial probe orientation. LTE Band 41 (Power Class 2) at 15MHz is the worst-case for the Radial probe orientation.

# G. WIFI

- 1. Radio Configuration
  - a. IEEE 802.11b: CCK 11Mbps
  - b. IEEE 802.11g/a: QPSK, 18Mbps
  - c. IEEE 802.11n/ac 20MHz: 64QAM, MCS 6
  - d. IEEE 802.11ax SU 20MHz: 64QAM, MCS 5
  - e. IEEE 802.11n/ac 40MHz: 64QAM, MCS 6
  - f. IEEE 802.11ax SU 40MHz: BPSK, MCS 1
- 2. RU Index
  - a. IEEE 802.11ax RU 20MHz: 37
  - b. IEEE 802.11ax RU 40MHz: 65
- 3. Vocoder Configuration: EVS Primary NB 24.4kbps
- 4. The worst-case standard for 2.4GHz WIFI in each probe orientation is additionally tested on the low and high channels. IEEE 802.11n is the worst-case for the Axial probe orientation. IEEE 802.11ax RU is the worst-case for the Radial probe orientation.
- 5. The worst-case standard for 5GHz WIFI in each probe orientation is additionally tested on higher U-NII bands as well as applicable low and high channels. IEEE 802.11ax SU 20MHz (U-NII 1) is the worst-case for the Axial probe orientation. IEEE 802.11ax RU 40MHz (U-NII 1) is the worstcase for the Radial probe orientation.

## H. OTT VoIP

- 1. Vocoder Configuration: OPUS 6kbps
- 2. EvDO Configuration
  - a. Revision: A
- 3. EDGE Configuration
  - a. MCS Index: 7
  - b. Number of TX slots: 2
- 4. HSPA Configuration:


FCC ID: A3LSMG998U	host to be port of a memory	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 45 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 45 01 97

- a. Release: 6
- b. 3GPP 34.121 Subtest 1
- 5. LTE FDD Configuration:
  - a. Power Configuration: TPC = "Max Power"
  - b. Radio Configuration: 16QAM, 1RB, 99%RB offset
  - c. LTE Band 71 was the worst-case band from Table 7-6 and was used to test both Axial and Radial probe orientations.
  - The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low and high channels for those combinations. LTE Band 71 at 5MHz is the worst-case for the Axial probe orientation. LTE Band 71 at 10MHz bandwidth is the worst-case for the Radial probe orientation.
- LTE TDD Configuration:
  - a. Power Configuration: TPC = "Max Power"
  - b. Radio Configuration: 16QAM, 1RB, 99%RB offset
  - c. Power Class 2 Uplink-Downlink configuration: 1
  - d. LTE Band 41 (Power Class 2) was the worst-case band from Table 7-7 and was used to test both Axial and Radial probe orientations.
  - e. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low, low-mid, high-mid, and high channels for those combinations. LTE Band 41 (Power Class 2) at 20MHz is the worst-case for the Axial probe orientation. LTE Band 41 (Power Class 2) at 5MHz is the worst-case for the Radial probe orientation.
- 7. NR FDD Configuration
  - Power Configuration: TxAGC is set such that the DUT operates at max power.
  - Radio Configuration: DFT-S-OFDM, 16QAM, 1RB, 99% RB Offset
  - Due to equipment limitations, ABM1 measurements were not possible. Therefore, the procedure outlined in Section 7.II.5 was followed to obtain SNNR values. Additionally, Frequency Response measurements were not possible due to equipment limitations.
  - d. NR Band n30 was the worst-case band from Table 7-12 and was used to test both Axial and Radial probe orientations.
  - e. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low and high channels for those combinations. NR n30 at 5MHz is the worstcase for both the Axial and Radial probe orientations.
- 8. NR TDD Configuration
  - a. Power Configuration: TxAGC is set such that the DUT operates at max power.
  - Radio Configuration: DFT-s-OFDM, 16QAM, 1RB, 99% RB Offset
  - Due to equipment limitations. ABM1 measurements were not possible. Therefore, the procedure outlined in Section 7.II.5 was followed to obtain SNNR values. Additionally, Frequency Response measurements were not possible due to equipment limitations.
  - d. NR Band n41 was the worst-case band from Table 7-13 and was used to test both Axial and Radial probe orientations.
  - The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low and high channels for those combinations. NR n41 (Power class 2) at 50MHz is the worst-case for the Axial probe orientation. NR n41 (Power Class 2) at 40MHz bandwidth is the worst-case for the Radial probe orientation.
- 9. WIFI Configuration:
  - a. Radio Configuration
    - i. IEEE 802.11b; CCK, 11Mbps
    - ii. IEEE 802.11g/a: QPSK, 18Mbps
    - iii. IEEE 802.11n/ac 20MHz: 64QAM, MCS 6
    - iv. IEEE 802.11ax SU 20MHz: 64QAM, MCS 5
    - v. IEEE 802.11n/ac 40MHz: 64QAM, MCS 6
    - vi. IEEE 802.11ax SU 40MHz: BPSK, MCS 1


FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 46 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 40 01 91

- b. RU Index
  - i. IEEE 802.11ax RU 20MHz: 37
  - ii. IEEE 802.11ax RU 40MHz: 65
- c. The worst-case standard for 2.4GHz WIFI in each probe orientation is additionally tested on the low and high channels. IEEE 802.11n is the worst-case for the Axial probe orientation. IEEE 802.11ax RU is the worst-case for the Radial probe orientation.
- d. The worst-case standard for 5GHz WIFI in each probe orientation is additionally tested on higher U-NII bands as well as applicable low and high channels. IEEE 802.11ax RU 20MHz (U-NII 2A) is the worst-case for the Axial probe orientation. IEEE 802.11ax 40MHz (U-NII 2A) is the worst-case for the Radial probe orientation.


# III. 1 kHz Vocoder Application Check



This model was verified to be within the linear region for ABM1 measurements at -18 dBm0 for CDMA. This measurement was taken in the axial configuration above the maximum location.



This model was verified to be within the linear region for ABM1 measurements at -16 dBm0 for GSM, UMTS, and VoLTE over IMS. This measurement was taken in the axial configuration above the maximum location.



This model was verified to be within the linear region for ABM1 measurements at -20 dBm0 for VoWIFI over IMS and OTT VoIP. This measurement was taken in the axial configuration above the maximum location.

FCC ID: A3LSMG998U	PCTEST Thought to be port of the received	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 47 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 47 of 97

# IV. T-Coil Validation Test Results

Table 9-38
Helmholtz Coil Validation Table of Results – 10/19/2020

Hommone on Fanadion Table of Recalls 10/10/2020								
ltem	Target	Result	Verdict					
Axial								
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.234	PASS					
Environmental Noise	< -58 dBA/m	-63.82	PASS					
Frequency Response, from limits	> 0 dB	0.70	PASS					
Radial								
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.268	PASS					
Environmental Noise	< -58 dBA/m	-63.87	PASS					
Frequency Response, from limits	> 0 dB	0.70	PASS					

Table 9-39
Helmholtz Coil Validation Table of Results – 11/02/2020

Item	Target	Result	Verdict	
Axial				
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.342	PASS	
Environmental Noise	< -58 dBA/m	-64.49	PASS	
Frequency Response, from limits	> 0 dB	0.70	PASS	
Radial				
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.363	PASS	
Environmental Noise	< -58 dBA/m	-63.14	PASS	
Frequency Response, from limits	> 0 dB	0.70	PASS	

Table 9-40
Helmholtz Coil Validation Table of Results – 11/09/2020

Item	Target	Result	Verdict
Axial			
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.232	PASS
Environmental Noise	< -58 dBA/m	-64.26	PASS
Frequency Response, from limits	> 0 dB	0.70	PASS
Radial			
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.392	PASS
Environmental Noise	< -58 dBA/m	-62.99	PASS
Frequency Response, from limits	> 0 dB	0.70	PASS

FCC ID: A3LSMG998U	PCTEST .  Road to be post of ® removed.	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 48 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 46 01 97

# V. ABM1 Magnetic Field Distribution Scan Overlays




Figure 9-1
T-Coil Scan Overlay Magnetic Field Distributions

# Notes:

- 1. Final measurement locations are indicated by a cursor on the contour plots. The GSM 850 radial measurement location is indicated by a blue cursor.
- 2. See Test Setup Photographs for actual WD overlay.

FCC ID: A3LSMG998U	PCTEST Thought to be port of the received	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 49 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 49 01 91

### **MEASUREMENT UNCERTAINTY** 10.

# **Table 10-1 Uncertainty Estimation Table**

Contribution	Data +/- %	Data +/- dB	Data Type	Probability distribution	Divisor	Standard uncertainty	Standard Uncertainty (dB)
ABM Noise	7.0%	0.29	Std. Dev.	Normal k=1	1.00	7.0%	
RF Reflections	4.7%	0.20	Specification	Rectangular	1.73	2.7%	
Reference Signal Level	12.2%	0.50	Specification	Rectangular	1.73	7.0%	
Positioning Accuracy	10.0%	0.41	Uncertainty	Rectangular	1.73	5.8%	
Probe Coil Sensitivity	12.2%	0.50	Specification	Rectangular	1.73	7.0%	
Probe Linearity	2.4%	0.10	Std. Dev.	Normal k=1	1.00	2.4%	
Cable Loss	2.8%	0.12	Specification	Rectangular	1.73	1.6%	
Frequency Analyzer	5.0%	0.21	Specification	Rectangular	1.73	2.9%	
System Repeatability	5.0%	0.21	Std. Dev.	Normal k=1	1.00	5.0%	
WD Repeatability	9.0%	0.37	Std. Dev.	Normal k=1	1.00	9.0%	
Positioner Accuracy	1.0%	0.04	Specification	Rectangular	1.73	0.6%	
Combined standard uncertainty, uc (k=1)						17.7%	0.71
Expanded uncertainty (k=2), 95% confidence level						35.3%	1.31

### Notes:

- Test equipments are calibrated according to techniques outlined in NIS81, NIS3003 and NIST Tech Note 1297.
- All equipments have traceability according to NIST. Measurement Uncertainties are defined in further detail in NIS 81 and NIST Tech Note 1297 and UKAS M3003.

Measurement uncertainty reflects the quality and accuracy of a measured result as compared to the true value. Such statements are generally required when stating results of measurements so that it is clear to the intended audience that the results may differ when reproduced by different facilities. Measurement results vary due to the measurement uncertainty of the instrumentation, measurement technique, and test engineer. Most uncertainties are calculated using the tolerances of the instrumentation used in the measurement, the measurement setup variability, and the technique used in performing the test. While not generally included, the variability of the equipment under test also figures into the overall measurement uncertainty. Another component of the overall uncertainty is based on the variability of repeated measurements (so-called Type A uncertainty). This may mean that the Hearing Aid compatibility tests may have to be repeated by taking down the test setup and resetting it up so that there are a statistically significant number of repeat measurements to identify the measurement uncertainty. By combining the repeat measurement results with that of the instrumentation chain using the technique contained in NIS 81 and NIS 3003, the overall measurement uncertainty was estimated.

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 50 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 50 of 97

### **EQUIPMENT LIST** 11.

# **Table 11-1 Equipment List**

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Control Company	4040	Temperature / Humidity Monitor	6/29/2019	Biennial	6/29/2021	192291470
Dell	Latitude E6540	SoundCheck Acoustic Analyzer Laptop	4/24/2019	Biennial	4/24/2021	7BFNM32
RME	Fireface UC	Soundcheck Acoustic Analyzer External Audio Interface	4/24/2019	Biennial	4/24/2021	23528889
Listen	SoundConnect	Microphone Power Supply	4/22/2019	Biennial	4/22/2021	PS2612
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	2/4/2020	Annual	2/4/2021	162125
Rohde & Schwarz	CMW500	Radio Communication Tester	5/21/2020	Annual	5/21/2021	128635
Seekonk	NC-100	Torque Wrench (8" lb)	8/4/2020	Biennial	8/4/2022	N/A
TEM		HAC System Controller with Software	N/A		N/A	N/A
TEM		HAC Positioner	N/A		N/A	N/A
TEM	Helmholtz Coil	Helmholtz Coil	5/20/2019	Biennial	5/20/2021	925
TEM	Axial T-Coil Probe	Axial T-Coil Probe	5/17/2019	Biennial	5/17/2021	TEM-1124
TEM	Radial T-Coil Probe	Radial T-Coil Probe	5/17/2019	Biennial	5/17/2021	TEM-1130

FCC ID: A3LSMG998U	PCTEST:	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Daga 51 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 51 of 97

# 12. TEST DATA

See following attached pages for Test Data.

FCC ID: A3LSMG998U	PCTEST: Houd to be part of & receiver	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 52 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		raye 32 01 97




Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011


### Equipment:

- Probe: Axial T-Coil Probe SN: TEM-1124; Calibrated: 05/17/2019
- Helmholtz Coil SN: 925; Calibrated: 05/20/2019

### **Noise Spectrum**



# Frequency Response



### Results

Verification 1kHz Intensity	-10.234	dB	~	Max/Min	-9.5/-10.5
Verification ABM2	-63.82	dB	•	Maximum	-58.0
Frequency Response Margin	700m	dB	•	Tolerance curves	Aligned Data

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 53 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 53 01 97



# **PCTEST Hearing-Aid Compatibility Facility**

DUT: HH Coil – SN: 925
Type: HH Coil


Serial: 925

### Measurement Standard: ANSI C63.19-2011


## Equipment:

- Probe: Axial T-Coil Probe SN: TEM-1124; Calibrated: 05/17/2019
- Helmholtz Coil SN: 925; Calibrated: 05/20/2019

### **Noise Spectrum**



## Frequency Response



### Results

Verification 1kHz Intensity	-10.342	dB	•	Max/Min	-9.5/-10.5
Verification ABM2	-64.49	dB	•	Maximum	-58.0
Frequency Response Margin	700m	dB	•	Tolerance curves	Aligned Data

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 54 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 54 01 97




Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011


## Equipment:

- Probe: Axial T-Coil Probe SN: TEM-1124; Calibrated: 05/17/2019
- Helmholtz Coil SN: 925; Calibrated: 05/20/2019

### **Noise Spectrum**



## Frequency Response



### Results

Verification 1kHz Intensity	-10.232	dB	$\checkmark$	Max/Min	-9.5/-10.5
Verification ABM2	-64.26	dB	~	Maximum	-58.0
Frequency Response Margin	700m	dB	~	Tolerance curves	Aligned Data

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 55 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 55 01 97




Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011


## Equipment:

- Probe: Radial T-Coil Probe SN: TEM-1130; Calibrated: 05/17/2019
- Helmholtz Coil SN: 925; Calibrated: 05/20/2019

### **Noise Spectrum**



## Frequency Response



### Results

Verification 1kHz Intensity	-10.268	dB	$\checkmark$	Max/Min	-9.5/-10.5
Verification ABM2	-63.87	dB	~	Maximum	-58.0
Frequency Response Margin	700m	dB	~	Tolerance curves	Aligned Data

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 56 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 50 01 97




Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011


## Equipment:

- Probe: Radial T-Coil Probe SN: TEM-1130; Calibrated: 05/17/2019
- Helmholtz Coil SN: 925; Calibrated: 05/20/2019

### **Noise Spectrum**



## Frequency Response



### Results

Verification 1kHz Intensity	-10.363	qB	$\checkmark$	Max/Min	-9.5/-10.5
Verification ABM2	-63.14	dB	~	Maximum	-58.0
Frequency Response Margin	700m	dB	•	Tolerance curves	Aligned Data

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 57 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 57 01 97




DUT: HH Coil - SN: 925 Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011


## Equipment:

- Probe: Radial T-Coil Probe SN: TEM-1130; Calibrated: 05/17/2019
- Helmholtz Coil SN: 925; Calibrated: 05/20/2019

### **Noise Spectrum**



## Frequency Response



### Results

Verification 1kHz Intensity	-10.392	dB	$\checkmark$	Max/Min	-9.5/-10.5
Verification ABM2	-62.99	dB	~	Maximum	-58.0
Frequency Response Margin	700m	dB		Tolerance curves	Aligned Data

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 58 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 56 01 97



Type: Portable Handset Serial: 0769M


Measurement Standard: ANSI C63.19-2011 / CTIA HAC Test Plan v3.1.1

# Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 05/17/2019

## **Test Configuration:**

- . Mode: CDMA Secondary Cellular
- Channel: 564
- · Speech Signal: 3GPP2 Normal Test Signal



FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 59 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 59 01 97



Type: Portable Handset Serial: 0769M


Measurement Standard: ANSI C63.19-2011 / CTIA HAC Test Plan v3.1.1

### Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 05/17/2019

## **Test Configuration:**

- Mode: CDMA Cellular
- Channel: 777
- · Speech Signal: 3GPP2 Normal Test Signal



FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 60 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 00 01 97




Type: Portable Handset Serial: 0769M

Measurement Standard: ANSI C63.19-2011 / CTIA HAC Test Plan v3.1.1

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 05/17/2019

## **Test Configuration:**

- Mode: CDMA PCS Channel: 1175
- Speech Signal: 3GPP2 Normal Test Signal



FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 61 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 010197



Type: Portable Handset Serial: 0769M


Measurement Standard: ANSI C63.19-2011

## Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 05/17/2019

## **Test Configuration:**

- Mode: GSM 850Channel: 190
- · Speech Signal: 3GPP2 Normal Test Signal



FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 62 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 02 01 97



Type: Portable Handset Serial: 0769M


Measurement Standard: ANSI C63.19-2011

## Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 05/17/2019

## **Test Configuration:**

- Mode: GSM 1900Channel: 512
- · Speech Signal: 3GPP2 Normal Test Signal



FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 63 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 03 01 97



Type: Portable Handset Serial: 0769M


Measurement Standard: ANSI C63.19-2011

## Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 05/17/2019

# **Test Configuration:**

- Mode: UMTS Band V
   Channel: 4183
- · Speech Signal: 3GPP2 Normal Test Signal



FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 64 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 04 01 97



Type: Portable Handset Serial: 0769M

Measurement Standard: ANSI C63.19-2011

## Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 05/17/2019

## **Test Configuration:**

Mode: UMTS Band IV

Channel: 1312

· Speech Signal: 3GPP2 Normal Test Signal



FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 65 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 05 01 97



Type: Portable Handset Serial: 0769M


Measurement Standard: ANSI C63.19-2011

## Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 05/17/2019

## **Test Configuration:**

- . Mode: UMTS Band II Channel: 9538
- Speech Signal: 3GPP2 Normal Test Signal



FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 66 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 00 01 97



Type: Portable Handset Serial: 0769M

Measurement Standard: ANSI C63.19-2011 / CTIA HAC Test Plan v3.1.1

## Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 05/17/2019

# **Test Configuration:**

Mode: LTE FDD Band 13

Bandwidth: 5MHzChannel: 23230

Speech Signal: 3GPP2 Normal Test Signal



FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 67 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage or or 97



Type: Portable Handset Serial: 0769M


Measurement Standard: ANSI C63.19-2011 / CTIA HAC Test Plan v3.1.1

## Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 05/17/2019

# **Test Configuration:**

- Mode: LTE TDD Band 41 (Power Class 2)
- Bandwidth: 5MHz Channel: 41490
- Speech Signal: 3GPP2 Normal Test Signal



FCC ID: A3LSMG998U	PCTEST Thought to be post of the received	HAC (I-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 69 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 68 of 97



Type: Portable Handset Serial: 0769M

Measurement Standard: ANSI C63.19-2011

# Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 05/17/2019

# **Test Configuration:**

Mode: 2.4GHz WIFIStandard: IEEE 802.11n

Channel: 1

Speech Signal: 3GPP2 Normal Test Signal



FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 69 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 09 01 97



Type: Portable Handset Serial: 0769M


Measurement Standard: ANSI C63.19-2011

## Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 05/17/2019

# **Test Configuration:**

- Mode: 5GHz WIFI
- Standard: IEEE 802.11ax SU (U-NII 1)
- · Bandwidth: 20MHz
- Channel: 40
- · Speech Signal: 3GPP2 Normal Test Signal



FCC ID: A3LSMG998U	PCTEST	HAC (L-COIL) LEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 70 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 70 01 97



Type: Portable Handset Serial: 0769M

Measurement Standard: ANSI C63.19-2011

## Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 05/17/2019

# **Test Configuration:**

VolP Application: Google Duo

Mode: NR TDD Band n41 (Power Class 2)

Bandwidth: 50MHz Channel: 518598



FCC ID: A3LSMG998U	PCTEST Thought to be post of the received	HAC (I-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 71 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 71 of 97



Type: Portable Handset Serial: 0769M

Measurement Standard: ANSI C63.19-2011 / CTIA HAC Test Plan v3.1.1

## Equipment:


Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 05/17/2019

# **Test Configuration:**

Mode: CDMA Secondary Cellular

· Channel: 476

### Noise Spectrum



# Results

ABM1	-6.79	dB	•	Minimum	-18.0
ABM2	-43.88	dB	~	Maximum	0.0
SNNR	37.09	dB	•	Minimum	20.0

FCC ID: A3LSMG998U	PCTEST Total to be part of Sements	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 72 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 12 01 91



Type: Portable Handset Serial: 0769M

Measurement Standard: ANSI C63.19-2011 / CTIA HAC Test Plan v3.1.1


### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 05/17/2019

# **Test Configuration:**

Mode: CDMA Cellular

# · Channel: 777



### Results

ABM1	-6.4	dB	•	Minimum	-18.0
ABM2	-43.3	dB	•	Maximum	0.0
SNNR	36.9	dB	0	Minimum	20.0

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 73 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 13 01 91



Type: Portable Handset Serial: 0769M

Measurement Standard: ANSI C63.19-2011 / CTIA HAC Test Plan v3.1.1


### **Equipment:**

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 05/17/2019

### **Test Configuration:**

 Mode: CDMA PCS Channel: 1175

#### Noise Spectrum



# Results

ABM1	-6.92	dB		Minimum	-18.0
ABM2	-42,88	dB	~	Maximum	0.0
SNNR	35.96	dB	~	Minimum	20.0

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 74 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 74 01 97



Type: Portable Handset Serial: 0769M

Measurement Standard: ANSI C63.19-2011


### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 05/17/2019

### **Test Configuration:**

 Mode: GSM 850 · Channel: 190

#### Noise Spectrum



### Results

ABM1	-5.74	dB		Minimum	-18.0
ABM2	-28.93	dB	~	Maximum	0.0
SNNR	23.2	dB	~	Minimum	20.0

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 75 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage /3 01 9/



Type: Portable Handset Serial: 0769M


Measurement Standard: ANSI C63.19-2011

### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 05/17/2019

### **Test Configuration:**

 Mode: GSM 1900 · Channel: 661



### Results

ABM1	-4.58	dB	$\checkmark$	Minimum	-18.0
ABM2	-30.91	dB	~	Maximum	0.0
SNNR	26.34	dB	<b>S</b>	Minimum	20.0

FCC ID: A3LSMG998U	PCTEST .  Road to be post of ® removed.	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 76 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 10 01 91



Type: Portable Handset Serial: 0769M

Measurement Standard: ANSI C63.19-2011


### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 05/17/2019

### **Test Configuration:**

. Mode: UMTS Band V Channel: 4233

#### Noise Spectrum



## Results

ABM1	-4.75	dB		Minimum	-18.0
ABM2	-53.54	dB	•	Maximum	0.0
SNNR	48.79	dB	~	Minimum	20.0

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 77 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 11 0191



Type: Portable Handset Serial: 0769M

Measurement Standard: ANSI C63.19-2011


### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 05/17/2019

### **Test Configuration:**

. Mode: UMTS Band IV Channel: 1513

#### Noise Spectrum



## Results

ABM1	-4.75	dB		Minimum	-18.0
ABM2	-53.84	dB	•	Maximum	0.0
SNNR	49.09	dB	~	Minimum	20.0

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 78 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 10 01 91



Type: Portable Handset Serial: 0769M

Measurement Standard: ANSI C63.19-2011


### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 05/17/2019

### **Test Configuration:**

. Mode: UMTS Band II Channel: 9538

#### Noise Spectrum



## Results

ABM1	-4.72	dB		Minimum	-18.0
ABM2	-53.81	dB	•	Maximum	0.0
SNNR	49.09	dB	~	Minimum	20.0

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 79 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 19 01 91



Type: Portable Handset Serial: 0769M

Measurement Standard: ANSI C63.19-2011 / CTIA HAC Test Plan v3.1.1


### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 05/17/2019

### **Test Configuration:**

. Mode: LTE FDD Band 7 Bandwidth: 5MHz Channel: 21425

#### **Noise Spectrum**



#### Results

ABM1	-5.77	dB	•	Minimum	-18.0
ABM2	-45.35	dB	•	Maximum	0.0
SNNR	39.57	dB	~	Minimum	20.0

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 80 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage ou oi 91



Type: Portable Handset Serial: 0769M

Measurement Standard: ANSI C63.19-2011 / CTIA HAC Test Plan v3.1.1


### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 05/17/2019

# **Test Configuration:**

. Mode: LTE TDD Band 41 (Power Class 2)

Bandwidth: 15MHz Channel: 41490



#### Results

ABM1	-5.76	dB	$\checkmark$	Minimum	-18.0
ABM2	-33.43	dB	<b>₹</b>	Maximum	0.0
SNNR	27.67	dB	•	Minimum	20.0

FCC ID: A3LSMG998U	PCTEST .  Road to be post of ® removed.	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 81 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 01 01 97



Type: Portable Handset Serial: 0769M

Measurement Standard: ANSI C63.19-2011


### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 05/17/2019

### **Test Configuration:**

Mode: 2.4GHz WIFI

Standard: IEEE 802.11ax RU



#### Results

ABM1	-10.52	dB	$\checkmark$	Minimum	-18.0
ABM2	-43.96	dB	•	Maximum	0.0
SNNR	33.44	dB	•	Minimum	20.0

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:	•	Page 82 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 62 01 91



Type: Portable Handset Serial: 0769M

Measurement Standard: ANSI C63.19-2011

### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 05/17/2019


### **Test Configuration:**

Mode: 5GHz WIFI

Standard: IEEE 802.11ax RU (U-NII 1)

Bandwidth: 40MHz Channel: 46

#### **Noise Spectrum**



#### Results

ABM1	-10.68	dB	$\checkmark$	Minimum	-18.0
ABM2	-43.36	dB	<b>~</b>	Maximum	0.0
SNNR	32.68	dB	~	Minimum	20.0

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 83 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 63 01 91



Type: Portable Handset Serial: 0769M

Measurement Standard: ANSI C63.19-2011

### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 05/17/2019

### **Test Configuration:**

· VolP Application: Google Duo

Mode: NR TDD Band n41 (Power Class 2)

Bandwidth: 40MHz Channel: 518598



FCC ID: A3LSMG998U	PCTEST:	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Daga 94 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 84 of 97

# 13. CALIBRATION CERTIFICATES

FCC ID: A3LSMG998U	PCTEST Total to be part of Secured	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 85 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 03 01 97

1M2009230152-21-R2.A3L 10/19/2020 - 11/14/2020 Portable Handset Page 85 of 97

© 2020 PCTEST REV 3.4.M



# **Certificate of Calibration**

for

AXIAL T COIL PROBE

Manufactured by:

TEM CONSULTING AXIAL T COIL PROBE

Model No: Serial No:

TEM-1124 29973

Calibration Recall No: 29

Submitted By:

Customer:

ANDREW HARWELL

Company: Address: PCTEST ENGINEERING LAB 6660-B DOBBIN ROAD

COLUMBIA

MD 21045

The subject instrument was calibrated to the indicated specification using standards traceable to the National Institute of Standards and Technology or to accepted values of natural physical constants. This document certifies that the instrument met the following specification upon its return to the submitter.

West Caldwell Calibration Laboratories Procedure No.

AXIAL T C TEM C

6/4/2019

Upon receipt for Calibration, the instrument was found to be:

Within (X)

tolerance of the indicated specification. See attached Report of Calibration.
The information supplied relates to the calibrated item listed above.
West Caldwell Calibration Laboratories' calibration control system meets the requirements, ISO 10012-1 MIL-STD-45662A, ANSI/NCSL Z540-1, IEC Guide 25, ISO 9001:2015 and ISO 17025.

Note: With this Certificate, Report of Calibration is included.

Approved by:

Calibration Date:

17-May-19

James Zhu

Certificate No:

29973 -1

Quality Manager ISO/IEC 17025:2005

QA Doc. #1051 Rev. 2.0 10/1/01

1 Certificate Page 1 of 1 West Caldwell A Calibration

ACCREDITED

uncompromised calibration Laboratories, Inc.

Calibration Lab. Cert. # 1533.01

1575 State Route 96, Victor, NY 14564, U.S.A.

 FCC ID: A3LSMG998U
 PCTEST
 HAC (T-COIL) TEST REPORT
 Approved by: Quality Manager

 Filename:
 Test Dates:
 DUT Type:

 1M2009230152-21-R2.A3L
 10/19/2020 - 11/14/2020
 Portable Handset



Calibration Lab. Cert. # 1533.01

ISO/IEC 17025: 2005

1575 State Route 96, Victor NY 14564

# REPORT OF CALIBRATION

TEM Consulting LP Axial T Coil Probe Company: PCTest Engineering Labs

Model No.: Axial T Coil Probe

Serial No.: TEM-1124

I. D. No.: XXXX

Probe Sensitivity measured wit	h Helmhol	tz Coil			
Helmholtz Coil;			Before & after data same:X		
the number of turns on each coil;	10	No.			
the radius of each coil, in meters;	0.204	m	Laboratory Environment:		
the current in the coils, in amperes.;	0.09	Α	Ambient Temperature:	20.7	°C
Helmholtz Coil Constant;	7.09	A/m/V	Ambient Humidity:	42.7	% RH
Helmholtz Coil magnetic field;	5.96	A/m	Ambient Pressure:	98.256	kPa
			Calibration Date:	17-May-2019	
Probe Sensitivity at	1000	Hz.	Calibration Due:	17-May-2020	
was	-60.41	dBV/A/m	Report Number:	29973	-1
	0.954	mV/A/m	Control Number:	29973	
Probe resistance	903	Ohms			


The above listed instrument meets or exceeds the tested manufacturer's specifications.

This Calibration is traceable through NIST test numbers:

683/290345-18

The expanded uncertainty of calibration: 0.30dB at 95% confidence level with a coverage factor of k=2.

Graph represents Probes Frequency Response.



The above listed instrument was checked using calibration procedure documented in West Caldwell

Calibration Laboratories Inc. procedure :

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC

Calibration was performed by West Caldwell Calibration Laboratories Inc. under Operating Procedures

intended to implement the requirements of ISO10012-1, IEC Guide 25, ANSI/NCSL Z540-1, (MIL-STD-45662A) and ISO 17025

Cal. Date: 17-May-2019

Measurements performed by: ......

James Zhu

Calibrated on WCCL system type 9700

This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Labs. Inc.

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC

### Page 1 of 2

FCC ID: A3LSMG998U	PCTEST: Noted to be part of @ secured	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Daga 97 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 87 of 97

# HCATEMC\_TEM-1124\_May-17-2019

### West Caldwell Calibration Laboratories Inc.

1575 State Route 96, Victor NY 14564 Tel. (585) 586-3900 FAX (585) 586-4327

# Calibration Data Record

Model No.: Axial T Coil Probe

Serial No.: TEM-1124

**TEM Consulting LP Axial T Coil Probe** Company: PCTest Engineering Labs

Function  Probe Sensitivity at  Probe Level Linearity	1000 Hz.	dBV/A/m dB	Before -60.41	Out	Remarks
**************************************	1000 Hz.		-60.41		
Probe Level Linearity		dВ			
Probe Level Linearity		4D			
		6	6.10		
	Ref. (0 dB)	0	0.00		
		-6	-6.00		ŀ
		-12	-12.00		
		Hz			
Probe Frequency Response		100	-19.9		
		3			
		1			
		i i			
	Ref. (0 dB)		I .		
			1		
			1		
					1
		10000	20.2		
	Probe Frequency Response		-6 -12 Probe Frequency Response 100 126 158 200 251 316 398 501 631 794	Ref. (0 dB)  Ref. (0 dB)  Ref. (0 dB)  Ref. (0 dB)  -6 -6 -6.00 -12.00  Hz -19.9 -19	Ref. (0 dB)  Ref. (0 dB)

			'		
Instruments used for o	alibration:		Date of Cal.	Traceability No.	Due Date
HP	34401A	S/N US360641	25-Jul-2018	,1010733	26-Jul-2019
HP	34401A	S/N US361024	25-Jul-2018	,1010733	26-Jul-2019
HP	33120A	S/N US360437	25-Jul-2018	,1010733	26-Jul-2019
B&K	2133	S/N 1583254	25-Jul-2018	683/290345-18	26-Jul-2019
1					

Cal. Date: 17-May-2019

Calibrated on WCCL system type 9700

This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Labs. Inc.

Tested by: James Zhu

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC

# Page 2 of 2

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 99 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 88 of 97



# **Certificate of Calibration**

for

#### RADIAL T COIL PROBE

Manufactured by:

TEM CONSULTING

Model No:

RADIAL T COIL PROBE

Serial No: Calibration Recall No: TEM-1130 29973

#### Submitted By:

Customer:

ANDREW HARWELL

Company: Address: PCTEST ENGINEERING LAB 6660-B DOBBIN ROAD

COLUMBIA

MD 21045

The subject instrument was calibrated to the indicated specification using standards traceable to the National Institute of Standards and Technology or to accepted values of natural physical constants. This document certifies that the instrument met the following specification upon its return to the submitter.

West Caldwell Calibration Laboratories Procedure No.

RADIAL T TEM C

Upon receipt for Calibration, the instrument was found to be:

6/4/2019

Within (X)

tolerance of the indicated specification. See attached Report of Calibration.

The information supplied relates to the calibrated item listed above.

West Caldwell Calibration Laboratories' calibration control system meets the requirements, ISO 10012-1 MIL-STD-45662A, ANSI/NCSL Z540-1, IEC Guide 25, ISO 9001:2015 and ISO 17025.

Note: With this Certificate, Report of Calibration is Included.

Approved by:

Calibration Date:

17-May-19

James Zhu

Certificate No:

29973 -2

Quality Manager ISO/IEC 17025:2005

QA Doc. #1051 Rev. 2.0 10/1/01 Certificate Page 1 of 1

West Caldwell Calibration

ACCREDITED

uncompromised calibration Laboratories, Inc.

Calibration Lab. Cert. # 1533.01

1575 State Route 96, Victor, NY 14564, U.S.A.

 FCC ID: A3LSMG998U
 PCTEST
 HAC (T-COIL) TEST REPORT
 Approved by: Quality Manager

 Filename:
 Test Dates:
 DUT Type:

 1M2009230152-21-R2.A3L
 10/19/2020 - 11/14/2020
 Portable Handset

© 2020 PCTEST

REV 3.4.N 8/18/2020



1575 State Route 96, Victor NY 14564



# REPORT OF CALIBRATION

TEM Consulting LP Radial T Coil Probe Company: PCTest Engineering Labs

Model No.: Radial T Coil Probe

Serial No.: TEM-1130

I. D. No.: XXXX

Probe Sensitivity measured wit	h Helmhol	z Coil			
Helmholtz Coll;			Before & after data same:	<b>X</b>	
the number of turns on each coil;	10	No.			
the radius of each coil, in meters;	0.204	m	Laboratory Environment:		
the current in the coils, in amperes.;	0.08	Α	Ambient Temperature:	20.7	°C
Helmholtz Coil Constant;	7.09	A/m/V	Ambient Humidity:	42.7	% RH
Helmholtz Coil magnetic field;	5.94	A/m	Ambient Pressure:	98.256	kPa
			Calibration Date:	17-May-2019	
Probe Sensitivity at	1000	Hz.	Calibration Due:	17-May-2020	
was	-60.37	dBV/A/m	Report Number:	29973	-2
	0.958	mV/A/m	Control Number:	29973	
Probe resistance	895	Ohms			


The above listed instrument meets or exceeds the tested manufacturer's specifications.

This Calibration is traceable through NIST test numbers:

683/290345-18

The expanded uncertainty of calibration: 0.30dB at 95% confidence level with a coverage factor of k=2.

Graph represents Probes Frequency Response.



The above listed instrument was checked using calibration procedure documented in West Caldwell

Calibration Laboratories Inc. procedure :

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCRTEMC

Calibration was performed by West Caldwell Calibration Laboratories Inc. under Operating Procedures

intended to implement the requirements of ISO10012-1, IEC Guide 25, ANSI/NCSL Z540-1, (MIL-STD-45662A) and ISO 17025

Cal. Date: 17-May-2019

Measurements performed by: ......

James Zhu

Calibrated on WCCL system type 9700 This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Labs. Inc.

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCRTEMC

### Page 1 of 2

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 90 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 90 01 97

# HCRTEMC\_TEM-1130\_May-17-2019

### West Caldwell Calibration Laboratories Inc.

1575 State Route 96, Victor NY 14564 Tel. (585) 586-3900 FAX (585) 586-4327

# Calibration Data Record

for

TEM Consulting LP Radial T Coil Probe Company: PCTest Engineering Labs

Model No.: Radial T Coil Probe

Serial No.: TEM-1130

IOIGIA	Tolerance		Measured values		
		Before	Out	Remarks	
1000 Hz.	dBV/A/m	-60.37			
	dB				
r	6	6.00			
Ref. (0 dB)	0	0.00			
	-6	-6.10			
	-12	-12.10			
	Hz				
sponse	100	-20.0			
	126	-17.9			
	158	-16.0			
	200	-14.0			
	251	-12.0			
	316	-10.0			
	398	-8.0		1	
	501	-6.0			
	631	-4.0			
	794	-2.0		ĺ	
Ref. (0 dB)	1000	0.0			
	1259	1.9			
	1585				
	1995				
	2512	7.9			
	3162	9.9			
	3981	11.9		1	
	5012	13.9			
	6310	15.9			
	7943	18.0			
	10000	20.1			
	Ref. (0 dB)	501 631 794 Ref. (0 dB) 1000 1259 1585 1995 2512 3162 3981 5012 6310 7943	501 -6.0 631 -4.0 794 -2.0 Ref. (0 dB) 1000 0.0 1259 1.9 1585 3.9 1995 5.9 2512 7.9 3162 9.9 3981 11.9 5012 13.9 6310 15.9 7943 18.0	501 -6.0 631 -4.0 794 -2.0 Ref. (0 dB) 1000 0.0 1259 1.9 1585 3.9 1995 5.9 2512 7.9 3162 9.9 3981 11.9 5012 13.9 6310 15.9 7943 18.0	

Instruments used for o	calibration:		Date of Cal.	Traceability No.	Due Date
HP	34401A	S/N US360641	25-Jul-2018	,1010733	26-Jul-2019
HP	34401A	S/N US361024	25-Jul-2018	,1010733	26-Jul-2019
HP	33120A	S/N US360437	25-Jul-2018	,1010733	26-Jul-2019
B&K	2133	S/N 1583254	25-Jul-2018	683/290345-18	26-Jul-2019

Cal. Date: 17-May-2019

Calibrated on WCCL system type 9700

This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Labs. Inc.

Tested by: James Zhu

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCRTEMC

# Page 2 of 2

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 91 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 91 01 97

# 14. CONCLUSION

The measurements taken in accordance with the procedures provided in the CTIA Test Plan for Hearing Aid Compatibility Rev 3.1.1, May 2017, indicate that the wireless communications device complies with the HAC limits specified in the ANSI C63.19 Standard and FCC WT Docket No. 01-309 RM-8658. Precise laboratory measures were taken to assure repeatability of the tests. The tested device complies with the requirements in respect to all parameters specific to the test. The test results and statements relate only to the item(s) tested.

The measurement system and techniques presented in this evaluation are proposed in the ANSI standard as a means of best approximating wireless device compatibility with a hearing-aid. The literature is under continual re-construction.

FCC ID: A3LSMG998U	PCTEST:	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Daga 02 of 07
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Page 92 of 97

# 15. REFERENCES

- ANSI C63.19-2011, American National Standard for Methods of Measurement of Compatibility between Wireless communication devices and Hearing Aids.", New York, NY, IEEE, May 2011
- CTIA Certification Program, "Test Plan for Hearing Aid Compatibility Rev 3.1.1", Washington, DC, CTIA, May 2017
- 3. FCC Office of Engineering and Technology KDB, "285076 D01 HAC Guidance v05," September 13, 2017
- FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017
- FCC Public Notice DA 06-1215, Wireless Telecommunications Bureau and Office of Engineering and Technology Clarify Use of Revised Wireless Phone Hearing Aid Compatibility Standard, June 6, 2006
- 6. FCC 3G Review Guidance, Laboratory Division OET FCC, May/June 2006
- Berger, H. S., "Compatibility Between Hearing Aids and Wireless Devices," Electronic Industries Forum, Boston, MA, May, 1997
- 8. Berger, H. S., "Hearing Aid and Cellular Phone Compatibility: Working Toward Solutions," Wireless Telephones and Hearing Aids: New Challenges for Audiology, Gallaudet University, Washington, D.C., May, 1997 (To be reprinted in the American Journal of Audiology).
- 9. Berger, H. S., "Hearing Aid Compatibility with Wireless Communications Devices, "IEEE International Symposium on Electromagnetic Compatibility, Austin, TX, August, 1997.
- Bronaugh, E. L., "Simplifying EMI Immunity (Susceptibility) Tests in TEM Cells," in the 1990 IEEE International Symposium on Electromagnetic Compatibility Symposium Record, Washington, D.C., August 1990, pp. 488-491
- 11. Byme, D. and Dillon, H., The National Acoustics Laboratory (NAL) New Procedure for Selecting the Gain and Frequency Response of a Hearing Aid, Ear and Hearing 7:257-265, 1986.
- 12. Crawford, M. L., "Measurement of Electromagnetic Radiation from Electronic Equipment using TEM Transmission Cells, "U.S. Department of Commerce, National Bureau of Standards, NBSIR 73-306, Feb. 1973.
- 13. Crawford, M. L., and Workman, J. L., "Using a TEM Cell for EMC Measurements of Electronic Equipment," U.S. Department of Commerce, National Bureau of Standards. Technical Note 1013, July 1981.
- EHIMA GSM Project, Development phase, Project Report (1st part) Revision A. Technical-Audiological Laboratory and Telecom Denmark. October 1993.
- 15. EHIMA GSM Project, Development phase, Part II Project Report. Technical-Audiological Laboratory and Telecom Denmark, June 1994.
- EHIMA GSM Project Final Report, Hearing Aids and GSM Mobile Telephones: Interference Problems, Methods of Measurement and Levels of Immunity. Technical-Audiological Laboratory and Telecom Denmark, 1995.
- 17. HAMPIS Report, Comparison of Mobile phone electromagnetic near field with an upscaled electromagnetic far field, using hearing aid as reference, 21 October 1999.
- 18. Hearing Aids/GSM, Report from OTWIDAM, Technical-Audiological Laboratory and Telecom Denmark, April 1993.
- 19. IEEE 100, The Authoritative Dictionary of IEEE Standards Terms, Seventh Edition.
- 20. Joyner, K. H, et. al., Interference to Hearing Aids by the New Digital Mobile Telephone System, Global System for Mobile (GSM) Communication Standard, National Acoustic Laboratory, Australian Hearing Series, Sydney 1993.
- Joyner, K. H., et. al., Interference to Hearing Aids by the Digital Mobile Telephone System, Global System for Mobile Communications (GSM), NAL Report #131, National Acoustic Laboratory, Australian Hearing Series, Sydney, 1995.
- 22. Kecker, W. T., Crawford, M. L., and Wilson, W. A., "Contruction of a Transverse Electromagnetic Cell", U.S. Department of Commerce, National Bureau of Standards, Technical Note 1011, Nov. 1978.

FCC ID: A3LSMG998U	PCTEST	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 93 of 97
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		rage 95 01 97

- 23. Konigstein, D., and Hansen, D., "A New Family of TEM Cells with enlarged bandwidth and Optimized working Volume," in the Proceedings of the 7th International Symposium on EMC, Zurich, Switzerland, March 1987; 50:9, pp. 127-132.
- 24. Kuk, F., and Hjorstgaard, N. K., "Factors affecting interference from digital cellular telephones," Hearing Journal, 1997; 50:9, pp 32-34.
- 25. Ma, M. A., and Kanda, M., "Electromagnetic Compatibility and Interference Metrology," U.S. Department of Commerce, National Bureau of Standards, Technical Note 1099, July 1986, pp. 17-43.
- 26. Ma, M. A., Sreenivashiah, I., and Chang, D. C., "A Method of Determining the Emission and Susceptibility Levels of Electrically Small Objects Using a TEM Cell," U.S. Department of Commerce, National Bureau of Standards, Technial Note 1040, July 1981.
- 27. McCandless, G. A., and Lyregaard, P. E., Prescription of Gain/Output (POGO) for Hearing Aids, Hearing Instruments 1:16-21, 1983
- 28. Skopec, M., "Hearing Aid Electromagnetic Interference from Digital Wireless Telephones, "IEEE Transactions on Rehabilitation Engineering, vol. 6, no. 2, pp. 235-239, June 1998.
- 29. Technical Report, GSM 05.90, GSM EMC Considerations, European Telecommunications Standards Institute, January 1993.
- 30. Victorian, T. A., "Digital Cellular Telephone Interference and Hearing Aid Compatibility—an Update," Hearing Journal 1998; 51:10, pp. 53-60
- 31. Wong, G. S. K., and Embleton, T. F. W., eds., AIP Handbook of Condenser Microphones: Theory, Calibration and Measurements, AIP Press.

FCC ID: A3LSMG998U	PCTEST:	HAC (T-COIL) TEST REPORT	SAMSUNG	Approved by: Quality Manager	
Filename:	Test Dates:	DUT Type:		Page 94 of 97	
1M2009230152-21-R2.A3L	10/19/2020 - 11/14/2020	Portable Handset		Fage 94 01 97	