

*FCC PART 15, SUBPART B and C
TEST REPORT*

for

InFocus TRANSMITTER

MODEL: IFS PRESENTER 2.4

Prepared for
INTERLINK ELECTRONICS
546 FLYNN ROAD
CAMARILLO, CALIFORNIA 93012

Prepared by: _____

KYLE FUJIMOTO

Approved by: _____

JAMES ROSS

COMPATIBLE ELECTRONICS INC.
114 OLINDA DRIVE
BREA, CALIFORNIA 92823
(714) 579-0500

DATE: FEBRUARY 6, 2004

	REPORT BODY	APPENDICES					TOTAL
		<i>A</i>	<i>B</i>	<i>C</i>	<i>D</i>	<i>E</i>	
PAGES	14	2	2	2	12	26	58

This report shall not be reproduced except in full, without the written approval of Compatible Electronics.

Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

TABLE OF CONTENTS

Section / Title	PAGE
GENERAL REPORT SUMMARY	4
SUMMARY OF TEST RESULTS	4
1. PURPOSE	5
2. ADMINISTRATIVE DATA	6
2.1 Location of Testing	6
2.2 Traceability Statement	6
2.3 Cognizant Personnel	6
2.4 Date Test Sample was Received	6
2.5 Disposition of the Test Sample	6
2.6 Abbreviations and Acronyms	6
3. APPLICABLE DOCUMENTS	7
4. DESCRIPTION OF TEST CONFIGURATION	8
4.1 Description Of Test Configuration - EMI	8
4.1.1 Cable Construction and Termination	9
5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT	10
5.1 EUT and Accessory List	10
5.2 EMI Test Equipment	11
6. TEST SITE DESCRIPTION	12
6.1 Test Facility Description	12
6.2 EUT Mounting, Bonding and Grounding	12
7. TEST PROCEDURES	13
7.1 Radiated Emissions (Spurious and Harmonics) Test	13
8. CONCLUSIONS	14

LIST OF APPENDICES

APPENDIX	TITLE
A	Laboratory Recognitions
B	Modifications to the EUT
C	Additional Models Covered Under This Report
D	Diagrams, Charts, and Photos • Test Setup Diagrams • Radiated Emissions Photos • Antenna and Effective Gain Factors
E	Data Sheets

LIST OF FIGURES

FIGURE	TITLE
1	Plot Map And Layout of Radiated Site

GENERAL REPORT SUMMARY

This electromagnetic emission test report is generated by Compatible Electronics Inc., which is an independent testing and consulting firm. The test report is based on testing performed by Compatible Electronics personnel according to the measurement procedures described in the test specifications given below and in the "Test Procedures" section of this report.

The measurement data and conclusions appearing herein relate only to the sample tested and this report may not be reproduced without the written permission of Compatible Electronics, unless done so in full.

This report must not be used to claim product endorsement by NVLAP, NIST or any other agency of the U.S. Government.

Device Tested: InFocus Transmitter
Model: IFS Presenter 2.4
S/N: N/A

Product Description: See Expository Statement

Modifications: The EUT was not modified in order to meet the specifications.

Manufacturer: Interlink Electronics
546 Flynn Road
Camarillo, California 93012

Test Dates: December 2, 15, and 15, 2003

Test Specifications: EMI requirements
CFR Title 47, Part 15 Subpart B; and Subpart C, Sections 15.205, 15.209 and 15.249

Test Procedure: ANSI C63.4: 2001


Test Deviations: The test procedure was not deviated from during the testing.

SUMMARY OF TEST RESULTS

TEST	DESCRIPTION	RESULTS
1	Conducted RF Emissions, 150 kHz - 30 MHz	This test was not performed because the EUT operates on DC power only and cannot be plugged into the AC public mains.
2	Radiated RF Emissions, 10 kHz - 25000 MHz	Complies with the Class B limits of CFR Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.209, and 15.249.

1. PURPOSE

This document is a qualification test report based on the Electromagnetic Interference (EMI) tests performed on the InFocus Transmitter Model: IFS Presenter 2.4. The EMI measurements were performed according to the measurement procedure described in ANSI C63.4: 2001. The tests were performed in order to determine whether the electromagnetic emissions from the equipment under test, referred to as EUT hereafter, are within the **Class B** specification limits defined by CFR Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.209, and 15.249.



2. ADMINISTRATIVE DATA

2.1 Location of Testing

The EMI tests described herein were performed at the test facility of Compatible Electronics, 114 Olinda Drive, Brea, California 92823.

2.2 Traceability Statement

The calibration certificates of all test equipment used during the test are on file at the location of the test. The calibration is traceable to the National Institute of Standards and Technology (NIST).

2.3 Cognizant Personnel

Interlink Electronics

Daniel Grieder

Compatible Electronics, Inc.

Kyle Fujimoto	Test Engineer
Kirit Ramani	Test Engineer
James Ross	Test Engineer

2.4 Date Test Sample was Received

The test sample was received on December 15, 2003.

2.5 Disposition of the Test Sample

The sample has yet to be returned to Interlink Electronics as of February 6, 2004.

2.6 Abbreviations and Acronyms

The following abbreviations and acronyms may be used in this document.

RF	Radio Frequency
EMI	Electromagnetic Interference
EUT	Equipment Under Test
P/N	Part Number
S/N	Serial Number
HP	Hewlett Packard
ITE	Information Technology Equipment
CML	Corrected Meter Limit
LISN	Line Impedance Stabilization Network
SA	Spectrum Analyzer

3. APPLICABLE DOCUMENTS

The following documents are referenced or used in the preparation of this EMI Test Report.

SPEC	TITLE
CFR Title 47, Part 15	FCC Rules – Radio frequency devices (including digital devices)
ANSI C63.4 2001	Methods of measurement of radio-noise emissions from low-voltage electrical and electronic equipment in the range of 9 kHz to 40 GHz

4. DESCRIPTION OF TEST CONFIGURATION

4.1 Description Of Test Configuration - EMI

Setup and operation of the equipment under test.

Specifics of the EUT and Peripherals Tested

The InFocus Transmitter Model: IFS Presenter 2.4 (EUT) was tested as a stand alone device. The EUT was tested while it was continuously transmitting and in three orthogonal axis. The EUT is a PCB trace.

The final radiated data was taken in the mode above. Please see Appendix E for the data sheets.

4.1.1 Cable Construction and Termination

The EUT has no external cables.



5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT**5.1 EUT and Accessory List**

EQUIPMENT	MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	FCC ID
INFOCUS TRANSMITTER (EUT)	INTERLINK ELECTRONICS	IFS PRESENTER 2.4	N/A	IE3VP41XX03

5.2 EMI Test Equipment

EQUIPMENT TYPE	MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	CAL. DATE	CAL. DUE DATE
Emissions Program	Compatible Electronics	2.3 (SR19)	N/A	N/A	N/A
SA* – Main Section	Hewlett Packard	8566B	3638A08784	June 20, 2003	1 Year
SA* – Display Section	Hewlett Packard	85662A	3701A22279	June 20, 2003	1 Year
Quasi-Peak Adapter	Hewlett Packard	85650A	2430A00424	June 20, 2003	1 Year
SA* – Main Section	Hewlett Packard	8566B	3638A08767	June 25, 2003	1 Year
SA* – Display Section	Hewlett Packard	85662A	3701A22262	June 25, 2003	1 Year
Quasi-Peak Adapter	Hewlett Packard	85650A	2811A01363	June 24, 2003	1 Year
EMI Receiver	Rhode & Schwarz	ESIB40	100172	July 22, 2003	1 Year
Preamplifier	Com-Power	PA-103	1582	March 6, 2003	1 Year
Biconical Antenna	Com-Power	AB-900	15226	April 21, 2003	1 Year
Log Periodic Antenna	Com-Power	AL-100	16202	February 3, 2003	1 Year
Antenna Mast	Com-Power	AM-100	N/A	N/A	N/A
Turntable	Com-Power	TT-100	N/A	N/A	N/A
Computer	Hewlett Packard	4530	US91912319	N/A	N/A
Monitor	Hewlett Packard	D5258A	TW74500641	N/A	N/A
Loop Antenna	Com-Power	AL-130	25310	June 4, 2003	1 Year
Microwave Preamplifier	Com-Power	PA-840	711013	March 6, 2002	2 Year
Horn Antenna	Com-Power	AH826	0071957	November 5, 2003	1 Year
Horn Antenna	Com-Power	AH-118	10073	January 21, 2002	2 Year
Microwave Preamplifier	Com-Power	PA-122	181917	October 31, 2003	1 Year

*SA = Spectrum Analyzer

6. TEST SITE DESCRIPTION


6.1 Test Facility Description

Please refer to section 2.1 and 7.1 of this report for EMI test location.

6.2 EUT Mounting, Bonding and Grounding

The EUT was mounted on a 1.0 by 1.5 meter non-conductive table 0.8 meters above the ground plane.

The EUT was not grounded.



7. TEST PROCEDURES

The following sections describe the test methods and the specifications for the tests. Test results are also included in this section.

7.1 Radiated Emissions (Spurious and Harmonics) Test

The spectrum analyzer was used as a measuring meter along with the quasi-peak adapter. Amplifiers were used to increase the sensitivity of the instrument. The Com-Power Preamplifier Model: PA-103 was used for frequencies from 30 MHz to 1 GHz, the Com-Power Microwave Preamplifier Model: PA-122 was used for frequencies from 1 GHz to 18 GHz, and the Com-Power Microwave Preamplifier Model: PA-840 was used for frequencies above 18 GHz. The spectrum analyzer was used in the peak detect mode with the "Max Hold" feature activated. In this mode, the spectrum analyzer records the highest measured reading over all the sweeps.

The measurement bandwidths and transducers used for the radiated emissions test were:

FREQUENCY RANGE	EFFECTIVE MEASUREMENT BANDWIDTH	TRANSDUCER
9 kHz to 150 kHz	200 Hz	Active Loop Antenna
150 kHz to 30 MHz	9 kHz	Active Loop Antenna
30 MHz to 300 MHz	120 kHz	Biconical Antenna
300 MHz to 1 GHz	120 kHz	Log Periodic Antenna
1 GHz to 3.15 GHz	1 MHz	Horn Antenna

The open field test site of Compatible Electronics, Inc. was used for radiated emission testing. This test site is set up according to ANSI C63.4: 2001. Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The turntable supporting the EUT is remote controlled using a motor. The turntable permits EUT rotation of 360 degrees in order to maximize emissions. Also, the antenna mast allows height variation of the antenna from 1 meter to 4 meters. Data was collected in the worst case (highest emission) configuration of the EUT. At each reading, the EUT was rotated 360 degrees and the antenna height was varied from 1 to 4 meters (for E field radiated field strength). The gunsight method was used when measuring with the horn antenna in order to ensure accurate results. The loop antenna was also rotated in the horizontal and vertical axis in order to ensure accurate results.

The presence of ambient signals was verified by turning the EUT off. In case an ambient signal was detected, the measurement bandwidth was reduced temporarily and verification was made that an additional adjacent peak did not exist. This ensures that the ambient signal does not hide any emissions from the EUT. The EUT was tested at a 3 meter test distance to obtain final test data. The final qualification data sheets are located in Appendix E.

8. CONCLUSIONS

The InFocus Transmitter Model: IFS Presenter 2.4 meets all of the Class B specification limits defined in CFR Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.209, and 15.249.



APPENDIX A

LABORATORY RECOGNITIONS

LABORATORY RECOGNITIONS

Compatible Electronics has the following agency accreditations:

National Voluntary Laboratory Accreditation Program - Lab Code: 200528-0

Voluntary Control Council for Interference - Registration Numbers: R-983, C-1026, R-984 and C-1027

Bureau of Standards and Metrology Inspection - Reference Number: SL2-IN-E-1031

Conformity Assessment Body for the EMC Directive Under the US/EU MRA Appointed by NIST

Compatible Electronics is recognized or on file with the following agencies:

Federal Communications Commission

Industry Canada

Radio-Frequency Technologies (Competent Body)

APPENDIX B

MODIFICATIONS TO THE EUT

MODIFICATIONS TO THE EUT

The modifications listed below were made to the EUT to pass FCC 15.249 or FCC Class B specifications.

All the rework described below was implemented during the test in a method that could be reproduced in all the units by the manufacturer.

No modifications were made during testing.





APPENDIX C

***ADDITIONAL MODELS COVERED
UNDER THIS REPORT***

ADDITIONAL MODELS COVERED UNDER THIS REPORT

USED FOR THE PRIMARY TEST

InFocus Transmitter
Model: IFS Presenter 2.4
S/N: N/A

There are no additional models covered under this report.




APPENDIX D


DIAGRAMS, CHARTS, AND PHOTOS

FIGURE 1: PLOT MAP AND LAYOUT OF RADIATED SITE

OPEN LAND > 15 METERS



OPEN LAND > 15 METERS



COM-POWER AB-900

BICONICAL ANTENNA

S/N: 15226

CALIBRATION DATE: APRIL 21, 2003

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
30	11.20	120	13.80
35	10.40	125	12.50
40	10.20	140	12.50
45	11.00	150	10.90
50	11.30	160	11.50
60	9.60	175	14.90
70	7.40	180	15.50
80	6.10	200	16.90
90	7.70	250	15.50
100	10.50	300	23.80

COM-POWER AL-100

LOG PERIODIC ANTENNA

S/N: 16202

CALIBRATION DATE: FEBRUARY 3, 2003

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
300	12.70	700	20.60
400	15.40	800	21.80
500	16.50	900	21.00
600	17.20	1000	21.50

COM-POWER PA-103**PREAMPLIFIER**

S/N: 1582

CALIBRATION DATE: MARCH 6, 2003

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
30	33.6	300	33.3
40	33.6	350	33.3
50	33.6	400	33.1
60	33.6	450	33.0
70	33.5	500	32.9
80	33.5	550	33.0
90	33.5	600	32.8
100	33.6	650	32.6
125	33.6	700	32.7
150	33.4	750	32.4
175	33.5	800	32.4
200	33.4	850	32.7
225	33.3	900	31.9
250	33.2	950	31.8
275	33.3	1000	32.5

COM-POWER PA-122**MICROWAVE PREAMPLIFIER****S/N: 181917****CALIBRATION DATE: OCTOBER 31, 2003**

FREQUENCY (GHz)	FACTOR (dB)	FREQUENCY (GHz)	FACTOR (dB)
1.0	33.5	6.0	34.5
1.1	33.6	6.5	34.6
1.2	33.6	7.0	33.1
1.3	33.3	7.5	32.5
1.4	33.1	8.0	33.5
1.5	32.7	8.5	35.1
1.6	32.6	9.0	35.5
1.7	32.5	9.5	36.8
1.8	31.5	10.0	35.7
1.9	31.4	11.0	31.8
2.0	30.0	12.0	29.5
2.5	33.2	13.0	31.2
3.0	32.0	14.0	31.7
3.5	33.0	15.0	31.1
4.0	33.4	16.0	32.9
4.5	34.7	17.0	33.6
5.0	34.2	18.0	31.0
5.5	33.2		

COM-POWER PA-840**MICROWAVE PREAMPLIFIER****S/N: 711013****CALIBRATION DATE: MARCH 06, 2002**

FREQUENCY (GHz)	FACTOR (dB)	FREQUENCY (GHz)	FACTOR (dB)
18.0	26.4	30.0	27.6
19.0	25.4	31.0	27.3
20.0	24.5	32.0	26.9
21.0	23.9	33.0	26.7
22.0	24.0	34.0	27.0
23.0	24.4	35.0	25.9
24.0	25.2	36.0	25.5
25.0	26.1	37.0	26.2
26.0	26.6	38.0	25.6
27.0	27.2	39.0	23.4
28.0	27.4	40.0	24.3
29.0	27.5		

COM-POWER AH-118**HORN ANTENNA****S/N: 10073****CALIBRATION DATE: JANUARY 21, 2002**

FREQUENCY (GHz)	FACTOR (dB)	FREQUENCY (GHz)	FACTOR (dB)
1.0	26.6	10.0	41.8
1.5	29.2	10.5	40.4
2.0	32.4	11.0	37.5
2.5	32.3	11.5	42.2
3.0	31.4	12.0	40.4
3.5	31.8	12.5	43.6
4.0	31.1	13.0	44.2
4.5	32.0	13.5	41.8
5.0	33.9	14.0	43.3
5.5	32.0	14.5	47.0
6.0	37.8	15.0	49.4
6.5	36.8	15.5	49.9
7.0	42.4	16.0	49.9
7.5	39.5	16.5	48.2
8.0	41.3	17.0	44.0
8.5	40.3	17.5	44.8
9.0	39.5	18.0	44.7
9.5	41.4		

COM-POWER AH826

HORN ANTENNA

S/N: 0071957

CALIBRATION DATE: NOVEMBER 05, 2003

FREQUENCY (GHz)	FACTOR (dB)	FREQUENCY (GHz)	FACTOR (dB)
18.0	32.3	22.5	32.9
18.5	32.9	23.0	33.0
19.0	32.7	23.5	33.6
19.5	32.6	24.0	33.6
20.0	32.7	24.5	33.5
20.5	33.0	25.0	33.5
21.0	33.0	25.5	33.7
21.5	33.2	26.0	34.1
22.0	32.9	26.5	34.5

COM-POWER AL-130**LOOP ANTENNA**

S/N: 25310

CALIBRATION DATE: JUNE 4, 2003

FREQUENCY (MHz)	MAGNETIC (dB/m)	ELECTRIC (dB/m)
0.009	-41.2	10.3
0.01	-41.3	10.2
0.02	-42.3	9.2
0.05	-42.5	9.0
0.07	-42.3	9.2
0.1	-42.5	9.0
0.2	-44.6	6.9
0.3	-42.1	9.4
0.5	-42.4	9.1
0.7	-42.1	9.4
1	-41.5	10.0
2	-41.0	10.5
3	-41.3	10.2
4	-41.3	10.2
5	-40.9	10.6
10	-41.6	9.9
15	-42.1	9.4
20	-42.2	9.3
25	-42.7	8.8
30	-44.3	7.2



FRONT VIEW

INTERLINK ELECTRONICS
InFocus TRANSMITTER
MODEL: IFS PRESENTER 2.4

FCC SUBPART B AND C - RADIATED EMISSIONS – 12-5-03 and 12-15-03

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



REAR VIEW

INTERLINK ELECTRONICS
InFocus TRANSMITTER
MODEL: IFS PRESENTER 2.4

FCC SUBPART B AND C - RADIATED EMISSIONS – 12-5-03 and 12-15-03

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**

APPENDIX E

DATA SHEETS

RADIATED EMISSIONS

DATA SHEETS

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	Interlink Electronics	DATE	12/5/03
EUT	InFocus Transmitter	DUTY CYCLE	10.63 %
MODEL	IFS Presenter 2.4	PEAK TO AVG	-19.4693347 dB
S/N	N/A	TEST DIST.	3 Meters
TEST ENGINEER	Kirit Ramani	LAB	A

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
2403.0000	85.9	66.4 A	H	1.0	135	X	LOW	32.3	4.6	32.6	0.0	0.0	70.8	-23.2	94.0	
2403.0000	88.6	69.1 A	H	1.0	135	Y	LOW	32.3	4.6	32.6	0.0	0.0	73.5	-20.5	94.0	
2403.0000	89.7	70.2 A	H	2.0	90	Z	LOW	32.3	4.6	32.6	0.0	0.0	74.6	-19.4	94.0	
2403.0000	84.3	64.8 A	V	1.0	90	X	LOW	32.3	4.6	32.6	0.0	0.0	69.2	-24.8	94.0	
2403.0000	88.7	69.2 A	V	2.3	135	Y	LOW	32.3	4.6	32.6	0.0	0.0	73.6	-20.4	94.0	
2403.0000	85.6	66.1 A	V	2.0	180	Z	LOW	32.3	4.6	32.6	0.0	0.0	70.5	-23.5	94.0	
2440.0000	87.0	67.5 A	H	1.3	180	X	MED.	32.3	4.6	32.8	0.0	0.0	71.7	-22.3	94.0	
2440.0000	84.6	65.1 A	H	1.0	180	Y	MED.	32.3	4.6	32.8	0.0	0.0	69.3	-24.7	94.0	
2440.0000	89.3	69.8 A	H	1.0	180	Z	MED.	32.3	4.6	32.8	0.0	0.0	74.0	-20.0	94.0	
2440.0000	84.2	64.7 A	V	1.0	270	X	MED.	32.3	4.6	32.8	0.0	0.0	68.9	-25.1	94.0	
2440.0000	87.6	68.1 A	V	1.0	135	Y	MED.	32.3	4.6	32.8	0.0	0.0	72.3	-21.7	94.0	
2440.0000	81.6	62.1 A	V	1.0	180	Z	MED.	32.3	4.6	32.8	0.0	0.0	66.3	-27.7	94.0	
2480.0000	87.8	68.3 A	H	1.0	180	X	HIGH	32.3	4.7	33.1	0.0	0.0	72.2	-21.8	94.0	
2480.0000	85.8	66.3 A	H	1.3	180	Y	HIGH	32.3	4.7	33.1	0.0	0.0	70.2	-23.8	94.0	
2480.0000	87.2	67.7 A	H	2.0	180	Z	HIGH	32.3	4.7	33.1	0.0	0.0	71.6	-22.4	94.0	
2480.0000	85.6	66.1 A	V	2.5	225	X	HIGH	32.3	4.7	33.1	0.0	0.0	70.0	-24.0	94.0	
2480.0000	86.1	66.6 A	V	3.0	225	Y	HIGH	32.3	4.7	33.1	0.0	0.0	70.5	-23.5	94.0	
2480.0000	81.5	62.0 A	V	2.0	180	Z	HIGH	32.3	4.7	33.1	0.0	0.0	65.9	-28.1	94.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN

** DELTA = SPEC LIMIT - CORRECTED READING

PAGE 1 of PAGE 2

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	Interlink Electronics	DATE	12/5/03
EUT	InFocus Transmitter	DUTY CYCLE	10.63 %
MODEL	IFS Presenter 2.4	PEAK TO AVG	-19.4693347 dB
S/N	N/A	TEST DIST.	3 Meters
TEST ENGINEER	Kirit Ramani	LAB	A

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
4806.0000	48.8	29.3 A	H	1.0	135	X	LOW	33.2	6.9	34.4	0.0	0.0	35.0	-19.0	54.0	Note: No Emissions Found after the 2nd Harmonic for the EUT
4806.0000	55.0	35.5 A	H	1.0	135	Y	LOW	33.2	6.9	34.4	0.0	0.0	41.2	-12.8	54.0	
4806.0000	47.3	27.8 A	H	2.5	90	Z	LOW	33.2	6.9	34.4	0.0	0.0	33.5	-20.5	54.0	
4806.0000	49.3	29.8 A	V	2.0	135	X	LOW	33.2	6.9	34.4	0.0	0.0	35.5	-18.5	54.0	
4806.0000	49.4	29.9 A	V	2.0	135	Y	LOW	33.2	6.9	34.4	0.0	0.0	35.6	-18.4	54.0	
4806.0000	49.8	30.3 A	V	1.5	180	Z	LOW	33.2	6.9	34.4	0.0	0.0	36.0	-18.0	54.0	
4880.0000	45.1	25.6 A	H	1.5	180	X	MED.	33.4	7.0	34.3	0.0	0.0	31.8	-22.2	54.0	
4880.0000	50.7	31.2 A	H	1.3	180	Y	MED.	33.4	7.0	34.3	0.0	0.0	37.4	-16.6	54.0	
4880.0000	48.4	28.9 A	H	1.5	180	Z	MED.	33.4	7.0	34.3	0.0	0.0	35.1	-18.9	54.0	
4880.0000	45.8	26.3 A	V	2.0	135	X	MED.	33.4	7.0	34.3	0.0	0.0	32.5	-21.5	54.0	
4880.0000	48.4	28.9 A	V	2.0	135	Y	MED.	33.4	7.0	34.3	0.0	0.0	35.1	-18.9	54.0	
4880.0000	49.3	29.8 A	V	1.5	180	Z	MED.	33.4	7.0	34.3	0.0	0.0	36.0	-18.0	54.0	
4960.0000	42.6	23.1 A	H	1.0	180	X	HIGH	33.7	7.1	34.2	0.0	0.0	29.7	-24.3	54.0	
4960.0000	48.2	28.7 A	H	1.3	180	Y	HIGH	33.7	7.1	34.2	0.0	0.0	35.3	-18.7	54.0	
4960.0000	48.7	29.2 A	H	2.0	180	Z	HIGH	33.7	7.1	34.2	0.0	0.0	35.8	-18.2	54.0	
4960.0000	47.2	27.7 A	V	2.0	180	X	HIGH	33.7	7.1	34.2	0.0	0.0	34.3	-19.7	54.0	
4960.0000	45.9	26.4 A	V	1.5	90	Y	HIGH	33.7	7.1	34.2	0.0	0.0	33.0	-21.0	54.0	
4960.0000	45.6	26.1 A	V	1.5	135	Z	HIGH	33.7	7.1	34.2	0.0	0.0	32.7	-21.3	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN

** DELTA = SPEC LIMIT - CORRECTED READING

PAGE 2 of PAGE 2

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	Interlink Electronics	DATE	12/12/03
EUT	InFocus Transmitter	DUTY CYCLE	10.63 %
MODEL	IFS Presenter 2.4	PEAK TO AVG	-19.4693347 dB
TEST MODE	SPURIOUS (NON-HARMONIC) EMISSIONS - LOW CHANNEL	TEST DIST.	3 Meters
TEST ENGINEER	Kirit Ramani	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
2411.9100	58.4	38.9 A	H	1.5	270	X	LOW	32.3	3.6	32.6	0.0	0.0	42.2	-11.8	54.0	Note: No Emissions detected below
2411.9100	57.7	38.2 A	H	2.0	90	Y	LOW	32.3	3.6	32.6	0.0	0.0	41.5	-12.5	54.0	2411.91 MHz
2411.9100	55.5	36.0 A	H	2.0	180	Z	LOW	32.3	3.6	32.6	0.0	0.0	39.3	-14.7	54.0	
2411.9100	58.5	39.0 A	V	1.3	180	X	LOW	32.3	3.6	32.6	0.0	0.0	42.3	-11.7	54.0	
2411.9100	62.4	42.9 A	V	1.5	180	Y	LOW	32.3	3.6	32.6	0.0	0.0	46.2	-7.8	54.0	
2411.9100	59.1	39.6 A	V	1.5	270	Z	LOW	32.3	3.6	32.6	0.0	0.0	42.9	-11.1	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	Interlink Electronics	DATE	12/12/03
EUT	InFocus Transmitter	DUTY CYCLE	10.63 %
MODEL	IFS Presenter 2.4	PEAK TO AVG	-19.4693347 dB
TEST MODE	SPURIOUS (NON-HARMONIC) EMISSIONS - LOW CHANNEL	TEST DIST.	3 Meters
TEST ENGINEER	Kirit Ramani	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
2441.0900	56.9	37.4 A	H	2.0	180	X	LOW	32.3	3.5	32.8	0.0	0.0	40.5	-13.5	54.0	
2441.0900	58.8	39.3 A	H	2.0	90	Y	LOW	32.3	3.5	32.8	0.0	0.0	42.4	-11.6	54.0	
2441.0900	54.4	34.9 A	H	2.0	180	Z	LOW	32.3	3.5	32.8	0.0	0.0	38.0	-16.0	54.0	
2441.0900	59.7	40.2 A	V	1.3	180	X	LOW	32.3	3.5	32.8	0.0	0.0	43.3	-10.7	54.0	
2441.0900	59.5	40.0 A	V	1.3	180	Y	LOW	32.3	3.5	32.8	0.0	0.0	43.1	-10.9	54.0	
2441.0900	58.2	38.7 A	V	1.3	270	Z	LOW	32.3	3.5	32.8	0.0	0.0	41.8	-12.2	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	Interlink Electronics	DATE	12/12/03
EUT	InFocus Transmitter	DUTY CYCLE	10.63 %
MODEL	IFS Presenter 2.4	PEAK TO AVG	-19.4693347 dB
TEST MODE	SPURIOUS (NON-HARMONIC) EMISSIONS - LOW CHANNEL	TEST DIST.	3 Meters
TEST ENGINEER	Kirit Ramani	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
2382.3700	58.0	38.5 A	H	1.5	270	X	LOW	32.3	3.7	32.4	0.0	0.0	42.1	-11.9	54.0	
2382.3700	58.4	38.9 A	H	1.5	90	Y	LOW	32.3	3.7	32.4	0.0	0.0	42.5	-11.5	54.0	
2382.3700	55.1	35.6 A	H	2.0	180	Z	LOW	32.3	3.7	32.4	0.0	0.0	39.2	-14.8	54.0	
2382.3700	61.2	41.7 A	V	1.3	180	X	LOW	32.3	3.7	32.4	0.0	0.0	45.3	-8.7	54.0	
2382.3700	63.0	43.5 A	V	1.3	180	Y	LOW	32.3	3.7	32.4	0.0	0.0	47.1	-6.9	54.0	
2382.3700	60.9	41.4 A	V	1.5	180	Z	LOW	32.3	3.7	32.4	0.0	0.0	45.0	-9.0	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	Interlink Electronics	DATE	12/12/03
EUT	InFocus Transmitter	DUTY CYCLE	10.63 %
MODEL	IFS Presenter 2.4	PEAK TO AVG	-19.4693347 dB
TEST MODE	SPURIOUS (NON-HARMONIC) EMISSIONS - LOW CHANNEL	TEST DIST.	3 Meters
TEST ENGINEER	Kirit Ramani	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
2328.5500	54.8	35.3 A	H	1.8	225	X	LOW	32.3	3.8	32.1	0.0	0.0	39.4	-14.6	54.0	
2328.5500	53.9	34.4 A	H	1.5	90	Y	LOW	32.3	3.8	32.1	0.0	0.0	38.5	-15.5	54.0	
2328.5500	52.2	32.7 A	H	2.0	180	Z	LOW	32.3	3.8	32.1	0.0	0.0	36.8	-17.2	54.0	
2328.5500	61.3	41.8 A	V	1.3	180	X	LOW	32.3	3.8	32.1	0.0	0.0	45.9	-8.1	54.0	
2328.5500	63.2	43.7 A	V	1.3	180	Y	LOW	32.3	3.8	32.1	0.0	0.0	47.8	-6.2	54.0	
2328.5500	60.7	41.2 A	V	2.0	90	Z	LOW	32.3	3.8	32.1	0.0	0.0	45.3	-8.7	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	Interlink Electronics	DATE	12/12/03
EUT	InFocus Transmitter	DUTY CYCLE	10.63 %
MODEL	IFS Presenter 2.4	PEAK TO AVG	-19.4693347 dB
TEST MODE	SPURIOUS (NON-HARMONIC) EMISSIONS - LOW CHANNEL	TEST DIST.	3 Meters
TEST ENGINEER	Kirit Ramani	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
2707.3400	49.4	29.9 A	H	1.5	45	X	LOW	31.9	3.9	32.7	0.0	0.0	33.1	-20.9	54.0	Note: No Non Harmonic emissions
2707.3400	48.5	29.0 A	H	2.0	45	Y	LOW	31.9	3.9	32.7	0.0	0.0	32.2	-21.8	54.0	detected above 2707.34 MHz
2707.3400	49.8	30.3 A	H	2.0	180	Z	LOW	31.9	3.9	32.7	0.0	0.0	33.5	-20.5	54.0	
2707.3400	55.3	35.8 A	V	1.3	180	X	LOW	31.9	3.9	32.7	0.0	0.0	39.0	-15.0	54.0	
2707.3400	55.2	35.7 A	V	1.3	180	Y	LOW	31.9	3.9	32.7	0.0	0.0	38.9	-15.1	54.0	
2707.3400	53.9	34.4 A	V	1.3	180	Z	LOW	31.9	3.9	32.7	0.0	0.0	37.6	-16.4	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	Interlink Electronics	DATE	12/12/03
EUT	InFocus Transmitter	DUTY CYCLE	10.63 %
MODEL	IFS Presenter 2.4	PEAK TO AVG	-19.4693347 dB
TEST MODE	SPURIOUS (NON-HARMONIC) EMISSIONS - MIDDLE CHANNEL	TEST DIST.	3 Meters
TEST ENGINEER	Kirit Ramani	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
2326.7400	58.3	38.8 A	H	1.5	0	X	LOW	32.3	3.8	32.1	0.0	0.0	42.9	-11.1	54.0	Note: No Emissions detected below
2326.7400	51.9	32.4 A	H	1.3	135	Y	LOW	32.3	3.8	32.1	0.0	0.0	36.5	-17.5	54.0	2326.74 MHz
2326.7400	54.9	35.4 A	H	2.0	180	Z	LOW	32.3	3.8	32.1	0.0	0.0	39.5	-14.5	54.0	
2326.7400	60.5	41.0 A	V	1.3	180	X	LOW	32.3	3.8	32.1	0.0	0.0	45.1	-8.9	54.0	
2326.7400	62.4	42.9 A	V	2.0	180	Y	LOW	32.3	3.8	32.1	0.0	0.0	47.0	-7.0	54.0	
2326.7400	60.4	40.9 A	V	1.3	315	Z	LOW	32.3	3.8	32.1	0.0	0.0	45.0	-9.0	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	Interlink Electronics	DATE	12/12/03
EUT	InFocus Transmitter	DUTY CYCLE	10.63 %
MODEL	IFS Presenter 2.4	PEAK TO AVG	-19.4693347 dB
TEST MODE	SPURIOUS (NON-HARMONIC) EMISSIONS - MIDDLE CHANNEL	TEST DIST.	3 Meters
TEST ENGINEER	Kirit Ramani	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
2380.4000	58.3	38.8 A	H	1.3	0	X	LOW	32.3	3.7	32.4	0.0	0.0	42.4	-11.6	54.0	
2380.4000	53.4	33.9 A	H	1.3	135	Y	LOW	32.3	3.7	32.4	0.0	0.0	37.5	-16.5	54.0	
2380.4000	53.9	34.4 A	H	2.0	180	Z	LOW	32.3	3.7	32.4	0.0	0.0	38.0	-16.0	54.0	
2380.4000	60.1	40.6 A	V	1.3	180	X	LOW	32.3	3.7	32.4	0.0	0.0	44.2	-9.8	54.0	
2380.4000	60.5	41.0 A	V	2.0	180	Y	LOW	32.3	3.7	32.4	0.0	0.0	44.6	-9.4	54.0	
2380.4000	61.8	42.3 A	V	1.3	135	Z	LOW	32.3	3.7	32.4	0.0	0.0	45.9	-8.1	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

PAGE 2 of PAGE 7

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	Interlink Electronics	DATE	12/12/03
EUT	InFocus Transmitter	DUTY CYCLE	10.63 %
MODEL	IFS Presenter 2.4	PEAK TO AVG	-19.4693347 dB
TEST MODE	SPURIOUS (NON-HARMONIC) EMISSIONS - MIDDLE CHANNEL	TEST DIST.	3 Meters
TEST ENGINEER	Kirit Ramani	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
2408.7200	53.1	33.6 A	H	1.3	180	X	LOW	32.3	3.6	32.6	0.0	0.0	37.0	-17.0	54.0	
2408.7200	58.6	39.1 A	H	1.0	225	Y	LOW	32.3	3.6	32.6	0.0	0.0	42.5	-11.5	54.0	
2408.7200	52.5	33.0 A	H	2.0	180	Z	LOW	32.3	3.6	32.6	0.0	0.0	36.4	-17.6	54.0	
2408.7200	60.7	41.2 A	V	1.3	180	X	LOW	32.3	3.6	32.6	0.0	0.0	44.6	-9.4	54.0	
2408.7200	61.2	41.7 A	V	2.0	180	Y	LOW	32.3	3.6	32.6	0.0	0.0	45.1	-8.9	54.0	
2408.7200	61.4	41.9 A	V	1.3	135	Z	LOW	32.3	3.6	32.6	0.0	0.0	45.3	-8.7	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	Interlink Electronics	DATE	12/12/03
EUT	InFocus Transmitter	DUTY CYCLE	10.63 %
MODEL	IFS Presenter 2.4	PEAK TO AVG	-19.4693347 dB
TEST MODE	SPURIOUS (NON-HARMONIC) EMISSIONS - MIDDLE CHANNEL	TEST DIST.	3 Meters
TEST ENGINEER	Kirit Ramani	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
2462.3400	56.2	36.7 A	H	1.5	180	X	LOW	32.3	3.5	33.0	0.0	0.0	39.6	-14.4	54.0	
2462.3400	54.7	35.2 A	H	1.0	225	Y	LOW	32.3	3.5	33.0	0.0	0.0	38.1	-15.9	54.0	
2462.3400	50.7	31.2 A	H	1.5	180	Z	LOW	32.3	3.5	33.0	0.0	0.0	34.1	-19.9	54.0	
2462.3400	59.8	40.3 A	V	1.3	180	X	LOW	32.3	3.5	33.0	0.0	0.0	43.2	-10.8	54.0	
2462.3400	59.4	39.9 A	V	2.5	180	Y	LOW	32.3	3.5	33.0	0.0	0.0	42.8	-11.2	54.0	
2462.3400	59.7	40.2 A	V	1.3	90	Z	LOW	32.3	3.5	33.0	0.0	0.0	43.1	-10.9	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	Interlink Electronics	DATE	12/12/03
EUT	InFocus Transmitter	DUTY CYCLE	10.63 %
MODEL	IFS Presenter 2.4	PEAK TO AVG	-19.4693347 dB
TEST MODE	SPURIOUS (NON-HARMONIC) EMISSIONS - MIDDLE CHANNEL	TEST DIST.	3 Meters
TEST ENGINEER	Kirit Ramani	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
2495.3400	54.5	35.0 A	H	1.5	135	X	LOW	32.3	3.4	33.2	0.0	0.0	37.6	-16.4	54.0	
2495.3400	55.2	35.7 A	H	1.0	225	Y	LOW	32.3	3.4	33.2	0.0	0.0	38.3	-15.7	54.0	
2495.3400	51.5	32.0 A	H	2.0	180	Z	LOW	32.3	3.4	33.2	0.0	0.0	34.6	-19.4	54.0	
2495.3400	58.8	39.3 A	V	1.3	180	X	LOW	32.3	3.4	33.2	0.0	0.0	41.9	-12.1	54.0	
2495.3400	59.5	40.0 A	V	2.0	180	Y	LOW	32.3	3.4	33.2	0.0	0.0	42.6	-11.4	54.0	
2495.3400	58.4	38.9 A	V	2.0	90	Z	LOW	32.3	3.4	33.2	0.0	0.0	41.5	-12.5	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	Interlink Electronics	DATE	12/12/03
EUT	InFocus Transmitter	DUTY CYCLE	10.63 %
MODEL	IFS Presenter 2.4	PEAK TO AVG	-19.4693347 dB
TEST MODE	SPURIOUS (NON-HARMONIC) EMISSIONS - MIDDLE CHANNEL	TEST DIST.	3 Meters
TEST ENGINEER	Kirit Ramani	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
2560.7400	52.5	33.0 A	H	1.3	135	X	LOW	32.2	3.5	33.1	0.0	0.0	35.7	-18.3	54.0	
2560.7400	52.3	32.8 A	H	1.0	225	Y	LOW	32.2	3.5	33.1	0.0	0.0	35.5	-18.5	54.0	
2560.7400	49.7	30.2 A	H	2.0	180	Z	LOW	32.2	3.5	33.1	0.0	0.0	32.9	-21.1	54.0	
2560.7400	57.1	37.6 A	V	1.3	180	X	LOW	32.2	3.5	33.1	0.0	0.0	40.3	-13.7	54.0	
2560.7400	58.1	38.6 A	V	2.0	180	Y	LOW	32.2	3.5	33.1	0.0	0.0	41.3	-12.7	54.0	
2560.7400	57.9	38.4 A	V	2.0	90	Z	LOW	32.2	3.5	33.1	0.0	0.0	41.1	-12.9	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	Interlink Electronics	DATE	12/12/03
EUT	InFocus Transmitter	DUTY CYCLE	10.63 %
MODEL	IFS Presenter 2.4	PEAK TO AVG	-19.4693347 dB
TEST MODE	SPURIOUS (NON-HARMONIC) EMISSIONS - MIDDLE CHANNEL	TEST DIST.	3 Meters
TEST ENGINEER	Kirit Ramani	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
2704.9000	49.4	29.9 A	H	1.5	180	X	LOW	31.9	3.9	32.7	0.0	0.0	33.0	-21.0	54.0	Note: No Non Harmonic emissions
2704.9000	48.6	29.1 A	H	1.5	180	Y	LOW	31.9	3.9	32.7	0.0	0.0	32.2	-21.8	54.0	detected above 2704.90 MHz
2704.9000	49.5	30.0 A	H	2.0	180	Z	LOW	31.9	3.9	32.7	0.0	0.0	33.1	-20.9	54.0	
2704.9000	55.5	36.0 A	V	1.3	180	X	LOW	31.9	3.9	32.7	0.0	0.0	39.1	-14.9	54.0	
2704.9000	54.4	34.9 A	V	2.0	180	Y	LOW	31.9	3.9	32.7	0.0	0.0	38.0	-16.0	54.0	
2704.9000	54.0	34.5 A	V	2.0	90	Z	LOW	31.9	3.9	32.7	0.0	0.0	37.6	-16.4	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	Interlink Electronics	DATE	12/12/03
EUT	InFocus Transmitter	DUTY CYCLE	10.63 %
MODEL	IFS Presenter 2.4	PEAK TO AVG	-19.4693347 dB
TEST MODE	SPURIOUS (NON-HARMONIC) EMISSIONS - HIGH CHANNEL	TEST DIST.	3 Meters
TEST ENGINEER	Kirit Ramani	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
2438.6800	58.7	39.2 A	H	1.5	225	X	LOW	32.3	3.5	32.8	0.0	0.0	42.3	-11.7	54.0	Note: No Emissions detected below
2438.6800	60.4	40.9 A	H	1.5	135	Y	LOW	32.3	3.5	32.8	0.0	0.0	44.0	-10.0	54.0	2438.68 MHz
2438.6800	59.4	39.9 A	H	1.5	180	Z	LOW	32.3	3.5	32.8	0.0	0.0	43.0	-11.0	54.0	
2438.6800	59.9	40.4 A	V	1.3	180	X	LOW	32.3	3.5	32.8	0.0	0.0	43.5	-10.5	54.0	
2438.6800	61.5	42.0 A	V	1.3	180	Y	LOW	32.3	3.5	32.8	0.0	0.0	45.1	-8.9	54.0	
2438.6800	60.5	41.0 A	V	1.5	90	Z	LOW	32.3	3.5	32.8	0.0	0.0	44.1	-9.9	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	Interlink Electronics	DATE	12/12/03
EUT	InFocus Transmitter	DUTY CYCLE	10.63 %
MODEL	IFS Presenter 2.4	PEAK TO AVG	-19.4693347 dB
TEST MODE	SPURIOUS (NON-HARMONIC) EMISSIONS - HIGH CHANNEL	TEST DIST.	3 Meters
TEST ENGINEER	Kirit Ramani	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
2465.1800	56.8	37.3 A	H	1.5	90	X	LOW	32.3	3.5	33.0	0.0	0.0	40.1	-13.9	54.0	
2465.1800	56.5	37.0 A	H	1.5	225	Y	LOW	32.3	3.5	33.0	0.0	0.0	39.8	-14.2	54.0	
2465.1800	55.8	36.3 A	H	1.5	180	Z	LOW	32.3	3.5	33.0	0.0	0.0	39.1	-14.9	54.0	
2465.1800	58.8	39.3 A	V	1.3	180	X	LOW	32.3	3.5	33.0	0.0	0.0	42.1	-11.9	54.0	
2465.1800	60.2	40.7 A	V	1.3	180	Y	LOW	32.3	3.5	33.0	0.0	0.0	43.5	-10.5	54.0	
2465.1800	60.6	41.1 A	V	1.5	135	Z	LOW	32.3	3.5	33.0	0.0	0.0	43.9	-10.1	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	Interlink Electronics	DATE	12/12/03
EUT	InFocus Transmitter	DUTY CYCLE	10.63 %
MODEL	IFS Presenter 2.4	PEAK TO AVG	-19.4693347 dB
TEST MODE	SPURIOUS (NON-HARMONIC) EMISSIONS - HIGH CHANNEL	TEST DIST.	3 Meters
TEST ENGINEER	Kirit Ramani	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
2496.2800	55.1	35.6 A	H	1.3	135	X	LOW	32.3	3.4	33.2	0.0	0.0	38.2	-15.8	54.0	
2496.2800	55.1	35.6 A	H	1.5	225	Y	LOW	32.3	3.4	33.2	0.0	0.0	38.2	-15.8	54.0	
2496.2800	50.5	31.0 A	H	1.8	0	Z	LOW	32.3	3.4	33.2	0.0	0.0	33.6	-20.4	54.0	
2496.2800	58.9	39.4 A	V	1.3	180	X	LOW	32.3	3.4	33.2	0.0	0.0	42.0	-12.0	54.0	
2496.2800	58.6	39.1 A	V	1.3	180	Y	LOW	32.3	3.4	33.2	0.0	0.0	41.7	-12.3	54.0	
2496.2800	59.2	39.7 A	V	1.5	135	Z	LOW	32.3	3.4	33.2	0.0	0.0	42.3	-11.7	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	Interlink Electronics	DATE	12/12/03
EUT	InFocus Transmitter	DUTY CYCLE	10.63 %
MODEL	IFS Presenter 2.4	PEAK TO AVG	-19.4693347 dB
TEST MODE	SPURIOUS (NON-HARMONIC) EMISSIONS - HIGH CHANNEL	TEST DIST.	3 Meters
TEST ENGINEER	Kirit Ramani	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
2561.7500	54.1	34.6 A	H	1.5	135	X	LOW	32.2	3.5	33.1	0.0	0.0	37.3	-16.7	54.0	
2561.7500	53.6	34.1 A	H	1.5	270	Y	LOW	32.2	3.5	33.1	0.0	0.0	36.8	-17.2	54.0	
2561.7500	48.9	29.4 A	H	2.0	45	Z	LOW	32.2	3.5	33.1	0.0	0.0	32.1	-21.9	54.0	
2561.7500	56.6	37.1 A	V	1.3	180	X	LOW	32.2	3.5	33.1	0.0	0.0	39.8	-14.2	54.0	
2561.7500	54.7	35.2 A	V	1.3	180	Y	LOW	32.2	3.5	33.1	0.0	0.0	37.9	-16.1	54.0	
2561.7500	57.1	37.6 A	V	1.5	90	Z	LOW	32.2	3.5	33.1	0.0	0.0	40.3	-13.7	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	Interlink Electronics	DATE	12/12/03
EUT	InFocus Transmitter	DUTY CYCLE	10.63 %
MODEL	IFS Presenter 2.4	PEAK TO AVG	-19.4693347 dB
TEST MODE	SPURIOUS (NON-HARMONIC) EMISSIONS - HIGH CHANNEL	TEST DIST.	3 Meters
TEST ENGINEER	Kirit Ramani	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
2706.3800	48.1	28.6 A	H	1.5	225	X	LOW	31.9	3.9	32.7	0.0	0.0	31.7	-22.3	54.0	Note: No Non Harmonic emissions
2706.3800	49.7	30.2 A	H	1.8	225	Y	LOW	31.9	3.9	32.7	0.0	0.0	33.3	-20.7	54.0	detected above 2706.38 MHz
2706.3800	48.5	29.0 A	H	2.0	180	Z	LOW	31.9	3.9	32.7	0.0	0.0	32.1	-21.9	54.0	
2706.3800	54.2	34.7 A	V	1.3	180	X	LOW	31.9	3.9	32.7	0.0	0.0	37.8	-16.2	54.0	
2706.3800	51.5	32.0 A	V	1.3	180	Y	LOW	31.9	3.9	32.7	0.0	0.0	35.1	-18.9	54.0	
2706.3800	51.6	32.1 A	V	1.3	270	Z	LOW	31.9	3.9	32.7	0.0	0.0	35.2	-18.8	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

Test Location : Compatible Electronics
Customer : INTERLINK ELECTRONICS
Manufacturer : INTERLINK ELECTRONICS
Eut name : INFOCUS
Model : IFS PRESENTER 2
Serial # :
Specification : FCC Class B
Distance correction factor (20 * log(test/spec)) : 0.00
Test Mode : TESTED BY MICHAEL CHRISTENSEN


Page : 1/1
Date : 12/15/2003
Time : 16:07:22
Lab : D
Test Distance : 3 Meters

Pol	Freq	Rdng	Cable	Ant	Amp	Cor'd	Limit	Delta
	MHZ	dBuV	loss	factor	gain	rdg = R	= L	R-L
			dB	dB	dB	dBuV	dBuV/m	dB

NO EMISSIONS FOUND FROM 10 KHZ TO 1 GHZ


BAND EDGES

DATA SHEETS



INTERLINK ELECTRONICS
InFocus TRANSMITTER
MODEL: IFS PRESENTER 2.4
FCC SUBPART C – BAND EDGES – 12-12-03

**PHOTOGRAPH SHOWING THE LOW BAND EDGE
TAKEN AT 3 METERS**



INTERLINK ELECTRONICS
InFocus TRANSMITTER
MODEL: IFS PRESENTER 2.4
FCC SUBPART C – BAND EDGES – 12-12-03

**PHOTOGRAPH SHOWING THE HIGH BAND EDGE
TAKEN AT 3 METERS**

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	Interlink Electronics	DATE	12/12/03
EUT	InFocus Transmitter	DUTY CYCLE	10.63 %
MODEL	IFS Presenter 2.4	PEAK TO AVG	-19.4693347 dB
S/N	N/A	TEST DIST.	3 Meters
TEST ENGINEER	Kirit Ramani	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
2400.0000	67.3	47.8 A	H	2.0	90	Z	LOW	32.3	3.6	32.6	0.0	0.0	51.2	-2.8	54.0	Band Edge - Low Channel
2483.5000	63.7	44.2 A	H	1.0	180	X	LOW	32.3	3.4	33.1	0.0	0.0	46.9	-7.1	54.0	Band Edge - High Channel
																Note: Horizontal Polarization
																is the worst case.

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

PAGE 1