

FCC TEST REPORT

REPORT NO.: RF910410R01

MODEL NO.: WLL030M
WLL030

RECEIVED: April 10, 2002

TESTED: April 15 ~ April 18, 2002

APPLICANT: ASKEY COMPUTER CORP.

ADDRESS: 2/FL, No. 2, Lane 497 Chung Cheng Road, Hsin Tien,
Taipei, Taiwan R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: 47 14th Lin, Chiapau Tsun, Linko, Taipei,
Taiwan, R.O.C.

This test report consists of 53 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, NVLAP or any government agencies. The test results in the report only apply to the tested sample.



0528
ILAC MRA



Lab Code: 200102-0



Table of Contents

1	CERTIFICATION	4
2	SUMMARY OF TEST RESULTS	5
3	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT	6
3.2	DESCRIPTION OF TEST MODES	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	7
3.4	DESCRIPTION OF SUPPORT UNITS	8
4	TEST TYPES AND RESULTS	9
4.1	CONDUCTED EMISSION MEASUREMENT	9
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	9
4.1.2	TEST INSTRUMENTS	9
4.1.3	TEST PROCEDURES	10
4.1.4	TEST SETUP	10
4.1.5	EUT OPERATING CONDITIONS	11
4.1.6	TEST RESULTS	12
4.2	RADIATED EMISSION MEASUREMENT	18
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	18
4.2.2	TEST INSTRUMENTS	19
4.2.3	TEST PROCEDURES	20
4.2.4	TEST SETUP	21
4.2.5	EUT OPERATING CONDITIONS	21
4.2.6	TEST RESULTS (A)	22
4.2.7	TEST RESULTS (B)	27
4.3	6DB BANDWIDTH MEASUREMENT	31
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	31
4.3.2	TEST INSTRUMENTS	31
4.3.3	TEST PROCEDURE	32
4.3.4	TEST SETUP	32
4.3.5	EUT OPERATING CONDITIONS	32
4.3.6	TEST RESULTS	33
4.4	MAXIMUM PEAK OUTPUT POWER	37
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	37
4.4.2	TEST INSTRUMENTS	37
4.4.3	TEST PROCEDURES	38
4.4.4	TEST SETUP	38



4.4.5	EUT OPERATING CONDITIONS.....	38
4.4.6	TEST RESULTS.....	39
4.5	POWER SPECTRAL DENSITY MEASUREMENT.....	40
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	40
4.5.2	TEST INSTRUMENTS	40
4.5.3	TEST PROCEDURE	41
4.5.4	TEST SETUP	41
4.5.5	EUT OPERATING CONDITIONS.....	41
4.5.6	TEST RESULTS.....	42
4.6	BAND EDGES MEASUREMENT	46
4.6.1	LIMITS OF BAND EDGES MEASUREMENT	46
4.6.2	TEST INSTRUMENTS	46
4.6.3	TEST PROCEDURE	46
4.6.4	EUT OPERATING CONDITION	47
4.6.5	TEST RESULTS.....	47
4.7	ANTENNA REQUIREMENT	50
4.7.1	STANDARD APPLICABLE	50
4.7.2	ANTENNA CONNECTED CONSTRUCTION.....	50
5	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	51
6	INFORMATION ON THE TESTING LABORATORIES	53



1 CERTIFICATION

PRODUCT : Mini PCI Combo Card
BRAND NAME : Askey
MODEL NO. : WLL030M
WLL030
APPLICANT : ASKEY COMPUTER CORP.
STANDARDS : 47 CFR Part 15, Subpart C (Section 15.247),
ANSI C63.4-1992, Canada RSS 210,
New Zealand RFS 29

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility from April 15 to April 18, 2002, The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

TESTED BY: Gary Chang, **DATE:** April 25, 2002
Gary Chang

CHECKED BY: Rennie Wang, **DATE:** April 25, 2002
Rennie Wang

APPROVED BY: Alan Lane, **DATE:** April 25, 2002
Dr. Alan Lane
Manager

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: 47 CFR Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission Limit: 48dBuV	PASS	Meet the requirement of limit Minimum passing margin is -11.13dBuV at 0.58MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -2.1dBuV at 176.00MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Mini PCI Combo Card
MODEL NO.	WLL030M, WLL030
POWER SUPPLY	3.3VDC
MODULATION TYPE	CCK, DBPSK, DQPSK
RADIO TECHNOLOGY	DSSS
TRANSFER RATE	1/2/5.5/11Mbps
FREQUENCY RANGE	2412MHz ~ 2467MHz
NUMBER OF CHANNEL	11
OUTPUT POWER	14.94dBm
ANTENNA TYPE	Inverted F Antenna
DATA CABLE	NA
I/O PORTS	NA
ASSOCIATED DEVICES	NA

NOTE:

1. Model WLL030M and WLL030 are identical except for model number and the model WLL030 is designed without modem part.
2. There are three antenna types provided to this EUT, and the minimum antenna gain (-3dBi) and the maximum antenna gain (-2dBi) were chosen for the final test.
3. This EUT was tested with the NB adapter which model number is SA80-3105, brand is ASTEC.
4. This EUT was tested with the Platform which model number is ACY25D01001, brand is COMPAL.
5. For a more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided in this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

NOTE:

1. Below 1 GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, worst case one, was chosen for final test.
2. Above 1 GHz, the channel 1, 6, and 11 were tested individually.
3. The test result A is for the maximum antenna gain (-2dBi) and the test result B is for the minimum antenna gain (-3dBi).

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a Mini PCI Combo Card. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC CFR 47 Part 15, Subpart C. (15.247)

ANSI C63.4 : 1992

All tests have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	IBM	THMKPAD A20M	NA	NA
2	PRINTER	EPSON	LQ-300+	DCGY017096	FCC DOC APPROVED
3	MODEM	ACEEX	1414	980020510	IFAXDM1414

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	1.8 m unshielded, DC connector, with core.
2	1.2m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core
3	1.2 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core.

NOTE: All power cords of the above support units are non shielded (1.8m).

4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class B (dBuV)	
	Quasi-peak	Average
0.45 – 30	48	-

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. All emanations from a class B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESHS30	828109/007	July 4, 2002
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH3-Z5	839135/006	July 3, 2002
* ROHDE & SCHWARZ 4-wire ISN	ENY41	838119/028	Dec. 2, 2002
* ROHDE & SCHWARZ 2-wire ISN	ENY22	837497/016	Dec. 2, 2002
EMCO-L.I.S.N. (for peripheral)	3825/2	9204-1964	July 3, 2002
Software	Cond-V2L	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C02.01	July 5, 2002
HP Terminator (For EMCO LISN)	11593A	E1-01-298	Feb. 20, 2003
HP Terminator (For EMCO LISN)	11593A	E1-01-299	Feb. 20, 2003
Shielded Room	Site 2	ADT-C02	NA
VCCI Site Registration No.	Site 2	C-240	NA

NOTE: 1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.


2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

3. “*”: These equipment are used for conducted telecom port test only (if tested).

4.1.3 TEST PROCEDURES

- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 450 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported

4.1.4 TEST SETUP



- Note:**
- Support units were connected to second LISN.
 - Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



4.1.5 EUT OPERATING CONDITIONS

- a. Plug the EUT into the PCI extender which connected to a computer system placed on a testing table.
- b. The computer system ran a test program to enable EUT under transmission/receiving condition continuously at specific channel frequency.
- c. The computer system sent "H" messages to its screen.
- d. The computer system sent "H" messages to modem.
- e. The computer system sent "H" messages to printer, and the printer prints them on paper.


4.1.6 TEST RESULTS

EUT	Mini PCI Combo Card	MODEL	WLL030M
MODE	Channel 1	6dB BANDWIDTH	10 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 1005 hPa	TESTED BY: Gary Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.584	0.10	34.26	-	34.36	-	48.00	-	-13.64	-
2	0.857	0.10	36.10	-	36.20	-	48.00	-	-11.80	-
3	2.124	0.11	36.24	-	36.35	-	48.00	-	-11.65	-
4	7.473	0.42	33.41	-	33.83	-	48.00	-	-14.17	-
5	12.839	0.67	30.22	-	30.89	-	48.00	-	-17.11	-
6	22.361	1.05	25.99	-	27.04	-	48.00	-	-20.96	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	Mini PCI Combo Card	MODEL	WLL030M
MODE	Channel 1	6dB BANDWIDTH	10 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 1005 hPa	TESTED BY: Gary Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.579	0.10	28.62	-	28.72	-	48.00	-	-19.28	-
2	0.828	0.10	28.16	-	28.26	-	48.00	-	-19.74	-
3	1.542	0.10	32.43	-	32.53	-	48.00	-	-15.47	-
4	7.541	0.36	27.21	-	27.57	-	48.00	-	-20.43	-
5	12.806	0.51	30.28	-	30.79	-	48.00	-	-17.21	-
6	21.782	0.84	31.99	-	32.83	-	48.00	-	-15.17	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	Mini PCI Combo Card	MODEL	WLL030M
MODE	Channel 6	6dB BANDWIDTH	10 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 1005 hPa	TESTED BY: Gary Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.564	0.10	34.38	-	34.48	-	48.00	-	-13.52	-
2	1.122	0.10	34.37	-	34.47	-	48.00	-	-13.53	-
3	1.545	0.10	32.61	-	32.71	-	48.00	-	-15.29	-
4	1.545	0.10	33.18	-	33.28	-	48.00	-	-14.72	-
5	6.821	0.39	30.77	-	31.16	-	48.00	-	-16.84	-
6	12.956	0.68	31.25	-	31.93	-	48.00	-	-16.07	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	Mini PCI Combo Card	MODEL	WLL030M
MODE	Channel 6	6dB BANDWIDTH	10 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 1005 hPa	TESTED BY: Gary Chang	

No	Freq.	Corr. Factor	Reading Value [dB (Uv)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.858	0.10	33.05	-	33.15	-	48.00	-	-14.85	-
2	1.347	0.10	30.24	-	30.34	-	48.00	-	-17.66	-
3	2.019	0.10	33.64	-	33.74	-	48.00	-	-14.26	-
4	7.184	0.35	30.86	-	31.21	-	48.00	-	-16.79	-
5	15.008	0.60	31.99	-	32.59	-	48.00	-	-15.41	-
6	24.329	0.89	30.87	-	31.76	-	48.00	-	-16.24	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	Mini PCI Combo Card	MODEL	WLL030M
MODE	Channel 11	6dB BANDWIDTH	10 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 1005 hPa	TESTED BY: Gary Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.477	0.10	33.84	-	33.94	-	48.00	-	-14.06	-
2	0.584	0.10	36.77	-	36.87	-	48.00	-	-11.13	-
3	1.539	0.10	33.36	-	33.46	-	48.00	-	-14.54	-
4	3.279	0.23	30.59	-	30.82	-	48.00	-	-17.18	-
5	13.076	0.68	31.13	-	31.81	-	48.00	-	-16.19	-
6	22.973	1.06	25.71	-	26.77	-	48.00	-	-21.23	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	Mini PCI Combo Card	MODEL	WLL030M
MODE	Channel 11	6dB BANDWIDTH	10 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Netural (N)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 1005 hPa	TESTED BY: Bruce Shiau	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.750	0.10	33.09	-	33.19	-	48.00	-	-14.81	-
2	1.395	0.10	32.89	-	32.99	-	48.00	-	-15.01	-
3	2.019	0.10	34.80	-	34.90	-	48.00	-	-13.10	-
4	6.823	0.35	29.59	-	29.94	-	48.00	-	-18.06	-
5	12.875	0.52	31.28	-	31.80	-	48.00	-	-16.20	-
6	21.077	0.82	30.42	-	31.24	-	48.00	-	-16.76	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Field strength limits are at the distance of 3 meters, emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field Strength of Fundamental	
	uV/m	dBuV/m
30-88	100	40.0
88-216	150	43.5
216-960	200	46.0
Above 960	500	54.0

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
*HP Spectrum Analyzer	8590L	3544A01176	May 7, 2002
*HP Preamplifier	8447D	2944A08485	May 7, 2002
* HP Preamplifier	8449B	3008A01201	Dec. 06, 2002
* HP Preamplifier	8449B	3008A01292	Aug. 21, 2002
* ROHDE & SCHWARZ TEST RECEIVER	ESMI	839013/007 839379/002	Jan. 27, 2003
SCHWARZBECK Tunable Dipole Antenna	VHA 9103 UHA 9105	E101051 E101055	Nov. 23, 2002
* CHASE BILOG Antenna	CBL6112A	2221	Aug. 2, 2002
* SCHWARZBECK Horn Antenna	BBHA9120-D1	D130	July 6, 2002
* EMCO Horn Antenna	3115	9312-4192	April 9, 2003
* EMCO Turn Table	1060	1115	NA
* SHOSHIN Tower	AP-4701	A6Y005	NA
* Software	AS61D4	NA	NA
* ANRITSU RF Switches	MP59B	M35046	Aug. 2, 2002
* TIMES RF cable	LMR-600	CABLE-ST5-01	Aug. 2, 2002
Open Field Test Site	Site 5	ADT-R05	July 28, 2002
VCCI Site Registration No.	Site 5	R-1039	NA
Site Registration No.	FCC: 90422 Canada IC: IC 3789 VCCI : R-1039		

- NOTE:** 1. The measurement uncertainty is less than +/- 3.0dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
3. "*" = These equipment are used for the final measurement.
4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.




4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 300 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.5 EUT OPERATING CONDITIONS

Same as 4.1.5.

4.2.6 TEST RESULTS (A)

EUT	Mini PCI Combo Card	MODEL	WLL030M
MODE	Channel 11	FREQUENCY RANGE	30-1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25 deg. C, 50%RH, 1050 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	132.00	39.8 QP	43.50	-3.70	1.61H	300	27.50	11.16	1.13	0.00	-12.29
2	166.00	40.8 QP	43.50	-2.70	1.54H	329	30.07	9.44	1.29	0.00	-10.74
3	176.00	41.4 QP	43.50	-2.10	1.40H	175	31.00	9.08	1.33	0.00	-10.42
4	220.00	42.6 QP	46.00	-3.40	1.41H	281	31.00	10.12	1.51	0.00	-11.63
5	233.60	43.0 QP	46.00	-3.00	1.31H	12	30.44	10.98	1.58	0.00	-12.56
6	264.00	43.6 QP	46.00	-2.40	1.27H	51	29.00	12.89	1.70	0.00	-14.58
7	300.00	40.0 QP	46.00	-6.00	1.24H	311	24.94	13.18	1.88	0.00	-15.06
8	352.00	36.0 QP	46.00	-10.00	1.22H	307	19.64	14.31	2.05	0.00	-16.36
9	366.00	38.0 QP	46.00	-8.00	1.08H	149	21.04	14.86	2.11	0.00	-16.97
10	396.00	34.7 QP	46.00	-11.30	1.01H	5	16.52	15.96	2.22	0.00	-18.19
11	440.00	32.0 QP	46.00	-14.00	1.31H	239	13.31	16.32	2.38	0.00	-18.69

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	66.60	34.0 QP	40.00	-6.00	1.35V	198	27.21	5.98	0.81	0.00	-6.79
2	132.00	35.0 QP	43.50	-8.50	1.28V	358	22.71	11.16	1.13	0.00	-12.29
3	166.00	36.0 QP	43.50	-7.50	1.05V	18	25.27	9.44	1.29	0.00	-10.73
4	176.00	35.8 QP	43.50	-7.70	1.08V	18	25.39	9.08	1.33	0.00	-10.41
5	233.00	37.0 QP	46.00	-9.00	1.06V	72	24.44	10.98	1.58	0.00	-12.57
6	264.00	35.0 QP	46.00	-11.00	1.04V	5	20.42	12.89	1.70	0.00	-14.59
7	308.00	29.4 QP	46.00	-16.60	1.65V	192	14.11	13.38	1.91	0.00	-15.29
8	352.00	32.4 QP	46.00	-13.60	1.66V	209	16.04	14.31	2.05	0.00	-16.36
9	373.00	38.0 QP	46.00	-8.00	1.04V	250	20.83	15.04	2.13	0.00	-17.18
10	400.00	35.0 QP	46.00	-11.00	1.07V	322	16.65	16.11	2.24	0.00	-18.35
11	440.00	34.0 QP	46.00	-12.00	1.33V	133	15.31	16.32	2.38	0.00	-18.69
12	528.00	31.8 QP	46.00	-14.20	1.46V	180	11.58	17.62	2.60	0.00	-20.22
13	572.00	28.0 QP	46.00	-18.00	1.37V	359	7.00	18.25	2.75	0.00	-21.00

NOTE:

1. Emission level = Raw value - Correction Factor



2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. The other emission levels were very low against the limit.

EUT	Mini PCI Combo Card	MODEL	WLL030M
MODE	Channel 1	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 50%RH, 1050 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2038.00	48.6 PK	74.00	-25.40	1.12H	279	53.40	25.20	4.86	34.90	4.84
2	*2413.00	99.5 PK	-	-	1.11V	358	67.30	27.11	5.10	0.00	-32.21
3	*2413.00	94.0 AV	-	-	1.11V	358	61.80	27.11	5.10	0.00	-32.21
4	4076.00	45.4 PK	74.00	-28.60	1.10H	245	43.00	30.13	6.78	34.52	-2.39
5	4824.00	47.5 PK	74.00	-26.50	1.05H	206	43.50	31.43	7.23	34.63	-4.02

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (DbuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2038.00	49.2 PK	74.00	-24.80	1.36V	122	54.00	25.20	4.86	34.90	4.84
2	*2413.00	65.1 PK	-	-	1.09V	186	67.80	27.11	5.10	34.90	2.70
3	*2413.00	60.0 AV	-	-	1.09V	186	62.70	27.11	5.10	34.90	2.70
4	4076.00	47.4 PK	74.00	-26.60	1.36V	357	45.00	30.13	6.78	34.52	-2.39
5	4113.00	43.2 PK	74.00	-30.80	1.38V	330	40.80	30.23	6.72	34.54	-2.40
6	4824.00	46.7 PK	74.00	-27.30	1.41V	24	42.70	31.43	7.23	34.63	-4.02

NOTE:

1. Emission level = Raw value - Correction Factor
2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. " * " : Fundamental frequency
5. The other emission levels were very low against the limit.

EUT	Mini PCI Combo Card	MODEL	WLL030M
MODE	Channel 6	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 50%RH, 1050 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2063.00	49.6 PK	74.00	-24.40	1.13H	281	54.10	25.41	4.96	34.90	4.53
2	*2437.00	98.6 PK	-	-	1.12H	225	66.20	27.33	5.08	0.00	-32.40
3	*2437.00	93.1 AV	-	-	1.12H	225	60.70	27.33	5.08	0.00	-32.40
4	4126.00	46.1 PK	74.00	-27.90	1.15H	140	43.60	30.32	6.70	34.56	-2.46
5	4874.00	47.1 PK	74.00	-26.90	1.33H	324	43.00	31.47	7.21	34.63	-4.05

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2063.00	49.6 PK	74.00	-24.40	1.13H	281	54.10	25.41	4.96	34.90	4.53
2	*2437.00	98.6 PK	-	-	1.12H	225	66.20	27.33	5.08	0.00	-32.40
3	*2437.00	93.1 AV	-	-	1.12H	225	60.70	27.33	5.08	0.00	-32.40
4	4126.00	46.1 PK	74.00	-27.90	1.15H	140	43.60	30.32	6.70	34.56	-2.46
5	4874.00	47.1 PK	74.00	-26.90	1.33H	324	43.00	31.47	7.21	34.63	-4.05

NOTE:

1. Emission level = Raw value - Correction Factor
2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. " * " : Fundamental frequency
5. The other emission levels were very low against the limit.

EUT	Mini PCI Combo Card	MODEL	WLL030M
MODE	Channel 11	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 50%RH, 1050 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2088.00	50.7 PK	74.00	-23.30	1.22H	166	55.00	25.62	5.02	34.90	4.26
2	*2463.00	98.3 PK	-	-	1.85H	9	65.90	27.33	5.08	0.00	-32.40.
3	*2463.00	92.4 AV	-	-	1.85H	9	60.00	27.33	5.08	0.00	-32.40.
4	2486.00	45.7 PK	74.00	-28.30	1.18H	87	48.00	27.54	5.06	34.90	2.32
5	4176.00	46.6 PK	74.00	-27.40	1.34H	71	44.10	30.41	6.68	34.58	-2.51
6	4924.00	47.5 PK	74.00	-26.50	1.20H	245	43.40	31.51	7.21	34.62	-4.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (DbuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2088.00	50.1 PK	74.00	-23.90	1.46V	165	54.40	25.62	5.02	34.90	4.26
2	*2463.00	102.4 PK	-	-	1.20V	322	70.00	27.33	5.08	0.00	-32.41
3	*2463.00	95.4 AV	-	-	1.20V	322	63.00	27.33	5.08	0.00	-32.41
4	2494.00	45.9 PK	74.00	-28.10	1.45V	100	48.20	27.54	5.06	34.90	2.31
5	4176.00	46.2 PK	74.00	-27.80	1.37V	80	43.70	30.41	6.68	34.58	-2.51
6	4924.00	47.1 PK	74.00	-26.90	1.37V	112	43.00	31.51	7.21	34.62	-4.10

NOTE:

1. Emission level = Raw value - Correction Factor
2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. " * " : Fundamental frequency
5. The other emission levels were very low against the limit.

4.2.7 TEST RESULTS (B)

EUT	Mini PCI Combo Card	MODEL	WLL030M
MODE	Channel 11	FREQUENCY RANGE	30-1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25 deg. C, 50%RH, 1050 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	132.00	29.0 QP	43.50	-14.50	1.63H	187	16.71	11.16	1.13	0.00	-12.29
2	166.00	38.4 QP	43.50	-5.10	1.84H	38	27.67	9.44	1.29	0.00	-10.73
3	232.00	42.0 QP	46.00	-4.00	1.67H	320	29.59	10.84	1.57	0.00	-12.42
4	232.00	41.8 QP	46.00	-4.20	1.56H	8	29.39	10.84	1.57	0.00	-12.41
5	264.00	38.0 QP	46.00	-8.00	1.24H	355	23.42	12.89	1.70	0.00	-14.59
6	308.00	28.4 QP	46.00	-17.60	1.47H	357	13.11	13.38	1.91	0.00	-15.29
7	352.00	29.0 QP	46.00	-17.00	1.34H	9	12.64	14.31	2.05	0.00	-16.36
8	432.00	31.0 QP	46.00	-15.00	1.05H	151	12.37	16.28	2.35	0.00	-18.63
9	440.00	35.0 QP	46.00	-11.00	1.04H	342	16.31	16.32	2.38	0.00	-18.69
10	748.00	32.0 QP	46.00	-14.00	1.48H	32	8.60	20.14	3.26	0.00	-23.41

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	132.00	30.0 QP	43.50	-13.50	1.39V	5	17.71	11.16	1.13	0.00	-12.29
2	166.00	35.2 QP	43.50	-8.30	1.01V	320	24.47	9.44	1.29	0.00	-10.73
3	232.00	37.0 QP	46.00	-9.00	1.03V	22	24.59	10.84	1.57	0.00	-12.41
4	264.00	31.0 QP	46.00	-15.00	1.00V	355	16.42	12.89	1.70	0.00	-14.58
5	365.00	34.0 QP	46.00	-12.00	1.10V	65	17.14	14.76	2.10	0.00	-16.87
6	396.00	31.7 QP	46.00	-14.30	1.17V	155	13.52	15.96	2.22	0.00	-18.18
7	440.00	31.5 QP	46.00	-14.50	1.50V	5	12.81	16.32	2.38	0.00	-18.69
8	528.00	30.8 QP	46.00	-15.20	1.81V	272	10.58	17.62	2.60	0.00	-20.22
9	531.00	32.7 QP	46.00	-13.30	1.11V	80	12.39	17.69	2.62	0.00	-20.31
10	660.00	32.0 QP	46.00	-14.00	1.69V	158	9.71	19.25	3.05	0.00	-22.29

NOTE:

1. Emission level = Raw value - Correction Factor
2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. The other emission levels were very low against the limit.

EUT	Mini PCI Combo Card	MODEL	WLL030M
MODE	Channel 1	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 50%RH, 1050 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2038.00	49.7 PK	74.00	-24.30	1.00H	354	54.50	25.20	4.86	34.90	4.84
2	*2412.00	100.0 PK	-	-	1.00H	260	67.80	27.11	5.10	0.00	-32.21
3	*2412.00	94.2 AV	-	-	1.00H	260	62.00	27.11	5.10	0.00	-32.21
4	4076.00	45.4 PK	74.00	-28.60	1.65H	15	43.00	30.13	6.78	34.52	-2.39
5	4824.00	46.6 PK	74.00	-27.40	1.39H	95	42.60	31.43	7.23	34.63	-4.02

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (DbuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2038.00	48.9 PK	74.00	-25.10	1.41V	108	53.70	25.20	4.86	34.90	4.84
2	*2412.00	94.6 PK	-	-	1.28V	53	62.40	27.11	5.10	0.00	-32.22
3	*2412.00	89.4 AV	-	-	1.28V	53	57.20	27.11	5.10	0.00	-32.22
4	4076.00	46.4 PK	74.00	-27.60	1.16V	14	44.00	30.13	6.78	34.52	-2.39
5	4824.00	46.5 PK	74.00	-27.50	1.36V	131	42.50	31.43	7.23	34.63	-4.02

NOTE:

1. Emission level = Raw value - Correction Factor
2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. " * " : Fundamental frequency
5. The other emission levels were very low against the limit.

EUT	Mini PCI Combo Card	MODEL	WLL030M
MODE	Channel 6	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 50%RH, 1050 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2063.00	50.6 PK	74.00	-23.40	1.09H	317	55.10	25.41	4.96	34.90	4.53
2	*2437.00	100.4 PK	-	-	1.01H	101	68.00	27.33	5.08	0.00	-32.40
3	*2437.00	93.4 AV	-	-	1.01H	101	61.00	27.33	5.08	0.00	-32.40
4	4126.00	45.2 PK	74.00	-28.80	1.39H	1	42.70	30.32	6.70	34.56	-2.46
5	4874.00	48.1 PK	74.00	-25.90	1.18H	277	44.00	31.47	7.21	34.63	-4.05

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2063.00	50.2 PK	74.00	-23.80	1.04V	53	54.70	25.41	4.96	34.90	4.53
2	*2437.00	96.6 PK	-	-	1.02V	3	64.22	27.33	5.08	0.00	-32.40
3	*2437.00	92.9 AV	-	-	1.02V	3	60.50	27.33	5.08	0.00	-32.40
4	4126.00	47.5 PK	74.00	-26.50	1.46V	353	45.00	30.32	6.70	34.56	-2.46
5	4874.00	46.3 PK	74.00	-27.70	1.27V	4	42.20	31.47	7.21	34.63	-4.05
6	4874.00	47.1 PK	74.00	-26.90	1.22V	358	43.00	31.47	7.21	34.63	-4.05
7	6188.00	47.7 PK	74.00	-26.30	1.24V	189	41.20	33.14	8.01	34.60	-6.55

NOTE:

1. Emission level = Raw value - Correction Factor
2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. " * " : Fundamental frequency
5. The other emission levels were very low against the limit.

EUT	Mini PCI Combo Card	MODEL	WLL030M
MODE	Channel 11	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 50%RH, 1050 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2088.00	50.2 PK	74.00	-23.80	1.18H	352	54.50	25.62	5.02	34.90	4.26
2	*2463.00	94.4 AV	-	-	1.45H	9	62.00	27.33	5.08	0.00	-32.40.
3	*2463.00	99.4 PK	-	-	1.45H	9	67.00	27.33	5.08	0.00	-32.40.
4	2486.00	44.9 PK	74.00	-29.10	1.20H	5	47.20	27.54	5.06	34.90	2.31
5	4176.00	45.7 PK	74.00	-28.30	1.41H	2	43.20	30.41	6.68	34.58	-2.52
6	4924.00	47.1 PK	74.00	-26.90	1.34H	44	43.00	31.51	7.21	34.62	-4.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (DbuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2088.00	50.7 PK	74.00	-23.30	1.26V	354	55.00	25.62	5.02	34.90	4.26
2	*2463.00	93.4 PK	-	-	1.34V	300	61.00	27.33	5.08	0.00	-32.41
3	*2463.00	89.4 AV	-	-	1.34V	300	57.00	27.33	5.08	0.00	-32.41
4	2495.00	45.7 PK	74.00	-28.30	1.36V	5	48.00	27.54	5.06	34.90	2.31
5	4176.00	47.5 PK	74.00	-26.50	1.16V	279	45.00	30.41	6.68	34.58	-2.51
6	4924.00	46.1 PK	74.00	-27.90	1.25V	127	42.00	31.51	7.21	34.62	-4.10
7	6263.00	48.0 PK	74.00	-26.00	1.39V	7	41.00	33.48	8.13	34.60	-7.01

NOTE:

1. Emission level = Raw value - Correction Factor
2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. " * " : Fundamental frequency
5. The other emission levels were very low against the limit.

4.3 6DB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	July 17, 2002

NOTE:

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

4.3.4 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.3.5 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




4.3.6 TEST RESULTS

EUT	Mini PCI Combo Card	MODEL	WLL030M
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	23 deg. C, 54%RH, 1005 hPa
TESTED BY: Steven Lu			


CHANNEL	CHANNEL FREQUENCY (MHz)	6 dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	11.142	0.5	PASS
6	2437	11.182	0.5	PASS
11	2462	11.142	0.5	PASS

[illegible]

CH6



CH11





4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
PEAK POWER SENSOR	NRV-Z32	100013	Feb. 21, 2003
POWER METER	NRVS	100026	Feb. 21, 2003

NOTE:

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST PROCEDURES

The transmitter output was connected to the peak power meter.

4.4.4 TEST SETUP



4.4.5 EUT OPERATING CONDITIONS

Same as Item 4.3.5

4.4.6 TEST RESULTS

EUT	Mini PCI Combo Card	MODEL	WLL030M
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	23 deg. C, 54%RH, 1005 hPa
TESTED BY: Steven Lu			

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	14.85	30	PASS
6	2437	14.82	30	PASS
11	2462	14.94	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	July 17, 2002

NOTE:

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time=span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3KHz for a full response of the mixer in the spectrum analyzer.

4.5.4 TEST SETUP



4.5.5 EUT OPERATING CONDITIONS


Same as 4.3.5

4.5.6 TEST RESULTS


EUT	Mini PCI Combo Card	MODEL	WLL030M
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	23 deg. C, 54%RH, 1005 hPa
TESTED BY: Bunny Yao			

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 KHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-8.84	8	PASS
6	2437	-8.18	8	PASS
11	2462	-8.93	8	PASS


CH1



CH6



CH11



4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	July 17, 2002

NOTE:

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 kHz bandwidth from band edge. The band edges was measured and recorded.




4.6.4 EUT OPERATING CONDITION


Same as Item 4.3.5

4.6.5 TEST RESULTS

The spectrum plots are attached on the following 2 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

NOTE: The band edge emission plot on the following 2 pages shows 49.91dB delta between carrier maximum power and local maximum emission in restrict band (2.4836GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.6 (Page 36) is 99.4dBuV/m, so the maximum field strength in restrict band is $99.4 - 49.91 = 49.49$ dBuV/m which is under 54 dBuV/m limit.







4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION

The Antenna used in this EUT is Inverted F Antenna. The antenna connector type is UFL. And the maximum Gain of these antennas is only -2dBi.

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST



RADIATED EMISSION TEST





6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

USA	FCC, NVLAP
Germany	TUV Rheinland
Japan	VCCI
New Zealand	MoC
Norway	NEMKO
R.O.C.	BSMI, DGT, CNLA

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC Lab:

Tel: 886-35-935343

Fax: 886-35-935342

Lin Kou Safety Lab:

Tel: 886-2-26093195

Fax: 886-2-26093184

Lin Kou RF&Telecom Lab

Tel: 886-3-3270910

Fax: 886-3-3270892

Email: service@mail.adt.com.tw

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.