

Prüfbericht-Nr.: Test Report No.:	18062203.f01	Auftrags-Nr.: Order No.:	300157308394	Seite 1 von 31 Page 1 of 31
Kunden-Referenz-Nr.: Client Reference No.:	4602437	Auftragsdatum: Order date:	July 2, 2018	
Auftraggeber: Client:	Intel Corporation SAS, Le Cargo B6 / 424 Rue de Goa, 06600 Antibes, France			
Prüfgegenstand: Test item:	Wireless Network Card			
Bezeichnung / Typ-Nr.: Identification / Type No.:	AX201D2WL			
Auftrags-Inhalt: Order content:	Compliance with EMC Standards			
Prüfgrundlage: Test specification:	47 CFR PART 15 (10-1-17 EDITION), Subpart 15B ICES-003 (Issue 6, January 2016)			

Wareneingangsdatum: Date of receipt:	Oct. 18, 2018
Prüfmuster-Nr.: Test sample No.:	WFM: 3413E8CAF96
Prüfzeitraum: Testing period:	Oct. 29 – Nov. 1, 2018
Ort der Prüfung: Place of testing:	Leek
Prüflaboratorium: Testing laboratory:	TÜV Rheinland Nederland B.V. Leek Laboratory
Prüfergebnis*: Test result*:	Pass



Geprüft von / tested by:	Kontrolliert von / reviewed by:
Nov 2, 2018 T.E.T. Koning, Senior Engineer EMC	Nov 5, 2018 K.F. van der Molen, Senior expert EMC
Datum Date	Datum Date
Name / Stellung Name / Position	Name / Stellung Name / Position
Unterschrift Signature	Unterschrift Signature

Sonstiges / Other:	None
---------------------------	------

Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged
* Legende: 1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut 3 = befriedigend F(ail) = entspricht nicht o.g. Prüfgrundlage(n)
Legend: 1 = very good P(ass) = passed a.m. Test specification(s)	2 = good 3 = satisfactory F(ail) a.m. test specification(s)
	4 = ausreichend N/A = nicht anwendbar
	5 = mangelhaft N/T = nicht getestet
	4 = sufficient N/A = not applicable
	5 = poor N/T = not tested

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.

This test report only relates to the a.m. testsample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This report does not entitle to carry any test mark

V04

Prüfbericht-Nr: 18062203.f01
Test report No: 18062203.f01

Seite 2 von 31
Page 2 of 31

Liste der verwendeten Prüfmittel
List of used test equipment

Prüfmittel Nr. / ID-Nr. Equipment No. / ID-No.	Prüfmittel Test equipment	Nächste Kalibrierung Next calibration
---	------------------------------	--

Verified List November, 2018				
Conducted emission				
A00726	Rohde & Schwarz	ESCS30	Measurement Receiver	25-10-2019
A01978	Rohde & Schwarz	ESH3-Z2	Impulse Limiter	27-6-2019
A00051	Rohde & Schwarz	ESH3-Z2	Impulse Limiter	15-11-2018
A01980	Rohde & Schwarz	ESCS 30	Test Receiver	28-6-2019
A00022	Emco	3725/2	LISN FCC 50 uH / 50 ohm	30-1-2019
A00023	Emco	3625/2	LISN 5 uH / 50 ohm	14-11-2018
A00354	Rohde & Schwarz	ESH2-Z5	LISN- artificial Network	27-6-2019
A00093	COMTES T	1415	Conducted Reference Source 9kHz-50MHz	4-6-2019
A02011	Rohde & Schwarz	ESH 3-Z5	LISN	7-11-2018
Radiated emission				
A00314	Rohde & Schwarz	ESCI	Measurement Receiver (9kHz-3GHz)	13-4-2019
A00337	R&S	FSV30	Signal Analyzer/Spectrum Analyzer	21-6-2019
A00077	Chase	CBL6111B	Biconilog	1-12-2019
A00029	Emco	4610	Gen. field source	29-1-2019
A00235	Siepel	FCC	FCC Test Site Registration nr 786213	15-3-2020
A00313	Comtest		Site registration filing Industry Canada	20-11-2020
A00436	Siepel		S-AR	28-9-2020
A00447	Gigalink	APG0500	RF Cable S-AR	7-2-2019
A00466	Teseq	CBL 6111D	Antenne S-AR, BiLog 30MHz-1GHz	11-10-2018
A00077	Teseq	CBL 6111B	Antenne S-AR, BiLog 30MHz-1GHz	1-12-2019
A01982	Rohde & Schwarz	ESR7	EMI Test Receiver 7GHz	6-7-2019
A00008	Emco	3115	Guide ant. 1-18GHz	19-12-2020
A00009	Emco	3115	Guide ant. 1-18GHz	13-2-2019
A00011	Emco	3116	Guide ant. 18-40GHz	13-2-2019
A00012	Emco	3160-09	Gain horn 18-26.5GHz	13-2-2019
A00209	Emco	3160-09	Gain horn 18-26.5GHz	13-2-2019
A00210	Emco	3160-10	Gain horn 26.5-40GHz	13-2-2019

Prüfbericht-Nr: 18062203.f01
Test report No: 18062203.f01

Seite 3 von 31
Page 3 of 31

A00339	H&S	Sucotest 18/Sucoflex 102	Cable RF S-AR >1G setup	13-7-2019
A00340	H&S	Sucotest 18/Sucoflex 102	Cable RF	12-7-2019
A00341	H&S	Sucotest 18/Sucoflex 102	Cable RF	12-7-2019

Prüfbericht-Nr: 18062203.f01
Test report No: 18062203.f01

Seite 4 von 31
Page 4 of 31

1	Produktdetails <i>Product details</i>	Wireless Communication Card AX201D2WL
2	Maße / Gewicht <i>Dimensions / Weight</i>	<< 50 gr
3	Bedienelemente <i>Operating elements</i>	Built inside Extender, processed by laptop
4	Ausstattung / Zubehör <i>Equipment / Accessories</i>	Extender card CRF CNV10 DB M2 PCB00651_01
5	Verwendete Materialien <i>Used materials</i>	PCB/Components
6	Sonstiges <i>Other</i>	Tested in external Extender card
7	This report concerns:	EMC Verification
		

Prüfbericht-Nr: 18062203.f01
Test report No: 18062203.f01

Seite 5 von 31
Page 5 of 31

Absatz				
Clause	Anforderungen – Prüfungen / Requirements - Tests			
1	47 CFR Part 15 (10-1-17 Edition) - 15.107(a) ICES-003 (Issue 6, January 2016) – Section 6.1 Table 2	AC Power Line Conducted Emissions	P ☒ F ☐ N/A ☐ N/T ☐	
2	47 CFR Part 15 (10-1-17 Edition) - 15.109 ICES-003 (Issue 6, January 2016) – Section 6.2.1 Table 5	Radiated unwanted emissions	P ☒ F ☐ N/A ☐ N/T ☐	

Zusammenfassung der Prüfergebnisse Summary of test results						
Index <i>Index</i>	Prüfung <i>Test</i>	Anwendbar <i>Applicable</i>	Prüfergebnis <i>Test result</i>	Paragraf <i>Paragraph</i>	Messungen unter Akkreditierung ausgeführt <i>under accreditation</i>	Kommentar <i>Remark</i>
Page 12	Radiated emission < 1000 MHz	Yes	Pass	3.1	Yes	
Page 17	Radiated emission > 1000 MHz	Yes	Pass	3.2	Yes	
Page 25	Conducted emission AC/DC port	Yes	Pass	3.3	Yes	

Prüfbericht-Nr: 18062203.f01
Test report No: 18062203.f01

Seite 6 von 31
Page 6 of 31

Table of contents

1	General test configuration.....	8
1.1	Tested system auxiliary details.....	9
1.2	Test methodology.....	10
1.3	Test facility.....	10
1.4	Test conditions.....	10
2	System test configuration.....	10
2.1	Justification.....	10
2.2	EUT mode of operation.....	10
2.3	Special accessories.....	11
2.4	Equipment modifications.....	11
3	Test results Emission according to FCC CRF47 Part 15B.....	12
3.1	Enclosure Radiated Emission 30-1000 MHz.....	12
3.2	Enclosure Radiated emission 1000 MHz – 25000 MHz.....	18
3.3	AC Mains Conducted Emission 0.15-30 MHz.....	25

Prüfbericht-Nr: 18062203.f01
Test report No: 18062203.f01

Seite 7 von 31
Page 7 of 31

Revisions Revisions			
Revision Revision	Datum Date	Anmerkung Remark	Verfasser Author
00	Nov. 2, 2018	First Release	T.E.T. Koning
Note: Latest revision report will replace all previous reports			

Prüfbericht-Nr: 18062203.f01
Test report No: 18062203.f01

Seite 8 von 31
Page 8 of 31

CONDITIONS FOR TESTING

1 General test configuration.

Test item	Wireless Communication Card
Model	AX201D2WL
Manufacturer	Intel Corporation SAS, Le Cargo B6 / 424 Rue de Goa, 06600 Antibes, France
Voltage input rating	Powered by extension board around 2-5 V DC
Current input rating	n.a.
Test software	
Driver version	
Auxiliary Equipment	See drawing in 1.1
Remarks	EUT tested in external extension board All EMC Emission testing has taken place: 1) within an environmental temperature range between 15 and 35 degrees Celsius 2) within an environmental relative humidity range between 20 and 85% 3) within an environmental air pressure range between 860 and 1060 mbar

List of used cables					
Number	Function	From	To	Length	Remarks
1	AC	Mains	Laptop	Any	

1.1 Tested system auxiliary details.

Details and an overview of the system and all of its components, as it has been tested, may be found below.

Test item (EUT1) : Wireless Communication Card
Manufacturer : Intel Corporation SAS
Brand mark : Intel
Model : AX201D2WL
Serial number : Engineering Sample
Remark : Tested in Extender board

Test item (AUX1) : Extender Main and Card board
Manufacturer : Intel Corporation SAS
Brand mark : Intel
Model : CRF CNVIO DB M2
Serial number : PCB00651_01
Remark : Used to have a functional EUT outside a PC or laptop

Test item (AUX2) : Laptop
Manufacturer : Dell
Brand mark : Dell
Model : E5470
Serial number : ---
Remark : Used as Host for AUX 1

Test item (AUX3) : Mobile Phone
Manufacturer : Samsung
Brand mark : Samsung
Model : Galaxy J7 (2016)
Serial number : ---
Remark : Used for BT communication




Figure 1. Total set-up used during testing

1.2 Test methodology.

The test methodology used is based on the requirements of 47 CFR Part 15 (10-1-17 Edition), sections 15.31, 15.107 and 15.109 and ICES-003 Issue 6 (January 2016) Sections 6.1 and 6.2. The EUT was tested in horizontal position only and is regarded as Table Top equipment.

The test methods, which have been used, are based on ANSI C63.4-2014.

Radiated emission tests were performed at a measurement distance of 3 meters.

The receivers are switching automatically to the right bandwidth in accordance with CISPR 16. This is implemented in the receiver. The antenna factors are programmed in the test receiver. The receiver automatically calculates the appropriate correction factor for the utilized antenna and also the appropriate antenna factor for the cable loss. The total correction is automatically added to the measured value.

1.3 Test facility.

The Federal Communications Commission and Industry Canada has reviewed the technical characteristics of the test facilities at TÜV Rheinland Nederland B.V., located at Eiberkamp 10, 9351 VT Leek, The Netherlands, and has found these test facilities to be in compliance with the requirements of 47 CFR Part 15, section 2.948.

The description of the test facilities has been filed at the Office of the Federal Communications Commission under registration number 786213. The facility has been added to the list of laboratories performing these test services for the public on a fee basis.

The description of the test facilities has been filed to Industry Canada under registration number 2932G-2. The facility has been added to the list of laboratories performing these test services for the public on a fee basis.

1.4 Test conditions.

Normal test conditions:

Temperature (*)	: +15°C to +35°C
Relative humidity(*)	: 20 % to 85 %
Supply voltage	: 120 Vac / 60 Hz

**When it was impracticable to carry out the tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests are stated separately.*

2 System test configuration.

2.1 Justification.

The system was configured for testing in a typical situation as a customer would normally use it. The test sample was configured by the applicant to enable continuous transmit. A normal 2.4 and/or 5 GHz Internet Link has been built-up to enable communication

The justification and manipulation of cables and equipment in order to simulate a worst-case behavior of the test setup has been carried out as prescribed in ANSI C63.4-2014.

2.2 EUT mode of operation.

The unintentional radiator tests have been performed with a complete functioning EUT.

Prufbericht-Nr: 18062203.f01
Test report No: 18062203.f01

Seite 11 von 31
Page 11 of 31

2.3 Special accessories.

No special accessories are used and/or needed to achieve compliance.

2.4 Equipment modifications.

No modifications have been made to the equipment.

Prüfbericht-Nr:
Test report No:

Seite 12 von 31
Page 12 of 31

3 Test results Emission according to FCC CRF47 Part 15B

3.1 Enclosure Radiated Emission 30-1000 MHz

3.1.1 Definition

Result of the measurements concerning radiated electromagnetic fields (electric component) emitted by the total set-up of the EUT.

3.1.2 Basic standard

The test is performed according to FCC CRF 47 Part 15B § 15.109

3.1.3 Limit

FCC 15.109(a) and IC ICES-003 section 6.2

Except for Class A digital devices, the field strength of radiated emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength (µV/meter)	Field strength (dBµV/m)	Measurement distance (meters)
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

Table of Applicable Limits

3.1.4 Test procedures

ANSI C63.4-2014.

Before final measurements of radiated emissions were performed, the EUT was scanned to determine its emission spectrum profile. The physical arrangement of the test system, the associated cabling and the EUT orientation (X, Y, Z) were varied in order to ensure that maximum emission amplitudes were attained.

The spectrum was examined from 30MHz to 25 GHz, the fifth harmonic of the implemented WLAN module. Final radiated emission measurements were made at 3 m distance.

At each frequency where a spurious emission was found, the EUT was rotated 360° and the antenna was raised and lowered from 1 to 4 m in order to determine the emission's maximum level. Measurements were taken using both horizontal and vertical antenna polarizations.

The highest emission amplitudes relative to the appropriate limit were recorded in this report. Field strength values of radiated emissions at frequencies not listed in the tables are more than 20 dB below the applicable limit.


3.1.5 Test deviation

There is no deviation with the original standard

Prufbericht-Nr: 18062203.f01
Test report No: 18062203.f01

Seite 13 von 31
Page 13 of 31

3.1.6 Test results

Test conditions			
		Test location	Leek
Applied Standard(s)	47 CFR Part 15 (10-1-17 Edition), ICES-003, January 2016)		
Test engineer	T.E.T. Koning	Test result	Pass
Test date	Oct. 30, 2018	Signature: 	

Prüfbericht-Nr: 18062203.f01
Test report No: 18062203.f01

Seite 14 von 31
Page 14 of 31

3.1.6.1 Test results 2.4 GHz WiFi and BT Mode

Results and limits						
Frequency (MHz)	Result (dB μ V/m)	Antenna polarization	Limit (dB μ V/m)	Margin	Height (cm)	Angle (deg)
71.27	24.3	Horizontal	40.0	15.7	239.6	343.7
103.64	26.8	Horizontal	43.5	16.7	276.2	35.7
132.40	26.7	Horizontal	43.5	16.8	257.6	359.3
181.01	31.0	Vertical	43.5	12.5	99.6	200.6
264.00	29.7	Vertical	46.0	16.3	162.6	9.8
312.00	28.7	Vertical	46.0	17.3	99.6	320.7

Table 1 Results Enclosure Radiated Emission 30.0 – 1000 MHz 2.4 WiFi and BT Mode

3.1.6.2 Test results 5 GHz WiFi Mode Mode

Results and limits						
Frequency (MHz)	Result (dB μ V/m)	Antenna polarization	Limit (dB μ V/m)	Margin	Height (cm)	Angle (deg)
36.87	28.0	Vertical	40.0	12.0	99.7	252.0
61.18	23.6	Vertical	43.5	19.9	99.7	248.9
104.59	20.0	Vertical	43.5	23.5	99.7	256.5
169.79	25.5	Horizontal	43.5	18.0	164.9	235.7
181.20	36.9	Horizontal	43.5	6.6	138.1	246.3
312.00	36.5	Horizontal	46.0	9.5	99.7	265.9

Table 2 Results Enclosure Radiated Emission 30.0 – 1000 MHz GHz Mode

Used Equipment

A01982	A00029	A00235	A00313	A00447	A00466				
--------	--------	--------	--------	--------	--------	--	--	--	--

Notes:

1. Field strength values of radiated emissions at frequencies not listed in the table above are more than 20 dB below the applicable limit.
2. Measurement uncertainty is 5.1 dB.
3. The EUT was tested in horizontal orientation only-it's normal operation orientation, the measuring antenna was varied in horizontal and vertical orientations and also around it's axis and height. The reported value is the worst case found at the reported frequency.
4. A selection of Photos and Graphical Displays is provided on the next pages.

3.1.6.3 Photograph test setup 2.4 GHz WiFi and BT / 5 GHz Mode





Photo 1 Photograph test setup radiated emissions 30-1000 MHz FCC 15, 2.4 GHz WiFi + BT Mode / 5 GHz Mode

Prüfbericht-Nr: 18062203.f01
Test report No: 18062203.f01

Seite 16 von 31
Page 16 of 31

3.1.6.4 Spectrum plot 2.4 GHz WiFi and BT Mode




Date: 30.OCT.2018 12:51:32

Plot 1: Pre-scan plot with peak detector. Radiated emissions from 30 MHz to 1000 MHz, 2.4 GHz and BT Mode.

Prüfbericht-Nr: 18062203.f01
Test report No: 18062203.f01

Seite 17 von 31
Page 17 of 31

3.1.6.5 Spectrum plot 5 GHz WiFi Mode



Date: 30.OCT.2018 13:18:13

Plot 2: Pre-scan plot with peak detector. Radiated emissions from 30 MHz to 1000 MHz, 5 GHz Mode.

Prüfbericht-Nr: 18062203.f01
Test report No: 18062203.f01

Seite 18 von 31
Page 18 of 31

3.2 Enclosure Radiated emission 1000 MHz – 25000 MHz

3.2.1 2.4 GHz WiFi and BT Mode

Results and limits						
Frequency (GHz)	Peak Results			Average Results		
	Vertical (dB μ V/m)	Horizontal (dB μ V/m)	Limit (dB μ V/m)	Vertical (dB μ V/m)	Horizontal (dB μ V/m)	Limit (dB μ V/m)
1.2445	48.0	45.0	74.0	27.0	26.0	54.0
1.86475	<<	47.5	74.0	<<	31.5	54.0
2.1235	50.0	<<	74.0	32.0	<<	54.0
2.6585	51.5	<<	74.0	33.5	<<	54.0

Table 3 Results Enclosure Radiated Emission 1000.0 – 25000.0 MHz 2.4 GHz and BT Mode

3.2.2 5 GHz WiFi Mode

Results and limits						
Frequency (GHz)	Peak Results			Average Results		
	Vertical (dB μ V/m)	Horizontal (dB μ V/m)	Limit (dB μ V/m)	Vertical (dB μ V/m)	Horizontal (dB μ V/m)	Limit (dB μ V/m)
1.2465	48.0	45.5	74.0	26.2	25.0	54.0
1.4175	44.0	<<	74.0	26.5	<<	54.0
2.126	50.0	<<	74.0	32.0	<<	54.0
2.71575	47.5	<<	74.0	34.5	<<	54.0
1.8435	<<	44.0	74.0	<<	31.0	54.0

Table 4 Results Enclosure Radiated Emission 1000.0 – 25000.0 MHz 5 GHz Mode

Notes:

Field strength values of radiated emissions at frequencies not listed in the table above are more than 20 dB below the applicable limit.

1. Measurement uncertainty is +/- 5.13 dB
2. The reported field strength values are the worst case values at the indicated frequency. The receiving antenna was varied in horizontal and vertical orientations and also in height (between 1m and 2m).
3. A Peak and Average detector was used with a resolution bandwidth of 1MHz.

Used Equipment

A01982	A00337	A00338	A00235	A00313	A00447	A00008			
--------	--------	--------	--------	--------	--------	--------	--	--	--

3.2.3 Photograph test setup 1- 18 GHz all modes




Photo 2: Photograph radiated emissions 1 – 18 GHz

3.2.4 test setup 18-25 GHz all modes





Photo 3: Photograph radiated emissions 6 – 18 GHz (Applying another Gainhorn in the range 18-25 GHz)

Prufbericht-Nr: 18062203.f01
Test report No: 18062203.f01

Seite 21 von 31
Page 21 of 31

3.2.5 Spectrum plot 2.4 GHz WiFi and BT Mode




Date: 29.OCT.2018 13:51:14

Plot 3: Pre-scan plot with peak detector. Radiated emissions from 1 GHz – 6 GHz 2.4 GHz WiFi and BT Mode (Antenna Vertical, max levels).

Prüfbericht-Nr: 18062203.f01
Test report No: 18062203.f01

Seite 22 von 31
Page 22 of 31

Spectrum plot 5 GHz WiFi Mode, 1 – 6 GHz



Date: 29.OCT.2018 13:17:21


Plot 4: Pre-scan plot with peak detector. Radiated emissions from 1 GHz – 6 GHz 5 GHz Mode (Antenna Vertical, max levels)..

Prüfbericht-Nr: 18062203.f01
Test report No: 18062203.f01

Seite 23 von 31
Page 23 of 31

3.2.6 Spectrum plot 2.4/5 GHz WiFi Mode and BT Mode, 6.5 – 18 GHz

(6.0 -6.5 GHz not presented as there were no EUT harmonics)



Date: 11.JAN.2003 06:04:30


Noise as presented here are internal noise signals, not generated by EUT

Plot 5: Pre-scan plot with peak detector. Radiated emissions from 6.5 GHz – 18 GHz.

Prüfbericht-Nr: 18062203.f01
Test report No: 18062203.f01

Seite 24 von 31
Page 24 of 31

3.2.7 Spectrum plot 2.4/5 GHz WiFi Mode and BT Mode, 18 – 25 GHz



Date: 11.JAN.2003 22:49:36

Plot 6: Pre-scan plot with peak detector. Radiated emissions from 18 GHz – 25 GHz. Noise peaks are not EUT related.

Prüfbericht-Nr: 18062203.f01
Test report No: 18062203.f01

Seite 25 von 31
Page 25 of 31

3.3 AC Mains Conducted Emission 0.15-30 MHz

3.3.1 Definition

Result of the measurements concerning the disturbance voltage level at the power input port emitted by the total set-up of the EUT.

3.3.2 Basic standard

The test is performed according to FCC CRF 47 Part 15B § 15.107

3.3.3 Limit

Frequency (MHz)	Limit Quasi-peak(dBμV)	Limit Average(dBμV)
0.15 - 0.50	66.0 – 56.0	56.0 – 46.0
0.50 - 5.0	56.0	46.0
5.0 – 30.0	60.0	50.0

3.3.4 Test procedures

Requirements: 15.107 (a) Except for Class A digital devices, for equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μH/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Test procedure according to ANSI C63.4-2014: Each phase and neutral of the AC power line were measured with respect to ground. Measurements were performed using a 50 μH / 50 Ω LISN. The frequency range from 150kHz to 30MHz was searched. The six highest EUT emissions relative to the limit were noted. The EUT is regarded as floor standing equipment and no isolating plane was used since the EUT is already provided with isolating material (of max 12mm height) underneath. The EUT was positioned at least 40cm from a vertical ground reference plane and at least 80cm from the LISN.

3.3.5 Test deviation

There is no deviation with the original standard

3.3.6 Test results

Test conditions			
		Test location	Leek
Applied Standard(s)	47 CFR Part 15 (10-1-17 Edition), ICES-003, January 2016)		
Test engineer	T.E.T. Koning	Test result	Pass
Test date	Nov. 1, 2018	Signature	

Prüfbericht-Nr: 18062203.f01
Test report No: 18062203.f01

Seite 26 von 31
Page 26 of 31

3.3.6.1 Results 2.4 GHz WiFi and BT Mode

Results and limits Neutral						
Frequency (MHz)	Quasi peak detector			Average detector		
	Result	Limit	Margin	Result	Limit	Margin
0.26	39.0	61.4	22.5	29.2	51.4	22.2
2.70	29.6	56.0	26.4	23.2	46.0	22.8
3.16	32.9	56.0	23.1	27.1	46.0	18.9
4.37	28.7	56.0	27.3	22.1	46.0	23.9
7.00	26.5	60.0	33.5	18.8	50.0	31.2
21.81	28.6	60.0	31.4	19.0	50.0	31.0

Table 5 Results Conducted Emission 0.15 - 30 MHz

Results and limits L1						
Frequency (MHz)	Quasi peak detector			Average detector		
	Result	Limit	Margin	Result	Limit	Margin
0.26	39.1	61.4	22.3	29.1	51.4	22.3
2.70	33.2	56.0	22.8	26.7	46.0	19.4
3.16	37.4	56.0	18.6	31.4	46.0	14.6
4.37	30.2	56.0	25.8	23.4	46.0	22.6
7.00	28.6	60.0	31.4	20.6	50.0	29.4
21.81	22.7	60.0	37.3	14.6	50.0	35.4

Table 6 Results Conducted Emission 0.15 - 30 MHz

Prüfbericht-Nr: 18062203.f01
Test report No: 18062203.f01

Seite 27 von 31
Page 27 of 31

3.3.6.2 Results 5 GHz WiFi Mode

Results and limits Neutral						
Frequency (MHz)	Quasi peak detector			Average detector		
	Result	Limit	Margin	Result	Limit	Margin
0.26	39.3	61.4	22.2	29.5	51.4	21.9
1.44	23.6	56.0	32.4	15.6	46.0	30.4
3.36	29.9	56.0	26.2	22.0	46.0	24.0
4.49	30.5	56.0	25.5	24.1	46.0	21.9
6.36	27.4	60.0	32.6	20.8	50.0	29.2
8.58	23.8	60.0	36.2	17.0	50.0	33.0

Table 7 Results Conducted Emission 0.15 - 30 MHz

Results and limits L1						
Frequency (MHz)	Quasi peak detector			Average detector		
	Result	Limit	Margin	Result	Limit	Margin
0.26	39.2	61.4	22.2	29.2	51.4	22.3
1.44	24.1	56.0	31.9	15.9	46.0	30.1
3.36	33.4	56.0	22.6	25.7	46.0	20.3
4.49	30.5	56.0	25.5	23.7	46.0	22.3
6.36	30.0	60.0	30.0	23.3	50.0	26.7
8.58	26.1	60.0	33.9	19.3	50.0	30.7

Table 8 Results Conducted Emission 0.15 - 30 MHz

The results of the AC power line conducted emission tests, carried out in accordance with 47 CFR Part 15 section 15.107 and ICES-003 Section 6.1, at the 120 Volts AC mains connection terminals of Aux2 of the system, are depicted in Table 4. Maximum values were recorded. The system is tested as in whole, so with all equipment as shown in Figure 1 in place and functioning. Being the worst case situation.

Notes:

1. Measurement uncertainty is ± 3.2 dB
2. The resolution bandwidth used was 9 kHz.
3. The six highest values relative to the applicable limits were noted.
4. Photo and Graphical Display is provided on the next page.

Used Equipment

A00726	A01978	A00022	A00354	A00093					
--------	--------	--------	--------	--------	--	--	--	--	--

3.3.6.3 Photograph test setup both modes




Photo 4: Photograph conducted emissions 0.15-30 MHz

Prüfbericht-Nr: 18062203.f01
Test report No: 18062203.f01


Seite 29 von 31
Page 29 of 31

3.3.6.4 Spectrum plot 2.4 GHz WiFi and BT Mode



Plot 7: Pre-scan plot with peak detector. Conducted emissions from 0.15 - 30 MHz 2.4 GHz WiFi and BT Mode.

3.3.6.5 Spectrum plot 5 GHz Mode



Plot 8: Pre-scan plot with peak detector. Conducted emissions from 0.15 - 30 MHz, 5 GHz WiFi Mode.

Prufbericht-Nr: 18062203.f01
Test report No: 18062203.f01

Seite 31 von 31
Page 31 of 31

END OF THIS EMC TESTREPORT