

|      |                  |                 |                |
|------|------------------|-----------------|----------------|
| Mode | TX channel 26915 | Frequency Range | Above 1000 MHz |
|------|------------------|-----------------|----------------|

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |                      |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|----------------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1673        | 36.79         | -65.84                | 6.31                   | -59.53               | -13         | -46.53      |
| 2                                                   | 2509.5      | 40.61         | -57.91                | 6.66                   | -51.25               | -13         | -38.25      |
| 3                                                   | 3346        | 46.16         | -56.48                | 7.95                   | -48.53               | -13         | -35.53      |
| 4                                                   | 4182.5      | 48.74         | -56.10                | 7.44                   | -48.66               | -13         | -35.66      |
| 5                                                   | 5019        | 48.74         | -55.52                | 7.01                   | -48.51               | -13         | -35.51      |
| 6                                                   | 5855.5      | 48.23         | -55.91                | 7.01                   | -48.90               | -13         | -35.90      |
| 7                                                   | 6692        | 49.11         | -54.22                | 5.56                   | -48.66               | -13         | -35.66      |
| 8                                                   | 7528.5      | 48.39         | -54.23                | 4.52                   | -49.71               | -13         | -36.71      |
| 9                                                   | 8365        | 48.11         | -54.44                | 4.19                   | -50.25               | -13         | -37.25      |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |                      |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1673        | 34.27         | -68.36                | 6.31                   | -62.05               | -13         | -49.05      |
| 2                                                   | 2509.5      | 37.54         | -60.98                | 6.66                   | -54.32               | -13         | -41.32      |
| 3                                                   | 3346        | 37.32         | -65.32                | 7.95                   | -57.37               | -13         | -44.37      |
| 4                                                   | 4182.5      | 40.42         | -64.42                | 7.44                   | -56.98               | -13         | -43.98      |
| 5                                                   | 5019        | 40.57         | -63.69                | 7.01                   | -56.68               | -13         | -43.68      |
| 6                                                   | 5855.5      | 42.55         | -61.59                | 7.01                   | -54.58               | -13         | -41.58      |
| 7                                                   | 6692        | 45.22         | -58.11                | 5.56                   | -52.55               | -13         | -39.55      |
| 8                                                   | 7528.5      | 47.85         | -54.77                | 4.52                   | -50.25               | -13         | -37.25      |
| 9                                                   | 8365        | 47.12         | -55.43                | 4.19                   | -51.24               | -13         | -38.24      |

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

|      |                  |                 |                |
|------|------------------|-----------------|----------------|
| Mode | TX channel 27033 | Frequency Range | Above 1000 MHz |
|------|------------------|-----------------|----------------|

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |                      |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|----------------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1696.6      | 35.06         | -67.45                | 6.35                   | -61.10               | -13         | -48.10      |
| 2                                                   | 2544.9      | 36.49         | -62.32                | 6.69                   | -55.63               | -13         | -42.63      |
| 3                                                   | 3393.2      | 37.66         | -65.15                | 7.92                   | -57.23               | -13         | -44.23      |
| 4                                                   | 4241.5      | 39.93         | -61.68                | 4.18                   | -57.51               | -13         | -44.51      |
| 5                                                   | 5089.8      | 40.75         | -61.98                | -5.18                  | -67.16               | -13         | -54.16      |
| 6                                                   | 5938.1      | 43.08         | -57.24                | 3.57                   | -53.67               | -13         | -40.67      |
| 7                                                   | 6786.4      | 45.15         | -52.20                | 3.70                   | -48.50               | -13         | -35.50      |
| 8                                                   | 7634.7      | 47.69         | -49.66                | 3.70                   | -45.96               | -13         | -32.96      |
| 9                                                   | 8483        | 46.75         | -55.86                | 4.21                   | -51.65               | -13         | -38.65      |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |                      |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1696.6      | 36.24         | -66.27                | 6.35                   | -59.92               | -13         | -46.92      |
| 2                                                   | 2544.9      | 40.20         | -58.61                | 6.69                   | -51.92               | -13         | -38.92      |
| 3                                                   | 3393.2      | 46.74         | -56.07                | 7.92                   | -48.15               | -13         | -35.15      |
| 4                                                   | 4241.5      | 48.61         | -53.00                | 4.18                   | -48.83               | -13         | -35.83      |
| 5                                                   | 5089.8      | 48.66         | -54.07                | -5.18                  | -59.25               | -13         | -46.25      |
| 6                                                   | 5938.1      | 46.89         | -53.43                | 3.57                   | -49.86               | -13         | -36.86      |
| 7                                                   | 6786.4      | 48.99         | -48.36                | 3.70                   | -44.66               | -13         | -31.66      |
| 8                                                   | 7634.7      | 48.31         | -49.04                | 3.70                   | -45.34               | -13         | -32.34      |
| 9                                                   | 8483        | 47.59         | -55.02                | 4.21                   | -50.81               | -13         | -37.81      |

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

### LTE Band 26: 3MHz

|      |                  |                 |                |
|------|------------------|-----------------|----------------|
| Mode | TX channel 26805 | Frequency Range | Above 1000 MHz |
|------|------------------|-----------------|----------------|

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |                      |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|----------------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1651        | 34.36         | -68.39                | 6.27                   | -62.12               | -13         | -49.12      |
| 2                                                   | 2476.5      | 40.64         | -57.59                | 6.62                   | -50.96               | -13         | -37.96      |
| 3                                                   | 3302        | 45.41         | -57.54                | 7.56                   | -49.98               | -13         | -36.98      |
| 4                                                   | 4127.5      | 47.56         | -57.34                | 7.47                   | -49.87               | -13         | -36.87      |
| 5                                                   | 4953        | 48.20         | -55.95                | 7.00                   | -48.96               | -13         | -35.96      |
| 6                                                   | 5778.5      | 47.31         | -57.21                | 6.93                   | -50.28               | -13         | -37.28      |
| 7                                                   | 6604        | 49.32         | -54.41                | 5.74                   | -48.67               | -13         | -35.67      |
| 8                                                   | 7429.5      | 49.72         | -52.90                | 4.61                   | -48.29               | -13         | -35.29      |
| 9                                                   | 8255        | 48.44         | -54.18                | 2.66                   | -51.52               | -13         | -38.52      |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |                      |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1651        | 34.78         | -67.97                | 6.27                   | -61.70               | -13         | -48.70      |
| 2                                                   | 2476.5      | 37.05         | -61.18                | 6.62                   | -54.55               | -13         | -41.55      |
| 3                                                   | 3302        | 38.09         | -64.86                | 7.56                   | -57.30               | -13         | -44.30      |
| 4                                                   | 4127.5      | 40.39         | -64.51                | 7.47                   | -57.04               | -13         | -44.04      |
| 5                                                   | 4953        | 41.73         | -62.42                | 7.00                   | -55.43               | -13         | -42.43      |
| 6                                                   | 5778.5      | 43.45         | -61.07                | 6.93                   | -54.14               | -13         | -41.14      |
| 7                                                   | 6604        | 45.16         | -58.57                | 5.74                   | -52.83               | -13         | -39.83      |
| 8                                                   | 7429.5      | 46.98         | -55.64                | 4.61                   | -51.03               | -13         | -38.03      |
| 9                                                   | 8255        | 46.34         | -56.28                | 2.66                   | -53.62               | -13         | -40.62      |

#### Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

|      |                  |                 |                |
|------|------------------|-----------------|----------------|
| Mode | TX channel 26915 | Frequency Range | Above 1000 MHz |
|------|------------------|-----------------|----------------|

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |                      |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|----------------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1673        | 34.43         | -62.08                | 9.04                   | -53.05               | -13         | -40.05      |
| 2                                                   | 2509.5      | 39.73         | -70.27                | 9.21                   | -61.06               | -13         | -48.06      |
| 3                                                   | 3346        | 44.41         | -58.21                | 8.10                   | -50.11               | -13         | -37.11      |
| 4                                                   | 4182.5      | 47.13         | -68.00                | 5.16                   | -62.83               | -13         | -49.83      |
| 5                                                   | 5019        | 48.57         | -54.18                | -5.28                  | -59.46               | -13         | -46.46      |
| 6                                                   | 5855.5      | 47.13         | -64.70                | 2.90                   | -61.81               | -13         | -48.81      |
| 7                                                   | 6692        | 50.14         | -60.00                | -8.52                  | -68.52               | -13         | -55.52      |
| 8                                                   | 7528.5      | 50.41         | -46.94                | 3.70                   | -43.24               | -13         | -30.24      |
| 9                                                   | 8365        | 47.49         | -49.86                | 3.70                   | -46.16               | -13         | -33.16      |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |                      |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1673        | 35.53         | -60.98                | 9.04                   | -51.95               | -13         | -38.95      |
| 2                                                   | 2509.5      | 36.48         | -73.52                | 9.21                   | -64.31               | -13         | -51.31      |
| 3                                                   | 3346        | 38.43         | -64.19                | 8.10                   | -56.09               | -13         | -43.09      |
| 4                                                   | 4182.5      | 39.60         | -75.53                | 5.16                   | -70.36               | -13         | -57.36      |
| 5                                                   | 5019        | 41.25         | -61.50                | -5.28                  | -66.78               | -13         | -53.78      |
| 6                                                   | 5855.5      | 43.57         | -68.26                | 2.90                   | -65.37               | -13         | -52.37      |
| 7                                                   | 6692        | 44.48         | -65.66                | -8.52                  | -74.18               | -13         | -61.18      |
| 8                                                   | 7528.5      | 47.62         | -49.73                | 3.70                   | -46.03               | -13         | -33.03      |
| 9                                                   | 8365        | 45.85         | -51.50                | 3.70                   | -47.80               | -13         | -34.80      |

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

|      |                  |                 |                |
|------|------------------|-----------------|----------------|
| Mode | TX channel 27025 | Frequency Range | Above 1000 MHz |
|------|------------------|-----------------|----------------|

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |                      |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|----------------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1695        | 34.86         | -67.66                | 6.35                   | -61.31               | -13         | -48.31      |
| 2                                                   | 2542.5      | 41.56         | -57.23                | 6.69                   | -50.54               | -13         | -37.54      |
| 3                                                   | 3390        | 46.20         | -56.60                | 7.92                   | -48.68               | -13         | -35.68      |
| 4                                                   | 4237.5      | 48.30         | -56.49                | 7.42                   | -49.07               | -13         | -36.07      |
| 5                                                   | 5085        | 47.39         | -56.93                | 7.02                   | -49.91               | -13         | -36.91      |
| 6                                                   | 5932.5      | 46.85         | -57.29                | 6.88                   | -50.41               | -13         | -37.41      |
| 7                                                   | 6780        | 49.35         | -52.41                | 5.16                   | -47.25               | -13         | -34.25      |
| 8                                                   | 7627.5      | 48.94         | -53.68                | 4.43                   | -49.25               | -13         | -36.25      |
| 9                                                   | 8475        | 49.22         | -53.39                | 4.20                   | -49.18               | -13         | -36.18      |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |                      |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1695        | 34.09         | -68.43                | 6.35                   | -62.08               | -13         | -49.08      |
| 2                                                   | 2542.5      | 36.02         | -62.77                | 6.69                   | -56.08               | -13         | -43.08      |
| 3                                                   | 3390        | 37.51         | -65.29                | 7.92                   | -57.37               | -13         | -44.37      |
| 4                                                   | 4237.5      | 39.03         | -65.76                | 7.42                   | -58.34               | -13         | -45.34      |
| 5                                                   | 5085        | 40.48         | -63.84                | 7.02                   | -56.82               | -13         | -43.82      |
| 6                                                   | 5932.5      | 43.11         | -61.03                | 6.88                   | -54.15               | -13         | -41.15      |
| 7                                                   | 6780        | 45.31         | -56.45                | 5.16                   | -51.29               | -13         | -38.29      |
| 8                                                   | 7627.5      | 47.37         | -55.25                | 4.43                   | -50.82               | -13         | -37.82      |
| 9                                                   | 8475        | 46.47         | -56.14                | 4.20                   | -51.93               | -13         | -38.93      |

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

# LTE Band 26: 5MHz

|      |                  |                 |                |
|------|------------------|-----------------|----------------|
| Mode | TX channel 26815 | Frequency Range | Above 1000 MHz |
|------|------------------|-----------------|----------------|

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |                      |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|----------------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1653        | 34.24         | -68.49                | 6.27                   | -62.22               | -13         | -49.22      |
| 2                                                   | 2479.5      | 40.24         | -58.03                | 6.63                   | -51.40               | -13         | -38.40      |
| 3                                                   | 3306        | 46.14         | -56.35                | 7.97                   | -48.38               | -13         | -35.38      |
| 4                                                   | 4132.5      | 47.92         | -56.97                | 7.47                   | -49.51               | -13         | -36.51      |
| 5                                                   | 4959        | 48.79         | -55.38                | 7.00                   | -48.38               | -13         | -35.38      |
| 6                                                   | 5785.5      | 47.52         | -56.98                | 6.92                   | -50.06               | -13         | -37.06      |
| 7                                                   | 6612        | 49.69         | -53.98                | 5.71                   | -48.26               | -13         | -35.26      |
| 8                                                   | 7438.5      | 49.39         | -53.23                | 4.60                   | -48.63               | -13         | -35.63      |
| 9                                                   | 8265        | 48.81         | -53.81                | 4.17                   | -49.64               | -13         | -36.64      |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |                      |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1653        | 35.76         | -66.97                | 6.27                   | -60.70               | -13         | -47.70      |
| 2                                                   | 2479.5      | 36.19         | -62.08                | 6.63                   | -55.45               | -13         | -42.45      |
| 3                                                   | 3306        | 36.73         | -65.76                | 7.97                   | -57.79               | -13         | -44.79      |
| 4                                                   | 4132.5      | 39.46         | -65.43                | 7.47                   | -57.97               | -13         | -44.97      |
| 5                                                   | 4959        | 40.10         | -64.07                | 7.00                   | -57.07               | -13         | -44.07      |
| 6                                                   | 5785.5      | 43.42         | -61.08                | 6.92                   | -54.16               | -13         | -41.16      |
| 7                                                   | 6612        | 44.20         | -59.47                | 5.71                   | -53.75               | -13         | -40.75      |
| 8                                                   | 7438.5      | 47.48         | -55.14                | 4.60                   | -50.54               | -13         | -37.54      |
| 9                                                   | 8265        | 46.42         | -56.20                | 4.17                   | -52.03               | -13         | -39.03      |

## Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

|      |                  |                 |                |
|------|------------------|-----------------|----------------|
| Mode | TX channel 26915 | Frequency Range | Above 1000 MHz |
|------|------------------|-----------------|----------------|

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |                      |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|----------------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1673        | 35.63         | -67.00                | 6.31                   | -60.69               | -13         | -47.69      |
| 2                                                   | 2509.5      | 41.47         | -57.05                | 6.66                   | -50.39               | -13         | -37.39      |
| 3                                                   | 3346        | 45.95         | -56.69                | 7.95                   | -48.74               | -13         | -35.74      |
| 4                                                   | 4182.5      | 46.01         | -58.83                | 7.44                   | -51.39               | -13         | -38.39      |
| 5                                                   | 5019        | 50.22         | -54.04                | 7.01                   | -47.03               | -13         | -34.03      |
| 6                                                   | 5855.5      | 48.97         | -55.17                | 7.01                   | -48.16               | -13         | -35.16      |
| 7                                                   | 6692        | 49.02         | -54.31                | 5.56                   | -48.75               | -13         | -35.75      |
| 8                                                   | 7528.5      | 50.92         | -51.70                | 4.52                   | -47.18               | -13         | -34.18      |
| 9                                                   | 8365        | 47.33         | -55.22                | 4.19                   | -51.03               | -13         | -38.03      |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |                      |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1673        | 34.91         | -67.72                | 6.31                   | -61.41               | -13         | -48.41      |
| 2                                                   | 2509.5      | 36.41         | -62.11                | 6.66                   | -55.45               | -13         | -42.45      |
| 3                                                   | 3346        | 37.40         | -65.24                | 7.95                   | -57.29               | -13         | -44.29      |
| 4                                                   | 4182.5      | 40.37         | -64.47                | 7.44                   | -57.03               | -13         | -44.03      |
| 5                                                   | 5019        | 40.78         | -63.48                | 7.01                   | -56.47               | -13         | -43.47      |
| 6                                                   | 5855.5      | 43.57         | -60.57                | 7.01                   | -53.56               | -13         | -40.56      |
| 7                                                   | 6692        | 45.69         | -57.64                | 5.56                   | -52.08               | -13         | -39.08      |
| 8                                                   | 7528.5      | 46.96         | -55.66                | 4.52                   | -51.14               | -13         | -38.14      |
| 9                                                   | 8365        | 47.34         | -55.21                | 4.19                   | -51.02               | -13         | -38.02      |

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

|      |                  |                 |                |
|------|------------------|-----------------|----------------|
| Mode | TX channel 27015 | Frequency Range | Above 1000 MHz |
|------|------------------|-----------------|----------------|

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |                      |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|----------------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1693        | 34.89         | -67.63                | 6.35                   | -61.28               | -13         | -48.28      |
| 2                                                   | 2539.5      | 41.57         | -57.22                | 6.69                   | -50.53               | -13         | -37.53      |
| 3                                                   | 3386        | 45.77         | -57.01                | 7.92                   | -49.09               | -13         | -36.09      |
| 4                                                   | 4232.5      | 48.33         | -56.46                | 7.42                   | -49.04               | -13         | -36.04      |
| 5                                                   | 5079        | 49.19         | -55.16                | 7.03                   | -48.13               | -13         | -35.13      |
| 6                                                   | 5925.5      | 46.80         | -57.34                | 6.90                   | -50.44               | -13         | -37.44      |
| 7                                                   | 6772        | 48.75         | -53.00                | 5.16                   | -47.83               | -13         | -34.83      |
| 8                                                   | 7618.5      | 48.80         | -53.82                | 4.44                   | -49.38               | -13         | -36.38      |
| 9                                                   | 8465        | 47.78         | -54.82                | 4.20                   | -50.62               | -13         | -37.62      |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |                      |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1693        | 34.62         | -67.90                | 6.35                   | -61.55               | -13         | -48.55      |
| 2                                                   | 2539.5      | 37.43         | -61.36                | 6.69                   | -54.67               | -13         | -41.67      |
| 3                                                   | 3386        | 38.29         | -64.49                | 7.92                   | -56.57               | -13         | -43.57      |
| 4                                                   | 4232.5      | 40.51         | -64.28                | 7.42                   | -56.86               | -13         | -43.86      |
| 5                                                   | 5079        | 40.64         | -63.71                | 7.03                   | -56.68               | -13         | -43.68      |
| 6                                                   | 5925.5      | 42.26         | -61.88                | 6.90                   | -54.98               | -13         | -41.98      |
| 7                                                   | 6772        | 45.10         | -56.65                | 5.16                   | -51.48               | -13         | -38.48      |
| 8                                                   | 7618.5      | 47.10         | -55.52                | 4.44                   | -51.08               | -13         | -38.08      |
| 9                                                   | 8465        | 46.40         | -56.20                | 4.20                   | -52.00               | -13         | -39.00      |

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).



### LTE Band 26: 10MHz

|      |                  |                 |                |
|------|------------------|-----------------|----------------|
| Mode | TX channel 26840 | Frequency Range | Above 1000 MHz |
|------|------------------|-----------------|----------------|

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |                      |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|----------------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1658        | 33.55         | -69.15                | 6.28                   | -62.87               | -13         | -49.87      |
| 2                                                   | 2487        | 41.07         | -57.26                | 6.64                   | -50.63               | -13         | -37.63      |
| 3                                                   | 3316        | 44.60         | -58.38                | 7.58                   | -50.79               | -13         | -37.79      |
| 4                                                   | 4145        | 46.59         | -58.29                | 7.46                   | -50.83               | -13         | -37.83      |
| 5                                                   | 4974        | 47.45         | -56.74                | 7.00                   | -49.74               | -13         | -36.74      |
| 6                                                   | 5803        | 46.58         | -57.89                | 6.91                   | -50.98               | -13         | -37.98      |
| 7                                                   | 6632        | 50.25         | -53.33                | 5.68                   | -47.66               | -13         | -34.66      |
| 8                                                   | 7461        | 49.08         | -53.54                | 4.58                   | -48.96               | -13         | -35.96      |
| 9                                                   | 8290        | 47.88         | -54.63                | 4.18                   | -50.45               | -13         | -37.45      |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |                      |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1658        | 32.64         | -70.06                | 6.28                   | -63.78               | -13         | -50.78      |
| 2                                                   | 2487        | 35.34         | -62.99                | 6.64                   | -56.36               | -13         | -43.36      |
| 3                                                   | 3316        | 37.59         | -65.39                | 7.58                   | -57.80               | -13         | -44.80      |
| 4                                                   | 4145        | 38.53         | -66.35                | 7.46                   | -58.89               | -13         | -45.89      |
| 5                                                   | 4974        | 39.39         | -64.80                | 7.00                   | -57.80               | -13         | -44.80      |
| 6                                                   | 5803        | 41.79         | -62.68                | 6.91                   | -55.77               | -13         | -42.77      |
| 7                                                   | 6632        | 43.69         | -59.89                | 5.68                   | -54.22               | -13         | -41.22      |
| 8                                                   | 7461        | 46.71         | -55.91                | 4.58                   | -51.33               | -13         | -38.33      |
| 9                                                   | 8290        | 47.79         | -54.72                | 4.18                   | -50.54               | -13         | -37.54      |

#### Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

|      |                  |                 |                |
|------|------------------|-----------------|----------------|
| Mode | TX channel 26915 | Frequency Range | Above 1000 MHz |
|------|------------------|-----------------|----------------|

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |                      |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|----------------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1673        | 33.52         | -69.11                | 6.31                   | -62.80               | -13         | -49.80      |
| 2                                                   | 2509.5      | 41.07         | -57.45                | 6.66                   | -50.79               | -13         | -37.79      |
| 3                                                   | 3346        | 45.43         | -57.21                | 7.95                   | -49.26               | -13         | -36.26      |
| 4                                                   | 4182.5      | 46.80         | -58.04                | 7.44                   | -50.60               | -13         | -37.60      |
| 5                                                   | 5019        | 47.51         | -56.75                | 7.01                   | -49.74               | -13         | -36.74      |
| 6                                                   | 5855.5      | 46.72         | -57.42                | 7.01                   | -50.41               | -13         | -37.41      |
| 7                                                   | 6692        | 48.51         | -54.82                | 5.56                   | -49.26               | -13         | -36.26      |
| 8                                                   | 7528.5      | 49.49         | -53.13                | 4.52                   | -48.61               | -13         | -35.61      |
| 9                                                   | 8365        | 48.87         | -53.68                | 4.19                   | -49.49               | -13         | -36.49      |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |                      |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1673        | 34.69         | -67.94                | 6.31                   | -61.63               | -13         | -48.63      |
| 2                                                   | 2509.5      | 36.32         | -62.20                | 6.66                   | -55.54               | -13         | -42.54      |
| 3                                                   | 3346        | 37.90         | -64.74                | 7.95                   | -56.79               | -13         | -43.79      |
| 4                                                   | 4182.5      | 41.15         | -63.69                | 7.44                   | -56.25               | -13         | -43.25      |
| 5                                                   | 5019        | 41.52         | -62.74                | 7.01                   | -55.73               | -13         | -42.73      |
| 6                                                   | 5855.5      | 44.43         | -59.71                | 7.01                   | -52.70               | -13         | -39.70      |
| 7                                                   | 6692        | 45.85         | -57.48                | 5.56                   | -51.92               | -13         | -38.92      |
| 8                                                   | 7528.5      | 47.94         | -54.68                | 4.52                   | -50.16               | -13         | -37.16      |
| 9                                                   | 8365        | 48.23         | -54.32                | 4.19                   | -50.13               | -13         | -37.13      |

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

|      |                  |                 |                |
|------|------------------|-----------------|----------------|
| Mode | TX channel 26990 | Frequency Range | Above 1000 MHz |
|------|------------------|-----------------|----------------|

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |                      |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|----------------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1688        | 33.37         | -69.18                | 6.34                   | -62.85               | -13         | -49.85      |
| 2                                                   | 2532        | 41.30         | -57.41                | 6.68                   | -50.73               | -13         | -37.73      |
| 3                                                   | 3376        | 45.85         | -56.90                | 7.93                   | -48.97               | -13         | -35.97      |
| 4                                                   | 4220        | 47.60         | -57.21                | 7.43                   | -49.78               | -13         | -36.78      |
| 5                                                   | 5064        | 48.51         | -55.82                | 7.02                   | -48.79               | -13         | -35.79      |
| 6                                                   | 5908        | 47.48         | -56.66                | 6.93                   | -49.73               | -13         | -36.73      |
| 7                                                   | 6752        | 48.53         | -53.19                | 5.18                   | -48.01               | -13         | -35.01      |
| 8                                                   | 7596        | 49.96         | -52.66                | 4.46                   | -48.20               | -13         | -35.20      |
| 9                                                   | 8440        | 48.69         | -53.90                | 4.20                   | -49.70               | -13         | -36.70      |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |                      |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1688        | 34.36         | -68.19                | 6.34                   | -61.86               | -13         | -48.86      |
| 2                                                   | 2532        | 38.18         | -60.53                | 6.68                   | -53.85               | -13         | -40.85      |
| 3                                                   | 3376        | 37.59         | -65.16                | 7.93                   | -57.23               | -13         | -44.23      |
| 4                                                   | 4220        | 40.50         | -64.31                | 7.43                   | -56.88               | -13         | -43.88      |
| 5                                                   | 5064        | 39.71         | -64.62                | 7.02                   | -57.59               | -13         | -44.59      |
| 6                                                   | 5908        | 43.21         | -60.93                | 6.93                   | -54.00               | -13         | -41.00      |
| 7                                                   | 6752        | 45.94         | -55.78                | 5.18                   | -50.60               | -13         | -37.60      |
| 8                                                   | 7596        | 47.11         | -55.51                | 4.46                   | -51.05               | -13         | -38.05      |
| 9                                                   | 8440        | 46.82         | -55.77                | 4.20                   | -51.57               | -13         | -38.57      |

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

# LTE Band 26: 15MHz

|      |                  |                 |                |
|------|------------------|-----------------|----------------|
| Mode | TX channel 26865 | Frequency Range | Above 1000 MHz |
|------|------------------|-----------------|----------------|

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |                      |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|----------------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1663        | 34.73         | -67.97                | 6.28                   | -61.69               | -13         | -48.69      |
| 2                                                   | 2494.5      | 41.25         | -57.08                | 6.64                   | -50.45               | -13         | -37.45      |
| 3                                                   | 3326        | 45.88         | -57.10                | 7.58                   | -49.51               | -13         | -36.51      |
| 4                                                   | 4157.5      | 48.03         | -56.85                | 7.46                   | -49.39               | -13         | -36.39      |
| 5                                                   | 4989        | 47.79         | -56.40                | 7.00                   | -49.40               | -13         | -36.40      |
| 6                                                   | 5820.5      | 47.41         | -57.06                | 6.91                   | -50.15               | -13         | -37.15      |
| 7                                                   | 6652        | 49.72         | -53.86                | 5.68                   | -48.19               | -13         | -35.19      |
| 8                                                   | 7483.5      | 50.27         | -52.35                | 4.58                   | -47.77               | -13         | -34.77      |
| 9                                                   | 8315        | 48.76         | -53.75                | 4.18                   | -49.57               | -13         | -36.57      |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |                      |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1663        | 33.82         | -68.88                | 6.28                   | -62.60               | -13         | -49.60      |
| 2                                                   | 2494.5      | 38.01         | -60.32                | 6.64                   | -53.69               | -13         | -40.69      |
| 3                                                   | 3326        | 36.46         | -66.52                | 7.58                   | -58.93               | -13         | -45.93      |
| 4                                                   | 4157.5      | 41.37         | -63.51                | 7.46                   | -56.05               | -13         | -43.05      |
| 5                                                   | 4989        | 39.58         | -64.61                | 7.00                   | -57.61               | -13         | -44.61      |
| 6                                                   | 5820.5      | 42.37         | -62.10                | 6.91                   | -55.19               | -13         | -42.19      |
| 7                                                   | 6652        | 45.15         | -58.43                | 5.68                   | -52.76               | -13         | -39.76      |
| 8                                                   | 7483.5      | 47.75         | -54.87                | 4.58                   | -50.29               | -13         | -37.29      |
| 9                                                   | 8315        | 46.00         | -56.51                | 4.18                   | -52.33               | -13         | -39.33      |

## Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

|      |                  |                 |                |
|------|------------------|-----------------|----------------|
| Mode | TX channel 26915 | Frequency Range | Above 1000 MHz |
|------|------------------|-----------------|----------------|

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |                      |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|----------------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1673        | 35.35         | -67.20                | 6.34                   | -60.87               | -13         | -47.87      |
| 2                                                   | 2509.5      | 39.72         | -58.99                | 6.68                   | -52.31               | -13         | -39.31      |
| 3                                                   | 3346        | 46.31         | -56.44                | 7.93                   | -48.51               | -13         | -35.51      |
| 4                                                   | 4182.5      | 47.55         | -57.26                | 7.43                   | -49.83               | -13         | -36.83      |
| 5                                                   | 5019        | 47.48         | -56.85                | 7.02                   | -49.82               | -13         | -36.82      |
| 6                                                   | 5855.5      | 48.07         | -56.07                | 6.93                   | -49.14               | -13         | -36.14      |
| 7                                                   | 6692        | 48.44         | -53.28                | 5.18                   | -48.10               | -13         | -35.10      |
| 8                                                   | 7528.5      | 48.89         | -53.73                | 4.46                   | -49.27               | -13         | -36.27      |
| 9                                                   | 8365        | 47.56         | -55.03                | 4.20                   | -50.83               | -13         | -37.83      |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |                      |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1673        | 35.31         | -67.24                | 6.34                   | -60.91               | -13         | -47.91      |
| 2                                                   | 2509.5      | 37.71         | -61.00                | 6.68                   | -54.32               | -13         | -41.32      |
| 3                                                   | 3346        | 37.74         | -65.01                | 7.93                   | -57.08               | -13         | -44.08      |
| 4                                                   | 4182.5      | 41.18         | -63.63                | 7.43                   | -56.20               | -13         | -43.20      |
| 5                                                   | 5019        | 40.60         | -63.73                | 7.02                   | -56.70               | -13         | -43.70      |
| 6                                                   | 5855.5      | 43.86         | -60.28                | 6.93                   | -53.35               | -13         | -40.35      |
| 7                                                   | 6692        | 46.14         | -55.58                | 5.18                   | -50.40               | -13         | -37.40      |
| 8                                                   | 7528.5      | 46.90         | -55.72                | 4.46                   | -51.26               | -13         | -38.26      |
| 9                                                   | 8365        | 46.14         | -56.45                | 4.20                   | -52.25               | -13         | -39.25      |

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

|      |                  |                 |                |
|------|------------------|-----------------|----------------|
| Mode | TX channel 26965 | Frequency Range | Above 1000 MHz |
|------|------------------|-----------------|----------------|

| Antenna Polarity & Test Distance: Horizontal at 3 M |             |               |                       |                        |                      |             |             |
|-----------------------------------------------------|-------------|---------------|-----------------------|------------------------|----------------------|-------------|-------------|
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1683        | 35.20         | -67.50                | 6.28                   | -61.22               | -13         | -48.22      |
| 2                                                   | 2524.5      | 40.39         | -57.94                | 6.64                   | -51.31               | -13         | -38.31      |
| 3                                                   | 3366        | 44.70         | -58.28                | 7.58                   | -50.69               | -13         | -37.69      |
| 4                                                   | 4207.5      | 46.66         | -58.22                | 7.46                   | -50.76               | -13         | -37.76      |
| 5                                                   | 5049        | 48.99         | -55.20                | 7.00                   | -48.20               | -13         | -35.20      |
| 6                                                   | 5890.5      | 46.44         | -58.03                | 6.91                   | -51.12               | -13         | -38.12      |
| 7                                                   | 6732        | 49.61         | -53.97                | 5.68                   | -48.30               | -13         | -35.30      |
| 8                                                   | 7573.5      | 50.42         | -52.20                | 4.58                   | -47.62               | -13         | -34.62      |
| 9                                                   | 8415        | 49.08         | -53.43                | 4.18                   | -49.25               | -13         | -36.25      |
| Antenna Polarity & Test Distance: Vertical at 3 M   |             |               |                       |                        |                      |             |             |
| No.                                                 | Freq. (MHz) | Reading (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Emission Value (dBm) | Limit (dBm) | Margin (dB) |
| 1                                                   | 1683        | 34.80         | -67.90                | 6.28                   | -61.62               | -13         | -48.62      |
| 2                                                   | 2524.5      | 38.34         | -59.99                | 6.64                   | -53.36               | -13         | -40.36      |
| 3                                                   | 3366        | 36.75         | -66.23                | 7.58                   | -58.64               | -13         | -45.64      |
| 4                                                   | 4207.5      | 40.14         | -64.74                | 7.46                   | -57.28               | -13         | -44.28      |
| 5                                                   | 5049        | 40.09         | -64.10                | 7.00                   | -57.10               | -13         | -44.10      |
| 6                                                   | 5890.5      | 42.26         | -62.21                | 6.91                   | -55.30               | -13         | -42.30      |
| 7                                                   | 6732        | 46.71         | -56.87                | 5.68                   | -51.20               | -13         | -38.20      |
| 8                                                   | 7573.5      | 47.10         | -55.52                | 4.58                   | -50.94               | -13         | -37.94      |
| 9                                                   | 8415        | 46.04         | -56.47                | 4.18                   | -52.29               | -13         | -39.29      |

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---