

1/F., Building No. 1 Building, Agriculture Machinery Materials Co. Wushan Road, Shipai, Tianhe District, Guangzhou, China Telephone: +86 (0) 20 3848 1001 Fax: +86 (0) 20 3848 1006

kent_hsu@sgs.com



Registration number: 282399



Report No.: 03.04.0520EF

Page: 1 of 11 FCC ID: Q6N170EL

FCC TEST REPORT

Application No. : 03.04.0520E (HK SGS NO.: 2005375/EL)

Applicant : Edu-science (H.K.) Ltd

FCC ID : Q6N170EL

Fundamental Frequency: 26.995 MHz

Equipment under Test (EUT):

Name : Airider Model : 170EL

Standards : FCC PART 15, SUBPART C : 2002

Date of Receipt : 23 April 2003

Date of Test : 23 April 2003 to 07 May 2003

Date of Issue : 26 May 2003

Test Result : PASS *

Authorized Signature:

Kent Hsu Laboratory Manager SGS-CSTC Co.,Ltd.

This report refers to the General Conditions for Inspection and Testing Services, printed overleaf

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the SGS PRODUCT CERTIFICATION MARK.. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

^{*} In the configuration tested, the EUT complied with the standards specified above.

Report No.: 03.04.0520EF

Page: 2 of 11

2 Contents

			Pa	ıge
1	(COVER	PAGE	1
2	(CONTE	NTS	2
3	(GENER	AL INFORMATION	3
	3.1		NT INFORMATION	
	3.2	DETA	AILS OF E.U.T	2
	3.3	DESC	CRIPTION OF SUPPORT UNITS	3
	3.4		LOCATION	
	3.5	OTHE	ER INFORMATION REQUESTED BY THE CUSTOMER	3
	3.6	TEST	FACILITY	4
4			ESULTS	
•				
	4.1	TEST	INSTRUMENTS	5
	4.2	E.U.T	C. OPERATION	5
	4.3	TEST	PROCEDURE & MEASUREMENT DATA	5
	4	1.3.1	Radiated Emissions	5
	4		Occupied Bandwidth	
	4	1.3.3	Photographs - Radiated Emission Test Setup in Chamber	8
5	P	РНОТО	GRAPHS - EUT CONSTRUCTIONAL DETAILS9)-1 0

Report No.: **03.04.0520EF**

Page: 3 of 11

3 General Information

3.1 Client Information

Applicant: Edu-science (H.K.) Ltd

Address of Applicant: Suite 701, 7/F, Wing on Plaza, 63 Mody road, T.S.T. East,

Kowloon, HongKong.

3.2 Details of E.U.T.

Product Name: Airider (Transmitter Part)

Model: 170EL

Power Supply: 9V DC (6 x 'AA' batteries)

Power Cord: N/A

3.3 Description of Support Units

The EUT was tested as an independent unit: a 27MHz radio transmitter.

3.4 Test Location

All tests were performed at:-

SGS-CSTC Standards Technical Services Ltd., Guangzhou Safety & EMC Laboratory, 1/F, Building No. 1, Agriculture Machinery Materials Company Warehouse Ltd., Wushan Road Shipai, Tianhe District, Guangzhou, China. P.C. 510630.

Tel: +86 20 3848 1001 Fax: +86 20 3848 1006

3.5 Other Information Requested by the Customer

None.

Report No.: **03.04.0520EF**

Page: 4 of 11

3.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• NVLAP – Lab Code: 200611-0

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is recognized under the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 2000611-0. Effective through February 2, 2003.

ACA

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

VCCI

The 3m Semi-anechoic chamber and Shielded Room (11.5m x 4m x 4m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-1599 and C-1706 respectively.

Date of Registration: February 28, 2003. Valid until May 30, 2005

• SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FINKO

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

• CNAL – LAB Code: L0141

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of Testing Laboratories.

• FCC – Registration No.: 282399

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002. With the above and NVLAP, SGS-CSTC is an authorized test laboratory for the DoC process.

Report No.: **03.04.0520EF**

Page: 5 of 11

4 Test Results

4.1 Test Instruments

Test Equipment	Manufacturer	Model	Asset No.	Cal. Due Date
Temperature, Humidity & Barometer	Oregon Scientific	BA-888	EMC0003	25-07-2003
3m Semi- Anechoic Chamber	Frankonia	N/A	EMC0501	04-11-2003
EMI Test Receiver	ROHDE & SCHWARZ	ESCS30	EMC0506	17-11-2003
Bilog Type Antenna	Schaffner Chase	CBL6143	EMC0519	01-12-2003
Coaxial cable	SGS	N/A	EMC0514	04-11-2003

4.2 E.U.T. Operation

Input voltage: 9V DC (6 x 'AA' batteries)

Operating Environment:

Temperature: 24.0 °C Humidity: 52 % RH Atmospheric Pressure: 1012 mbar

EUT Operation:

Test the EUT in transmitting mode.

4.3 Test Procedure & Measurement Data

4.3.1 Radiated Emissions

Test Requirement: FCC Part15 C

Test Method: Based on FCC Part15 C Section 15.227

Test Date: 07 May 2003

Measurement Distance: 3m (Semi-Anechoic Chamber)

Requirements: Carrier frequency will not exceed 80dBuV/m AT 3m.

Out of band emissions shall not exceed: $40.0~dB\mu V/m$ between 30MHz & 88MHz $43.5~dB\mu V/m$ between 88MHz & 216MHz $46.0~dB\mu V/m$ between 216MHz & 960MHz

54.0 dBµV/m above 960MHz

Detector: Peak Scan (120kHz resolution bandwidth)

Report No.: **03.04.0520EF**

Page: 6 of 11

Test Procedure: The procedure uesd was ANSI Standard C63.4-2000. The receive was scanned from 30MHz to 1000MHz. When an emission was found, the table was roated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. The worst case emissions were reported.

The following measurements were performed on the EUT on 07 May 2003: Test the EUT in transmitting mode.

Intentional emission

Test	Average (dBuV/m)		Limits	Margin (dB)	
Frequency (MHz)	Vertical	Horizontal	(dBuV/m)	Vertical	Horizontal
26.995	75.3	67.2	80.0	4.7	12.8

Other emissions

Frequency (MHz)	Antenna Polarization	Quasi-peak (dBuV/m)	Limit (dBuV/m)	Margin (dB)
53.990	Vertical	20.4	40.0	19.6
80.985	Vertical	33.9	40.0	6.1
107.980	Vertical	31.3	43.5	12.2
188.965	Vertical	30.5	43.5	13.0
404.895	Vertical	39.8	46.0	6.2
431.891	Vertical	41.5	46.0	4.5
620.833	Vertical	40.8	46.0	5.2
80.985	Horizontal	8.8	40.0	31.2
404.895	Horizontal	25.4	46.0	20.6
431.890	Horizontal	26.7	46.0	19.3
458.885	Horizontal	29.6	46.0	16.4
539.870	Horizontal	24.1	46.0	21.9

Test Results: The unit does meet the FCC Part 15 C requirements.

Report No.: **03.04.0520EF**

Page: 7 of 11

4.3.2 Occupied Bandwidth

Test Requirement: FCC Part15 C

Test Method: Based on FCC Part15 C Section 15.227:

Operation within the band 26.96 – 27.28 MHz

Test Date: 07 May 2003


Requirements: The field strength of any emissions which appear outside of this band

shall not exceed the general radiated emission limits in Section 15.209.

Method of measurement: The useful radiated emission from the EUT was detected by the

spectrum analyer with peak detector. The vertical Scale is set to -10dB

per division. The horizontal scale is set to 5KHz per division.



The graph as below, represents the emissions take for this device.

The results: The unit does meet the FCC Part 15 C requirements.