



## **CFR 47 FCC PART 15 SUBPART C**

### **CERTIFICATION TEST REPORT**

*For*

**Blood Pressure Monitor**

**MODEL NUMBER: TMB-2080/TMB-2080-A/TMB-2080-K/TMB-2083/TMB-2083-K/TMB-2084/TMB-2084-T/TMB-2084-K/TMB-2084-KT/TMB-2084-A**

**FCC ID: OU9TMB2080-B**

**REPORT NUMBER: 4789796104-1**

**ISSUE DATE: March 22, 2021**

*Prepared for*

**Guangdong Transtek Medical Electronics Co.,Ltd  
Zone A,No.105,Dongli Road,Torch Development  
District,Zhongshan,528437,Guangdong,China**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch**

**Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China**

**Tel: +86 769 22038881**

**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**



Revision History

Rev.	Issue Date	Revisions	Revised By
V0	03/22/2021	Initial Issue	



Summary of Test Results			
Clause	Test Items	FCC Rules	Test Results
1	6dB Bandwidth and 99% Occupied Bandwidth	FCC Part 15.247 (a) (2)	Pass
2	Peak Conducted Output Power	FCC Part 15.247 (b) (3)	Pass
3	Power Spectral Density	FCC Part 15.247 (e)	Pass
4	Conducted Bandedge and Spurious Emission	FCC Part 15.247 (d)	Pass
5	Radiated Bandedge and Spurious Emission	FCC Part 15.247 (d) FCC Part 15.209 FCC Part 15.205	Pass
6	Conducted Emission Test for AC Power Port	FCC Part 15.207	Pass
7	Antenna Requirement	FCC Part 15.203	Pass
<p>Note:</p> <p>1.This test report is only published to and used by the applicant, and it is not for evidence purpose in China.</p> <p>2. The measurement result for the sample received is &lt;Pass&gt; according to &lt; CFR 47 FCC PART 15 SUBPART C &gt; when &lt;Accuracy Method&gt; decision rule is applied.</p>			

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS.....</b>	<b>6</b>
<b>2. TEST METHODOLOGY .....</b>	<b>7</b>
<b>3. FACILITIES AND ACCREDITATION.....</b>	<b>7</b>
<b>4. CALIBRATION AND UNCERTAINTY .....</b>	<b>8</b>
4.1. MEASURING INSTRUMENT CALIBRATION .....	8
4.2. MEASUREMENT UNCERTAINTY .....	8
<b>5. EQUIPMENT UNDER TEST .....</b>	<b>9</b>
5.1. DESCRIPTION OF EUT .....	9
5.2. CHANNEL LIST.....	9
5.3. MAXIMUM PEAK OUTPUT POWER .....	10
5.4. TEST CHANNEL CONFIGURATION .....	10
5.5. THE WORSE CASE POWER SETTING PARAMETER.....	10
5.6. DESCRIPTION OF AVAILABLE ANTENNAS .....	10
5.7. DESCRIPTION OF TEST SETUP .....	11
<b>6. MEASURING INSTRUMENT AND SOFTWARE USED .....</b>	<b>12</b>
<b>7. ANTENNA PORT TEST RESULTS .....</b>	<b>14</b>
7.1. ON TIME AND DUTY CYCLE .....	14
7.2. 6 dB DTS BANDWIDTH AND 99 % OCCUPIED BANDWIDTH.....	15
7.3. CONDUCTED OUTPUT POWER .....	17
7.4. POWER SPECTRAL DENSITY .....	18
7.5. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS .....	20
<b>8. RADIATED TEST RESULTS .....</b>	<b>22</b>
8.1. RESTRICTED BANDEDGE .....	27
8.1.1. LE 1M MODE .....	27
8.1.2. LE 2M MODE .....	31
8.2. SPURIOUS EMISSIONS (1 GHz ~ 3 GHz) .....	35
8.2.1. LE 2M MODE .....	35
8.3. SPURIOUS EMISSIONS (3 GHz ~ 18 GHz) .....	41
8.3.1. LE 1M MODE .....	41
8.3.2. LE 2M MODE .....	47
8.4. SPURIOUS EMISSIONS (18 GHz ~ 26 GHz) .....	53
8.4.1. LE 2M MODE .....	53
8.5. SPURIOUS EMISSIONS (30 MHz ~ 1 GHz) .....	55
8.5.1. LE 2M MODE .....	55



8.6.	SPURIOUS EMISSIONS BELOW 30 MHz .....	57
8.6.1.	LE 2M MODE .....	57
<b>9.</b>	<b>AC POWER LINE CONDUCTED EMISSIONS .....</b>	<b>60</b>
9.1.	LE 2M MODE .....	61
<b>10.</b>	<b>ANTENNA REQUIREMENTS .....</b>	<b>63</b>
<b>11.</b>	<b>Appendix .....</b>	<b>64</b>
11.1.	Appendix A: DTS Bandwidth .....	64
11.1.1.	Test Result .....	64
11.1.2.	Test Graphs .....	65
11.2.	Appendix B: Occupied Channel Bandwidth .....	67
11.2.1.	Test Result .....	67
11.2.2.	Test Graphs .....	68
11.3.	Appendix C: Maximum PEAK conducted output power .....	70
11.3.1.	Test Result .....	70
11.4.	Appendix D: Maximum power spectral density .....	71
11.4.1.	Test Result .....	71
11.4.2.	Test Graphs .....	72
11.5.	Appendix E: Band edge measurements .....	74
11.5.1.	Test Result .....	74
11.5.2.	Test Graphs .....	75
11.6.	Appendix F: Conducted Spurious Emission .....	77
11.6.1.	Test Result .....	77
11.6.2.	Test Graphs .....	78
11.7.	Appendix G: Duty Cycle .....	84
11.7.1.	Test Result .....	84
11.7.2.	Test Graphs .....	85



## 1. ATTESTATION OF TEST RESULTS

### Applicant Information

Company Name: Guangdong Transtek Medical Electronics Co.,Ltd  
Address: Zone A,No.105,Dongli Road,Torch Development  
District,Zhongshan,528437,Guangdong,China

### Manufacturer Information

Company Name: Guangdong Transtek Medical Electronics Co.,Ltd  
Address: Zone A,No.105,Dongli Road,Torch Development  
District,Zhongshan,528437,Guangdong,China

### EUT Information

EUT Name: Blood Pressure Monitor  
Model: TMB-2080/TMB-2080-A/TMB-2080-K/TMB-2083/TMB-2083-K/TMB-2084/TMB-2084-T/TMB-2084-K/TMB-2084-KT/TMB-2084-A  
Model difference: Please refer to clause 5.1. Description of EUT  
Serial Number: BA5281201000001D  
Brand: Transtek  
Sample Received Date: January 11, 2021  
Sample Status: Normal  
Sample ID: 3586559  
Date of Tested: January 11, 2021 ~ March 19, 2021

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	PASS

Prepared By:

Denny Huang  
Project Engineer

Checked By:

Shawn Wen  
Laboratory Leader

Approved By:

Stephen Guo  
Laboratory Manager



## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 15.247 Meas Guidance v05r02, 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, CFR 47 FCC Part 15, ANSI C63.10-2013

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4102.01)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p><b>ISED (Company No.: 21320)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p><b>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B, the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	--

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.



## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognize national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
Duty Cycle	±0.028%
DTS and 99% Occupied Bandwidth	±0.0196%
Maximum Conducted Output Power	±0.686 dB
Maximum Power Spectral Density Level	±0.743 dB
Conducted Band-edge Compliance	±1.328 dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	±0.746 dB (9 kHz ~ 1 GHz)
	±1.328dB (1 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	





## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

EUT Name	Blood Pressure Monitor	
Test Model	TMB-2084-T	
Series Model	TMB-2080/TMB-2080-A/TMB-2080-K/TMB-2083/TMB-2083-K/TMB-2084/TMB-2084-K/TMB-2084-KT/TMB-2084-A	
Model Difference	TMB-2080/TMB-2080-A/TMB-2080-K/TMB-2083/TMB-2083-K/TMB-2084/TMB-2084-K/TMB-2084-KT/TMB-2084-A have the same technical construction including circuit diagram, PCB Layout, components and component layout, all electrical construction and mechanical construction with TMB-2084-T. The difference lies only the model number, appearance and voice function. All models which is without voice function were removed the speech function circuit and this function will be shielded by software. Pre-scan has been conducted to determine the worst-case mode between with and without voice function model. Only the worst test data (TMB-2084-T) were report in this report.	
Technology	Bluetooth - Low Energy	
Transmit Frequency Range	2402 MHz ~ 2480 MHz	
Modulation	GFSK	
Data Rate	LE 1M	1 Mbps
	LE 2M	2 Mbps
Power Supply	DC 5 V, 1 A by USB or DC 1.5 V (AAA)*4	

Note: Both DC 5 V by USB and DC 6 V by battery power supply had been tested, but only the worst data was recorded in the report.

### 5.2. CHANNEL LIST

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	11	2424	22	2446	33	2468
1	2404	12	2426	23	2448	34	2470
2	2406	13	2428	24	2450	35	2472
3	2408	14	2430	25	2452	36	2474
4	2410	15	2432	26	2454	37	2476
5	2412	16	2434	27	2456	38	2478
6	2414	17	2436	28	2458	39	2480
7	2416	18	2438	29	2460	/	/
8	2418	19	2440	30	2462	/	/
9	2420	20	2442	31	2464	/	/
10	2422	21	2444	32	2468	/	/

### 5.3. MAXIMUM PEAK OUTPUT POWER

Test Mode	Frequency (MHz)	Channel Number	Maximum Peak Output Power (dBm)
LE 1M	2402 ~ 2480	0-39[40]	-1.61
LE 2M	2402 ~ 2480	0-39[40]	-1.54

### 5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
LE 1M	CH 0(Low Channel), CH 19(MID Channel), CH 39(High Channel)	2402 MHz, 2440 MHz, 2480 MHz
LE 2M	CH 0(Low Channel), CH 19(MID Channel), CH 39(High Channel)	2402 MHz, 2440 MHz, 2480 MHz

### 5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2402 ~ 2480MHz Band				
Test Software Version		FCC_assist_1.0.2.2		
Test Mode	Transmit Antenna Number	Test Software Setting Value		
		CH 0	CH 19	CH 39
LE 1M	1	Default	Default	Default
LE 2M	1	Default	Default	Default

### 5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2402-2480	PCB	0.9

Test Mode	Transmit and Receive Mode	Description
LE 1M	<input checked="" type="checkbox"/> 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
LE 2M	<input checked="" type="checkbox"/> 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.

Note: The value of the antenna gain was declared by customer.

## 5.7. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	P/N
1	Laptop	ThinkPad	X230i	/
2	Laptop	ThinkPad	E480	/
3	Serial to USB Board	/	/	/

### I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	USB	Unshielded	1.0 m	/


### ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
1	AC Adapter	/	BLJ06L0501 00U-U	Input: 100-240 V ~ 50/60 Hz 0.2 A Max Output: DC 5.0 V 1.0 A

### TEST SETUP

The EUT can work in engineering mode with a software through a Laptop.

### SETUP DIAGRAM FOR TESTS





## 6. MEASURING INSTRUMENT AND SOFTWARE USED

Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Nov. 12, 2020	Nov. 11, 2021
Two-Line V-Network	R&S	ENV216	101983	Nov. 12, 2020	Nov. 11, 2021
Software					
Description			Manufacturer	Name	Version
Test Software for Conducted Emissions			Farad	EZ-EMC	Ver. UL-3A1

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Nov. 12, 2020	Nov. 11, 2021
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	Aug. 11, 2018	Aug. 10, 2021
Preamplifier	HP	8447D	2944A09099	Nov. 12, 2020	Nov. 11, 2021
EMI Measurement Receiver	R&S	ESR26	101377	Nov. 12, 2020	Nov. 11, 2021
Horn Antenna	TDK	HRN-0118	130939	Sept. 17, 2018	Sept. 17, 2021
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Nov. 20, 2020	Nov. 19, 2021
Horn Antenna	Schwarzbeck	BBHA9170	#691	Aug. 11, 2018	Aug. 11, 2021
Preamplifier	TDK	PA-02-2	TRS-307-00003	Nov. 12, 2020	Nov. 11, 2021
Loop antenna	Schwarzbeck	1519B	00008	Jan.17, 2019	Jan.17,2022
Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Nov. 12, 2020	Nov. 11, 2021
Preamplifier	Mini-Circuits	ZX60-83LN-S+	SUP01201941	Nov. 20, 2020	Nov. 19, 2021
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Nov. 12, 2020	Nov. 11, 2021
Software					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1



Other instruments					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Spectrum Analyzer	Keysight	N9030A	MY55410512	Nov. 20, 2020	Nov. 19, 2021
Dual Channel Power Meter	Keysight	N1912A	MY55416024	Nov. 20, 2020	Nov. 19, 2021
Power Sensor	Keysight	USB Wideband Power Sensor	MY5100022	Nov. 20, 2020	Nov. 19, 2021



## 7. ANTENNA PORT TEST RESULTS

### 7.1. ON TIME AND DUTY CYCLE


#### LIMITS

None; for reporting purposes only.

#### PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	22.8 °C	Relative Humidity	39.8 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V

#### RESULTS

Please refer to appendix G.

## 7.2. 6 dB DTS BANDWIDTH AND 99 % OCCUPIED BANDWIDTH

### LIMITS

CFR 47FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2)	6 dB Bandwidth	$\geq 500$ kHz	2400-2483.5

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.


Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW
Detector	Peak
RBW	For 6 dB Bandwidth: 100 kHz For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 6 dB Bandwidth: $\geq 3 \times$ RBW For 99 % Occupied Bandwidth: $\geq 3 \times$ RBW
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### TEST SETUP





### **TEST ENVIRONMENT**

Temperature	22.8 °C	Relative Humidity	39.8 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V

### **RESULTS**

Please refer to appendix A & B.





### 7.3. CONDUCTED OUTPUT POWER


#### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3)	Peak Conducted Output Power	1 watt or 30 dBm	2400-2483.5

#### TEST PROCEDURE

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).  
Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	22.8 °C	Relative Humidity	39.8 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V

#### RESULTS

Please refer to appendix C.

## 7.4. POWER SPECTRAL DENSITY

### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.10.


Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	$1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### TEST SETUP



### TEST ENVIRONMENT

Temperature	22.8 °C	Relative Humidity	39.8 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V



## **RESULTS**

Please refer to appendix D.



## 7.5. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS

### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d)	Conducted Bandedge and Spurious Emissions	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyser and use the following settings for reference level measurement:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.


Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

### TEST SETUP



#### **TEST ENVIRONMENT**

Temperature	22.8 °C	Relative Humidity	39.8 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V

#### **RESULTS**

Please refer to appendix E & F.

## 8. RADIATED TEST RESULTS

### LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz-1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

FCC Restricted bands of operation refer to FCC §15.205 (a):


MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
<sup>1</sup> 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

Note: <sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup>Above 38.6c

## TEST SETUP AND PROCEDURE

Below 30 MHz




The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 11.11.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

Below 1 GHz and above 30 MHz




The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 11.11.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.



Above 1GHz




The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 11.11 and 11.12.
2. The EUT was arranged to its worst case and then tune the antenna tower (1.5 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1.ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

Note 2: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

Note 3: Both DC 5 V by USB and DC 6 V by battery power supply had been tested, but only the worst data was recorded in the report.

## **TEST ENVIRONMENT**

Temperature	18.3 °C	Relative Humidity	43.9 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V

## **RESULTS**




## 8.1. RESTRICTED BANDEDGE

### 8.1.1. LE 1M MODE

#### RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)


##### PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.925	21.15	33.35	54.50	74.00	-19.50	peak
2	2390.000	20.07	33.35	53.42	74.00	-20.58	peak


Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.925	1.46	33.35	34.81	54.00	-19.19	AVG
2	2390.000	1.55	33.35	34.90	54.00	-19.10	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.  
5. For the transmitting duration, please refer to clause 7.1.  
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	36.82	33.71	70.53	74.00	-3.47	peak


Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	11.95	33.71	45.66	54.00	-8.34	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.  
5. For the transmitting duration, please refer to clause 7.1.  
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

## 8.1.2. LE 2M MODE

### RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)


#### PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.660	21.39	33.34	54.73	74.00	-19.27	peak
2	2390.000	19.62	33.35	52.97	74.00	-21.03	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


### AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.660	1.38	33.34	34.72	54.00	-19.28	AVG
2	2390.000	1.62	33.35	34.97	54.00	-19.03	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.  
5. For the transmitting duration, please refer to clause 7.1.  
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	34.10	33.71	67.81	74.00	-6.19	peak
2	2484.225	32.54	33.71	66.25	74.00	-7.75	peak


Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	9.58	33.71	43.29	54.00	-10.71	AVG
2	2484.225	10.30	33.71	44.01	54.00	-9.99	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.  
5. For the transmitting duration, please refer to clause 7.1.  
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Note: Both the horizontal and vertical polarities had been tested, but only the worst data was recorded in the report.



## 8.2. SPURIOUS EMISSIONS (1 GHz ~ 3 GHz)

### 8.2.1. LE 2M MODE


#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1248.000	44.68	-12.92	31.76	74.00	-42.24	peak
2	1554.000	44.10	-11.86	32.24	74.00	-41.76	peak
3	1742.000	45.31	-10.49	34.82	74.00	-39.18	peak
4	1992.000	46.27	-10.19	36.08	74.00	-37.92	peak
5	2402.000	44.93	-8.39	36.54	74.00	-37.46	peak
6	2842.000	42.84	-6.35	36.49	74.00	-37.51	peak


- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1162.000	50.58	-13.18	37.40	74.00	-36.60	peak
2	1212.000	49.52	-12.97	36.55	74.00	-37.45	peak
3	2338.000	47.63	-8.60	39.03	74.00	-34.97	peak
4	2402.000	49.80	-8.39	41.41	74.00	-32.59	peak
5	2688.000	43.88	-7.28	36.60	74.00	-37.40	peak
6	2992.000	44.84	-5.63	39.21	74.00	-34.79	peak


- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1358.000	45.08	-12.77	32.31	74.00	-41.69	peak
2	1666.000	46.28	-11.06	35.22	74.00	-38.78	peak
3	1908.000	45.65	-10.12	35.53	74.00	-38.47	peak
4	1992.000	46.00	-10.19	35.81	74.00	-38.19	peak
5	2334.000	43.80	-8.61	35.19	74.00	-38.81	peak
6	2834.000	42.65	-6.39	36.26	74.00	-37.74	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1164.000	51.01	-13.16	37.85	74.00	-36.15	peak
2	1326.000	48.30	-12.81	35.49	74.00	-38.51	peak
3	1664.000	47.65	-11.08	36.57	74.00	-37.43	peak
4	2128.000	46.30	-9.46	36.84	74.00	-37.16	peak
5	2440.000	55.44	-8.33	47.11	74.00	-26.89	peak
6	2688.000	45.36	-7.28	38.08	74.00	-35.92	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1546.000	44.48	-11.92	32.56	74.00	-41.44	peak
2	1660.000	46.72	-11.10	35.62	74.00	-38.38	peak
3	1864.000	45.48	-10.10	35.38	74.00	-38.62	peak
4	2142.000	43.70	-9.37	34.33	74.00	-39.67	peak
5	2480.000	45.58	-8.26	37.32	74.00	-36.68	peak
6	2772.000	43.15	-6.74	36.41	74.00	-37.59	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1290.000	50.26	-12.86	37.40	74.00	-36.60	peak
2	1790.000	44.51	-10.13	34.38	74.00	-39.62	peak
3	2304.000	44.93	-8.71	36.22	74.00	-37.78	peak
4	2480.000	56.87	-8.26	48.61	74.00	-25.39	peak
5	2562.000	48.67	-8.00	40.67	74.00	-33.33	peak
6	2912.000	42.97	-6.01	36.96	74.00	-37.04	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

Note: All the modes have been tested, only the worst data was recorded in the report.






### 8.3. SPURIOUS EMISSIONS (3 GHz ~ 18 GHz)

#### 8.3.1. LE 1M MODE

##### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3990.000	48.22	-2.51	45.71	74.00	-28.29	peak
2	8115.000	37.32	10.13	47.45	74.00	-26.55	peak
3	11715.000	35.08	15.34	50.42	74.00	-23.58	peak
4	13635.000	34.27	17.28	51.55	74.00	-22.45	peak
5	14790.000	33.65	18.01	51.66	74.00	-22.34	peak
6	17205.000	30.02	22.02	52.04	74.00	-21.96	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3975.000	49.52	-2.57	46.95	74.00	-27.05	peak
2	4800.000	44.31	1.40	45.71	74.00	-28.29	peak
3	9000.000	36.54	11.27	47.81	74.00	-26.19	peak
4	11505.000	35.88	14.66	50.54	74.00	-23.46	peak
5	13515.000	34.44	17.19	51.63	74.00	-22.37	peak
6	16920.000	30.71	21.51	52.22	74.00	-21.78	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	44.05	1.32	45.37	74.00	-28.63	peak
2	9255.000	37.31	10.17	47.48	74.00	-26.52	peak
3	11055.000	34.89	13.58	48.47	74.00	-25.53	peak
4	12645.000	35.30	15.71	51.01	74.00	-22.99	peak
5	16755.000	31.15	20.37	51.52	74.00	-22.48	peak
6	17760.000	27.97	23.82	51.79	74.00	-22.21	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3975.000	51.04	-2.57	48.47	74.00	-25.53	peak
2	4875.000	44.69	1.32	46.01	74.00	-27.99	peak
3	8115.000	38.44	10.13	48.57	74.00	-25.43	peak
4	10410.000	42.33	12.25	54.58	74.00	-19.42	peak
5	10410.000	27.86	12.25	40.11	54.00	-13.89	AVG
6	14820.000	33.63	17.91	51.54	74.00	-22.46	peak
7	17235.000	30.35	22.21	52.56	74.00	-21.44	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	44.48	1.71	46.19	74.00	-27.81	peak
2	8100.000	37.27	10.18	47.45	74.00	-26.55	peak
3	9210.000	37.88	9.95	47.83	74.00	-26.17	peak
4	12585.000	35.33	15.77	51.10	74.00	-22.90	peak
5	14820.000	33.54	17.91	51.45	74.00	-22.55	peak
6	16845.000	30.82	21.10	51.92	74.00	-22.08	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	45.42	1.71	47.13	74.00	-26.87	peak
2	9390.000	37.18	10.92	48.10	74.00	-25.90	peak
3	10260.000	36.97	11.68	48.65	74.00	-25.35	peak
4	12210.000	34.80	15.97	50.77	74.00	-23.23	peak
5	14820.000	33.33	17.91	51.24	74.00	-22.76	peak
6	17775.000	28.14	23.91	52.05	74.00	-21.95	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


### 8.3.2. LE 2M MODE

#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	43.17	1.40	44.57	74.00	-29.43	peak
2	7770.000	37.93	9.09	47.02	74.00	-26.98	peak
3	8970.000	37.10	10.70	47.80	74.00	-26.20	peak
4	12615.000	34.65	15.75	50.40	74.00	-23.60	peak
5	14820.000	33.30	17.91	51.21	74.00	-22.79	peak
6	17295.000	30.32	22.58	52.90	74.00	-21.10	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	43.38	1.40	44.78	74.00	-29.22	peak
2	8010.000	38.01	8.79	46.80	74.00	-27.20	peak
3	8970.000	37.39	10.70	48.09	74.00	-25.91	peak
4	12255.000	34.06	16.03	50.09	74.00	-23.91	peak
5	14820.000	33.20	17.91	51.11	74.00	-22.89	peak
6	17100.000	30.35	21.90	52.25	74.00	-21.75	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	42.89	1.32	44.21	74.00	-29.79	peak
2	8115.000	37.23	10.13	47.36	74.00	-26.64	peak
3	11355.000	34.17	14.34	48.51	74.00	-25.49	peak
4	12285.000	35.33	16.08	51.41	74.00	-22.59	peak
5	14820.000	33.39	17.91	51.30	74.00	-22.70	peak
6	17085.000	30.36	21.80	52.16	74.00	-21.84	peak


Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	43.61	1.32	44.93	74.00	-29.07	peak
2	7875.000	39.21	8.98	48.19	74.00	-25.81	peak
3	9390.000	37.30	10.92	48.22	74.00	-25.78	peak
4	12525.000	34.80	15.70	50.50	74.00	-23.50	peak
5	14820.000	33.35	17.91	51.26	74.00	-22.74	peak
6	17325.000	30.19	22.42	52.61	74.00	-21.39	peak


Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3975.000	48.20	-2.57	45.63	74.00	-28.37	peak
2	4950.000	44.30	1.71	46.01	74.00	-27.99	peak
3	7815.000	39.51	9.28	48.79	74.00	-25.21	peak
4	11835.000	35.08	15.34	50.42	74.00	-23.58	peak
5	13920.000	33.93	17.55	51.48	74.00	-22.52	peak
6	16920.000	30.30	21.51	51.81	74.00	-22.19	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	45.62	1.71	47.33	74.00	-26.67	peak
2	8100.000	37.13	10.18	47.31	74.00	-26.69	peak
3	8985.000	36.62	10.99	47.61	74.00	-26.39	peak
4	11685.000	35.10	15.26	50.36	74.00	-23.64	peak
5	13980.000	33.39	17.64	51.03	74.00	-22.97	peak
6	17115.000	30.03	21.91	51.94	74.00	-22.06	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

## 8.4. SPURIOUS EMISSIONS (18 GHz ~ 26 GHz)

### 8.4.1. LE 2M MODE

#### SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18264.000	50.15	-5.53	44.62	74.00	-29.38	peak
2	20000.000	50.81	-5.45	45.36	74.00	-28.64	peak
3	20560.000	50.23	-5.30	44.93	74.00	-29.07	peak
4	21856.000	49.52	-4.39	45.13	74.00	-28.87	peak
5	23064.000	48.99	-3.42	45.57	74.00	-28.43	peak
6	24664.000	47.40	-2.33	45.07	74.00	-28.93	peak


Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.



**SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18112.000	49.96	-5.47	44.49	74.00	-29.51	peak
2	19784.000	50.57	-5.28	45.29	74.00	-28.71	peak
3	20472.000	49.57	-5.39	44.18	74.00	-29.82	peak
4	21584.000	49.60	-4.56	45.04	74.00	-28.96	peak
5	23264.000	48.76	-3.36	45.40	74.00	-28.60	peak
6	25688.000	45.81	-0.90	44.91	74.00	-29.09	peak

Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.


Note: All the modes have been tested, only the worst data was recorded in the report.



## 8.5. SPURIOUS EMISSIONS (30 MHz ~ 1 GHz)

### 8.5.1. LE 2M MODE


#### SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	180.3500	54.18	-16.82	37.36	43.50	-6.14	QP
2	203.6300	56.19	-16.70	39.49	43.50	-4.01	QP
3	227.8800	58.44	-18.55	39.89	46.00	-6.11	QP
4	276.3800	57.98	-17.06	40.92	46.00	-5.08	QP
5	323.9100	57.61	-14.74	42.87	46.00	-3.13	QP
6	372.4100	52.86	-13.87	38.99	46.00	-7.01	QP

Note: 1. Result Level = Read Level + Correct Factor.  
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

**SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	48.4300	56.44	-20.63	35.81	40.00	-4.19	QP
2	84.3200	56.25	-21.63	34.62	40.00	-5.38	QP
3	156.1000	54.20	-17.96	36.24	43.50	-7.26	QP
4	203.6300	54.08	-16.70	37.38	43.50	-6.12	QP
5	299.6600	51.90	-15.31	36.59	46.00	-9.41	QP
6	600.3600	44.59	-9.54	35.05	46.00	-10.95	QP

- Note: 1. Result Level = Read Level + Correct Factor.  
 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto

Note: All the modes have been tested, only the worst data was recorded in the report.




## 8.6. SPURIOUS EMISSIONS BELOW 30 MHz

### 8.6.1. LE 2M MODE

#### SPURIOUS EMISSIONS (HIGH CHANNEL, LOOP ANTENNA FACE ON TO THE EUT, WORST-CASE CONFIGURATION)

9 kHz~ 150 kHz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.0100	73.22	-101.40	-28.18	47.6	-79.68	-3.90	-75.78	peak
2	0.0120	70.36	-101.39	-31.03	46.02	-82.53	-5.48	-77.05	peak
3	0.0171	67.88	-101.36	-33.48	42.94	-84.98	-8.56	-76.42	peak
4	0.0279	65.67	-101.38	-35.71	38.69	-87.21	-12.81	-74.40	peak
5	0.0432	61.57	-101.45	-39.88	34.89	-91.38	-16.61	-74.77	peak
6	0.0981	56.27	-101.78	-45.51	27.77	-97.01	-23.73	-73.28	peak

Note: 1. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

2. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.




150 kHz ~ 490 kHz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.1554	72.27	-101.65	-29.38	23.77	-80.88	-27.73	-53.15	peak
2	0.1794	69.27	-101.68	-32.41	22.53	-83.91	-28.97	-54.94	peak
3	0.2200	66.24	-101.75	-35.51	20.75	-87.01	-30.75	-56.26	peak
4	0.2605	62.14	-101.81	-39.67	19.28	-91.17	-32.22	-58.95	peak
5	0.3382	59.73	-101.90	-42.17	17.02	-93.67	-34.48	-59.19	peak
6	0.4142	55.23	-101.98	-46.75	15.26	-98.25	-36.24	-62.01	peak

Note: 1. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.  
2. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

**490 kHz ~ 30 MHz**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.5453	62.87	-62.08	0.79	32.87	-50.71	-18.63	-32.08	peak
2	1.0443	60.03	-62.25	-2.22	27.23	-53.72	-24.27	-29.45	peak
3	1.8205	56.45	-61.90	-5.45	29.54	-56.95	-21.96	-34.99	peak
4	5.2705	53.04	-61.45	-8.41	29.54	-59.91	-21.96	-37.95	peak
5	17.3992	51.93	-60.92	-8.99	29.54	-60.49	-21.96	-38.53	peak
6	21.9143	51.72	-60.69	-8.97	29.54	-60.47	-21.96	-38.51	peak

Note: 1. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

2. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

Note: All the modes have been tested, but only the worst data was recorded in the report.

## 9. AC POWER LINE CONDUCTED EMISSIONS


### LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

### TEST SETUP AND PROCEDURE

Refer to ANSI C63.10-2013 clause 6.2.




The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

### TEST ENVIRONMENT

Temperature	21.5 °C	Relative Humidity	60.1 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V

**RESULTS****9.1. LE 2M MODE****LINE L RESULTS (HIGH CHANNEL, WORST-CASE CONFIGURATION)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1628	19.90	9.59	29.49	65.32	-35.83	QP
2	0.1628	-2.12	9.59	7.47	55.32	-47.85	AVG
3	0.2590	15.47	9.59	25.06	61.46	-36.40	QP
4	0.2590	-3.66	9.59	5.93	51.46	-45.53	AVG
5	0.4069	10.95	9.60	20.55	57.71	-37.16	QP
6	0.4069	-3.86	9.60	5.74	47.71	-41.97	AVG
7	0.7117	3.36	9.60	12.96	56.00	-43.04	QP
8	0.7117	-5.20	9.60	4.40	46.00	-41.60	AVG
9	1.2501	-0.43	9.61	9.18	56.00	-46.82	QP
10	1.2501	-5.74	9.61	3.87	46.00	-42.13	AVG
11	24.8729	-2.65	9.85	7.20	60.00	-52.80	QP
12	24.8729	-4.85	9.85	5.00	50.00	-45.00	AVG


Note: 1. Result = Reading + Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).

4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

### LINE N RESULTS (HIGH CHANNEL, WORST-CASE CONFIGURATION)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1519	20.46	9.59	30.05	65.90	-35.85	QP
2	0.1519	-0.38	9.59	9.21	55.90	-46.69	AVG
3	0.1666	19.33	9.59	28.92	65.13	-36.21	QP
4	0.1666	-1.31	9.59	8.28	55.13	-46.85	AVG
5	0.2475	15.01	9.59	24.60	61.84	-37.24	QP
6	0.2475	-2.40	9.59	7.19	51.84	-44.65	AVG
7	0.4168	15.32	9.60	24.92	57.51	-32.59	QP
8	0.4168	-1.24	9.60	8.36	47.51	-39.15	AVG
9	0.7130	11.13	9.60	20.73	56.00	-35.27	QP
10	0.7130	-2.33	9.60	7.27	46.00	-38.73	AVG
11	25.3532	1.76	9.75	11.51	60.00	-48.49	QP
12	25.3532	-4.20	9.75	5.55	50.00	-44.45	AVG

Note: 1. Result = Reading + Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).

4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, but only the worst data was recorded in the report.



## 10. ANTENNA REQUIREMENTS

### APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### RESULTS

Complies



## 11. Appendix

### 11.1. Appendix A: DTS Bandwidth

#### 11.1.1. Test Result

Test Mode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
LE 1M	Ant1	2402	0.666	2401.673	2402.339	0.5	PASS
		2440	0.654	2439.679	2440.333	0.5	PASS
		2480	0.696	2479.667	2480.363	0.5	PASS
LE 2M	Ant1	2402	1.144	2401.440	2402.584	0.5	PASS
		2440	1.248	2439.352	2440.600	0.5	PASS
		2480	1.152	2479.424	2480.576	0.5	PASS





## 11.1.2. Test Graphs







## 11.2. Appendix B: Occupied Channel Bandwidth

### 11.2.1. Test Result

Test Mode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Verdict
LE 1M	Ant1	2402	1.0458	2401.482	2402.528	PASS
		2440	1.0376	2439.487	2440.524	PASS
		2480	1.0464	2479.484	2480.530	PASS
LE 2M	Ant1	2402	2.0913	2400.970	2403.061	PASS
		2440	2.0783	2438.984	2441.062	PASS
		2480	2.0831	2478.976	2481.059	PASS

## 11.2.2. Test Graphs





**11.3. Appendix C: Maximum PEAK conducted output power****11.3.1. Test Result**

Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
LE 1M	Ant1	2402	-3.43	<=30	PASS
		2440	-2.52	<=30	PASS
		2480	-1.61	<=30	PASS
LE 2M	Ant1	2402	-3.41	<=30	PASS
		2440	-2.48	<=30	PASS
		2480	-1.54	<=30	PASS




## 11.4. Appendix D: Maximum power spectral density

### 11.4.1. Test Result


Test Mode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
LE 1M	Ant1	2402	-20.89	$\leq 8$	PASS
		2440	-19.32	$\leq 8$	PASS
		2480	-18.32	$\leq 8$	PASS
LE 2M	Ant1	2402	-24.03	$\leq 8$	PASS
		2440	-22.63	$\leq 8$	PASS
		2480	-21.6	$\leq 8$	PASS



## 11.4.2. Test Graphs









## 11.5. Appendix E: Band edge measurements


### 11.5.1. Test Result

Test Mode	Antenna	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
LE 1M	Ant1	Low	2402	-5.14	-36.62	<=-25.14	PASS
		High	2480	-1.85	-42.87	<=-21.85	PASS
LE 2M	Ant1	Low	2402	-5.20	-37.68	<=-25.2	PASS
		High	2480	-4.45	-47.01	<=-24.45	PASS



## 11.5.2. Test Graphs





LE 2M\_Ant1\_High\_2480


## 11.6. Appendix F: Conducted Spurious Emission


### 11.6.1. Test Result


Test Mode	Antenna	Channel	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
LE 1M	Ant1	2402	Reference	-5.23	-5.23	---	PASS
			30~1000	-5.23	-62.62	<=-25.23	PASS
			1000~26500	-5.23	-52.58	<=-25.23	PASS
		2440	Reference	-3.44	-3.44	---	PASS
			30~1000	-3.44	-62.89	<=-23.44	PASS
			1000~26500	-3.44	-54.02	<=-23.44	PASS
		2480	Reference	-1.88	-1.88	---	PASS
			30~1000	-1.88	-63.63	<=-21.88	PASS
			1000~26500	-1.88	-51.19	<=-21.88	PASS
LE 2M	Ant1	2402	Reference	-5.60	-5.60	---	PASS
			30~1000	-5.60	-63.09	<=-25.6	PASS
			1000~26500	-5.60	-54.36	<=-25.6	PASS
		2440	Reference	-4.10	-4.10	---	PASS
			30~1000	-4.10	-63.13	<=-24.1	PASS
			1000~26500	-4.10	-53.17	<=-24.1	PASS
		2480	Reference	-2.87	-2.87	---	PASS
			30~1000	-2.87	-62.97	<=-22.87	PASS
			1000~26500	-2.87	-54.91	<=-22.87	PASS




## 11.6.2. Test Graphs


















## 11.7. Appendix G: Duty Cycle

### 11.7.1. Test Result

Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
LE 1M	0.39	2.11	0.185	18.5	3.96	2.56	3
LE 2M	1.07	3.5	0.306	30.6	1.68	0.29	1

Note:

Duty Cycle Correction Factor= $10\log(1/x)$ .


Where: x is Duty Cycle (Linear)

Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.



## 11.7.2. Test Graphs



END OF REPORT