

RF Exposure Report

Report No.: SA191227E08C

FCC ID: Q87-08151

Test Model: MR7350

Series Model: MR7340, MR7320, MR7310

Received Date: Jan. 13, 2020

Test Date: May 07, 2020

Issued Date: June 12, 2020

Applicant: LINKSYS LLC

Address: 121 Theory Drive Irvine California 92617 United States

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

**FCC Registration /
Designation Number:** 723255 / TW2022

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity.....	4
2 RF Exposure.....	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result of Maximum Conducted Power	7

Release Control Record

Issue No.	Description	Date Issued
SA191227E08C	Original release.	June 12, 2020

1 Certificate of Conformity

Product: Linksys Dual-Band 802.11ax Wireless Router

Brand: Linksys

Test Model: MR7350

Series Model: MR7340, MR7320, MR7310

Sample Status: ENGINEERING SAMPLE

Applicant: LINKSYS LLC

Test Date: May 07, 2020

Standards: FCC Part 2 (Section 2.1091)
IEEE C95.3-2002

References Test Guidance: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Vivian Huang , **Date:** June 12, 2020
Vivian Huang / Specialist

Approved by : Clark Lin , **Date:** June 12, 2020
Clark Lin / Technical Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$Pd = (P_{out} * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 35cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Antenna No.	Antenna Net Gain (dBi)	Frequency Range (GHz)	Antenna Type	Connector Type	Cable Length (mm)
WiFi 1	2.05	2.4~2.4835	Dipole	i-pex(MHF)	330
	2.44	5.15~5.25			
	2.71	5.25~5.35			
	3.07	5.47~5.725			
	3.02	5.725~5.85			
WiFi 2	2.39	2.4~2.4835	Dipole	i-pex(MHF)	80
	3.07	5.15~5.25			
	3.03	5.25~5.35			
	3.08	5.47~5.725			
	3.13	5.725~5.85			
BT	3.6	2.4~2.4835	Metal	none	NA

2.5 Calculation Result of Maximum Conducted Power

For 2.4GHz, 5GHz (U-NII-1 & U-NII-3 band) data was copied from the original test report (Report No.: SA191227E08)

Operation Mode	Evaluation Frequency (MHz)	Max. Average Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN 2.4GHz	2412~2462	974.252	5.23	35	0.21102	1
WLAN 5GHz U-NII-1	5180~5250	918.001	5.77	35	0.22516	1
WLAN 5GHz U-NII-2A	5260~5320	240.165	5.88	35	0.06042	1
WLAN 5GHz U-NII-2C	5500~5720	236.902	6.09	35	0.06255	1
WLAN 5GHz U-NII-3	5745~5825	958.805	6.09	35	0.25315	1
BT-EDR	2402~2480	8.81	3.6	35	0.00131	1
BT-LE	2402~2480	4.102	3.6	35	0.00061	1

NOTE:

2.4GHz: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.23 \text{ dBi}$

5GHz:

U-NII-1: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.77 \text{ dBi}$

U-NII-2A: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.88 \text{ dBi}$

U-NII-2C: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 6.09 \text{ dBi}$

U-NII-3: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 6.09 \text{ dBi}$

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + WLAN 5GHz + Bluetooth = $0.21102 / 1 + 0.25315 / 1 + 0.00131 / 1 = 0.46548$

Therefore the maximum calculations of above situations are less than the “1” limit.

--- END ---