

# **RADIO TEST REPORT**

Test Report No. : 11182619H-D-R1

| Applicant         | : | silex technology, Inc.                         |
|-------------------|---|--|
| Type of Equipment | : | SDIO Wireless Module                           |
| Model No.         | : | SX-SDMAC                                       |
| FCC ID            | : | N6C-SDMAC                                      |
| Test regulation   | : | FCC Part 15 Subpart E: 2016<br>(DFS test only) |

# Test Result : Complied

- 1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
- 2. The results in this report apply only to the sample tested.
- 3. This sample tested is in compliance with the above regulation.
- 4. The test results in this report are traceable to the national or international standards.
- 5. This test report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.
- 6. This test report covers Radio technical requirements. It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)
- 7. This report is a revised version of 111182619H-D. 11182619H-D is replaced with this report.

Date of test:

Representative test engineer:

Yuta Moriya Engineer Consumer Technology Division

August 30 and 31, 2016

Approved by:

Tsubasa Takayama Engineer Consumer Technology Division



This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation. \*As for the range of Accreditation in NVLAP, you may refer to the WEB address, http://japan.ul.com/resources/emc\_accredited/

# **REVISION HISTORY**

# **Original Test Report No.: 11182619H-D**

| Revision        | Test report No. | Date               | Page<br>revised | Contents  |
|-----------------|-----------------|--------------------|-----------------|---|
| -<br>(Original) | 11182619H-D     | September 27, 2016 | -               | -   |
| 1               | 11182619H-D-R1  | November 7, 2016   | P11             | Addition of explanatory note about tested port. |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |
|                 |                 |                    |                 |   |

| Test report No. | : 11182619H-D-R1   |
|-----------------|--------------------|
| Page            | : 3 of 22          |
| Issued date     | : November 7, 2016 |
| FCC ID          | : N6C-SDMAC        |

PAGE

# **CONTENTS**

| <b>SECTION 1:</b> | Customer information                                 | 4  |
|-------------------|--|----|
| <b>SECTION 2:</b> | Equipment under test (E.U.T.)                        | 4  |
| <b>SECTION 3:</b> | Scope of Report                                      | 6  |
| <b>SECTION 4:</b> | Test specification, procedures & results             | 6  |
| <b>SECTION 5:</b> | Operation of E.U.T. during testing                   | 11 |
| <b>SECTION 6:</b> | Channel Move Time, Channel Closing Transmission Time | 17 |
| <b>SECTION 7:</b> | Non-Occupancy Period                                 | 19 |
| <b>APPENDIX 1</b> | : Test instruments                                   | 21 |
| <b>APPENDIX 2</b> | : Photographs of test setup                          | 22 |
|                   |  |    |

# **SECTION 1: Customer information**

| Company Name     | : | silex technology, Inc.                            |
|------------------|---|---|
| Address          | : | 2-3-1 Hikaridai, Seika-cho, Kyoto 619-0237, Japan |
| Telephone Number | : | +81-774-98-3878                                   |
| Facsimile Number | : | +81-774-98-3758                                   |
| Contact Person   | : | Toshiro Kometani                                  |

# **SECTION 2: Equipment under test (E.U.T.)**

# 2.1 Identification of E.U.T.

| Type of Equipment      | : | SDIO Wireless Module  |
|------------------------|---|---|
| Model No.              | : | SX-SDMAC  |
| Serial No.             | : | Refer to Section 4, Clause 4.2                                    |
| Rating                 | : | DC 3.3 V  |
| Receipt Date of Sample | : | March 7, 2016   |
| Country of Manufacture | : | Japan   |
| Condition of EUT       | : | Production prototype  |
|                        |   | (Not for Sale: This sample is equivalent to mass-produced items.) |
| Modification of EUT    | : | No Modification by the test lab                                   |

| Test report No. | : 11182619H-D-R1   |
|-----------------|--------------------|
| Page            | : 5 of 22          |
| Issued date     | : November 7, 2016 |
| FCC ID          | : N6C-SDMAC        |
|                 |                    |

# 2.2 Product Description

Model: SX-SDMAC (referred to as the EUT in this report) is a SDIO Wireless Module.

| General Specification              |   |                         |
|------------------------------------|---|-------------------------|
| Clock frequency(ies) in the system | : | 48 MHz                  |
| Operating Temperature              | : | -40 deg. C - +85 deg. C |
| Radio Specification                |   |                         |
| Radio Type                         | : | Transceiver             |
| Method of Frequency Generation     | : | Synthesizer             |
| Power Supply (inner)               | : | DC 1.1 V                |

|                              | IEEE802.11b  | IEEE802.11g/n<br>(20 M band)              | IEEE802.11a/n/ac<br>(20 M band)   | IEEE802.11n/ac<br>(40 M band)   | IEEE802.11ac<br>(80 M band)                                     | Bluetooth Ver.4.0<br>with EDR function                   |  |  |
|------------------------------|--|---|---|---|---|--|--|--|
| Frequency<br>of operation    | 2412 MHz - 2462 MHz  | 2412 MHz - 2462 MHz                       | 2412 MHz - 2462 MHz<br>5180 MHz - 5240 MHz<br>5260 MHz - 5320 MHz *1)<br>5500 MHz - 5700 MHz *1)<br>5745 MHz - 5825 MHz | 2422 MHz - 2452 MHz<br>5190 MHz - 5230 MHz<br>5270 MHz - 5310 MHz *1)<br>5510 MHz - 5670 MHz *1)<br>5755 MHz - 5795 MHz | 5210 MHz<br>5290 MHz *1)<br>5530 MHz - 5610 MHz *1)<br>5775 MHz | 2402 MHz - 2480 MHz                                      |  |  |
| Type of<br>modulation        | DSSS<br>(CCK, DQPSK,<br>DBPSK)   | OFDM-CCK<br>(64QAM, 16QAM,<br>QPSK, BPSK) | 11a/n: OFDM (64QAM, 16QA)<br>11ac: OFDM (64QAM, 16QA)   | M, QPSK, BPSK)<br>4, QPSK, BPSK, 256QAM)  |   | BT:<br>FHSS<br>(GFSK, π/4-DQPSK, 8-<br>DPSK)<br>LE: GFSK |  |  |
| Channel<br>spacing           | 5 MHz 20 MHz 40 MHz  |   |   |   | 80 MHz  | BT: 1 MHz<br>LE: 2 MHz                                   |  |  |
| Antenna<br>type              | [Antenna 1] Model Name:<br>PCB antenna (Dipole anter   | 146153<br>ma)                             |   |   |   |  |  |  |
|                              | [Antenna 2] Model Name: H2U84W1H1S<br>Chip Antenna   |   |   |   |   |  |  |  |
| Antenna<br>Connector<br>type | Antenna 1: U.FL Alternative connectorUFL<br>Antenna 2: -none   |   |   |   |   |  |  |  |
| Antenna<br>Gain              | Antenna 1: 3.25 dBi (2.4 GHz Band), 5.0 dBi (5 GHz Band)<br>Antenna 2: 1.40 dBi (2.4 GHz Band), 2.3 dBi (5 GHz Band) |   |   |   |   |  |  |  |

\*1) This test report applies to IEEE802.11a / n-20 / n-40/ ac-20 / ac-40 / ac-80 (W53, W56 band).

\* Spurious emission test was performed with two anntena type (PCB antenna (Dipole antenna) and Chip antenna). \*\* WLAN and Bluetooth do not transmit simultaneously.

# SECTION 3: Scope of Report

This report only covers DFS requirement, as specified by the following referenced procedures.

# **SECTION 4: Test specification, procedures & results**

| 4.1 Test Specification |   |   |
|------------------------|---|---|
| Test Specification     | : | FCC Part 15 Subpart E: 2016, final revised on April 6, 2016   |
| Title                  | : | FCC 47CFR Part15 Radio Frequency Device Subpart E<br>Unlicensed National Information Infrastructure Devices<br>Section 15.407 General technical requirements  |
| Test Specification     | : | KDB905462 D02 UNII DFS Compliance Procedures New Rules v02  |
| Title                  | : | COMPLIANCE MEASUREMENT PROCEDURES FOR UNLICENSED-<br>NATIONAL INFORMATION INFRASTRUCTURE DEVICES OPERATING IN<br>THE 5250-5350MHz AND 5470-5725MHz BANDS INCORPORATING<br>DYNAMIC FREQUENCY SELECTION |
| Test Specification     | : | KDB905462 D03 Client Without DFS New Rules v01r02   |
| Title                  | : | U-NII CLIENT DEVICES WITHOUT RADAR DETECTION CAPABILITY   |

# FCC Part 15.31 (e)

The stable voltage (DC1.1V) was provided to the EUT during the tests. Therefore, this EUT complies with the requirement.

# FCC Part 15.203 Antenna requirement

[PCB antenna (Dipole antenna)] The EUT has a unique coupling/antenna connector (UFL). Therefore the equipment complies with the requirement of 15.203.

[Chip Antenna]

The antenna is not removable from the EUT. Therefore, the equipment complies with the antenna requirement of Section 15.203.

#### 4.2 **Procedures and results**

| <b>Table 1: Applicabil</b> | ity of DFS | Requirements |
|----------------------------|------------|--------------|
|----------------------------|------------|--------------|

| Requirement   | Operating Mode<br>Client without | Test Procedures &<br>Limits         | Deviation | Results  |  |  |  |
|---|----------------------------------|-------------------------------------|-----------|----------|--|--|--|
|   | <b>Radar Detection</b>           |                                     |           |          |  |  |  |
| U-NII Detection   | Not required                     | KDB905462 D02 UNII DFS              | N/A       | N/A      |  |  |  |
| Bandwidth   |                                  | Compliance Procedures New Rules v02 |           |          |  |  |  |
| Initial Channel   | Not required                     | FCC15.407 (h)                       | N/A       | N/A      |  |  |  |
| Availability Check  |                                  | KDB905462 D02 UNII DFS              | -         |          |  |  |  |
| Time  |                                  | Compliance Procedures New Rules v02 |           |          |  |  |  |
|   |                                  | RSS-247 6.3                         |           |          |  |  |  |
| Radar Burst at the  | Not required                     | FCC15.407 (h)                       | N/A       | N/A      |  |  |  |
| Beginning of the  |                                  | KDB905462 D02 UNII DFS              |           |          |  |  |  |
| Channel Availability  |                                  | Compliance Procedures New Rules v02 |           |          |  |  |  |
| Check Thile   |                                  | RSS-247 6.3                         |           |          |  |  |  |
| Radar Burst at the  | Not required                     | FCC15.407 (h)                       | N/A       | N/A      |  |  |  |
| End of the Channel  |                                  | KDB905462 D02 UNII DFS              |           |          |  |  |  |
| Availability Check  |                                  | Compliance Procedures New Rules v02 |           |          |  |  |  |
| Time  |                                  | RSS-247 6.3                         |           |          |  |  |  |
| In-Service Monitoring                                       | Yes                              | FCC15.407 (h)                       | N/A       | Complied |  |  |  |
| for Channel Move  |                                  | KDB905462 D02 UNII DFS              |           |          |  |  |  |
| Time, Channel   |                                  | Compliance Procedures New Rules v02 |           |          |  |  |  |
| Time  |                                  | RSS-247 6.3                         |           |          |  |  |  |
| In-Service Monitoring                                       | Yes *                            | FCC15.407 (h)                       | N/A       | Complied |  |  |  |
| for Non-Occupancy   |                                  | KDB905462 D02 UNII DFS              |           |          |  |  |  |
| period  |                                  | Compliance Procedures New Rules v02 |           |          |  |  |  |
|   |                                  | RSS-247 6.3                         | 1         |          |  |  |  |
| Statistical   | Not required                     | FCC15.407 (h)                       | N/A       | N/A      |  |  |  |
| Performance Check   |                                  | KDB905462 D02 UNII DFS              |           |          |  |  |  |
|   |                                  | Compliance Procedures New Rules v02 |           |          |  |  |  |
| Note: UL Japan, Inc.'s EMI Work Procedures No. 13-EM-W0422. |                                  |                                     |           |          |  |  |  |

Note: UL Japan, Inc.'s EMI Work Procedures No. 13-EM-W0422.

\*Although this test was not required in FCC, KDB 905462 D02, it was performed as additional test.

# Table 2 DFS Detection Thresholds for Master Devices and Client Devices With Radar Detection

| Maximum Transmit Power  | Value (See Notes 1,2, and 3)  |  |  |  |
|---|---|--|--|--|
| $\geq$ 200 milliwatt  | -64 dBm   |  |  |  |
| < 200 milliwatt and power spectral density <  | -62 dBm   |  |  |  |
| 10dBm/MHz   |   |  |  |  |
| < 200 milliwatt that do not meet the power spectral   | -64 dBm   |  |  |  |
| density requirement   |   |  |  |  |
| Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna.                  |   |  |  |  |
| Note 2: Throughout these test procedures an additional  | Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test |  |  |  |
| transmission waveforms to account for variations in measurement equipment. This will ensure that the test |   |  |  |  |
| signal is at or above the detection threshold level to trigger a DFS response.                            |   |  |  |  |
| Note 3: EIRP is based on the highest antenna gain. Fo   | or MIMO devices refer to KDB Publication 662911 D01.  |  |  |  |

# **Table 3 DFS Response Requirement Values**

| Parameter  | Value   |  |  |
|--|---|--|--|
| Non-occupancy period   | Minimum 30 minutes                            |  |  |
| Channel Availability Check Time  | 60 seconds                                    |  |  |
| Channel Move Time  | 10 seconds                                    |  |  |
|  | See Note 1                                    |  |  |
| Channel Closing Transmission Time  | 200 milliseconds + an aggregate of 60         |  |  |
|  | milliseconds over remaining 10 second period. |  |  |
|  | See Notes 1 and 2                             |  |  |
| U-NII Detection Bandwidth  | Minimum 100 % of the U-NII 99 % transmission  |  |  |
|  | power bandwidth                               |  |  |
|  | See Note 3                                    |  |  |
| Note 1: Channel Move Time and the Channel Closing Tran   | smission Time should be performed with Radar  |  |  |
| Type 0. The measurement timing begins at the end of the Radar Type 0 burst.                              |   |  |  |
| Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning |   |  |  |

**Note 2:** The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signal will not count quiet periods in between transmissions.

**Note 3:** During the U-NII Detection Bandwidth detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.

| Test report No. | : 11182619H-D-R1   |
|-----------------|--------------------|
| Page            | : 9 of 22          |
| Issued date     | : November 7, 2016 |
| FCC ID          | : N6C-SDMAC        |

# **Table 4 Short Pulse Radar Test Waveform**

| Radar Type   | Pulse Width<br>(µsec) | PRI<br>(µsec)   | Number of<br>Pulses      | Minimum<br>Percentage of<br>Successful | Minimum<br>Number of<br>Traials |  |
|--|-----------------------|---|--------------------------|--|---------------------------------|--|
|  |                       |   |                          | Detection                              |                                 |  |
| 0  | 1                     | 1428  | 18                       | See Note 1                             | See Note 1                      |  |
| 1  | 1                     | Test A: 15 unique<br>PRI values randomly  | Roundup{(1/36<br>0)*     | 60 %                                   | 30                              |  |
|  |                       | selected from the list  | (19*10 <sup>6</sup> /PRI |  |                                 |  |
|  |                       | of 23 PRI values in   | usec)}                   |  |                                 |  |
|  |                       | Table 5a  |                          |  |                                 |  |
|  |                       | Test B: 15 unique<br>PRI values randomly<br>selected within the<br>range of 518-3066<br>µsec, with a<br>minimum increment<br>of 1 µsec, excluding<br>PRI values selected<br>in Test A |                          |  |                                 |  |
| 2  | 1-5                   | 150-230   | 23-29                    | 60 %                                   | 30                              |  |
| 3  | 6-10                  | 200-500   | 16-18                    | 60 %                                   | 30                              |  |
| 4  | 11-20                 | 200-500   | 12-16                    | 60 %                                   | 30                              |  |
| Aggregate (Rader Types 1-4)80 %120   |                       |   |                          |  |                                 |  |
| Note 1: Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests. |                       |   |                          |  |                                 |  |

# Table 5 Long Pulse Radar Test Waveform

| Radar Type | Pulse<br>Width<br>(µsec) | Chip Width<br>(MHz) | PRI (µsec) | Number of<br>Pulses per<br><i>Burst</i> | Number of<br>Burst | Minimum<br>Percentage<br>of<br>Successful<br>Detection | Minimum<br>Number of<br>Trials |
|------------|--------------------------|---------------------|------------|---|--------------------|--|--------------------------------|
| 5          | 50-100                   | 5 - 20              | 1000-2000  | 1-3                                     | 8-20               | 80 %   | 30                             |

# Table 6 Frequency Hopping Radar Test Waveform

| Radar T | ype Pulse<br>Width<br>(µsec) | PRI (µsec) | Pulse per<br>Hop (kHz) | Hopping<br>Rate (kHz) | Hopping<br>Sequence<br>Length<br>(msec) | Minimum<br>Percentage<br>of<br>Successful<br>Detection | Minimum<br>Number of<br>Trials |
|---------|------------------------------|------------|------------------------|-----------------------|---|--|--------------------------------|
| 6       | 1                            | 333        | 9                      | 0.333                 | 300                                     | 70 %   | 30                             |

| Test report No. | : 11182619H-D-R1   |
|-----------------|--------------------|
| Page            | : 10 of 22         |
| Issued date     | : November 7, 2016 |
| FCC ID          | : N6C-SDMAC        |

# 4.3 Test Location

| 1 elephone. + 01 570 24    | off, i desimile.          | +01 570 24 0124               |   |                           |                                     |
|----------------------------|---------------------------|-------------------------------|---|---------------------------|-------------------------------------|
| Test site                  | IC Registration<br>Number | Width x Depth x<br>Height (m) | Size of reference ground plane (m) /<br>horizontal conducting plane | Other rooms               | M aximum<br>measurement<br>distance |
| No.1 semi-anechoic chamber | 2973C-1                   | 19.2 x 11.2 x 7.7             | 7.0 x 6.0   | No.1 Power source<br>room | 10 m                                |
| No.2 semi-anechoic chamber | 2973C-2                   | 7.5 x 5.8 x 5.2               | 4.0 x 4.0   | -                         | 3 m                                 |
| No.3 semi-anechoic chamber | 2973C-3                   | 12.0 x 8.5 x 5.9              | 6.8 x 5.75  | No.3 Preparation room     | 3 m                                 |
| No.3 shielded room         | -                         | 4.0 x 6.0 x 2.7               | N/A   | -                         | -                                   |
| No.4 semi-anechoic chamber | 2973C-4                   | 12.0 x 8.5 x 5.9              | 6.8 x 5.75  | No.4 Preparation<br>room  | 3 m                                 |
| No.4 shielded room         | -                         | 4.0 x 6.0 x 2.7               | N/A   | -                         | -                                   |
| No.5 semi-anechoic chamber | -                         | 6.0 x 6.0 x 3.9               | 6.0 x 6.0   | -                         | -                                   |
| No.6 shielded room         | -                         | 4.0 x 4.5 x 2.7               | 4.0 x 4.5   | -                         | -                                   |
| No.6 measurement room      | -                         | 4.75 x 5.4 x 3.0              | 4.75 x 4.15   | -                         | -                                   |
| No.7 shielded room         | -                         | 4.7 x 7.5 x 2.7               | 4.7 x 7.5   | -                         | -                                   |
| No.8 measurement<br>room   | -                         | 3.1 x 5.0 x 2.7               | N/A   | -                         | -                                   |
| No.9 measurement<br>room   | -                         | 8.8 x 4.6 x 2.8               | 2.4 x 2.4   | -                         | -                                   |
| No.11 measurement room     | -                         | 6.2 x 4.7 x 3.0               | 4.8 x 4.6   | -                         | -                                   |

UL Japan, Inc. Ise EMC Lab. \*NVLAP Lab. code: 200572-0 4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN Telephone: +81 596 24 8999. Facsimile: +81 596 24 8124

\* Size of vertical conducting plane (for Conducted Emission test) : 2.0 x 2.0 m for No.1, No.2, No.3, and No.4 semi-anechoic chambers and No.3 and No.4 shielded rooms.

## 4.4 Uncertainty

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2. Time Measurement uncertainty for this test was:  $(\pm) 0.012\%$ 

# 4.5 Test instruments of DFS and Test set up

Refer to APPENDIX.

# SECTION 5: Operation of E.U.T. during testing

# 5.1 Operating Modes

Operation frequencies: Please see page 5.

The channel-loading of approximately 17% or greater was used for testing, and its test data was transferred from the Master Device to the Client Device for all test configurations.

The EUT utilizes the 802.11a/n/ac architecture, with a 20MHz, 40MHz and 80MHz channel bandwidth.

The FCC ID for the Master Device used with EUT for DFS testing is LDK102087.

The rated output power of the Master unit is  $\geq 200$  mW(23dBm). Therefore the required interference threshold level is -64 dBm. After correction for antenna gain and procedural adjustments, the required conducted threshold at the antenna port is -64 + 1 + 0 = -63.0 dBm (threshold level + additional 1dB + antenna gain).

It is impossible for users to change DFS control, because the DFS function is written on the firmware and users cannot access it.

\*DFS test was performed on U.FL port because the structures of the route to both antennas are the same.

The EUT was set by the software as follows: Software name:iperf

| Test report No. | : 11182619H-D-R1   |
|-----------------|--------------------|
| Page            | : 12 of 22         |
| Issued date     | : November 7, 2016 |
| FCC ID          | : N6C-SDMAC        |

# 5.2 Configuration and peripherals



: Standard Ferrite Core

| Description of EUT |                      |                   |                        |                   |         |  |
|--------------------|----------------------|-------------------|------------------------|-------------------|---------|--|
| No.                | Item                 | Model number      | Serial number          | Manufacturer      | Remarks |  |
| А                  | SDIO Wireless Module | SX-SDMAC          | MA999118               | silex technology, | EUT     |  |
|                    |                      |                   |                        | Inc.              |         |  |
| В                  | Jig                  | -                 | SXO4417                | silex technology, | -       |  |
|                    |                      |                   |                        | Inc.              |         |  |
| С                  | AC Adapter           | ATS030T-A050      | PS2D-505APL05          | SCEDTRE           | -       |  |
| D                  | Laptop PC            | Latitnd F5540     | P35F001                | DELL              | -       |  |
| Е                  | AC Adapter           | LA65NM130         | CH03NKWD-72438-580-    | DELL              | -       |  |
|                    |                      |                   | 8CCF-A43               |                   |         |  |
| F                  | Wireless LAN Access  | AIR-CAP3702E-A-K9 | FTX1822760C            | Cisco System      | -       |  |
|                    | Point                |                   |                        |                   |         |  |
| G                  | AC Adapter           | AA25480L          | ALD030406GR            | Cisco System      | -       |  |
| Н                  | Laptop PC            | 1952-D65          | L3-DM302               | Lenovo            | -       |  |
| Ι                  | AC Adapter           | 92P1160           | 11S92P1160Z1ZBGH7B99A8 | Lenovo            | -       |  |

# List of cables used

| No. | Name      | Length (m) | Shie       | Shield     |   |
|-----|-----------|------------|------------|------------|---|
|     |           |            | Cable      | Connector  |   |
| 1   | DC Cable  | 1.0        | Unshielded | Unshielded | - |
| 2   | AC Cable  | 1.8        | Unshielded | Unshielded | - |
| 3   | LAN Cable | 2.0        | Shielded   | Shielded   | - |
| 4   | USB Cable | 0.9        | Shielded   | Shielded   | - |
| 5   | DC Cable  | 1.8        | Unshielded | Unshielded | - |
| 6   | AC Cable  | 0.9        | Unshielded | Unshielded | - |
| 7   | LAN Cable | 1.0        | Unshielded | Unshielded | - |
| 8   | DC Cable  | 1.9        | Unshielded | Unshielded | - |
| 9   | AC Cable  | 2.1        | Unshielded | Unshielded | - |
| 10  | DC Cable  | 1.0        | Unshielded | Unshielded | - |
| 11  | AC Cable  | 1.8        | Unshielded | Unshielded | - |

# UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN Telephone : +81 596 24 8999 Facsimile : +81 596 24 8124

# 5.3 Test and Measurement System

# SYSTEM OVERVIEW

The measurement system is based on a conducted test method.

The software selects waveform parameters from within the bounds of the signal type on a random basis using uniform distribution. The short pulse types 1, 2, 3, and 4, the long pulse type 5, and the frequency hopping type 6 parameters are randomized at run-time.

The signal monitoring equipment consists of a spectrum analyzer with the capacity to display 8001 bins on the horizontal axis. A time-domain resolution of 2 msec/bin is achievable with a 16 second sweep time, meeting the 10 seconds short pulse reporting criteria. The aggregate ON time is calculated by multiplying the number of bins above a threshold during a particular observation period by the dwell time per bin, with the analyzer set to peak detection.

# FREQUENCY HOPPING RADAR WAVEFORM GENERATING SUBSYSTEM

The first 100 frequencies are selected out of the hopping sequence of the randomized 475 hop frequencies. Only a *Burst* that has the frequency falling within the receiver bandwidth of the tested U-NII device is selected among those frequencies. (Frequency-domain simulation). The radar waveform generated at the start time of the selected *Burst* (Time-domain simulation) is download to the Signal Generator.

If all of the randomly selected 100 frequencies do not fall within the receiver bandwidth of the U-NII device, the radar waveform is not used for the test.

# CONDUCTED METHODS SYSTEM BLOCK DIAGRM



# MEASUREMENT SYSTEM FREQUENCY REFERENCE

Lock the signal generator and the spectrum analyzer to the same reference sources as follows: Connect the 10 MHz OUT on the signal generator to the EXT REF IN on the spectrum analyzer and set the spectrum analyzer Ext to On.

# SYSTEM CALIBRATION

Step 1: Set the system as shown in Figure 3 of KDB905462 7.2.2.

Step 2: Adjust each attenuator to fulfill the following three conditions:

- WLAN can be communicated, and
- Rader detection threshold level is bigger than Client Device traffic level on the spectrum analyzer, and
- Master Device traffic level is not displayed on the spectrum analyzer.

Step 3: Terminate 50 ohm at B, C and D points, and connect the spectrum analyzer to the point A. (See the figure on page 14)

At the point A, adjust the signal generator and spectrum analyzer to the center frequency of the channel to be measured.

Download the applicable radar waveforms to the signal generator. Select the radar waveform, trigger a burst manually and measure the amplitude on the spectrum analyzer. Readjust the amplitude of the signal generator as required so that the peak level of the waveform is at a displayed level equal to the required or desired interference detection threshold.

Separate signal generator amplitude settings are determined as required for each radar type.

**Step 4**: Without changing any of the instrument settings, restore the system setting to Step 2 and adjust the Reference Level Offset of the spectrum analyzer to the level at Step 3.

By taking the above steps 1 to 4, the spectrum analyzer displays the level of the signal generator as received at the antenna ports of the Master Device.

See Clause 5.4 for Plots of Noise, Rader Waveforms, and WLAN signals.

# 5.4 Plots of Noise, Rader Waveforms, and WLAN signals





## UL Japan, Inc. Ise EMC Lab. 4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN Telephone : +81 596 24 8999 Facsimile : +81 596 24 8124

| Test report No. | : 11182619H-D-R1   |
|-----------------|--------------------|
| Page            | : 17 of 22         |
| Issued date     | : November 7, 2016 |
| FCC ID          | : N6C-SDMAC        |

# SECTION 6: Channel Move Time, Channel Closing Transmission Time

# 6.1 **Operating environment**

| Test place            | Ise EMC Lab.No.6 Measurement Room |
|-----------------------|-----------------------------------|
| Date                  | 08/30/2016                        |
| Temperature/ Humidity | 23deg. C / 52% RH                 |
| Engineer              | Yuta Moriya                       |
| Mode                  | 11ac-80                           |

## 6.2 Test Procedure

Transmit the data from the Master Device to the Client Device on the test Channel for the entire period of the test. The Radar Waveform generator sends a Burst of pulses for one of the Short Pulse Radar Types 0 at levels defined, on the Operating Channel. An additional 1 dB is added to the radar test signal to ensure it is at or above the DFS Detection Threshold, accounting for equipment variations/errors.

Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel for duration greater than 10 seconds.

## 6.3 Test data

#### 11ac-80

| Test Item             | Unit   | Measurement Time | Limit  | Results |
|-----------------------|--------|------------------|--------|---------|
| Channel Move Time *1) | [sec]  | 0.076            | 10.000 | Pass    |
| Channel Closing       |        |                  |        |         |
| Transmission Time *2) | [msec] | 0                | 60     | Pass    |

\*1) Channel Move Time is calculated as follows:

(Channel Move Time) = (End of Transmission) - (End of Burst) = 1.81-1.734

\*2) Channel Closing Transmission Time is calculated from (End of Burst + 200msec) to (End of Burst + 10sec) (Channel Closing Transmission Time) = (Number of analyzer bins showing transmission) × (dwell time per bin) =  $0 \times 2$  [msec]



## 6.4 Test result

Test result: Pass

| Test report No. | : 11182619H-D-R1   |
|-----------------|--------------------|
| Page            | : 19 of 22         |
| Issued date     | : November 7, 2016 |
| FCC ID          | : N6C-SDMAC        |
|                 |                    |

# **SECTION 7: Non-Occupancy Period**

# 7.1 Operating environment

| Test place            | Ise EMC Lab.No.6 Measurement Room |
|-----------------------|-----------------------------------|
| Date                  | 08/31/2016                        |
| Temperature/ Humidity | 24deg. C / 58% RH                 |
| Engineer              | Yuta Moriya                       |
| Mode                  | 11ac-80                           |

# 7.2 Test Procedure

The following two tests are performed:

1). Transmit the data from the Master Device to the Client Device on the test Channel for the entire period of the test. The Radar Waveform generator sends a Burst of pulses for one of the Radar Types 0 at levels defined on the Operating Channel. An additional 1 dB is added to the radar test signal to ensure it is at or above the DFS Detection Threshold, accounting for equipment variations/errors.

Observe the transmissions of the EUT after the Channel Move Time on the Operating Channel for duration greater than

30 minutes.

2). Transmit the data from the Master Device to the Client Device on the test Channel for the entire period of the test. Observe the transmissions of the EUT on the Operating Channel for duration greater than 30 minutes after the Master Device is shut off.

# 7.3 Test data





# 7.4 Test result

Test result: Pass

# **APPENDIX 1: Test instruments**

# EMI Test Equipment

| Control No.      | Instrument                        | Manufacturer         | Model No        | Serial No  | Test Item | Calibration Date * |
|------------------|-----------------------------------|----------------------|-----------------|------------|-----------|--------------------|
|                  |                                   |                      |                 |            |           | Interval(month)    |
| MOS-14           | Thermo-Hygrometer                 | Custom               | CTH-201         | 1401       | DFS       | 2016/01/21 * 12    |
| MSA-13           | Spectrum Analyzer                 | Agilent              | E4440A          | MY46185823 | DFS       | 2016/06/17 * 12    |
| EST-48           | Signal Generator                  | Agilent              | E4438C          | MY45090353 | DFS       | 2015/12/30 * 12    |
| MCC-210          | Microwave Cable                   | RS Components        | R-132G7210200CD | -          | DFS       | 2016/04/01 * 12    |
| MCC-170          | Microwave Cable                   | Junkosha             | MWX221          | 1409S493   | DFS       | 2016/03/11 * 12    |
| MCC-96           | Microwave Cable 1G-<br>40GHz      | Suhner               | SUCOFLEX102     | 30817/2    | DFS       | 2016/05/09 * 12    |
| MCC-98           | Microwave Cable 1G-<br>40GHz      | Suhner               | SUCOFLEX102     | 30819/2    | DFS       | 2016/05/09 * 12    |
| MCC-67           | Microwave Cable 1G-<br>40GHz      | Suhner               | SUCOFLEX102     | 28635/2    | DFS       | 2016/04/18 * 12    |
| MPSC-01          | Power<br>splitters/Combiners      | Mini-Circuit         | ZFSC-2-2500     | 0124       | DFS       | 2015/09/16 * 12    |
| MPSC-04          | Power<br>Splitters/Combiners      | Mini-Circuit         | ZFSC-2-10G      | 0326       | DFS       | 2015/09/18 * 12    |
| MAT-88           | Attenuator                        | Weinschel Associates | WA56-10         | 56100304   | DFS       | 2016/06/15 * 12    |
| MAT-89           | Attenuator                        | Weinschel Associates | WA56-10         | 56100305   | DFS       | 2016/06/09 * 12    |
| MAT-23           | Attenuator(10dB) 1-<br>18GHz      | Orient Microwave     | BX10-0476-00    | -          | DFS       | 2016/03/18 * 12    |
| MPD-01           | PowerDivider DC to 26.5GHz        | Agilent              | 11636B          | 52258      | DFS       | 2016/03/23 * 12    |
| MAT-56           | Attenuator(10dB)                  | Suhner               | 6810.19.A       | -          | DFS       | 2016/01/18 * 12    |
| MAT-60           | Attenuator(20dB)                  | Suhner               | 6820.19.A       | -          | DFS       | Pre Check          |
| MAT-57           | Attenuator(10dB)                  | Suhner               | 6810.19.A       | -          | DFS       | 2016/01/18 * 12    |
| MTA-36           | Terminator                        | -                    | 50ΩSMA          | -          | DFS       | Pre Check          |
| MTA-44           | Terminator                        | Mini-Circuits        | ANNE-50X+       | MUU3460141 | DFS       | Pre Check          |
| MTA-45           | Terminator                        | Mini-Circuits        | ANNE-50X+       | MUU3460142 | DFS       | Pre Check          |
| COTS-MDFS-<br>01 | Signal Studio Software<br>for DFS | Agilent              | N7620A-101      | 5010-7739  | DFS       | -                  |

\*1) Signal generator is only used to generate radar test signal, and the wave form is confirmed with spectrum analyzer every time before the test.

The expiration date of the calibration is the end of the expired month. All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

**DFS: Dynamic Frequency Selection**